



BizTrack CM

Route ↔ API Endpoint Coverage Matrix

Every desktop-v2 route mapped through its `dataClient` calls to the REST endpoints it consumes on the NestJS API. A companion to the Functionality Map.

44 routes

26 client domains

apps/desktop-v2 → apps/api

Product: BizTrack CM — offline-first POS for Cameroonian SMBs

Scope: renderer routes (`router.tsx`) · cloud data-client (`cloud-*.ts`) · API controllers

Generated: 2026-07-17

§ How to read this matrix

REQUEST PATH

Route **component** → **dataClient.<domain>.<method>()** → **cloud-http** (cget/cpost/cpatch/cdelete) → **API** /api/v1/...

In the **browser/cloud build** the data-client hits the REST API directly (shown here). In the **Electron build** the same **dataClient** call routes through IPC to the main process, which reads/writes local SQLite and mirrors every write to the API via the outbox sync engine — so the endpoints below are also the sync targets.

All paths are relative to the versioned base /api/v1. Path params shown as :id. Query strings omitted for brevity.

LEGEND

GET read **POST** create / action **PATCH** update **DELETE** remove
GUEST pre-login route **OWNER** owner-only **PLAN** BUSINESS/PRO gated **SYNCED** local write + sync parity

1 Authentication & Onboarding **GUEST**

Pre-login routes under AuthShell / RequireGuest. Two-phase JWT: phase-1 (no business) → select business → phase-2.

ROUTE / SCREEN	DATACLIENT CALL	API ENDPOINT
/signin Sign in	auth.login	POST /auth/login GET /auth/session
/signup Create account + OTP	auth.register auth.verifyPhone / verifyEmail auth.resendOtp auth.getInvitePreview	POST /auth/register POST /auth/verify-phone POST /auth/verify-email POST /auth/resend-otp GET /invites/:token
/invite Accept invite	auth.getInvitePreview auth.register / login auth.acceptInvite / rejectInvite	GET /invites/:token POST /invites/:token/accept POST /invites/:token/reject POST /auth/register · /auth/login
/sso One-time-code login	auth.requestLogin auth.loginOtp auth.resendOtp	POST /auth/request-login-otp POST /auth/login-otp POST /auth/resend-otp
/forgot-password Reset password	auth.requestPasswordReset auth.resetPassword	POST /auth/request-password-reset POST /auth/reset-password
/select-business Choose business	auth.listBusinesses auth.selectBusiness	GET /businesses/mine POST /auth/select-business
/setup-business Business setup wizard	auth.setupBusiness	POST /businesses/setup POST /auth/select-business
/select-plan Choose plan	auth.selectPlan (auth.listPlans)	GET /plans POST /plans/select POST /auth/select-business
/invitations My invitations	invitations.list invitations.accept / reject	GET /businesses/invitations POST /businesses/invitations/:id/accept POST /businesses/invitations/:id/reject

ROUTE / SCREEN	DATACLIENT CALL	API ENDPOINT
(session/logout) Shared	auth.getSession auth.logout	POST /auth/refresh GET /auth/session POST /auth/logout

2 Home & Point of Sale

ROUTE / SCREEN	DATACLIENT CALL	API ENDPOINT
/ Dashboard (role-tailored)	sync.trigger	– internal sync (IPC / pull); no direct REST
/sell Point of Sale SYNCED	products.list / listVariants products.resolveScan products.listInStockSerials categories.listSelectable charges.listActive contacts.get / listAllCustomers savings.getForCustomer sales.create sales.receiptHtml / printReceipt	GET /products · /products/:id/variants GET /products/scan · /products/:id/serial-units GET /products/categories/selectable GET /charges GET /contacts · /contacts/:id GET /deposits/open/:customerId POST /sales GET /sales/:id/receipt

3 Products (Catalog)

ROUTE / SCREEN	DATACLIENT CALL	API ENDPOINT
/products Product list	products.list / stats / remove categories.listAll brands.list	GET /products · /products/stats DELETE /products/:id GET /products/categories · /brands
/products/new/products/:id/edit Product form	products.get / create / update products.setImages / setVariants products.setSerialUnits categories.listSelectable attributes.listCategoryLinks brands.get · units.list uploads.file	POST /products · PATCH /products/:id POST /products/:id/images · /variants · /serial-units GET /products/categories/selectable GET /products/categories/:id/attribute-groups GET /brands/:id · /unit-of-measures POST /uploads
/products/:id Product detail	products.get / remove products.listImages / listVariants products.listMovements	GET /products/:id · /images · /variants GET /inventory/:id/movements DELETE /products/:id
/products/categories Categories	categories.list / remove products.list	GET /products/categories DELETE /products/categories/:id GET /products
/products/categories/new/.../:id Category form	categories.create / update categories.listParentOptions / listAll attributes.listAllGroups attributes.listCategoryLinks / setCategoryLinks	POST /products/categories · PATCH /.../:id GET /products/categories/parent-options GET /attribute-groups POST / PATCH / DEL /products/categories/:id/attribute-groups
/products/brands Brands & models	brands.list / create / update / remove brands.addModel / updateModel / removeModel categories.listAll	GET /brands · POST /brands PATCH / DEL /brands/:id POST /brands/:id/models PATCH / DEL /brands/:id/models/:modelId

ROUTE / SCREEN	DATACLIENT CALL	API ENDPOINT
/products/attributes Attribute groups	attributes.listGroups attributes.createGroup / updateGroup / deleteGroup attributes.addOption / updateOption / deleteOption	GET /attribute-groups POST / PATCH / DEL /attribute-groups/:id POST / PATCH / DEL /attribute-groups/:id/options/:optionId
/products/units Units of measure	units.list / create / update / remove	GET /unit-of-measures · POST /unit-of-measures PATCH / DEL /unit-of-measures/:id

4 Inventory

ROUTE / SCREEN	DATACLIENT CALL	API ENDPOINT
/inventory Stock levels	inventory.list / stats inventory.reorderSuggestions categories.listAll	GET /inventory · /inventory/stats GET /inventory/alerts GET /products/categories
/inventory/restock Receive stock (ad-hoc) SYNCED	purchaseOrders.list products.list / get / listVariants inventory.restock	GET /purchase-orders · /products POST /inventory/restock
(product detail actions) Adjust / threshold	inventory.adjust inventory.setThreshold	POST /inventory/:id/adjust PATCH /inventory/:id/threshold

5 Purchasing (RFQ → PO → Receive)

ROUTE / SCREEN	DATACLIENT CALL	API ENDPOINT
/purchasing/rfqs RFQ list	rfqs.list	GET /rfqs
/purchasing/rfqs/new New RFQ	rfqs.create	POST /rfqs
/purchasing/rfqs/:id RFQ detail	rfqs.get / buildDocument rfqs.recordQuote documents.send	GET /rfqs/:id POST /rfqs/:id/quotes POST /rfqs/:id/send GET /rfqs/:id/document
/purchasing/rfqs/:id/convert/:supplierId Convert RFQ → PO	rfqs.get products.listVariants purchaseOrders.createFromRfq	GET /rfqs/:id POST /purchase-orders/from-rfq/:rfqId
/purchasing/orders PO list	purchaseOrders.list	GET /purchase-orders
/purchasing/orders/new New PO	purchaseOrders.create contacts.listAllSuppliers	POST /purchase-orders GET /contacts?isActive=true
/purchasing/orders/:id PO detail	purchaseOrders.get / cancel purchaseOrders.buildDocument documents.send	GET /purchase-orders/:id POST /purchase-orders/:id/cancel · /send GET /purchase-orders/:id/document
/purchasing/orders/:id/receive Receive PO SYNCED	purchaseOrders.get products.get / listVariants inventory.restock	GET /purchase-orders/:id POST /inventory/restock

6 Sales

ROUTE / SCREEN	DATACLIENT CALL	API ENDPOINT
/sales Transactions + KPIs + CSV	sales.summary sales.list / listAll	GET /sales · /sales/summary GET /sales/:id · /sales/:id/receipt

7 Online Store PLAN — BUSINESS/PRO

ROUTE / SCREEN	DATACLIENT CALL	API ENDPOINT
/online/orders Online orders	online.listOrders / getOrder online.updateOrderStatus / updateOrderPayment products.get / listInStockSerials	GET /online-store/orders · /:id PATCH /online-store/orders/:id/status PATCH /online-store/orders/:id/payment
/online/products Online products	online.getStore online.listProducts online.setProductPublished	GET /online-store · /online-store/products PATCH /online-store/products/:id
/online/store Storefront config	online.getStore / createStore / updateStore online.checkSlug online.publishStore online.listPublications / restorePublication	GET / POST / PATCH /online-store POST /online-store/publish GET /online-store/publications POST /online-store/publications/:version/restore GET /online-store/slug-check

8 Contacts & Debts

ROUTE / SCREEN	DATACLIENT CALL	API ENDPOINT
/contacts Contacts list	contacts.summary / list	GET /contacts · /contacts/summary
/contacts/new/contacts/:id/edit Contact form (+KYC)	contacts.get / create / update openingBalances.upsert	POST /contacts · PATCH /contacts/:id POST /contacts/:id/opening-balance
/contacts/:id Contact detail + statement	contacts.get / remove debts.statement / offset debts.recordPayment	GET /contacts/:id · /contacts/:id/statement POST /contacts/:id/offset POST /debtors/:debtId/payments · /creditors/:debtId/payments DELETE /contacts/:id

9 Expenses

ROUTE / SCREEN	DATACLIENT CALL	API ENDPOINT
/expenses Expense ledger	expenses.list / summary / trend expenses.create / update / setStatus / remove expenseCategories.listAll / create	GET /expenses · /summary · /trend POST /expenses · PATCH /expenses/:id DELETE /expenses/:id GET / POST /expense-categories

10 Deposits (Layaway / Savings)

ROUTE / SCREEN	DATACLIENT CALL	API ENDPOINT
/deposits Deposit sessions SYNCED	deposits.summary / list / get deposits.create / addPayment / close deposits.receiptHtml / reportHtml products.* · contacts.*	GET /deposits · /:id · /:id/statement · /summary POST /deposits · POST /deposits/:id/payments POST /deposits/:id/close GET /deposits/:id/report · /transactions/:id/receipt

11 Reports

ROUTE / SCREEN	DATACLIENT CALL	API ENDPOINT
/reports/reports/:reportId Report viewer	business.getProfile sales.summary · expenses.summary contacts.summary documents.downloadHtmlPdf	GET /businesses/mine GET /sales/summary · /expenses/summary GET /contacts/summary POST /documents/pdf

12 Organization (Team & Roles)

ROUTE / SCREEN	DATACLIENT CALL	API ENDPOINT
/team Team & invites	team.listMembers / updateMemberRole team.removeMember / setMemberActive team.listInvites / sendInvite / resendInvite / cancelInvite roles.list	GET /businesses/members PATCH /businesses/members/:userId/role · /status DELETE /businesses/members/:userId GET / POST /invites · DEL /invites/:id
/roles Roles matrix OWNER	roles.list / permissions / get / remove roles.setPermissions	GET /roles · /roles/permissions · /roles/:id PATCH /roles/:id/permissions DELETE /roles/:id
/roles/new/roles/:id/edit Role form OWNER	roles.get / permissions roles.create / update / setPermissions	POST /roles · PATCH /roles/:id PATCH /roles/:id/permissions

13 Settings & Profile

ROUTE / SCREEN	DATACLIENT CALL	API ENDPOINT
/settings Business settings OWNER	business.getProfile / update	GET /businesses/mine POST /businesses/setup
/profile User settings (Appearance)	— local only (theme store)	— no API (prototype sections)
/more Mobile hub	— derived from nav + session	— no API

§ Appendix — client endpoints not yet surfaced in a route

Defined in the data-client / API but not consumed by any current route component (available for dashboards, analytics, or future screens).

SALES ANALYTICS

GET /sales/summary/daily-series · /sales/cashier-roster · /sales/by-product · /sales/by-payment-method · /sales/refunds · /sales/gross-profit

INVENTORY ANALYTICS

GET /inventory/movements · /inventory/turnover · /inventory/dead-stock · /inventory/supplier-price-trend

DEBTS / AGEING

GET /contacts/:id/debts · /debtors/ageing · /creditors/ageing · /contacts/:id/opening-balance

NOTIFICATIONS · PLANS · AUDIT

GET /notifications · /notifications/unread-count · /plans/my-subscription · /plans/quota-usage · /audit **POST** /plans/upgrade · /plans/cancel **PATCH** /notifications/:id/read · /notifications/read-all

Sources: apps/desktop-v2/src/renderer/src/router.tsx, lib/cloud-*.ts, lib/cloud-data.ts, and apps/api/src/**/controllers. Endpoints are relative to /api/v1. Generated 2026-07-17.