

GeoPAT 2.0 user's manual

Notice: At present this is a very incomplete manual but it has installation instructions.

`http://sil.uc.edu`

August 3, 2017

Contents

| | | |
|----------|---|-----------|
| 1 | Introduction | 4 |
| 2 | GeoPAT 2.0 architecture | 5 |
| 2.1 | General description | 5 |
| 2.2 | GeoPAT Modules | 5 |
| 2.2.1 | Signature building | 5 |
| 2.2.1.1 | gpat_gridhis | 5 |
| 2.2.1.2 | gpat_gridts | 8 |
| 2.2.1.3 | gpat_pointshis | 8 |
| 2.2.1.4 | gpat_pointsts | 11 |
| 2.2.1.5 | gpat_polygon | 11 |
| 2.2.2 | Similarity measuring | 13 |
| 2.2.2.1 | gpat_search | 13 |
| 2.2.2.2 | gpat_compare | 14 |
| 2.2.2.3 | gpat_segment | 14 |
| 2.2.2.4 | gpat_distsmx | 14 |
| 2.2.3 | Tools | 15 |
| 2.2.3.1 | gpat_grd2txt | 15 |
| 2.2.3.2 | gpat_globnorm | 15 |
| 2.2.3.3 | gpat_segquality | 15 |
| 3 | Basic workflow paths with examples | 17 |
| 3.1 | Search | 17 |
| 3.1.1 | Search on categorical maps | 17 |
| 3.1.2 | Search on time series | 18 |
| 3.2 | Change detection | 19 |
| 3.3 | Segmentation | 19 |
| 3.4 | Clustering | 20 |
| 3.4.1 | Clustering of individual motifs | 21 |
| 3.4.2 | Clustering of grid of motifs | 22 |
| 3.4.3 | Clustering of segments/predefined irregular regions | 22 |
| | Appendices | 23 |
| A | GeoPAT 2.0 installation | 23 |
| A.1 | System requirements | 23 |
| A.2 | Windows installer | 23 |
| A.3 | Fedora 25 binary installation | 23 |
| A.4 | Building from source code | 24 |

| | | |
|----------|---|-----------|
| B | Numerical signatures and normalization methods available in GeoPAT | 26 |
| B.1 | Cartesian product | 26 |
| B.2 | Class co-occurrence histogram | 26 |
| B.3 | Decomposition histogram | 26 |
| B.4 | Local binary pattern histogram | 26 |
| B.5 | Landscape indices vector | 26 |
| C | Dissimilarity measures available in GeoPAT | 26 |

1 Introduction

TODO

2 GeoPAT 2.0 architecture

TODO




Figure 1: Outline of GeoPAT 2.0 architecture.

2.1 General description

TODO

2.2 GeoPAT Modules

2.2.1 Signature building

2.2.1.1 gpat_gridhis

Creates a binary grid of signatures from a categorical raster map(s).

Usage:

```

gpat_gridhis [-lh] -i <file_name> -o <file_name> [-s <signature_name>] [--level=<n>] [-z <n>]
  [-f <n>] [-n <normalization_name>] [-t <n>]

-i, --input=<file_name> name of input file (GeoTIFF)
-o, --output=<file_name> name of output file (GRID)
-s, --signature=<name> motifel's signature (use -l to list all signatures, default: 'cooc')
--level=<n> full decomposition level (default: 0, auto)
-z, --size=<n> motifel size in cells (default: 150)
-f, --shift=<n> shift of motifels (default: 100)
-n, --normalization=<name> signature normalization method (use -l to list all methods, default: 'pdf')
-l list all signatures and normalization methods
-t <n> number of threads (default: 1)
-h, --help print this help and exit

```

Options:

input

Defines a categorical raster layer(s) which will be used as a source for extracting pattern signature. Layers must be a categorical one. For the Cartesian product method ('prod') there can be more than one input map. Other methods use a one map only (the first one provided). In order to provide more than one input map, type multiple input options ("-i map1.tif -i map2.tif" or "-input=map1.tif -input=map2.tif").

output

Output consists of two files: one of them is a dataset containing a grid of signatures in binary form, the other one is a header text file (the .hdr extension) containing a grid topology and an information about the input data parameters. Modifying the header is strongly discouraged as it may cause some calculations to fail. Structure of the header is as follows:

- dim – number of dimensions of each signature
- dims – size of each dimension
- type – type of data stored in the grid (integer, float, etc.)
- at0 – top left x
- at1 – w-e grid resolution
- at2 – rotation (0 if grid is north-up)
- at3 – top left y
- at4 – rotation (0 if grid is north-up)
- at5 – n-s grid resolution
- rows – number of rows in the grid
- cols – number of cols in the grid

- proj – projection in wkt style
- desc – command used to create the grid

size

Size of a motifel (local calculation window) expressed in the number of pixels. It defines the extent of a local pattern. It is the length of the side of square-shaped block of pixels (motifel). It must be at least 10 and cannot exceed the input map size.

shift

Parameter defines the shift between adjacent scenes along the grid in n-s and w-e directions. It describes the density of the output grid and defines a new topology of the grid. Formula $\text{original_resolution} \times \text{shift} = \text{new_resolution}$ explains how resolution of the original map will be reduced. If shift is set to the same value as 'size', the input map will be simply divided into a grid of non-overlapping motifels. Setting shift to a value smaller than 'size' parameter will result in grid of overlapping motifels. Shift cannot be larger than 'size', and cannot be smaller than 5.

signature

Defines method of calculating signatures of motifels. GeoPAT offers the following methods:

- prod – Cartesian product of input category lists
- cooc – spatial cooccurrence of categories
- sdec – simple 2-level decomposition
- fdec – full decomposition
- lbp – histogram of local binary patterns
- lind – landscape indices vector
- linds – selected landscape indices vector

See Appendix B for the details.

level

This option is used only if 'full decomposition' (fdec) is used. It defines the highest level of decomposition. See Appendix B for the details.

normalization

Specifies normalization method used on the signatures. See Appendix B for the details.

threads (-t)

The module is parallel, therefore use more than one processing thread can be used in order to speed up calculations. This option specifies how many threads will be used. The default is 1.

Description:

This module extracts a "grid-of-scenes" (grid of pattern signatures, grid of motifs). The output is a grid of the same spatial extent as the input raster map, but with a different cell size. Each cell in a new grid has only one attribute - the signature of its pattern. Pattern is calculated over a window centered on the cell and having a user-defined size. Resolution of the output grid equals to the resolution of the input raster map multiplied by the shift parameter. A signature of pattern for each scene is stored as a numerical vector in a binary form. The module outputs a header file (.hdr) containing a topology of a grid-of-scenes and a binary file containing signatures ordered by rows.

This module uses categorical raster data in GeoTIFF format as an input. It might be more than one map for the Cartesian product signature. Raster maps must be categorical and its size must be greater than the scene size specified by the user. Size defines the size of individual scene for which the histogram is calculated. Shift shows how scenes shift along the grid in n-s and w-e directions. Shift defines the resolution of the new grid. If window size is bigger than shift (recommended), motifs will overlap. If shift and size is equal, windows will not overlap. Shift cannot be greater than size.

The output grid may be an input to one of the following GeoPAT modules: *gpat_search*, *gpat_compare*, *gpat_segment*, *gpat_segquality*, *gpat_grd2txt*, and *gpat_globnorm*.

2.2.1.2 gpat_gridts

Usage:

```
gpat_gridts [-nh] -i <file_name> [-i <file_name>]... -o <file_name> [-d <n>]

-i, --input=<file_name> name of input file(s) (GeoTIFF)
-o, --output=<file_name> name of output file (GRID)
-d, --dimension=<n> dimension of vector that describes time series element (default: 1)
-n, --normalize normalize each vector coordinate to [0.0, 1.0] (default: no)
-h, --help print this help and exit
```

2.2.1.3 gpat_pointshis

Calculates numerical signatures of individual motifs within a raster map.

Usage:


```

gpat_pointshis [-lah] -i <file_name> -o <file_name> [-s <signature_name>] [--level=<n>] [-z <n>]
               [-n <normalization_name>] [-x <double>] [-y <double>] [-d <string>] [--xy_file=<file_name>]

-i, --input=<file_name> name of input file (GeoTIFF)
-o, --output=<file_name> name of output file (TXT)
-s, --signature=<name> motifel's signature (use -l to list all signatures, default: 'cooc')
--level=<n> full decomposition level (default: 0, auto)
-z, --size=<n> motifel size in cells (default: 150)
-n, --normalization=<name> signature normalization method (use -l to list all methods, default: 'pdf')
-l list all signatures and normalization methods
-x <double> x coord
-y <double> y coord
-d, --description=<string> description of the location
--xy_file=<file_name> name of file with coordinates (TXT)
-a, --append append results to output file
-h, --help print this help and exit

```

Options:

input

Defines categorical raster map(s) in the GeoTIFF format, which will be used as a source for extracting pattern signature. For the Cartesian product method ('prod') there can be more than one input map. Other methods use one map only (the first one provided). In order to provide more than one input map, type multiple input options ("-i map1.tif -i map2.tif" or "-input=map1.tif -input=map2.tif").

output

Name of output text file containing signatures. In the output file, each line corresponds to a single motifel's signature. Each signature is preceded by its header. A header always consists of: coordinates of the midpoint of motifel (scene), name, number of dimensions, and length of each dimension. Modifying the signature file is strongly discouraged as it may cause some calculations to fail.

signature

Defines method for calculating signatures of motifels. GeoPAT offers the following methods:

- prod – Cartesian product of input category lists
- cooc – spatial cooccurrence of categories
- sdec – simple 2-level decomposition
- fdec – full decomposition
- lbp – histogram of local binary patterns
- lind – landscape indices vector
- linds – selected landscape indices vector

See Appendix B for details.

level

This option is used only when 'full decomposition' (fdec) is used. It defines the highest level of decomposition. See Appendix B for the details.

size

Size of a motifel (scene) for which signature is calculated. Scene is a square centered at the coordinate pair location, while its extent is defined by size.

normalization

Specifies normalization method used on the signatures. See Appendix B for the details.

x

X coordinate of the midpoint of motifel for which signature will be calculated.

y

Y coordinate of the midpoint of motifel for which signature will be calculated.

description

Description of a motifel. It can be a name of location, description of pattern, or anything else. If not provided, the default description is "location".

xy_file

Name of a text file with list of coordinates. This option is useful for calculating signatures for multiple motifels in a single run.

append (flag)

Append mode. Useful when using the coordinate pair mode and when scenes are processed one by one (see description below). If the append flag is used and the output file already exists, signatures will be appended at the end of file instead of overwriting it.

Description:

This module extracts signatures for a scene (motifel) or collection of scenes defined over square-shaped windows. User provides coordinates of the center of each scene and the size of the scene. The module outputs a list of scene-labeled signatures. As an input the module uses categorical raster map in the GeoTIFF format (or a few maps if user calculates the Cartesian product of multiple maps), coordinates of the center of each scene and size of scenes. The coordinates must be in the input map's coordinate system. There are two ways of defining the scenes:

Definition by coordinate pair: This is the simplest mode designed for a batch or interactive processing. In this mode, scene is defined by a pair of its midpoint's coordinates (the *x* and *y* options) and scene size parameter (the *size* option). Only one scene can be processed at once. The *xy_file* option is not used in this mode. If used with the append flag (-a),

signatures can be calculated one by one and added to the same output file. Additionally, the *description* option lets user name a scene. This name will be stored in the output file.

Definition by text file: In this mode, scene midpoint's coordinates are defined in an external text file in which each line contains X,Y coordinates and, optionally, name/description using the following syntax: *x_coordinate,y_coordinate,scene_name*. The name of a file with coordinates is provided using the *xy_file* option. Extent of a scene is defined by the *size* parameter. The *x*, *y* and *description* options are not used in this mode. Example of the content of coordinates file:

```
1289255,1271313,forest
1306271,1272740,city
1268560,1264726
```

If a description is not provided (like in the example above), the program will assign a default name ("location") with id representing the number of line in the coordinate file.

The output signature text file can be used as an input to the following modules: *gpat_search*, *gpat_distrib*.

2.2.1.4 gpat_pointsts

Usage:

```
gpat_pointsts [-ah] -i <file_name> -o <file_name> [-x <double>] [-y <double>] [-d <string>]
               [--xy_file=<file_name>]

-i, --input=<file_name> name of input file (GRID)
-o, --output=<file_name> name of output file (TXT)
-x <double> x coord
-y <double> y coord
-d, --description=<string> description of the location
--xy_file=<file_name> name of file with coordinates (TXT)
-a, --append append results to output file
-h, --help print this help and exit
```

2.2.1.5 gpat_polygon

Calculates numerical signatures of irregular regions.

Usage:

```
gpat_polygon [-lh] -i <file_name> -e <file_name> -o <file_name> [-s <signature_name>] [-n
<normalization_name>] [-t <n>]

-i, --input=<file_name> name of input file (GeoTIFF)
-e, --segments=<file_name> name of input file (GeoTIFF, int)
-o, --output=<file_name> name of output file (TXT)
-s, --signature=<name> signature method (use -l to list all methods, default: 'cooc')
-n, --normalization=<name> signature normalization method (use -l to list all methods, default: 'pdf')
-l list all signatures and normalization methods
-t <n> number of threads (default: 1)
-h, --help print this help and exit
```

Options:

input

Categorical raster map(s) in the GeoTIFF format, which will be used as a source for extracting pattern signature. For the Cartesian product method ('prod') there can be more than one input map. Other methods only use one map (the first one provided). In order to provide more than one input map, type multiple input options ("-i map1.tif -i map2.tif" or "-input=map1.tif -input=map2.tif").

segments

Categorical raster map in the GeoTIFF format which defines spatial division of area of interest into polygonal regions. In this map, regions should be defined as areas of unique ids. Layer must be a raster and its projection, extents and resolution should be identical to the main input map. This layer may be a result of the segmentation module *gpat_segment* or any other categorical map (e.g. map of ids of watersheds).

output

Name of output text file containing signatures. In the output file each line corresponds to a region's signature. Each signature is preceded by its header. A header always consists of: the coordinates of the midpoint of region, name, number of dimensions, and length of each dimension. Modifying the signature file is strongly discouraged as it may cause some calculations to fail.

signature

Defines method for calculating signatures of motifs. GeoPAT offers the following methods:

- prod – Cartesian product of input category lists
- cooc – spatial cooccurrence of categories
- sdec – simple 2-level decomposition
- fdec – full decomposition
- lbp – histogram of local binary patterns
- lind – landscape indices vector
- linds – selected landscape indices vector

See Appendix B for the details.

normalization

Specifies normalization method used on the signatures. See Appendix B for the details.

threads (-t)

The module is parallel, therefore use more than one processing thread can be used in order to speed up calculations. This option specifies how many threads will be used. The default is 1.

Description:

Module extracts signatures for a collection of irregular regions using the same methods as in the *gpat_pointshis* and *gpat_gridhis* modules. As an input, apart from categorical raster map from which signatures are calculated, user provides a categorical raster map which defines spatial division of area of interest into polygonal regions. The module outputs a list of polygon labeled-signatures stored in the form of a text file. Output can be transferred to the *p.sim.distmatrix* for further processing.

The output signature text file can be used as an input to the following modules: *gpat_search*, *gpat_distmtx*.

2.2.2 Similarity measuring

2.2.2.1 gpat_search

Produces similarity maps which show similarity value between query motifs (scenes) and every motif in the input grid.

Usage:

```
gpat_search [-dlh] -i <file_name> [-o <file_name>] -r <file_name> [-m <measure_name>]
  [--type=Byte/....] [-p <file_name>] [-n <n>] [-t <n>]

-i, --input=<file_name> name of input file (GRID)
-o, --output=<file_name> name of output file (TIFF)
-r, --reference=<file_name> reference data to calculate similarity (TXT)
-d, --description use description of the reference histogram(s) as name of output file(s)
-m, --measure=<measure_name> similarity measure (use -l to list all measures; default 'jsd')
-l, --list_measures list all measures
--type=Byte/.... output data type (default: Float64)
-p, --palette=<file_name> name of the file with colors definition (CSV)
-n, --no_data=<n> output NO DATA value (default: none)
-t <n> number of threads (default: 1)
-h, --help print this help and exit
```

input

Binary file containing grid of signatures (grid-of-scenes). Grid is mandatory. User has to provide a name of grid file (without the .hdr extension). Header file is read automatically. Grid is an output from either *gpat_gridhis* or *gpat_gridts* module. Header of the grid will define topology of the output layers. Do not modify header file.

reference

Text file containing one or more signatures of either individual motifs (scenes) or irregular polygons. This option is mandatory. Input text file can be created using the *gpat_pointshis*, *gpat_pointsts* or *gpat_polygons* module. The number of outputs depends on the number of scenes in the input scene file. At least one scene is required.

2.2.2.2 gpat_compare

Usage:

```
gpat_compare [-lh] -i <file_name> -i <file_name> -o <file_name> [--type=Byte/....] [-p
<file_name>] [-n <n>] [-m <measure_name>] [-t <n>]

-i, --input=<file_name> name of input files (GRID)
-o, --output=<file_name> name of output file with similarity (TIFF)
--type=Byte/.... output data type (default: Float64)
-p, --palette=<file_name> name of the file with colors definition (CSV)
-n, --no_data=<n> output NO DATA value (default: none)
-m, --measure=<measure_name> similarity measure (use -l to list all measures; default 'jsd')
-l, --list_measures list all measures
-t <n> number of threads (default: 1)
-h, --help print this help and exit
```

2.2.2.3 gpat_segment

Usage:

```
gpat_segment [-lcgaqh] -i <file_name> -o <file_name> [-v <file_name>] [--size=<n>] [-m
<measure_name>] [--lthreshold=<double>] [--uthreshold=<double>] [--swap=<double>]
[--minarea=<n>] [--maxhist=<n>] [-t <n>]

-i, --input=<file_name> name of input files (GRID)
-o, --output=<file_name> name of output file with segments (TIFF)
-v, --vector=<file_name> name of output vector file with segments (SHP)
--size=<n> output resolution modifier (default: 1)
-m, --measure=<name> similarity measure (use -l to list all measures; default: jsd)
-l, --list_measures list all measures
--lthreshold=<double> minimum distance threshold to build areas (default: 0.1)
--uthreshold=<double> maximum distance threshold to build areas (default: 0.3)
--swap=<double> improve segmentation by swapping unmatched areas. -1 to skip (default: 0.001)
--minarea=<n> minimum number of motifs in individual segment (default: 0)
--maxhist=<n> create similarity/distance matrix for maxhist histograms; leave 0 to use all (default:
200)
-c, --complete use complete linkage (default is average)
-g, --no_growing skip growing phase
-a, --no_hierarchical skip hierarchical phase
-q, --quad quad mode (rook topology)
-t <n> number of threads (default: 1)
-h, --help print help and exit
```

2.2.2.4 gpat_distmtx

Usage:

```

gpat_distmtx [-lsh] -i <file_name> -o <file_name> [-m <measure_name>]

-i, --input=<file_name> name of input file witch signatures (TXT)
-o, --output=<file_name> name of output file (CSV) with similarity matrix
-m, --measure=<name> similarity measure (use -l to list all measures; default 'jsd')
-l, --list_measures list all measures
-s, --similarity output is a similarity matrix
-h, --help print this help and exit

```

2.2.3 Tools

2.2.3.1 gpat_grd2txt

Usage:

```

gpat_grd2txt [-h] -i <file_name> -o <file_name>

-i, --input=<file_name> name of input file (GRID)
-o, --output=<file_name> name of output file (TXT)
-h, --help print this help and exit

```

2.2.3.2 gpat_globnorm

Usage:

```

gpat_globnorm [-lh] -i <file_name> -o <file_name> [-m <method_name>] [-t <n>]

-i, --input=<file_name> name of input file (GRID)
-o, --output=<file_name> name of output file (GRID)
-m, --method=<method_name>
normalization method (use -l to list all methods, default: '01')
-l, --list_methods list all methods
-t <n> number of threads (default: 1)
-h, --help print this help and exit

```

2.2.3.3 gpat_segquality

Usage:

```

gpat_segquality [-lcqwh] -i <file_name> -s <file name> [-g <file_name>] [-o <file_name>] [-m
<measure_name>] [--maxhist=<n>] [-t <n>]

-i, --input=<file_name> name of input file (GRID)
-s, --segments=<file name> name of input segmentation map (TIFF)
-g, --inhomogeneity=<file_name> name of output file with segment inhomogeneity (TIF
F)
-o, --isolation=<file_name> name of output file with segment isolation (TIFF)
-m, --measure=<name> similarity measure (use -l to list all measures; default: jsd)
-l, --list_measures list all measures
--maxhist=<n> create similarity/distance matrix for maxhist histograms; leave 0 to use all (default:
200)
-c, --complete use complete linkage (default is average)
-q, --quad quad mode (rook topology)
-w, --no_weight switch off edge-based weighting in isolation
-t <n> number of threads (default: 1)
-h, --help print help and exit

```


3 Basic workflow paths with examples

In this section, basic procedures that can be performed using GeoPAT are presented. These are:

- **Search** - search for areas similar to a query,
- **Change detection** - comparison of local patterns of two different maps,
- **Segmentation** - division of a map into regions of cohesive patterns,
- **Clustering** - grouping patterns that are similar to each other.

The procedures are explained using workflow schemes, and examples. All the examples of how to process categorical data are shown on a 1400×2300 px (42×69 km) part of the National Land Cover Dataset (NLCD) covering area around the city of Augusta, GA (Figure 2). This area is characterized by high diversity of land cover categories and patterns. Thus it is perfect for various pattern analyzes.

Figure 2: Part of NLCD, covering area around Augusta, GA used in the examples.

3.1 Search

Search functionality enables user to produce maps of similarity. These maps show the level of similarity between a specified motifel (query) and a grid of motifels. The input is one or more GeoTIFF raster maps (depending on a data and signature type; see appendix B for more information), and XY coordinates of one or more points in space. The result is one or more GeoTIFF raster maps which have the same extent as the grid of motifels specified by user. The number of resulting maps is the same as the number of points provided. The workflows for categorical maps and time series differ.

3.1.1 Search on categorical maps

Figure 3 presents general workflow path for producing similarity maps using a categorical raster data.




Figure 3: Workflow path for search on categorical maps.

The first step is to prepare signature files for both query motifs and grid of motifs using two separate modules, *gpat_pointshis* and *gpat_gridhis* respectively. The second step is to use these signature files as inputs to *gpat_search* module in order to produce similarity maps.

Example:

```

gpat_gridhis -i Augusta2011.tif -o grid -s cooc -z 50 -f 50 -n pdf
gpat_pointshis -i Augusta2011.tif -o query_signatures.txt -s cooc -z 50 -n pdf
--xy_file=coordinates.txt
gpat_search -i grid -r query_signatures.txt
gpat_pointsts -i grid -o query_signatures.txt --xy_file=coordinates.txt
  
```

do not have to have the same size (but is recommended)

3.1.2 Search on time series

TODO




Figure 4: Workflow path for search on time series.

3.2 Change detection

TODO




Figure 5: Workflow path for change detection.

3.3 Segmentation

TODO




Figure 6: Workflow path for segmentation.

3.4 Clustering

TODO

3.4.1 Clustering of individual motifels




Figure 7: Workflow path for clustering of motifels.




Figure 8: Workflow path for clustering of time series motifels.

3.4.2 Clustering of grid of motifs




Figure 9: Workflow path for clustering of grid of motifs.

3.4.3 Clustering of segments/predefined irregular regions




Figure 10: Workflow path for clustering of segments (regions).

Appendices

A GeoPAT 2.0 installation

A.1 System requirements

Windows installer and Linux binaries provides all necessary components. To build GeoPAT 2.0 from the source code the user has to install the GDAL library and compile and install the ezGDAL and SML libraries.

A.2 Windows installer

The windows installer works under 64 bit versions of Windows 7, 8.1, and 10. The installer provides four components:

- GDAL library package
- ezGDAL and SML libraries
- GeoPAT 2.0 software
- Microsoft Visual C 13 runtime libraries (optional)

To start installation process user has to run GPAT20setup.exe. The setup program should be ran in "Run as administrator" mode. If an antivirus software is running on the computer, user should switch it off temporary for the time of GeoPAT installation. The installer will create directory for GDAL and GeoPAT and copy all necessary files. Optionally, GPAT20setup.exe will start installer of Microsoft Visual C runtime libraries. When installation is finished, the user can find "SIL GeoPAT 2.0" submenu in Windows start menu with "GeoPAT console" and "Uninstall GeoPAT".

The installer for Windows x64 is available at:

```
http://sil.uc.edu/cms/data/uploads/software\_data/GPAT20setup.exe
```

A.3 Fedora 25 binary installation

To install binary version of GeoPAT 2.0, user has to copy contents of gpat20 directory from gpat20.tar.gz file to /usr/local directory. The GeoPAT 2.0 binaries require the GDAL package installed on the computer. The user can install this package using dnf package manager on a Fedora system.

```
dnf install gdal
```

The additional requirement is a proper configuration of the libraries path. The Fedora system should look for libraries in /usr/local/lib. Sometimes it is necessary to create file local.conf containing following text: "/usr/local/lib". The file has to be placed in /etc/ld.so.conf.d directory.

The Fedora 25 x64 binaries are available at:

```
http://sil.uc.edu/cms/data/uploads/software_data/gpat20.tar.gz
```

A.4 Building from source code

This compilation procedure is focused on Fedora 25 Linux distribution. The user has to modify the procedure to fit it for a different Linux distribution.

To build GeoPAT 2.0 from the source code the user has to do four following steps:

- Install the development version of GDAL
- Build and install the ezGDAL library
- Build and install the SML library
- Build and install the GeoPAT 2.0 software

To install the development version of GDAL, the dnf package manager can be used:

```
dnf install gdal-devel
```

To install the ezGDAL library the user has to download the ezGDAL source code and unpack it. Next, he has to compile the code by calling the following command in an unpacked source code directory:

```
make
```

and to install it

```
make install
```

By default the library is placed in /usr/local/lib directory and include file is placed in /usr/local/include. The user can change the destination directory by adding the PREFIX parameter.

```
make PREFIX=/my/destination/directory
```

When PREFIX is provided, the library is placed in /my/destination/directory/lib and the include file is placed in /my/destination/directory/include.

Installation procedure of the SML library is similar. After extraction of the source code of SML, the user should call: "make" and "make install".

The command "make install" should be called using sudo command or in root user context.

After finishing libraries installation procedure the user has to ensure that PREFIX/lib is on the library search path.

The last step of installation procedure is a compilation of the GeoPAT 2.0 source code. GeoPAT depends on the GDAL, SML, and ezGDAL libraries. So, after installing above libraries the user has to unpack, compile and install GeoPAT code. The installation procedure is similar to installation procedures of ezGDAL and SML libraries. PREFIX parameter works in the same way. "make" commands should be run in the root GeoPAT 2.0 source code directory.

The source code of GeoPAT 2.0 is available at:

http://sil.uc.edu/cms/data/uploads/software_data/gpat2.0src.tar.gz

The source code of ezGDAL is available at:

<http://pawel.netzel.pl/data/uploads/software/libezgdal.src.tar.gz>

The source code of SML is available at:

<http://pawel.netzel.pl/data/uploads/software/libsmml.src.tar.gz>

B Numerical signatures and normalization methods available in GeoPAT

A signature is the numerical description of a motif

B.1 Cartesian product

B.2 Class co-occurrence histogram

B.3 Decomposition histogram

B.4 Local binary pattern histogram

B.5 Landscape indices vector

C Dissimilarity measures available in GeoPAT

TODO