

Programozási nyelvek Java

Kódszervezés

Kozsik Tamás

Hibajelzés kivétel kiváltásával

```
public class Time {  
    int hour;           // 0 <= hour < 24  
    int min;            // 0 <= min < 60  
  
    ...  
  
    public void setHour(int hour) {  
        if (0 <= hour && hour <= 23) {  
            this.hour = hour;  
        } else {  
            throw new IllegalArgumentException("Invalid hour!");  
        }  
    }  
}
```

Az assert utasítás

```
public class Time {  
    int hour;           // 0 <= hour < 24  
    int min;           // 0 <= min < 60  
  
    ...  
  
    public void setHour(int hour) {  
        assert 0 <= hour && hour <= 23;  
        this.hour = hour;  
    }  
}
```

Az assert utasítás

TestTime.java

```
Time time = new Time(6,30);  
time.setHour(30);
```

Futtatás

```
$ java TestTime  
$ java -enableassertions TestTime  
Exception in thread "main" java.lang.AssertionError  
    at Time.setHour(Time.java:7)  
    at TestTime.main(TestTime.java:5)  
$
```

Opciók hibák jelzésére

Jó megoldások

- `IllegalArgumentException`: modul határán
- `assert`: modul belsejében
- Dokumentációs megjegyzés

Rossz megoldások

- Csendben elszabotálni a műveletet
- Elsumákolni az ellenőrzéseket

Ellenőrzött kivételek

Checked exception

```
public Time readTime(String fname) throws java.io.IOException
    // ez a kódrészlet kiválthat IOException kivételt
}
```

- A programszövegben jelölni kell a terjedését
- A fordítóprogram ellenőrzi a konzisztenciát
- Ilyen: `java.sql.SQLException`, `java.security.KeyException`
- Nem ilyen: `NullPointerException`,
`ArrayIndexOutOfBoundsException`



Ellenőrzött kivételek

Checked exception

```
public Time readTime(String fname) throws java.io.IOException  
    // ez a kódrészlet kiválthat IOException kivételt  
}
```

- A programszövegben jelölni kell a terjedését
- A fordítóprogram ellenőrzi a konzisztenciát
- Ilyen: `java.sql.SQLException`, `java.security.KeyException`
- Nem ilyen: `NullPointerException`,
`ArrayIndexOutOfBoundsException`

Unchecked exception

- Pl. `NullPointerException`, `ArrayIndexOutOfBoundsException`
- Dinamikus szemantikai hiba
- „Bárhol” keletkezhet



Terjedés követése: fordítási hiba

```
import java.io.IOException;

public class TestTime {
    public Time readTime(String fname) throws IOException {
        ... new java.io.FileReader(fname) ...
    }

    public static void main(String[] args) {
        TestTime tt = new TestTime();
        Time wakeUp = tt.readTime("wakeup.txt");
        wakeUp.aMinutePassed();
    }
}
```


Terjedés követése: fordítási hiba javítva

```
import java.io.IOException;

public class TestTime {
    public Time readTime(String fname) throws IOException {
        ... new java.io.FileReader(fname) ...
    }

    public static void main(String[] args) throws IOException {
        TestTime tt = new TestTime();
        Time wakeUp = tt.readTime("wakeup.txt");
        wakeUp.aMinutePassed();
    }
}
```

Kivételkezelés

```
import java.io.IOException;

public class TestTime {
    public Time readTime(String fname) throws IOException {
        ... new java.io.FileReader(fname) ...
    }

    public static void main(String[] args) {
        TestTime tt = new TestTime();
        try {
            Time wakeUp = tt.readTime("wakeup.txt");
            wakeUp.aMinutePassed();
        } catch (IOException e) {
            System.err.println("Could not read wake-up time.");
        }
    }
}
```



A program tovább futhat a probléma ellenére

```
public class Receptionist {  
    ...  
    public Time[] readWakeupTimes(String[] fnames) {  
        Time[] times = new Time[fnames.length];  
        for (int i = 0; i < fnames.length; ++i) {  
            try {  
                times[i] = readTime(fnames[i]);  
            } catch (java.io.IOException e) {  
                times[i] = null;    // no-op  
                System.err.println("Could not read " + fnames[i]);  
            }  
        }  
        return times; // maybe sort times before returning?  
    }  
}
```



Több catch-ág

```
public static Time parse(String str) {  
    String errorMessage;  
    try {  
        String[] parts = str.split(":");  
        int hour = Integer.parseInt(parts[0]);  
        int minute = Integer.parseInt(parts[1]);  
        return new Time(hour,minute);  
    } catch (NullPointerException e) {  
        errorMessage = "Null parameter is not allowed!";  
    } catch (ArrayIndexOutOfBoundsException e) {  
        errorMessage = "String must contain \":\"!";  
    } catch (NumberFormatException e) {  
        errorMessage = "String must contain two numbers!";  
    }  
    throw new IllegalArgumentException(errorMessage);  
}
```



Egy catch-ágban több kivétel

```
public static Time parse(String str) {  
    try {  
        String[] parts = str.split(":");  
        int hour = Integer.parseInt(parts[0]);  
        int minute = Integer.parseInt(parts[1]);  
        return new Time(hour,minute);  
    } catch (NullPointerException  
            | ArrayIndexOutOfBoundsException  
            | NumberFormatException e) {  
        throw new IllegalArgumentException("Can't parse time!");  
    }  
}
```

finally


A try-finally utasítás

```
public static Time readTime(String fname) throws IOException {
    var in = new BufferedReader(new FileReader(fname));
    Time time;
    try {
        String line = in.readLine();
        time = parse(line);
    } finally {
        in.close();
    }
    return time;
}
```

finally

A finally mindenképp vezérlést kap!

```
public static Time readTime(String fname) throws IOException {  
    var in = new BufferedReader(new FileReader(fname));  
    try {  
        String line = in.readLine();  
        return parse(line);  
    } finally {  
        in.close();  
    }  
}
```



finally

A try-catch-finally utasítás

```

public static Time readTime(String fname) throws IOException {
    var in = new BufferedReader(new FileReader(fname));
    try {
        String line = in.readLine();
        return parse(line);
    } catch (IllegalArgumentException e) {
        System.err.println(e);
        System.err.println("Using default value!");
        return new Time(0,0);
    } finally {
        in.close();
    }
}

```


finally

A try-utasítások egymásba ágyazhatók

```
public static Time readTimeOrUseDefault(String fn) {  
    try {  
        var in = new BufferedReader(new FileReader(fn));  
        try {  
            String line = in.readLine();  
            return parse(line);  
        } finally {  
            in.close();  
        }  
    } catch (IOException | IllegalArgumentException e) {  
        System.err.println(e);  
        System.err.println("Using default value!");  
        return new Time(0,0);  
    }  
}
```

Erőforráskezelő try (*try-with-resources*) utasítás

```
public static Time readTimeOrUseDefault(String fn) {  
    try (  
        var in = new BufferedReader(new FileReader(fn))  
    ) {  
        String line = in.readLine();  
        return parse(line);  
    } catch (IOException | IllegalArgumentException e) {  
        System.err.println(e);  
        System.err.println("Using default value!");  
        return new Time(0,0);  
    }  
}
```

Lényegében ekvivalensek

try-finally

```
BufferedReader in = ...;
try {
    String line = in.readLine();
    return parse(line);
} finally {
    in.close();
}
```

try-with-resources

```
try (
    BufferedReader in = ...
) {
    String line = in.readLine();
    return parse(line);
}
```



Több erőforrás használata

```
static void copy(String in, String out) throws IOException {  
    try (  
        FileInputStream infile = new FileInputStream(in);  
        FileOutputStream outfile = new FileOutputStream(out)  
    ) {  
        int b;  
        while ((b = infile.read()) != -1) {    // idióma!  
            outfile.write(b);  
        }  
    }  
}
```

Dokumentációs megjegyzés

```
/** May throw AssertionError. */  
public void setHour(int hour) {  
    assert 0 <= hour && hour <= 23;  
    this.hour = hour;  
}
```

Dokumentált potenciálisan hibás használat

```
/**
    Blindly sets the hour property to the given value.
    Use it with care: only pass {@code hour} satisfying
    {@code 0 <= hour && hour <= 23}.
 */
public void setHour(int hour) {
    this.hour = hour;
}
```

javadoc Time.java

PACKAGE CLASS TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES ALL CLASSES

SEARCH: 

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

Constructor Summary**Constructors****Constructor****Description**

Time()

Method Summary**All Methods****Instance Methods****Concrete Methods****Modifier and Type****Method****Description**

int

getHour()

int

getMinute()

void

oneMinutePassed()

void

setHour(int hour)

Blindly sets the hour property to the given value.



javadoc Time.java

PACKAGE CLASS TREE DEPRECATED INDEX HELP

PREV CLASS NEXT CLASS FRAMES NO FRAMES ALL CLASSES

SEARCH:

SUMMARY: NESTED | FIELD | CONSTR | METHOD DETAIL: FIELD | CONSTR | METHOD

getHour

```
public int getHour()
```

getMinute

```
public int getMinute()
```

setHour

```
public void setHour(int hour)
```

Blindly sets the hour property to the given value. Use it with care: only pass hour satisfying $0 \leq \text{hour} \ \&\& \ \text{hour} \leq 23$.

Szokásos (túl bőbeszédű) dokumentációs megjegyzés

```
/**  
 * Sets the hour property. Only pass an {@code hour}  
 * satisfying {@code 0 <= hour && hour <= 23}.  
 * @param hour The value to be set.  
 * @throws IllegalArgumentException  
 *     If the supplied value is not between 0 and 23,  
 *     inclusively.  
 */
```

```
public void setHour(int hour) {  
    if (0 <= hour && hour <= 23) {  
        this.hour = hour;  
    } else {  
        throw new IllegalArgumentException("Invalid hour");  
    }  
}
```

javadoc Time.java

setHour

```
public void setHour(int hour)
```

Sets the hour property. Only pass an hour satisfying $0 \leq \text{hour} \leq 23$.

Parameters:

hour - The value to be set.

Throws:

java.lang.IllegalArgumentException - If the supplied value is not between 0 and 23, inclusively.

Syntax highlighting

```
/**
 * Sets the hour property. Only pass an {@code hour}
 * satisfying {@code 0 <= hour && hour <= 23}.
 * @param hour The value to be set.
 * @throws IllegalArgumentException
 *     If the supplied value is not between 0 and 23,
 *     inclusively.
 */
public void setHour( int hour ){
    if( 0 <= hour && hour <= 23 ){
        this.hour = hour;
    } else {
        throw new IllegalArgumentException("Invalid hour!");
    }
}
```

21,1

Racionális számok megvalósítása

```
package numbers;

public class Rational {
    private int numerator, denominator;
    /* class invariant: denominator > 0 */

    public Rational(int numerator, int denominator) {
        if (denominator <= 0) throw new IllegalArgumentException();
        this.numerator = numerator;
        this.denominator = denominator;
    }
}
```

Getter-setter

```
package numbers;

public class Rational {
    private int numerator, denominator;

    public Rational(int numerator, int denominator) { ... }

    public void setDenominator(int denominator) {
        if (denominator <= 0) throw new IllegalArgumentException();
        this.denominator = denominator;
    }

    public int getDenominator() { return denominator; }

    ...
}
```

Tervezett használat

```
import numbers.Rational;

public class Main {
    public static void main(String[] args) {
        Rational p = new Rational(1,3);
        Rational q = new Rational(1,2);
        p.multiplyWith(q);
        println(p);           // 1/6
        println(q);           // 1/2
    }
    private static void println(Rational r) {
        System.out.println(r.getNumerator()+"/"+r.getDenominator());
    }
}
```

Aritmetika

```
package numbers;

public class Rational {
    private int numerator, denominator;
    public Rational(int numerator, int denominator) { ... }
    public int getNumerator() { return numerator; }
    public int getDenominator() { return denominator; }
    public void setNumerator(int numerator) { ... }
    public void setDenominator(int denominator) { ... }

    public void multiplyWith(Rational that) {
        this.numerator *= that.numerator;
        this.denominator *= that.denominator;
    }
    ...
}
```

Dokumentációs megjegyzéssel

```
package numbers;

public class Rational {

    ...
    /**
     * Set {@code this} to {@code this} * {@code that}.
     * @param that Non-null reference to a rational number,
     *           it will not be changed in the method.
     * @throws NullPointerException When {@code that} is null.
     */
    public void multiplyWith(Rational that) {
        this.numerator *= that.numerator;
        this.denominator *= that.denominator;
    }

    ...
}
```


Műveletek sorozása

```
package numbers;

public class Rational {
    ...
    public Rational multiplyWith(Rational that) {
        this.numerator *= that.numerator;
        this.denominator *= that.denominator;
        return this;
    }
    ...
}
```

```
Rational p = new Rational(1,3);
Rational q = new Rational(1,2);
p.multiplyWith(q).multiplyWith(q).divideBy(q);
println(p);
```

Osztálysztintű metódus (függvény)

```
public class Rational {  
    private final int numerator, denominator;  
    public Rational(int numerator, int denominator) { ... }  
    public int numerator() { return numerator; }  
    public int denominator() { return denominator; }  
  
    public static Rational times(Rational left, Rational right)  
        return new Rational(left.numerator * right.numerator,  
                             left.denominator * right.denominator);  
}  
}
```

```
Rational p = new Rational(1,3), q = new Rational(1,2);  
Rational r = Rational.times(p,q);
```

Osztálysztintű metódus (eljárás)

```
public class Rational {  
    private int numerator, denominator;  
    ...  
    public static void multiplyInPlace(Rational left,  
                                       Rational right) {  
        left.numerator *= right.numerator;  
        left.denominator *= right.denominator;  
    }  
}
```

```
Rational p = new Rational(1,3), q = new Rational(1,2);  
Rational.multiplyLeftWithRight(p,q);
```

Egy másfajta megközelítés

```
package numbers;

public class Rational {
    ...
    public void multiplyWith(Rational that) { ... }
    public Rational times(Rational that) { ... }
}
```

```
Rational p = new Rational(1,3);
Rational q = new Rational(1,2);
p.multiplyWith(q);
println(p);           // 1/6
Rational r = p.times(q);
println(r);           // 1/12
println(p);           // 1/6
```

Megvalósítások

```
package numbers;

public class Rational {
    private int numerator;
    private int denominator;
    public Rational(int numerator, int denominator) { ... }
    ...
    public Rational times(Rational that) {
        return new Rational(this.numerator * that.numerator,
                             this.denominator * that.denominator);
    }
    public void multiplyWith(Rational that) {
        this.numerator *= that.numerator;
        this.denominator *= that.denominator;
    }
}
```

Megvalósítások

```
package numbers;

public class Rational {
    private int numerator;
    private int denominator;
    public Rational(int numerator, int denominator) { ... }
    ...
    public Rational times(Rational that) {
        return new Rational(this.numerator * that.numerator,
                             this.denominator * that.denominator);
    }
    public Rational multiplyWith(Rational that) {
        this.numerator *= that.numerator;
        this.denominator *= that.denominator;
        return this;
    }
}
```

Operátor-túlterhelés nincs a Javában

```
package numbers;

public class Rational {
    private int numerator;
    private int denominator;
    public Rational(int numerator, int denominator) { ... }
    ...
    public Rational operator*(Rational that) { // compilation error
        return new Rational(this.numerator * that.numerator,
                             this.denominator * that.denominator);
    }
    public Rational operator*=(Rational that) { // compilation error
        this.numerator *= that.numerator;
        this.denominator *= that.denominator;
        return this;
    }
}
```

Sosem módosuló belső állapot

```
package numbers;

public class Rational {
    private int numerator;
    private int denominator;
    public Rational(int numerator, int denominator) {
        if (denominator <= 0) throw new IllegalArgumentException();
        this.numerator = numerator;
        this.denominator = denominator;
    }
    public int getNumerator() { return numerator; }
    public int getDenominator() { return denominator; }
    public Rational times(Rational that) { ... }
    public Rational plus(Rational that) { ... }
    ...
}
```


Módosíthatatlan mezőkkel

```
package numbers;

public class Rational {
    private final int numerator, denominator;
    public Rational(int numerator, int denominator) {
        if (denominator <= 0) throw new IllegalArgumentException();
        this.numerator = numerator;
        this.denominator = denominator;
    }
    public int getNumerator() { return numerator; }
    public int getDenominator() { return denominator; }
    public Rational times(Rational that) { ... }
    public Rational plus(Rational that) { ... }
    ...
}
```

Több metódus ugyanazzal a névvel

```
public class Rational {  
    ...  
    public void multiplyWith(Rational that) {  
        this.numerator *= that.numerator;  
        this.denominator *= that.denominator;  
    }  
  
    public void multiplyWith(int that) {  
        this.numerator *= that;  
    }  
}
```

```
Rational p = new Rational(1,3), q = new Rational(1,2);  
p.multiplyWith(q);  
p.multiplyWith(2);
```

Trükkös szabályok: „jobban illeszkedő”

```
static void m(long n) { ... }  
static void m(float n) { ... }  
public static void main(String[] args) {  
    m(3);  
}
```

Egyformán illeszkedő

```
static void m(long n, float m) { ... }  
static void m(float m, long n) { ... }  
public static void main(String[] args) {  
    m(4,2);  
}
```

Foo.java:5: error: reference to m is ambiguous

```
    m(4,2);  
    ^
```

both method m(long,float) in Foo

and method m(float,long) in Foo match

1 error

Több konstruktor ugyanabban az osztályban

```
public class Rational {  
    ...  
    public Rational(int numerator, int denominator) {  
        if (denominator <= 0) throw new IllegalArgumentException();  
        this.numerator = numerator;  
        this.denominator = denominator;  
    }  
  
    public Rational(int value) {  
        numerator = value;  
        denominator = 1;  
    }  
}
```

```
Rational p = new Rational(1,3), q = new Rational(3);
```



Túlterhelés (overloading)

- Több metódus ugyanazzal a névvel, több konstruktor

Túlterhelés (overloading)

- Több metódus ugyanazzal a névvel, több konstruktor
- Formális paraméterek eltérnek
 - ◇ Paraméterek száma
 - ◇ Paraméterek deklarált típusa

Túlterhelés (overloading)

- Több metódus ugyanazzal a névvel, több konstruktor
- Formális paraméterek eltérnek
 - ◇ Paraméterek száma
 - ◇ Paraméterek deklarált típusa
- Híváskor a fordító eldönti, melyiket kell hívni
 - ◇ Az aktuális paraméterek száma,
 - ◇ illetve deklarált típusa alapján

Túlterhelés (overloading)

- Több metódus ugyanazzal a névvel, több konstruktor
- Formális paraméterek eltérnek
 - ◇ Paraméterek száma
 - ◇ Paraméterek deklarált típusa
- Híváskor a fordító eldönti, melyiket kell hívni
 - ◇ Az aktuális paraméterek száma,
 - ◇ illetve deklarált típusa alapján
- Fordítási hiba, ha:
 - ◇ Egyik sem felel meg a hívásnak
 - ◇ Több is egyformán megfelel

Túlterhelés (overloading)

- Több metódus ugyanazzal a névvel, több konstruktor
- Formális paraméterek eltérnek
 - ◇ Paraméterek száma
 - ◇ Paraméterek deklarált típusa
- Híváskor a fordító eldönti, melyiket kell hívni
 - ◇ Az aktuális paraméterek száma,
 - ◇ illetve deklarált típusa alapján
- Fordítási hiba, ha:
 - ◇ Egyik sem felel meg a hívásnak
 - ◇ Több is egyformán megfelel
- Angolul nem összekeverendő: **overriding** (felüldefiniálás) vs **overloading** (túlterhelés)

Jó ez így?

```
public class Rational {  
    ...  
  
    public void multiplyWith(Rational that) {  
        this.numerator *= that.numerator;  
        this.denominator *= that.denominator;  
    }  
  
    public Rational multiplyWith(Rational that) {  
        this.numerator *= that.numerator;  
        this.denominator *= that.denominator;  
        return this;  
    }  
    ...  
}
```

Jogos túlterhelés

```
public class Rational {  
    ...  
    public void set(int numerator, int denominator) {  
        if (denominator <= 0) throw new IllegalArgumentException();  
        this.numerator = numerator;  
        this.denominator = denominator;  
    }  
  
    public void set(Rational that) {  
        if (that == null) throw new IllegalArgumentException();  
        this.numerator = that.numerator;  
        this.denominator = that.denominator;  
    }  
    ...  
}
```

Alapértelmezett érték?

```
public class Rational {  
    ...  
    public void set(int numerator, int denominator) {  
        if (denominator <= 0) throw new IllegalArgumentException();  
        this.numerator = numerator;  
        this.denominator = denominator;  
    }  
    public void set(int value) {  
        set(value, 1);  
    }  
    public void set() {  
        set(0);  
    }  
    ...  
}
```

Alapértelmezett érték – a Java ezt nem engedi

```
public class Rational {  
    ...  
    public Rational(int numerator = 0, int denominator = 1) {  
        if (denominator <= 0) throw new IllegalArgumentException();  
        this.numerator = numerator;  
        this.denominator = denominator;  
    }  
  
    public void set(int numerator = 0, int denominator = 1) {  
        if (denominator <= 0) throw new IllegalArgumentException();  
        this.numerator = numerator;  
        this.denominator = denominator;  
    }  
    ...  
}
```

Konstruktorok hívhatják egymást

```
public class Rational {  
    ...  
    public Rational(int numerator, int denominator) {  
        if (denominator <= 0) throw new IllegalArgumentException();  
        this.numerator = numerator;  
        this.denominator = denominator;  
    }  
  
    public Rational(int value) {  
        this(value, 1); // a legelső utasításnak kell lennie!  
    }  
  
    public Rational() {  
        this(0);  
    }  
    ...  
}
```

Konstruktor(ok) helyett gyártóművelet(ek)

e.g. Rational.zero() instead of new Rational(0)

```
public class Rational {  
    ...  
    private Rational(int numerator, int denominator) {  
        this.numerator = numerator;  
        this.denominator = denominator;  
    }  
    public static Rational make(int numerator, int denominator) {  
        return new Rational(numerator, denominator);  
    }  
    public static Rational valueOf(int val) {return make(val, 1);}  
    public static Rational oneOver(int den) {return make(1, den);}  
    public static Rational zero() { return make(0, 1); }  
}
```



Paraméterátadási technikák

- Szövegszerű helyettesítés
- Érték szerinti
- Érték-eredmény szerinti
- Eredmény szerinti
- Cím szerinti
- Megosztás szerinti
- Név szerinti
- Igény szerinti

Paraméterátadás Javában

Érték szerinti (call-by-value)

primitív típusú paraméterre

```
public void setNumerator(int numerator) {  
    this.numerator = numerator;  
}
```

Megosztás szerinti (call-by-sharing)

referencia típusú paraméterre (a referenciát érték szerint adjuk át)

```
public static void multiplyLeftWithRight(Rational left,  
                                         Rational right) {  
    left.numerator    *= right.numerator;  
    left.denominator *= right.denominator;  
}
```

Érték szerinti (call-by-value)

```
public void setNumerator(int numerator) {  
    this.numerator = numerator;  
    numerator = 0;  
}
```

```
Rational p = new Rational(1,3);  
int two = 2;  
p.setNumerator(two);  
println(p);  
System.out.println(two);
```

Megosztás szerinti (call-by-sharing)

```
public static void multiplyLeftWithRight(Rational left,
                                         Rational right) {
    left.numerator    *= right.numerator;
    left.denominator  *= right.denominator;
    left = new Rational(9,7);
}
```

```
Rational p = new Rational(1,3), q = new Rational(1,2);
Rational.multiplyLeftWithRight(p,q);
println(p);
```

Változó számú paraméter

```
static int sum(int[] nums) {  
    int sum = 0;  
    for (int num: nums) { sum += num; }  
    return sum;  
}  
  
sum(new int[] {1,2,3,4,5,6})
```

Változó számú paraméter

```
static int sum(int[] nums) {  
    int sum = 0;  
    for (int num: nums) { sum += num; }  
    return sum;  
}
```

```
sum(new int[]{1,2,3,4,5,6})
```

```
static int sum(int... nums) {  
    int sum = 0;  
    for (int num: nums) { sum += num; }  
    return sum;  
}
```

```
sum(new int[]{1,2,3,4,5,6})
```

Globális konstans

```
public static final int WIDTH = 80;
```

- Osztályszintű mező
- Picit olyan, mint a C-ben egy `#define`
- Hasonló a C-beli `const`-hoz is (de nem pont ugyanaz)
- Konvenció: végig nagybetűvel írjuk a nevét

Módosíthatatlan mező

- Például WIDTH globális konstans
- Vagy Rational két mezője
- Ha egyszer értéket kapott, nem adhatunk új értéket neki
- Inicializáció során értéket kell kapjon
 - ◇ „Üres konstans” (blank final)!

```
public class Rational {  
    private final int numerator, denominator;  
    public Rational(int numerator, int denominator) {  
        this.numerator = numerator;  
        this.denominator = denominator;  
    }  
    ...  
}
```


Módosíthatatlan lokális változó

```
public class Rational {  
    ...  
    public void simplify() {  
        final int gcd = gcd(numerator, denominator);  
        numerator /= gcd;  
        denominator /= gcd;  
    }  
    ...  
}
```

Módosíthatatlan formális paraméter

Hibás

```
static java.math.BigInteger factorial(final int n) {  
    assert n > 0;  
    java.math.BigInteger result = java.math.BigInteger.ONE;  
    while (n > 1) {  
        result = result.multiply(java.math.BigInteger.valueOf(n));  
        --n;  
    }  
    return result;  
}
```

Módosíthatatlan formális paraméter

Helyes

```
static java.math.BigInteger factorial(final int n) {  
    assert n > 0;  
    java.math.BigInteger result = java.math.BigInteger.ONE;  
    for (int i=n; i>1; --i) {  
        result = result.multiply(java.math.BigInteger.valueOf(i));  
    }  
    return result;  
}
```

Mutable versus Immutable

Módosítható belső állapot

```
public class Rational {  
    private int numerator, denominator;  
    public Rational(int numerator, int denominator) { ... }  
    public int getNumerator() { return numerator; } ...  
    public void setNumerator(int numerator) { ... } ...  
    public void multiplyWith(Rational that) { ... }
```

Módosíthatatlan belső állapot

```
public class Rational {  
    private final int numerator, denominator;  
    public Rational(int numerator, int denominator) { ... }  
    public int getNumerator() { return numerator; }  
    public int getDenominator() { return denominator; }  
    public Rational times(Rational that) { ... }
```

Nyilvános módosíthatatlan belső állapot

```
public class Rational {  
    public final int numerator, denominator;  
    public Rational(int numerator, int denominator) { ... }  
    public Rational times(Rational that) { ... }  
    ...  
}
```

Érzékeny a reprezentációváltoztatásra!

Reprezentációváltás

```
public class Rational {  
    private final int[] data;  
    public Rational(int numerator, int denominator) {  
        if (denominator <= 0) throw new IllegalArgumentException;  
        data = new int[]{ numerator, denominator };  
    }  
    public int numerator() { return data[0]; }  
    public int denominator() { return data[1]; }  
    public Rational times(Rational that) { ... }  
}
```

Kitérő

```
int[] t = new int[3];
```

```
t = new int[4];
```

```
int[] s = {1,2,3};
```

```
s = {1,2,3,4}; // compilation error
```

```
s = new int[]{1,2,3,4};
```

final hivatkozás

```
final Rational p = new Rational(1,2);  
p.setNumerator(3);  
p = new Rational(1,4); // compilation error
```


final hivatkozás

```
final Rational p = new Rational(1,2);  
p.setNumerator(3);  
p = new Rational(1,4); // compilation error  
  
final int[] data = new int[2];  
data[0] = 3;  
data[1] = 4;  
data = new int[3]; // compilation error
```

Karaktersorozatok ábrázolása

- `java.lang.String`: módosíthatatlan (immutable)

```
String num42 = "42";
```

```
String num24 = num42.reverse();
```

```
String num4224 = num42 + num24;
```

Karakter sorozatok ábrázolása

- `java.lang.String`: módosíthatatlan (immutable)

```
String num42 = "42";  
String num24 = num42.reverse();  
String num4224 = num42 + num24;
```

- `java.lang.StringBuilder` (és `StringBuffer`): módosítható

```
StringBuilder sb = new StringBuilder("");  
for (char c = 'a'; c <= 'z'; ++c) {  
    sb.append(c).append(',');  
}  
sb.deleteCharAt(sb.length()-1); // cut last comma  
String letters = sb.toString();
```



Karaktersorozatok ábrázolása

- `java.lang.String`: módosíthatatlan (immutable)

```
String num42 = "42";
String num24 = num42.reverse();
String num4224 = num42 + num24;
```

- `java.lang.StringBuilder` (és `StringBuffer`): módosítható

```
StringBuilder sb = new StringBuilder("");
for (char c = 'a'; c <= 'z'; ++c) {
    sb.append(c).append(',');
}
sb.deleteCharAt(sb.length()-1); // cut last comma
String letters = sb.toString();
```

- `char[]`: módosítható



Hatékonyágbeli kérdés

```
StringBuilder sb = new StringBuilder("");  
for (char c = 'a'; c <= 'z'; ++c) {  
    sb.append(c).append(',');  
}  
sb.deleteCharAt(sb.length()-1);  
String letters = sb.toString();
```

```
String letters = "";  
for (char c = 'a'; c <= 'z'; ++c) {  
    letters += (c + ",");  
}  
letters = letters.substring(0, letters.length()-1);
```

Íme egy jól kinéző osztálydefiníció...

```
package numbers;

public class Rational {
    ...
    public void multiplyWith(Rational that) {
        this.numerator *= that.numerator;
        this.denominator *= that.denominator;
    }
    public void divideBy(Rational that) {
        if (that.numerator == 0)
            throw new ArithmeticException("Division by zero!");
        this.numerator *= that.denominator;
        this.denominator *= that.numerator;
    }
}
```

És ha a paraméterek nem diszjunktak?

```
package numbers;
public class Rational {
    ...
    public void divideBy(Rational that) {
        if (that.numerator == 0)
            throw new ArithmeticException("Division by zero!");
        this.numerator *= that.denominator;
        this.denominator *= that.numerator;
    }
}
```

```
Rational p = new Rational(1,2);
p.divideBy(p);
```




Belső állapot kiszivárgása ügyetlen konstruálás miatt

```
public class Rational {
    private final int[] data;
    public int getNumerator() { return data[0]; }
    public int getDenominator() { return data[1]; }
    public Rational(int[] data) {
        if (data == null || data.length != 2 || data[1] <= 0)
            throw new IllegalArgumentException();
        this.data = data;
    }
}
```

```
int[] cheat = {3,4};
Rational p = new Rational(cheat);
cheat[1] = 0;           // p.getDenominator() == 0    :-(
```

Belső állapot kiszivárgása *getteren* keresztül

```
public class Rational {
    private final int[] data;
    ...
    public int getNumerator() { return data[0]; }
    public int getDenominator() { return data[1]; }
    public int[] get() { return data; }
}
```

```
Rational p = new Rational(1,2);
int[] cheat = p.get();
cheat[1] = 0;           // p.getDenominator() == 0    :-(
```

Defenzív másolás

```
public class Rational {  
    private final int[] data;  
    public Rational(int[] data) {  
        if (data == null || data.length != 2 || data[1] <= 0)  
            throw new IllegalArgumentException();  
        this.data = new int[]{ data[0], data[1] };  
    }  
    public void set(int[] data) { /* similarly */ }  
    public int[] get() {  
        return new int[]{ data[0], data[1] };  
    }  
}
```

Módosíthatatlan objektumokat nem kell másolni

```
public class Person {  
    private String name;  
    private int age;  
    public Person(String name, int age) {  
        if (name == null || name.trim().isEmpty() || age < 0)  
            throw new IllegalArgumentException();  
        this.name = name;  
        this.age = age;  
    }  
    public String getName() { return name; }  
    public int getAge() { return age; }  
    public void setName(String name) { ... this.name = name; }  
    public void setAge(int age) { ... this.age = age; }  
}
```

Tömbelemek között is lehet aliasing

```
Rational rats[2]; // fordítási hiba
```

```
Rational rats[] = new Rational[2]; // = {null,null};
```

```
Rational[] rats = new Rational[2]; // gyakoribb
```

```
rats[0] = new Rational(1,2);
```

```
rats[1] = rats[0];
```

```
rats[1].setDenominator(3);
```

```
System.out.println(rats[0].getDenominator());
```

- módosítható versus módosíthatatlan

Ugyanaz az objektum többször is lehet a tömbben

```
/**
 * ...
 * PRE: rats != null
 * ...
 */
public static void increaseAllByOne(Rational[] rats) {
    for (Rational r: rats) {
        r.setNumerator(r.getNumerator() + r.getDenominator());
    }
}
```

Dokumentálva

```
/**
 * ...
 * PRE: rats != null and (i!=j => rats[i] != rats[j])
 * ...
 */
public static void increaseAllByOne(Rational[] rats) {
    for (Rational r: rats) {
        r.setNumerator(r.getNumerator() + r.getDenominator());
    }
}
```

Tömbök tömbje

- Javában nincs többdimenziós tömb (sor- vagy oszlopfolytonos)
- Tömbök tömbje (referenciák tömbje)

```
int[] [] matrix = {{1,0,0},{0,1,0},{0,0,1}};
```

```
int[] [] matrix = new int[3][3];  
for (int i=0; i<matrix.length; ++i) matrix[i][i] = 1;
```

```
int[] [] matrix = new int[5][];  
for (int i=0; i<matrix.length; ++i) matrix[i] = new int[i];
```


Ismét aliasing – bug-gyanús

```
Rational[] [] matrix =  
    { {new Rational(1,2), new Rational(1,2)},  
      {new Rational(1,2), new Rational(1,2)},  
      {new Rational(1,2), new Rational(1,2)} };
```

```
Rational half = new Rational(1,2);  
Rational[] halves = {half, half};  
Rational[] [] matrix = {halves, halves, halves};
```