

Secure Computation in Online Social Networks

Presenter: Yi LIU

Secure Multiparty Computation

- Lover matching

Secure Multiparty Computation

Protocols for Secure Computations.

FOCS'82



Andrew Yao 姚期智
Turing Award (2000)

Secure Multiparty Computation

Protocols for Secure Computations.

FOCS'82

Yao's Millionaires' Problem



Andrew Yao 姚期智
Turing Award (2000)

Secure Multiparty Computation

Protocols for Secure Computations.

FOCS'82

Yao's Millionaires' Problem

For definiteness, suppose Alice has i millions and Bob has j millions, where $1 < i, j < 10$. We need a protocol for them to decide whether $i < j$, such that this is also the only thing they know in the end (aside from their own values). Let M be the set of all N -bit nonnegative integers, and Q_N be the set of all 1-1 onto functions from M to M . Let E_a be the public key of Alice, generated by choosing a random element from Q_N .

1. Bob picks a random N -bit integer, and computes privately the value of $E_a(x)$; call the result k .
2. Bob sends Alice the number $k - j + 1$;
3. Alice computes privately the values of $y_u = D_a(k - j + u)$ for $u = 1, 2, \dots, 10$.
4. Alice generates a random prime p of $N/2$ bits, and computes the values $z_u = y_u \pmod{p}$ for all u ; if all z_u differ by at least 2 in the \pmod{p} sense, stop; otherwise generates another random prime and repeat the process until all z_u differ by at least 2; let p, z_u denote this final set of numbers;
5. Alice sends the prime p and the following 10 numbers to B : z_1, z_2, \dots, z_i followed by $z_i + 1, z_{i+1} + 1, \dots, z_{10} + 1$; the above numbers should be interpreted in the \pmod{p} sense.
6. Bob looks at the j -th number (not counting p) sent from Alice, and decides that $i \geq j$ if it is equal to $x \pmod{p}$, and $i < j$ otherwise.
7. Bob tells Alice what the conclusion is.



Andrew Yao 姚期智
Turing Award (2000)

Secure Multiparty Computation

Why (mod p)?

1. Bob picks a random N -bit integer, and computes privately the value of $E_a(x)$; call the result k .
2. Bob sends Alice the number $k - j + 1$;
3. Alice computes privately the values of $y_u = D_a(k - j + u)$ for $u = 1, 2, \dots, 10$.
4. Alice generates a random prime p of $N/2$ bits, and computes the values $z_u = y_u \pmod{p}$ for all u ; if all z_u differ by at least 2 in the mod p sense, stop; otherwise generates another random prime and repeat the process until all z_u differ by at least 2; let p, z_u denote this final set of numbers;
5. Alice sends the prime p and the following 10 numbers to B : z_1, z_2, \dots, z_i followed by $z_i + 1, z_{i+1} + 1, \dots, z_{10} + 1$; the above numbers should be interpreted in the mod p sense.
6. Bob looks at the j -th number (not counting p) sent from Alice, and decides that $i \geq j$ if it is equal to $x \pmod{p}$, and $i < j$ otherwise.
7. Bob tells Alice what the conclusion is.



Andrew Yao 姚期智
Turing Award (2000)


Homomorphic Encryption

Two groups G and G' are *homomorphic* if there exists a function (*homomorphism*) $f : G \rightarrow G'$ such that for all $x, y \in G$, $f(x +_G y) = f(x) +_{G'} f(y)$.

Homomorphic Encryption

Two groups G and G' are *homomorphic* if there exists a function (*homomorphism*) $f : G \rightarrow G'$ such that for all $x, y \in G$, $f(x +_G y) = f(x) +_{G'} f(y)$.



Why do we need *homomorphic encryption*?



Homomorphic Encryption

Two groups G and G' are *homomorphic* if there exists a function (*homomorphism*) $f : G \rightarrow G'$ such that for all $x, y \in G$, $f(x +_G y) = f(x) +_{G'} f(y)$.

Why do we need *homomorphic encryption*?



Homomorphic Encryption

Recall RSA encryption

$$E(m_1) = m_1^e \bmod n, E(m_2) = m_2^e \bmod n$$

Homomorphic Encryption

Recall RSA encryption

$$E(m_1) = m_1^e \bmod n, E(m_2) = m_2^e \bmod n$$

$$E(m_1) \cdot E(m_2) = m_1^e \cdot m_2^e = (m_1 \cdot m_2)^e = E(m_1 \cdot m_2)$$

Homomorphic Encryption

Recall RSA encryption

$$E(m_1) = m_1^e \bmod n, E(m_2) = m_2^e \bmod n$$

$$E(m_1) \cdot E(m_2) = m_1^e \cdot m_2^e = (m_1 \cdot m_2)^e = E(m_1 \cdot m_2)$$

RSA is **multiplicatively homomorphic**, but **not additively homomorphic**.

Homomorphic Encryption

Recall RSA encryption

$$E(m_1) = m_1^e \bmod n, E(m_2) = m_2^e \bmod n$$

$$E(m_1) \cdot E(m_2) = m_1^e \cdot m_2^e = (m_1 \cdot m_2)^e = E(m_1 \cdot m_2)$$

RSA is **multiplicatively homomorphic**, but **not additively homomorphic**.

Paillier cryptosystem: additively homomorphic

Homomorphic Encryption

Recall RSA encryption

$$E(m_1) = m_1^e \bmod n, E(m_2) = m_2^e \bmod n$$

$$E(m_1) \cdot E(m_2) = m_1^e \cdot m_2^e = (m_1 \cdot m_2)^e = E(m_1 \cdot m_2)$$

RSA is **multiplicatively homomorphic**, but **not additively homomorphic**.

Paillier cryptosystem (*EUROCRYPT'99*): additively homomorphic

The original system: semantic security against chosen-plaintext attacks (IND-CPA)

The improved system: IND-CCA2 secure in the random oracle model

Homomorphic Encryption

We need **both**!

What people really wanted was the ability to do **arbitrary** computing on encrypted data, and this requires the ability to compute both **sums** and **products**.

Homomorphic Encryption

Why **SUM**s and **PRODUCT**s?

SUM



XOR

$$x + y \bmod 2$$

PRODUCT



AND

$$x \cdot y \bmod 2$$

Homomorphic Encryption

Why SUMs and PRODUCTs?

SUM



XOR

$$x + y \bmod 2$$

PRODUCT



AND

$$x \cdot y \bmod 2$$

{**XOR**, **AND**} is **complete**, i.e.,
any function is a combination of **XOR** and **AND**. (e.g., **OR**)

Homomorphic Encryption

Why **SUM**s and **PRODUCT**s?

SUM



XOR

$$x + y \bmod 2$$

PRODUCT



AND

$$x \cdot y \bmod 2$$

{**XOR**, **AND**} is **complete**, i.e.,
any function is a combination of **XOR** and **AND**. (e.g., **OR**)

Example

$$x \text{ OR } y = x + y + x \cdot y \bmod 2.$$

Homomorphic Encryption

Because {XOR, AND} is *complete*, if we can compute SUMs and PRODUCTs on encrypted bits, we can compute *any* function on encrypted inputs.

Homomorphic Encryption

Because {XOR, AND} is *complete*, if we can compute SUMs and PRODUCTs on encrypted bits, we can compute *any* function on encrypted inputs.

Fully-homomorphic encryption!

We can delegate *arbitrary* processing of data without giving away access to it.

Homomorphic Encryption

Because $\{\text{XOR}, \text{AND}\}$ is *complete*, if we can compute SUMs and PRODUCTs on encrypted bits, we can compute *any* function on encrypted inputs.

Fully-homomorphic encryption!

We can delegate *arbitrary* processing of data without giving away access to it.

Applications: *private cloud computing, private information retrieval, multi-party secure computation, encrypted search, ...*

Homomorphic Encryption

Fully Homomorphic Encryption Using Ideal Lattices

Craig Gentry
Stanford University and IBM Watson
cgentry@cs.stanford.edu

ABSTRACT

We propose a fully homomorphic encryption scheme – i.e., a scheme that allows one to evaluate circuits over encrypted data without being able to decrypt. Our solution comes in three steps. First, we provide a general result – that, to construct an encryption scheme that permits evaluation of *arbitrary circuits*, it suffices to construct an encryption

duced by Rivest, Adleman and Dertouzos [54] shortly after the invention of RSA by Rivest, Adleman and Shamir [55]. Basic RSA is a multiplicatively homomorphic encryption scheme – i.e., given RSA public key $pk = (N, e)$ and ciphertexts $\{\psi_i \leftarrow \pi_i^e \bmod N\}$, one can efficiently compute $\prod_i \psi_i = (\prod_i \pi_i)^e \bmod N$, a ciphertext that encrypts the product of the original plaintexts. Rivest et al. [54] asked

Fully Homomorphic Encryption over the Integers

Marten van Dijk¹, Craig Gentry², Shai Halevi², and Vinod Vaikuntanathan²

¹ MIT CSAIL

² IBM Research

Abstract. We construct a simple fully homomorphic encryption scheme, using only elementary modular arithmetic. We use Gentry's technique to construct a fully homomorphic scheme from a "bootstrappable" somewhat homomorphic scheme. However, instead of using ideal lattices over a



Craig Gentry

STOC'09

EUROCRYPT'10

Server-Aided Secure Computation with Off-line Parties

- ESORICS'17

Server-Aided Secure Computation with Off-line Parties

- ESORICS'17
- Extend version: *Secure Computation in Online Social Networks*


Server-Aided Secure Computation with Off-line Parties

- Foteini Baldimtsi¹, Dimitrios Papadopoulos, Stavros Papadopoulos, Alessandra Scafuro, and Nikos Triandopoulos
- ESORICS'17
- Extend version: *Secure Computation in Online Social Networks*
- Contribution
 - First MPC model that is specifically tailored for secure computation in the OSN setting (efficiency, friend non-participation and data re-usability)
 - Two very well-studied techniques from secure two-party computation (garbled circuits and mixed protocols) can be adapted for use in this setting
 - Implementation and experimental evaluation


Assumption

- No collusion between server and users!

Garbled circuit



Garbled circuit



How to obtain

w_{S*}^*

Protocol

1. **Join** $\langle U_i(1^\lambda), S(\mathcal{G}) \rangle$: On input 1^λ , U_i randomly chooses a PRF key $K_i \in \{0, 1\}^\lambda$, and sends her public-key pk_i to S . S adds v_i initialized with value pk_i into \mathcal{V} of \mathcal{G} .
2. **Connect** $\langle U_i(K_i), U_j(K_j) \rangle$: U_i receives the public key pk_j of U_j from S . Sets $k_{i \rightarrow j}$ to $E'(pk_j, K_i)$ and sends it to S . U_j computes and sends $k_{j \rightarrow i}$ to S who then creates edge e_{ij} storing $k_{i \rightarrow j}$, $k_{j \rightarrow i}$, and adds it to \mathcal{E} of \mathcal{G} .
3. **Upload** $\langle U_i(K_i, x_i), S(\mathcal{G}) \rangle$: U_i chooses nonce r_i , computes value $X_{il}^{x_i[l]}$ as $F_{K_i}(x_i[l], l, r_i) \forall l \in [\ell]$, and sends them to S who stores the value $c_i = ((X_{i1}^{x_i[1]}, \dots, X_{i\ell}^{x_i[\ell]}), r_i)$ in v_i .
4. **Query** $\langle U_q(K_q, \alpha), S(\mathcal{G}) \rangle(f)$: U_q does the following:
 - (a) **Key and nonce retrieval.** For each $U_j \in \mathcal{G}_q$, retrieve key $k_{j \rightarrow q}$ and (latest) nonce r_j from S , and decrypt $k_{j \rightarrow q}$ to get K_j .
 - (b) **Garbled circuit computation.** U_q transforms f into a circuit, and garbles it as GC .
 - (c) **Selection table generation.** For each user U_j in \mathcal{G}_q and index $l \in [\ell]$:
Compute selection keys: Generate $s_{jl}^0 = F_{K_j}(0, l, r_j)$, $s_{jl}^1 = F_{K_j}(1, l, r_j)$.
Compute garbled inputs: Produce encryptions $E_{s_{jl}^0}(w_{jl}^0)$ and $E_{s_{jl}^1}(w_{jl}^1)$ with the selection keys.
Set selection table entry: Store $E_{s_{jl}^0}(w_{jl}^0)$ and $E_{s_{jl}^1}(w_{jl}^1)$ into $T_q[j, l]$ in a random order.
 - (d) **Circuit transmission.** Send GC, T_q to S .
 S then decrypts the garbled values of each $U_j \in \mathcal{G}_q$ from T_q , with the encoding $X_{jl}^{x_j[l]}$ for each $l \in [\ell]$. He evaluates GC and sends output to U_q who obtains the result y by decoding the circuit output.

Protocol

1. $\text{Join}\langle U_i(1^\lambda), S(\mathcal{G}) \rangle$: On input 1^λ , U_i randomly chooses a PRF key $K_i \in \{0, 1\}^\lambda$, and sends her public-key pk_i to S . S adds v_i initialized with value pk_i into \mathcal{V} of \mathcal{G} .

Protocol

2. Connect $\langle U_i(K_i), U_j(K_j) \rangle$: U_i receives the public key pk_j of U_j from S . Sets $k_{i \rightarrow j}$ to $E'(pk_j, K_i)$ and sends it to S . U_j computes and sends $k_{j \rightarrow i}$ to S who then creates edge e_{ij} storing $k_{i \rightarrow j}$, $k_{j \rightarrow i}$, and adds it to \mathcal{E} of \mathcal{G} .

Protocol

3. Upload $\langle U_i(K_i, x_i), S(\mathcal{G}) \rangle$: U_i chooses nonce r_i , computes value $X_{il}^{x_i[l]}$ as $F_{K_i}(x_i[l], l, r_i) \forall l \in [\ell]$, and sends them to S who stores the value $c_i = ((X_{i1}^{x_i[1]}, \dots, X_{i\ell}^{x_i[\ell]}), r_i)$ in v_i .


Protocol

3. Upload $\langle U_i(K_i, x_i), S(\mathcal{G}) \rangle$: U_i chooses nonce r_i , computes value $X_{il}^{x_i[l]}$ as $F_{K_i}(x_i[l], l, r_i) \forall l \in [\ell]$, and sends them to S who stores the value $c_i = ((X_{i1}^{x_i[1]}, \dots, X_{i\ell}^{x_i[\ell]}), r_i)$ in v_i .

$$F_{K_a}(x_1, 1, r)$$

Protocol


$$F_{K_a}(x_1, 1, r)$$



Protocol

How to obtain $w_{S^*}^*$ without learning x_1

$$F_{K_a}(x_1, 1, r)$$



Protocol

4. Query $\langle U_q(K_q, \alpha), S(\mathcal{G}) \rangle(f)$: U_q does the following:
 - (a) **Key and nonce retrieval.** For each $U_j \in \mathcal{G}_q$, retrieve key $k_{j \rightarrow q}$ and (latest) nonce r_j from S , and decrypt $k_{j \rightarrow q}$ to get K_j .
 - (b) **Garbled circuit computation.** U_q transforms f into a circuit, and garbles it as GC .
 - (c) **Selection table generation.** For each user U_j in \mathcal{G}_q and index $l \in [\ell]$:
Compute selection keys: Generate $s_{jl}^0 = F_{K_j}(0, l, r_j)$, $s_{jl}^1 = F_{K_j}(1, l, r_j)$.
Compute garbled inputs: Produce encryptions $E_{s_{jl}^0}(w_{jl}^0)$ and $E_{s_{jl}^1}(w_{jl}^1)$ with the selection keys.
Set selection table entry: Store $E_{s_{jl}^0}(w_{jl}^0)$ and $E_{s_{jl}^1}(w_{jl}^1)$ into $T_q[j, l]$ in a random order.
 - (d) **Circuit transmission.** Send GC, T_q to S .
 S then decrypts the garbled values of each $U_j \in \mathcal{G}_q$ from T_q , with the encoding $X_{jl}^{x_j[l]}$ for each $l \in [\ell]$. He evaluates GC and sends output to U_q who Obtains the result y by decoding the circuit output.

Protocol

4. $\text{Query}\langle U_q(K_q, \tilde{\alpha}), S(\mathcal{G}) \rangle(f)$: U_q does the following:
 - (a) **Key and nonce retrieval.** For each $U_j \in \mathcal{G}_q$, retrieve key $k_{j \rightarrow q}$ and (latest) nonce r_j from S , and decrypt $k_{j \rightarrow q}$ to get K_j .

Protocol

4. Query $\langle U_q(K_q, \tilde{\alpha}), S(\mathcal{G}) \rangle(f)$: U_q does the following:
- (a) **Key and nonce retrieval.** For each $U_j \in \mathcal{G}_q$, retrieve key $k_{j \rightarrow q}$ and (latest) nonce r_j from S , and decrypt $k_{j \rightarrow q}$ to get K_j .

Get

K_a

r

Protocol

- (b) **Garbled circuit computation.** U_q transforms f into a circuit, and garbles it as GC .
- (c) **Selection table generation.** For each user U_j in \mathcal{G}_q and index $l \in [\ell]$:
 - Compute selection keys:* Generate $s_{jl}^0 = F_{K_j}(0, l, r_j)$, $s_{jl}^1 = F_{K_j}(1, l, r_j)$.
 - Compute garbled inputs:* Produce encryptions $E_{s_{jl}^0}(w_{jl}^0)$ and $E_{s_{jl}^1}(w_{jl}^1)$ with the selection keys.
 - Set selection table entry:* Store $E_{s_{jl}^0}(w_{jl}^0)$ and $E_{s_{jl}^1}(w_{jl}^1)$ into $T_q[j, l]$ in a random order.

Protocol

- (b) **Garbled circuit computation.** U_q transforms f into a circuit, and garbles it as GC .
- (c) **Selection table generation.** For each user U_j in \mathcal{G}_q and index $l \in [\ell]$:
 - Compute selection keys:* Generate $s_{jl}^0 = F_{K_j}(0, l, r_j)$, $s_{jl}^1 = F_{K_j}(1, l, r_j)$.
 - Compute garbled inputs:* Produce encryptions $E_{s_{jl}^0}(w_{jl}^0)$ and $E_{s_{jl}^1}(w_{jl}^1)$ with the selection keys.
 - Set selection table entry:* Store $E_{s_{jl}^0}(w_{jl}^0)$ and $E_{s_{jl}^1}(w_{jl}^1)$ into $T_q[j, l]$ in a random order.

$$F_{K_a}(x_1, 1, r)$$

$$K_a$$

r

Protocol

- (b) **Garbled circuit computation.** U_q transforms f into a circuit, and garbles it as GC .
- (c) **Selection table generation.** For each user U_j in \mathcal{G}_q and index $l \in [\ell]$:
 - Compute selection keys:* Generate $s_{jl}^0 = F_{K_j}(0, l, r_j)$, $s_{jl}^1 = F_{K_j}(1, l, r_j)$.
 - Compute garbled inputs:* Produce encryptions $E_{s_{jl}^0}(w_{jl}^0)$ and $E_{s_{jl}^1}(w_{jl}^1)$ with the selection keys.
 - Set selection table entry:* Store $E_{s_{jl}^0}(w_{jl}^0)$ and $E_{s_{jl}^1}(w_{jl}^1)$ into $T_q[j, l]$ in a random order.

$$F_{K_a}(x_1, 1, r)$$


$$K_a$$

$$s^0 = F_{K_a}(0, 1, r)$$

$$s^1 = F_{K_a}(1, 1, r)$$

r

Protocol



$$F_{K_a}(x_1, 1, r)$$

$$K_a$$

$$s^0 = F_{K_a}(0, 1, r)$$

$$s^1 = F_{K_a}(1, 1, r)$$

r

Protocol

- (b) **Garbled circuit computation.** U_q transforms f into a circuit, and garbles it as GC .
- (c) **Selection table generation.** For each user U_j in \mathcal{G}_q and index $l \in [\ell]$:
 - Compute selection keys:* Generate $s_{jl}^0 = F_{K_j}(0, l, r_j)$, $s_{jl}^1 = F_{K_j}(1, l, r_j)$.
 - Compute garbled inputs:* Produce encryptions $E_{s_{jl}^0}(w_{jl}^0)$ and $E_{s_{jl}^1}(w_{jl}^1)$ with the selection keys.
 - Set selection table entry:* Store $E_{s_{jl}^0}(w_{jl}^0)$ and $E_{s_{jl}^1}(w_{jl}^1)$ into $T_q[j, l]$ in a random order.

$$F_{K_a}(x_1, 1, r)$$


$$K_a$$

$$s^0 = F_{K_a}(0, 1, r)$$

$$s^1 = F_{K_a}(1, 1, r)$$

r

Protocol



$$w^0, w^1$$

$$F_{K_a}(x_1, 1, r)$$


$$K_a$$

$$s^0 = F_{K_a}(0, 1, r)$$

$$s^1 = F_{K_a}(1, 1, r)$$

r

Protocol



$$w^0, w^1$$

$$E_{s^0}(w^0), E_{s^1}(w^1)$$

$$F_{K_a}(x_1, 1, r)$$

$$K_a$$

$$s^0 = F_{K_a}(0, 1, r)$$


$$s^1 = F_{K_a}(1, 1, r)$$

r


Protocol

4. Query $\langle U_q(K_q, \alpha), S(\mathcal{G}) \rangle(f)$: U_q does the following:
 - (a) **Key and nonce retrieval.** For each $U_j \in \mathcal{G}_q$, retrieve key $k_{j \rightarrow q}$ and (latest) nonce r_j from S , and decrypt $k_{j \rightarrow q}$ to get K_j .
 - (b) **Garbled circuit computation.** U_q transforms f into a circuit, and garbles it as GC .
 - (c) **Selection table generation.** For each user U_j in \mathcal{G}_q and index $l \in [\ell]$:
Compute selection keys: Generate $s_{jl}^0 = F_{K_j}(0, l, r_j)$, $s_{jl}^1 = F_{K_j}(1, l, r_j)$.
Compute garbled inputs: Produce encryptions $E_{s_{jl}^0}(w_{jl}^0)$ and $E_{s_{jl}^1}(w_{jl}^1)$ with the selection keys.
Set selection table entry: Store $E_{s_{jl}^0}(w_{jl}^0)$ and $E_{s_{jl}^1}(w_{jl}^1)$ into $T_q[j, l]$ in a random order.
 - (d) **Circuit transmission.** Send GC, T_q to S .
 S then decrypts the garbled values of each $U_j \in \mathcal{G}_q$ from T_q , with the encoding $X_{jl}^{x_j[l]}$ for each $l \in [\ell]$. He evaluates GC and sends output to U_q who Obtains the result y by decoding the circuit output.


Protocol



Protocol



Mixed Protocol



Mixed Protocol

- How do server obtain $[[x_a]]$ while preserving the original value?

Mixed Protocol

- How do server obtain $[[x_a]]$ while preserving the original value?

We need **Re-Encryption Protocol!**

Re-Encryption Protocol

1. **Join** $\langle U_i(1^\lambda), S(\mathcal{G}) \rangle$: On input the security parameter λ , U_i generates a PRF key K_i , and notifies S that she joins the system by sending pk_i . S adds node v_i (initialized with pk_i) to graph \mathcal{G} .
2. **Connect** $\langle U_i(K_i), U_j(K_j), S(\mathcal{G}) \rangle$: Users U_i and U_j , having each other public keys, compute $k_{j \rightarrow i} = \llbracket K_j \rrbracket_{pk_i}$, $k_{i \rightarrow j} = \llbracket K_i \rrbracket_{pk_j}$ respectively, and send them to S . Then, S creates an edge e_{ij} in \mathcal{G} storing the two values.

Re-Encryption Protocol

3. Upload $\langle U_i(K_i, x_i), S(\mathcal{G}) \rangle$: User U_i picks random nonce r_i , computes $\rho_i = F_{K_i}(r_i)$, and sends $c_i = (x_i + \rho_i, r_i)$ to S , who stores it into $v_i \in \mathcal{G}$.
4. Query $\langle U_q(K_q, \alpha), S(\mathcal{G}) \rangle(f)$: User U_q and S run π_{RE} , where U_q has as input K_q and S has \mathcal{G} . Recall that \mathcal{G} contains c_j and $k_{j \rightarrow q}$ for every friend U_j of U_q . The server receives as output $\llbracket x_j \rrbracket_{pk_q}$, where x_j is the private input of a friend U_j . Subsequently, S and U_q execute π_f , where S uses as input the ciphertexts $\llbracket x_j \rrbracket_{pk_q}$, along with $\llbracket \alpha \rrbracket_{pk_q}$ which is provided by the querier. At the end of this protocol, U_q learns $y = f(\alpha, x_q, \{x_j \mid \forall j : U_j \in \mathcal{G}_q\})$.


Re-Encryption Protocol

3. Upload $\langle U_i(K_i, x_i), S(\mathcal{G}) \rangle$: User U_i picks random nonce r_i , computes $\rho_i = F_{K_i}(r_i)$, and sends $c_i = (x_i + \rho_i, r_i)$ to S , who stores it into $v_i \in \mathcal{G}$.

Re-Encryption Protocol

$$\rho_i = F_{K_i}(r_i)$$

$$c_i = (x_i + \rho_i, r_i)$$



Acknowledgement

- Some materials are extracted from the slides created by Prof. Qi WANG in the course Cryptography and Network Security