

范围判定

1. 知识图谱构建

system:

You are a helpful assistant. You can help me by answering my questions.

user:

这是我刚才跟你谈论记录，请你先了解我们的任务

assistant:

好的，我已经仔细阅读了您提供的这份名为“改进建议.md”的文档。

根据文档内容，我理解我们当前的任务是围绕**构建一个关于特定管理规定（以《广铁集团动车组

具体来说，这个任务包含以下几个核心方面：

- 目标文档分析与知识图谱设计**：
 - 分析类似“广铁集团动车组列车票价管理实施细则”这样的规章制度文档。
 - 设计并优化知识图谱的模式（Schema），包括定义更精确、更全面的**实体类型**（如
- 信息抽取方法**：
 - 利用强大的**大型语言模型（LLM）**，结合文档已有的良好结构（章、节、条），从
 - 探讨并确定具体的技术实施细节，包括：
 - 文本分块策略**：如何将长文档切分成适合LLM处理的小块（建议按“节”或“条”
 - 提示词（Prompt）设计**：如何编写清晰、有效的指令来引导LLM准确地抽取
 - 结果审核机制**：如何设计自动（如一致性、格式、逻辑校验）和半自动（如抽
- 知识图谱的应用目标**：
 - 最终构建的知识图谱旨在提高对管理规定信息的**检索效率**，增强**信息完整性**，
 - 关注组织层级、文档制定与执行单位、文档结构与内容细节（主题、事件、人物、单位）

总而言之，我们的任务是**设计一个优化的知识图谱模型来表示管理规定文档中的复杂信息，并探

我的理解是否准确？接下来您希望我们聚焦于哪个具体环节进行讨论或操作呢？

user:

现在我给你一份对markdown格式的管理文件的解析结果（json）格式，请你先理解这个json文档

assistant:

好的，我已经加载并查看了您提供的 ``demo3.json`` 文件。

这是一个 JSON 数组，其中每个元素（对象）代表从一个 Markdown 文件（``tests/demo3.md``）

根据其结构和字段，我理解这个 JSON 文件主要包含以下信息：

- **分块 (Chunking) **:**
 - * 原始的 Markdown 文档被分割成了多个块 (chunks)。
 - * 每个块由一个 JSON 对象表示。
- **块内容与元数据**:**
 - * ``content``: 每个块包含其对应的文本内容。值得注意的是，内容似乎包含了从根节点
 - * ``heading``: 明确提取了该块对应的 Markdown 标题。
 - * ``tokens``: 该块内容的 token 数量（可能是用于衡量文本长度或 LLM 处理成本）。
 - * ``file_path``: 指向原始 Markdown 文件的路径。
 - * ``full_doc_id``: 整个文档的唯一标识符。
 - * ``page_numbers``: 包含一个数组，指示该块内容在原始文档（可能是 PDF 转换而来
- **层级结构 (Hierarchy) **:**
 - * ``chunk_id``: 每个块的唯一标识符。
 - * ``parent_id``: 指向其父块的 ``chunk_id``。根块的 ``parent_id`` 为 ``null``。
 - * ``child_ids``: 包含一个数组，列出了直接属于该块的子块的 ``chunk_id``。叶子节
 - * ``chunk_order_index``: 块在其父块下的顺序索引。
 - * 这种父子关系 (``parent_id``, ``child_ids``) 清晰地表达了原始 Markdown 文档
- **文档内容概要**:**
 - * 从 ``heading`` 和 ``content`` 字段的内容来看，这份 JSON 解析的是一份名为《广
 - * 文件包含了总则、组织管理、监测预警、应急处置、恢复重建、调查评估、应急保障、附
 - * 内容详细规定了票务系统突发事件的分类、预警级别、组织职责、响应流程、处置措施等

****总结**:** 这份 JSON 文件是对一份结构化的应急预案 Markdown 文档进行层级化分块后的结果

我的理解是否准确？您可以基于这份解析结果提出下一步的要求了。

user:

现在你用python写一个从这个json文件中提取知识图谱实体和实体关系的程序：

- 1、提取实体和实体关系建模和方法已经在之前我给你的改进建议.md里；
 - 2、用LLM进行实体和实体关系提取；
- 请你先理解我的要求，提出你的思路，我们讨论后再开始具体写出程序

assistant:

好的，我理解您的要求。

您希望我基于以下条件，为您编写一个 Python 程序，用于从 `demo3.json` 文件中提取知识

1. ****输入数据****: `demo3.json` 文件，它包含了从 Markdown 管理文件解析出的、带有层
2. ****知识图谱模式 (Schema)****: 实体和关系的类型已经在您之前提供的 `改进建议.md` 文
3. ****提取方法****: 利用大型语言模型 (LLM) 进行实体和关系的抽取。
4. ****输出****: 提取出的实体和关系列表。
5. ****当前步骤****: 在编写具体代码之前，先提出我的思路，供您审阅和讨论。

****我的思路如下:****

1. ****环境准备与配置****:
 - * 需要安装必要的 Python 库: `json` (内置库, 用于加载 JSON 文件), 以及一个用
 - * 配置 LLM API 密钥: 通常通过环境变量或配置文件安全地管理 API 密钥。
 - * 定义知识图谱模式: 在代码中明确定义 `改进建议.md` 中确定的实体类型列表和关系类
2. ****数据加载****:
 - * 编写函数读取 `demo3.json` 文件, 将其内容加载为一个 Python 列表 (其中每个元
3. ****选择处理单元 (Chunk Selection)****:
 - * 遍历 JSON 文件中的每一个 chunk 对象。
 - * ****策略****: 初步考虑处理****每一个**** chunk。因为 `demo3.json` 中的 `content`
4. ****构建 LLM 提示词 (Prompt Engineering)****:
 - * 根据 `改进建议.md` 中的指导, 设计两个核心的提示词模板:
 - * ****实体提取提示词****:
 - * 输入: 单个 chunk 的 `content` 文本。
 - * 指令: 要求 LLM 从文本中识别并抽取出所有预定义的实体类型 (文档、章节
 - * 附加信息: 在提示词中包含每种实体类型的简要定义或示例, 以提高准确性。
 - * 输出格式: 明确要求 LLM 以 JSON 格式输出, 例如 `{"entities": [{
 - * ****关系提取提示词****:
 - * 输入: 单个 chunk 的 `content` 文本。 (*或者, 为了更好地捕捉关系,
 - * 指令: 要求 LLM 从文本中识别并抽取出所有预定义的关系类型 (隶属、版本
 - * 附加信息: 在提示词中包含每种关系类型的简要定义或示例。
 - * 输出格式: 明确要求 LLM 以 JSON 格式输出, 例如 `{"relations": [
 - * 将 chunk 的 `content` 填入提示词模板, 生成最终发送给 LLM 的具体指令。
5. ****LLM API 调用与结果解析****:
 - * 编写一个函数, 负责调用配置好的 LLM API。该函数接收生成的提示词作为输入。
 - * 发送请求并获取 LLM 的响应。
 - * 处理 API 可能返回的错误 (如超时、速率限制、认证失败等)。
 - * 解析 LLM 返回的 JSON 字符串。需要健壮地处理可能出现的 JSON 解析错误 (例如
 - * 从解析后的 Python 对象中提取出实体列表和关系列表。
6. ****结果聚合与去重****:

- * 初始化两个集合 (Set)：一个用于存储所有提取到的实体 (元组形式, 例如 `(name, ...)`)
- * 在处理完每个 chunk 后, 将从 LLM 获取并解析出的实体和关系添加到相应的集合中。

7. **输出**:

- * 处理完所有 chunk 后, 将集合中的实体和关系转换回列表或字典的格式, 方便查看或进一步处理。
- * 打印或保存最终提取到的、去重后的实体和关系列表。

8. **代码结构**:

- * 主函数/脚本: 协调整个流程 (加载数据 -> 遍历 chunk -> 调用提取 -> 聚合结果)
- * LLM 调用模块/函数: 封装与 LLM API 的交互。
- * 提示词生成模块/函数: 根据 chunk 内容和模式生成具体的提示词。
- * 配置文件 (可选): 存储 API 密钥、模型名称等。

待讨论/确认的点:

- * **LLM 选择**: 您计划使用哪个具体的 LLM 服务或模型? 不同的模型可能在遵循指令、输出格式等方面存在差异。
- * **API 密钥管理**: 确认 API 密钥的安全存储方式。
- * **性能与成本**: `demo3.json` 文件包含 61 个 chunk。对每个 chunk 分别调用 LLM 可能会带来较高的成本。
- * **错误处理**: 对于 LLM 返回无效 JSON 或提取结果不符合预期的情况, 需要定义处理策略 (如重试、跳过等)。
- * **关系提取的上下文**: 仅使用单个 chunk 的 `content` 提取关系可能无法捕捉跨 chunk 的复杂关系。
- * **实体/关系规范化**: LLM 提取的实体名称可能存在细微差异 (如“集团公司客运部” vs “客运部”)。

请您审阅以上思路, 特别是待讨论的点。如果您觉得方向正确, 或者有任何修改意见, 请告诉我, 谢谢!

user:

你提出下面的两点非常有意义, 请你考虑进去

- 1、关系提取的上下文: 仅使用单个 chunk 的 content 提取关系可能无法捕捉跨 chunk 的复杂关系。
- 2、实体/关系规范化: LLM 提取的实体名称可能存在细微差异 (如“集团公司客运部” vs “客运部”)

assistant:

好的, 这确实是两个非常关键的点, 直接关系到知识图谱的完整性和准确性。我们来把这两点考虑进去。

Refined 思路:

1. **环境准备与配置** (同前)

- * 安装所需库 (`json`, LLM 库)。
- * 配置 LLM API 密钥。
- * 定义知识图谱模式 (实体类型、关系类型)。
- * **新增**: 定义一个简单的**实体名称规范化映射表 (Canonical Map)**，例如：

```
CANONICAL_MAP = {
    "客运部": "集团公司客运部",
    "信息技术所": "集团公司信息技术所", # 假设需要统一
```

```

        "广铁集团": "中国铁路广州局集团有限公司",
        "集团公司": "中国铁路广州局集团有限公司", # 根据上下文判断是否合适
        "本预案": "《广州局集团公司客票发售和预订系统（含互联网售票部分）应急预案》",
        # ... 更多可能的别名、简称 -> 规范名
    }

```

2. ****数据加载****: (同前)

```
* 读取 `demo3.json`。
```

3. ****处理单元选择与上下文增强****:

```

* 遍历 JSON 文件中的每一个 chunk 对象。
* **策略**: 仍然以单个 chunk 作为 LLM 处理的基本单元。
* **上下文增强**: 虽然 `content` 字段包含了标题路径，这有助于理解当前 chunk
    * **阶段一 (LLM 抽取)**: LLM 专注于从**当前 chunk 的 `content` 文本中抽取信息。
    * **阶段二 (结构化抽取)**: 在 LLM 处理完所有 chunk 后，利用 `demo3.json` 中的标题路径进行结构化抽取。

```

4. ****构建 LLM 提示词****: (基本同前)

```

* **实体提取提示词**: 保持不变，要求提取预定义实体并以 JSON 输出。包含类型定义。
* **关系提取提示词**: 明确指示 LLM **仅提取在所提供的文本段落内能直接找到依据的信息**。

```

5. ****LLM API 调用与结果解析****: (同前)

```
* 调用 LLM API，处理错误，解析返回的 JSON。
```

6. ****结果聚合、规范化与去重****: (****重点改进****)

```

* 初始化三个集合: `entities_set` (存储规范化后的 `(name, type)` 元组), `normalized_entities` (存储规范化后的实体信息), `normalized_relations` (存储规范化后的关系信息)。
* **定义规范化函数**:

```

```

def normalize_entity_name(raw_name):
    cleaned_name = raw_name.strip() # 去除首尾空格
    # 查找映射表，如果找到则返回规范名，否则返回清理后的原始名
    return CANONICAL_MAP.get(cleaned_name, cleaned_name)

```

```

* **处理 LLM 结果**:
* 对于从 LLM 提取的每个实体 `(raw_name, type)``:
    * `normalized_name = normalize_entity_name(raw_name)`
    * 将 `(normalized_name, type)` 添加到 `entities_set`。
    * 将规范化后的实体信息存入 `chunk_entities[current_chunk_id]`。
* 对于从 LLM 提取的每个关系 `(raw_source, raw_target, type)``:
    * `normalized_source = normalize_entity_name(raw_source)`
    * `normalized_target = normalize_entity_name(raw_target)`
    * 将 `(normalized_source, normalized_target, type)` 添加到 `normalized_relations`。

```

7. ****添加结构化关系 (BelongsTo) ****: (****新增步骤****)

```

* 在所有 chunk 都经过 LLM 处理后，再次遍历 `demo3.json` 数据。
* 对于每一个 chunk `C`:
    * 获取其 `chunk_id` 和 `parent_id`。
    * 如果 `parent_id` 不为 `null`:

```

```

* 获取当前 chunk `C` 的规范化实体名称（可能需要从 `C['heading']` 规范
* 获取父 chunk `P` 的规范化实体名称（同理，从 `P['heading']` 规范
* **如果能成功找到代表这两个 chunk 的实体名称**（例如，`child_entity`
* *注意：* 此处需要仔细处理如何准确识别代表 chunk 本身的实体。一个简

8. **输出**：(同前)
* 将 `entities_set` 和 `relations_set` 中的内容转换为列表或字典格式进行输出

**改进后的优势：**

* **关系上下文**：通过结合 LLM 抽取（处理文本内关系）和结构化抽取（处理层级关系），
* **实体规范化**：通过引入简单的规范化步骤，减少了因名称不一致导致的数据冗余和后续处理

**待确认/进一步细化：**

* **规范化映射表 `CANONICAL_MAP` 的构建**：这个表需要根据文档内容和常见缩写预先定义
* **结构化关系中实体的识别**：在步骤 7 中，如何精确地将 chunk ID 映射到其代表的实体
* **LLM 能力**：即使有规范化，LLM 提取的实体名可能仍有预期外的变化。规范化映射表需要

这个细化后的思路解决了您提出的两个关键问题，使得程序的目标更加清晰和健壮。如果您同意这个

```

user:

可以开始构思具体的 Python 代码实现了

assistant:

```

Okay, let's start building the Python code based on our refined思路.

I'll structure the code with clear functions for each step: loading data, processing, and output.

**Assumptions:**

1. You have a Python environment (>= 3.7 for type hints).
2. You will replace the placeholder `call_llm` function with your actual LLM integration.
3. You have the `demo3.json` file in the same directory or provide the correct path.
4. You'll set the `LLM_API_KEY` environment variable or modify the code to use a different API key.

import json
import os
import logging
import time # For potential rate limiting
from typing import List, Dict, Set, Tuple, Optional, Any

# --- Configuration ---

```

```

# 1. LLM Configuration
# !! IMPORTANT: Replace with your actual LLM provider's method !!
# Example for OpenAI (requires `pip install openai`)
# from openai import OpenAI
# client = OpenAI(api_key=os.environ.get("OPENAI_API_KEY"))
# LLM_MODEL = "gpt-3.5-turbo" # Or your preferred model

# For this example, we use a placeholder
LLM_API_KEY = os.environ.get("YOUR_LLM_API_KEY") # Replace YOUR_LLM_API_KEY
LLM_MODEL = "your-chosen-llm-model" # Replace with your model identifier

# 2. File Path
INPUT_JSON_PATH = "demo3.json"

# 3. Knowledge Graph Schema (Based on 改进建议.md)
ENTITY_TYPES = [
    "文档", "章节", "主题", "关键词", "人员", "角色",
    "组织", "时间", "事件", "法规"
]

RELATION_TYPES = [
    "隶属关系", "版本关系", "引用", "依据", "责任",
    "审批", "时间", "生效", "关联"
]

# 4. Entity Normalization Map (Example - expand as needed)
CANONICAL_MAP = {
    "客运部": "集团公司客运部",
    "信息技术所": "集团公司信息技术所",
    "科信部": "集团公司科信部",
    "财务部": "集团公司财务部",
    "计统部": "集团公司计统部",
    "电务部": "集团公司电务部",
    "供电部": "集团公司供电部",
    "宣传部": "集团公司宣传部",
    "调度所": "集团公司调度所",
    "集团公司应急领导小组办公室": "集团公司应急领导小组办公室", # Already specific
    "集团公司应急领导小组": "集团公司应急领导小组", # Already specific
    "国铁集团应急领导小组办公室": "国铁集团应急领导小组办公室",
    "国铁集团应急领导小组": "国铁集团应急领导小组",
    "国铁集团客运部": "国铁集团客运部",
    "12306科创中心": "12306科创中心",
    "广铁集团": "中国铁路广州局集团有限公司",
    "集团公司": "中国铁路广州局集团有限公司", # Be careful with context, might
    "本预案": "《广州局集团公司客票发售和预订系统（含互联网售票部分）应急预案》", #
    "《铁路客票发售和预订系统（含互联网售票部分）应急预案》": "《铁路客票发售和预订系统
    "《广州局集团公司网络安全事件应急预案》": "《广州局集团公司网络安全事件应急预案》
    "《广州局集团公司信息系统故障应急处置和调查处理办法》": "《广州局集团公司信息系统

```

```

    "客票系统": "客票发售和预订系统", # Normalize system name
    # Add station names if needed, e.g., "广州站": "广州站"
}

# 5. Logging Configuration
logging.basicConfig(level=logging.INFO, format='%(asctime)s - %(levelname)s - %(message)s')

# --- Helper Functions ---

def load_json_data(file_path: str) -> Optional[List[Dict[str, Any]]]:
    """Loads data from a JSON file."""
    try:
        with open(file_path, 'r', encoding='utf-8') as f:
            data = json.load(f)
            logging.info(f"Successfully loaded data from {file_path}")
            return data
    except FileNotFoundError:
        logging.error(f"Error: Input file not found at {file_path}")
        return None
    except json.JSONDecodeError:
        logging.error(f"Error: Could not decode JSON from {file_path}")
        return None

def normalize_entity_name(raw_name: str) -> str:
    """Normalizes entity names using the CANONICAL_MAP."""
    if not isinstance(raw_name, str):
        logging.warning(f"Attempted to normalize non-string value: {raw_name}")
        return str(raw_name) # Attempt to convert to string if not already
    cleaned_name = raw_name.strip().replace('\n', ' ') # Clean whitespace
    # Simple lookup, case-sensitive for now
    return CANONICAL_MAP.get(cleaned_name, cleaned_name)

def create_entity_prompt(chunk_content: str) -> str:
    """Creates the prompt for entity extraction."""
    # Provide definitions to help the LLM
    definitions = """
    实体类型定义：
    - 文档：管理规定的文件名称，如《应急预案》。
    - 章节：文档中的具体章节标题，如“1 总则”。
    - 主题：文档或章节的核心议题，如“应急组织机构”。
    - 关键词：文本中重要的名词或术语，如“客票系统”、“应急响应”、“电子客票”。
    - 人员：具体的人名（此文档中可能较少）。
    - 角色：指代具有特定职责的职位或岗位，如“客运部主任”、“售票员”。
    - 组织：涉及的单位、部门或公司，如“中国铁路广州局集团有限公司”、“集团公司客运部”、
    - 时间：具体的日期、时间点或时间段，如“2021年”、“4小时及以上”、“每年3月”。
    - 事件：文档中描述的具体活动或状况，如“系统突发事件”、“启动应急预案”、“应急演练”。
    - 法规：引用的其他法规或文件名称及其编号，如“《铁路客票发售和预订系统(含互联网售票系统)管理办法》”。
    """

```



```

    prompt = f"""
请从以下文本中提取定义的实体类型。

{definitions}

预定义的实体类型列表: {' , '.join(ENTITY_TYPES)}

文本:
\"\"\"
{chunk_content}
\"\"\"

请以严格的 JSON 格式输出, 包含一个名为 "entities" 的列表, 其中每个对象包含 "name"
例如:
{{
  "entities": [
    {{ "name": "集团公司客运部", "type": "组织" }},
    {{ "name": "售票故障", "type": "事件" }},
    {{ "name": "《铁路客票发售和预订系统(含互联网售票部分)应急预案》(铁办客〔2021〕"
  ]
}}
"""

    return prompt

def create_relation_prompt(chunk_content: str) -> str:
    """Creates the prompt for relation extraction (within the chunk)."""
    # Provide definitions
    definitions = """
关系类型定义 (请仅提取文本段落内明确描述的关系):
- 隶属关系 (BelongsTo): 通常是结构化的, 此提示词主要关注文本内描述, 如“办公室设
- 版本关系 (HasVersion): 指明文档的版本信息或与其他版本的关系 (如“修订版”、“废
- 引用 (References): 一个实体提到了另一个实体或文件, 如“详见附件5”。
- 依据 (BasedOn): 指出制定某文件或采取某行动所依据的法规或原则, 如“根据...制定
- 责任 (ResponsibleFor): 指明某个角色或组织负责某项任务或职责, 如“客运部负责协
- 审批 (ApprovedBy): 指出某事项需要经过哪个组织或角色批准, 如“经...同意后”。
- 时间 (OccursAt): 事件发生的时间, 或规定适用的时间点/段, 如“事件影响4小时”、“
- 生效 (EffectiveFrom): 规定或文件的生效日期, 如“自发布之日起实施”。
- 关联 (RelatedTo): 实体间的其他关联, 如“与...不一致时, 以此为准”。
"""

    prompt = f"""
请从以下文本中提取实体之间的关系。请专注于在文本段落中**直接陈述**的关系。

{definitions}

预定义的关系类型列表: {' , '.join(RELATION_TYPES)}

文本:
\"\"\"

```

```
{chunk_content}
\\\\"
```

请以严格的 JSON 格式输出，包含一个名为 "relations" 的列表，其中每个对象包含 "source" 和 "target" 属性。
例如：

```
{{
  "relations": [
    {{ "source": "集团公司应急领导小组办公室", "target": "集团公司客运部", "type": "责任" }},
    {{ "source": "本预案", "target": "《铁路客票发售和预订系统(含互联网售票部分)应急预案", "type": "责任" }},
    {{ "source": "客运部", "target": "协调各相关部门", "type": "责任" }}
  ]
}}
```

```
return prompt

# --- LLM Interaction (Placeholder) ---

def call_llm(prompt: str) -> Optional[str]:
    """
    Placeholder function to call the LLM API.
    Replace this with your actual LLM API call logic.
    """
    logging.info(f"--- Sending Prompt to LLM (Length: {len(prompt)}) ---")
    # logging.debug(prompt) # Uncomment to see the full prompt
    logging.info("--- Waiting for LLM Response ---")

    # !! --- REPLACE THIS SECTION --- !!
    # Example using OpenAI client (ensure client is initialized above)
    # try:
    #     response = client.chat.completions.create(
    #         model=LLM_MODEL,
    #         messages=[{"role": "user", "content": prompt}],
    #         temperature=0.1, # Lower temperature for more deterministic output
    #         response_format={ "type": "json_object" } # If supported by the model
    #     )
    #     llm_output = response.choices[0].message.content
    #     logging.info("--- Received LLM Response ---")
    #     # time.sleep(1) # Add delay if needed for rate limiting
    #     return llm_output
    # except Exception as e:
    #     logging.error(f"LLM API call failed: {e}")
    #     return None

# --- Placeholder Response (REMOVE WHEN USING REAL LLM) ---
# Simulate a response for testing parsing logic
if "提取定义的实体类型" in prompt:
    # Simulate entity extraction response
    logging.warning("Using PLACEHOLDER response for entity extraction")
```

```

# Simulate based on a known chunk, e.g., chunk_id: e50d6d8c_chunk1
if "集团公司成立客票系统应急领导小组" in prompt:
    return json.dumps({
        "entities": [
            {"name": "集团公司", "type": "组织"},
            {"name": "客票系统应急领导小组", "type": "组织"},
            {"name": "集团公司应急领导小组", "type": "组织"},
            {"name": "科信部", "type": "组织"},
            {"name": "客运部", "type": "组织"},
            {"name": "信息技术所", "type": "组织"},
            {"name": "财务部", "type": "组织"},
            {"name": "计统部", "type": "组织"},
            {"name": "电务部", "type": "组织"},
            {"name": "供电部", "type": "组织"},
            {"name": "宣传部", "type": "组织"},
            {"name": "调度所", "type": "组织"},
            {"name": "广州铁路公安局", "type": "组织"},
            {"name": "集团公司应急领导小组办公室", "type": "组织"},
            {"name": "客运部主任", "type": "角色"},
            {"name": "057-22632", "type": "关键词"}, # Example, 1
            {"name": "各车务站段", "type": "组织"}
        ]
    })
else:
    return json.dumps({"entities": []}) # Default empty for placeholder
elif "提取实体之间的关系" in prompt:
    # Simulate relation extraction response
    logging.warning("Using PLACEHOLDER response for relation extraction")
    if "集团公司成立客票系统应急领导小组" in prompt:
        return json.dumps({
            "relations": [
                {"source": "集团公司应急领导小组办公室", "target": "集团公司"},
                {"source": "集团公司应急领导小组办公室", "target": "客运部"},
                {"source": "各车务站段", "target": "集团公司", "type": "组织"}
            ]
        })
    else:
        return json.dumps({"relations": []}) # Default empty
else:
    return None
# !! --- END REPLACE/REMOVE --- !!

```

```

def parse_llm_response(response_text: Optional[str]) -> Optional[Dict[str, str]]:
    """Safely parses the LLM's JSON response."""
    if not response_text:
        return None
    try:

```

```

# Sometimes LLMs wrap the JSON in ...
if response_text.strip().startswith('"'):
    response_text = response_text.strip()[7:-3].strip()
elif response_text.strip().startswith("`"):
    response_text = response_text.strip()[1:-1].strip()

parsed_data = json.loads(response_text)
# Basic validation
if isinstance(parsed_data, dict) and \
    (('entities' in parsed_data and isinstance(parsed_data['entities'], list) and
     ('relations' in parsed_data and isinstance(parsed_data['relations'], list))):
    return parsed_data
else:
    logging.warning(f"LLM response is valid JSON but not the expected format")
    return None
except json.JSONDecodeError as e:
    logging.error(f"Failed to decode LLM JSON response: {e}\nResponse: {response_text}")
    return None
except Exception as e:
    logging.error(f"An unexpected error occurred during LLM response processing: {e}")
    return None

# --- Main Processing Logic ---

def main():
    """Main function to orchestrate the KG extraction process."""
    data = load_json_data(INPUT_JSON_PATH)
    if not data:
        return

    # Use sets for automatic deduplication
    entities_set: Set[Tuple[str, str]] = set()
    relations_set: Set[Tuple[str, str, str]] = set()
    chunk_map: Dict[str, Dict[str, Any]] = {'chunk_id': chunk_id, 'content': content, 'heading': heading}
    # Store normalized entities per chunk if needed for complex structures
    # chunk_entities: Dict[str, List[Tuple[str, str]]] = {}

    # --- Phase 1: LLM Extraction and Normalization ---
    for i, chunk in enumerate(data):
        chunk_id = chunk.get("chunk_id", f"unknown_{i}")
        content = chunk.get("content")
        heading = chunk.get("heading", "")

        if not content:
            logging.warning(f"Chunk {chunk_id} has no content. Skipping.")
            continue

```

```

logging.info(f"Processing chunk {i+1}/{len(data)}: ID {chunk_id}")

# 1. Extract Entities
entity_prompt = create_entity_prompt(content)
entity_response_text = call_llm(entity_prompt)
parsed_entities = parse_llm_response(entity_response_text)

current_chunk_norm_entities = []
if parsed_entities and 'entities' in parsed_entities:
    for entity in parsed_entities['entities']:
        raw_name = entity.get('name')
        raw_type = entity.get('type')
        if raw_name and raw_type and raw_type in ENTITY_TYPES:
            normalized_name = normalize_entity_name(raw_name)
            entity_tuple = (normalized_name, raw_type)
            entities_set.add(entity_tuple)
            current_chunk_norm_entities.append(entity_tuple)
        else:
            logging.warning(f"Invalid entity format or type in chunk {chunk_id}")
    # Store if needed later: chunk_entities[chunk_id] = current_chunk_norm_entities

# 2. Extract Relations (within chunk)
relation_prompt = create_relation_prompt(content)
relation_response_text = call_llm(relation_prompt)
parsed_relations = parse_llm_response(relation_response_text)

if parsed_relations and 'relations' in parsed_relations:
    for relation in parsed_relations['relations']:
        raw_source = relation.get('source')
        raw_target = relation.get('target')
        raw_type = relation.get('type')
        if raw_source and raw_target and raw_type and raw_type in RELATION_TYPES:
            normalized_source = normalize_entity_name(raw_source)
            normalized_target = normalize_entity_name(raw_target)
            relation_tuple = (normalized_source, normalized_target, raw_type)
            relations_set.add(relation_tuple)
        else:
            logging.warning(f"Invalid relation format or type in chunk {chunk_id}")

logging.info(f"Finished LLM extraction. Found {len(entities_set)} unique entities and {len(relations_set)} unique relations.")

# --- Phase 2: Add Structural Relations (BelongsTo) ---
logging.info("Adding structural 'BelongsTo' relations...")
structural_relations_added = 0
for chunk in data:
    chunk_id = chunk.get("chunk_id")
    parent_id = chunk.get("parent_id")
    heading = chunk.get("heading")

```

```

    if parent_id and chunk_id and heading:
        parent_chunk = chunk_map.get(parent_id)
        if parent_chunk and parent_chunk.get("heading"):
            # Use normalized heading as the entity name for the chunk
            # Assume chunks with headings map to '章节' or '文档' entities
            # A more robust method might check if these entities were
            child_entity_name = normalize_entity_name(heading)
            parent_entity_name = normalize_entity_name(parent_chunk["heading"])

            # Add the BelongsTo relation
            # Add the entities themselves if not already present (as sets)
            # Infer type crudely - root is Document, others are Sections
            child_type = "章节" # Default assumption for non-root headings
            parent_type = "章节" if parent_chunk.get("parent_id") else "文档"

            entities_set.add((child_entity_name, child_type))
            entities_set.add((parent_entity_name, parent_type))

            relation_tuple = (child_entity_name, parent_entity_name, "BelongsTo")
            if relation_tuple not in relations_set:
                relations_set.add(relation_tuple)
                structural_relations_added += 1

logging.info(f"Added {structural_relations_added} structural 'BelongsTo' relations")

# --- Output Results ---
print("\n--- Final Extracted Entities ---")
# Sort for consistency
sorted_entities = sorted(list(entities_set))
for name, type in sorted_entities:
    print(f"- ({type}) {name}")
print(f"\nTotal Unique Entities: {len(sorted_entities)}")

print("\n--- Final Extracted Relations ---")
sorted_relations = sorted(list(relations_set))
for source, target, type in sorted_relations:
    print(f"- {source} --[{type}]--> {target}")
print(f"\nTotal Unique Relations: {len(sorted_relations)}")

if __name__ == "__main__":
    main()

```

****How to Use:****

1. ****Save:**** Save the code as a Python file (e.g., `kg_extractor.py`).

2. ****Install Libraries:**** If you choose a specific LLM library (like `openai` or `anthropic`), install it.
3. ****Configure:****
 - * Set the environment variable `YOUR_LLM_API_KEY` (or rename it in the script).
 - * Update `LLM_MODEL` to the specific model you want to use.
 - * Ensure `INPUT_JSON_PATH` points to your `demo3.json` file.
 - * Review and expand the `CANONICAL_MAP` based on your document's structure.
4. ****Replace Placeholder:**** Modify the `call_llm` function to use your chosen LLM library and model.
5. ****Run:**** Execute the script from your terminal: `python kg_extractor.py`
6. ****Review Output:**** Check the printed lists of entities and relations.

****Next Steps & Potential Improvements:****

1. ****Implement Real `call_llm`:**** This is the most critical step.
2. ****Refine `CANONICAL_MAP`:**** Add more mappings based on observed LLM output.
3. ****Improve Structural Relation Logic:**** Make the mapping between chunks more robust.
4. ****Error Handling:**** Add more specific error handling around LLM calls.
5. ****Confidence Scores:**** If your LLM provides confidence scores, you can filter results.
6. ****Advanced Normalization/Entity Linking:**** Use libraries like `spaCy` for better entity resolution.
7. ****Output Format:**** Save results to CSV, JSONL, or directly into a graph database.
8. ****Batching/Async:**** For large documents, consider batching chunks or using async LLM calls.

This code provides a solid starting point for extracting the knowledge graph from your documents.

user:

增加输出格式：
memgraph Cypher statements

assistant:

Okay, let's add the functionality to output the extracted knowledge graph as Cypher statements.

We'll add a new function `generate_cypher_statements` and call it at the end of the script.

```
import json
import os
import logging
import time # For potential rate limiting
from typing import List, Dict, Set, Tuple, Optional, Any

# --- Configuration ---

# [ Existing configurations remain the same: LLM_API_KEY, LLM_MODEL, INPUT_JSON_PATH ]
# 1. LLM Configuration
LLM_API_KEY = os.environ.get("YOUR_LLM_API_KEY")
LLM_MODEL = "your-chosen-llm-model"
```

```

# 2. File Path
INPUT_JSON_PATH = "demo3.json"
OUTPUT_CYPHER_PATH = "output_graph.cypher" # Optional: File to save Cypher

# 3. Knowledge Graph Schema (Based on 改进建议.md)
ENTITY_TYPES = [
    "文档", "章节", "主题", "关键词", "人员", "角色",
    "组织", "时间", "事件", "法规"
]

# Map Chinese types to English for potentially better compatibility or portability
ENTITY_TYPE_MAP_CYPHER = {
    "文档": "Document",
    "章节": "Section",
    "主题": "Topic",
    "关键词": "Keyword",
    "人员": "Person",
    "角色": "Role",
    "组织": "Organization",
    "时间": "Time",
    "事件": "Event",
    "法规": "Regulation"
}

RELATION_TYPES = [
    "隶属关系", "版本关系", "引用", "依据", "责任",
    "审批", "时间", "生效", "关联"
]

# Map Chinese types to English (often uppercase) for Cypher relationships
RELATION_TYPE_MAP_CYPHER = {
    "隶属关系": "BELONGS_TO",
    "版本关系": "HAS_VERSION",
    "引用": "REFERENCES",
    "依据": "BASED_ON",
    "责任": "RESPONSIBLE_FOR",
    "审批": "APPROVED_BY",
    "时间": "OCCURS_AT", # Consider if Time should be a node instead
    "生效": "EFFECTIVE_FROM", # Consider if Time should be a node instead
    "关联": "RELATED_TO"
}

# 4. Entity Normalization Map (Example - expand as needed)
CANONICAL_MAP = {
    "客运部": "集团公司客运部",

```



```

"信息技术所": "集团公司信息技术所",
"科信部": "集团公司科信部",
"财务部": "集团公司财务部",
"计统部": "集团公司计统部",
"电务部": "集团公司电务部",
"供电部": "集团公司供电部",
"宣传部": "集团公司宣传部",
"调度所": "集团公司调度所",
"集团公司应急领导小组办公室": "集团公司应急领导小组办公室", # Already specific
"集团公司应急领导小组": "集团公司应急领导小组", # Already specific
"国铁集团应急领导小组办公室": "国铁集团应急领导小组办公室",
"国铁集团应急领导小组": "国铁集团应急领导小组",
"国铁集团客运部": "国铁集团客运部",
"12306科创中心": "12306科创中心",
"广铁集团": "中国铁路广州局集团有限公司",
"集团公司": "中国铁路广州局集团有限公司", # Be careful with context, might
"本预案": "《广州局集团公司客票发售和预订系统（含互联网售票部分）应急预案》", #
"《铁路客票发售和预订系统(含互联网售票部分)应急预案》": "《铁路客票发售和预订系统
《广州局集团公司网络安全事件应急预案》": "《广州局集团公司网络安全事件应急预案》
《广州局集团公司信息系统故障应急处置和调查处理办法》": "《广州局集团公司信息系统
"客票系统": "客票发售和预订系统", # Normalize system name
}

# 5. Logging Configuration
logging.basicConfig(level=logging.INFO, format='%(asctime)s - %(levelname)s - %(message)s')

# --- Helper Functions ---

def load_json_data(file_path: str) -> Optional[List[Dict[str, Any]]]:
    """Loads data from a JSON file."""
    # [ Function code remains the same ]
    try:
        with open(file_path, 'r', encoding='utf-8') as f:
            data = json.load(f)
            logging.info(f"Successfully loaded data from {file_path}")
            return data
    except FileNotFoundError:
        logging.error(f"Error: Input file not found at {file_path}")
        return None
    except json.JSONDecodeError:
        logging.error(f"Error: Could not decode JSON from {file_path}")
        return None
    except Exception as e:
        logging.error(f"An unexpected error occurred during JSON loading: {e}")
        return None

```

```
def normalize_entity_name(raw_name: str) -> str:
    """Normalizes entity names using the CANONICAL_MAP."""
    # [ Function code remains the same ]
    if not isinstance(raw_name, str):
        logging.warning(f"Attempted to normalize non-string value: {raw_name}")
        return str(raw_name)
    cleaned_name = raw_name.strip().replace('\n', ' ')
    return CANONICAL_MAP.get(cleaned_name, cleaned_name)

def escape_cypher_string(value: str) -> str:
    """Escapes single quotes and backslashes for Cypher strings."""
    if not isinstance(value, str):
        return str(value) # Return as string if not already
    return value.replace('\\', '\\\\').replace("'", "\\'")

def create_entity_prompt(chunk_content: str) -> str:
    """Creates the prompt for entity extraction."""
    # [ Function code remains the same ]
    definitions = """
    实体类型定义：
    - 文档：管理规定的文件名称，如《应急预案》。
    - 章节：文档中的具体章节标题，如“1 总则”。
    - 主题：文档或章节的核心议题，如“应急组织机构”。
    - 关键词：文本中重要的名词或术语，如“客票系统”、“应急响应”、“电子客票”。
    - 人员：具体的人名（此文档中可能较少）。
    - 角色：指代具有特定职责的职位或岗位，如“客运部主任”、“售票员”。
    - 组织：涉及的单位、部门或公司，如“中国铁路广州局集团有限公司”、“集团公司客运部”、
    - 时间：具体的日期、时间点或时间段，如“2021年”、“4小时及以上”、“每年3月”。
    - 事件：文档中描述的具体活动或状况，如“系统突发事件”、“启动应急预案”、“应急演练”。
    - 法规：引用的其他法规或文件名称及其编号，如“《铁路客票发售和预订系统(含互联网售票)》”
    """

    prompt = f"""
```

请从以下文本中提取定义的实体类型。

```
{definitions}
```

预定义的实体类型列表：{' , '.join(ENTITY_TYPES)}

文本：

```
\\"\\""
```

```
{chunk_content}
```

```
\\"\\""
```

请以严格的 JSON 格式输出，包含一个名为 "entities" 的列表，其中每个对象包含 "name" 例如：

```
{{
  "entities": [
    {{ "name": "集团公司客运部", "type": "组织" }},
```

```

        [{"name": "售票故障", "type": "事件"}],
        [{"name": "《铁路客票发售和预订系统(含互联网售票部分)应急预案》（铁办客〔2021〕"}
    ]
}
"""

    return prompt

def create_relation_prompt(chunk_content: str) -> str:
    """Creates the prompt for relation extraction (within the chunk)."""
    # [ Function code remains the same ]
    definitions = """
    关系类型定义（请仅提取文本段落内明确描述的关系）：
    - 隶属关系（BelongsTo）：通常是结构化的，此提示词主要关注文本内描述，如“办公室设
    - 版本关系（HasVersion）：指明文档的版本信息或其他版本的关系（如“修订版”、“废
    - 引用（References）：一个实体提到了另一个实体或文件，如“详见附件5”。
    - 依据（BasedOn）：指出制定某文件或采取某行动所依据的法规或原则，如“根据...制定
    - 责任（ResponsibleFor）：指明某个角色或组织负责某项任务或职责，如“客运部负责协
    - 审批（ApprovedBy）：指出某事项需要经过哪个组织或角色批准，如“经...同意后”。
    - 时间（OccursAt）：事件发生的时间，或规定适用的时间点/段，如“事件影响4小时”、“
    - 生效（EffectiveFrom）：规定或文件的生效日期，如“自发布之日起实施”。
    - 关联（RelatedTo）：实体间的其他关联，如“与...不一致时，以此为准”。
    """

    prompt = f"""
    请从以下文本中提取实体之间的关系。请专注于在文本段落中**直接陈述**的关系。

    {definitions}

    预定义的关系类型列表：{' , '.join(RELATION_TYPES)}

    文本：
    {chunk_content}

    请以严格的 JSON 格式输出，包含一个名为 "relations" 的列表，其中每个对象包含 "source"
    例如：
    {{
        "relations": [
            {{ "source": "集团公司应急领导小组办公室", "target": "集团公司客运部", "type": "隶属关系" }},
            {{ "source": "本预案", "target": "《铁路客票发售和预订系统(含互联网售票部分)应急预案》", "type": "引用" }},
            {{ "source": "客运部", "target": "协调各相关部门", "type": "责任" }}
        ]
    }}
    """

    return prompt

# --- LLM Interaction (Placeholder) ---

```

```

def call_llm(prompt: str) -> Optional[str]:
    """
    Placeholder function to call the LLM API.
    Replace this with your actual LLM API call logic.
    """
    # [ Function code remains largely the same, use your actual LLM call
    logging.info(f"--- Sending Prompt to LLM (Length: {len(prompt)}) ---")
    logging.info("--- Waiting for LLM Response ---")

    # !! --- REPLACE THIS SECTION with your actual LLM call --- !!
    # Simulate a response for testing
    if "提取定义的实体类型" in prompt:
        logging.warning("Using PLACEHOLDER response for entity extraction")
        if "集团公司成立客票系统应急领导小组" in prompt:
            return json.dumps({ "entities": [ {"name": "集团公司", "type": "集团"} ] })
        else: return json.dumps({"entities": []})
    elif "提取实体之间的关系" in prompt:
        logging.warning("Using PLACEHOLDER response for relation extraction")
        if "集团公司成立客票系统应急领导小组" in prompt:
            return json.dumps({ "relations": [ {"source": "集团公司应急领导小组", "target": "客票系统"} ] })
        else: return json.dumps({"relations": []})
    else: return None
    # !! --- END REPLACE/REMOVE --- !!

def parse_llm_response(response_text: Optional[str]) -> Optional[Dict[str, Any]]:
    """Safely parses the LLM's JSON response."""
    # [ Function code remains the same ]
    if not response_text: return None
    try:
        if response_text.strip().startswith("("):
            response_text = response_text.strip()[7:-3].strip()
        elif response_text.strip().startswith("`"):
            response_text = response_text.strip()[1:-1].strip()
        parsed_data = json.loads(response_text)
        if isinstance(parsed_data, dict) and \
            (('entities' in parsed_data and isinstance(parsed_data['entities'], list)) or
             ('relations' in parsed_data and isinstance(parsed_data['relations'], list))):
            return parsed_data
        else:
            logging.warning(f"LLM response is valid JSON but not the expected format")
            return None
    except json.JSONDecodeError as e:
        logging.error(f"Failed to decode LLM JSON response: {e}\nResponse: {response_text}")
        return None
    except Exception as e:
        logging.error(f"An unexpected error occurred during LLM response parsing: {e}")
        return None

```

```

        return None

# --- Cypher Generation ---

def generate_cypher_statements(entities: Set[Tuple[str, str]], relations
    """Generates Memgraph/Neo4j Cypher MERGE statements."""
    cypher_statements = []

    # Add constraint for uniqueness if desired (recommended)
    # You might want to run these manually once or ensure they exist
    # for entity_type_cn in ENTITY_TYPES:
    #     entity_type_cypher = ENTITY_TYPE_MAP_CYPHER.get(entity_type_cn
    #     cypher_statements.append(f"CREATE CONSTRAINT ON (n:{entity_type

    cypher_statements.append("\n// --- Entity Creation ---")
    sorted_entities = sorted(list(entities))
    for name, type_cn in sorted_entities:
        if not name: # Skip empty names
            continue
        entity_type_cypher = ENTITY_TYPE_MAP_CYPHER.get(type_cn, type_cn
        escaped_name = escape_cypher_string(name)
        # Use MERGE to avoid duplicates
        cypher_statements.append(f"MERGE (:`{entity_type_cypher}` `{name

    cypher_statements.append("\n// --- Relationship Creation ---")
    sorted_relations = sorted(list(relations))
    for source, target, type_cn in sorted_relations:
        if not source or not target: # Skip if source or target is missin
            continue
        relation_type_cypher = RELATION_TYPE_MAP_CYPHER.get(type_cn, type
        escaped_source = escape_cypher_string(source)
        escaped_target = escape_cypher_string(target)

        # Find the types of source and target from the entities set for l
        source_type_cn = next((t for n, t in sorted_entities if n == sou
        target_type_cn = next((t for n, t in sorted_entities if n == tar

        if source_type_cn and target_type_cn:
            source_type_cypher = ENTITY_TYPE_MAP_CYPHER.get(source_type_c
            target_type_cypher = ENTITY_TYPE_MAP_CYPHER.get(target_type_c
            # Use MERGE for relationships too
            cypher_statements.append(
                f"MATCH (a:`{source_type_cypher}` {{name: '{escaped_sour
                f"MERGE (a)-[:`{relation_type_cypher}`]->(b);"
            )
        else:
            # Fallback if type not found (less safe, might match wrong
            logging.warning(f"Could not determine types for relationship

```

```

        cypher_statements.append(
            f"MATCH (a {{name: '{escaped_source}'}}), (b {{name: '{escaped_target}'}})
            f"MERGE (a)-[:`{relation_type_cypher}`]->(b);"
        )

    return cypher_statements

# --- Main Processing Logic ---

def main():
    """Main function to orchestrate the KG extraction process."""
    data = load_json_data(INPUT_JSON_PATH)
    if not data:
        return

    entities_set: Set[Tuple[str, str]] = set()
    relations_set: Set[Tuple[str, str, str]] = set()
    chunk_map: Dict[str, Dict[str, Any]] = {chunk['chunk_id']: chunk for chunk in data}

    # --- Phase 1: LLM Extraction and Normalization ---
    # [ This loop remains the same as before ]
    for i, chunk in enumerate(data):
        chunk_id = chunk.get("chunk_id", f"unknown_{i}")
        content = chunk.get("content")
        heading = chunk.get("heading", "")
        if not content:
            continue
        logging.info(f"Processing chunk {i+1}/{len(data)}: ID {chunk_id}")

        # Extract Entities
        entity_prompt = create_entity_prompt(content)
        entity_response_text = call_llm(entity_prompt)
        parsed_entities = parse_llm_response(entity_response_text)
        if parsed_entities and 'entities' in parsed_entities:
            for entity in parsed_entities['entities']:
                raw_name = entity.get('name')
                raw_type = entity.get('type')
                if raw_name and raw_type and raw_type in ENTITY_TYPES:
                    normalized_name = normalize_entity_name(raw_name)
                    entities_set.add((normalized_name, raw_type))
                else:
                    logging.warning(f"Invalid entity format or type in {chunk_id}")

        # Extract Relations
        relation_prompt = create_relation_prompt(content)
        relation_response_text = call_llm(relation_prompt)
        parsed_relations = parse_llm_response(relation_response_text)
        if parsed_relations and 'relations' in parsed_relations:
            for relation in parsed_relations['relations']:

```

```

        raw_source = relation.get('source')
        raw_target = relation.get('target')
        raw_type = relation.get('type')
        if raw_source and raw_target and raw_type and raw_type in valid_types:
            normalized_source = normalize_entity_name(raw_source)
            normalized_target = normalize_entity_name(raw_target)
            relations_set.add((normalized_source, normalized_target, raw_type))
        else: logging.warning(f"Invalid relation format or type: {raw_source}, {raw_target}, {raw_type}")

logging.info(f"Finished LLM extraction. Found {len(entities_set)} unique entities.")

# --- Phase 2: Add Structural Relations (BelongsTo) ---
# [ This loop remains the same as before ]
logging.info("Adding structural 'BelongsTo' relations...")
structural_relations_added = 0
for chunk in data:
    chunk_id = chunk.get("chunk_id")
    parent_id = chunk.get("parent_id")
    heading = chunk.get("heading")
    if parent_id and chunk_id and heading:
        parent_chunk = chunk_map.get(parent_id)
        if parent_chunk and parent_chunk.get("heading"):
            child_entity_name = normalize_entity_name(heading)
            parent_entity_name = normalize_entity_name(parent_chunk.get("heading"))
            if child_entity_name and parent_entity_name: # Ensure names are not empty
                child_type = "章节"
                parent_type = "章节" if parent_chunk.get("parent_id") else None
                entities_set.add((child_entity_name, child_type))
                entities_set.add((parent_entity_name, parent_type))
                relation_tuple = (child_entity_name, parent_entity_name, "BelongsTo")
                if relation_tuple not in relations_set:
                    relations_set.add(relation_tuple)
                    structural_relations_added += 1
logging.info(f"Added {structural_relations_added} structural 'BelongsTo' relations.")

# --- Output Results ---

# 1. Console Output (Original)
print("\n--- Final Extracted Entities (Console) ---")
sorted_entities = sorted(list(entities_set))
for name, type in sorted_entities:
    print(f"- ({type}) {name}")
print(f"\nTotal Unique Entities: {len(sorted_entities)}")

print("\n--- Final Extracted Relations (Console) ---")
sorted_relations = sorted(list(relations_set))
for source, target, type in sorted_relations:

```

```

        print(f"- {source} --[{type}]--> {target}")
    print(f"\nTotal Unique Relations: {len(sorted_relations)}")

# 2. Cypher Statement Generation and Output
print(f"\n--- Generating Cypher Statements (Memgraph/Neo4j) ---")
cypher_statements = generate_cypher_statements(entities_set, relations_set)

# Option A: Print to console
# print("\n".join(cypher_statements))

# Option B: Save to file
try:
    with open(OUTPUT_CYPHER_PATH, 'w', encoding='utf-8') as f:
        f.write("; \n".join(cypher_statements) + "; \n") # Add semicolon at the end
    print(f"\nCypher statements saved to: {OUTPUT_CYPHER_PATH}")
except IOError as e:
    print(f"\nError writing Cypher statements to file {OUTPUT_CYPHER_PATH}")
    print("\nCypher Statements: \n")
    print("; \n".join(cypher_statements) + "; \n") # Print to console as fallback

if __name__ == "__main__":
    main()

```

****Changes Made:****

1. ****Cypher Configuration:**** Added `OUTPUT_CYPHER_PATH`, `ENTITY_TYPE_MAPPING`, and `RELATIONSHIP_TYPE_MAPPING`.
2. ****`escape_cypher_string` Function:**** Added a helper to escape single quotes in Cypher strings.
3. ****`generate_cypher_statements` Function:****
 - * Takes the final `entities_set` and `relations_set` as input.
 - * Iterates through entities, generating `MERGE (:<EntityType> {name: <EntityName>})` statements.
 - * Iterates through relations, generating `MATCH (a:<SourceType> {name: <SourceName>})-[:<RelationshipType>]->(b:<TargetType> {name: <TargetName>})` statements.
 - * Uses the `escape_cypher_string` function for all names.
 - * Uses backticks (```) around labels and relationship types just in case they contain special characters.
4. ****`main` Function Integration:****
 - * Calls `generate_cypher_statements` after all entities and relations are processed.
 - * Includes logic to either print the Cypher statements to the console or save them to a file.

Now, when you run the script (after replacing the placeholder LLM call),

