

# Deep Learning

## 7.2 Autoencoders

Dr. Konda Reddy Mopuri  
kmopuri@iittp.ac.in  
Dept. of CSE, IIT Tirupati

# Beyond Classification and Regression

- ① Applications such as image synthesis, image-to-image transformations model high-dim signals

# Beyond Classification and Regression

- ① Applications such as image synthesis, image-to-image transformations model high-dim signals
- ② These applications require to learn the meaningful degrees of freedom that constitute the signal

# Beyond Classification and Regression

- ① Applications such as image synthesis, image-to-image transformations model high-dim signals
- ② These applications require to learn the meaningful degrees of freedom that constitute the signal
- ③ These degrees of freedom are of lesser dimensions than the signal

# Example: Synthesizing Human faces

- ① For generating new faces, it makes sense to capture a small number of degrees of freedom such as
  - skull size and shape
  - color of skin and eyes
  - features of nose and lips, etc.

# Example: Synthesizing Human faces

- ① For generating new faces, it makes sense to capture a small number of degrees of freedom such as
  - skull size and shape
  - color of skin and eyes
  - features of nose and lips, etc.
- ② Even a comprehensive list of such things will be less than the number of pixels in the image (i.e. resolution)

# Example: Synthesizing Human faces

- ① For generating new faces, it makes sense to capture a small number of degrees of freedom such as
  - skull size and shape
  - color of skin and eyes
  - features of nose and lips, etc.
- ② Even a comprehensive list of such things will be less than the number of pixels in the image (i.e. resolution)
- ③ If we can model these relatively small number of dimensions, we can synthesize a face with thousands of dimensions

# Autoencoder

- 1 Neural network that maps a space to itself



# Autoencoder


- ① Neural network that maps a space to itself
- ② Trained to copy its input to itself (close to, but not an identity function)

# Autoencoder

- ① Neural network that maps a space to itself
- ② Trained to copy its input to itself (close to, but not an identity function)
- ③ Network consists of two parts: encoder ( $f$ ) and decoder ( $g$ )

# Autoencoder

- ① Neural network that maps a space to itself
- ② Trained to copy its input to itself (close to, but not an identity function)
- ③ Network consists of two parts: encoder ( $f$ ) and decoder ( $g$ )



④

# Autoencoder

- ① Original (input) space is of higher dimensions but the data lies in a manifold of smaller dimension

# Autoencoder

- ① Original (input) space is of higher dimensions but the data lies in a manifold of smaller dimension
- ② Dimension of the latent space is a hyper-parameter chosen from prior knowledge, or through heuristics

# Autoencoder

- ① Let  $p$  be the data distribution in the input space, autoencoder is characterized with the following loss

$$\mathbb{E}_{x \sim p} \|x - g \circ f(x)\|^2 \approx 0$$

- ① Let  $p$  be the data distribution in the input space, autoencoder is characterized with the following loss

$$\mathbb{E}_{x \sim p} \|x - g \circ f(x)\|^2 \approx 0$$

- ② Training the autoencoder consists of finding the parameters for the encoder ( $f(\cdot; w_f)$ ) and decoder ( $g(\cdot; w_g)$ ) optimizing the following empirical loss

$$\hat{w}_f, \hat{w}_g = \operatorname{argmin}_{w_f, w_g} \frac{1}{N} \sum_n \|x_n - g(f(x_n; w_f); w_g)\|^2$$

# Autoencoder

- ① A simple example:  $f$  and  $g$  are linear functions  $\rightarrow$  optimal solution is PCA



# Autoencoder

- ① A simple example:  $f$  and  $g$  are linear functions  $\rightarrow$  optimal solution is PCA
- ② Better results can be made possible with sophisticated transformations such as deep neural networks  $\rightarrow$  Deep Autoencoders

# Deep Autoencoders

AutoEncoder (

(encoder): Sequential (

(0): Conv2d(1, 32, kernel\_size=(5, 5), stride=(1, 1)) (1): ReLU (inplace)  
 (2): Conv2d(32, 32, kernel\_size=(5, 5), stride=(1, 1)) (3): ReLU (inplace)  
 (4): Conv2d(32, 32, kernel\_size=(4, 4), stride=(2, 2)) (5): ReLU (inplace)  
 (6): Conv2d(32, 32, kernel\_size=(3, 3), stride=(2, 2)) (7): ReLU (inplace)  
 (8): Conv2d(32, 8, kernel\_size=(4, 4), stride=(1, 1)) )

(decoder): Sequential (

(0): ConvTranspose2d(8, 32, kernel\_size=(4, 4), stride=(1, 1)) (1): ReLU  
 (inplace)  
 (2): ConvTranspose2d(32, 32, kernel\_size=(3, 3), stride=(2, 2)) (3): ReLU  
 (inplace)  
 (4): ConvTranspose2d(32, 32, kernel\_size=(4, 4), stride=(2, 2)) (5): ReLU  
 (inplace)  
 (6): ConvTranspose2d(32, 32, kernel\_size=(5, 5), stride=(1, 1)) (7): ReLU  
 (inplace)  
 (8): ConvTranspose2d(32, 1, kernel\_size=(5, 5), stride=(1, 1)) ) )

# Deep Autoencoders



Top row: original data samples

Bottom row: corresponding reconstructed samples (with linear layer of dimension 32)

---

Figure credits: [blog.keras.io](http://blog.keras.io)