

Deep Learning

9.1 Generative Adversarial Networks (GANs)

Dr. Konda Reddy Mopuri
kmopuri@iittp.ac.in
Dept. of CSE, IIT Tirupati

Let's see something cool

- 1 Popular framework for learning high-dimensional densities

GANs

- ① Popular framework for learning high-dimensional densities
- ② Proposed by Goodfellow et al. (2014)

- ① Popular framework for learning high-dimensional densities
- ② Proposed by Goodfellow et al. (2014)
- ③ Non-parametric (implicit) density modeling

GANs

- ① Two neural networks are trained jointly

GANs

- ① Two neural networks are trained jointly
- ② Discriminator D classifies samples: real versus fake

- ① Two neural networks are trained jointly
- ② Discriminator D classifies samples: real versus fake
- ③ Generator G produces samples (maps a simple, fixed distribution to generated samples)

GANs





Figure credits: Francois Fleuret

GANs



Framework is adversarial: Both the modules have conflicting objectives.

Figure credits: Francois Fleuret

GANs

If \mathcal{X} is the data space and D is the dimension of the latent space,

① Generator $G : \mathbb{R}^D \rightarrow \mathcal{X}$

If \mathcal{X} is the data space and D is the dimension of the latent space,

- ① Generator $G : \mathbb{R}^D \rightarrow \mathcal{X}$
- ② Maps a random normal sample to data distribution

If \mathcal{X} is the data space and D is the dimension of the latent space,

- ① Generator $G : \mathbb{R}^D \rightarrow \mathcal{X}$
- ② Maps a random normal sample to data distribution
- ③ Discriminator $D : \mathcal{X} \rightarrow [0, 1]$

If \mathcal{X} is the data space and D is the dimension of the latent space,

- ① Generator $G : \mathbb{R}^D \rightarrow \mathcal{X}$
- ② Maps a random normal sample to data distribution
- ③ Discriminator $D : \mathcal{X} \rightarrow [0, 1]$
- ④ Takes a sample as input and predicts if it comes from G or the actual data distribution

GANs

- ① If G is fixed, D can be trained by taking

- ① If G is fixed, D can be trained by taking
 - real samples $x_n \sim \mu, n = 1, 2, \dots, N$

- ① If G is fixed, D can be trained by taking
- real samples $x_n \sim \mu, n = 1, 2, \dots, N$
 - fake samples generated by the $G, z_n \sim \mathcal{N}(0, I), n = 1, 2, \dots, N$

- ① If G is fixed, D can be trained by taking
- real samples $x_n \sim \mu, n = 1, 2, \dots, N$
 - fake samples generated by the $G, z_n \sim \mathcal{N}(0, I), n = 1, 2, \dots, N$
 - Two class classification dataset $\mathcal{D} =$
 $\{(x_1, 1), (x_2, 1), \dots, (x_n, 1), (G(z_1), 0), (G(z_2), 0), \dots, (G(z_n), 0)\}$

- ① If G is fixed, D can be trained by taking
 - real samples $x_n \sim \mu, n = 1, 2, \dots, N$
 - fake samples generated by the $G, z_n \sim \mathcal{N}(0, I), n = 1, 2, \dots, N$
 - Two class classification dataset $\mathcal{D} = \{(x_1, 1), (x_2, 1), \dots, (x_n, 1), (G(z_1), 0), (G(z_2), 0), \dots, (G(z_n), 0)\}$
- ② Minimize the binary cross entropy loss

$$\begin{aligned}\mathcal{L}(D) &= -\frac{1}{2N} \left(\sum_1^N \log(D(x_n)) + \sum_1^N \log(1 - D(G(z_n))) \right) \\ &= -\frac{1}{2} \left(\mathbb{E}_{X \sim \mu} [\log(D(X))] + \mathbb{E}_{X \sim \mu_G} [\log(1 - D(X))] \right)\end{aligned}$$

- ① Loss for training the Generator G is negation of that of D



$$\begin{aligned}\mathcal{L}(G) &= -\frac{1}{2}\left(\mathbb{E}_{X\sim\mu}\left[\log(D(X))\right] + \mathbb{E}_{X\sim\mu_G}\left[\log(1 - D(X))\right]\right) \\ &= -\frac{1}{2}\mathbb{E}_{X\sim\mu_G}\left[\log(1 - D(X))\right]\end{aligned}$$

- ① Loss for training the Generator G is negation of that of D

$$\begin{aligned}\mathcal{L}(G) &= -\frac{1}{2} \left(\mathbb{E}_{X \sim \mu} [\log(D(X))] + \mathbb{E}_{X \sim \mu_G} [\log(1 - D(X))] \right) \\ &= -\frac{1}{2} \mathbb{E}_{X \sim \mu_G} [\log(1 - D(X))]\end{aligned}$$

- ② In practice, initial fake samples are very poor that D response is saturated and $\log(1 - D(X))$ generates zero gradients \rightarrow Goodfellow *et al.* suggest to use $-\log(D(X))$

GANs



Deep Convolutional GANs

① Proposed by Radford *et al.* (2015)

Deep Convolutional GANs


- ① Proposed by Radford *et al.* (2015)
- ② Scales GANs to generating realistic images

Deep Convolutional GANs

- ① Proposed by Radford *et al.* (2015)
- ② Scales GANs to generating realistic images
- ③ Uses convolution and transposed convolution layers


Deep Convolutional GANs

① Architecture of Generator (G) (Radford *et al.* 2015)




Deep Convolutional GANs

- ① Architecture of Generator (G) (Radford *et al.* 2015)
- ② D is a binary CNN classifier (typically doesn't use fc layers and pooling layers)





Deep Convolutional GANs

- ① Architecture of Generator (G) (Radford *et al.* 2015)
- ② D is a binary CNN classifier (typically doesn't use fc layers and pooling layers)
- ③ Batch Normalization layers are used, ReLU for G, leakyReLU for D



Deep Convolutional GANs



GAN training pathologies

- ① Loss oscillation as opposed to a convergence

GAN training pathologies

- ① Loss oscillation as opposed to a convergence
- ② Mode collapse: G learns models only a portion of real data distribution

Quality assessment of GANs

- ① Inception score (Salimans *et al.* 2016) → verifies the posterior distribution of fake images is similar to that of real data (penalizes missing classes)

Quality assessment of GANs

- ① Inception score (Salimans *et al.* 2016) → verifies the posterior distribution of fake images is similar to that of real data (penalizes missing classes)
- ② Fréchet Inception Distance (FID) (Heusel *et al.* 2017) → evaluates the similarity between distributions of the features in one of the feature maps

Quality assessment of GANs

- ① Inception score (Salimans *et al.* 2016) → verifies the posterior distribution of fake images is similar to that of real data (penalizes missing classes)
- ② Fréchet Inception Distance (FID) (Heusel *et al.* 2017) → evaluates the similarity between distributions of the features in one of the feature maps
- ③ Assessment is often deals aesthetic evaluation of the generated samples

References

- ① I. J. Goodfellow, J. Pouget-Abadie, M. Mirza, B. Xu, D. Warde-Farley, S. Ozair, A. Courville, and Y. Bengio. Generative adversarial networks. CoRR, abs/1406.2661, 2014
- ② A. Radford, L. Metz, and S. Chintala. Unsupervised representation learning with deep convolutional generative adversarial networks. CoRR, abs/1511.06434, 2015
- ③ T. Salimans, I. Goodfellow, W. Zaremba, V. Cheung, A. Radford, X. Chen, and X. Chen. Improved techniques for training GANs. In Neural Information Processing Systems (NIPS), pages 2234–2242, 2016
- ④ M. Heusel, H. Ramsauer, T. Unterthiner, B. Nessler, and S. Hochreiter. GANs trained by a two time-scale update rule converge to a local nash equilibrium. CoRR, abs/1706.08500, 2017