

Deep Learning

2.2 Over and Under fitting

Dr. Konda Reddy Mopuri
kmopuri@iittp.ac.in
Dept. of CSE, IIT Tirupati
Aug-Dec 2021




Generalization

- ① Ability of an ML model to perform on unseen data

Generalization

- ① Ability of an ML model to perform on unseen data
- ② Goal of good ML model is to generalize well from training data to any data from the task domain

① Refers to how well the model can approximate a target



- ① Refers to how well the model can approximate a target function
- ② Goodness of the fit refers to measures used to estimate how well the approximation matches the target


- ① Refers to how well the model can approximate a target function
- ② Goodness of the fit refers to measures used to estimate how well the approximation matches the target
- ③ In ML we don't know the target function under approximation

Over and under fitting

- ① Cause of poor performance in ML is either overfitting or underfitting to the data


Overfitting

- 1 Refers to a model which learns the training data too well



Overfitting


- 1 Refers to a model which learns the training data too well



- 2 Model learns the noise and random fluctuations in the data as concepts (to an extent that affects its generalization)

Overfitting

- ① Refers to a model which learns the training data too well



- ② Model learns the noise and random fluctuations in the data as concepts (to an extent that affects its generalization)
- ③ More likely to occur in case of nonparametric and nonlinear models with more flexibility

Example

- 1 Decision trees are a nonparametric model

Example


- ① Decision trees are a nonparametric model
- ② Flexible and prone to overfitting training data

Example

- ① Decision trees are a nonparametric model
- ② Flexible and prone to overfitting training data
- ③ Can be addressed by pruning the tree after learning (removes some of the detail picked up)


Underfitting

- 1 Refers to a scenario where the model can neither model the training data nor generalize to new data



Underfitting


- 1 Refers to a scenario where the model can neither model the training data nor generalize to new data



- 2 Obvious since the performance on the training data is poor (hence often not discussed)

Underfitting


- 1 Refers to a scenario where the model can neither model the training data nor generalize to new data



- 2 Obvious since the performance on the training data is poor (hence often not discussed)
- 3 Can be alleviated by trying alternate ML algorithms (e.g. relatively complex)


Good fit in ML

- 1 Ideally, one should select a model at the sweet spot between over and underfitting



Good fit in ML

- 1 Ideally, one should select a model at the sweet spot between over and underfitting




- 2 Very difficult in practice

Good fit in ML

- ① One can observe the behavior of the model during the training


Good fit in ML

- ① One can observe the behavior of the model during the training
- ② Error on train and held out/validation sets



Good fit in ML

- ① One can observe the behavior of the model during the training
- ② Error on train and held out/validation sets



- ③ Cross validation is often used for estimating the generalization (hence limit overfitting)

Capacity

- ① Vaguely, it is the ability to model an arbitrary function

Capacity

- ① Vaguely, it is the ability to model an arbitrary function
- ② More rigorous notion is VC dimension

Capacity

- ① Although it is difficult to define precisely, in practice it is not very hard to manipulate it for a given class of models

Capacity

- ① Although it is difficult to define precisely, in practice it is not very hard to manipulate it for a given class of models
- ② In general overfitting can be controlled by
 - Restricting the space of functions \mathcal{F} (regularization, constrained optimization)
 - Making the choice of optimal function f^* less dependent on the data (e.g. ensemble methods)

Polynomial Model

- ① Given a polynomial model

$$\forall x, \alpha_0, \dots, \alpha_D \in \mathcal{R}, f(x, \alpha) = \sum_{d=0}^D \alpha_d \mathbf{x}^d,$$

and a training set $(x_n, y_n) \in \mathcal{R}^2, n = 1, \dots, N$, the quadratic loss is

Polynomial Model

- ① Given a polynomial model

$$\forall x, \alpha_0, \dots, \alpha_D \in \mathcal{R}, f(x, \alpha) = \sum_{d=0}^D \alpha_d x^d,$$

and a training set $(x_n, y_n) \in \mathcal{R}^2, n = 1, \dots, N$, the quadratic loss is

②

$$\begin{aligned} \mathcal{L}(\alpha) &= \sum_n (f(x_n; \alpha) - y_n)^2 \\ &= \sum_n \left(\sum_{d=0}^D \alpha_d x_n^d - y_n \right)^2 \\ &= \left\| \begin{bmatrix} x_1^0 & \dots & x_1^D \\ \vdots & \ddots & \vdots \\ x_N^0 & \dots & x_N^D \end{bmatrix} \begin{bmatrix} \alpha_0 \\ \vdots \\ \alpha_D \end{bmatrix} - \begin{bmatrix} y_1 \\ \vdots \\ y_N \end{bmatrix} \right\|^2 \end{aligned}$$

Polynomial Model

- $$\underset{\alpha}{\operatorname{argmin}} \left\| \begin{bmatrix} x_1^0 & \dots & x_1^D \\ \vdots & \ddots & \vdots \\ x_N^0 & \dots & x_N^D \end{bmatrix} \begin{bmatrix} \alpha_0 \\ \vdots \\ \alpha_D \end{bmatrix} - \begin{bmatrix} y_1 \\ \vdots \\ y_N \end{bmatrix} \right\|^2$$

problem is a standard least squares

Polynomial Model- Prediction with degree

