



BUSINESS CONTINUITY

Business Continuity & Disaster Recovery Plan

Lightweight BC/DR for a founder-led startup. The VRU PLC operates autonomously — cloud downtime does not affect vapor recovery. Subprocessors provide platform resilience.

This plan documents the BC/DR arrangements for the Masar Zero VRU deployment. The key resilience property is that the VRU PLC operates autonomously — cloud downtime does not affect vapor recovery. Cloud-side resilience is delegated to subprocessors (Vercel, Supabase, WorkOS). Masar Zero does not conduct formal BC/DR exercises.

PREPARED BY	Masar Zero W.L.L.
DOCUMENT ID	MZ-POL-012
VERSION	v1.0
EFFECTIVE	12 July 2026
CLASSIFICATION	Confidential — Authorized Recipients Only

Document Control

Document ID	MZ-POL-012	Version	v1.0
Effective Date	12 July 2026	Review Cycle	Annual (next review: July 2027)
Document Owner	Dr. A. Latif Alkhaja	Classification	Confidential
Publisher	Masar Zero W.L.L.	Contact	hari@masarzero.com

Revision History

Version	Date	Author	Summary of Change
v1.0	12 July 2026	Masar Zero	Initial release of Business Continuity & Disaster Recovery Plan.

Approval

This document is prepared by Hari Krishna and approved by Dr. A. Latif Alkhaja, Chairman of Masar Zero W.L.L. It is effective as of the date shown above and is reviewed annually or upon significant change per MZ-POL-001 §7. Distribution is restricted to authorized recipients; redistribution requires written approval from Masar Zero leadership.

Role	Name	Signature	Date
Prepared by	Hari Krishna		
Approved by	Dr. A. Latif Alkhaja (Chairman)		

1. Purpose & Scope

This Business Continuity and Disaster Recovery (BC/DR) Plan defines the arrangements Masar Zero W.L.L. has in place to ensure that the Stage III Vapor Recovery Unit (VRU) deployment at customer service stations can survive and recover from disruptive incidents. It is aligned with ISO 22301 and NIST SP 800-34 as reference frameworks.

Honest scope statement. Masar Zero is a small founder-led startup. We do not conduct formal annual BC/DR exercises, tabletop simulations, or component restore tests. The key resilience property is that the VRU PLC operates autonomously — cloud downtime does not affect vapor recovery. Cloud-side resilience is delegated to subprocessors (Vercel, Supabase, WorkOS) which each operate their own BC/DR programs as part of their SOC 2 attestation.

2. Business Impact Assessment

The Masar Zero business impact assessment identifies the criticality of each component in the VRU deployment. Criticality is based on the operational impact of loss.

Component	Criticality	Impact of Loss	RTO	RPO
VRU + WeCon box	Critical	VRU cannot run; station vapor recovery stops.	4 hours (founder on-site visit)	0 (config is static)
Station-side router	High	Loss of telemetry to WeCon cloud; PLC continues autonomously.	24 hours	0
External Wi-Fi/cellular	Medium	Loss of cloud monitoring; PLC continues autonomously.	24 hours	0
WeCon cloud platform	Medium	Loss of telemetry ingestion; PLC continues autonomously.	Per WeCon SLA	Per WeCon retention
Masar Zero dashboard (Vercel)	Low	Remote monitoring unavailable; PLC continues autonomously.	Per Vercel SLA	0
Supabase (hourly aggregate)	Low	Historical data unavailable; live monitoring still works.	Per Supabase SLA	24 hours (last backup)
WorkOS (auth)	Low	No new logins possible; existing sessions continue.	Per WorkOS SLA	0

Table 1 — Business impact assessment with RTO/RPO targets.

VRU resilience by design. The VRU PLC is designed to operate autonomously — it continues vapor recovery even if the router, external Wi-Fi, WeCon cloud, Masar Zero dashboard, Supabase, or WorkOS is unavailable. The cloud is for *monitoring* and *remote configuration*, not for VRU control. This architectural choice means most disruption scenarios have low or zero operational impact on vapor recovery itself.

3. Backup Strategy

Masar Zero maintains backups for data that is not trivially reproducible. The backup strategy relies primarily on subprocessor platform features:

Asset	Backup Method	Frequency	Owner
Supabase operational data	Supabase automated backup + PITR	Daily + continuous	Supabase (subprocessor)
WeCon box configuration	Manual export to Google Sheet on change	On change	Founders
Masar Zero dashboard source code	GitHub repository	On every push	GitHub (subprocessor)
Founder documents	Google Workspace	Continuous	Google (subprocessor)
Founder credentials	1Password	Continuous	1Password (subprocessor)

Table 2 — Backup strategy by asset.

4. Recovery Procedures

Each disruption scenario has a documented recovery procedure. The procedures are lightweight and rely on subprocessor platform recovery features where possible.

4.1 Loss of Cloud (Vercel/Supabase/WorkOS)

If any subprocessor experiences a major outage: (a) founders become aware via the subprocessor status page or alert email; (b) the VRU PLC continues operating autonomously — no vapor recovery impact; (c) remote monitoring is unavailable for the duration of the outage; (d) local monitoring via the HMI at the station continues to work; (e) on subprocessor recovery, the dashboard resumes pulling hourly aggregates from WeCon cloud.

4.2 Loss of Station-Side Router

If the station-side router fails: (a) the VRU PLC continues operating autonomously — no vapor recovery impact; (b) telemetry to WeCon cloud stops; (c) founders become aware via dashboard alert (no new data); (d) a founder visits the station to replace the router (target RTO: 24 hours); (e) on router replacement, telemetry resumes.

4.3 Loss of External Wi-Fi/Cellular

If the external Wi-Fi/cellular uplink fails: (a) the VRU PLC continues operating autonomously; (b) telemetry to WeCon cloud stops; (c) if the outage exceeds 24 hours, a founder visits the station to troubleshoot or arrange an alternative uplink; (d) on uplink recovery, telemetry resumes.

4.4 Loss of Station Power

If station power is lost: (a) the PLC, HMI, and router are on the station UPS, which provides 30 minutes of runtime; (b) on UPS depletion, the PLC performs a controlled shutdown of the VRU; (c) on power restoration, the PLC, HMI, and router auto-boot and the VRU resumes operation. RTO: 30 minutes from power restoration.

4.5 Loss of Subprocessor

If a subprocessor (WorkOS, Vercel, Supabase, WeCon, Google Workspace, GitHub, 1Password) is permanently lost (e.g., business failure): (a) founders declare a P1 incident per MZ-POL-007; (b) founders activate the pre-identified alternative subprocessor (the alternatives are documented in the subprocessor register Google Sheet); (c) data is migrated from the failed subprocessor's export (or from Masar Zero backups if export is unavailable); (d) the dashboard is re-pointed to the alternative. RTO: 7 days for permanent migration.

5. Testing & Exercises

Masar Zero does not conduct formal BC/DR exercises, tabletop simulations, or component restore tests. This is a scope limitation acknowledged in the master questionnaire response. The key resilience property — VRU PLC operates autonomously — is verified informally whenever cloud downtime occurs (the VRU keeps running).

Subprocessor BC/DR testing is performed by the subprocessors themselves as part of their SOC 2 attestation: Vercel, Supabase, WorkOS, Google Workspace, GitHub, and 1Password each operate their own BC/DR programs with regular testing. Masar Zero relies on these tests.

6. Roles & Responsibilities

BC/DR roles: (a) founders are collectively accountable for the BC/DR plan; (b) founders execute the recovery procedures during a real incident; (c) customer site operations are notified for any disruption that affects VRU availability or requires station access.

7. Communication During Disruption

During a disruption, communication follows the incident response communication protocol (MZ-POL-007 §7). The incident commander (a founder) is the single point of contact for external communication. Customer site operations are notified within 4 hours of any disruption that affects VRU availability or requires station access. Customer vendor risk management is notified within 72 hours of any disruption declared a P1 or P2 incident.

8. References

- BAPCO-QR-001 — Master Questionnaire Response §8.15
- MZ-POL-001 — Governance Program
- MZ-POL-007 — Incident Response Plan
- MZ-POL-006 — Network Security
- ISO 22301:2019 — Business Continuity Management Systems (reference)
- NIST SP 800-34r1 — Contingency Planning Guide (reference)

MZ-POL-012 — Business Continuity & Disaster Recovery Plan. End of document.