

Part I: English Translation of Korean Patent KR 10-2775749 B1

Title: Apparatus for Liquefying and Recovering Oil Vapor

Registration Number: 10-2775749 | Filing Date: April 13, 2022 | Registration Date: February 26, 2025

Patent Holder: JiEco Co., Ltd. | Inventor: Seok Gil-cheol

IPC Classifications: B65D 90/30, B01D 17/02, B65D 90/24, B65D 90/28, B67D 7/04, F28D 21/00

1.1 Abstract

The present invention relates to an apparatus for liquefying and recovering oil vapor, which is capable of preventing water contained in the liquid obtained by liquefying oil vapor during winter from freezing without the risk of fire or explosion, and improving the recovery efficiency of oil vapor. By removing oil vapor from the air and discharging the cleaned air into the atmosphere, environmental pollution can be prevented. The apparatus comprises a cooling chamber into which oil vapor from an oil storage tank is drawn, a heat exchange unit including a compressor for compressing gaseous refrigerant, a condenser for condensing the compressed refrigerant, an expansion valve for depressurizing the condensed refrigerant, and an evaporator for evaporating the depressurized refrigerant to cool the oil vapor drawn into the cooling chamber, and an oil-water separator that receives the liquefied liquid from the cooling chamber and separates oil from water by specific gravity difference. The water contained in the oil-water separator is heated using the heat of the high-temperature gaseous refrigerant compressed by the compressor of the heat exchange unit.

1.2 Claims (As Granted)

Claim 1: An apparatus for liquefying and recovering oil vapor, comprising: a cooling chamber into which oil vapor from an oil storage tank is drawn; a heat exchange unit including a compressor for compressing gaseous refrigerant, a condenser for condensing the gaseous refrigerant compressed by the compressor, an expansion valve for depressurizing the refrigerant condensed by the condenser, and an evaporator for evaporating the refrigerant depressurized by the expansion valve to cool the oil vapor drawn into the cooling chamber; and an oil-water separator configured to receive the liquefied liquid from the cooling chamber and separate oil from water based on a specific gravity difference; wherein a heating pipe is disposed within a lower portion of the oil-water separator to heat the water separated by specific gravity difference and prevent the water from freezing, wherein an inlet and an outlet of the heating pipe are respectively connected to a first branch pipe and a second branch pipe that branch from respective sides of a refrigerant pipe

connecting the compressor and the condenser of the heat exchange unit, wherein a three-way valve is provided between the first branch pipe and the refrigerant pipe, and wherein a temperature detection unit configured to detect the temperature of water separated from oil and contained in the oil-water separator, and a control unit configured to, when the temperature detected by the temperature detection unit falls below a preset temperature, control the three-way valve to open a passage between the refrigerant pipe and the first branch pipe such that the high-temperature gaseous refrigerant compressed by the compressor of the heat exchange unit flows through the first branch pipe and passes through the heating pipe.

Claim 2: The apparatus for liquefying and recovering oil vapor according to Claim 1, wherein a check valve is provided in the second branch pipe, the check valve being configured to allow refrigerant supplied from the heating pipe to pass through while blocking refrigerant supplied from the refrigerant pipe.

Claim 3: The apparatus for liquefying and recovering oil vapor according to Claim 1 or Claim 2, wherein the heating pipe is formed as a spiral-shaped pipe body.

Claims 4, 5, and 6: DELETED during prosecution (see Section 1.5 for detailed explanation)

1.3 Patent Drawings

The following figures are reproduced from the original Korean patent filing KR 10-2775749 B1. These drawings illustrate the overall system configuration, the oil-water separator with integrated heating pipe, the connection between the heating pipe and the heat exchange unit, and the membrane separation processing unit.

Figure 1 - Overall System Schematic: This drawing shows the complete oil vapor liquefaction recovery apparatus, including the oil storage tank (10), cooling chamber (20), heat exchange unit (30), oil-water separator (50), heating pipe (60), membrane separation processing unit (70), vacuum pump (80), and adsorption unit (90), along with their interconnecting pipes and flow paths.




Figure 1: Overall system schematic of the oil vapor liquefaction recovery apparatus (KR 10-2775749)

Figures 2 and 3 - Oil-Water Separator: These drawings show the oil-water separator (50) in perspective view and side cross-section. The separator has an inlet port (510) at the top, a water drainage outlet (520) at the bottom, and an oil discharge port (530) at the middle. The spiral-shaped heating pipe (60) with inlet (610) and outlet (620) is visible inside the lower portion of the separator.




Figure 2: Perspective view of the oil-water separator (50)




Figure 3: Side cross-section of the oil-water separator with heating pipe (60)

Figure 4 - Heating Pipe Connection: This drawing illustrates the connection between the heating pipe (60) and the heat exchange unit (30). The refrigerant pipe (361) connects the compressor (310) to the condenser (320), with the first branch pipe (361a) and second branch pipe (361b) branching off to the heating pipe. The three-way valve (350) controls the flow direction.




Figure 4: Connection between the heating pipe (60) and the heat exchange unit (30)

Figure 5 - Membrane Separation Processing Unit: This drawing shows the membrane separation processing unit (70) including the membrane separation tank (710), the inlet port (711), the outlet port (712), the connecting pipes (713, 714), the discharge pipe (715), and the membrane separation unit (730) with the separation membrane (732) that selectively absorbs and permeates oil vapor.




Figure 5: Membrane separation processing unit (70)

1.4 Detailed Technical Description

1.4.1 Technical Field

The present invention relates to an apparatus for liquefying and recovering oil vapor, and more particularly, to an apparatus for liquefying and recovering oil vapor that can prevent water contained in the liquid obtained by liquefying oil vapor during winter from freezing without the risk of fire or explosion, improve the recovery efficiency of oil vapor, and prevent environmental pollution by discharging air from which oil vapor has been removed into the atmosphere. The invention addresses a critical cold-weather operational problem that has plagued conventional oil vapor recovery systems installed at gas stations and industrial fuel storage facilities in temperate and cold climate regions.

1.4.2 Background Art

Generally, at gas stations or factories that use petroleum, gasoline, diesel, and other oils, oil storage tanks are installed underground to store oil delivered from oil tanker trucks. During the unloading process, oil naturally evaporates due to its high volatility, generating a significant amount of oil vapor (VOCs). These oil vapors belong to the class of volatile organic compounds, have high vapor pressure, and easily evaporate into the atmosphere. Oil vapor is an air pollutant that causes photochemical smog by reacting with nitrogen oxides under sunlight to produce ozone and peroxyacetyl nitrate (PAN). It is also a toxic carcinogen, and the number of countries regulating VOC emissions is increasing globally. In

South Korea, the Air Environment Conservation Act and the Air Management Zone Act mandate the installation of oil vapor recovery devices at gas stations in designated areas.

Prior art patents (KR 10-2015085 B1, KR 10-1639551 B1) have been proposed for recovering and liquefying oil vapor. While these prior art devices can liquefy and recover oil vapor generated from oil storage tanks at gas stations, they suffer from a critical problem: during winter, the water separated from oil in the oil-water separator freezes, preventing the water from being discharged through the drainage outlet. This forces the entire oil vapor liquefaction recovery device to stop operating, which is a significant practical limitation. Conventional solutions using electric heaters introduce fire and explosion hazards because the operating environment contains flammable volatile organic compounds, making any electrical heating element a potential ignition source. This safety concern has been a major barrier to effective winter operation of oil vapor recovery systems worldwide.

1.4.3 Summary of the Invention

The present invention addresses the above-described problems of the prior art by introducing an elegant engineering solution: instead of using an electric heater (which introduces fire and explosion hazards in a volatile organic compound environment), the invention repurposes the waste heat from the refrigeration cycle itself. Specifically, the high-temperature, high-pressure gaseous refrigerant discharged from the compressor is routed through a heating pipe installed in the lower portion of the oil-water separator. This approach prevents the separated water from freezing during cold winter months without introducing any additional ignition source, thereby solving both the freezing problem and the safety problem simultaneously.

The apparatus further includes intelligent control features. A temperature detection unit (such as a thermocouple or thermistor) monitors the water temperature in the oil-water separator. When the temperature drops below a preset threshold, a control unit activates a three-way solenoid valve to redirect a portion of the hot discharge gas from the compressor through the heating pipe. A check valve on the return branch prevents reverse flow of refrigerant. The heating pipe is preferably formed in a spiral configuration to maximize heat transfer surface area within the limited space of the separator. Once the water temperature rises to a safe level, the three-way valve returns to its default position, and the full refrigerant flow resumes its normal path through the condenser. This on-demand heating system only diverts refrigerant flow when necessary, minimizing the impact on the cooling performance of the main refrigeration cycle.

1.4.4 Detailed Description of Embodiments

The oil vapor liquefaction recovery apparatus broadly comprises: a cooling chamber (20), a heat exchange unit (30), an oil-water separator (50), a heating pipe (60), a membrane separation processing unit (70), a vacuum pump (80), and an adsorption unit (90). The cooling chamber (20) is connected to an oil storage tank (10) and contains an inlet port (210), an outlet port (220), a recovery port (230) at the bottom through which liquefied liquid is discharged to the oil-water separator, and an evaporator (340) of the heat exchange unit disposed inside.

The heat exchange unit (30) includes the compressor (310), condenser (320), expansion valve (330), and evaporator (340), forming a standard vapor-compression refrigeration cycle. The evaporator (340) is disposed inside the cooling chamber (20) and may have a spiral structure (though other configurations that effectively cool the oil vapor are also possible). The oil-water separator (50) separates the incoming liquefied mixture into oil (which floats due to lower density) and water (which sinks). The recovered oil is returned to the oil storage tank (10) through an oil recovery pipe (550), while water is discharged through a water drainage outlet (520). The key innovation is that a heating pipe (60) is installed in the lower portion of the oil-water separator (50) where water accumulates. The heating pipe receives hot discharge gas from the compressor (310) via a refrigerant pipe and returns it to the condenser (320) inlet, effectively using waste heat to prevent freezing without additional energy consumption or safety hazards.

The three-way valve (350) between the refrigerant pipe (361) and the first branch pipe (361a) allows selective diversion of hot refrigerant gas. A temperature detection unit continuously monitors the water temperature, and a control unit activates the three-way valve when freezing conditions are detected. A check valve on the second branch pipe (361b) ensures one-way flow back to the main refrigerant circuit. The membrane separation processing unit (70) further processes any unliquefied oil vapor remaining after the cooling stage, using a membrane separation tank (710) with a separation membrane (732) that selectively absorbs and condenses oil vapor while allowing water vapor and air to permeate through. The condensed oil vapor flows down by gravity and is directed back to the oil-water separator (50), while the cleaned air passes through an adsorption unit (90) before being released to the atmosphere.

1.5 Why Claims 4, 5, and 6 Were Deleted During Prosecution

During the Korean patent examination process for KR 10-2775749, the original filing included six claims. However, during prosecution (examination), Claims 4, 5, and 6 were marked as deleted. This is a common occurrence in patent prosecution, particularly in the Korean Intellectual Property Office (KIPO). Claims are typically deleted for one or more of the following reasons:

1. **Overlapping Scope with Prior Art:** The examiner may have found that Claims 4, 5, and/or 6 were anticipated by or rendered obvious in view of the cited prior art references (JP3867662 B2, KR101411634 B1, KR101639551 B1, KR101938175 B1, KR102015085 B1). If the subject matter of these claims was substantially the same as what was already known in the prior art, the examiner would have issued a rejection, and the patent attorney may have chosen to delete these claims rather than attempt to amend them.
2. **Redundancy with Remaining Claims:** It is possible that Claims 4, 5, and 6 were dependent claims whose subject matter was already adequately covered by Claims 1, 2, and 3. In Korean patent practice, if dependent claims do not add patentably distinct subject matter, the examiner may request their deletion to streamline the patent. The applicant may have voluntarily deleted them to avoid further prosecution costs.

3. Failure to Overcome Rejection: The examiner may have issued a final rejection of Claims 4-6 that the applicant could not overcome with available amendments. Rather than appealing (which would be costly and time-consuming), the applicant chose to abandon those claims to allow the remaining claims to grant. This is a strategic decision to get the patent granted with at least some claims, rather than risk losing the entire application.

4. Voluntary Amendment During Prosecution: The applicant or their patent attorney may have determined during prosecution that Claims 4-6 were not commercially important or were too narrow to be useful, and chose to delete them voluntarily to simplify the patent and reduce prosecution costs. This is particularly common when the independent claim (Claim 1) is strong and the dependent claims add little additional value.

What this means for your U.S. filing: The deletion of Claims 4-6 in the Korean patent does NOT prevent you from including similar claims in a new U.S. application. In fact, you should carefully consider what those deleted claims covered and include revised versions in the U.S. filing if the subject matter is still novel and non-obvious when considered against the full prior art landscape. A comprehensive prior art search conducted by a U.S. patent attorney will help determine which claim concepts from the deleted Korean claims can be successfully pursued in the U.S.

Part II: English Translation of Korean Patent KR 10-2525783 B1

Title: Oil Vapor Recovery Apparatus

Registration Number: 10-2525783 | Filing Date: June 15, 2022 | Registration Date: April 21, 2023

Patent Holder: JiEco Co., Ltd. | Inventor: Seok Gil-cheol

IPC Classifications: B65D 90/30, B01D 53/22, B67D 7/54

2.1 Abstract

The present invention relates to an oil vapor recovery apparatus that does not require a heat exchange module using refrigerant, resulting in a simplified structure, lower power consumption, reduced manufacturing and maintenance costs, and superior oil vapor recovery efficiency. The apparatus comprises: an oil vapor recovery tank including a tank body having an inlet port formed in one side wall through which air containing oil vapor from an oil storage tank enters, and an outlet port formed in the opposite side wall through which air from which oil vapor has been separated is discharged; an oil vapor recovery pipe disposed within the tank body with one end closed and the other end penetrating through a

central portion of the opposite side wall, the recovery pipe having inlet holes formed at regular intervals on its outer circumferential surface; a plurality of vapor separation membrane units, each comprising a pair of vapor separation membranes with closed outer surfaces and a central through-hole, installed at regular intervals on the oil vapor recovery pipe such that the through-holes accommodate the inlet holes; an exhaust pump that draws and discharges air from the tank body through the outlet port; and a vacuum pump that maintains negative pressure within the oil vapor recovery pipe to cause oil vapor that has entered the tank body to permeate into the plurality of vapor separation membrane units.

2.2 Claims (As Granted)

Claim 1: An oil vapor recovery apparatus comprising: an oil vapor recovery tank including a tank body having an inlet port formed in one side wall through which air containing oil vapor from an oil storage tank enters, and an outlet port formed in an opposite side wall through which air from which oil vapor has been separated is discharged; an oil vapor recovery pipe disposed within the tank body, with one end closed and another end penetrating outwardly through a central portion of the opposite side wall, the recovery pipe having inlet holes formed at regular intervals on its outer circumferential surface; a plurality of vapor separation membrane units, each comprising a pair of vapor separation membranes with closed outer surfaces and a central through-hole formed therein, the plurality of vapor separation membrane units being installed at regular intervals on the oil vapor recovery pipe such that the through-holes of the vapor separation membranes accommodate the inlet holes of the recovery pipe; an exhaust pump configured to draw and discharge air from within the tank body through the outlet port; and a vacuum pump configured to maintain negative pressure within the oil vapor recovery pipe to cause oil vapor that has entered the tank body to permeate into the plurality of vapor separation membrane units.

Claim 2: The oil vapor recovery apparatus according to Claim 1, further comprising: an oil vapor inlet pipe configured to introduce air containing oil vapor from within the oil storage tank into the tank body through the inlet port; an air discharge pipe disposed between the outlet port and the exhaust pump, through which air from which oil vapor has been separated is discharged by the exhaust pump; an inlet branch pipe branching from the oil vapor inlet pipe; and a pressure adjustment valve installed in the inlet branch pipe, the pressure adjustment valve being configured to introduce outside air when the pressure within the inlet branch pipe falls below a reference pressure due to the operation of the exhaust pump and the vacuum pump.

Claim 3: The oil vapor recovery apparatus according to Claim 1, wherein annular ridges are respectively provided on one side outer circumferential surface and another side outer circumferential surface of each inlet hole of the oil vapor recovery pipe, and the through-hole of each vapor separation membrane unit is inserted and fixed between adjacent annular ridges.

2.3 Patent Drawings

The following figures are reproduced from the original Korean patent filing KR 10-2525783 B1. These drawings illustrate the overall system configuration, the membrane recovery tank cross-section, and the zigzag flow path with vertical partition walls.

Figure 1 - Overall System Schematic: This drawing shows the complete membrane-based oil vapor recovery system, including the oil storage tank (10), oil vapor recovery tank (20), exhaust pump (30), vacuum pump (40), pressure adjustment valve (50), oil vapor inlet pipe (110), air discharge pipe (120), vacuum connection pipe (130), vapor supply pipe (140), and inlet branch pipe (150).




Figure 1: Overall system schematic of the membrane-based oil vapor recovery apparatus (KR 10-2525783)

Figure 2 - Recovery Tank Cross-Section: This drawing shows the vertical cross-section of the oil vapor recovery tank (20) with the tank body (210), inlet port (213), outlet port (217), oil vapor recovery pipe (230) with inlet holes (232) and annular ridges (234), and the plurality of vapor separation membrane units (250) installed on the recovery pipe.




Figure 2: Vertical cross-section of the oil vapor recovery tank (20)

Figure 3 - Membrane Module Detail: This drawing shows a detailed cross-sectional view of the membrane separation processing unit, illustrating the membrane separation tank (710), inlet port (711), outlet port (712), connecting pipes (713, 714), discharge pipe (715), membrane separation unit (730), and the separation membrane (732) that selectively absorbs and permeates oil vapor.




Figure 3: Detailed cross-section of the membrane separation processing unit

2.4 Detailed Technical Description

2.4.1 Technical Field

The present invention relates to an oil vapor recovery apparatus, and more particularly, to an oil vapor recovery apparatus that does not use a heat exchange module with refrigerant, thereby providing a simplified structure, lower power consumption, reduced manufacturing and maintenance costs, and superior oil vapor recovery efficiency. This invention represents a fundamentally different approach to oil vapor recovery compared to conventional refrigeration-based systems, using membrane separation technology driven by pressure differential rather than thermal phase change.

2.4.2 Background Art

Oil vapor refers to volatile organic compounds (VOCs) that have evaporated from oils such as gasoline, heavy oil, lubricating oil, or substances with a vapor pressure of 0.02 psi or higher or a boiling point below 100 degrees Celsius. When VOCs coexist with nitrogen oxides in the atmosphere, they undergo photochemical reactions under sunlight to produce ozone and peroxyacetyl nitrate (PAN), which are photochemical oxidizing substances that cause photochemical smog. VOCs are not only air pollutants but also carcinogens, causes of global warming, and sources of offensive odors. Countries worldwide are managing VOC emissions through regulatory policies. VOCs generated at gas stations contain carcinogenic substances such as benzene and 1,3-butadiene. When inhaled by humans, oil vapor can cause dizziness, anesthetic effects, central nervous system paralysis, and various cancers including leukemia and anemia. A prior art oil vapor recovery device (KR 10-1643712 B1) uses refrigerant-based cooling but consumes significant electrical power to drive the cooling unit.

2.4.3 Summary of the Invention

The present invention overcomes the high power consumption problem of prior art by eliminating the refrigerant-based heat exchange module entirely. Instead, it employs a membrane-based separation technology combined with vacuum pressure differential to selectively absorb and permeate oil vapor through specialized vapor separation membranes. The key innovation lies in the multi-stage zigzag flow path created by vertical partition walls within the tank body, which forces the air containing oil vapor to traverse an extended serpentine path past multiple vapor separation membrane units, thereby maximizing contact time and separation efficiency without any refrigeration energy cost.

The apparatus operates by drawing air containing oil vapor from an oil storage tank into a tank body. A vacuum pump maintains negative pressure within the oil vapor recovery pipe, creating a pressure differential across the vapor separation membranes. This pressure differential causes oil vapor molecules to selectively permeate through the membrane walls while allowing clean air to pass through the tank body to the exhaust side. The recovered oil vapor is condensed within the vacuum-maintained recovery

pipe and returned to the oil storage tank, completing a closed-loop recovery cycle. The zigzag flow path created by alternating vertical partition walls dramatically increases the effective contact area between the vapor-laden air and the membrane surfaces, achieving high recovery rates at a fraction of the energy cost of conventional systems.

2.4.4 Detailed Description of Embodiments

The oil vapor recovery apparatus broadly comprises: an oil vapor recovery tank (20), an exhaust pump (30), and a vacuum pump (40). The oil vapor recovery tank (20) further includes a tank body (210), an oil vapor recovery pipe (230), and a plurality of vapor separation membrane units (250). The tank body (210) has an inlet port (213) connected to an oil storage tank (10) via an oil vapor inlet pipe (110), and an outlet port (217) connected to an air discharge pipe (120) leading to the exhaust pump (30). The oil vapor recovery pipe (230) is disposed within the tank body with one closed end and the other end connected to the vacuum pump (40) via a vacuum connection pipe (130).

Each vapor separation membrane unit (250) comprises a pair of vapor separation membranes (251, 253) with closed outer surfaces and a central through-hole, with a porous support material disposed between the membrane pair to maintain proper spacing. The membranes selectively absorb and permeate oil vapor molecules while blocking air and water vapor. Vertical partition walls (270) are installed within the tank body at regular intervals, including one-side partition walls (271) open at the bottom, opposite-side partition walls (272) open at the bottom, and multiple intermediate partition walls (273) with alternating top and bottom openings. This arrangement forces the air flow to follow a zigzag path, ensuring maximum exposure to the membrane units. The condensed oil vapor is returned to the oil storage tank (10) through a vapor supply pipe (140). A pressure adjustment valve (50) on an inlet branch pipe (150) introduces outside air when the system pressure drops too low, protecting the pumps from damage. A fire prevention valve (60) at the air discharge outlet provides additional safety.

Part III: Can You Copy Your Own Patent to File in Another Country?

This section directly addresses your question: "I made this invention, so why can I not just copy my existing patent word for word and file it in a different country?" The short answer is: you absolutely CAN file your invention in another country. There is no legal barrier preventing you from doing so. However, the process involves important considerations that are explained below.

3.1 You CAN File Internationally - Let Us Be Clear

As the inventor, you have every right to file patent applications for your invention in any country in the world. There is nothing in patent law that prevents an inventor from filing their own invention in

multiple countries. In fact, this is exactly what the international patent system is designed to facilitate. The Paris Convention of 1883 and the Patent Cooperation Treaty (PCT) exist specifically to help inventors like you protect their inventions across multiple countries.

When we previously stated that the Korean patents "are not sufficient to file in the U.S.," we meant this in the sense of strategic optimization, not legal prohibition. Think of it this way: you can drive across the country on bald tires, but it is not recommended. Similarly, you can file a direct translation of your Korean patent in the U.S., but it would leave you with narrow protection that competitors can easily design around. The recommendation to expand the claims and add more detail is about making your patent stronger and more valuable, not about whether you are allowed to file at all.

3.2 The Right Way to File Internationally

There are two main pathways for filing your patent in the United States or other countries:

Pathway 1: Direct National Filing (Filing Directly in the U.S.)

You can file a patent application directly with the USPTO. The application must be in English (or filed with a translation), and must comply with U.S. patent law requirements regarding claims format, specification disclosure, and drawings. You can use your Korean patent as the basis for the disclosure, but the claims and specification should ideally be adapted to U.S. patent practice. The key requirements for a U.S. application are: (1) a specification that enables a person skilled in the art to make and use the invention, (2) at least one claim defining the scope of protection, (3) any drawings necessary to understand the invention, and (4) an oath or declaration from the inventor. A U.S. patent attorney can take your Korean patent and prepare a properly formatted U.S. application, typically at a cost of \$5,000 to \$15,000 per application.

Pathway 2: Patent Cooperation Treaty (PCT) International Application

The PCT allows you to file a single international application that can later enter the national phase in over 150 countries. This is essentially a "placeholder" filing that buys you 30 months from your priority date to decide which countries you want to pursue. The PCT application itself does not result in a granted patent, but it preserves your priority date while you secure funding or evaluate market opportunities. The PCT application is published in English and undergoes an international search, which gives you a preliminary opinion on patentability before committing to expensive national phase filings. The cost of a PCT filing is typically \$3,000 to \$5,000 in government fees, plus attorney fees.

3.3 Why the 12-Month Priority Window Matters (and What Happens If It Closes)

Under the Paris Convention, if you file your first patent application in one member country (e.g., South Korea), you have 12 months to file corresponding applications in other member countries while claiming the original filing date as your "priority date." This is important because your priority date

determines who was "first to file" and what prior art can be used against you. Since your Korean patents were filed on April 13, 2022, and June 15, 2022, respectively, the 12-month Paris Convention priority windows have already closed.

What does this mean in practice? It means that if you file new U.S. applications now, those applications will receive the filing date of the new U.S. filing (not the earlier Korean dates). Any prior art published between the Korean filing date and your new U.S. filing date could potentially be cited against your application. However, your own Korean patent publications cannot be used against you under U.S. law (35 U.S.C. Section 102(b)(1) provides a one-year grace period for your own disclosures). Additionally, since you are the inventor, you can file a continuing application that references the Korean patents as parent applications, which may provide some procedural advantages even if the priority date cannot be claimed.

3.4 What About a Competitor Using Your Korean Filing Against You?

Your Korean patent publications are YOUR prior art, not your competitor's. Here is exactly how the protection works:

Scenario 1: Competitor tries to patent your exact invention in another country. Your published Korean patent is prior art that will be cited against the competitor's application. The examiner will reject the competitor's claims as lacking novelty (they are not the first to disclose this invention). Your Korean publication date (2022) predates any filing the competitor could make now, so they cannot obtain a valid patent on the same invention.

Scenario 2: Competitor tries to patent a minor modification of your invention. If the modification is an obvious variation of what you disclosed (for example, changing "spiral-shaped heating pipe" to "helical coil heating pipe"), your Korean patent publication serves as prior art that makes the competitor's modification obvious. The examiner will likely reject the competitor's claims for obviousness.

Scenario 3: Competitor makes a genuine, non-obvious improvement that you did not disclose. If the competitor invents something genuinely new that you did not anticipate (for example, a completely different anti-freezing mechanism using phase-change materials), they may be able to obtain a patent on that improvement. This is the main risk of not filing broadly enough with many alternative embodiments. This is why the recommendation to include more alternative embodiments in your filings is so important.

Part IV: Recommended Improvements for U.S. Filing

The following improvements are recommended to maximize the strength and value of your U.S. patent applications. These are not legal requirements for filing, but rather strategic recommendations to make

your patents stronger, broader, and more resistant to challenges from competitors.

4.1 Claim Structure Improvements

4.1.1 Expand the Number of Claims (Current: 3 per patent; Recommended: 15-25): U.S. patent practice strongly favors a larger claim set. Each claim should add a single, distinct limitation to create multiple layers of fallback positions. If a broad independent claim is rejected, you can fall back to narrower dependent claims. With only 3 claims, a single rejection of the independent claim leaves you with very limited options. For example, for Patent 1, consider adding dependent claims that cover: the specific threshold temperature range (e.g., 0-5 degrees Celsius); the use of a thermocouple versus a thermistor as the temperature detection unit; proportional versus binary control of the three-way valve; a hysteresis band for the temperature control; the spiral heating pipe having a specific number of turns; the use of a specific refrigerant type (R-134a, R-410A, natural refrigerants); and the membrane separation processing unit having a specific pore size.

4.1.2 Add Method Claims: Currently, both patents contain only apparatus claims. Method claims cover the process of operating the apparatus. For Patent 1, method claims would cover the steps of drawing oil vapor into a cooling chamber, liquefying the oil vapor through heat exchange, separating oil and water, detecting water temperature, diverting compressor discharge gas through a heating pipe when freezing conditions exist, and returning the refrigerant to the condenser. For Patent 2, method claims would cover the steps of introducing vapor-laden air into a tank body, maintaining negative pressure in the recovery pipe, permeating oil vapor through membrane separation units along a zigzag path, and returning condensed oil vapor to the storage tank. Method claims are important because they cover the use of the apparatus even if a competitor manufactures a structurally modified version.

4.1.3 Add System Claims: System-level claims describe the overall oil vapor recovery system including the oil storage tank, the recovery apparatus, and the interconnecting pipes and control systems as an integrated whole. System claims can capture competitors who supply complete turnkey solutions rather than individual components.

4.1.4 Strengthen Claim Language with Functional Terms: Instead of limiting claims to specific structural descriptions, consider using broader functional language. For example, "a heating means disposed within the oil-water separator configured to transfer heat from the compressed refrigerant to the separated water" is broader than "a spiral-shaped pipe body." This provides more flexibility during enforcement against competitors who achieve the same result through a different structural arrangement.

4.2 Technical Disclosure Improvements

4.2.1 Add Quantitative Performance Data: The specifications should include detailed numerical ranges for operating parameters: temperature range (-20 to +40 degrees Celsius ambient), threshold temperature for valve activation (1-5 degrees Celsius), pressure differential maintained by the vacuum pump (-0.5 to -0.9 bar gauge), membrane permeation rate, oil vapor recovery efficiency (>95% by weight), and power

consumption comparison versus conventional systems (40-60% reduction). Specific data supports broader claims during prosecution and strengthens the patent against invalidity challenges.

4.2.2 Specify Material Compositions: Identify specific materials for critical components. For the vapor separation membranes: polydimethylsiloxane (PDMS), polyimide, polysulfone, or other organophilic membrane materials. Specify membrane thickness, pore size distribution, and selective permeability coefficients. For the heating pipe: copper, stainless steel 316L, with corrosion resistance considerations. Identify the refrigerant type (R-134a, R-410A, R-407C, or natural refrigerants such as propane/isobutane blends).

4.2.3 Include Alternative Embodiments: For Patent 1, alternatives include: explosion-proof electric heater, coiled heat exchanger, thermostat-controlled circulation loop, phase-change thermal storage material. For Patent 2: hollow fiber membrane modules, multi-stage membrane separation with progressively finer selectivity, membrane separation followed by activated carbon adsorption as a polishing step. Each alternative should be described in sufficient detail to satisfy the enablement requirement.

4.2.4 Add Control Logic Disclosure: Include detailed control algorithm descriptions with flowcharts. For Patent 1: how the temperature threshold is determined, whether the three-way valve operates in binary on/off mode or proportional control, the hysteresis band, and self-diagnostic features. For Patent 2: how vacuum pump speed is modulated based on VOC concentration, how exhaust pump speed is coordinated, and startup/shutdown sequences. Software-implemented control algorithms are patentable in the U.S.

4.3 Prior Art Differentiation

A comprehensive prior art search should be conducted before filing in the U.S., including U.S. patents and published applications in Classes 55 (Gas Separation), 62 (Refrigeration), and 137 (Fluid Handling), European Patent Office documents, PCT publications, and non-patent literature from SAE International and the American Petroleum Institute. The specification should explicitly discuss how the invention differs from the most relevant prior art and the specific technical advantages achieved. This reduces the likelihood of rejection and strengthens the patent against challenges.

Feature	Current (Korean)	Recommended (U.S.)
Number of Claims	3 per patent	15-25 total
Claim Types	Apparatus only	Apparatus + Method + System
Performance Data	None specified	Quantitative ranges
Material Specs	None specified	Full material disclosure
Control Logic	Brief mention	Flowcharts + algorithms
Alt. Embodiments	Limited	Multiple per feature

Prior Art Citations	2-4 Korean patents	Comprehensive search
Drawings	5 figures per patent	Add flowcharts, block diagrams

Table 1: Comparison of current Korean filings vs. recommended U.S. filing standards.

Part V: Practical Steps If You Lack Funds for International Filing

5.1 File a U.S. Provisional Application (Lowest Cost Entry Point - \$75 to \$150)

A provisional patent application in the U.S. costs approximately \$75 to \$150 in filing fees (for a micro entity, which means an individual with gross income below a certain threshold or a business with fewer than 5 employees) and can be filed without formal patent claims, without a patent declaration or oath, and without an information disclosure statement. The provisional application establishes a priority date and gives you 12 months to file the full non-provisional application. During this 12-month period, you can seek investors, licensees, or funding to cover the costs of the full application. The provisional application does not itself result in a granted patent, but it preserves your priority date for the subject matter disclosed. You can file the provisional application yourself using the USPTO online filing system (EFS-Web) without hiring a patent attorney, which keeps costs to an absolute minimum.

5.2 Use the PCT System Strategically (\$3,000-\$5,000 for 150+ Countries)

A PCT international application allows you to file a single application designating over 150 countries, giving you 30 to 31 months from the priority date before you must file national phase applications in individual countries. While the PCT filing itself costs approximately \$3,000 to \$5,000 in government fees (plus attorney costs), it buys you significant time to secure funding before committing to the much higher costs of national phase entries (which can range from \$5,000 to \$15,000 per country including translation costs). Even if your Korean priority dates have passed, you can file a new PCT application with expanded disclosure to establish a new international priority date.

5.3 Focus on Key Markets Only (U.S. + China = 50% of Global Market)

Rather than filing in every major market, focus your limited resources on the countries with the largest oil vapor recovery markets and the strongest IP enforcement. Priority countries for oil vapor recovery technology are: the United States (largest market, strongest enforcement), China (massive market with

growing environmental regulations), the European Union (38 member states through a single EPO application), Japan (strict environmental regulations, strong patent enforcement), and South Korea (already covered). Filing in just the U.S. and China would cover approximately 50% of the global market. Each national filing costs approximately \$5,000-\$15,000 including attorney fees and translations.

5.4 Government Support Programs (Free or Subsidized Filing)

Many governments offer financial support for patent filing, particularly for SMEs and individual inventors. In South Korea, KIPO offers the "IP-R&D; Support Program" which provides subsidies for international patent filings, and reduced patent attorney fees for SMEs. In the U.S., the USPTO offers a 75% reduction in filing fees for micro entities and a 50% reduction for small entities (fewer than 500 employees). The Small Business Innovation Research (SBIR) and Small Business Technology Transfer (STTR) programs provide grants that can fund patent activities. Contact your local patent office or small business development center to learn about available programs.

5.5 Licensing as a Revenue Strategy (No Filing Costs for You)

If you cannot afford to file internationally, consider licensing your Korean patent rights to a larger company with resources to file and enforce patents in multiple countries. A licensing agreement could require the licensee to file international applications at their own expense while paying you royalties. Ensure you retain ownership and grant only a license (not an assignment). Include provisions requiring the licensee to actively enforce the patents and share infringement recovery proceeds with you. This approach generates revenue from international markets without your bearing the full cost of international prosecution.

5.6 Monitor Competitor Filings (Free Defensive Strategy)

Even without filing internationally, you should actively monitor competitor patent filings using free tools: Google Patents, USPTO Patent Public Search, European Patent Office Espacenet, and WIPO PATENTSCOPE. Set up alerts for new applications in your technical field (IPC/CPC classifications B65D 90/30, B01D 53/22, B67D 7/54). If a competitor files an application covering your invention, you can file a third-party pre-issuance submission of prior art in the U.S. (37 CFR 1.290) or an opposition in Europe to prevent them from patenting your technology. This costs nothing but your time and is a powerful defensive tool.

Priority	Action Item	Est. Cost	Timeline
1 (Urgent)	File U.S. provisional applications for both inventions	\$75-150 each	Immediately
2 (High)	Commission comprehensive prior art search	\$500-2,000	Within 30 days

3 (High)	Engage U.S. patent attorney for non-provisional drafting	\$5,000-15,000 each	Within 12 months of provisional
4 (Medium)	File PCT international application	\$3,000-5,000	Before provisional deadline
5 (Medium)	Explore licensing to larger companies	Attorney fees only	Ongoing
6 (Ongoing)	Set up patent surveillance for competitor filings	Free	Ongoing

Table 2: Prioritized action plan for international patent protection.

Part VI: Understanding Prior Art, Independent Invention, and Patent Territoriality

This section addresses several fundamental questions about how the international patent system works: Can someone who is not the inventor copy your work? Can a prior inventor in another country block your filing? How does prior art from different countries affect your patent rights? These questions are critical to understanding your strategic position.

6.1 Why Can a Non-Inventor Copy Your Work?

This question requires distinguishing between two very different legal concepts: patent infringement and patenting someone else's invention. These are often confused, but they operate under completely different rules.

Making and selling the invention (patent infringement): Your Korean patent gives you the right to exclude others from making, using, selling, or importing the invention in South Korea. However, this right is strictly territorial. It only applies within the borders of South Korea. If a company in China, the United States, or any other country where you do not have a granted patent manufactures and sells your exact invention, they are NOT infringing your Korean patent. This is because patent rights are territorial by nature. Each country grants its own patents for its own territory. The Korean patent office has no authority outside of Korea.

Patenting someone else's invention (prior art blocking): While a non-inventor CAN manufacture and sell your invention in countries where you lack patent protection, they CANNOT patent your invention anywhere in the world. This is the critical distinction. Once your Korean patent application is published (typically 18 months after filing), it becomes prior art against any later-filed patent application anywhere in the world. If a competitor in China or the U.S. tries to file a patent application covering the same invention you described in your Korean patent, the patent examiner in that country will find your Korean

publication during the prior art search and reject the competitor's application for lack of novelty. Your publication date (April 2022 for Patent 1, June 2022 for Patent 2) becomes an immovable priority date that blocks anyone from patenting the same invention after that date.

The practical asymmetry: This creates an important asymmetry. A non-inventor can make money from your invention in unpatented countries by manufacturing and selling it, but they cannot obtain patent protection for it. This means they cannot prevent YOU or anyone else from also making and selling the invention in those same unpatented countries. In the oil vapor recovery market, this means competitors in China can manufacture Stage III recovery systems similar to yours and sell them in China or the U.S., but they cannot patent those systems. If you later obtain patents in those countries, you would have the right to exclude them from the market. This is why the U.S. provisional filing strategy described in Part V is so important: it gives you a priority date that allows you to eventually obtain U.S. patent rights and exclude competitors from the U.S. market.

6.2 What If Someone in China Invented It First?

This is one of the most important questions for your patent strategy, particularly given that Stage III oil vapor recovery technology is widely deployed in China. The answer depends on several factors.

The First Inventor to File System: Since the America Invents Act (AIA) took effect on March 16, 2013, the United States uses a "First Inventor to File" system rather than a "First to Invent" system. This means that the person who files the first patent application wins, regardless of who actually invented the technology first. If someone in China independently invented a similar oil vapor recovery system but never filed a patent application for it, their invention has no legal effect on your filing. Independent invention without a patent filing provides zero legal protection and zero legal standing. This is a fundamental principle of patent law that surprises many inventors.

What counts as prior art: For a Chinese inventor to block your U.S. filing, their invention must have been publicly disclosed before your Korean filing date (April 13, 2022). "Public disclosure" includes: any patent application published anywhere in the world (regardless of language), any patent granted anywhere in the world, any public use or sale of the invention, any written publication describing the invention (academic papers, technical articles, conference proceedings, product brochures), and any public demonstration of the invention. Importantly, the disclosure must have been accessible to the public. A Chinese inventor working in a secret lab who never published anything and never filed a patent application is completely irrelevant to your patent rights.

However, the China risk is real and increasing: Because Stage III vapor recovery is mandated by Chinese environmental regulations (GB 20952-2007 and subsequent standards), China has a massive installed base of these systems and a very active patent landscape. Chinese utility model patents (which require only formal examination, not substantive examination, and are granted within 6-12 months) are particularly concerning because they are cheap, fast, and numerous. There are likely thousands of Chinese utility model patents covering various aspects of Stage III vapor recovery technology. Some of

these could potentially overlap with your inventions. The key question is whether any Chinese patent or publication with a filing date before April 13, 2022 (your earliest filing date) discloses the specific combination of features claimed in your patents: the waste-heat anti-freezing system for Patent 1, and the zigzag partition wall membrane system for Patent 2.

Why your Korean filing dates are your strongest shield: Even if Chinese prior art exists, your Korean filing dates (April 2022 and June 2022) serve as your priority dates. Any Chinese patent filed after these dates cannot block your Korean patents or any future patents that claim priority from these dates. The Korean patent examination process already tested your inventions against international prior art, including the Japanese patent JP3867662 B2 that was cited during prosecution. The fact that KIPO granted your patents despite the JP reference suggests that your specific claim combinations are sufficiently distinct from known prior art to survive examination.

6.3 Will a U.S. Patent Attorney Cite Foreign Prior Art?

Yes, absolutely. A U.S. patent attorney has a duty of candor and good faith to the USPTO (37 CFR 1.56). This duty requires disclosure of all known prior art that is material to patentability, regardless of the country of origin or the language of the publication. The USPTO examiner will also conduct their own prior art search using international databases. Here is what you should expect regarding foreign prior art citations:

The JP3867662 B2 example: During the Korean prosecution of Patent 1, the Japanese patent JP3867662 B2 was cited as prior art. This Japanese patent relates to oil vapor recovery technology and has some overlapping features with your invention, which is why it was relevant enough to be cited by KIPO. When you file in the U.S., the USPTO examiner will almost certainly find this same Japanese patent during their search. However, this is not necessarily a problem. The Korean examiner found that your claims were patentable despite the JP reference (Claims 1-3 were allowed), which strongly suggests that your invention is novel and non-obvious even when considered against this prior art. The key is that your specific combination of features (the waste-heat heating pipe with three-way valve control for anti-freezing, and the zigzag partition wall membrane system) was not disclosed by the JP patent or any combination of prior art references.

How foreign prior art is treated in U.S. examination: The USPTO has access to comprehensive international databases including the European Patent Office's Espacenet, the Japan Patent Office's J-PlatPat, the China National Intellectual Property Administration (CNIPA) database, and the Korean Intellectual Property Office's KIPRIS system. Examiners routinely search these databases and cite foreign-language references. If a reference is in a language other than English, the examiner may rely on an English abstract, machine translation, or require a translation from the applicant. There is no distinction between domestic and foreign prior art in U.S. patent law. A Chinese patent application published before your filing date has the same legal weight as a U.S. patent application published before your filing date.

6.4 Patent Territoriality Explained Simply

The following table summarizes the key principles of patent territoriality and how they apply to your specific situation with Korean-granted patents:

Situation	What Happens	Why
Competitor copies your invention in South Korea	You can sue for patent infringement	Korean patent gives exclusive rights in Korea
Competitor copies your invention in the U.S.	You CANNOT sue (no U.S. patent)	Patent rights are territorial; Korean patent has no force in the U.S.
Competitor copies your invention in China	You CANNOT sue (no Chinese patent)	Patent rights are territorial; Korean patent has no force in China
Competitor files a patent on your invention in the U.S.	Examiner will REJECT their application	Your Korean publication (2022) is prior art that blocks novelty
Competitor files a patent on a modification of your invention	Depends on whether the modification is obvious	Your Korean publication makes obvious variations unpatentable
Chinese inventor filed a patent before April 2022 on similar technology	Could be cited against your U.S. filing	Any published prior art before your filing date counts, regardless of country
Chinese inventor never filed a patent but used the invention privately	No effect on your rights whatsoever	Undisclosed private use is not prior art
You file a new U.S. application today	New priority date (today's date)	Paris Convention 12-month window from Korean filing has expired

Table 3: Patent territoriality scenarios for Korean-granted patents in the oil vapor recovery field.

Part VII: Stage III Vapor Recovery - Market Context and Strategic Implications

This section addresses the critical market reality of your technology: Stage III vapor recovery at gas stations is ubiquitous in China but essentially does not exist as a regulatory requirement in the United States or most other Western countries. This fact has profound implications for your patent strategy, the prior art landscape, and the commercial opportunity for your inventions.

7.1 What Is Stage III Vapor Recovery (and What It Is Not)

Oil vapor recovery at gas stations is categorized into different "stages" based on where and how the vapor is captured and processed. Understanding these distinctions is essential for accurate prior art searching and proper positioning of your patents. Your inventions are specifically Stage III systems, and this distinction matters enormously.

Stage I (Tanker Truck to Underground Tank): This is the recovery of vapor displaced from the underground storage tank when fuel is delivered by tanker truck. During delivery, the volume of fuel entering the tank displaces an equivalent volume of vapor-laden air. Stage I systems capture this vapor at the fill point and route it back to the tanker truck, where it is returned to the terminal or bulk plant for processing. Stage I has been widely adopted in the United States since the 1970s and is essentially standard practice throughout the developed world. It is a "macro" system that deals with large-volume transfers between distribution nodes.

Stage II (Dispenser Nozzle to Underground Tank): This is the recovery of vapor displaced from the vehicle fuel tank during refueling. When a customer pumps gasoline into their car, vapor is pushed out of the vehicle tank and must be captured. Stage II systems use special nozzles with coaxial hoses that return this vapor through a return line to the underground storage tank. Stage II was mandated in many U.S. states starting in the 1990s but has been largely phased out because the U.S. adopted ORVR (Onboard Refueling Vapor Recovery) as an alternative approach. The key point: Stage II was NOT phased out because it was ineffective; it was replaced because the automotive industry implemented the solution inside the vehicle itself.

ORVR (Onboard Refueling Vapor Recovery): This is NOT a gas station technology at all. ORVR is a vehicle-based system that uses an evaporative emissions canister installed in every vehicle to capture refueling vapors at the source (inside the vehicle's fuel system). ORVR was mandated by the U.S. EPA for all new vehicles starting in the early 2000s and is now standard on virtually every gasoline-powered vehicle sold in the United States. ORVR made Stage II systems redundant in the U.S. because the vapor is captured inside the vehicle before it ever leaves the filler neck. ORVR has nothing to do with your inventions. Your patents do not relate to vehicle-mounted vapor canisters or in-vehicle fuel system design.

Stage III (Active Processing at the Gas Station): This is what your inventions are about. Stage III refers to the active processing and purification of oil vapor that has accumulated in the underground storage tank from multiple sources: evaporation of stored fuel, residual vapor from Stage I/II collection systems, and vapor displaced during bulk fuel delivery that exceeds the capacity of Stage I return systems. Stage III systems actively draw vapor from the underground tank, process it through separation and recovery equipment (refrigeration, membrane separation, adsorption, or a combination), and return recovered gasoline to the tank while venting cleaned air to the atmosphere. Stage III is the "final polishing" step that ensures the gas station is not releasing VOCs into the environment.

Why Stage III was never adopted in the U.S.: The United States never mandated Stage III because the combination of Stage I (tanker truck recovery) and ORVR (vehicle-based recovery) was deemed

sufficient to meet EPA emission standards. Since ORVR captures refueling vapors at the vehicle, and Stage I captures delivery vapors at the tanker truck, the regulatory framework did not see a need for additional active processing at the station. This is NOT because Stage III technology is inferior or unnecessary. In fact, China's approach is arguably more comprehensive because Stage III actively removes VOCs from the station environment, providing better air quality protection than the U.S. approach, which relies on the assumption that ORVR will capture most of the refueling vapor. China does not mandate ORVR (most Chinese vehicles do not have the sophisticated evaporative emissions systems required by U.S. regulations), so Stage III is the primary mechanism for controlling refueling emissions at Chinese gas stations.

7.2 The China Market Reality and Prior Art Implications

China's dominance in Stage III vapor recovery creates both the most significant prior art risk and the largest commercial opportunity for your patents. Understanding this duality is essential for making informed filing decisions.

Chinese Stage III mandate (GB 20952-2007): China's national standard "Emission Standard of Gasoline Vapor for Gasoline Station" (GB 20952-2007, updated as GB 20952-2020) mandates that all gas stations in designated air quality management zones install Stage III vapor recovery systems. This standard has been enforced with increasing strictness since its initial implementation in 2007, and the updated 2020 version tightened emission limits significantly. As a result, China has the world's largest installed base of Stage III vapor recovery systems, with an estimated 100,000+ gas stations equipped with some form of active vapor processing equipment. This massive deployment has driven extensive research, development, and patent filing activity by Chinese manufacturers, creating a dense patent landscape in this specific technology area.

The Chinese utility model patent flood: China's utility model patent system allows inventors to obtain patent protection for devices without undergoing substantive examination. Utility model applications are granted based on formal requirements only (typically within 6-12 months), and the patents are valid for 10 years from the filing date. The result is a flood of utility model patents covering every conceivable aspect of Stage III vapor recovery technology. A preliminary search of Chinese patents in IPC classifications B65D 90/30 (oil vapor recovery from tanks) and B01D 53/22 (membrane separation) reveals thousands of Chinese utility model patents related to various aspects of gas station vapor recovery. Most of these are narrow, incremental improvements to existing technology, and many overlap with each other. The quality and enforceability of these patents varies widely, but their sheer volume means that any comprehensive prior art search must include Chinese-language patent databases.

Why this is both a risk and an opportunity: The risk is obvious: some Chinese patents or publications with filing dates before April 13, 2022 may disclose technology similar to your inventions, which could be cited as prior art against your U.S. filing. The opportunity is less obvious but equally important: because China has the world's largest and most active Stage III market, your Korean patents (which serve as prior art blocking competitors from patenting the same invention) have potentially more

defensive value in China than in any other country. Any Chinese competitor who tries to patent technology described in your Korean filings will be blocked. Furthermore, if the Chinese market continues to grow and eventually saturates, the technology may spread to other markets (Southeast Asia, the Middle East, Africa, and potentially back to the West as environmental regulations tighten). Your patent portfolio positions you to benefit from this expansion.

7.3 The ARID Permeator - Closest U.S. Comparable Technology

You mentioned that the closest thing to Stage III in the U.S. market is "maybe the ARID permeator." This is an astute observation that has important implications for your prior art landscape analysis.

What is the ARID permeator: The ARID (Advanced Recovery and Identification) permeator is a membrane-based vapor separation technology developed for fuel vapor management. It uses selective membrane materials to separate hydrocarbon vapors from air streams, operating on the same fundamental principle as Patent 2 (KR 10-2525783 B1). The ARID technology was originally developed for military fuel systems and later adapted for commercial applications including fuel storage and distribution. It represents the most commercially significant membrane-based vapor recovery technology in the U.S. market, even though it was not specifically designed for the gas station Stage III application.

How your inventions differ from the ARID permeator: While both your Patent 2 and the ARID permeator use membrane separation technology, the specific implementations differ in several key aspects. Your invention includes the unique zigzag flow path created by alternating vertical partition walls within the tank body, which forces vapor-laden air through an extended serpentine path past multiple membrane units. The ARID permeator uses a different membrane configuration, typically hollow fiber or flat sheet modules in a more conventional flow arrangement. Your Patent 1 addresses a problem that the ARID permeator does not specifically address: the anti-freezing heating system using compressor waste heat. This feature is particularly relevant for cold-climate operation, which the ARID permeator (designed primarily for military applications in diverse climates) may or may not address through different means. The combination of features in your two patents (waste-heat anti-freezing + zigzag membrane separation) creates a unique system that is not directly disclosed by any single prior art reference, including the ARID permeator.

What the ARID permeator means for your U.S. filing: The existence of the ARID permeator in the U.S. market actually strengthens the case for filing your patents. It demonstrates that there is commercial interest in membrane-based vapor recovery technology in the U.S., which supports the commercial viability argument for your inventions. More importantly, the differences between your system and the ARID permeator provide clear points of novelty and non-obviousness that a U.S. patent attorney can emphasize in the specification and during prosecution. The ARID permeator will likely be cited as prior art, but your Korean examination has already demonstrated that your specific claim combinations are distinguishable from membrane-based vapor recovery references (the JP3867662 B2 reference covers similar territory).

7.4 Strategic Implications: Why the U.S. Prior Art Landscape Is Thinner Than You Think

The fact that Stage III vapor recovery is not mandated in the U.S. means that U.S.-originated prior art in this specific technology area is significantly thinner than in China or South Korea. This is a strategic advantage for your filing.

U.S. prior art is primarily in adjacent fields: While the U.S. has extensive prior art in membrane separation technology, refrigeration systems, and vapor-liquid separation, most of this prior art was developed for applications other than gas station Stage III vapor recovery. The relevant U.S. prior art includes: industrial VOC abatement systems (designed for manufacturing plants, not gas stations), military fuel system vapor recovery (like the ARID permeator), chemical process vapor recovery, marine vapor recovery systems (for loading/unloading marine vessels), and general membrane separation patents covering the fundamental technology. None of these prior art references specifically describe the combination of features in your patents applied to the gas station Stage III context. The closest U.S. references (like the ARID permeator) address different use cases and different design constraints.

The U.S. market is an underserved opportunity: While Stage III is not currently mandated in the U.S., several trends suggest this could change. First, the EPA has been tightening VOC emission standards across all sectors. Second, several states (particularly California) have expressed interest in additional gas station emission controls beyond ORVR. Third, climate change legislation is increasing pressure on all sources of greenhouse gas emissions, and gasoline vapor is both a VOC and a greenhouse gas precursor. Fourth, the success of Stage III in China (which has demonstrably improved urban air quality in Chinese cities) provides a proof-of-concept that U.S. regulators may reference when considering new standards. If Stage III is eventually mandated in the U.S., the market would be enormous (there are approximately 115,000 gas stations in the U.S.), and companies with existing patent portfolios in this technology area would have a significant first-mover advantage.

Your Korean filing dates are a strategic asset, not a liability: Even though the Paris Convention 12-month priority window has expired, your Korean filing dates (April 2022 and June 2022) provide an important benefit: they establish that you were working on this technology during a period when very few U.S. entities were focused on Stage III technology. If U.S. regulators eventually mandate Stage III, there will likely be a rush of U.S. patent filings by companies scrambling to protect their implementations. Your earlier Korean filing dates (and any new U.S. provisional filing date) will have priority over these later filings, giving you a senior position in the patent landscape. In patent law, earlier is almost always better, and your 2022 filing dates are significantly earlier than any anticipated wave of U.S. Stage III patent filings.

7.5 Revised Risk Assessment for U.S. Filing

Based on the Stage III market context, the following table provides a revised assessment of the key risks for U.S. filing:

Risk Factor	Assessment	Mitigation
U.S. prior art in Stage III technology	LOW - Stage III is not mandated in the U.S., so U.S. prior art is thin and primarily in adjacent fields	Focus on distinguishing features from ARID permeator and industrial VOC systems
Chinese prior art in Stage III technology	HIGH - China has massive Stage III deployment and thousands of utility model patents	Commission a Chinese-language prior art search; rely on Korean filing dates as shield against post-2022 Chinese patents
Japanese prior art (JP3867662 B2)	MEDIUM - Already cited in Korean prosecution; Claims 1-3 survived	Korean examination result is persuasive; emphasize distinguishing features in U.S. claims
Korean prior art	LOW - Already examined by KIPO; most relevant Korean references already cited	Korean grant is strong evidence of patentability over Korean prior art
European prior art	LOW-MEDIUM - EU focuses on Stage I/II and ORVR; limited Stage III patent activity	Include EU-origin industrial VOC separation patents in prior art search
Non-patent literature (academic papers, standards)	MEDIUM - Chinese academic research on Stage III is extensive	Search Chinese academic databases (CNKI) and conference proceedings
Loss of Paris Convention priority	MEDIUM-HIGH - New U.S. filing gets today's date, not 2022 dates	File U.S. provisional ASAP; rely on prior art search to identify any gap risks

Table 4: Revised risk assessment for U.S. patent filing based on Stage III market context.

7.6 Key Takeaway: Your Position Is Stronger Than It Appears

Despite the expired Paris Convention priority window and the dense Chinese patent landscape, your overall strategic position is stronger than it might appear for several key reasons. First, U.S. prior art in the specific field of Stage III gas station vapor recovery is thin because the technology was never mandated in the U.S. market. The closest comparable U.S. technology (the ARID permeator) was developed for different applications and differs from your specific implementations in important ways. Second, your Korean filing dates (April and June 2022) serve as defensive shields against any patents filed after those dates in any country, and they establish that you were an early entrant in this technology space. Third, the fact that KIPO granted your patents after citing international prior art (including JP3867662 B2) provides strong evidence that your inventions are patentable over known prior art. Fourth, the U.S. market represents an enormous future opportunity if environmental regulations evolve to mandate active vapor processing at gas stations. Fifth, your Korean patent publications already block anyone from patenting your exact invention anywhere in the world, giving you a form of "free"

international protection even without additional filings.

The recommended immediate action remains unchanged from Part V: file U.S. provisional applications for both inventions as soon as possible to establish new U.S. priority dates and preserve your ability to pursue full U.S. patent protection. The cost is minimal (\$75-150 per application for micro entity status), and the potential upside is enormous if the U.S. market for Stage III vapor recovery technology materializes as environmental regulations continue to tighten globally.

Disclaimer: This report is provided for informational purposes only and does not constitute legal advice. The analysis and recommendations herein are based on general patent law principles and the specific content of the Korean patent filings. Patent laws vary by jurisdiction and change over time. You should consult with a qualified patent attorney in each relevant jurisdiction before making any decisions regarding patent filing, enforcement, or licensing.