

C++ Template

한양대학교 컴퓨터소프트웨어학부
2017년 2학기



◆ C++ templates

- Allow very "general" definitions for functions and classes
- Type names are "parameters" instead of actual types

Polymorphism

◆ One of four polymorphisms in C++:

- Subtype polymorphism
 - Runtime polymorphism
- Parametric polymorphism (C++ template !!)
 - Compile-time polymorphism
- Ad-hoc polymorphism
 - Overloading
- Coercion polymorphism
 - (Implicit or explicit) casting

Function Templates

- ◆ Recall function swapValues:

```
void swapValues(int& var1, int& var2)
{
    int temp;
    temp = var1;
    var1 = var2;
    var2 = temp;
}
```
- ◆ Applies only to variables of type int
- ◆ But code would work for any types!

Function Templates vs. Overloading

- ◆ Could overload function for char's:

```
void swapValues(char& var1, char& var2)
{
    char temp;
    temp = var1;
    var1 = var2;
    var2 = temp;
}
```
- ◆ But notice: code is nearly identical!
 - Only difference is type used in 3 places

Function Template Syntax

- ◆ Allow "swap values" of any type variables:

```
template<class T>
void swapValues(T& var1, T& var2)
{
    T temp;
    temp = var1;
    var1 = var2;
    var2 = temp;
}
```

- ◆ First line called "template prefix"

- Tells compiler what's coming is "template"
- And that T is a type parameter

Template Prefix

- ◆ Recall:
template<class T>
- ◆ In this usage, "class" means "type", or "classification"
- ◆ Can be confused with other "known" use of word "class"!
 - C++ allows keyword "typename" in place of keyword "class" here
 - But most use "class" anyway

Template Prefix 2

- ◆ Again:
 `template<class T>`
- ◆ T can be replaced by any type
 - ▣ Predefined or user-defined (like a C++ class type)
- ◆ In function definition body:
 - ▣ T used like any other type
- ◆ Note: can use other than "T", but T is "traditional" usage

Function Template Definition

- ◆ swapValues() function template is actually large "collection" of definitions!
 - A definition for each possible type!
- ◆ Compiler only generates definitions when required
 - But it's "as if" you'd defined for all types
- ◆ Write one definition → works for all types that might be needed

Calling a Function Template

- ◆ Consider following call:
 `swapValues(int1, int2);`
 - C++ compiler "generates" function definition for two int parameters using template
- ◆ Likewise for all other types
- ◆ Needn't do anything "special" in call
 - Required definition automatically generated

Generic Programming

Generic programming is a style of computer programming in which algorithms are written in terms of **to-be-specified-later** types that are then instantiated when needed for specific types provided as parameters.^[wikipedia]

- C++ Standard Template Library (STL).
- Data containers such as matrix, vector, array, image, etc.
- Algorithms such as sorting, searching, hashing, etc.
- ...

Generic Programming

```
// Suppose we want to sort an integer array.
```

```
void SelectionSort(int* array, int size) {  
    for (int i = 0; i < size; ++i) {  
        int min_idx = i;  
        for (int j = i + 1; j < size; ++j) {  
            if (array[min_idx] > array[j])  
                min_idx = j;  
        }  
        // Swap array[i] and array[min_idx].  
        int tmp = array[i];  
        array[i] = array[min_idx];  
        array[min_idx] = tmp;  
    }  
}
```

Generic Programming

// Suppose we want to sort an integer array.

```
void SelectionSort(int* array, int size) {
    for (int i = 0; i < size; ++i) {
        int min_idx = i;
        for (int j = i + 1; j < size; ++j) {
            if (array[min_idx] > array[j])
                min_idx = j;
        }
        // Swap array[i] and array[min_idx].
        int tmp = array[i];
        array[i] = array[min_idx];
        array[min_idx] = tmp;
    }
}
```

// We also want to sort a double array.

```
void SelectionSort(double* array, int size) {
    for (int i = 0; i < size; ++i) {
        int min_idx = i;
        for (int j = i + 1; j < size; ++j) {
            if (array[min_idx] > array[j])
                min_idx = j;
        }
        double tmp = array[i];
        array[i] = array[min_idx];
        array[min_idx] = tmp;
    }
}
```

Generic Programming

```
// Suppose we want to sort an integer array.
```

```
void SelectionSort(int* array, int size) {  
    for (int i = 0; i < size; ++i) {  
        int min_idx = i;  
        for (int j = i + 1; j < size; ++j) {  
            if (array[min_idx] > array[j])  
                min_idx = j;  
        }  
        // Swap array[i] and array[min_idx].  
        int tmp = array[i];  
        array[i] = array[min_idx];  
        array[min_idx] = tmp;  
    }  
}
```

```
// We also want to sort a double array.
```

```
void SelectionSort(double* array, int size) {  
    for (int i = 0; i < size; ++i) {  
        int min_idx = i;  
        for (int j = i + 1; j < size; ++j) {  
            if (array[min_idx] > array[j])  
                min_idx = j;  
        }  
        double tmp = array[i];  
        array[i] = array[min_idx];  
        array[min_idx] = tmp;  
    }  
}
```

```
// And also a string array.
```

```
void SelectionSort(string* array, int size) {  
    for (int i = 0; i < size; ++i) {  
        int min_idx = i;  
        for (int j = i + 1; j < size; ++j) {  
            if (array[min_idx] > array[j])  
                min_idx = j;  
        }  
        string tmp = array[i];  
        array[i] = array[min_idx];  
        array[min_idx] = tmp;  
    }  
}
```

C++ Template

- C++ template allows us to avoid this repeated codes.

```
// Suppose we want to sort an array of type T.
```

```
template <typename T>
void SelectionSort(T* array, int size) {
    for (int i = 0; i < size; ++i) {
        int min_idx = i;
        for (int j = i + 1; j < size; ++j) {
            if (array[min_idx] > array[j])
                min_idx = j;
        }
        // Swap array[i] and array[min_idx].
        T tmp = array[i];
        array[i] = array[min_idx];
        array[min_idx] = tmp;
    }
}
```

C++ Template

```
// Suppose we want to sort an integer array.
```

```
template <typename T>
void SelectionSort(T* array, int size) {
    for (int i = 0; i < size; ++i) {
        int min_idx = i;
        for (int j = i + 1; j < size; ++j) {
            if (array[min_idx] > array[j])
                min_idx = j;
        }
        T tmp = array[i];
        array[i] = array[min_idx];
        array[min_idx] = tmp;
    }
}
```

```
int main() {
    int array[] = { 2, 5, 3, 1, 4 };
    const int size = sizeof(array) / sizeof(int);
    SelectionSort<int>(array, size);    // You may use SelectionSort(array, size);
    for (int i = 0; i < size; ++i) cout << " " << array[i];
    cout << endl;
    return 0;
}
```


C++ Template

```
template <typename T>
void Swap(T& a, T& b) {
    T tmp = a;
    a = b;
    b = tmp;
}

template <typename T>
void SelectionSort(T* array, int size) {
    for (int i = 0; i < size; ++i) {
        int min_idx = i;
        for (int j = i + 1; j < size; ++j) {
            if (array[min_idx] > array[j])
                min_idx = j;
        }
        Swap(array[i], array[min_idx]); // Clearly states the meaning of operation.
    }
}
```

C++ Template

- Functions and classes can be templated.
- Template parameters can be typenames (= classes) or integers.

```
template <class First, class Second> // Same as <typename First, typename Second>.
struct Pair {
    First first;
    Second second;
};

template <typename T, int d> // d must be a constant integer.
void Reverse(T array[d]) { // Same as (T* array) - array size is not checked.
    for (int i = 0; i < d / 2; ++i) Swap(array[i], array[d - i - 1]);
}

int main() {
    int array[10] = { ... };
    int size = 10;
    Reverse<int, 10>(array); // OK.
    Reverse<int, size>(array); // Error.
    return 0;
}
```

C++ Template

```
template <class First, class Second>
struct Pair {
    First first;
    Second second;

    Pair(const First& f, const Second& s) : first(f), second(s) {}
};

template <class First, class Second>
Pair<First, Second> MakePair(const First& first, const Second& second) {
    return Pair<First, Second>(first, second);
}

int main() {
    Pair<int, int> p = MakePair(10, 10); // Equivalently MakePair<int, int>(10, 10);
    Pair<int, int> q = Pair<int, int>(20, 20);
    return 0;
}
```

Another Function Template

◆ Declaration/prototype:

```
Template<class T>  
void showStuff(int stuff1, T stuff2, T stuff3);
```

◆ Definition:

```
template<class T>  
void showStuff(int stuff1, T stuff2, T stuff3)  
{  
    cout << stuff1 << endl  
        << stuff2 << endl  
        << stuff3 << endl;  
}
```

showStuff Call

- ◆ Consider function call:
`showStuff(2, 3.3, 4.4);`
- ◆ Compiler generates function definition
 - ▣ Replaces T with double
 - Since second parameter is type double
- ◆ Displays:
2
3.3
4.4

Compiler Complications

◆ Function declarations and definitions

- Typically we have them separate
- For templates → not supported on most compilers!

◆ Safest to place template function definition in file where invoked

- Many compilers require it appear 1st
- Often we #include all template definitions

Multiple Type Parameters

- ◆ Can have:
`template<class T1, class T2>`
- ◆ Not typical
 - Usually only need one "replaceable" type
 - Cannot have "unused" template parameters
 - Each must be "used" in definition
 - Error otherwise!

Algorithm Abstraction

- ◆ Refers to implementing templates
- ◆ Express algorithms in "general" way:
 - Algorithm applies to variables of any type
 - Ignore incidental detail
 - Concentrate on substantive parts of algorithm
- ◆ Function templates are one way C++ supports algorithm abstraction

Defining Templates Strategies

- ◆ Develop function normally
 - Using actual data types
- ◆ Completely debug "ordinary" function
- ◆ Then convert to template
 - Replace type names with type parameter as needed
- ◆ Advantages:
 - Easier to solve "concrete" case
 - Deal with algorithm, not template syntax

Inappropriate Types in Templates

- ◆ Can use any type in template for which code makes "sense"
 - Code must behave in appropriate way
- ◆ e.g., `swapValues()` template function
 - Cannot use type for which assignment operator isn't defined
 - Example: an array:

```
int a[10], b[10];  
swapValues(a, b);
```

 - Arrays cannot be "assigned"!

C++ Template Classes

```
template <typename T, int d>
class Vector {
public:
    typedef T DataType;      // Access as Vector<T, d>::DataType.

    Vector() { for (int i = 0; i < d; ++i) vec_[i] = T(); }
    Vector(const Vector& v) { for (int i = 0; i < d; ++i) vec_[i] = v.vec_[i]; }
    const int size() const { return d; }

    const T& operator[](int i) const { return vec_[i]; }
    T& operator[](int i) { return vec_[i]; }

    Vector operator+() const { return *this; }
    Vector operator-() const;

    T Sum() const;
    T Dot(const Vector& v) const;

private:
    T vec_[d];
};
```

C++ Template Classes

```
template <typename T, int d>
Vector<T, d> Vector<T, d>::operator-() const {
    Vector<T, d> ret;
    for (int i = 0; i < d; ++i) ret.vec_[i] = -vec_[i];
    return ret;
}

template <typename T, int d>
T Vector<T, d>::Sum() const {
    T ret = T();
    for (int i = 0; i < d; ++i) ret += vec_[i];
    return ret;
}

template <typename T, int d>
T Vector<T, d>::Dot(const Vector& v) const {
    T ret = T();
    for (int i = 0; i < d; ++i) ret += vec_[i] * v.vec_[i];
    return ret;
}
```

C++ Template Classes

```
template <typename T, int d>
class Vector {
public:
    // ....

    template <typename S>
    Vector<S, d> cast() const {
        Vector<S, d> ret;
        for (int i = 0; i < d; ++i) ret[i] = static_cast<S>(vec_[i]);
        return ret;
    }

private:
    T vec_[d];
};
```

```
int main() {
    Vector<int, 3> v, w;
    Vector<int, 3>::DataType dot = v.Dot(-w);
    Vector<double, 3> x = v.cast<double>();
    cout << x.Sum();
    return 0;
}
```

C++ Template Classes

```
int main() {  
    Vector<int, 3> v;  
    return 0;  
}
```

```
template <>  
class Vector<int, 3> {  
public:  
    typedef int DataType;    // Access as Vector<T, d>::DataType.  
  
    Vector() { for (int i = 0; i < 3; ++i) vec_[i] = int(); }  
    Vector(const Vector& v) { for (int i = 0; i < 3; ++i) vec_[i] = v.vec_[i]; }  
    const int size() const { return d; }  
  
    const int& operator[](int i) const { return vec_[i]; }  
    int& operator[](int i) { return vec_[i]; }  
  
    Vector operator+() const { return *this; }  
    Vector operator-() const;  
  
    int Sum() const;  
    int Dot(const Vector& v) const;  
  
private:  
    int vec_[3];  
};
```

Class Templates

- ◆ Can also "generalize" classes
`template<class T>`
 - Can also apply to class definition
 - All instances of "T" in class definition replaced by type parameter
 - Just like for function templates!
- ◆ Once template defined, can declare objects of the class

Class Template Definition

```
◆ template<class T>
  class Pair
  {
  public:
    Pair();
    Pair(T firstVal, T secondVal);
    void setFirst(T newVal);
    void setSecond(T newVal);
    T getFirst() const;
    T getSecond() const;
  private:
    T first; T second;
  };

```


Template Class Pair Members

```
◆ template<class T>
  Pair<T>::Pair(T firstVal, T secondVal)
  {
    first = firstVal;
    second = secondVal;
  }
  template<class T>
  void Pair<T>::setFirst(T newVal)
  {
    first = newVal;
  }
```

Template Class Pair

- ◆ Objects of class have "pair" of values of type T
- ◆ Can then declare objects:
`Pair<int> score;`
`Pair<char> seats;`
 - Objects then used like any other objects
- ◆ Example uses:
`score.setFirst(3);`
`score.setSecond(0);`

Pair Member Function Definitions

◆ Notice in member function definitions:

- Each definition is itself a "template"
- Requires template prefix before each definition
- Class name before :: is "Pair<T>"
 - Not just "Pair"
- But constructor name is just "Pair"
- Destructor name is also just "~Pair"

Class Templates as Parameters

◆ Consider:

```
int addUP(const Pair<int>& the Pair);
```

- The type (int) is supplied to be used for T in defining this class type parameter
- It "happens" to be call-by-reference here

◆ Again: template types can be used anywhere standard types can

Class Templates Within Function Templates

- ◆ Rather than defining new overload:
template<class T>
T addUp(const Pair<T>& the Pair);
//Precondition: Operator + is defined for values
 of type T
//Returns sum of two values in thePair
- ◆ Function now applies to all kinds
of numbers

Predefined Template Classes

◆ Recall vector class

- It's a template class!

◆ Another: `basic_string` template class

- Deals with strings of "any-type" elements
- e.g.,

<code>basic_string<char></code>	works for char's
<code>basic_string<double></code>	works for doubles
<code>basic_string<YourClass></code>	works for YourClass objects

vector - a resizable array

- Iterator : access the elements in the container iteratively in order.
 - Const and non-const types : `const_iterator` and `iterator`.
 - In many cases, it can be considered as a pointer to an element.

```
#include <vector>
#include <iostream>
using namespace std;

int main(void) {
    // vector(sz)
    vector<int> v(10);
    for (int i = 0; i < v.size(); ++i) v[i] = i;

    // begin(), end()
    for (vector<int>::iterator it = v.begin(); it != v.end(); ++it) {
        cout << " " << *it;
    }
    // Output:  0 1 2 3 4 5 6 7 8 9

    // rbegin(), rend()
    for (vector<int>::reverse_iterator it = v.rbegin(); it != v.rend(); ++it) {
        cout << " " << *it;
    }
    // Output:  9 8 7 6 5 4 3 2 1 0
}
```

basic_string Template Class

- ◆ Already used it!
- ◆ Recall "string"
 - It's an alternate name for `basic_string<char>`
 - All member functions behave similarly for `basic_string<T>`
- ◆ `basic_string` defined in library `<string>`
 - Definition is in `std` namespace

Inline Function

- Request the compiler to insert the function body in the place that the function is called.
 - The function body will not be included in the object file.
- Compilers are not obligated to respect this request.
- Member functions defined in the class definition are inlined.
- Inline function definitions are placed in header files.
- Pros/cons: eliminate function call overhead / code bloat.

```
inline void Swap(int& a, int& b) {  
    int tmp = a;  
    a = b;  
    b = tmp;  
}
```

