Lab 5 Specifications

Lab 5 is focused on interrupts. The specifications emphasize correct interrupt-driven design, which includes keeping your interrupt service routines small. We pay special attention to whether your system keeps working at the edge cases (very fast and very slow motor speeds) to emphasize this behavior.

Hardware Specifications

Proficiency

- ☐ Encoder used to interpret and display motor direction and speed.
- ☐ System does not miss any encoder pulses at normal speed.
- ☐ Design measures and displays speed of motor in units of rev/s with an update rate of at least 1 Hz.
- ☐ Measured speed and direction match the true motor speed and direction (calculations should be provided in the report to verify this).
- ☐ Motor speed is reported as zero when it is not spinning.
- ☐ Encoder outputs are connected only to 5V-tolerant MCU pins (see the tolerant pin list in the datasheet) or are shifted to 3.3V logic with a conversion circuit.

Excellence

- ☐ MCU does not miss any pulses at high speed, and still outputs a non-zero velocity at low speeds.

Software and Microcontroller Design Specifications

Proficiency

- ☐ Code uses interrupts (rather than polling or timers) to detect encoder pulses.
- ☐ Code adheres to most of the C-style guidelines see here.

Excellence

- ☐ Design uses both edges of both encoder channels to achieve the highest possible resolution measurement.

Other Documentation

Proficiency

- ☐ Report explains how raw encoder pulses and their timing are converted into a velocity in rev/s and a direction, with calculations to back up the update rate and resolution achieved.

Excellence

- ☐ Report includes a flowchart illustrating the main loop and each interrupt handler, and how they communicate.
- ☐ Report compares the performance of interrupt-based code to manual polling at high speeds, and quantitatively discusses the tradeoffs between the two approaches.

Schematic Specifications

Proficiency

- ☐ Schematic correctly represents the circuit that was built on the breadboard.
- ☐ No parts of motherboard schematic replicated. Shows only off-board components. Indicate on-board components with a brief paragraph that links the motherboard schematic (here).
- ☐ No parts internal to the chip (e.g., internal pullup resistors) drawn on schematic. Indicate important pullups, capacitors, etc. with comments instead.
- ☐ All pin names labeled.
- ☐ All pin numbers labeled.
- ☐ Crossing wires clearly identified as junction or unconnected.
- ☐ Neat layout (e.g., clear organization and spacing).
- ☐ All parts labeled with part number.
- ☐ All component values present.

Excellence

- ☐ Standard symbols used for all components where applicable.
- ☐ Signals "flow" from left to right where possible (e.g., inputs on left hand side, outputs on right hand side, power on top, ground on bottom)
- ☐ Title block with author name, title, and date.

Lab Writeup

Proficiency and Excellence

- ☐ Documentation embedded in a well-structured, concise report with one section per major deliverable. Sections should match structure of other specs.
- ☐ Spoiler tags are used to hide screenshots and code. Some unspoilered entries (~1 waveform, essential code snippets) allowed if they are essential to the narrative, kept to a minimum.
- ☐ Writeup contains minimal spelling or grammar issues and any errors do not significantly detract from clarity of the writeup.
- ☐ Statement of whether the design meets all the requirements. If not, list the shortcomings.
- ☐ AI prototype attempted and some reflection is recorded.
- ☐ Number of hours spent working on the lab are included.
- ☐ (Optional) List comments or suggestions on what was particularly good about the assignment or what you think needs to change in future versions.