

API Platform Reference

Authentication and Authorization

The API uses bearer-token authentication. Every protected request must include an Authorization header containing a valid access token. Access tokens are validated before application handlers execute. Authentication establishes the caller identity, while authorization determines whether that identity may access the requested resource.

API Versioning

The current stable API version is v2. Requests to the versioned API must use the `/api/v2/` path prefix. The legacy v1 interface remains available only for compatibility testing and should not be used for new integrations. Version negotiation is explicit rather than inferred.

Request IDs

Every accepted API request receives a request ID. The request ID is returned through the X-Request-ID response header and is included in structured application logs. Clients should preserve the request ID when reporting failures because it allows operators to correlate the request with backend logs and upstream events.

Timeout Policy

The API gateway uses a 60 second external API timeout. The PostgreSQL query timeout is 30 seconds. Redis operations have a 5 second timeout. These limits are intentionally different because database, cache, and external service operations have different expected latency profiles.

Pagination

Collection endpoints use cursor-based pagination. The default page size is 50 records and the maximum permitted page size is 200 records. A response contains `next_cursor` when additional records are available. Clients should not assume that an empty page means the collection is exhausted unless `next_cursor` is absent.

Streaming

Streaming responses use Server-Sent Events, abbreviated SSE. An SSE stream is established over HTTP and emits ordered events until completion or cancellation. The client must keep the connection open while events are being received and should treat a transport disconnect as a recoverable stream failure when the request is otherwise safe to retry.

Redis Integration

Redis is used for short-lived control-plane state, rate limiting, and selected request coordination. Redis connections are obtained from the configured asynchronous client pool. A Redis timeout is five seconds. Redis is not the authoritative source for persistent document content.

PostgreSQL Integration

PostgreSQL is the authoritative relational datastore for users, chats, documents, messages, and document chunks. Vector retrieval is implemented with pgvector inside PostgreSQL. Database operations must respect the authenticated user's ownership boundary.

Error Handling

HTTP 400 indicates an invalid client request. HTTP 401 indicates that authentication is missing or invalid. HTTP 403 indicates that authentication succeeded but the caller is not authorized to access the requested resource. HTTP 404 indicates that the requested resource does not exist or is intentionally not exposed to the caller.