Permuting Two Arrays



There are two n-element arrays of integers, A and B. Permute them into some A' and B' such that the relation $A'[i] + B'[i] \ge k$ holds for all i where $0 \le i < n$.

There will be q queries consisting of A, B, and k. For each query, return YES if some permutation A', B' satisfying the relation exists. Otherwise, return NO.

Example

$$A = [0, 1]$$

$$B = [0, 2]$$

$$k = 1$$

A valid A',B' is A'=[1,0] and B'=[0,2]: $1+0\geq 1$ and $0+2\geq 1$. Return YES.

Function Description

Complete the twoArrays function in the editor below. It should return a string, either YES or NO.

twoArrays has the following parameter(s):

- int k: an integer
- int A[n]: an array of integers
- int B[n]: an array of integers

Returns

- string: either YES or NO

Input Format

The first line contains an integer q, the number of queries.

The next q sets of 3 lines are as follows:

- The first line contains two space-separated integers n and k, the size of both arrays A and B, and the relation variable.
- ullet The second line contains n space-separated integers A[i].
- ullet The third line contains n space-separated integers B[i].

Constraints

- $1 \le q \le 10$
- $1 \le n \le 1000$
- $1 \le k \le 10^9$
- $0 \le A[i], B[i] \le 10^9$

Sample Input

```
STDIN Function

2          q = 2
3 10          A[] and B[] size n = 3, k = 10
2 1 3          A = [2, 1, 3]
7 8 9          B = [7, 8, 9]
4 5          A[] and B[] size n = 4, k = 5
1 2 2 1         A = [1, 2, 2, 1]
3 3 3 4         B = [3, 3, 3, 4]
```

Sample Output

```
YES
NO
```

Explanation

There are two queries:

- 1. Permute these into $A^\prime = [1,2,3]$ and $B^\prime = [9,8,7]$ so that the following statements are true:
 - $A[0] + B[1] = 1 + 9 = 10 \ge k$
 - $A[1] + B[1] = 2 + 8 = 10 \ge k$
 - $A[2] + B[2] = 3 + 7 = 10 \ge k$
- 2. A=[1,2,2,1], B=[3,3,3,4], and k=5. To permute A and B into a valid A' and B', there must be at least three numbers in A that are greater than 1.