ignite Technologies

A LITTLE GUIDE TO



SMB ENUMERATION

www.hackingarticles.in



Contents

Introduction	3
What is SMB?	3
SMB Working	3
SMB Versions	3
SMB Security	4
SMB Enumeration: Hostname	4
nmblookup	4
nbtscan	5
nbstat NSE Script	5
nbtstat	6
Ping	7
smb-os-discovery NSE Script	7
SMB Enumeration: Share and Null Session	8
SMBMap	8
smbclient	9
smb-enum-shares NSE Script	10
Net view	11
Metasploit: smb_enumshares	12
CrackMapExec	13
rpcclient	13
SMB Enumeration: Vulnerability Scanning	14
smb-vuln NSE Script	14
SMB Enumeration: Users	15
Metasploit: smb_lookupsid	15
Impacket: Lookupsid	16
SMB Enumeration: Enum4Linux	17
Conclusion	20









Introduction

We will shine the light on the process or methodology for enumerating SMB services on the Target System/Server in this article. There are numerous tools and methods to perform enumeration, we will be finding different types of information on SMB throughout the article.

What is SMB?

SMB or Server Message Block is the modernized concept of what was used to known as Common Internet File System. It works as an Application Layer Network Protocol. It is designed to be used as a File Sharing Protocol. Different Applications can on a system can read and write simultaneously to the files and request the server for services inside a network. One of the interesting functionalities of SMB is that it allows users to run it top of its TCP/IP protocol or other network protocols. Additionally, with the help of SMB, authorized users, applications, or software can access files or other resources on a remote server. Users can perform actions that include reading data, creating data, and updating data. Clients and servers communicate using something called SMB client request.

SMB Working

The SMB Protocol delegates the client to communicate with other participants in the same network, allowing it to access files or services open to it in the network. In order for it to function the other device also requires the implemented network protocol and receive and process the respective client request using an SMB server application. Therefore, client computers using SMB connect to a supporting server using NetBIOS over TCP/IP, IPX/SPX, or NetBEUI. The initial establishment of the connection is required for exchanging information. Subsequent data transport is regulated by the provisions of the TCP protocol. SMB functions as a request-response or client-server protocol. Once the connection is established, the client's computer or program can then open, read/write, and access files similar to the file system on a local computer.

SMB Versions

- CIFS: The old version of SMB, which was included in Microsoft Windows NT 4.0 in 1996.
- SMB 1.0 / SMB1: The version used in Windows 2000, Windows XP, Windows Server 2003 and Windows Server 2003 R2.
- SMB 2.0 / SMB2: This version is used in Windows Vista and Windows Server 2008.
- SMB 2.1 / SMB2.1: This version is used in Windows 7 and Windows Server 2008 R2.
- SMB 3.0 / SMB3: This version used in Windows 8 and Windows Server 2012.
- SMB 3.02 / SMB3: This version is used in Windows 8.1 and Windows Server 2012 R2.
- SMB 3.1: This version is used in Windows Server 2016 and Windows 10.

Currently, the latest version of SMB is SMB 3.1.1, which was introduced with Windows 10 and Windows Server 2016. This version supports AES 128 GCM encryption in addition to AES 128 CCM encryption added in SMB3 and implements pre-authentication integrity check using SHA-512 hash. SMB 3.1.1 also makes secure negotiation mandatory when connecting to clients using SMB 2.x and higher.











SMB Security

The SMB protocol supports two levels of security. The first is the share level. The server is protected at this level and each share has a password. The client computer or user has to enter the password to access data or files saved under the specific share. This is the only security model available in the Core and Core plus SMG protocol definitions. User level protection was later added to the SMB protocol. It is applied to individual files and each share is based on specific user access rights. Once a server authenticates the client, he/she is given a unique identification (UID) that is presented upon access to the server. The SMB protocol has supported individual security since LAN Manager 1.0 was implemented.

SMB Enumeration: Hostname

Firstly, we will start the enumeration of the SMB by finding the hostname of the target machine. This can be done by various tools.

nmblookup

We started with nmblookup tool. It is designed to make use of queries for the NetBIOS names and then map them to their subsequent IP addresses in a network. The options allow the name queries to be directed at a particular IP broadcast area or to a particular machine. All queries are done over UDP.

For unique names:

- 00: Workstation Service (workstation name)
- 03: Windows Messenger service
- 06: Remote Access Service
- 20: File Service (also called Host Record)
- 21: Remote Access Service client
- 1B: Domain Master Browser Primary Domain Controller for a domain
- 1D: Master Browser

For group names:

- 00: Workstation Service (workgroup/domain name)
- 1C: Domain Controllers for a domain
- 1E: Browser Service Elections

```
nmblookup -A 192.168.1.17
```











Here, we can see that we have enumerated the hostname to be DESKTOP-ATNONJ9.

nbtscan

Moving Forward we used nbtscan tool. NBTscan is a program for scanning IP networks for NetBIOS name information. It sends NetBIOS status query to each address in supplied range and lists received information in human-readable form. For each responded host it lists IP address, NetBIOS computer name, logged-in user name and MAC address (such as Ethernet).

```
nbtscan 192.168.1.17
```

```
The state of the s
```

Finally, we can see that we have enumerated the hostname to be DESKTOP-ATNONJ9.

nbstat NSE Script

This nmap script attempts to retrieve the target's NetBIOS names and MAC address. By default, the script displays the name of the computer and the logged-in user; if the verbosity is turned up, it displays all names the system thinks it owns. It also shows the flags that we studied in nmblookup tool.

```
nmap --script nbstat.nse 192.168.1.17
```

```
kali)-[~]
   nmap -- script nbstat.nse 192.168.1.17
Starting Nmap 7.91 ( https://nmap.org ) at 2021-03-05 11:23 EST
Nmap scan report for 192.168.1.17
Host is up (0.00059s latency).
Not shown: 996 closed ports
        STATE SERVICE
PORT
135/tcp open msrpc
139/tcp open netbios-ssn
445/tcp open microsoft-ds
3389/tcp open ms-wbt-server
MAC Address: 00:0C:29:54:91:59 (VMware)
Host script results:
 nbstat: NetBIOS name: DESKTOP-ATNONJ9, NetBIOS user: <unknown>, NetBIOS
   DESKTOP-ATNONJ9<00> Flags: <unique><active>
   DESKTOP-ATNONJ9<20> Flags: <unique><active>
   WORKGROUP<00>
                        Flags: <group><active>
   WORKGROUP<1e>
                        Flags: <group><active>
   WORKGROUP<1d>
                        Flags: <unique><active>
    \x01\x02_MSBROWSE_\x02<01> Flags: <group><active>
```









Finally, we can see that we have enumerated the hostname to be DESKTOP-ATNONJ9.

nbtstat

This Windows command displays the NetBIOS over TCP/IP (NetBT) protocol statistics. It can read the NetBIOS name tables for both the local computer and remote computers. It can also read the NetBIOS name cache. This command allows a refresh of the NetBIOS name cache and the names registered with Windows Internet Name Service (WINS). When used without any parameters, this command displays Help Information. This command is available only if the Internet Protocol (TCP/IP) protocol is installed as a component in the properties of a network adapter in Network Connections.

```
nbtstat -A 192.168.1.17
```

```
C:\Users\raj>nbtstat -A 192.168.1.17 🛥
Ethernet 2:
Host not found.
Ethernet 3:
Node IpAddress: [192.168.85.2] Scope Id: []
   Host not found.
VMware Network Adapter VMnet1:
Node IpAddress: [192.168.226.1] Scope Id: []
   Host not found.
VMware Network Adapter VMnet8:
Node IpAddress: [192.168.205.1] Scope Id: []
   Host not found.
Ethernet:
Node IpAddress: [192.168.1.3] Scope Id: []
          NetBIOS Remote Machine Name Table
      Name
                        Type
                                    Status
   DESKTOP-ATNONJ9<00>
                                  Registered
                       UNIQUE
   DESKTOP-ATNONJ9<20>
                       UNIQUE
                                  Registered
   WORKGROUP
                 <00>
                       GROUP
                                  Registered
   WORKGROUP
                       GROUP
                 <1E>
                                  Registered
   WORKGROUP
                 <1D>
                       UNIQUE
                                  Registered
   GROUP
                                  Registered
   MAC Address = 00-0C-29-54-91-59
```

Finally, we can see that we have enumerated the hostname to be DESKTOP-ATNONJ9.











Ping

We can also use the ping command to detect the hostname of an SMB server or machine. The -a parameter specifies reverse name resolution to be performed on the destination IP address. If this is successful, ping displays the corresponding hostname.

```
ping -a 192.168.1.17
```

Then, we can see that we have enumerated the hostname to be DESKTOP-ATNONJ9.

```
C:\Users\raj>ping -a 192.168.1.17◀
Pinging DESKTOP-ATNONJ9 [192.168.1.17] with 32 bytes of data:
Reply from 192.168.1.17: bytes=32 time<1ms TTL=128
Ping statistics for 192.168.1.17:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
   Minimum = 0ms, Maximum = 0ms, Average = 0ms
```

smb-os-discovery NSE Script

This NSE script attempts to determine the operating system, computer name, domain, workgroup, and current time over the SMB protocol (ports 445 or 139). You achieve it by initiating a session with the anonymous account (or with a proper user account, if one is given; it likely doesn't make a difference); in response to a session starting, the server will send back all this information.

The following fields may be included in the output, depending on the circumstances (e.g., the workgroup name is mutually exclusive with domain and forest names) and the information available:

- OS
- Computer name
- Domain name
- Forest name
- **FQDN**
- NetBIOS computer name
- NetBIOS domain name
- Workgroup
- System time

```
nmap --script smb-os-discovery 192.168.1.17
```











```
kali)-[~]
  -# nmap --script smb-os-discovery 192.168.1.17
Starting Nmap 7.91 ( https://nmap.org ) at 2021-03-05 12:03 EST
Nmap scan report for 192.168.1.17
Host is up (0.00069s latency).
Not shown: 996 closed ports
        STATE SERVICE
PORT
135/tcp open msrpc
139/tcp open
              netbios-ssn
445/tcp open microsoft-ds
3389/tcp open
              ms-wbt-server
MAC Address: 00:0C:29:54:91:59 (VMware)
Host script results:
  smb-os-discovery:
    OS: Windows 10 Pro 18362 (Windows 10 Pro 6.3)
    OS CPE: cpe:/o:microsoft:windows_10::-
    Computer name: DESKTOP-ATNON19
    NetBIOS computer name: DESKTOP-ATNONJ9\x00
    Workgroup: WORKGROUP\x00
    System time: 2021-03-05T09:03:24-08:00
Nmap done: 1 IP address (1 host up) scanned in 1.83 seconds
```

Then, we can see that we have enumerated the hostname to be DESKTOP-ATNONJ9.

SMB Enumeration: Share and Null Session

As we discussed earlier that SMB works on sharing files and resources. In order to transfer these files or resources, there are data streams that are called shares. There are public shares that are accessible to everyone on the network and then there are the user-specific shares. Let's enumerate these shares.

SMBMap

SMBMap allows users to enumerate samba share drives across an entire domain. List share drives, drive permissions, share contents, upload/download functionality, file name auto-download pattern matching, and even execute remote commands. This tool was designed with pen testing in mind and is intended to simplify searching for potentially sensitive data across large networks.

```
smbmap -H 192.168.1.40
```

```
smbmap -H 192.168.1.40
                       IP: 192.168.1.40:445
[+] Guest session
                                                Name: 192.168.1.40
       Disk
                                                                 Permissions
                                                                                 Comment
                                                                                 Printer Drivers
       print$
                                                                 NO ACCESS
                                                                 READ, WRITE
       guest
        IPC$
                                                                                  IPC Service (ubuntu
                                                                 NO ACCESS
```

Here we see that the target machine has some shares. There is a share by the name of the guest. That must be a public share. Let's enumerate a user-specific share using the credentials for that user. We are enumerating the share for the user raj as shown in the image below.











```
smbmap -H 192.168.1.17 -u raj -p 123
```

```
smbmap -H 192.168.1.17 -u raj -p 123
                                Name: 192.168.1.17
[+] IP: 192.168.1.17:445
        Disk
                                                                 Permissions
                                                                                 Comment
        ADMIN$
                                                                 NO ACCESS
                                                                                 Remote Admin
        C$
                                                                 NO ACCESS
                                                                                 Default share
        IPC$
                                                                 READ ONLY
                                                                                 Remote IPC
        share
                                                                 READ, WRITE
                                                                 READ ONLY
        Users
```

smbclient

smbclient is samba client with an "ftp like" interface. It is a useful tool to test connectivity to a Windows share. It can be used to transfer files, or to look at share names. In addition, it has a nifty ability to 'tar' (backup) and restore files from a server to a client and vice versa. We enumerated the target machine and found the guest share using the smbclient directly. Then we connect to the guest share and see that there is a text file by the name of file.txt. We can download it using the get command.

```
smbclient -L 192.168.1.40
smbclient //192.168.1.40/guest
get file.txt
```

```
(root® kali)-[~]
smbclient -L 192.168.1.40
Enter WORKGROUP\root's password:
                                   Comment
        Sharename
                        Type
                                  Printer Drivers
                        Disk
        print$
       guest
                        Disk
                        IPC
        IPC$
                                  IPC Service (ubuntu server (Samba, Ubuntu))
SMB1 disabled -- no workgroup available
  smbclient //192.168.1.40/guest
Enter WORKGROUP\root's password:
Try "help" to get a list of possible commands.
smb: \> ls
                                       D
                                                0 Fri Mar 5 13:01:46 2021
                                       D
                                               0 Fri Mar 5 13:00:54 2021
 file.txt
                                               25 Fri Mar 5 13:01:17 2021
                20509264 blocks of size 1024. 15451640 blocks available
smb: \> get file.txt
getting file \file.txt of size 25 as file.txt (6.1 KiloBytes/sec) (average 6.1
smb: \> exit
```

Then we enumerate the user-specific share. We connect to the SMB as user raj and find a share by the name of 'share'. We reconfigured the smbclient command to access the share and we see that we find a file named raj.txt. Again, we can download this file as well as using the get command.











```
smbclient -L 192.168.1.17 -U raj%123
smbclient //192.168.1.17/share -U raj%123
get raj.txt
```

```
smbclient -L 192.168.1.17 -U raj%123
        Sharename
                        Type
                                  Comment
        ADMIN$
                        Disk
                                  Remote Admin
                                  Default share
        C$
                        Disk
        IPC$
                        IPC
                                  Remote IPC
        share
                        Disk
        Users
                        Disk
SMB1 disabled -- no workgroup available
    smbclient //192.168.1.17/share -U raj%123
Try "help" to get a list of possible commands.
smb: \> ls
                                      D
                                               0
                                                  Fri Mar
                                                          5 11:51:13 2021
                                                           5 11:51:13 2021
                                                  Fri Mar
                                      n
                                               a
                                               4 Fri Mar 5 10:22:51 2021
 raj.txt
                15563263 blocks of size 4096. 9657922 blocks available
smb: \> get raj.txt
getting file \raj.txt of size 4 as raj.txt (0.4 KiloBytes/sec) (average 0.4 KiloBytes/sec)
smb: \>
```

smb-enum-shares NSE Script

This NSE scirpt attempts to list shares using the srvsvc.NetShareEnumAll MSRPC function and retrieve more information about them using srvsvc.NetShareGetInfo. If access to those functions is denied, the system checks a list of common share names. An administrator account is required to call NetShareGetInfo on all versions of Windows up to 2003, as well as Windows Vista, Windows 7, and Windows 10, if UAC is turned down. Even if NetShareEnumAll is restricted, users attempting to connect to a share will always reveal its existence. So, if NetShareEnumAll fails, the script uses a pregenerated list of shares, based on a large test network. If any of those succeed, the script records them. After finding a list of shares, the script attempts to connect to each of them anonymously, which divides them into "anonymous" for shares that the NULL user can connect to, or "restricted" for shares that require a user account.

```
nmap --script smb-enum-shares -p139,445 192.168.1.17
```









```
-# nmap --script smb-enum-shares -p139,445 192.168.1.17
Starting Nmap 7.91 ( https://nmap.org ) at 2021-03-05 11:59 EST
Nmap scan report for 192.168.1.17
Host is up (0.00054s latency).
        STATE SERVICE
PORT
139/tcp open netbios-ssn
445/tcp open microsoft-ds
MAC Address: 00:0C:29:54:91:59 (VMware)
Host script results:
  smb-enum-shares:
    note: ERROR: Enumerating shares failed, guessing at common ones (NT_STAT
    account_used: <blank>
    \\192.168.1.17\ADMIN$:
     warning: Couldn't get details for share: NT_STATUS_ACCESS_DENIED
      Anonymous access: <none>
    \\192.168.1.17\C$:
      warning: Couldn't get details for share: NT_STATUS_ACCESS_DENIED
      Anonymous access: <none>
    \\192.168.1.17\IPC$:
      warning: Couldn't get details for share: NT_STATUS_ACCESS_DENIED Anonymous access: REΛD
    \\192.168.1.17\SHARE:
      warning: Couldn't get details for share: NT_STATUS_ACCESS_DENIED
      Anonymous access: <none>
    \\192.168.1.17\USERS:
      warning: Couldn't get details for share: NT_STATUS_ACCESS_DENIED
      Anonymous access: <none>
Nmap done: 1 IP address (1 host up) scanned in 1.18 seconds
```

Then, we can see that we have the shares listed although the Access is Denied the existence of the share is confirmed.

Net view

Displays a list of domains, computers, or resources that are being shared by the specified computer. Used without parameters, net view displays a list of computers in your current domain. This time we are on the Windows machine. We used the net view with the /All parameter to list all the shares on the target machine.

```
net view \\192.168.1.17 /All
```











```
C:\Users\raj>net view \\192.168.1.17 /All
Shared resources at \\192.168.1.17
Share name Type Used as Comment
ADMIN$
           Disk
                        Remote Admin
€2
           Disk
                      Default share
IPC$
           IPC
                         Remote IPC
share
           Disk
Users
           Disk
The command completed successfully.
C:\Users\raj>net use \\192.168.1.17\share 🔫
The command completed successfully.
C:\Users\raj>net use 🚤
New connections will be remembered.
Status
         Local
                     Remote
                                               Network
ЭК
                     \\192.168.1.17\share
                                              Microsoft Windows Network
                                              Microsoft Windows Network
Disconnected
                     \\192.168.1.16\IPC$
The command completed successfully.
C:\Users\raj>copy \\192.168.1.17\share\raj.txt 🚄
       1 file(s) copied.
C:\Users\raj>
```

Then we changed the command by adding the share, and we can read the contents of that share. Now using the copy command, we can download the file from share.

Metasploit: smb enumshares

The smb_enumshares module enumerates any SMB shares that are available on a remote system. You need the IP Address of the target server or machine followed by the set of credentials that can be used to access the share.

```
use auxiliary/scanner/smb/smb_enumshares
set rhosts 192.168.1.17
set smbuser raj
set smbpass 123
exploit
```











```
msf6 > use auxiliary/scanner/smb/smb_enumshares
msf6 auxiliary(
                                            ) > set rhosts 192.168.1.17
rhosts ⇒ 192.168.1.17
                                  enumshares) > set smbuser raj
msf6 auxiliary(
smbuser ⇒ raj
msf6 auxiliary(
                                           s) > set smbpass 123
smbpass ⇒ 123
<u>msf6</u> auxiliary(

    Login Failed: Unable to negotiate SMB1 with the remote host: Not a
    peer_native_os is only available with SMB1 (current version: SMB3)

    192.168.1.17:139
    192.168.1.17:445
                         - peer_native_lm is only available with SMB1 (current version: SMB3)
 !1 192.168.1.17:445
                           - ADMINS - (DISK) Remote Admin
[+] 192.168.1.17:445
[+] 192.168.1.17:445
                       - C$ - (DISK) Default share
                          - IPC$ - (IPC) Remote IPC
[+] 192.168.1.17:445
                            - share - (DISK)
   192.168.1.17:445
                          - Users - (DISK)
   192.168.1.17:445
    192.168.1.17: - Scanned 1 of 1 hosts (100% complete)
[*] Auxiliary module execution completed
msf6 auxiliary()
```

CrackMapExec

CrackMapExec (a.k.a CME) is a post-exploitation tool that helps automate assessing the security of large Active Directory networks. Built with stealth in mind, CME follows the concept of "Living off the Land": abusing built-in Active Directory features/protocols to achieve its functionality and allowing it to evade most endpoint protection/IDS/IPS solutions. Additionally, CrackMapExec can Map the network hosts, Generate Relay List, enumerate shares and access, enumerate active sessions, enumerate disks, enumerate logged on users, enumerate domain users, Enumerate Users by bruteforcing RID, enumerate domain groups, enumerate local groups etc.

```
crackmapexec smb 192.168.1.17 -u 'raj' -p '123' -shares
```

```
crackmapexec smb 192.168.1.40
        192.168.1.40
192.168.1.40
                          445
445
                                                       *] Windows 6.1 (name:UBUNTU) (domain:) (signing:False) (SMBv1:True)
                                  UBUNTU
                                  UBUNTU
                                                       [+] Enumerated shares
         192.168.1.40
192.168.1.40
                                   UBUNTU
         192.168.1.40
                                   UBUNTU
                                                                                          Printer Drivers
                                                                        READ, WRITE
                                                                                          IPC Service (ubuntu server (Samba, Ubuntu))
         192,168,1,40
                                   UBUNTU
```

Then, we can see different shares and the permissions that are allowed on that particular share.

rpcclient

rpcclient is a utility initially developed to test MS-RPC functionality in Samba itself. It has undergone several stages of development and stability. Many system administrators have now written scripts around it to manage Windows NT clients from their UNIX workstation. We will be using it to enumerate the users on the SMB shares using the option of netshareenum as shown in the image below.

```
rpcclient -U "" -N 192.168.1.40
netshareenum
netshareenumall
```











```
rpcclient -U "" -N 192.168.1.40
rpcclient $> netshareenum
netname: guest
        remark:
                C:\srv\samba\guest\
        password:
rpcclient $> netshareenumall
netname: print$
        remark: Printer Drivers
               C:\var\lib\samba\printers
        path:
        password:
netname: guest
        remark:
               C:\srv\samba\guest\
        path:
        password:
netname: IPC$
        remark: IPC Service (ubuntu server (Samba, Ubuntu))
                C:\tmp
```

SMB Enumeration: Vulnerability Scanning

We enumerate a SMB server to compromise it, as we need to enumerate and find possible vulnerabilities that we can use to exploit the server. In order to do this in an optimized method, we can perform Vulnerability Scanning. There might be multiple tools to perform this kind of Scanning but here we will be focusing on this NSE script.

smb-vuln NSE Script

Nmap in past used to have a script by the name of smb-check-vulns. It used to scan the target server for the various vulnerabilities such as:

- conficker
- cve2009-3103
- ms06-025
- ms07-029
- regsvc-dos
- ms08-067

Then the script was divided into single vulnerability checks that can run individually, such as smbvuln-ms08-067. Hence to check all SMB vulnerabilities available in the Nmap Scripting Engine we use the * with the script.

```
nmap --script smb-vuln* 192.168.1.16
```









```
(reet@ kali)-[~]
nmap --script smb-vuln* 192.168.1.16
Starting Nmap 7.91 ( https://nmap.org ) at 2021-03-05 14:33 EST
Nmap scan report for 192.168.1.16
Host is up (0.00061s latency).
Not shown: 991 closed ports
PORT
         STATE SERVICE
135/tcp open msrpc
139/tcp open netbios-ssn
445/tcp open microsoft-ds
49152/tcp open unknown
49153/tcp open unknown
49154/tcp open unknown
49155/tcp open unknown
49156/tcp open unknown
49157/tcp open unknown
MAC Address: 00:0C:29:5C:69:16 (VMware)
Host script results:
 _smb-vuln-ms10-054: false
  smb-vuln-ms10-061: NT_STATUS_ACCESS_DENIED
 smb-vuln-ms17-010:
    VULNERABLE:
    Remote Code Execution vulnerability in Microsoft SMBv1 servers (ms17-010)
      State: VULNERABLE
      IDs: CVE:CVE-2017-0143
      Risk factor: HIGH
        A critical remote code execution vulnerability exists in Microsoft SMBv1
         servers (ms17-010).
      Disclosure date: 2017-03-14
      References:
        https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2017-0143
        https://blogs.technet.microsoft.com/msrc/2017/05/12/customer-guidance-for-wan
        https://technet.microsoft.com/en-us/library/security/ms17-010.aspx
```

SMB Enumeration: Users

In a Windows environment, the system assigns each user a unique identifier called Security ID or SID, which controls access to various resources like Files, Registry keys, network shares, etc. Hence, users shouldn't compromise their SID.

Metasploit: smb lookupsid

The smb lookupsid module brute-forces SID lookups on a range of targets to determine what local users exist in the system. Knowing what users exist on a system can greatly speed up any further brute-force logon attempts later on.

```
use auxiliary/scanner/smb/smb lookupsid
set rhosts 192.168.1.17
set smbuser raj
set smbpass 123
exploit
```











```
msf6 > use auxiliary/scanner/smb/smb_lookupsid
msf6 auxiliary(
                                       d) > set rhosts 192.168.1.17
rhosts ⇒ 192.168.1.17
                                      id) > set smbuser raj
msf6 auxiliary(
smbuser ⇒ raj
                                       id) > set smbpass 123
msf6 auxiliary(
smbpass ⇒ 123
                       -mb/smb lookupsid) > exploit
msf6 auxiliary(
[*] 192.168.1.17:445
                          - PIPE(LSARPC) LOCAL(DESKTOP-ATNONJ9 - 5-21-1276730070-
[*] 192.168.1.17:445
                          - USER=Administrator RID=500
[*] 192.168.1.17:445
                         - USER=Guest RID=501
[*] 192.168.1.17:445
                          - USER=DefaultAccount RID=503
[*] 192.168.1.17:445
                          - USER=WDAGUtilityAccount RID=504
[*] 192.168.1.17:445
                            GROUP=None RID=513
                         - USER=raj RID=1001
[*] 192.168.1.17:445
                          - USER=aart RID=1002
[*] 192.168.1.17:445
                          - DESKTOP-ATNONJ9 [Administrator, Guest, DefaultAccount
[*] 192.168.1.17:445
    192.168.1.17:
                          - Scanned 1 of 1 hosts (100% complete)
[*] Auxiliary module execution completed
```

Here, we can see that through enumerating SMB we have extracted two users: raj and aart.

Impacket: Lookupsid

A Security Identifier (SID) is a unique value of variable length that is used to identify a user account. Through a SID User Enumeration, we can extract information about what users exist and their data. Lookupsid script can enumerate both local and domain users. There is a Metasploit module too for this attack. If you are planning on injecting a target server with a golden or a silver ticket then one of the things that are required is the SID of the 500 user. Lookupsid.py can be used in that scenario. When we provide the following parameters to the Lookupsid in such a format as shown below.

Requirements:

- Domain
- Username
- Password/Password Hash
- Target IP Address

```
python3 lookupsid.py DESKTOP-ATNONJ9/raj:123@192.168.1.17
```

```
li)-[~/impacket/examples]
python3 lookupsid.py DESKTOP-ATNONJ9/raj:123@192.168.1.17
Impacket v0.9.22 - Copyright 2020 SecureAuth Corporation
[*] Brute forcing SIDs at 192.168.1.17
[*] StringBinding ncacn_np:192.168.1.17[\pipe\lsarpc]
[*] Domain SID is: S-1-5-21-1276730070-1850728493-30201559
500: DESKTOP-ATNONJ9\Administrator (SidTypeUser)
501: DESKTOP-ATNONJ9\Guest (SidTypeUser)
503: DESKTOP-ATNONJ9\DefaultAccount (SidTypeUser)
504: DESKTOP-ATNONJ9\WDAGUtilityAccount (SidTypeUser)
513: DESKTOP-ATNONJ9\None (SidTvpeGroup)
1001: DESKTOP-ATNONJ9\raj (SidTypeUser)
1002: DESKTOP-ATNONJ9\aart (SidTypeUser)
```









SMB Enumeration: Enum4Linux

Enum4linux is a tool that developers designed to detect and extract data or enumerate from Windows and Linux operating systems, including SMB hosts on a network. Enum4linux can discover the following:

- Domain and group membership
- **User listings**
- Shares on a device (drives and folders)
- Password policies on a target
- The operating system of a remote target

To begin with, we start a normal scan using enum4linux. It then extracts the RID Range, Usernames, Workgroup, Nbtstat Information, Sessions, SID Information, and OS Information.

enum4linux 192.168.1.40









```
enum4linux 192.168.1.40
Starting enum4linux v0.8.9 ( http://labs.portcullis.co.uk/application/enum4linux/ ) on
     Target Information
Target ...... 192.168.1.40
RID Range ...... 500-550,1000-1050
Username .....
Password .....
Known Usernames .. administrator, guest, krbtgt, domain admins, root, bin, none
     Enumerating Workgroup/Domain on 192.168.1.40
[+] Got domain/workgroup name: WORKGROUP
     Nbtstat Information for 192.168.1.40
Looking up status of 192.168.1.40
       UBUNTU
                       <00> -
                                      B <ACTIVE> Workstation Service
        UBUNTU
                       <03> -
                                      B <ACTIVE> Messenger Service
                                      B <ACTIVE> File Server Service
                       <20> -
        ..__MSBROWSE__. <01> - <GROUP> B <ACTIVE> Master Browser
        WORKGROUP
                       <00> - <GROUP> B <ACTIVE>
                                                  Domain/Workgroup Name
        WORKGROUP
                       <1d> -
                                      B <ACTIVE>
                                                  Master Browser
                       <1e> - <GROUP> B <ACTIVE> Browser Service Elections
       WORKGROUP
       MAC Address = 00-00-00-00-00-00
     Session Check on 192.168.1.40
[+] Server 192.168.1.40 allows sessions using username '', password ''
     Getting domain SID for 192.168.1.40
Domain Name: WORKGROUP
Domain Sid: (NULL SID)
[+] Can't determine if host is part of domain or part of a workgroup
    OS information on 192.168.1.40
Use of uninitialized value $os_info in concatenation (.) or string at ./enum4linux.pl
[+] Got OS info for 192.168.1.40 from smbclient:
[+] Got OS info for 192.168.1.40 from srvinfo:
                      Wk Sv PrQ Unx NT SNT ubuntu server (Samba, Ubuntu)
       UBUNTU
                               500
        platform id
        os version
                               6.1
                               0×809a03
        server type
```

We see that it has also extracted the two uses based on the SID. These two users are privs and ignite. The enum4linux script extracted this user information through communication via the SMB channels.











```
S-1-5-32-1050 *unknown*\*unknown* (8)
[+] Enumerating users using SID S-1-22-1 and logon username '', password ''
S-1-22-1-1000 Unix User\privs (Local User)
S-1-22-1-1001 Unix User\ignite (Local User)
[+] Enumerating users using SID S-1-5-21-894636310-4219792968-1492264695 and l
S-1-5-21-894636310-4219792968-1492264695-500 *unknown*\*unknown* (8)
S-1-5-21-894636310-4219792968-1492264695-501 UBUNTU\nobody (Local User)
S-1-5-21-894636310-4219792968-1492264695-502 *unknown*\*unknown* (8)
S-1-5-21-894636310-4219792968-1492264695-503 *unknown*\*unknown* (8)
S-1-5-21-894636310-4219792968-1492264695-504 *unknown*\*unknown* (8)
S-1-5-21-894636310-4219792968-1492264695-505 *unknown*\*unknown* (8)
    5-21-894636310-4219792968-1492264695-506 *unknown*\*unknown*
```

Finally, we have the Share Enumeration, which had the guest share that we enumerated earlier. Then we see that it attempted to enumerate inside the print share and IPC but faced restrictions. Then we have the Password Policy Information regarding the users on the system. It indicates whether the password was changed recently or if it has never been changed. It also tells us the complexity and other stuff regarding users and the operating system of the target system.









```
Share Enumeration on 192.168.1.40
        Sharename
                         Type
                                   Comment
                                   Printer Drivers
        print$
                         Disk
       guest
                         Disk
        IPC$
                         IPC
                                   IPC Service (ubuntu server (Samba, Ubuntu))
SMB1 disabled -- no workgroup available
[+] Attempting to map shares on 192.168.1.40
//192.168.1.40/print$
                        Mapping: DENIED, Listing: N/A
//192.168.1.40/guest
                        Mapping: OK, Listing: OK
//192.168.1.40/IPC$
                        [E] Can't understand response:
NT_STATUS_OBJECT_NAME_NOT_FOUND listing \*
     Password Policy Information for 192.168.1.40
[+] Attaching to 192.168.1.40 using a NULL share
[+] Trying protocol 139/SMB...
[+] Found domain(s):
        [+] UBUNTU
        [+] Builtin
[+] Password Info for Domain: UBUNTU
        [+] Minimum password length: 5
        [+] Password history length: None
[+] Maximum password age: 37 days 6 hours 21 minutes
        [+] Password Complexity Flags: 000000
                [+] Domain Refuse Password Change: 0
                [+] Domain Password Store Cleartext: 0
                [+] Domain Password Lockout Admins: 0
                [+] Domain Password No Clear Change: 0
                [+] Domain Password No Anon Change: 0
                [+] Domain Password Complex: 0
        [+] Minimum password age: None
        [+] Reset Account Lockout Counter: 30 minutes
        [+] Locked Account Duration: 30 minutes
        [+] Account Lockout Threshold: None
        [+] Forced Log off Time: 37 days 6 hours 21 minutes
```

Conclusion

In this article, we discuss the various scripts and tools that can enumerate with the SMB/MSRPC services on a target system. Enumeration is the key step in order to compromise and in order to defend your system and network. Be sure to safeguard your SMB service.

To learn more about Penetration Testing. Follow this Link.










ignite
Technologies

FOLLOWUSON social median









CONTACT US
FOR MORE DETAILS

+91 95993-87841 www.ignitetechnologies.in



JOIN OUR TRAINING PROGRAMS







