

Package ‘GWmodel’

September 30, 2016

Type Package

Version 2.0-1

Date 2016-09-30

Title Geographically-Weighted Models

Depends R (>= 3.0.0),maptools (>= 0.5-2), robustbase,sp,Rcpp (>= 0.12.0), RcppArmadillo (>= 0.6.2.2.0)

LinkingTo Rcpp,RcppArmadillo

Suggests mvoutlier, RColorBrewer, gstat

Description In GWmodel, we introduce techniques from a particular branch of spatial statistics, termed geographically-weighted (GW) models. GW models suit situations when data are not described well by some global model, but where there are spatial regions where a suitably localised calibration provides a better description. GWmodel includes functions to calibrate: GW summary statistics, GW principal components analysis, GW discriminant analysis and various forms of GW regression; some of which are provided in basic and robust (outlier resistant) forms.

Author Binbin Lu[aut], Paul Harris[aut], Martin Charlton[aut], Chris Brunsdon[aut], Tomoki Nakaya[aut], Isabella Gollini[ctb]

Maintainer Binbin Lu <binbinlu@whu.edu.cn>

License GPL (>= 2)

Repository CRAN

URL <http://gwr.nuim.ie/>

Archs i386, x64

R topics documented:

| | |
|---------------------------|----|
| GWmodel-package | 3 |
| bw.ggwr | 4 |
| bw.gw.average | 5 |
| bw.gwda | 6 |
| bw.gwpca | 7 |
| bw.gwr | 8 |
| bw.gwr.lcr | 9 |
| DubVoter | 11 |
| EWHP | 12 |
| EWOutline | 13 |

| | |
|----------------------------------|----|
| Georgia | 13 |
| GeorgiaCounties | 14 |
| ggwr.cv | 14 |
| ggwr.cv.contrib | 15 |
| gw.dist | 16 |
| gw.pcplot | 18 |
| gw.weight | 19 |
| gwda | 20 |
| gwpca | 21 |
| gwpca.check.components | 24 |
| gwpca.cv | 24 |
| gwpca.cv.contrib | 25 |
| gwpca.glyph.plot | 26 |
| gwpca.montecarlo.1 | 27 |
| gwpca.montecarlo.2 | 29 |
| gwr.basic | 30 |
| gwr.collin.diagno | 32 |
| gwr.cv | 34 |
| gwr.cv.contrib | 35 |
| gwr.generalised | 36 |
| gwr.hetero | 37 |
| gwr.lcr | 39 |
| gwr.lcr.cv | 41 |
| gwr.lcr.cv.contrib | 42 |
| gwr.mink.approach | 44 |
| gwr.mink.matrixview | 45 |
| gwr.mink.pval | 46 |
| gwr.mixed | 47 |
| gwr.model.selection | 49 |
| gwr.model.sort | 51 |
| gwr.model.view | 51 |
| gwr.montecarlo | 52 |
| gwr.predict | 53 |
| gwr.robust | 55 |
| gwr.t.adjust | 57 |
| gwr.write | 58 |
| gwss | 59 |
| gwss.montecarlo | 61 |
| LondonBorough | 62 |
| LondonHP | 63 |
| USelect | 64 |

Description

In GWmodel, we introduce techniques from a particular branch of spatial statistics, termed geographically-weighted (GW) models. GW models suit situations when data are not described well by some global model, but where there are spatial regions where a suitably localised calibration provides a better description. GWmodel includes functions to calibrate: GW summary statistics, GW principal components analysis, GW discriminant analysis and various forms of GW regression; some of which are provided in basic and robust (outlier resistant) forms.

Details

| | |
|-----------|------------|
| Package: | GWmodel |
| Type: | Package |
| Version: | 2.0-1 |
| Date: | 2016-09-30 |
| License: | GPL (>=2) |
| LazyLoad: | yes |

Note

Acknowledgements: We gratefully acknowledge support from Science Foundation Ireland under the National Development Plan through the award of a Strategic Research Centre grant 07-SRC-I1168.

A beta versions can always be found at https://github.com/lbb220/GWmodel/blob/master/GWmodel_beta, which includes all the newly developed functions for GW models.

For latest tutorials on using GWmodel please go to: <https://rpubs.com/gwmodel>

Author(s)

Binbin Lu, Paul Harris, Martin Charlton, Chris Brunsdon, Tomoki Nakaya, Isabella Gollini

Maintainer: Binbin Lu <binbinlu@whu.edu.cn>

References

Gollini I, Lu B, Charlton M, Brunsdon C, Harris P (2015) GWmodel: an R Package for exploring Spatial Heterogeneity using Geographically Weighted Models. Journal of Statistical Software, 63(17):1-50, <http://www.jstatsoft.org/v63/i17/>

Lu B, Harris P, Charlton M, Brunsdon C (2014) The GWmodel R Package: further topics for exploring Spatial Heterogeneity using Geographically Weighted Models. Geo-spatial Information Science 17(2): 85-101, <http://www.tandfonline.com/doi/abs/10.1080/10095020.2014.917453>

| | |
|---------|---|
| bw.ggwr | <i>Bandwidth selection for generalised geographically weighted regression (GWR)</i> |
|---------|---|

Description

A function for automatic bandwidth selection to calibrate a generalised GWR model

Usage

```
bw.ggwr(formula, data, family = "poisson", approach = "CV",
kernel = "bisquare", adaptive = FALSE, p = 2, theta = 0, longlat = F, dMat)
```

Arguments

| | |
|----------|--|
| formula | Regression model formula of a formula object |
| data | a Spatial*DataFrame, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| family | a description of the error distribution and link function to be used in the model, which can be specified by “poisson” or “binomial” |
| approach | specified by CV for cross-validation approach or by AIC corrected (AICc) approach |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5 * (vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1 - (vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1 - (vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| dMat | a pre-specified distance matrix, it can be calculated by the function gw.dist |

Value

Returns the adaptive or fixed distance bandwidth

Note

For a discontinuous kernel function, a bandwidth can be specified either as a fixed (constant) distance or as a fixed (constant) number of local data (i.e. an adaptive distance). For a continuous kernel function, a bandwidth can be specified either as a fixed distance or as a 'fixed quantity that reflects local sample size' (i.e. still an 'adaptive' distance but the actual local sample size will be the sample size as functions are continuous). In practise a fixed bandwidth suits fairly regular sample configurations whilst an adaptive bandwidth suits highly irregular sample configurations. Adaptive bandwidths ensure sufficient (and constant) local information for each local calibration. This note is applicable to all GW models

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

bw.gw.average

*Bandwidth selection for GW averages***Description**

A function for automatic bandwidth selections to calculate GW averages, including means and medians, via a cross-validation approach.

Usage

```
bw.gw.average(data, summary.locat, vars, kernel = "bisquare", adaptive = FALSE,
              p = 2, theta = 0, longlat = F, dMat)
```

Arguments

| | |
|---------------|--|
| data | a Spatial*DataFrame, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| summary.locat | a Spatial*DataFrame object for providing summary locations, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| vars | a vector of variable names to be summarized |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5 * (vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1 - (vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1 - (vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| dMat | a pre-specified distance matrix, it can be calculated by the function gw.dist |

Value

Returns the adaptive or fixed distance bandwidths (in a two-column matrix) for calculating the averages of each variable.

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

bw.gwda

*Bandwidth selection for GW Discriminant Analysis***Description**

A function for automatic bandwidth selection for GW Discriminant Analysis using a cross-validation approach only

Usage

```
bw.gwda(formula, data, COV.gw = T, prior.gw = T, mean.gw = T,
        prior = NULL, wqda = F, kernel = "bisquare", adaptive
        = FALSE, p = 2, theta = 0, longlat = F, dMat)
```

Arguments

| | |
|----------|--|
| formula | Model formula of a formula object |
| data | a Spatial*DataFrame for training, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| COV.gw | if true, localised variance-covariance matrix is used for GW discriminant analysis; otherwise, global variance-covariance matrix is used |
| mean.gw | if true, localised mean is used for GW discriminant analysis; otherwise, global mean is used |
| prior.gw | if true, localised prior probability is used for GW discriminant analysis; otherwise, fixed prior probability is used |
| prior | a vector of given prior probability |
| wqda | if TRUE, a weighted quadratic discriminant analysis will be applied; otherwise a weighted linear discriminant analysis will be applied |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5*(vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1-(vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1-(vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| dMat | a pre-specified distance matrix, it can be calculated by the function gw.dist |

Value

Returns the adaptive or fixed distance bandwidth.

Note

For a discontinuous kernel function, a bandwidth can be specified either as a fixed (constant) distance or as a fixed (constant) number of local data (i.e. an adaptive distance). For a continuous kernel function, a bandwidth can be specified either as a fixed distance or as a 'fixed quantity that reflects local sample size' (i.e. still an 'adaptive' distance but the actual local sample size will be the sample size as functions are continuous). In practise a fixed bandwidth suits fairly regular sample configurations whilst an adaptive bandwidth suits highly irregular sample configurations. Adaptive bandwidths ensure sufficient (and constant) local information for each local calibration. This note is applicable to all GW models

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

bw.gwpca

Bandwidth selection for Geographically Weighted Principal Components Analysis (GWPCA)

Description

A function for automatic bandwidth selection to calibrate a basic or robust GWPCA via a cross-validation approach only

Usage

```
bw.gwpca(data, vars, k=2, robust=FALSE, kernel="bisquare", adaptive=FALSE, p=2,
          theta=0, longlat=F, dMat)
```

Arguments

| | |
|----------|--|
| data | a Spatial*DataFrame, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| vars | a vector of variable names to be evaluated |
| k | the number of retained components, and it must be less than the number of variables |
| robust | if TRUE, robust GWPCA will be applied; otherwise basic GWPCA will be applied |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5*(vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1-(vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1-(vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| dMat | a pre-specified distance matrix, it can be calculated by the function gw.dist |

Value

Returns the adaptive or fixed distance bandwidth

Note

For a discontinuous kernel function, a bandwidth can be specified either as a fixed (constant) distance or as a fixed (constant) number of local data (i.e. an adaptive distance). For a continuous kernel function, a bandwidth can be specified either as a fixed distance or as a 'fixed quantity that reflects local sample size' (i.e. still an 'adaptive' distance but the actual local sample size will be the sample size as functions are continuous). In practise a fixed bandwidth suits fairly regular sample configurations whilst an adaptive bandwidth suits highly irregular sample configurations. Adaptive bandwidths ensure sufficient (and constant) local information for each local calibration. This note is applicable to all GW models

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

References

Harris P, Clarke A, Juggins S, Brunson C, Charlton M (2015) Enhancements to a geographically weighted principal components analysis in the context of an application to an environmental data set. *Geographical Analysis* 47: 146-172

 bw.gwr

Bandwidth selection for basic GWR

Description

A function for automatic bandwidth selection to calibrate a basic GWR model

Usage

```
bw.gwr(formula, data, approach="CV", kernel="bisquare",
        adaptive=FALSE, p=2, theta=0, longlat=F, dMat)
```

Arguments

| | |
|----------|--|
| formula | Regression model formula of a formula object |
| data | a Spatial*DataFrame, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| approach | specified by CV for cross-validation approach or by AIC corrected (AICc) approach |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5 * (vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1 - (vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1 - (vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |

| | |
|----------|---|
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| dMat | a pre-specified distance matrix, it can be calculated by the function gw.dist |

Value

Returns the adaptive or fixed distance bandwidth

Note

For a discontinuous kernel function, a bandwidth can be specified either as a fixed (constant) distance or as a fixed (constant) number of local data (i.e. an adaptive distance). For a continuous kernel function, a bandwidth can be specified either as a fixed distance or as a 'fixed quantity that reflects local sample size' (i.e. still an 'adaptive' distance but the actual local sample size will be the sample size as functions are continuous). In practise a fixed bandwidth suits fairly regular sample configurations whilst an adaptive bandwidth suits highly irregular sample configurations. Adaptive bandwidths ensure sufficient (and constant) local information for each local calibration. This note is applicable to all GW models

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

 bw.gwr.lcr

Bandwidth selection for locally compensated ridge GWR (GWR-LCR)

Description

A function for automatic bandwidth selection for [gwr.lcr](#) via a cross-validation approach only

Usage

```
bw.gwr.lcr(formula, data, kernel="bisquare",
            lambda=0, lambda.adjust=FALSE, cn.thresh=NA,
            adaptive=FALSE, p=2, theta=0, longlat=F, dMat)
```

Arguments

| | |
|---------|--|
| formula | Regression model formula of a formula object |
| data | a Spatial*DataFrame, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5 * (vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1 - (vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1 - (vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |

| | |
|---------------|--|
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| lambda | option for a globally-defined (constant) ridge parameter. Default is lambda=0, which gives a basic GWR fit |
| lambda.adjust | a locally-varying ridge parameter. Default FALSE, refers to: (i) a basic GWR without a local ridge adjustment (i.e. lambda=0, everywhere); or (ii) a penalised GWR with a global ridge adjustment (i.e. lambda is user-specified as some constant, other than 0 everywhere); if TRUE, use cn.tresh to set the maximum condition number. For locations with a condition number (for its local design matrix), above this user-specified threshold, a local ridge parameter is found |
| cn.tresh | maximum value for condition number, commonly set between 20 and 30 |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| dMat | a pre-specified distance matrix, it can be calculated by the function gw.dist |

Value

Returns the adaptive or fixed distance bandwidth

Note

For a discontinuous kernel function, a bandwidth can be specified either as a fixed (constant) distance or as a fixed (constant) number of local data (i.e. an adaptive distance). For a continuous kernel function, a bandwidth can be specified either as a fixed distance or as a 'fixed quantity that reflects local sample size' (i.e. still an 'adaptive' distance but the actual local sample size will be the sample size as functions are continuous). In practise a fixed bandwidth suits fairly regular sample configurations whilst an adaptive bandwidth suits highly irregular sample configurations. Adaptive bandwidths ensure sufficient (and constant) local information for each local calibration. This note is applicable to all GW models

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

References

Gollini I, Lu B, Charlton M, Brunsdon C, Harris P (2015) GWmodel: an R Package for exploring Spatial Heterogeneity using Geographically Weighted Models. *Journal of Statistical Software* 63(17): 1-50

DubVoter

*Voter turnout data in Greater Dublin(SpatialPolygonsDataFrame)***Description**

Voter turnout and social characters data in Greater Dublin for the 2002 General election and the 2002 census. Note that this data set was originally thought to relate to 2004, so for continuity we have retained the associated variable names.

Usage

```
data(DubVoter)
```

Format

A SpatialPolygonsDataFrame with 322 electoral divisions on the following 11 variables.

DED_ID a vector of ID

X a numeric vector of x coordinates

Y a numeric vector of y coordinates

DiffAdd percentage of the population in each ED who are one-year migrants (i.e. moved to a different address 1 year ago)

LARent percentage of the population in each ED who are local authority renters

SC1 percentage of the population in each ED who are social class one (high social class)

Unempl percentage of the population in each ED who are unemployed

LowEduc percentage of the population in each ED who are with little formal education

Age18_24 percentage of the population in each ED who are age group 18-24

Age25_44 percentage of the population in each ED who are age group 25-44

Age45_64 percentage of the population in each ED who are age group 45-64

GenEl2004 percentage of population in each ED who voted in 2004 election

Details

Variables are from DubVoter.shp.

References

Kavanagh A (2006) Turnout or turned off? Electoral participation in Dublin in the early 21st Century. *Journal of Irish Urban Studies* 3(2):1-24

Harris P, Brunsdon C, Charlton M (2011) Geographically weighted principal components analysis. *International Journal of Geographical Information Science* 25 (10):1717-1736

Examples

```
data(DubVoter)
ls()
## Not run:
spplot(Dub.voter,names(Dub.voter)[4:12])

## End(Not run)
```

EWHP

*House price data set (DataFrame) in England and Wales***Description**

A house price data set for England and Wales from 2001 with 9 hedonic (explanatory) variables.

Usage

```
data(EWHP)
```

Format

A data frame with 519 observations on the following 12 variables.

Easting a numeric vector, X coordinate

Northing a numeric vector, Y coordinate

PurPrice a numeric vector, the purchase price of the property

BldIntWr a numeric vector, 1 if the property was built during the world war, 0 otherwise

BldPostW a numeric vector, 1 if the property was built after the world war, 0 otherwise

Bld60s a numeric vector, 1 if the property was built between 1960 and 1969, 0 otherwise

Bld70s a numeric vector, 1 if the property was built between 1970 and 1979, 0 otherwise

Bld80s a numeric vector, 1 if the property was built between 1980 and 1989, 0 otherwise

TypDetch a numeric vector, 1 if the property is detached (i.e. it is a stand-alone house), 0 otherwise

TypSemiD a numeric vector, 1 if the property is semi detached, 0 otherwise

TypFlat a numeric vector, if the property is a flat (or 'apartment' in the USA), 0 otherwise

FlrArea a numeric vector, floor area of the property in square metres

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

References

Fotheringham, A.S., Brunsdon, C., and Charlton, M.E. (2002), Geographically Weighted Regression: The Analysis of Spatially Varying Relationships, Chichester: Wiley.

Examples

```
###
data(EWHP)
head(ewhp)
houses.spdf <- SpatialPointsDataFrame(ewhp[, 1:2], ewhp)
####Get the border of England and Wales
data(EWOutline)
plot(ewoutline)
plot(houses.spdf, add = TRUE, pch = 16)
```

EWOutline

*Outline of England and Wales for data [EWHP](#)***Description**

Outline (SpatialPolygonsDataFrame) of the England and Wales house price data [EWHP](#).

Usage

```
data(EWOutline)
```

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

Georgia

*Georgia census data set (csv file)***Description**

Census data from the county of Georgia, USA

Usage

```
data(Georgia)
```

Format

A data frame with 159 observations on the following 13 variables.

AreaKey An identification number for each county

Latitude The latitude of the county centroid

Longitud The longitude of the county centroid

TotPop90 Population of the county in 1990

PctRural Percentage of the county population defined as rural

PctBach Percentage of the county population with a bachelors degree

PctEld Percentage of the county population aged 65 or over

PctFB Percentage of the county population born outside the US

PctPov Percentage of the county population living below the poverty line

PctBlack Percentage of the county population who are black

ID a numeric vector of IDs

X a numeric vector of x coordinates

Y a numeric vector of y coordinates

Details

This data set can also be found in GWR 3 and in spgwr.

References

Fotheringham S, Brunson, C, and Charlton, M (2002), Geographically Weighted Regression: The Analysis of Spatially Varying Relationships, Chichester: Wiley.

Examples

```
data(Georgia)
ls()
coords <- cbind(Gedu.df$X, Gedu.df$Y)
educ.spdf <- SpatialPointsDataFrame(coords, Gedu.df)
spplot(educ.spdf, names(educ.spdf)[4:10])
```

| | |
|-----------------|---|
| GeorgiaCounties | <i>Georgia counties data (SpatialPolygonsDataFrame)</i> |
|-----------------|---|

Description

The Georgia census data with boundaries for mapping

Usage

```
data(GeorgiaCounties)
```

Details

This data set can also be found in GWR 3 and in spgwr.

Examples

```
data(GeorgiaCounties)
plot(Gedu.counties)
data(Georgia)
coords <- cbind(Gedu.df$X, Gedu.df$Y)
educ.spdf <- SpatialPointsDataFrame(coords, Gedu.df)
plot(educ.spdf, add=TRUE)
```

| | |
|---------|---|
| ggwr.cv | <i>Cross-validation score for a specified bandwidth for generalised GWR</i> |
|---------|---|

Description

This function finds the cross-validation score for a specified bandwidth for generalised GWR. It can be used to construct the bandwidth function across all possible bandwidths and compared to that found automatically.

Usage

```
ggwr.cv(bw, X, Y, family="poisson", kernel="bisquare", adaptive=F, dp.locat,
        p=2, theta=0, longlat=F, dMat)
```

Arguments

| | |
|----------|--|
| bw | bandwidth used in the weighting function;fixed (distance) or adaptive bandwidth(number of nearest neighbours) |
| X | a numeric matrix of the independent data with an extra column of “ones” for the 1st column |
| Y | a column vector of the dependent data |
| family | a description of the error distribution and link function to be used in the model, which can be specified by “poisson” or “binomial” |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5*(vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1-(vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1-(vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| dp.locat | a two-column numeric array of observation coordinates |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| dMat | a pre-specified distance matrix, it can be calculated by the function gw.dist |

Value

| | |
|----------|------------------------|
| CV.score | cross-validation score |
|----------|------------------------|

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

| | |
|-----------------|---|
| ggwr.cv.contrib | <i>Cross-validation data at each observation location for a generalised GWR model</i> |
|-----------------|---|

Description

This function finds the individual cross-validation score at each observation location, for a generalised GWR model, for a specified bandwidth. These data can be mapped to detect unusually high or low cross-validations scores.

Usage

```
ggwr.cv.contrib(bw, X, Y,family="poisson", kernel="bisquare",adaptive=F,
               dp.locat, p=2, theta=0, longlat=F,dMat)
```

Arguments

| | |
|----------|--|
| bw | bandwidth used in the weighting function;fixed (distance) or adaptive bandwidth(number of nearest neighbours) |
| X | a numeric matrix of the independent data with an extra column of “ones” for the 1st column |
| Y | a column vector of the dependent data |
| family | a description of the error distribution and link function to be used in the model, which can be specified by “poisson” or “binomial” |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5*(vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1-(vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1-(vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| dp.locat | a two-column numeric array of observation coordinates |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| dMat | a pre-specified distance matrix, it can be calculated by the function gw.dist |

Value

| | |
|----|--|
| CV | a data vector consisting of squared residuals, whose sum is the cross-validation score for the specified bandwidth |
|----|--|

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

gw.dist

Distance matrix calculation

Description

Calculate a distance vector(matrix) between any GW model calibration point(s) and the data points.

Usage

```
gw.dist(dp.locat, rp.locat, focus=0, p=2, theta=0, longlat=F)
```


Arguments

| | |
|----------|--|
| dp.locat | a numeric matrix of two columns giving the coordinates of the data points |
| rp.locat | a numeric matrix of two columns giving the coordinates of the GW model calibration points |
| focus | an integer, indexing to the current GW model point, if focus=0, all the distances between all the GW model calibration points and data points will be calculated and a distance matrix will be returned; if 0<focus<length(rp.locat), then the distances between the 'focus'th GW model points and data points will be calculated and a distance vector will be returned |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |

Value

Returns a numeric distance matrix or vector; matrix with its rows corresponding to the observations and its columns corresponds to the GW model calibration points.

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

See Also

[dist](#) in **stats**

Examples

```
dp<-cbind(sample(100),sample(100))
rp<-cbind(sample(10),sample(10))
#Euclidean distance metric is used.
dist.v1<-gw.dist(dp.locat=dp, focus=5, p=2, theta=0, longlat=FALSE)
#Manhattan distance metric is used.
#The coordinate system is rotated by an angle 0.5 in radian.
dist.v2<-gw.dist(dp.locat=dp, focus=5, p=1, theta=0.5)
#Great Circle distance metric is used.
dist.v3<-gw.dist(dp.locat=dp, focus=5, longlat=TRUE)
#A generalized Minkowski distance metric is used with p= 0.75 .
#The coordinate system is rotated by an angle 0.8 in radian.
dist.v4<-gw.dist(dp.locat=dp,rp.locat=rp, focus=5, p=0.75,theta=0.8)
#####
#matrix is calculated
#Euclidean distance metric is used.
dist.m1<-gw.dist(dp.locat=dp, p=2, theta=0, longlat=FALSE)
#Manhattan distance metric is used.
#The coordinate system is rotated by an angle 0.5 in radian.
dist.m2<-gw.dist(dp.locat=dp, p=1, theta=0.5)
#Great Circle distance metric is used.
dist.m3<-gw.dist(dp.locat=dp, longlat=TRUE)
#A generalized Minkowski distance metric is used with p= 0.75 .
#The coordinate system is rotated by an angle 0.8 in radian.
dist.m4<-gw.dist(dp.locat=dp,rp.locat=rp, p=0.75,theta=0.8)
```

| | |
|-----------|--|
| gw.pcplot | <i>Geographically weighted parallel coordinate plot for investigating multivariate data sets</i> |
|-----------|--|

Description

This function provides a geographically weighted parallel coordinate plot for locally investigating a multivariate data set. It has an option that weights the lines of the plot with increasing levels of transparency, according to their observation's distance from a specified focal/observation point.

Usage

```
gw.pcplot(data, vars, focus, bw, adaptive = FALSE, ylim=NULL, ylab="", fixtrans=FALSE,
           p=2, theta=0, longlat=F, dMat,...)
```

Arguments

| | |
|----------|---|
| data | a Spatial*DataFrame, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| vars | a vector of variable names to be evaluated |
| focus | an integer, indexing to the observation point |
| bw | bandwidth used in the weighting function; fixed (distance) or adaptive bandwidth(number of nearest neighbours) |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| ylim | the y limits of the plot |
| ylab | a label for the y axis |
| fixtrans | if TRUE, the transparency of the neighbouring observation plot lines increases with distance; If FALSE a standard (non-spatial) parallel coordinate plot is returned. |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| dMat | a pre-specified distance matrix, it can be calculated by the function gw.dist |
| ... | other graphical parameters, (see par) |

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

References

Harris P, Brunsdon C, Charlton M, Juggins S, Clarke A (2014) Multivariate spatial outlier detection using robust geographically weighted methods. *Mathematical Geosciences* 46(1) 1-31

Harris P, Clarke A, Juggins S, Brunsdon C, Charlton M (2015) Enhancements to a geographically weighted principal components analysis in the context of an application to an environmental data set. *Geographical Analysis* 47: 146-172

gw.weight

*Weight matrix calculation***Description**

Calculate a weight vector(matrix) from a distance vector(matrix).

Usage

```
gw.weight(vdist,bw,kernel,adaptive=FALSE)
```

Arguments

| | |
|-----------------------|--|
| <code>vdist</code> | a distance matrix or vector |
| <code>bw</code> | bandwidth used in the weighting function, possibly calculated by bw.gwr ; fixed (distance) or adaptive bandwidth(number of nearest neighbours) |
| <code>kernel</code> | function chosen as follows: gaussian: $wgt = \exp(-.5*(vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1-(vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1-(vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| <code>adaptive</code> | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |

Value

Returns a numeric weight matrix or vector; matrix with its rows corresponding to the observations and its columns corresponds to the GW model calibration points.

Note

The gaussian and exponential kernel functions are continuous and valued in the interval (0,1]; while bisquare, tricube and boxcar kernel functions are discontinuous and valued in the interval [0,1]. Notably, the upper limit of the bandwidth is exactly the number of observations when the adaptive kernel is used. In this function, the adaptive bandwidth will be specified as the number of observations even though a larger number is assigned. The function will be the same as a global application function (i.e. all weights are 1) when the adaptive bandwidth is equal to or larger than the number of observations when using the boxcar kernel function.

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

Description

This function implements GW discriminant analysis.

Usage

```
gwda(formula, data, predict.data, validation = T, COV.gw=T,
      mean.gw=T, prior.gw=T, prior=NULL, wqda =F,
      kernel = "bisquare", adaptive = FALSE, bw,
      p = 2, theta = 0, longlat = F, dMat)
## S3 method for class 'gwda'
print(x, ...)
```

Arguments

| | |
|--------------|--|
| formula | Model formula of a formula object |
| data | a Spatial*DataFrame for training, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| predict.data | a Spatial*DataFrame object for prediction, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp ; if it is not given, the training data will be predicted using leave-one-out cross-validation. |
| validation | If TRUE, the results from the prediction will be validated and the correct proportion will be calculated. |
| COV.gw | if true, localised variance-covariance matrix is used for GW discriminant analysis; otherwise, global variance-covariance matrix is used |
| mean.gw | if true, localised mean is used for GW discriminant analysis; otherwise, global mean is used |
| prior.gw | if true, localised prior probability is used for GW discriminant analysis; otherwise, fixed prior probability is used |
| prior | a vector of given prior probability |
| wqda | if TRUE, weighted quadratic discriminant analysis will be applied; otherwise weighted linear discriminant analysis will be applied |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5 * (vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1 - (vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1 - (vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| bw | bandwidth used in the weighting function, possibly calculated by bw.gwpca ; fixed (distance) or adaptive bandwidth(number of nearest neighbours) |

| | |
|---------|---|
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| dMat | a pre-specified distance matrix, it can be calculated by the function gw.dist |
| x | an object of class "gwda" |
| ... | arguments passed through (unused) |

Value

A class of object "gwda"

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

References

- Brunsdon, C, Fotheringham S, and Charlton, M (2007), Geographically Weighted Discriminant Analysis, *Geographical Analysis* 39:376-396
- Lu B, Harris P, Charlton M, Brunsdon C (2014) The GWmodel R Package: further topics for exploring Spatial Heterogeneity using Geographically Weighted Models. *Geo-spatial Information Science* 17(2): 85-101

| | |
|-------|--------------|
| gwpca | <i>GWPCA</i> |
|-------|--------------|

Description

This function implements basic or robust GWPCA.

Usage

```
gwpca(data, elocat, vars, k = 2, robust = FALSE, kernel = "bisquare",
      adaptive = FALSE, bw, p = 2, theta = 0, longlat = F, cv = T,
      dMat)
```

Arguments

| | |
|--------|--|
| data | a Spatial*DataFrame, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| elocat | a two-column numeric array or Spatial*DataFrame object for providing evaluation locations, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| vars | a vector of variable names to be evaluated |
| k | the number of retained components; k must be less than the number of variables |
| robust | if TRUE, robust GWPCA will be applied; otherwise basic GWPCA will be applied |

| | |
|----------|--|
| kernel | function chosen as follows: gaussian: $\text{wgt} = \exp(-.5 * (\text{vdist}/\text{bw})^2)$; exponential: $\text{wgt} = \exp(-\text{vdist}/\text{bw})$; bisquare: $\text{wgt} = (1 - (\text{vdist}/\text{bw})^2)^2$ if $\text{vdist} < \text{bw}$, $\text{wgt}=0$ otherwise; tricube: $\text{wgt} = (1 - (\text{vdist}/\text{bw})^3)^3$ if $\text{vdist} < \text{bw}$, $\text{wgt}=0$ otherwise; boxcar: $\text{wgt}=1$ if $\text{dist} < \text{bw}$, $\text{wgt}=0$ otherwise |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| bw | bandwidth used in the weighting function, possibly calculated by bw.gwpca ; fixed (distance) or adaptive bandwidth (number of nearest neighbours) |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| cv | If TRUE, cross-validation data will be found that are used to calculate the cross-validation score for the specified bandwidth. |
| dMat | a pre-specified distance matrix, it can be calculated by the function gw.dist |

Value

A list of components:

| | |
|--------------|---|
| loadings | The localised loadings |
| var | The local amount of variance accounted for by each component |
| GW.arguments | A list of geographically weighted arguments supplied to the function call |
| CV | Vector of cross-validation data |

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

References

- Fotheringham S, Brunson, C, and Charlton, M (2002), Geographically Weighted Regression: The Analysis of Spatially Varying Relationships, Chichester: Wiley.
- Harris P, Brunson C, Charlton M (2011) Geographically weighted principal components analysis. International Journal of Geographical Information Science 25:1717-1736
- Harris P, Brunson C, Charlton M, Juggins S, Clarke A (2014) Multivariate spatial outlier detection using robust geographically weighted methods. Mathematical Geosciences 46(1) 1-31
- Harris P, Clarke A, Juggins S, Brunson C, Charlton M (2014) Geographically weighted methods and their use in network re-designs for environmental monitoring. Stochastic Environmental Research and Risk Assessment 28: 1869-1887
- Harris P, Clarke A, Juggins S, Brunson C, Charlton M (2015) Enhancements to a geographically weighted principal components analysis in the context of an application to an environmental data set. Geographical Analysis 47: 146-172

Examples

```
## Not run:
if(require("mvoutlier") && require("RColorBrewer"))
{
  data(bsstop)
  Data.1 <- bsstop[, 1:14]
  colnames(Data.1)
  Data.1.scaled <- scale(as.matrix(Data.1[5:14])) # standardised data...
  rownames(Data.1.scaled) <- Data.1[, 1]
  #compute principal components:
  pca <- princomp(Data.1.scaled, cor = FALSE, scores = TRUE)
  # use covariance matrix to match the following...
  pca$loadings
  data(bss.background)
  backdrop <- function()
  {
    plot(bss.background, asp = 1, type = "l", xaxt = "n", yaxt = "n",
         xlab = "", ylab = "", bty = "n", col = "grey")
  }
  pc1 <- pca$scores[, 1]
  backdrop()
  points(Data.1$XC00[pc1 > 0], Data.1$YC00[pc1 > 0], pch = 16, col = "blue")
  points(Data.1$XC00[pc1 < 0], Data.1$YC00[pc1 < 0], pch = 16, col = "red")

  #Geographically Weighted PCA and mapping the local loadings
  # Coordinates of the sites
  Coords1 <- as.matrix(cbind(Data.1$XC00, Data.1$YC00))
  d1s <- SpatialPointsDataFrame(Coords1, as.data.frame(Data.1.scaled))
  pca.gw <- gwpca(d1s, vars=colnames(d1s@data), bw=1000000, k=10)
  local.loadings <- pca.gw$loadings[, , 1]

  # Mapping the winning variable with the highest absolute loading
  # note first component only - would need to explore all components..

  lead.item <- colnames(local.loadings)[max.col(abs(local.loadings))]
  df1p <- SpatialPointsDataFrame(Coords1, data.frame(lead = lead.item))
  backdrop()
  colour <- brewer.pal(8, "Dark2")[match(df1p$lead, unique(df1p$lead))]
  plot(df1p, pch = 18, col = colour, add = TRUE)
  legend("topleft", as.character(unique(df1p$lead)), pch = 18, col =
        brewer.pal(8, "Dark2"))
  backdrop()

  #Glyph plots give a view of all the local loadings together
  glyph.plot(local.loadings, Coords1, add = TRUE)

  #it is not immediately clear how to interpret the glyphs fully,
  #so inter-actively identify the full loading information using:
  check.components(local.loadings, Coords1)

  # GWPCA with an optimal bandwidth
  bw.choice <- bw.gwpca(d1s, vars=colnames(d1s@data), k=2)
  pca.gw.auto <- gwpca(d1s, vars=colnames(d1s@data), bw=bw.choice, k=2)
  # note first component only - would need to explore all components..
  local.loadings <- pca.gw.auto$loadings[, , 1]

  lead.item <- colnames(local.loadings)[max.col(abs(local.loadings))]
  df1p <- SpatialPointsDataFrame(Coords1, data.frame(lead = lead.item))
}
```

```

backdrop()
colour <- brewer.pal(8, "Dark2")[match(df1p$lead, unique(df1p$lead))]
plot(df1p, pch = 18, col = colour, add = TRUE)
legend("topleft", as.character(unique(df1p$lead)), pch = 18,
col = brewer.pal(8, "Dark2"))

# GWPCPLOT for investigating the raw multivariate data
gw.pcplot(d1s, vars=colnames(d1s@data),focus=359, bw = bw.choice)
}

## End(Not run)

```

gwpca.check.components

Interaction tool with the GWPCA glyph map

Description

The function interacts with the multivariate glyph plot of GWPCA loadings.

Usage

```
gwpca.check.components(ld,loc)
```

Arguments

| | |
|-----|--|
| ld | GWPCA loadings returned by gwpca |
| loc | a 2-column numeric array of GWPCA evaluation locations |

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

See Also

[gwpca.glyph.plot](#)

gwpca.cv

Cross-validation score for a specified bandwidth for GWPCA

Description

This function finds the cross-validation score for a specified bandwidth for basic or robust GWPCA. It can be used to construct the bandwidth function across all possible bandwidths and compared to that found automatically.

Usage

```
gwpca.cv(bw,x,loc,k=2,robust=FALSE,kernel="bisquare",adaptive=FALSE,p=2,
theta=0, longlat=F,dMat)
```


Arguments

| | |
|----------|--|
| bw | bandwidth used in the weighting function;fixed (distance) or adaptive bandwidth(number of nearest neighbours) |
| x | the variable matrix |
| loc | a two-column numeric array of observation coordinates |
| k | the number of retained components; k must be less than the number of variables |
| robust | if TRUE, robust GWPCA will be applied; otherwise basic GWPCA will be applied |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5*(vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1-(vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1-(vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| dMat | a pre-specified distance matrix, it can be calculated by the function gw.dist |

Value

| | |
|----------|------------------------|
| CV.score | cross-validation score |
|----------|------------------------|

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

gwpca.cv.contrib

Cross-validation data at each observation location for a GWPCA

Description

This function finds the individual cross-validation score at each observation location, for a GWPCA model, for a specified bandwidth. These data can be mapped to detect unusually high or low cross-validations scores.

Usage

```
gwpca.cv.contrib(x,loc,bw, k=2,robust=FALSE,kernel="bisquare",adaptive=FALSE,
                p=2, theta=0, longlat=F,dMat)
```

Arguments

| | |
|----------|--|
| x | the variable matrix |
| loc | a two-column numeric array of observation coordinates |
| bw | bandwidth used in the weighting function;fixed (distance) or adaptive bandwidth(number of nearest neighbours) |
| k | the number of retained components; k must be less than the number of variables |
| robust | if TRUE, robust GWPCA will be applied; otherwise basic GWPCA will be applied |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5*(vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1-(vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1-(vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| dMat | a pre-specified distance matrix, it can be calculated by the function gw.dist |

Value

| | |
|----|--|
| CV | a data vector consisting of squared residuals, whose sum is the cross-validation score for the specified bandwidth (bw) and component (k). |
|----|--|

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

gwpca.glyph.plot

Multivariate glyph plots of GWPCA loadings

Description

This function provides a multivariate glyph plot of GWPCA loadings at each output location.

Usage

```
gwpca.glyph.plot(ld,loc, r1=50, add=FALSE,alpha=1,sep.contrasts=FALSE)
```

Arguments

| | |
|---------------|--|
| ld | GWPCA loadings returned by gwpca |
| loc | a two-column numeric array for providing evaluation locations of GWPCA calibration |
| r1 | argument for the size of the glyphs, default is 50; glyphs get larger as r1 is reduced |
| add | if TRUE, add the plot to the existing window. |
| alpha | the level of transparency of glyph from function <code>rgb()</code> and ranges from 0 to max (fully transparent to opaque) |
| sep.contrasts | allows different types of glyphs and relates to whether absolute loadings are used (TRUE) or not |

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

References

Harris P, Brunsdon C, Charlton M (2011) Geographically weighted principal components analysis. *International Journal of Geographical Information Science* 25:1717-1736

| | |
|--------------------|--|
| gwpca.montecarlo.1 | <i>Monte Carlo (randomisation) test for significance of GWPCA eigenvalue variability for the first component only - option 1</i> |
|--------------------|--|

Description

This function implements a Monte Carlo (randomisation) test for a basic or robust GW PCA with the bandwidth pre-specified and constant. The test evaluates whether the GW eigenvalues vary significantly across space for the first component only.

Usage

```
gwpca.montecarlo.1(data, bw, vars, k = 2, nsims=99, robust = FALSE, kernel = "bisquare",
                   adaptive = FALSE, p = 2, theta = 0, longlat = F, dMat)
## S3 method for class 'mcsims'
plot(x, sname="SD of local eigenvalues from randomisations", ...)
```

Arguments

| | |
|-------|--|
| data | a Spatial*DataFrame, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| bw | bandwidth used in the weighting function, possibly calculated by bw.gwpca ; fixed (distance) or adaptive bandwidth(number of nearest neighbours) |
| vars | a vector of variable names to be evaluated |
| k | the number of retained components; k must be less than the number of variables |
| nsims | the number of simulations for MontCarlo test |

| | |
|----------|--|
| robust | if TRUE, robust GWPCA will be applied; otherwise basic GWPCA will be applied |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5*(vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1-(vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1-(vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| dMat | a pre-specified distance matrix, it can be calculated by the function gw.dist |
| x | an object of class "mcsims", returned by the function gwpca.montecarlo.1 or gwpca.montecarlo.2 |
| sname | the label for the observed value on the plot |
| ... | arguments passed through (unused) |

Value

A list of components:

| | |
|--------|--|
| actual | the observed standard deviations (SD) of eigenvalues |
| sims | a vector of the simulated SDs of eigenvalues |

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

References

Harris P, Brunsdon C, Charlton M (2011) Geographically weighted principal components analysis. *International Journal of Geographical Information Science* 25:1717-1736

Examples

```
## Not run:
data(DubVoter)
DM<-gw.dist(dp.locat=coordinates(Dub.voter))
gmc.res<-gwpca.montecarlo.1(data=Dub.voter, vars=c("DiffAdd", "LARent",
"SC1", "Unempl", "LowEduc"), bw=20,dMat=DM,adaptive=TRUE)
gmc.res
plot(gmc.res)

## End(Not run)
```

| | |
|--------------------|--|
| gwpca.montecarlo.2 | <i>Monte Carlo (randomisation) test for significance of GWPCA eigenvalue variability for the first component only - option 2</i> |
|--------------------|--|

Description

This function implements a Monte Carlo (randomisation) test for a basic or robust GW PCA with the bandwidth automatically re-selected via the cross-validation approach. The test evaluates whether the GW eigenvalues vary significantly across space for the first component only.

Usage

```
gwpca.montecarlo.2(data, vars, k = 2, nsims=99, robust = FALSE, kernel = "bisquare",
  adaptive = FALSE, p = 2, theta = 0, longlat = F, dMat)
```

Arguments

| | |
|----------|--|
| data | a Spatial*DataFrame, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| vars | a vector of variable names to be evaluated |
| k | the number of retained components; k must be less than the number of variables |
| nsims | the number of simulations for MontCarlo test |
| robust | if TRUE, robust GWPCA will be applied; otherwise basic GWPCA will be applied |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5*(vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1-(vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1-(vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| dMat | a pre-specified distance matrix, it can be calculated by the function gw.dist |

Value

A list of components:

| | |
|--------|--|
| actual | the observed standard deviations (SD) of eigenvalues |
| sims | a vector of the simulated SDs of eigenvalues |

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

References

Harris P, Brunsdon C, Charlton M (2011) Geographically weighted principal components analysis. International Journal of Geographical Information Science 25:1717-1736

Examples

```
## Not run:
data(DubVoter)
DM<-gw.dist(dp.locat=coordinates(Dub.voter))
gmc.res.autow<-gwpca.montecarlo.2(data=Dub.voter, vars=c("DiffAdd", "LAREnt",
"SC1", "Unempl", "LowEduc"), dMat=DM,adaptive=TRUE)
gmc.res.autow
plot.mcsims(gmc.res.autow)

## End(Not run)
```

gwr.basic

Basic GWR model

Description

This function implements basic GWR

Usage

```
gwr.basic(formula, data, regression.points, bw, kernel="bisquare",
adaptive=FALSE, p=2, theta=0, longlat=F,dMat,F123.test=F,cv=T, W.vect=NULL)
## S3 method for class 'gwrn'
print(x, ...)
```

Arguments

| | |
|-------------------|--|
| formula | Regression model formula of a formula object |
| data | a Spatial*DataFrame, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| regression.points | a Spatial*DataFrame object, i.e. SpatialPointsDataFrame or SpatialPolygons-DataFrame as defined in package sp |
| bw | bandwidth used in the weighting function, possibly calculated by bw.gwr ;fixed (distance) or adaptive bandwidth(number of nearest neighbours) |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5*(vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1-(vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1-(vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |

| | |
|-----------|--|
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| dMat | a pre-specified distance matrix, it can be calculated by the function gw.dist |
| F123.test | If TRUE, conduct three separate F-tests according to Leung et al. (2000). |
| cv | if TRUE, cross-validation data will be calculated and returned in the output Spatial*DataFrame |
| W.vect | default NULL, if given it will be used to weight the distance weighting matrix |
| x | an object of class "gwr", returned by the function gwr.basic |
| ... | arguments passed through (unused) |

Value

A list of class "gwr":

| | |
|---------------|--|
| GW.arguments | a list class object including the model fitting parameters for generating the report file |
| GW.diagnostic | a list class object including the diagnostic information of the model fitting |
| lm | an object of class inheriting from "lm", see lm . |
| SDF | a SpatialPointsDataFrame (may be gridded) or SpatialPolygonsDataFrame object (see package "sp") integrated with fit.points,GWR coefficient estimates, y value,predicted values, coefficient standard errors and t-values in its "data" slot. |
| timings | starting and ending time. |
| this.call | the function call used. |
| Ftest.res | results of Leung's F tests when F123.test is TRUE. |

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

References

- Brunsdon, C, Fotheringham, S, Charlton, M (1996), Geographically Weighted Regression: A Method for Exploring Spatial Nonstationarity. *Geographical Analysis* 28(4):281-298
- Charlton, M, Fotheringham, S, and Brunsdon, C (2007), GWR3.0, <http://gwr.nuim.ie/>.
- Fotheringham S, Brunsdon, C, and Charlton, M (2002), *Geographically Weighted Regression: The Analysis of Spatially Varying Relationships*, Chichester: Wiley.
- Leung, Y, Mei, CL, and Zhang, WX (2000), Statistical tests for spatial nonstationarity based on the geographically weighted regression model. *Environment and Planning A*, 32, 9-32.
- Lu, B, Charlton, M, Harris, P, Fotheringham, AS (2014) Geographically weighted regression with a non-Euclidean distance metric: a case study using hedonic house price data. *International Journal of Geographical Information Science* 28(4): 660-681

Examples

```

data(LondonHP)
DM<-gw.dist(dp.locat=coordinates(londonhp))
##Compare the time consumed with and without a specified distance matrix
## Not run:
system.time(gwr.res<-gwr.basic(PURCHASE~FLOORSZ, data=londonhp, bw=1000,
                              kernel = "gaussian"))
system.time(DM<-gw.dist(dp.locat=coordinates(londonhp)))
system.time(gwr.res<-gwr.basic(PURCHASE~FLOORSZ, data=londonhp, bw=1000,
                              kernel = "gaussian", dMat=DM))

## specify an optimum bandwidth by cross-validation approach
bw1<-bw.gwr(PURCHASE~FLOORSZ, data=londonhp, kernel = "gaussian",dMat=DM)
gwr.res1<-gwr.basic(PURCHASE~FLOORSZ, data=londonhp, bw=bw1,kernel = "gaussian",
                   dMat=DM)

gwr.res1
## End(Not run)
data(LondonBorough)

nsa = list("SpatialPolygonsRescale", layout.north.arrow(), offset = c(561900,200900),
scale = 500, col=1)
## Not run:
if(require("RColorBrewer"))
{
  mypalette<-brewer.pal(6,"Spectral")
  x11()
  spplot(gwr.res1$SDF, "FLOORSZ", key.space = "right", cex=1.5, cuts=10,
        ylim=c(155840.8,200933.9), xlim=c(503568.2,561957.5),
        main="GWR estimated coefficients for FLOORSZ with a fixed bandwidth",
        col.regions=mypalette, sp.layout=list(nsa, londonborough))}

## End(Not run)
## Not run:
bw2<-bw.gwr(PURCHASE~FLOORSZ,approach="aic",adaptive=TRUE, data=londonhp,
            kernel = "gaussian", dMat=DM)
gwr.res2<-gwr.basic(PURCHASE~FLOORSZ, data=londonhp, bw=bw2,adaptive=TRUE,
                   kernel = "gaussian", dMat=DM)

gwr.res2
if(require("RColorBrewer"))
{
  x11()
  spplot(gwr.res2$SDF, "FLOORSZ", key.space = "right", cex=1.5, cuts=10,
        ylim=c(155840.8,200933.9), xlim=c(503568.2,561957.5),
        main="GWR estimated coefficients for FLOORSZ with an adaptive bandwidth",
        col.regions=mypalette, sp.layout=list(nsa,londonborough))}

## End(Not run)

```

gwr.collin.diagno

Local collinearity diagnostics for basic GWR

Description

This function provides a series of local collinearity diagnostics for the independent variables of a basic GWR model.

Usage

```
gwr.collin.diagno(formula, data, bw, kernel="bisquare",
                  adaptive=FALSE, p=2, theta=0, longlat=F, dMat)
```

Arguments

| | |
|----------|--|
| formula | Regression model formula of a formula object |
| data | a Spatial*DataFrame, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| bw | bandwidth used in the weighting function, probably calculated by <code>bw.gwr</code> or <code>bw.gwr.lcr</code> ; fixed (distance) or adaptive bandwidth (number of nearest neighbours) |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5*(vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1-(vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1-(vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| dMat | a pre-specified distance matrix, it can be calculated by the function gw.dist |

Value

| | |
|----------|---|
| corr.mat | Local correlation matrix |
| VIF | Local Variance inflation factors (VIFs) matrix |
| local_CN | Local condition numbers |
| VDP | Local variance-decomposition proportions |
| SDF | a SpatialPointsDataFrame (may be gridded) or SpatialPolygonsDataFrame object (see package “sp”) integrated with VIF, local_CN, VDP and corr.mat |

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

References

- Wheeler D, Tiefelsdorf M (2005) Multicollinearity and correlation among local regression coefficients in geographically weighted regression. *Journal of Geographical Systems* 7:161-187
- Wheeler D (2007) Diagnostic tools and a remedial method for collinearity in geographically weighted regression. *Environment and Planning A* 39:2464-2481
- Gollini I, Lu B, Charlton M, Brunsdon C, Harris P (2015) GWmodel: an R Package for exploring Spatial Heterogeneity using Geographically Weighted Models. *Journal of Statistical Software*, 63(17):1-50

gwr.cv

*Cross-validation score for a specified bandwidth for basic GWR***Description**

This function finds the cross-validation score for a specified bandwidth for basic GWR. It can be used to construct the bandwidth function across all possible bandwidths and compared to that found automatically.

Usage

```
gwr.cv(bw, X, Y, kernel="bisquare", adaptive=FALSE, dp.locat, p=2, theta=0,
       longlat=F, dMat, verbose=T)
```

Arguments

| | |
|----------|--|
| bw | bandwidth used in the weighting function; fixed (distance) or adaptive bandwidth (number of nearest neighbours) |
| X | a numeric matrix of the independent data with an extra column of “ones” for the 1st column |
| Y | a column vector of the dependent data |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5 * (vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1 - (vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1 - (vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| dp.locat | a two-column numeric array of observation coordinates |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| dMat | a pre-specified distance matrix, it can be calculated by the function gw.dist |
| verbose | if TRUE (default), reports the progress of search for bandwidth |

Value

CV.score cross-validation score

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

| | |
|----------------|---|
| gwr.cv.contrib | <i>Cross-validation data at each observation location for a basic GWR model</i> |
|----------------|---|

Description

This function finds the individual cross-validation score at each observation location, for a basic GWR model, for a specified bandwidth. These data can be mapped to detect unusually high or low cross-validations scores.

Usage

```
gwr.cv.contrib(bw, X, Y, kernel="bisquare", adaptive=FALSE, dp.locat, p=2,
              theta=0, longlat=F, dMat)
```

Arguments

| | |
|----------|--|
| bw | bandwidth used in the weighting function; fixed (distance) or adaptive bandwidth (number of nearest neighbours) |
| X | a numeric matrix of the independent data with an extra column of “ones” for the 1st column |
| Y | a column vector of the dependent data |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5 * (vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1 - (vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1 - (vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| dp.locat | a two-column numeric array of observation coordinates |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| dMat | a pre-specified distance matrix, it can be calculated by the function gw.dist |

Value

| | |
|----|---|
| CV | a data vector consisting of squared residuals, whose sum is the cross-validation score for the specified bandwidth. |
|----|---|

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

gwr.generalised

*Generalised GWR models with Poisson and Binomial options***Description**

This function implements generalised GWR

Usage

```
gwr.generalised(formula, data, regression.points, bw, family =
  "poisson", kernel = "bisquare", adaptive = FALSE, cv =
  T, tol = 1e-05, maxiter = 20, p = 2, theta = 0,
  longlat = F, dMat, dMat1)
```

```
## S3 method for class 'ggwrml'
print(x, ...)
```

Arguments

| | |
|-------------------|--|
| formula | Regression model formula of a formula object |
| data | a Spatial*DataFrame, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| regression.points | a Spatial*DataFrame object, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| bw | bandwidth used in the weighting function, possibly calculated by bw.ggwr(); fixed (distance) or adaptive bandwidth (number of nearest neighbours) |
| family | a description of the error distribution and link function to be used in the model, which can be specified by “poisson” or “binomial” |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5 * (vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1 - (vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1 - (vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| cv | if TRUE, cross-validation data will be calculated |
| tol | the threshold that determines the convergence of the IRLS procedure |
| maxiter | the maximum number of times to try the IRLS procedure |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| dMat | a pre-specified distance matrix between regression points and observations, it can be calculated by the function gw.dist |

| | |
|-------|--|
| dMat1 | a square distance matrix between each pair of observations, it can be calculated by the function gw.dist |
| x | an object of class “ggwrn”, returned by the function gwr.generalised |
| ... | arguments passed through (unused) |

Value

A list of class “ggwrn”:

| | |
|---------------|--|
| GW.arguments | a list class object including the model fitting parameters for generating the report file |
| GW.diagnostic | a list class object including the diagnostic information of the model fitting |
| glm.res | an object of class inheriting from “glm” which inherits from the class “lm”, see glm . |
| SDF | a SpatialPointsDataFrame (may be gridded) or SpatialPolygonsDataFrame object (see package “sp”) integrated with fit.points,GWR coefficient estimates, y value,predicted values, coefficient standard errors and t-values in its "data" slot. |
| CV | a data vector consisting of the cross-validation data |

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

References

Charlton, M, Fotheringham, S, and Brunsdon, C (2007), GWR3.0, <http://gwr.nuim.ie/>.
 Fotheringham S, Brunsdon, C, and Charlton, M (2002), Geographically Weighted Regression: The Analysis of Spatially Varying Relationships, Chichester: Wiley.

Examples

```
data(LondonHP)
## Not run:
DM<-gw.dist(dp.locat=coordinates(londonhp))
bw.f1 <- bw.gwr(BATH2~FLOORSZ,data=londonhp, dMat=DM)
res.poisson<-gwr.generalised(BATH2~FLOORSZ, bw=bw.f1,data=londonhp, dMat=DM)
bw.f2 <- bw.gwr(BATH2~FLOORSZ,data=londonhp, dMat=DM,family ="binomial")
res.binomial<-gwr.generalised(BATH2~FLOORSZ, bw=bw.f2,data=londonhp, dMat=DM,
                             family ="binomial")

## End(Not run)
```

gwr.hetero

Heteroskedastic GWR

Description

This function implements a heteroskedastic GWR model

Usage

```
gwr.hetero(formula, data, regression.points, bw, kernel="bisquare",
            adaptive=FALSE, tol=0.0001, maxiter=50, verbose=T,
            p=2, theta=0, longlat=F, dMat)
```

Arguments

| | |
|-------------------|--|
| formula | Regression model formula of a formula object |
| data | a Spatial*DataFrame, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| regression.points | a Spatial*DataFrame object, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| bw | bandwidth used in the weighting function, possibly calculated by bw.gwr ; fixed (distance) or adaptive bandwidth(number of nearest neighbours) |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5 * (vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1 - (vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1 - (vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| tol | the threshold that determines the convergence of the iterative procedure |
| maxiter | the maximum number of times to try the iterative procedure |
| verbose | logical, if TRUE verbose output will be made from the iterative procedure |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| dMat | a pre-specified distance matrix, it can be calculated by the function gw.dist |

Value

SDF a SpatialPointsDataFrame (may be gridded) or SpatialPolygonsDataFrame object (see package “sp”) integrated with coefficient estimates in its "data" slot.

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

References

Fotheringham S, Brunsdon, C, and Charlton, M (2002), Geographically Weighted Regression: The Analysis of Spatially Varying Relationships, Chichester: Wiley.

Harris P, Fotheringham AS, Juggins S (2010) Robust geographically weighed regression: a technique for quantifying spatial relationships between freshwater acidification critical loads and catchment attributes. Annals of the Association of American Geographers 100(2): 286-306

Harris P, Brunsdon C, Fotheringham AS (2011) Links, comparisons and extensions of the geographically weighted regression model when used as a spatial predictor. *Stochastic Environmental Research and Risk Assessment* 25:123-138

gwr.lcr

GWR with a locally-compensated ridge term

Description

To address possible local collinearity problems in basic GWR, GWR-LCR finds local ridge parameters at affected locations (set by a user-specified threshold for the design matrix condition number).

Usage

```
gwr.lcr(formula, data, regression.points, bw, kernel="bisquare",
        lambda=0, lambda.adjust=FALSE, cn.thresh=NA,
        adaptive=FALSE, p=2, theta=0, longlat=F, cv=T, dMat)
## S3 method for class 'gwrlcr'
print(x, ...)
```

Arguments

| | |
|-------------------|--|
| formula | Regression model formula of a formula object |
| data | a Spatial*DataFrame, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| regression.points | a Spatial*DataFrame object, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp , or a two-column numeric array |
| bw | bandwidth used in the weighting function, possibly calculated by bw.gwr.lcr; fixed (distance) or adaptive bandwidth(number of nearest neighbours) |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5*(vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1-(vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1-(vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| lambda | option for a globally-defined (constant) ridge parameter. Default is $\lambda=0$, which gives a basic GWR fit |
| lambda.adjust | a locally-varying ridge parameter. Default FALSE, refers to: (i) a basic GWR without a local ridge adjustment (i.e. $\lambda=0$, everywhere); or (ii) a penalised GWR with a global ridge adjustment (i.e. λ is user-specified as some constant, other than 0 everywhere); if TRUE, use cn.thresh to set the maximum condition number. Here for locations with a condition number (for its local design matrix) above this user-specified threshold, a local ridge parameter is found |
| cn.thresh | maximum value for condition number, commonly set between 20 and 30 |

| | |
|-----------------------|---|
| <code>adaptive</code> | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| <code>theta</code> | an angle in radians to rotate the coordinate system, default is 0 |
| <code>longlat</code> | if TRUE, great circle distances will be calculated |
| <code>cv</code> | if TRUE, 'cross-validation data will be calculated and returned in the output Spatial*DataFrame |
| <code>dMat</code> | a pre-specified distance matrix, it can be calculated by the function <code>gw.dist</code> |
| <code>x</code> | an object of class "gwr_lcr", returned by the function <code>gwr.lcr</code> |
| <code>...</code> | arguments passed through (unused) |

Value

A list of class "rgwr":

| | |
|----------------------------|---|
| <code>SDF</code> | a <code>SpatialPointsDataFrame</code> (may be gridded) or <code>SpatialPolygonsDataFrame</code> object (see package "sp") with coordinates of regression.points in its "data" slot. |
| <code>GW.arguments</code> | parameters used for the LCR-GWR calibration |
| <code>GW.diagnostic</code> | diagnostic information is given when data points are also used as regression locations |
| <code>timings</code> | timing information for running this function |
| <code>this.call</code> | the function call used. |

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

References

- Wheeler D (2007) Diagnostic tools and a remedial method for collinearity in geographically weighted regression. *Environment and Planning A* 39:2464-2481
- Brunsdon C, Charlton M, Harris P (2012) Living with collinearity in Local Regression Models. GISRUUK 2012, Lancaster, UK
- Brunsdon C, Charlton M, Harris P (2012) Living with collinearity in Local Regression Models. Spatial Accuracy 2012, Brazil
- Gollini I, Lu B, Charlton M, Brunsdon C, Harris P (2015) GWmodel: an R Package for exploring Spatial Heterogeneity using Geographically Weighted Models. *Journal of Statistical Software* 63(17): 1-50

Examples

```
data(DubVoter)
require(RColorBrewer)

# Function to find the global condition number (CN)
BKW_cn <- function (X) {
  p <- dim(X)[2]
  Xscale <- sweep(X, 2, sqrt(colSums(X^2)), "/")
  Xsvd <- svd(Xscale)$d
  cn <- Xsvd[1] / Xsvd[p]
```



```

    cn
  }
  #
  X <- cbind(1,Dub.voter@data[,3:10])
  head(X)
  CN.global <- BKW_cn(X)
  CN.global
  ## Not run:
  # gwr.lcr function with a global bandwidth to check that the global CN is found
  gwr.lcr1 <- gwr.lcr(GenEl2004~DiffAdd+LARent+SC1+Unempl+LowEduc+Age18_24
+Age25_44+Age45_64, data=Dub.voter, bw=10000000000)
  summary(gwr.lcr1$SDF$Local_CN)

  # Find and map the local CNs from a basic GWR fit using the lcr-gwr function
  #(note this is NOT the locally-compensated ridge GWR fit as would need to set
  #lambda.adjust=TRUE and cn.thresh=30, say)

  bw.lcr2 <- bw.gwr.lcr(GenEl2004~DiffAdd+LARent+SC1+Unempl+LowEduc+Age18_24
+Age25_44+Age45_64, data=Dub.voter, kernel="bisquare", adaptive=TRUE)
  gwr.lcr2 <- gwr.lcr(GenEl2004~DiffAdd+LARent+SC1+Unempl+LowEduc+Age18_24
+Age25_44+Age45_64, data=Dub.voter, bw=bw.lcr2, kernel="bisquare", adaptive=TRUE)
  if(require("RColorBrewer"))
    spplot(gwr.lcr2$SDF,"Local_CN",col.regions=brewer.pal(9,"YlOrRd"),cuts=8,
    main="Local CN")

  ## End(Not run)

```

gwr.lcr.cv

Cross-validation score for a specified bandwidth for GWR-LCR model

Description

This function finds the cross-validation score for a specified bandwidth for GWR-LCR. It can be used to construct the bandwidth function across all possible bandwidths and compared to that found automatically.

Usage

```

gwr.lcr.cv(bw,X,Y,locs, kernel="bisquare",
           lambda=0, lambda.adjust=FALSE, cn.thresh=NA,
           adaptive=FALSE, p=2, theta=0, longlat=F, dMat)

```

Arguments

| | |
|--------|---|
| bw | bandwidth used in the weighting function;fixed (distance) or adaptive band-width(number of nearest neighbours) |
| X | a numeric matrix of the independent data with an extra column of “ones” for the 1st column |
| Y | a column vector of the dependent data |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5*(vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; |

| | |
|---------------|---|
| | bisquare: $\text{wgt} = (1 - (\text{vdist}/\text{bw})^2)^2$ if $\text{vdist} < \text{bw}$, $\text{wgt}=0$ otherwise; |
| | tricube: $\text{wgt} = (1 - (\text{vdist}/\text{bw})^3)^3$ if $\text{vdist} < \text{bw}$, $\text{wgt}=0$ otherwise; |
| | boxcar: $\text{wgt}=1$ if $\text{dist} < \text{bw}$, $\text{wgt}=0$ otherwise |
| locs | a two-column numeric array of observation coordinates |
| lambda | option for a globally-defined (constant) ridge parameter. Default is $\text{lambda}=0$, which gives a basic GWR fit |
| lambda.adjust | a locally-varying ridge parameter. Default FALSE, refers to: (i) a basic GWR without a local ridge adjustment (i.e. $\text{lambda}=0$, everywhere); or (ii) a penalised GWR with a global ridge adjustment (i.e. lambda is user-specified as some constant, other than 0 everywhere); if TRUE, use <code>cn.thresh</code> to set the maximum condition number. Here for locations with a condition number (for its local design matrix) above this user-specified threshold, a local ridge parameter is found |
| cn.thresh | maximum value for condition number, commonly set between 20 and 30 |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| dMat | a pre-specified distance matrix, it can be calculated by the function gw.dist |

Value

| | |
|----------|------------------------|
| CV.score | cross-validation score |
|----------|------------------------|

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

| | |
|---------------------------------|---|
| <code>gwr.lcr.cv.contrib</code> | <i>Cross-validation data at each observation location for the GWR-LCR model</i> |
|---------------------------------|---|

Description

This function finds the individual cross-validation score at each observation location, for a GWR-LCR model, for a specified bandwidth. These data can be mapped to detect unusually high or low cross-validations scores.

Usage

```
gwr.lcr.cv.contrib(bw,X,Y,locs,kernel="bisquare",
                  lambda=0,lambda.adjust=FALSE,cn.thresh=NA,
                  adaptive=FALSE, p=2, theta=0, longlat=F,dMat)
```

Arguments

| | |
|---------------|---|
| bw | bandwidth used in the weighting function;fixed (distance) or adaptive bandwidth(number of nearest neighbours) |
| X | a numeric matrix of the independent data with an extra column of “ones” for the 1st column |
| Y | a column vector of the dependent data |
| locs | a two-column numeric array of observation coordinates |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5*(vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1-(vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1-(vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| lambda | option for a globally-defined (constant) ridge parameter. Default is $\lambda=0$, which gives a basic GWR fit |
| lambda.adjust | a locally-varying ridge parameter. Default FALSE, refers to: (i) a basic GWR without a local ridge adjustment (i.e. $\lambda=0$, everywhere); or (ii) a penalised GWR with a global ridge adjustment (i.e. λ is user-specified as some constant, other than 0 everywhere); if TRUE, use cn.tresh to set the maximum condition number. Here for locations with a condition number (for its local design matrix) above this user-specified threshold, a local ridge parameter is found |
| cn.tresh | maximum value for condition number, commonly set between 20 and 30 |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| dMat | a pre-specified distance matrix, it can be calculated by the function gw.dist |

Value

| | |
|----|---|
| CV | a data vector consisting of squared residuals, whose sum is the cross-validation score for the specified bandwidth. |
|----|---|

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

| | |
|-------------------|-----------------------------------|
| gwr.mink.approach | <i>Minkovski approach for GWR</i> |
|-------------------|-----------------------------------|

Description

This function implements the Minkovski approach to select an 'optimum' distance metric for calibrating a GWR model.

Usage

```
gwr.mink.approach(formula, data, criterion="AIC", bw, bw.sel.approach = "AIC", adaptive=F,
  kernel="bisquare", p.vals=seq(from=0.25, to=8, length.out=32), p.inf = T,
  theta.vals = seq(from=0, to=0.5*pi, length.out=10), verbose=F,
  nlower = 10)
```

Arguments

| | |
|-----------------|--|
| formula | Regression model formula of a formula object |
| data | a Spatial*DataFrame, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| criterion | the criterion used for distance metric selection, AICc ("AICc") or cross-validation ("CV") score; default is "AICc" |
| bw | bandwidth used in the weighting function, possibly calculated by bw.gwr ; fixed (distance) or adaptive bandwidth(number of nearest neighbours) |
| bw.sel.approach | approach used to select an optimum bandwidth for each calibration if no bandwidth (bw) is given; specified by CV for cross-validation approach or by AIC corrected (AICc) approach |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5*(vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1-(vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1-(vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| p.vals | a collection of positive numbers used as the power of the Minkowski distance |
| p.inf | if TRUE, Chebyshev distance is tried for model calibration, i.e. p is infinity |
| theta.vals | a collection of values used as angles in radians to rotate the coordinate system |
| verbose | if TRUE and bandwidth selection is undertaken, the bandwidth searches are reported |
| nlower | the minimum number of nearest neighbours if an adaptive kernel is used |

Value

A list of:

| | |
|-----------|--|
| diag.df | a data frame with four columns (p, theta, bandwidth, AICc/CV), each row corresponds to a calibration |
| coefs.all | a list class object including all the estimated coefficients |

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

References

LU, B., CHARLTON, M., BRUNSDON, C. & HARRIS, P. 2016. The Minkowski approach for choosing the distance metric in Geographically Weighted Regression. *International Journal of Geographical Information Science*, 30(2): 351-368.

| | |
|---------------------|--|
| gwr.mink.matrixview | <i>Visualisation of the results from gwr.mink.approach</i> |
|---------------------|--|

Description

This function visualises the AICc/CV results from the [gwr.mink.approach](#).

Usage

```
gwr.mink.matrixview(diag.df, znm=colnames(diag.df)[4], criterion="AIC")
```

Arguments

| | |
|-----------|---|
| diag.df | the first part of a list object returned by gwr.mink.approach |
| znm | the name of the forth column in diag.df |
| criterion | the criterion used for distance metric selection in gwr.mink.approach |

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

References

LU, B., CHARLTON, M., BRUNSDON, C. & HARRIS, P. 2016. The Minkowski approach for choosing the distance metric in Geographically Weighted Regression. *International Journal of Geographical Information Science*, 30(2): 351-368.

gwr.mink.pval

*Select the values of p for the Minkovski approach***Description**

These functions implement heuristics to select the values of p from two intervals: (0, 2] in a 'backward' direction and (2, Inf) in a 'forward' direction.

Usage

```
gwr.mink.pval(formula, data, criterion="AIC", bw, bw.sel.approach = "AIC",
              adaptive=F, kernel="bisquare", left.interval=0.25,
              right.interval=0.5, drop.tol=3, theta0=0, verbose=F, nlower = 10)
gwr.mink.pval.forward(formula, data, bw, bw.sel.approach = "AIC",
                      adaptive=F, kernel="bisquare", p.max=Inf, p.min=2,
                      interval=0.5, drop.tol=3, theta0=0, verbose=F, nlower = 10)
gwr.mink.pval.backward(formula, data, bw, bw.sel.approach = "AIC",
                      adaptive=F, kernel="bisquare", p.max=2, p.min=0.1,
                      interval=0.5, drop.tol=3, theta0=0, verbose=F, nlower = 10)
## S3 method for class 'pvlas'
plot(x, ...)
```

Arguments

| | |
|-----------------|--|
| formula | Regression model formula of a formula object |
| data | a Spatial*DataFrame, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| criterion | the criterion used for distance metric selection, AICc ("AICc") or cross-validation ("CV") score; default is "AICc" |
| bw | bandwidth used in the weighting function, possibly calculated by bw.gwr ; fixed (distance) or adaptive bandwidth(number of nearest neighbours) |
| bw.sel.approach | approach used to select an optimum bandwidth for each calibration if no bandwidth (bw) is given; specified by CV for cross-validation approach or by AIC corrected (AICc) approach |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5*(vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1-(vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1-(vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| left.interval | the step-size for searching the left interval (0, 2] in a 'backward' direction |
| right.interval | the step-size for searching the right interval (2, Inf) in a 'forward' direction |
| p.max | the maximum value of p |

| | |
|----------|---|
| p.min | the minimum value of p |
| interval | the step-size for searching the given interval in a 'backward' or 'forward' direction |
| drop.tol | an AICc difference threshold to define whether the values of p to be dropped or not |
| theta0 | a fixed rotation angle in radians |
| verbose | if TRUE and bandwidth selection is undertaken, the bandwidth searches are reported |
| nlower | the minimum number of nearest neighbours if an adaptive kernel is used |
| x | an object of class "pvlas", returned by these functions |
| ... | arguments passed through (unused) |

Value

A list of:

| | |
|---------------|--|
| p.vals | a vector of tried values of p |
| creation.vals | a vector of criterion values (AICc or CV) for tried values of p |
| p.dropped | a vector of boolean to label whether a value of p to be dropped or not: TRUE means to be dropped and FALSE means to be used for the Minkovski approach |

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

References

LU, B., CHARLTON, M., BRUNSDON, C. & HARRIS, P. 2016. The Minkowski approach for choosing the distance metric in Geographically Weighted Regression. *International Journal of Geographical Information Science*, 30(2): 351-368.

gwr.mixed

Mixed GWR

Description

This function implements mixed (semiparametric) GWR

Usage

```
gwr.mixed(formula, data, regression.points, fixed.vars,
           intercept.fixed=FALSE, bw, diagnostic=T, kernel="bisquare",
           adaptive=FALSE, p=2, theta=0, longlat=F,dMat)
```

Arguments

| | |
|--------------------------------|--|
| <code>formula</code> | Regression model formula of a formula object |
| <code>data</code> | a <code>Spatial*DataFrame</code> , i.e. <code>SpatialPointsDataFrame</code> or <code>SpatialPolygonsDataFrame</code> as defined in package <code>sp</code> |
| <code>regression.points</code> | a <code>Spatial*DataFrame</code> object, i.e. <code>SpatialPointsDataFrame</code> or <code>SpatialPolygonsDataFrame</code> as defined in package <code>sp</code> |
| <code>fixed.vars</code> | independent variables that appeared in the formula that are to be treated as global |
| <code>intercept.fixed</code> | logical, if TRUE the intercept will be treated as global |
| <code>bw</code> | bandwidth used in the weighting function, possibly calculated by bw.gwr ; fixed (distance) or adaptive bandwidth (number of nearest neighbours) |
| <code>diagnostic</code> | logical, if TRUE the diagnostics will be calculated |
| <code>kernel</code> | function chosen as follows: gaussian: $wgt = \exp(-.5 * (vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1 - (vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1 - (vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| <code>adaptive</code> | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| <code>p</code> | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| <code>theta</code> | an angle in radians to rotate the coordinate system, default is 0 |
| <code>longlat</code> | if TRUE, great circle distances will be calculated |
| <code>dMat</code> | a pre-specified distance matrix, it can be calculated by the function gw.dist |

Value

A list of class "mgwr":

| | |
|---------------------------|---|
| <code>GW.arguments</code> | a list class object including the model fitting parameters for generating the report file |
| <code>aic</code> | AICc value from this calibration |
| <code>df.used</code> | effective degree of freedom |
| <code>rss</code> | residual sum of squares |
| <code>SDF</code> | a <code>SpatialPointsDataFrame</code> (may be gridded) or <code>SpatialPolygonsDataFrame</code> object (see package "sp") integrated with coefficient estimates in its "data" slot. |
| <code>timings</code> | starting and ending time. |
| <code>this.call</code> | the function call used. |

Note

For an alternative formulation of mixed GWR, please refer to GWR 4, which provides useful tools for automatic bandwidth selection. This windows-based software also implements generalised mixed GWR.

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

References

- Fotheringham S, Brunsdon, C, and Charlton, M (2002), Geographically Weighted Regression: The Analysis of Spatially Varying Relationships, Chichester: Wiley.
- Brunsdon C, Fotheringham AS, Charlton ME (1999) Some notes on parametric significance tests for geographically weighted regression. *Journal of Regional Science* 39(3):497-524
- Mei L-M, He S-Y, Fang K-T (2004) A note on the mixed geographically weighted regression model. *Journal of regional science* 44(1):143-157
- Mei L-M, Wang N, Zhang W-X (2006) Testing the importance of the explanatory variables in a mixed geographically weighted regression model. *Environment and Planning A* 38:587-598
- Nakaya T, Fotheringham AS, Brunsdon C, Charlton M (2005) Geographically Weighted Poisson Regression for Disease Association Mapping, *Statistics in Medicine* 24: 2695-2717
- Nakaya T et al. (2011) GWR4.0, <http://gwr.nuim.ie/>.

`gwr.model.selection` *Model selection for GWR with a given set of independent variables*

Description

This function selects one GWR model from many alternatives based on the AICc values.

Usage

```
gwr.model.selection(DeVar=NULL, InDeVars=NULL, data=list(), bw=NULL, approach="CV",
                    adaptive=F, kernel="bisquare", dMat=NULL, p=2, theta=0, longlat=F)
```

Arguments

| | |
|----------|--|
| DeVar | dependent variable |
| InDeVars | a vector of independent variables for model selection |
| data | a Spatial*DataFrame, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| bw | bandwidth used in the weighting function, possibly calculated by bw.gwr |
| approach | specified by CV (cv) for cross validation approach or AIC (aic) for selecting bandwidth by AICc values |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5*(vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1-(vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1-(vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |

| | |
|---------|---|
| dMat | a pre-specified distance matrix, it can be calculated by the function gw.dist |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |

Value

A list of:

| | |
|------------|---|
| model.list | a list of all the tried GWR models consisted of formulas and variables. |
| GWR.df | a data frame consisted of four columns: bandwidth, AIC, AICc, RSS |

Note

The algorithm for selecting GWR models consists of the following four steps:

Step 1. Start by calibrating all the possible bivariate GWR models by sequentially regressing a single independent variable against the dependent variable;

Step 2. Find the best performing model which produces the minimum AICc value, and permanently include the corresponding independent variable in subsequent models;

Step 3. Sequentially introduce a variable from the remaining group of independent variables to construct new models with the permanently included independent variables, and determine the next permanently included variable from the best fitting model that has the minimum AICc value;

Step 4. Repeat step 3 until all the independent variables are permanently included in the model.

In this procedure, the independent variables are iteratively included into the model in a "forward" direction. Note that there is a clear distinction between the different number of involved variables in a selection step, which can be called model levels.

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

References

Lu, B, Charlton, M, Harris, P, Fotheringham, AS (2014) Geographically weighted regression with a non-Euclidean distance metric: a case study using hedonic house price data. International Journal of Geographical Information Science 28(4): 660-681

See Also

[gwr.model.view](#), [gwr.model.sort](#)

| | |
|----------------|--|
| gwr.model.sort | <i>Sort the results of the GWR model selection function gwr.model.selection.</i> |
|----------------|--|

Description

Sort the results from the GWR model selection function [gwr.model.selection](#)

Usage

```
gwr.model.sort(Sorting.list , numVars, ruler.vector)
```

Arguments

| | |
|--------------|---|
| Sorting.list | a list returned by function gwr.model.selection |
| numVars | the number of independent variables involved in model selection |
| ruler.vector | a numeric vector as the sorting basis |

Note

The function sorts the results of model selection within individual levels.

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

See Also

[gwr.model.selection](#), [gwr.model.view](#)

| | |
|----------------|--|
| gwr.model.view | <i>Visualise the GWR models from gwr.model.selection</i> |
|----------------|--|

Description

This function visualises the GWR models from [gwr.model.selection](#).

Usage

```
gwr.model.view(DeVar, InDeVars, model.list)
```

Arguments

| | |
|------------|--|
| DeVar | dependent variable |
| InDeVars | a vector of independent variables for model selection |
| model.list | a list of all GWR model tried in gwr.model.selection |

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

See Also

[gwr.model.selection](#), [gwr.model.sort](#)

Examples

```
## Not run:
data(LondonHP)
DM<-gw.dist(dp.locat=coordinates(londonhp))
DeVar<-"PURCHASE"
InDeVars<-c("FLOORSZ", "GARAGE1", "BLDPWW1", "BLDPOSTW")
model.sel<-gwr.model.selection(DeVar, InDeVars, data=londonhp,
kernel = "gaussian", dMat=DM, bw=5000)
model.list<-model.sel[[1]]
gwr.model.view(DeVar, InDeVars, model.list=model.list)

## End(Not run)
```

| | |
|----------------|---|
| gwr.montecarlo | <i>Monte Carlo (randomisation) test for significance of GWR parameter variability</i> |
|----------------|---|

Description

This function implements a Monte Carlo (randomisation) test to test for significant (spatial) variability of a GWR model's parameters or coefficients.

Usage

```
gwr.montecarlo(formula, data = list(), nsims=99, kernel="bisquare", adaptive=F, bw,
p=2, theta=0, longlat=F, dMat)
```

Arguments

| | |
|----------|--|
| formula | Regression model formula of a formula object |
| data | a Spatial*DataFrame, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| nsims | the number of randomisations |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5 * (vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1 - (vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1 - (vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| bw | bandwidth used in the weighting function, possibly calculated by bw.gwr |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| dMat | a pre-specified distance matrix, it can be calculated by the function gw.dist |

Value

pmat A vector containing p-values for all the GWR parameters

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

References

Brunsdon C, Fotheringham AS, Charlton ME (1998) Geographically weighted regression - modelling spatial non-stationarity. *Journal of the Royal Statistical Society, Series D-The Statistician* 47(3):431-443

Fotheringham S, Brunsdon, C, and Charlton, M (2002), *Geographically Weighted Regression: The Analysis of Spatially Varying Relationships*, Chichester: Wiley.

Charlton, M, Fotheringham, S, and Brunsdon, C (2007), *GWR3.0*.

Examples

```
## Not run:
data(LondonHP)
DM<-gw.dist(dp.locat=coordinates(londonhp))
bw<-bw.gwr(PURCHASE~FLOORSZ,data=londonhp,dMat=DM, kernel="gaussian")
#See any difference in the next two commands and why?
res.mont1<-gwr.montecarlo(PURCHASE~PROF+FLOORSZ, data = londonhp,dMat=DM,
nsim=99, kernel="gaussian", adaptive=FALSE, bw=3000)
res.mont2<-gwr.montecarlo(PURCHASE~PROF+FLOORSZ, data = londonhp,dMat=DM,
nsim=99, kernel="gaussian", adaptive=FALSE, bw=300000000000)

## End(Not run)
```

gwr.predict

GWR used as a spatial predictor

Description

This function implements basic GWR as a spatial predictor. The GWR prediction function is able to do leave-out-one predictions (when the observation locations are used for prediction) and predictions at a set-aside data set (when unobserved locations are used for prediction).

Usage

```
gwr.predict(formula, data, predictdata, bw, kernel="bisquare",adaptive=FALSE, p=2,
            theta=0, longlat=F,dMat1, dMat2)
## S3 method for class 'gwr.m.pred'
print(x, ...)
```

Arguments

| | |
|-------------|--|
| formula | Regression model formula of a formula object |
| data | a Spatial*DataFrame, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| predictdata | a Spatial*DataFrame object to provide prediction locations, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| bw | bandwidth used in the weighting function, possibly calculated by bw.gwr ; fixed (distance) or adaptive bandwidth(number of nearest neighbours) |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5*(vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1-(vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1-(vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| dMat1 | a pre-specified distance matrix between data points and prediction locations; if not given, it will be calculated by the given parameters |
| dMat2 | a pre-specified symmetric distance matrix between data points; if not given, it will be calculated by the given parameters |
| x | an object of class "gwr.pred", returned by the function gwr.predict |
| ... | arguments passed through (unused) |

Value

A list of class "gwr.pred":

| | |
|--------------|---|
| GW.arguments | a list of geographically weighted arguments |
| SDF | a SpatialPointsDataFrame (may be gridded) or SpatialPolygonsDataFrame object (see package "sp") with GWR coefficients, predictions and prediction variances in its "data" slot. |
| this.call | the function call used. |

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

References

- Harris P, Fotheringham AS, Crespo R, Charlton M (2010) The use of geographically weighted regression for spatial prediction: an evaluation of models using simulated data sets. *Mathematical Geosciences* 42:657-680
- Harris P, Juggins S (2011) Estimating freshwater critical load exceedance data for Great Britain using space-varying relationship models. *Mathematical Geosciences* 43: 265-292

| | |
|------------|--|
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5*(vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1-(vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1-(vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| adaptive | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| dMat | a pre-specified distance matrix, it can be calculated by the function gw.dist |
| F123.test | default FALSE, otherwise calculate F-test results (Leung et al. 2000) |
| maxiter | default 20, maximum number of iterations for the automatic approach |
| cut.filter | If filtered is TRUE, it will be used as the residual cutoff for filtering data; default cutoff is 3 |
| cut1 | default 2, first cutoff for the residual weighting function. $wr(e)=1$ if $ e \leq cut1 * \sigma$ |
| cut2 | default 3, second cutoff for the residual weighting function. $wr(e)=(1-(e -2)^2)^2$ if $cut1 * \sigma < e < cut2 * \sigma$, and $wr(e)=0$ if $ e \geq cut2 * \sigma$; cut 1 and cut2 refer to the automatic approach |
| delta | default 1.0e-5, tolerance of the iterative algorithm |

Value

A list of class “gwr”:

| | |
|---------------|--|
| GW.arguments | a list class object including the model fitting parameters for generating the report file |
| GW.diagnostic | a list class object including the diagnostic information of the model fitting |
| lm | an object of class inheriting from “lm”, see lm . |
| SDF | a SpatialPointsDataFrame (may be gridded) or SpatialPolygonsDataFrame object (see package “sp”) integrated with fit.points,GWR coefficient estimates, y value,predicted values, coefficient standard errors and t-values in its "data" slot. Notably, E_weights will be also included in the output SDF which represents the residual weighting when automatic approach is used; When the filtered approach is used, E_weight is a vector consisted of 0 and 1, where 0 means outlier to be excluded from calibration. |
| timings | starting and ending time. |
| this.call | the function call used. |
| Ftest.res | results of Leung’s F tests when F123.test is TRUE. |

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

References

Fotheringham S, Brunson, C, and Charlton, M (2002), Geographically Weighted Regression: The Analysis of Spatially Varying Relationships, Chichester: Wiley.

Harris P, Fotheringham AS, Juggins S (2010) Robust geographically weighed regression: a technique for quantifying spatial relationships between freshwater acidification critical loads and catchment attributes. Annals of the Association of American Geographers 100(2): 286-306

Examples

```
## Not run:
data(DubVoter)
bw.a <- bw.gwr(GenEl2004~DiffAdd+LAREnt+SC1+Unempl+LowEduc+Age18_24
+Age25_44+Age45_64,
data=Dub.voter,approach="AICc",kernel="bisquare",adaptive=TRUE)
bw.a
gwr.res <- gwr.basic(GenEl2004~DiffAdd+LAREnt+SC1+Unempl+LowEduc+Age18_24
+Age25_44+Age45_64,
data=Dub.voter,bw=bw.a,kernel="bisquare",adaptive=TRUE,F123.test=TRUE)
print(gwr.res)

# Map of the estimated coefficients for LowEduc
names(gwr.res$SDF)
if(require("RColorBrewer"))
{
  mypalette<-brewer.pal(6,"Spectral")
  X11(width=10,height=12)
  spplot(gwr.res$SDF,"LowEduc",key.space = "right",
col.regions=mypalette,at=c(-8,-6,-4,-2,0,2,4),
main="Basic GW regression coefficient estimates for LowEduc")
}
# Robust GW regression and map of the estimated coefficients for LowEduc
rgwr.res <- gwr.robust(GenEl2004~DiffAdd+LAREnt+SC1+Unempl+LowEduc+Age18_24
+Age25_44+Age45_64, data=Dub.voter,bw=bw.a,kernel="bisquare",
adaptive=TRUE,F123.test=TRUE)
print(rgwr.res)
if(require("RColorBrewer"))
{
  X11(width=10,height=12)
  spplot(rgwr.res$SDF, "LowEduc", key.space = "right",
col.regions=mypalette,at=c(-8,-6,-4,-2,0,2,4),
main="Robust GW regression coefficient estimates for LowEduc")
}

## End(Not run)
```

gwr.t.adjust

Adjust p-values for multiple hypothesis tests in basic GWR

Description

Given a set of p-values from the pseudo t-tests of basic GWR outputs, this function returns adjusted p-values using: (a) Bonferroni, (b) Benjamini-Hochberg, (c) Benjamini-Yekutieli and (d) Fotheringham-Byrne procedures.

Usage

```
gwr.t.adjust(gwm.Obj)
```

Arguments

gwm.Obj an object of class “gwr”, returned by the function [gwr.basic](#)

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

References

Byrne, G., Charlton, M. and Fotheringham, S., 2009. Multiple dependent hypothesis tests in geographically weighted regression. In: Lees, B. and Laffan, S. eds. 10th International conference on geocomputation. Sydney.

gwr.write

Write the GWR results into files

Description

This function writes the calibration result of function [gwr.basic](#) to a text file and shape files

Usage

```
gwr.write(x,fn="GWRresults")
gwr.write.shp(x,fn="GWRresults")
```

Arguments

x an object of class “gwr”, returned by the function [gwr.basic](#)

fn file name for the written results, by default the output files can be found in the working directory, “GWRresults.txt”, “GWRresults(.shp, .shx, .dbf)”

Note

The projection file is missing for the written shapefiles.

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

gwss

*Geographically weighted summary statistics (GWSS)***Description**

This function calculates basic and robust GWSS. This includes geographically weighted means, standard deviations and skew. Robust alternatives include geographically weighted medians, inter-quartile ranges and quantile imbalances. This function also calculates basic geographically weighted covariances together with basic and robust geographically weighted correlations.

Usage

```
gwss(data, summary.locat, vars, kernel="bisquare", adaptive=FALSE, bw, p=2,
      theta=0, longlat=F, dMat, quantile=FALSE)
## S3 method for class 'gwss'
print(x, ...)
```

Arguments

| | |
|----------------------------|--|
| <code>data</code> | a <code>Spatial*DataFrame</code> , i.e. <code>SpatialPointsDataFrame</code> or <code>SpatialPolygonsDataFrame</code> as defined in package sp |
| <code>summary.locat</code> | a <code>Spatial*DataFrame</code> object for providing summary locations, i.e. <code>SpatialPointsDataFrame</code> or <code>SpatialPolygonsDataFrame</code> as defined in package sp |
| <code>vars</code> | a vector of variable names to be summarized |
| <code>bw</code> | bandwidth used in the weighting function |
| <code>kernel</code> | function chosen as follows: gaussian: $wgt = \exp(-.5*(vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1-(vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1-(vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| <code>adaptive</code> | if TRUE calculate an adaptive kernel where the bandwidth (bw) corresponds to the number of nearest neighbours (i.e. adaptive distance); default is FALSE, where a fixed kernel is found (bandwidth is a fixed distance) |
| <code>p</code> | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| <code>theta</code> | an angle in radians to rotate the coordinate system, default is 0 |
| <code>longlat</code> | if TRUE, great circle distances will be calculated |
| <code>dMat</code> | a pre-specified distance matrix, it can be calculated by the function gw.dist |
| <code>quantile</code> | if TRUE, median, interquartile range, quantile imbalance will be calculated |
| <code>x</code> | an object of class "gwss", returned by the function gwss |
| <code>...</code> | arguments passed through (unused) |

Value

A list of class “lss”:

| | |
|-----|---|
| SDF | a <code>SpatialPointsDataFrame</code> (may be gridded) or <code>SpatialPolygonsDataFrame</code> object (see package “sp”) with local means, local standard deviations, local variance, local skew, local coefficients of variation, local covariances, local correlations (Pearson’s), local correlations (Spearman’s), local medians, local interquartile ranges, local quantile imbalances and coordinates. |
| ... | other information for reporting |

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

References

Fotheringham S, Brunsdon, C, and Charlton, M (2002), *Geographically Weighted Regression: The Analysis of Spatially Varying Relationships*, Chichester: Wiley.

Brunsdon C, Fotheringham AS, Charlton ME (2002) Geographically weighted summary statistics - a framework for localised exploratory data analysis. *Computers, Environment and Urban Systems* 26:501-524

Harris P, Clarke A, Juggins S, Brunsdon C, Charlton M (2014) Geographically weighted methods and their use in network re-designs for environmental monitoring. *Stochastic Environmental Research and Risk Assessment* 28: 1869-1887

Examples

```
## Not run:
data(EWHP)
data(EWOutline)
head(ewhp)
houses.spdf <- SpatialPointsDataFrame(ewhp[, 1:2], ewhp)
localstats1 <- gwss(houses.spdf, vars = c("PurPrice", "FlrArea"), bw = 50000)
head(data.frame(localstats1$SDF))
localstats1
##A function for mapping data
if(require("RColorBrewer"))
{
  quick.map <- function(spdf,var,legend.title,main.title)
  {
    x <- spdf@data[,var]
    cut.vals <- pretty(x)
    x.cut <- cut(x,cut.vals)
    cut.levels <- levels(x.cut)
    cut.band <- match(x.cut,cut.levels)
    colors <- brewer.pal(length(cut.levels), "YlOrRd")
    colors <- rev(colors)
    par(mar=c(1,1,1,1))
    plot(ewoutline,col="olivedrab",bg="lightblue1")
    title(main.title)
    plot(spdf,add=TRUE,col=colors[cut.band],pch=16)
    legend("topleft",cut.levels,col=colors,pch=16,bty="n",title=legend.title)
  }
  quick.map(localstats1$SDF, "PurPrice_LM", "1000's Uk Pounds",
```

```

    "Geographically Weighted Mean")
  par(mfrow = c(1, 2))
  quick.map(localstats1$SDF, "PurPrice_LSK", "Skewness Level", "Local Skewness")
  quick.map(localstats1$SDF, "PurPrice_LSD", "1000's Pounds", "Local Standard Deviation")
  #Exploring Non-Stationarity of Relationships
  quick.map(localstats1$SDF, "Corr_PurPrice_FlrArea", expression(rho),
    "Geographically Weighted Pearson Correlation")
  #Robust, Quantile Based Local Summary Statistics
  localstats2 <- gwss(houses.spdf, vars = c("PurPrice", "FlrArea"),
    bw = 50000, quantile = TRUE)
  quick.map(localstats2$SDF, "PurPrice_Median", "1000 UK Pounds",
    "Geographically Weighted Median House Price")
}

## End(Not run)

```

gwss.montecarlo

Monte Carlo (randomisation) test for gwss

Description

This function implements Monte Carlo (randomisation) tests for the GW summary statistics found in [gwss](#).

Usage

```

gwss.montecarlo(data, vars, kernel = "bisquare",
  adaptive = FALSE, bw, p = 2, theta = 0, longlat = F,
  dMat, quantile=FALSE,nsim=99)

```

Arguments

| | |
|----------|--|
| data | a Spatial*DataFrame, i.e. SpatialPointsDataFrame or SpatialPolygonsDataFrame as defined in package sp |
| vars | a vector of variable names to be summarized |
| bw | bandwidth used in the weighting function |
| kernel | function chosen as follows: gaussian: $wgt = \exp(-.5*(vdist/bw)^2)$; exponential: $wgt = \exp(-vdist/bw)$; bisquare: $wgt = (1-(vdist/bw)^2)^2$ if $vdist < bw$, $wgt=0$ otherwise; tricube: $wgt = (1-(vdist/bw)^3)^3$ if $vdist < bw$, $wgt=0$ otherwise; boxcar: $wgt=1$ if $dist < bw$, $wgt=0$ otherwise |
| adaptive | if TRUE calculate the adaptive kernel, and bw correspond to the number of nearest neighbours, default is FALSE. |
| p | the power of the Minkowski distance, default is 2, i.e. the Euclidean distance |
| theta | an angle in radians to rotate the coordinate system, default is 0 |
| longlat | if TRUE, great circle distances will be calculated |
| dMat | a pre-specified distance matrix, it can be calculated by the function gw.dist |
| quantile | if TRUE, median, interquartile range, quantile imbalance will be calculated |
| nsim | default 99, the number of randomisations |

Value

test probability of the test statistics of the GW summary statistics; if $p < 0.025$ or if $p > 0.975$ then the true local summary statistics can be said to be significantly different (at the 0.95 level) to such a local summary statistics found by chance.

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

References

Fotheringham S, Brunson, C, and Charlton, M (2002), Geographically Weighted Regression: The Analysis of Spatially Varying Relationships, Chichester: Wiley.

Brunson C, Fotheringham AS, Charlton ME (2002) Geographically weighted summary statistics - a framework for localised exploratory data analysis. Computers, Environment and Urban Systems 26:501-524

Harris P, Brunson C (2010) Exploring spatial variation and spatial relationships in a freshwater acidification critical load data set for Great Britain using geographically weighted summary statistics. Computers & Geosciences 36:54-70

Examples

```
## Not run:
data(LondonHP)
DM<-gw.dist(dp.locat=coordinates(londonhp))
test.lss<-gwss.montecarlo(data=londonhp, vars=c("PURCHASE", "FLOORSZ"), bw=5000,
                           kernel ="gaussian", dMat=DM,nsim=99)
test.lss

## End(Not run)
```

LondonBorough

London boroughs data

Description

Outline (SpatialPolygonsDataFrame) of London boroughs for the [LondonHP](#) data.

Usage

```
data(LondonBorough)
```

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

LondonHP

*London house price data set (SpatialPointsDataFrame)***Description**

A house price data set with 18 hedonic variables for London in 2001.

Usage

```
data(LondonHP)
```

Format

A SpatialPointsDataFrame object (proj4string set to "+init=epsg:27700 +datum=OSGB36").

The "data" slot is a data frame with 372 observations on the following 21 variables.

X a numeric vector, X coordinate

Y a numeric vector, Y coordinate

PURCHASE a numeric vector, the purchase price of the property

FLOORSZ a numeric vector, floor area of the property in square metres

TYPEDETCH a numeric vector, 1 if the property is detached (i.e. it is a stand-alone house), 0 otherwise

TPSEMIDTCH a numeric vector, 1 if the property is semi detached, 0 otherwise

TYPETRRD a numeric vector, 1 if the property is in a terrace of similar houses (commonly referred to as a 'row house' in the USA), 0 otherwise

TYPEBNGLW a numeric vector, 1 if the property is a bungalow (i.e. it has only one floor), 0 otherwise

TYPEFLAT a numeric vector, 1 if the property is a flat (or 'apartment' in the USA), 0 otherwise

BLDPWW1 a numeric vector, 1 if the property was built prior to 1914, 0 otherwise

BLDPOSTW a numeric vector, 1 if the property was built between 1940 and 1959, 0 otherwise

BLD60S a numeric vector, 1 if the property was built between 1960 and 1969, 0 otherwise

BLD70S a numeric vector, 1 if the property was built between 1970 and 1979, 0 otherwise

BLD80S a numeric vector, 1 if the property was built between 1980 and 1989, 0 otherwise

BLD90S a numeric vector, 1 if the property was built between 1990 and 2000, 0 otherwise

BATH2 a numeric vector, 1 if the property has more than 2 bathrooms, 0 otherwise

GARAGE a numeric vector, 1 if the house has a garage, 0 otherwise

CENTHEAT a numeric vector, 1 if the house has central heating, 0 otherwise

BEDS2 a numeric vector, 1 if the property has more than 2 bedrooms, 0 otherwise

UNEMPLOY a numeric vector, the rate of unemployment in the census ward in which the house is located

PROF a numeric vector, the proportion of the workforce in professional or managerial occupations in the census ward in which the house is located

Author(s)

Binbin Lu <binbinlu@whu.edu.cn>

References

- Fotheringham, A.S., Brunsdon, C., and Charlton, M.E. (2002), Geographically Weighted Regression: The Analysis of Spatially Varying Relationships, Chichester: Wiley.
- Lu, B, Charlton, M, Harris, P, Fotheringham, AS (2014) Geographically weighted regression with a non-Euclidean distance metric: a case study using hedonic house price data. International Journal of Geographical Information Science 28(4): 660-681

Examples

```
data(LondonHP)
data(LondonBorough)
ls()
plot(londonborough)
plot(londonhp, add=TRUE)
```

USelect

Results of the 2004 US presidential election at the county level (SpatialPolygonsDataFrame)

Description

Results of the 2004 US presidential election at the county level, together with five socio-economic (census) variables. This data can be used with GW Discriminant Analysis.

Usage

```
data(USelect)
```

Format

A SpatialPolygonsDataFrame with 3111 electoral divisions on the following 6 variables.

winner Categorical variable with three classes: i) Bush, ii) Kerry and iii) Borderline (supporting ratio for a candidate ranges from 0.45 to 0.55)

unemploy percentage unemployed

pctcoled percentage of adults over 25 with 4 or more years of college education

PEROVER65 percentage of persons over the age of 65

pcturban percentage urban

WHITE percentage white

References

- Robinson, A. C. (2013). Geovisualization of the 2004 Presidential Election. In: NATIONAL INSTITUTES OF HEALTH, P. S. U. (ed.). Penn State: <http://www.personal.psu.edu/users/a/c/acr181/election.html>.
- Foley, P. & Demsar, U. (2012). Using geovisual analytics to compare the performance of geographically weighted discriminant analysis versus its global counterpart, linear discriminant analysis. International Journal of Geographical Information Science, 27, 633-661.

Examples

```
data(USelect)  
ls()
```

Index

- *Topic **GW, PCP**
 - gw.pcplot, 18
- *Topic **GWDA**
 - bw.gwda, 6
 - gwda, 20
- *Topic **GWR, prediction**
 - gwr.predict, 53
- *Topic **Heteroskedastic, GWR**
 - gwr.hetero, 37
- *Topic **London, Boroughs**
 - LondonBorough, 62
- *Topic **Minkovski approach, GWR, distance metric, selection**
 - gwr.mink.pval, 46
- *Topic **Minkovski approach, GWR, result visualization**
 - gwr.mink.matrixview, 45
- *Topic **Monte Carlo, GWPCA**
 - gwpca.montecarlo.1, 27
 - gwpca.montecarlo.2, 29
- *Topic **MonteCarlo , test**
 - gwr.montecarlo, 52
- *Topic **bandwidth, GW mean, GW median, GW average**
 - bw.gw.average, 5
- *Topic **bandwidth**
 - bw.ggwr, 4
 - bw.gwr, 8
- *Topic **basic, GWR**
 - gwr.basic, 30
- *Topic **collinearity,diagnostic, GWR**
 - gwr.collin.diagno, 32
- *Topic **cv, GWPCA**
 - gwpca.cv, 24
 - gwpca.cv.contrib, 25
- *Topic **cv, GWR**
 - ggwr.cv, 14
 - ggwr.cv.contrib, 15
 - gwr.cv, 34
 - gwr.cv.contrib, 35
 - gwr.lcr.cv, 41
 - gwr.lcr.cv.contrib, 42
- *Topic **data,house price**
 - EWHP, 12
 - LondonHP, 63
- *Topic **datasets**
 - DubVoter, 11
 - Georgia, 13
 - GeorgiaCounties, 14
 - USelect, 64
- *Topic **distance metric, selection**
 - gwr.mink.approach, 44
- *Topic **distance, matrix**
 - gw.dist, 16
- *Topic **generalised, GWR**
 - gwr.generalised, 36
- *Topic **glyph plot, GWPCA**
 - gwpca.check.components, 24
 - gwpca.glyph.plot, 26
- *Topic **gwr, p-values, adjustment**
 - gwr.t.adjust, 57
- *Topic **gwr, write, shape files**
 - gwr.write, 58
- *Topic **local, summary stastics**
 - gwss, 59
- *Topic **mixed, GWR**
 - gwr.mixed, 47
- *Topic **model selection, view, visualization**
 - gwr.model.view, 51
- *Topic **model specification, variable selection, gwr**
 - gwr.model.selection, 49
- *Topic **model, sort**
 - gwr.model.sort, 51
- *Topic **outline,England, Wales**
 - EWOutline, 13
- *Topic **package**
 - GWmodel-package, 3
- *Topic **ridge, GWR**
 - gwr.lcr, 39
- *Topic **ridge, bandwidth, GWR**
 - bw.gwr.lcr, 9
- *Topic **robust, GWPCA, bandwidth**
 - bw.gwpca, 7
- *Topic **robust, GWPCA**

- gwpca, 21
- *Topic **robust, GWR**
 - gwr.robust, 55
- *Topic **test, summary statics**
 - gwss.montecarlo, 61
- *Topic **weight, matrix**
 - gw.weight, 19
- AICc (gwr.model.selection), 49
- AICc_rss (gwr.model.selection), 49
- bisq_wt_mat (gw.weight), 19
- bisq_wt_vec (gw.weight), 19
- bw.ggwr, 4
- bw.gw.average, 5
- bw.gwda, 6
- bw.gwpca, 7, 20, 22, 27
- bw.gwr, 8, 19, 30, 38, 44, 46, 48, 49, 52, 54, 55
- bw.gwr.lcr, 9
- bw.gwr1 (gwr.mink.approach), 44
- cd_dist_mat (gw.dist), 16
- cd_dist_smat (gw.dist), 16
- cd_dist_vec (gw.dist), 16
- Ci_mat (gwr.basic), 30
- confusion.matrix (gwda), 20
- coordinate_rotate (gw.dist), 16
- dist, 17
- Dub.voter (DubVoter), 11
- DubVoter, 11
- ehat (gwr.model.selection), 49
- eu_dist_mat (gw.dist), 16
- eu_dist_smat (gw.dist), 16
- eu_dist_vec (gw.dist), 16
- EWHP, 12, 13
- ewhp (EWHP), 12
- EWOutline, 13
- ewoutline (EWOutline), 13
- exp_wt_mat (gw.weight), 19
- exp_wt_vec (gw.weight), 19
- extract.mat (gwr.model.selection), 49
- F1234.test (gwr.basic), 30
- formula, 4, 6, 8, 9, 20, 30, 33, 36, 38, 39, 44, 46, 48, 52, 54, 55
- gauss_wt_mat (gw.weight), 19
- gauss_wt_vec (gw.weight), 19
- Gedu.counties (GeorgiaCounties), 14
- Gedu.df (Georgia), 13
- Generate.formula (gwr.model.selection), 49
- Georgia, 13
- GeorgiaCounties, 14
- ggwr.aic (bw.ggwr), 4
- ggwr.cv, 14
- ggwr.cv.contrib, 15
- glm, 37
- gold (bw.gwr), 8
- grouping.xy (gwda), 20
- gw.average.cv (bw.gw.average), 5
- gw.dist, 4-7, 9, 10, 15, 16, 16, 18, 21, 22, 25, 26, 28, 29, 31, 33-38, 40, 42, 43, 48, 50, 52, 56, 59, 61
- gw.fitted (gwr.model.selection), 49
- gw.mean.cv (bw.gw.average), 5
- gw.median.cv (bw.gw.average), 5
- gw.pcplot, 18
- gw.reg1 (gwr.predict), 53
- gw.weight, 19
- gw_reg (gwr.basic), 30
- gwda, 20
- GWmodel (GWmodel-package), 3
- GWmodel-package, 3
- gwpca, 21, 24, 27
- gwpca.check.components, 24
- gwpca.cv, 24
- gwpca.cv.contrib, 25
- gwpca.glyph.plot, 24, 26
- gwpca.montecarlo.1, 27, 28
- gwpca.montecarlo.2, 28, 29
- gwr.aic (bw.gwr), 8
- gwr.aic1 (gwr.mink.approach), 44
- gwr.basic, 30, 31, 58
- gwr.binomial (gwr.generalised), 36
- gwr.collin.diagno, 32
- gwr.cv, 34
- gwr.cv.contrib, 35
- gwr.cv1 (gwr.mink.approach), 44
- gwr.fitted (gwr.generalised), 36
- gwr.generalised, 36, 37
- gwr.hetero, 37
- gwr.lcr, 9, 39, 40
- gwr.lcr.cv, 41
- gwr.lcr.cv.contrib, 42
- gwr.mink.approach, 44, 45
- gwr.mink.matrixview, 45
- gwr.mink.pval, 46
- gwr.mixed, 47
- gwr.model.selection, 49, 51, 52
- gwr.model.sort, 50, 51, 52
- gwr.model.view, 50, 51, 51
- gwr.montecarlo, 52
- gwr.poisson (gwr.generalised), 36

`gwr.predict`, 53, 54
`gwr.q` (`gwr.mixed`), 47
`gwr.robust`, 55
`gwr.t.adjust`, 57
`gwr.write`, 58
`gwr_diag` (`gwr.basic`), 30
`gwss`, 59, 59, 61
`gwss.montecarlo`, 61

`list`, 37, 56
`lm`, 31, 56
`local.corr` (`gwss`), 59
`LondonBorough`, 62
`londonborough` (`LondonBorough`), 62
`LondonHP`, 62, 63
`londonhp` (`LondonHP`), 63

`md_dist_mat` (`gw.dist`), 16
`md_dist_smat` (`gw.dist`), 16
`md_dist_vec` (`gw.dist`), 16
`mk_dist_mat` (`gw.dist`), 16
`mk_dist_smat` (`gw.dist`), 16
`mk_dist_vec` (`gw.dist`), 16

`par`, 18
`plot.mcsims` (`gwpca.montecarlo.1`), 27
`plot.pvlas` (`gwr.mink.pval`), 46
`print.ggwrn` (`gwr.generalised`), 36
`print.gwda` (`gwda`), 20
`print.gwrlcr` (`gwr.lcr`), 39
`print.gwrn` (`gwr.basic`), 30
`print.gwrn.pred` (`gwr.predict`), 53
`print.gwss` (`gwss`), 59
`print.mgwr` (`gwr.mixed`), 47

`ridge.lm` (`gwr.lcr`), 39
`robustSvd` (`gwpca`), 21
`rss` (`gwr.model.selection`), 49
`rwpcn` (`gwpca`), 21

`splitx` (`gwda`), 20

`tri_wt_mat` (`gw.weight`), 19
`tri_wt_vec` (`gw.weight`), 19

`USelect`, 64
`USelect2004` (`USelect`), 64

`wlda` (`gwda`), 20
`wlda.cr` (`bw.gwda`), 6
`wmean` (`gwda`), 20
`wpcn` (`gwpca`), 21
`wprior` (`gwda`), 20
`wqda` (`gwda`), 20
`wqda.cr` (`bw.gwda`), 6
`wt.median` (`gwpca`), 21
`wvarcov` (`gwda`), 20