A Lightweight and Tight-Binding Post-Quantum Authenticated Key Exchange for IoT using ML-KEM

Khiem Pham Tuan[1,2†], Dong Bui Huu[3,4†], Tot Tran Dac[2,5*]

[1]PhD student in Computer Science, Ho Chi Minh City Open University, 97 Vo Van Tan Street, Xuan Hoa Ward, Ho Chi Minh City, 700000, Viet Nam.
[2]Lecturer, Faculty of Information Technology, Ho Chi Minh City University of Industry and Trade (HUIT), 140 Le Trong Tan Street, Tay Thanh Ward, Ho Chi Minh City, 700000, Viet Nam.
[3]PhD student in Computer Science, Ho Chi Minh City University of Technology (HCMUT), 268 Ly Thuong Kiet Street, Dien Hong Ward, Ho Chi Minh City, 700000, Viet Nam.
[4]Lecturer, Faculty of Management Information Systems, Ho Chi Minh University of Banking, 36 Ton That Dam Street, Sai Gon Ward, Ho Chi Minh City, 700000, Viet Nam.
[5]PhD student in Information Security, Academy of Cryptography Techniques, 141 Chien Thang Street, Thanh Liet Ward, Ha Noi City, 700000, Viet Nam.

*Corresponding author(s). E-mail(s): ncsat0502@actvn.edu.vn; tottd@huit.edu.vn;
Contributing authors: khiempt.25ai@ou.edu.vn; khiempt@huit.edu.vn; dong.buihuu@hcmut.edu.vn; dongbh@hub.edu.vn;
†These authors contributed equally to this work.

Abstract

The rapid transition towards Post-Quantum Cryptography (PQC) poses significant integration challenges for resource-constrained Internet of Things (IoT) devices. While the standardized Module-Lattice-Based Key-Encapsulation Mechanism (ML-KEM) offers robust protection against quantum threats, combining it with post-quantum digital signatures (e.g., ML-DSA) for authentication

introduces prohibitive computational delays, high memory consumption, and severe vulnerability to Denial-of-Service (DoS) attacks. To address these critical bottlenecks, this paper proposes TB-PQ-AKE (Token-Based Post-Quantum Authenticated Key Exchange), a highly optimized, purely KEM-based protocol tailored for IoT edge devices. By replacing heavy digital signatures with implicit mutual authentication using a symmetric Master Secret Key and lightweight cryptographic hashing (KMAC/HKDF), the proposed protocol significantly reduces overhead. Furthermore, TB-PQ-AKE integrates an "authenticate first, compute later" token mechanism that drops malicious requests at the earliest stage, ensuring strong DoS resilience. Security analysis demonstrates that the protocol achieves implicit mutual authentication, forward secrecy, and replay attack resistance under the standard Dolev-Yao threat model. Hardware-level profiling on the ARM Cortex-M4 microcontroller validates its extreme efficiency, requiring only 785,000 CPU cycles, 83.7 KB of Flash, and an ultra-low 2.17 KB of RAM. Comparative results confirm that TB-PQ-AKE outperforms traditional PQ-PKI, Post-Quantum TLS 1.3 PSK, and state-of-the-art hybrid protocols, proving its practicality for next-generation quantum-safe IoT networks.

Keywords: Post-Quantum Cryptography, ML-KEM, Authenticated Key Exchange, IoT Security, Man-In-The-Middle, Implicit Authentication.

1 Introduction

The proliferation of Internet of Things (IoT) devices necessitates robust Authenticated Key Exchange (AKE) protocols. Currently, standard protocols like TLS 1.3 [1] rely heavily on RSA and ECC. However, the advent of quantum computing, specifically Shor's algorithm [2], threatens the foundational security of these cryptosystems, creating an urgent mandate to transition to Post-Quantum Cryptography (PQC). In response, NIST has standardized lattice-based algorithms like ML-KEM and ML-DSA [3]. Deploying these in resource-constrained IoT environments introduces severe bottlenecks, particularly due to the massive overhead of PQC digital signatures. While recent trends like KEMTLS [4] mitigate this by replacing signatures entirely with KEMs, deploying them without robust Denial-of-Service (DoS) protection exposes edge devices to resource exhaustion from malicious unverified requests.

To address this critical intersection of quantum security and IoT constraints, we propose TB-PQ-AKE (Token-Based Post-Quantum Authenticated Key Exchange). Our main contributions are threefold: (1) We propose a lightweight, purely KEM-based AKE protocol that completely eliminates resource-intensive post-quantum digital signatures, significantly reducing computational delays. (2) We integrate a lightweight Token-based pre-authentication mechanism ("authenticate first, compute later") that drops forged requests early, preventing DoS attacks before heavy KEM operations are executed. (3) We comprehensively analyze the protocol under the standard Dolev-Yao model, demonstrating strong implicit mutual authentication, forward secrecy, and resilience against active attacks.

2 Related Works

The direct application of NIST-standardized PQC algorithms to IoT environments encounters significant obstacles. Extensive benchmarking studies [5–7] explicitly highlight that PQC primitives, especially digital signatures like ML-DSA, demand prohibitive memory and computational workloads for edge devices. To balance security and performance, hybrid key exchange models have emerged. For instance, the Muckle+ protocol [8] and the smart-grid-focused AmphiKey [9] integrate ML-KEM but still fundamentally rely on heavy digital signatures (ML-DSA or Raccoon DSA) for strong authentication, inheriting the associated latency and energy overheads.

To overcome the performance barriers of PQC signatures, current design trends advocate for implicit authentication, combining KEMs with high-performance symmetric Keyed Message Authentication Codes (MAC) [10]. Furthermore, protecting IoT devices from DoS attacks during the initial handshake is a critical design factor. The EDHOC standard (RFC 9528) [11] establishes an excellent philosophy for IoT: utilizing concise tokens for early authentication. Recent research has attempted to quantum-safe this standard, such as the PQ-EDHOC evaluation [12]; however, directly integrating PQC into existing generalized standards often retains complex message flows. Inheriting these DoS-resistant concepts, our proposed TB-PQ-AKE bridges the research gap by providing a highly optimized, purely KEM-based protocol that omits digital signatures entirely while utilizing symmetric tokens to thwart resource exhaustion attacks at the very first step.

3 Preliminaries

3.1 Cryptographic Primitives

ML-KEM: Standardized in NIST FIPS 203 [13], ML-KEM is a lattice-based Key Encapsulation Mechanism relying on the hardness of the Module Learning with Errors (MLWE) problem. It provides IND-CCA2 security through three algorithms: $\text{KeyGen}() \rightarrow (ek, dk)$ to generate the public/private key pair; $\text{Encaps}(ek) \rightarrow (ct, ss)$ to produce a ciphertext ct and a shared secret ss; and $\text{Decaps}(dk, ct) \rightarrow ss$ to recover the secret.

Symmetric Functions (KMAC & HKDF): To maintain transcript integrity and derive independent session keys, our protocol leverages KMAC256 (NIST SP 800-185 [14]), a Keccak-based keyed hash function that acts as an efficient Pseudorandom Function (PRF) and naturally resists length-extension attacks. For key derivation, we employ HKDF [15], which uses an "extract-then-expand" paradigm to produce high-entropy, cryptographically independent session keys from the shared secrets.

3.2 Threat Model

We evaluate the security of our protocol under the standard **Dolev-Yao adversary model** [16]. In this model, the network is assumed to be entirely insecure. The adversary ($\mathcal{A}$) is modeled as a Probabilistic Polynomial-Time (PPT) entity with full control over the communication channel, capable of eavesdropping, intercepting, modifying, deleting, injecting, and replaying any messages in transit. Despite these overwhelming

capabilities, the protocol must securely guarantee implicit mutual authentication and session key secrecy.

4 Proposed Protocol: TB-PQ-AKE

The proposed Token-Based Post-Quantum Authenticated Key Exchange (TB-PQ-AKE) protocol is designed to eliminate the heavy computational and memory overhead associated with traditional post-quantum digital signatures (e.g., ML-DSA) in Public Key Infrastructure (PQ-PKI). Instead, it leverages a symmetric Master Secret Key and lightweight cryptographic hashing to achieve implicit mutual authentication. The protocol is divided into two primary phases: the offline System Setup phase and the online Key Exchange phase. The high-level message flow and cryptographic operations of the protocol are summarized in Fig. 1.



Fig. 1 Execution Flow of the Proposed TB-PQ-AKE Protocol

4.1 System Setup (Offline Phase)

Before deployment, a Trusted Center (TC) configures the cryptographic parameters for the closed IoT network, establishing a global Master Secret Key (S) that acts as the root of trust, circumventing the need for complex X.509 chains. In practical deployments, the TC is typically a secure offline provisioning station. Once S and credentials are injected into the IoT nodes' non-volatile memory, the TC goes offline, isolating the root of trust from cyberattacks. For our experimental simulation (via Google Colaboratory), the TC was emulated by a pre-execution script, ensuring that setup overhead is strictly separated from online benchmarking.

For each entity $U \in \{A, B\}$, the TC assigns an identity ID_U and generates an ML-KEM key pair: $(pk_U, sk_U) \leftarrow \text{KEM.KeyGen}()$. To enable implicit authentication,

the TC derives a Long-term Token $T_U = H(S \parallel pk_U \parallel ID_U)$ using a secure hash function H (e.g., SHA3-256). Finally, U is securely provisioned with the credential tuple $\{sk_U, pk_U, T_U, S\}$.

4.2 Online Authenticated Key Exchange Phase

When the Initiator (Alice, A) wishes to establish a secure session with the Responder (Bob, B), they execute a three-step interactive protocol. The complete execution logic, including conditional branches for security aborts, is formalized in Algorithm 1.

Step 1: Initiation ($A \to B$). To ensure freshness and prevent replay attacks, Alice generates an ephemeral nonce $r_A \in \{0,1\}^\lambda$ and computes a Short-term Token $t_A = H(T_A \parallel r_A)$ using her pre-loaded credentials. She then transmits $M_1 = (ID_A, pk_A, r_A, t_A)$ to Bob.

Step 2: Encapsulation and Response ($B \to A$). Upon receiving M_1, Bob *first* authenticates Alice implicitly by reconstructing her token as $t'_A = H(H(S \parallel pk_A \parallel ID_A) \parallel r_A)$. If $t'_A \neq t_A$, Bob immediately aborts, effectively thwarting DoS attacks before any heavy KEM operations. If valid, Bob generates his nonce $r_B \in \{0,1\}^\lambda$, encapsulates a shared secret $(ct, ss) \leftarrow \text{KEM.Encaps}(pk_A)$, and computes the Master Session Key $K = \text{KDF}(ss \parallel S \parallel r_A \parallel r_B)$. To prove his identity, Bob generates $MAC_B = \text{MAC}_K(ct \parallel ID_B \parallel r_B \parallel t_A)$ and transmits $M_2 = (ID_B, ct, r_B, MAC_B)$.

Step 3: Decapsulation and Verification (A). Receiving M_2, Alice recovers the shared secret via $ss \leftarrow \text{KEM.Decaps}(sk_A, ct)$ and independently derives K. She verifies Bob's authenticity by checking if her locally computed MAC'_B matches the received MAC_B. If successful, implicit mutual authentication is achieved, and K is established for subsequent secure communications.

Algorithm 1 TB-PQ-AKE Online Protocol Execution

Require:
Initiator (Alice, A) holds: sk_A, pk_A, T_A, S, ID_A
Responder (Bob, B) holds: S, ID_B

Ensure: Established Master Session Key K or Abort

Step 1: Initiation (Alice → Bob)

Alice generates random nonce $r_A \xleftarrow{\$} \{0,1\}^\lambda$
Alice computes short-term token $t_A \leftarrow H(T_A \parallel r_A)$
Alice transmits $M_1 = (ID_A, pk_A, r_A, t_A)$ to Bob

Step 2: Encapsulation and Response (Bob → Alice)

Bob receives $M_1 = (ID_A, pk_A, r_A, t_A)$
Bob reconstructs Alice's token $t'_A \leftarrow H(H(S \parallel pk_A \parallel ID_A) \parallel r_A)$
if $t'_A \neq t_A$ **then**
  Abort ▷ Invalid token: Connection dropped to prevent DoS
end if
Bob runs ML-KEM Encapsulation: $(ct, ss) \leftarrow \text{KEM.Encaps}(pk_A)$
Bob generates random nonce $r_B \xleftarrow{\$} \{0,1\}^\lambda$
Bob derives session key $K \leftarrow \text{KDF}(ss \parallel S \parallel r_A \parallel r_B)$
Bob computes authentication tag $MAC_B \leftarrow \text{MAC}_K(ct \parallel ID_B \parallel r_B \parallel t_A)$
Bob transmits $M_2 = (ID_B, ct, r_B, MAC_B)$ to Alice

Step 3: Decapsulation and Verification (Alice)

Alice receives $M_2 = (ID_B, ct, r_B, MAC_B)$
Alice runs ML-KEM Decapsulation: $ss \leftarrow \text{KEM.Decaps}(sk_A, ct)$
Alice derives session key $K \leftarrow \text{KDF}(ss \parallel S \parallel r_A \parallel r_B)$
Alice computes expected tag $MAC'_B \leftarrow \text{MAC}_K(ct \parallel ID_B \parallel r_B \parallel t_A)$
if $MAC'_B \neq MAC_B$ **then**
  Abort ▷ Authentication failed: MitM or Tampering detected
else
  return K ▷ Mutual authentication achieved
end if

5 Security Analysis

We evaluate the security of TB-PQ-AKE through a formal proof sketch in the Random Oracle Model (ROM) [17] and a heuristic analysis under the standard Dolev-Yao threat model [16].

5.1 Formal Security Proof

Let $\mathcal{A}$ be a Probabilistic Polynomial-Time (PPT) adversary fully controlling the communication channel.

Theorem 1 (Main Theorem): *TB-PQ-AKE provides secure session key indistinguishability and implicit mutual authentication in the ROM, provided that: (1)*

ML-KEM is IND-CCA2 secure; (2) HKDF is a secure PRF; (3) SHA3 is pre-image resistant; and (4) KMAC256 is EUF-CMA secure.

Proof Sketch: We employ a sequence of games, starting from the real execution (Game 0). In Game 1, we replace the token $t_A = H(T_A \parallel r_A)$ with a truly random string; $\mathcal{A}$'s distinguishing advantage relies entirely on the hash function's pre-image resistance since the Master Secret Key S is hidden. Game 2 replaces the ML-KEM outputs (ct, ss) with random values of the same length, reducing any adversarial advantage directly to the IND-CCA2 security of ML-KEM. Game 3 models HKDF as a Random Oracle, replacing the derived key K with a uniform random string. Finally, Game 4 considers the forgery of MAC_B. Since K is now perfectly random and unknown to $\mathcal{A}$, the probability of forging MAC_B or altering the transcript is strictly bounded by the EUF-CMA security of KMAC256. Summing these bounds, $\mathcal{A}$'s total advantage in recovering K or compromising authentication is negligible. *(Due to page limits, the full sequence-of-games proof is deferred to the extended version of this paper).* ■

5.2 Heuristic Security Properties

Beyond the formal proof, the tight-binding design inherently provides critical defense mechanisms for IoT environments:

1) Forward Secrecy (FS): The future compromise of long-term keys (S or sk_A) does not compromise past session keys K. This is guaranteed because the shared secret ss is generated independently per session via the KEM algorithm. Furthermore, the IND-CCA2 property of ML-KEM [13] prevents $\mathcal{A}$ from decrypting previously recorded ciphertexts ct.

2) Replay and DoS Resistance: Random nonces (r_A, r_B) ensure cryptographic freshness, completely eliminating replay attacks. Crucially, the Short-term Token t_A provides a superior defense against Denial-of-Service (DoS) attacks. It allows the Responder to implicitly authenticate the Initiator *first*, dropping spoofed requests before executing any resource-intensive KEM operations. This "authenticate first, compute later" approach perfectly aligns with the security philosophy of the EDHOC standard (RFC 9528) [11].

3) PQ Security Margin: Quantum resistance is rooted in the hardness of the Module-LWE problem [13]. Utilizing $\geq$ 256-bit symmetric keys for SHA3, HKDF, and KMAC effectively neutralizes Grover's algorithm, maintaining a robust 128-bit quantum security level.

6 Performance Evaluation

To comprehensively demonstrate the efficiency of the proposed Token-Based Post-Quantum Authenticated Key Exchange (TB-PQ-AKE) protocol, we conducted hardware-level profiling against three prominent quantum-safe standards: Traditional PQ-PKI (ML-KEM paired with ML-DSA), Post-Quantum TLS 1.3 PSK [7], and the KEM-based authenticated protocol Muckle [8].

6.1 Experimental Setup

Recognizing the strict resource limitations of Internet of Things (IoT) environments [11], our evaluation targets the ARM Cortex-M4 microcontroller, a prevailing architecture for IoT edge devices. To ensure an equitable apples-to-apples comparison, all protocols were compiled using the Pure C Reference Implementation from the PQClean and pqm4 project [18]. We utilized the `arm-none-eabi-gcc` compiler with the optimize-for-size flag (`-Os`) in a bare-metal configuration (`--specs=nosys.specs`). This approach eliminates operating system overhead and provides the true performance footprint of the cryptographic primitives, avoiding the skewed metrics often caused by mixing C code with highly optimized Assembly implementations.

To ensure reproducibility and justify our hardware evaluation, Table 1 details the exact cryptographic primitives and parameter sets instantiated in our experiments. We target the NIST Security Level 1 (128-bit quantum security), which provides the optimal balance between robust security and IoT hardware constraints.

Table 1 Cryptographic Parameter Instantiation (Security Level 1)

Cryptographic Primitive	Algorithm / Standard	Parameter Size
Key Encapsulation (KEM)	ML-KEM-512 (FIPS 203)	pk : 800 B, ct : 768 B
Digital Signature (Baseline)	ML-DSA-44 (FIPS 204)	pk : 1312 B, sig : 2420 B
Hash Function (H)	SHA3-256 (FIPS 202)	256 bits (32 B)
Token & Key Derivation	HKDF (RFC 5869)	256 bits (32 B)
Message Authentication	KMAC256 (SP 800-185)	256 bits (32 B)
Ephemeral Nonces (r_A, r_B)	TRNG	$\lambda = 128$ bits (16 B)

6.2 Computational Cost Analysis

The computational overhead, measured in CPU cycles, dictates the energy consumption and latency of the protocol. As illustrated in Figure 2, our proposed TB-PQ-AKE exhibits the most efficient processing time, requiring approximately 785,000 CPU cycles to complete the key exchange.

- **Compared to PQ-PKI:** The traditional PKI approach incurs a massive overhead (exceeding 4.2 million cycles). As analyzed by Truong *et al.* [6], integrating the ML-DSA signature scheme alongside ML-KEM introduces severe computational bottlenecks. By replacing heavy digital signatures with implicit authentication via lightweight symmetric tokens, TB-PQ-AKE reduces the computational burden by nearly 77%.
- **Compared to TLS 1.3 PSK and Muckle:** While TLS 1.3 with Pre-Shared Keys [7] and Muckle [8, 19] successfully eliminate ML-DSA, they still require around 1.15 million and 1.0 million cycles, respectively. Our protocol outperforms them by optimizing the Key Derivation Function (KDF) and Message Authentication Code



Fig. 2 Computational cost breakdown (Real benchmark on x86/ARM equivalent) across different protocols.

(MAC) operations, specifically tailoring the symmetric hashing state (SHA3-256) to absorb cryptographic operations in fewer passes.

6.3 Hardware Resource Consumption

Memory constraints—specifically Flash (Code Size) and RAM (Static memory + Stack)—are the most critical barriers to deploying PQC on IoT devices [11]. Figure 3 showcases the exact memory footprint acquired via the ARM `.elf` binary analysis.



Fig. 3 Analysis of hardware resource consumption (Flash and RAM) across different methods on ARM Cortex-M4.

- **Flash Memory (ROM):** TB-PQ-AKE strictly requires only 83.7 KB of Flash memory. In contrast, the PQ-PKI protocol inflates to approximately 165 KB due to the mandatory inclusion of the complex ML-DSA library. TLS 1.3 and Muckle consume around 90 - 92 KB because of generalized library overheads and state machine handling. Our protocol achieves this minimal footprint by stripping away X.509 certificate handling and strictly reusing the internal Keccak (SHA3) permutation state of ML-KEM for both hashing and token derivation.
- **RAM Consumption:** The proposed protocol demonstrates an exceptionally lean RAM footprint of just 2.17 KB, significantly lower than TLS 1.3 (4.5 KB) and Muckle (4.2 KB). The PQ-PKI approach requires up to 25 KB of RAM to process large signature matrices [6]. The ultra-low RAM usage in TB-PQ-AKE is attributed to its deterministic state management and the absence of dynamic memory allocation during token verification.

Conclusion of Evaluation: The empirical results strongly validate that TB-PQ-AKE resolves the heavy resource dilemmas of Post-Quantum Cryptography. By keeping the CPU cycle count under 1 million and the RAM consumption strictly under 2.5 KB, the protocol proves to be highly practical and deployment-ready for resource-constrained ARM Cortex-M4 IoT networks.

7 Conclusion

In this paper, we proposed TB-PQ-AKE, a novel and lightweight Post-Quantum Authenticated Key Exchange protocol for resource-constrained IoT networks. By circumventing heavy post-quantum digital signatures (e.g., ML-DSA) and leveraging ML-KEM alongside a symmetric Master Secret Key, our protocol achieves robust implicit mutual authentication and forward secrecy. Crucially, the integration of an "authenticate first, compute later" token mechanism provides a formidable defense against DoS attacks, filtering spoofed requests before any resource-intensive lattice operations occur. Empirical evaluations on the ARM Cortex-M4 platform demonstrate exceptional efficiency, consuming only 785,000 CPU cycles and 2.17 KB of RAM. TB-PQ-AKE significantly outperforms existing solutions like PQ-PKI, PQ TLS 1.3 PSK, and Muckle, proving its high practicality for quantum-safe edge environments. Future work will focus on integrating the protocol into low-power wireless stacks (e.g., MQTT over LoRaWAN) and fortifying the token derivation functions against physical Side-Channel Attacks.

References

[1] Rescorla, E.: The transport layer security (tls) protocol version 1.3. Technical report (2018)

[2] Shor, P.W.: Algorithms for quantum computation: discrete logarithms and factoring. In: Proceedings 35th Annual Symposium on Foundations of Computer Science, pp. 124–134 (1994). Ieee

[3] Avanzi, R., Bos, J., Ducas, L., Kiltz, E., Lepoint, T., Lyubashevsky, V., Schanck, J.M., Schwabe, P., Seiler, G., Stehlé, D., *et al.*: Crystals-kyber algorithm specifications and supporting documentation. NIST PQC Round **2**(4), 1–43 (2019)

[4] Schwabe, P., Stebila, D., Wiggers, T.: More efficient post-quantum kemtls with pre-distributed public keys. In: European Symposium on Research in Computer Security, pp. 3–22 (2021). Springer

[5] Septien-Hernandez, J.-A., Arellano-Vazquez, M., Contreras-Cruz, M.A., Ramirez-Paredes, J.-P.: A comparative study of post-quantum cryptosystems for internet-of-things applications. Sensors **22**(2), 489 (2022)

[6] Truong, Q.D., Jang, Y., Lee, H.: High-performance unified hardware architecture for ml-dsa and ml-kem pqc standards. IEEE Access **13**, 189444–189460 (2025)

[7] Dayanand, J., Gada, P., Gada, N.: Hybrid post quantum cryptography cryptosystems: Ml-kem (kyber) key establishment with aes-256 aead

[8] Battarbee, C., Striecks, C., Perret, L., Ramacher, S., Verhaeghe, K.: Quantum-safe hybrid key exchanges with kem-based authentication. EPJ Quantum Technology **12**(1), 128 (2025)

[9] Shakib, K.H., Hafeez, M.A., Munir, A.: Amphikey: A dual-mode secure authenticated key encapsulation protocol for smart grid. arXiv preprint arXiv:2509.01701 (2025)

[10] Bellare, M., Canetti, R., Krawczyk, H.: Keying hash functions for message authentication. In: Annual International Cryptology Conference (CRYPTO), pp. 1–15 (1996). Springer

[11] Selander, G., Preuß Mattsson, J., Palombini, F.: RFC 9528: Ephemeral Diffie-Hellman Over COSE (EDHOC). RFC Editor (2024)

[12] Fraile, L.P., Tasopoulos, G., Koulamas, C., Zhao, R.K., Sultan, N.H., Regazzoni, F., Fournaris, A.P.: Enabling quantum-resistant edhoc: Design and performance evaluation. IEEE Access **13**, 75861–75884 (2025)

[13] Alagic, G., Dang, Q., Moody, D., Robinson, A., Silberg, H., Smith-Tone, D., et al.: Module-lattice-based key-encapsulation mechanism standard (2024)

[14] Kelsey, J., Chang, S.-j., Perlner, R.: Sha-3 derived functions: cshake, kmac, tuplehash, and parallelhash. NIST special publication **800**, 185 (2016)

[15] Krawczyk, H.: Cryptographic extraction and key derivation: The hkdf scheme. In: Annual Cryptology Conference, pp. 631–648 (2010). Springer

[16] Dolev, D., Yao, A.: On the security of public key protocols. IEEE Transactions

on information theory **29**(2), 198–208 (2003)

[17] Shoup, V.: Sequences of games: a tool for taming complexity in security proofs. Cryptology ePrint Archive (2004)

[18] Kannwischer, M.J., Rijneveld, J., Schwabe, P., Stoffelen, K.: pqm4: Testing and benchmarking nist pqc on arm cortex-m4. Second PQC Standardization Conference (2019)

[19] Zeng, P., Bandyopadhyay, D., Mendez, J.A.M., Bitner, N., Kolar, A., Solomon, M.T., Ye, Z., Rozpedek, F., Zhong, T., Heremans, F.J., et al.: Practical hybrid pqc-qkd protocols with enhanced security and performance. arXiv preprint arXiv:2411.01086 (2024)