

Models 

© Copy page

# Flagship models

#### GPT-4o

Our versatile, high-intelligence flagship model

Text and image input, text output

128k context length

Smarter model, higher price per token

#### GPT-40 mini

Our fast, affordable small model for focused tasks

Text and image input, text output

128k context length

Faster model, lower price per token

#### o1 & o1-mini

Reasoning models that excel at complex, multi-step tasks

Text and image input, text output

128k context length

Uses additional tokens for reasoning

Model pricing details >

### Models overview

The OpenAl API is powered by a diverse set of models with different capabilities and price points. You can also make customizations to our models for your specific use case with fine-tuning.

MODEL	DESCRIPTION
GPT-4o	Our versatile, high-intelligence flagship model

GPT-4o-mini	Our fast, affordable small model for focused tasks
o1 and o1-mini	Reasoning models that excel at complex, multi-step tasks
GPT-4o Realtime	GPT-4o models capable of realtime text and audio inputs and outputs
GPT-4o Audio	GPT-4o models capable of audio inputs and outputs via REST API
GPT-4 Turbo and GPT-4	The previous set of high-intelligence models
GPT-3.5 Turbo	A fast model for simple tasks, superceded by GPT-4o-mini
DALLE	A model that can generate and edit images given a natural language prompt
TTS	A set of models that can convert text into natural sounding spoken audio
Whisper	A model that can convert audio into text
Embeddings	A set of models that can convert text into a numerical form
Moderation	A fine-tuned model that can detect whether text may be sensitive or unsafe
Deprecated	A full list of models that have been deprecated along with the suggested replacement

We have also published open source models including Point-E, Whisper, Jukebox, and CLIP.

### Context window


Models on this page will list a **context window**, which refers to the maximum number of tokens that can be used in a single request, inclusive of both input, output, and reasoning tokens. For example, when making an API request to chat completions with the o1 model, the following token counts will apply toward the context window total:

Input tokens (inputs you include in the messages array with chat completions)

Output tokens (tokens generated in response to your prompt)

Reasoning tokens (used by the model to plan a response)

Tokens generated in excess of the context window limit may be truncated in API responses.



You can estimate the number of tokens your messages will use with the tokenizer tool.

# Model ID aliases and snapshots

In the tables below, you will see **model IDs** that can be used in REST APIs like chat completions to generate outputs. Some of these model IDs are **aliases** which point to specific **dated snapshots**.

For example, the <code>gpt-4o</code> model ID is an alias that points to a specific dated snapshot of GPT-4o. The dated snapshots that these aliases point to are periodically updated to newer snapshots a few months after a newer snapshot becomes available. Model IDs that are aliases note the model ID they currently point to in the tables below.

```
javascript $
                                                                                    ð
API request using a model alias
   import OpenAI from "openai";
2
   const openai = new OpenAI();
3
4
   const completion = await openai.chat.completions.create({
5
       model: "gpt-4o",
6
       messages: [
7
            { role: "developer", content: "You are a helpful assistant." },
8
9
                role: "user",
10
                content: "Write a haiku about recursion in programming.",
```

```
11     },
12     ],
13 });
14
15 console.log(completion.choices[0].message);
```

In API requests where an alias was used as a model ID, the body of the response will contain the actual model ID used to generate the response.

```
ð
1
  {
     "id": "chatcmpl-Af6LFgb0Ppqu2fhGsVktc9xFaYUVh",
2
3
     "object": "chat.completion",
     "created": 1734359189,
5
     "model": "gpt-4o-2024-08-06",
6
     "choices": [
       {
8
         "index": 0,
         "message": {
9
           "role": "assistant",
10
           "content": "Code within a loop, \nFunction calls itself again, \nInfini
11
           "refusal": null
12
13
         },
         "logprobs": null,
14
         "finish_reason": "stop"
15
16
       }
     ],
17
     "usage": {}
19 }
```

### Current model aliases

Below, please find current model aliases, and guidance on when they will be updated to new versions (if guidance is available).

ALIAS	POINTS TO	
gpt-4o	gpt-4o-2024-08-06	
chatgpt-4o-latest	Latest used in ChatGPT	
gpt-4o-mini	gpt-4o-mini-2024-07-18	
01	01-2024-12-17	

o1-mini	o1-mini-2024-09-12
o1-preview	o1-preview-2024-09-12
gpt-4o-realtime-preview	gpt-4o-realtime-preview-2024-12-17
gpt-4o-mini-realtime-preview	gpt-4o-mini-realtime-preview-2024-12-17
gpt-4o-audio-preview	gpt-4o-audio-preview-2024-12-17

in production applications, it is a best practice to use dated model snapshot IDs instead of aliases, which may change periodically.

### GPT-40

GPT-4o ("o" for "omni") is our versatile, high-intelligence flagship model. It accepts both text and image inputs, and produces text outputs (including Structured Outputs). Learn how to use GPT-4o in our text generation guide.

The chatgpt-4o-latest model ID below continuously points to the version of GPT-4o used in ChatGPT. It is updated frequently, when there are significant changes to ChatGPT's GPT-4o model.

The knowledge cutoff for GPT-40 models is October, 2023.

MODEL	CONTEXT WINDOW	MAX OUTPUT TOKENS
gpt-4o Ly (gpt-4o-2024-08-06)	128,000 tokens	16,384 tokens
gpt-4o-2024-11-20	128,000 tokens	16,384 tokens
gpt-4o-2024-08-06	128,000 tokens	16,384 tokens
gpt-4o-2024-05-13	128,000 tokens	4,096 tokens
chatgpt-4o-latest L, GPT-4o used in ChatGPT	128,000 tokens	16,384 tokens

## GPT-40 mini

GPT-40 mini ("o" for "omni") is a fast, affordable small model for focused tasks. It accepts both text and image inputs, and produces text outputs (including Structured Outputs). It is ideal for fine-tuning, and model outputs from a larger model like GPT-40 can be distilled to GPT-40-mini to produce similar results at lower cost and latency.

The knowledge cutoff for GPT-4o-mini models is October, 2023.

MODEL	CONTEXT WINDOW	MAX OUTPUT TOKENS
gpt-4o-mini Ly (gpt-4o-mini-2024-07-18)	128,000 tokens	16,384 tokens
gpt-4o-mini-2024-07-18	128,000 tokens	16,384 tokens

#### o1 and o1-mini

The o1 series of models are trained with reinforcement learning to perform complex reasoning. o1 models think before they answer, producing a long internal chain of thought before responding to the user. Learn about the capabilities of o1 models in our reasoning guide.

There are two model types available today:

o1: reasoning model designed to solve hard problems across domains

o1-mini: fast and affordable reasoning model for specialized tasks

The latest o1 model supports both text and image inputs, and produces text outputs (including Structured Outputs). o1-mini currently only supports text inputs and outputs.

The knowledge cutoff for o1 and o1-mini models is October, 2023.

MODEL	CONTEXT WINDOW	MAX OUTPUT TOKENS
o1 l, o1-2024-12-17	200,000 tokens	100,000 tokens
01-2024-12-17	200,000 tokens	100,000 tokens
o1-mini l, o1-mini-2024-09-12	128,000 tokens	65,536 tokens
o1-mini-2024-09-12	128,000 tokens	65,536 tokens

o1-preview	128,000 tokens	32,768 tokens	
o1-preview-2024-09-12			
o1-preview-2024-09-12	128,000 tokens	32,768 tokens	

### GPT-40 and GPT-40-mini Realtime Beta

This is a preview release of the GPT-4o and GPT-4o-mini Realtime models. These models are capable of responding to audio and text inputs in realtime over WebRTC or a WebSocket interface. Learn more in the Realtime API guide.

The knowledge cutoff for GPT-40 Realtime models is October, 2023.

MODEL	CONTEXT WINDOW	MAX OUTPUT TOKENS
<pre>gpt-4o-realtime-preview ly (gpt-4o-realtime-preview-2024-12-17)</pre>	128,000 tokens	4,096 tokens
gpt-4o-realtime-preview-2024-12-17	128,000 tokens	4,096 tokens
gpt-4o-realtime-preview-2024-10-01	128,000 tokens	4,096 tokens
<pre>gpt-4o-mini-realtime-preview Ly (gpt-4o-mini-realtime-preview-2024-12-17)</pre>	128,000 tokens	4,096 tokens
gpt-4o-mini-realtime-preview-2024-12-17	128,000 tokens	4,096 tokens

#### GPT-40 Audio Beta

This is a preview release of the GPT-4o Audio models. These models accept audio inputs and outputs, and can be used in the Chat Completions REST API. Learn more.

The knowledge cutoff for GPT-4o Audio models is October, 2023.

MODEL	CONTEXT WINDOW	MAX OUTPUT TOKENS
<pre>gpt-4o-audio-preview  Ly gpt-4o-audio-preview-2024-12-17</pre>	128,000 tokens	16,384 tokens
gpt-4o-audio-preview-2024-12-17	128,000 tokens	16,384 tokens

gpt-4o-audio-preview-2024-10-01

128,000 tokens

16,384 tokens

#### GPT-4 Turbo and GPT-4

GPT-4 is an older version of a high-intelligence GPT model, usable in Chat Completions. Learn more in the text generation guide. The knowledge cutoff for the latest GPT-4 Turbo version is **December**, **2023**.

MODEL	CONTEXT WINDOW	MAX OUTPUT TOKENS
gpt-4-turbo-2024-04-09	128,000 tokens	4,096 tokens
gpt-4-turbo-2024-04-09	128,000 tokens	4,096 tokens
<pre>gpt-4-turbo-preview l, gpt-4-0125-preview</pre>	128,000 tokens	4,096 tokens
gpt-4-0125-preview	128,000 tokens	4,096 tokens
gpt-4-1106-preview	128,000 tokens	4,096 tokens
gpt-4 L, gpt-4-0613	8,192 tokens	8,192 tokens
gpt-4-0613	8,192 tokens	8,192 tokens
gpt-4-0314	8,192 tokens	8,192 tokens

## GPT-3.5 Turbo

GPT-3.5 Turbo models can understand and generate natural language or code and have been optimized for chat using the Chat Completions API but work well for non-chat tasks as well.

(i) As of July 2024, gpt-4o-mini should be used in place of gpt-3.5-turbo, as it is cheaper, more capable, multimodal, and just as fast. gpt-3.5-turbo is still available for use in the API.

MODEL	CONTEXT WINDOW	MAX OUTPUT TOKENS	KNOWLEDGE CUTOFF
gpt-3.5-turbo-0125 The latest GPT-3.5 Turbo model with higher accuracy at responding in requested formats and a fix for a bug which caused a text encoding issue for non-English language function calls.  Learn more.	16,385 tokens	4,096 tokens	Sep 2021
<pre>gpt-3.5-turbo Currently points to gpt-3.5-turbo-0125.</pre>	16,385 tokens	4,096 tokens	Sep 2021
gpt-3.5-turbo-1106 GPT-3.5 Turbo model with improved instruction following, JSON mode, reproducible outputs, parallel function calling, and more. Learn more.	16,385 tokens	4,096 tokens	Sep 2021
gpt-3.5-turbo-instruct Similar capabilities as GPT-3 era models. Compatible with legacy Completions endpoint and not Chat Completions.	4,096 tokens	4,096 tokens	Sep 2021

#### **DALL-E**

DALL-E is a AI system that can create realistic images and art from a description in natural language. DALL-E 3 currently supports the ability, given a prompt, to create a new image with a specific size. DALL-E 2 also support the ability to edit an existing image, or create variations of a user provided image.

DALL-E 3 is available through our Images API along with DALL-E 2. You can try DALL-E 3 through ChatGPT Plus.

MODEL	DESCRIPTION
dall-e-	The latest DALL-E model released in Nov 2023. Learn more.
dall-e-	The previous DALL·E model released in Nov 2022. The 2nd iteration of DALL·E with more realistic, accurate, and 4x greater resolution images than the original model.

### **TTS**

TTS is an AI model that converts text to natural sounding spoken text. We offer two different model variates, tts-1 is optimized for real time text to speech use cases and tts-1-hd is optimized for quality. These models can be used with the Speech endpoint in the Audio API.

MODEL	DESCRIPTION
tts-1	The latest text to speech model, optimized for speed.

tts-1-hd

The latest text to speech model, optimized for quality.

## Whisper

Whisper is a general-purpose speech recognition model. It is trained on a large dataset of diverse audio and is also a multi-task model that can perform multilingual speech recognition as well as speech translation and language identification. The Whisper v2-large model is currently available through our API with the whisper-1 model name.

Currently, there is no difference between the open source version of Whisper and the version available through our API. However, through our API, we offer an optimized inference process which makes running Whisper through our API much faster than doing it through other means. For more technical details on Whisper, you can read the paper.

# **Embeddings**

Embeddings are a numerical representation of text that can be used to measure the relatedness between two pieces of text. Embeddings are useful for search, clustering, recommendations, anomaly detection, and classification tasks. You can read more about our latest embedding models in the announcement blog post.

MODEL	OUTPUT DIMENSION
text-embedding-3-large  Most capable embedding model for both english and non-english tasks	3,072
text-embedding-3-small Increased performance over 2nd generation ada embedding model	1,536
text-embedding-ada-002	1,536

Most capable 2nd generation embedding model, replacing 16 first generation models

### Moderation

The Moderation models are designed to check whether content complies with OpenAl's usage policies. The models provide classification capabilities that look for content in categories like hate, self-harm, sexual content, violence, and others. Learn more about moderating text and images in our moderation guide.

MODEL	MAX TOKENS
omni-moderation-latest	32,768

MODEL	MAX TOKENS
Currently points to omni-moderation-2024-09-26.	
omni-moderation-2024-09-26	32,768
Latest pinned version of our new multi-modal moderation model, capable of analyzing both text and images.	
text-moderation-latest	32,768
Currently points to text-moderation-007.	
text-moderation-stable	32,768
Currently points to text-moderation-007.	
text-moderation-007	32,768

Previous generation text-only moderation. We expect omni-moderation-\* models to be the best default moving forward.

#### **GPT** base

GPT base models can understand and generate natural language or code but are not trained with instruction following. These models are made to be replacements for our original GPT-3 base models and use the legacy Completions API. Most customers should use GPT-3.5 or GPT-4.

MODEL	MAX TOKENS	KNOWLEDGE CUTOFF
babbage-002 Replacement for the GPT-3 ada and babbage base models.	16,384 tokens	Sep 2021
davinci-002  Replacement for the GPT-3 curie and davinci base models.	16,384 tokens	Sep 2021

## How we use your data

Your data is your data.

As of March 1, 2023, data sent to the OpenAl API will not be used to train or improve OpenAl models (unless you explicitly opt-in to share data with us, such as by providing feedback in the Playground). One advantage to opting in is that the models may get better at your use case over time.

To help identify abuse, API data may be retained for up to 30 days, after which it will be deleted (unless otherwise required by law). For trusted customers with sensitive applications, zero data retention may be available. With zero data retention, request and response bodies are not persisted to any logging mechanism and exist only in memory in order to serve the request.

Note that this data policy does not apply to OpenAl's non-API consumer services like ChatGPT or DALL-E Labs.

# Default usage policies by endpoint

ENDPOINT	DATA USED FOR TRAINING	DEFAULT RETENTION	ELIGIBLE FOR ZERO RETENTION
/v1/chat/completions*	No	30 days	Yes, except (a) image inputs, (b) schemas provided for Structured Outputs, or (c) audio outputs. *
/v1/assistants	No	30 days **	No
/v1/threads	No	30 days **	No
/v1/threads/messages	No	30 days **	No
/v1/threads/runs	No	30 days **	No
/v1/vector_stores	No	30 days **	No
/v1/threads/runs/steps	No	30 days **	No
/v1/images/generations	No	30 days	No
/v1/images/edits	No	30 days	No
/v1/images/variations	No	30 days	No
/v1/embeddings	No	30 days	Yes
/v1/audio/transcriptions	No	Zero data retention	-
/v1/audio/translations	No	Zero data retention	-
/v1/audio/speech	No	30 days	Yes
/v1/files	No	Until deleted by customer	No
/v1/fine_tuning/jobs	No	Until deleted by customer	No
/v1/batches	No	Until deleted by customer	No
/v1/moderations	No	Zero data retention	-
/v1/completions	No	30 days	Yes
/v1/realtime (beta)	No	30 days	Yes

#### \* Chat Completions:

Image inputs via the [o1], [gpt-4o], [gpt-4o-mini], [chatgpt-4o-latest], or [gpt-4-turbo] models (or previously [gpt-4-vision-preview]) are not eligible for zero retention.

Audio outputs are stored for 1 hour to enable multi-turn conversations, and are not currently eligible for zero retention.

When Structured Outputs is enabled, schemas provided (either as the response\_format or in the function definition) are not eligible for zero retention, though the completions themselves are.

When using Stored Completions via the store: true option in the API, those completions are stored for 30 days. Completions are stored in an unfiltered form after an API response, so please avoid storing completions that contain sensitive data.

#### \*\* Assistants API:

Objects related to the Assistants API are deleted from our servers 30 days after you delete them via the API or the dashboard. Objects that are not deleted via the API or dashboard are retained indefinitely.

#### **Evaluations:**

Evaluation data: When you create an evaluation, the data related to that evaluation is deleted from our servers 30 days after you delete it via the dashboard. Evaluation data that is not deleted via the dashboard is retained indefinitely.

For details, see our API data usage policies. To learn more about zero retention, get in touch with our sales team.

## Model endpoint compatibility

ENDPOINT	LATEST MODELS
/v1/assistants	All GPT-4o (except chatgpt-4o-latest), GPT-4o-mini, GPT-4, and GPT-3.5 Turbo models. The retrieval tool requires gpt-4-turbo-preview (and subsequent dated model releases) or gpt-3.5-turbo-1106 (and subsequent versions).
/v1/audio/transcriptions	whisper-1
/v1/audio/translations	whisper-1
/v1/audio/speech	tts-1, tts-1-hd

ENDPOINT	LATEST MODELS
/v1/chat/completions	All GPT-4o (except for Realtime preview), GPT-4o-mini, GPT-4, and GPT-3.5 Turbo models and their dated releases. chatgpt-4o-latest dynamic model. Fine-tuned versions of gpt-4o, gpt-4o-mini, gpt-4, and gpt-3.5-turbo.
/v1/completions (Legacy)	gpt-3.5-turbo-instruct, babbage-002, davinci-002
/v1/embeddings	text-embedding-3-small, text-embedding-3-large, text-embedding-ada-002
/v1/fine_tuning/jobs	gpt-4o, gpt-4o-mini, gpt-4, gpt-3.5-turbo
/v1/moderations	text-moderation-stable, text-moderation-latest
/v1/images/generations	dall-e-2, dall-e-3
/v1/realtime (beta)	gpt-4o-realtime-preview, gpt-4o-realtime-preview-2024-10-01

This list excludes all of our deprecated models.