NSC LAB

Week-1: Caeser Cipher

```
#include <iostream>
using namespace std;
string encrypt(string text, int s)
    string result = "";
    for (int i = 0; i < text.length(); i++)</pre>
        if (isupper(text[i]))
            result += char(int(text[i] + s - 65) % 26 + 65);
            result += char(int(text[i] + s - 97) % 26 + 97);
    return result;
string decrypt(string text, int s)
    string result = "";
    for (int i = 0; i < text.length(); i++)</pre>
        if (isupper(text[i]))
            int res=int(text[i] - s - 65) % 26 + 65;
            if(res<65)
                 result += char(res+26);
            else
                result += char(res);
        else
            int res=int(text[i] - s - 97) % 26 + 97;
            if(res<97)
                result += char(res+26);
            else
                result += char(res);
        }
    return result;
int main()
    string text;
    int key;
    cout<<"Enter a string to encrypt:";</pre>
    cin>>text;
```

```
cout<<"Enter the key:";
cin>>key;
cout << "Text : " << text;
cout << "\nKey: " << key;
string result = encrypt(text,key);
cout << "\nEncrypted text is: " << encrypt(text,key);
cout << "\nDecrypted text is: " << decrypt(result,key);
return 0;
}</pre>
```

Enter a string to encrypt: NETWORKSECURITY

Enter the key:4

Text: NETWORKSECURITY

Key: 4

Encrypted text is: RIXASVOWIGYVMXC

Decrypted text is: NETWORKSECURITY

WEEK-2: Hill Cipher

```
#include<bits/stdc++.h>
using namespace std;
int b[3][3],de[3][3],messageVector[1][3],keyMatrix[3][3],inverseMatrix[3][3];
string text,key,res;
int calcInverse(int det)
{
    int i=1;
    while((det*i)%26!=1)
    {
        i++;
    }
        return i;
}
void getkeyMatrix(string key,int keyMatrix[][3])
{
    int k = 0;
    for (int i = 0; i < 3; i++)
    {
}</pre>
```

```
for (int j = 0; j < 3; j++)
            keyMatrix[i][j] = (key[k]) % 65;
            k++;
        }
void encrypt(int cipherkeyMatrix[][3],int keyMatrix[][3],int
messageVector[][3])
    int x, i, j;
    for (j = 0; j < 3; j++)
        for (i = 0; i < 1; i++)
            cipherkeyMatrix[i][j] = 0;
            for (x = 0; x < 3; x++)
                cipherkeyMatrix[i][j] +=
                    keyMatrix[x][j] * messageVector[0][x];
            cipherkeyMatrix[i][j] = cipherkeyMatrix[i][j] % 26;
        }
void HillCipher(string message, string key)
    int keyMatrix[3][3];
    getkeyMatrix(key, keyMatrix);
    int i=0;
    while(i<message.length())</pre>
        for(int j=0;j<3;j++)
        messageVector[0][j] = (message[i]) % 65;
        i++;
    int cipherkeyMatrix[1][3];
    encrypt(cipherkeyMatrix, keyMatrix, messageVector);
    for (int i = 0; i < 3; i++)
        res += cipherkeyMatrix[0][i] + 65;
    res+="";
    cout << " Ciphertext:" << res;</pre>
void inversekeyMatrix(string key) {
```

```
getkeyMatrix(key, keyMatrix);
   int det=0;
   for(int i = 0; i < 3; i++)
    det = det + (keyMatrix[0][i] * (keyMatrix[1][(i+1)%3] *
keyMatrix[2][(i+2)%3] - keyMatrix[1][(i+2)%3] * keyMatrix[2][(i+1)%3]));
    cout<<det<<endl;</pre>
    if(det<0)
        det=det%26+26;
        cout<<det;</pre>
    cout<<"\n\nInverse of keyMatrix is: \n";</pre>
    for(int i = 0; i < 3; i++){
    for(int j = 0; j < 3; j++)
    inverseMatrix[i][j]=((keyMatrix[(j+1)%3][(i+1)%3] *
keyMatrix[(j+2)%3][(i+2)%3]) - (keyMatrix[(j+1)%3][(i+2)%3] *
keyMatrix[(j+2)%3][(i+1)%3]))%26;
    if(inverseMatrix[i][j]<0)</pre>
    inverseMatrix[i][j]+=26;
    int x=calcInverse(det);
   for(int i = 0; i < 3; i++){
    for(int j = 0; j < 3; j++)
        inverseMatrix[i][j]*=x;
        inverseMatrix[i][j]%=26;
void decrypt(string key)
   inversekeyMatrix(key);
   int x, i, j;
   string res1;
   int a[res.length()],c[1][3],cipherkeyMatrix1[1][3];
   for(int i=0;i<res.length();i++)</pre>
       a[i]=res[i]%65;
   for(int b=0;b<res.length();b+=3)</pre>
       c[0][0]=a[b];
       c[0][1]=a[b+1];
       c[0][2]=a[b+2];
       for (j = 0; j < 3; j++)
```

```
for (i = 0; i < 1; i++)
                 cipherkeyMatrix1[i][j] = 0;
                for (x = 0; x < 3; x++)
                     cipherkeyMatrix1[i][j] +=inverseMatrix[x][j] * c[0][x];
                cipherkeyMatrix1[i][j] = cipherkeyMatrix1[i][j] % 26;
       for (int i = 0; i < 3; i++)
            res1 += cipherkeyMatrix1[0][i] + 65;
        res1+=" ";
   cout<<res1<<" ";</pre>
int main()
    cout<<"Enter a string to encrypt:";</pre>
    cin>>text;
    if(text.length()%3!=0)
        int s=text.length()%3;
        for(int i=0;i<3-s;i++)</pre>
        text+="X";
    cout<<"Enter the key:";</pre>
    cin>>key;
    // string key = "RRFVSVCCT";
   HillCipher(text, key);
   decrypt(key);
    return 0;
```

Enter a string to encrypt:PAYMOREMONEY

Enter the key:RRFVSVCCT

Cipher text is:RRLMWBKASPDH

Decrypted text is:PAY MOR EMO NEY

WEEK-3: DES

```
#include <bits/stdc++.h>
using namespace std;
string hex2bin(string s)
   unordered_map<char, string> mp;
   mp['0'] = "0000";
   mp['1'] = "0001";
   mp['2'] = "0010";
   mp['3'] = "0011";
   mp['4'] = "0100";
    mp['5'] = "0101";
    mp['6'] = "0110";
   mp['7'] = "0111";
   mp['8'] = "1000";
   mp['9'] = "1001";
   mp['A'] = "1010";
   mp['B'] = "1011";
   mp['C'] = "1100";
   mp['D'] = "1101";
   mp['E'] = "1110";
   mp['F'] = "1111";
    string bin = "";
    for (int i = 0; i < s.size(); i++) {
        bin += mp[s[i]];
    return bin;
string bin2hex(string s)
    unordered_map<string, string> mp;
   mp["0000"] = "0";
   mp["0001"] = "1";
   mp["0010"] = "2";
   mp["0011"] = "3";
   mp["0100"] = "4";
    mp["0101"] = "5";
    mp["0110"] = "6";
    mp["0111"] = "7";
   mp["1000"] = "8";
   mp["1001"] = "9";
   mp["1010"] = "A";
   mp["1011"] = "B";
   mp["1100"] = "C";
    mp["1101"] = "D";
    mp["1110"] = "E";
   mp["1111"] = "F";
```

```
string hex = "";
    for (int i = 0; i < s.length(); i += 4) {
        string ch = "";
        ch += s[i];
        ch += s[i + 1];
        ch += s[i + 2];
        ch += s[i + 3];
        hex += mp[ch];
    return hex;
string permute(string k, int* arr, int n)
    string per = "";
    for (int i = 0; i < n; i++) {
        per += k[arr[i] - 1];
    return per;
string shift_left(string k, int shifts)
    string s = "";
    for (int i = 0; i < shifts; i++) {</pre>
        for (int j = 1; j < 28; j++) {
            s += k[j];
        s += k[0];
        k = s;
    return k;
string xor_(string a, string b)
    string ans = "";
    for (int i = 0; i < a.size(); i++) {
        if (a[i] == b[i]) {
            ans += "0";
        else {
            ans += "1";
        }
    return ans;
string encrypt(string pt, vector<string> rkb,
```

```
vector<string> rk)
pt = hex2bin(pt);
int initial_perm[64]
   = \{ 58, 50, 42, 34, 26, 18, 10, 2, 60, 52, 44, \}
       36, 28, 20, 12, 4, 62, 54, 46, 38, 30, 22,
       14, 6, 64, 56, 48, 40, 32, 24, 16, 8, 57,
       49, 41, 33, 25, 17, 9, 1, 59, 51, 43, 35,
       27, 19, 11, 3, 61, 53, 45, 37, 29, 21, 13,
       5, 63, 55, 47, 39, 31, 23, 15, 7 };
pt = permute(pt, initial_perm, 64);
string left = pt.substr(0, 32);
string right = pt.substr(32, 32);
int exp_d[48]
   = { 32, 1,
             2, 3, 4, 5, 4, 5, 6, 7, 8,
       8, 9, 10, 11, 12, 13, 12, 13, 14, 15, 16, 17,
       16, 17, 18, 19, 20, 21, 20, 21, 22, 23, 24, 25,
       24, 25, 26, 27, 28, 29, 28, 29, 30, 31, 32, 1 };
int s[8][4][16] = {
   \{14, 4, 13, 1, 2, 15, 11, 8, 3, 10, 6, 12, 5,
     9, 0, 7, 0, 15, 7, 4, 14, 2, 13, 1, 10, 6,
                             1, 14, 8, 13, 6,
     12, 11, 9, 5, 3, 8, 4,
     11, 15, 12, 9, 7, 3, 10, 5, 0, 15, 12, 8,
     4, 9, 1, 7, 5, 11, 3, 14, 10, 0, 6,
   { 15, 1, 8, 14, 6, 11, 3, 4, 9, 7, 2,
                                             13, 12,
            10, 3, 13, 4, 7, 15, 2,
                                     8,
                                        14, 12, 0,
     0, 5,
     1, 10, 6, 9, 11, 5, 0, 14, 7, 11, 10, 4, 13,
        5, 8, 12, 6, 9, 3, 2, 15, 13, 8, 10, 1,
     1,
        15, 4, 2, 11, 6,
                          7, 12, 0, 5, 14, 9 },
     3,
   { 10, 0, 9, 14, 6, 3, 15, 5, 1, 13, 12,
     7, 11, 4, 2, 8, 13, 7, 0, 9, 3,
     6, 10, 2, 8,
                   5, 14, 12, 11, 15, 1,
                                          13,
        4, 9, 8, 15, 3, 0, 11, 1, 2,
                                          12,
        10, 14, 7, 1, 10, 13, 0, 6, 9,
                       11, 5, 2,
     7,
        4, 15, 14, 3,
                                   12 },
   { 7, 13, 14, 3, 0,
                       6, 9,
                              10, 1, 2, 8, 5,
     12, 4, 15, 13, 8,
                       11, 5, 6, 15, 0, 3, 4,
     2, 12, 1, 10, 14, 9, 10, 6, 9, 0, 12, 11, 7,
     13, 15, 1, 3, 14, 5, 2, 8, 4, 3, 15, 0,
     10, 1, 13, 8, 9, 4,
                              11, 12, 7, 2, 14 },
   { 2, 12, 4, 1, 7, 10, 11, 6, 8, 5, 3, 15, 13,
     0, 14, 9, 14, 11, 2, 12, 4, 7, 13, 1,
                                            5, 0,
     15, 10, 3, 9, 8, 6, 4, 2, 1, 11, 10, 13, 7,
     8, 15, 9, 12, 5, 6, 3, 0, 14, 11, 8, 12, 7,
     1, 14, 2, 13, 6, 15, 0, 9, 10, 4, 5, 3 },
   \{12, 1, 10, 15, 9, 2, 6, 8, 0, 13, 3, 4, 14,
           11, 10, 15, 4, 2, 7, 12, 9, 5, 6, 1,
        5,
```

```
13, 14, 0, 11, 3, 8, 9, 14, 15, 5, 2, 8, 12,
     3, 7, 0, 4, 10, 1, 13, 11, 6, 4, 3, 2, 12,
     9, 5, 15, 10, 11, 14, 1, 7, 6, 0, 8, 13 },
    { 4, 11, 2, 14, 15, 0, 8, 13, 3, 12, 9, 7, 5,
     10, 6, 1, 13, 0, 11, 7, 4, 9, 1, 10, 14, 3,
     5, 12, 2, 15, 8, 6, 1, 4, 11, 13, 12, 3, 7,
     14, 10, 15, 6, 8, 0, 5, 9, 2, 6, 11, 13, 8,
     1, 4, 10, 7, 9, 5, 0, 15, 14, 2, 3, 12 },
    { 13, 2, 8, 4, 6, 15, 11, 1, 10, 9, 3, 14, 5,
     0, 12, 7, 1, 15, 13, 8, 10, 3, 7, 4, 12, 5,
     6, 11, 0, 14, 9, 2, 7, 11, 4, 1, 9, 12, 14,
     2, 0, 6, 10, 13, 15, 3, 5, 8, 2, 1, 14, 7,
     4, 10, 8, 13, 15, 12, 9, 0, 3, 5, 6, 11 }
};
int per[32]
    = { 16, 7, 20, 21, 29, 12, 28, 17, 1, 15, 23,
       26, 5, 18, 31, 10, 2, 8, 24, 14, 32, 27,
       3, 9, 19, 13, 30, 6, 22, 11, 4, 25 };
cout << endl;</pre>
for (int i = 0; i < 16; i++) {
    string right_expanded = permute(right, exp_d, 48);
   string x = xor_(rkb[i], right_expanded);
   string op = "";
   for (int i = 0; i < 8; i++) {
       int row = 2 * int(x[i * 6] - '0')
                + int(x[i * 6 + 5] - '0');
       int col = 8 * int(x[i * 6 + 1] - '0')
                 + 4 * int(x[i * 6 + 2] - '0')
                 + 2 * int(x[i * 6 + 3] - '0')
                 + int(x[i * 6 + 4] - '0');
       int val = s[i][row][col];
       op += char(val / 8 + '0');
       val = val % 8;
       op += char(val / 4 + '0');
       val = val % 4;
       op += char(val / 2 + '0');
       val = val % 2;
       op += char(val + '0');
   op = permute(op, per, 32);
   x = xor_(op, left);
   left = x;
   if (i != 15) {
       swap(left, right);
}
string combine = left + right;
```

```
int final_perm[64]
        = \{ 40, 8, 48, 16, 56, 24, 64, 32, 39, 7, 47, 
            15, 55, 23, 63, 31, 38, 6, 46, 14, 54, 22,
            62, 30, 37, 5, 45, 13, 53, 21, 61, 29, 36,
            4, 44, 12, 52, 20, 60, 28, 35, 3, 43, 11,
            51, 19, 59, 27, 34, 2, 42, 10, 50, 18, 58,
            26, 33, 1, 41, 9, 49, 17, 57, 25 };
    string cipher
        = bin2hex(permute(combine, final_perm, 64));
    return cipher;
int main()
    string pt, key;
    cout<<"Enter plain text(in hexadecimal)(123456ABCD132536): ";</pre>
    cout<<"Enter key(in hexadecimal)(AABB09182736CCDD): ";</pre>
    cin>>key;
   int keyp[56]
        = \{ 57, 49, 41, 33, 25, 17, 9, 1, 58, 50, 42, 34, 
            26, 18, 10, 2, 59, 51, 43, 35, 27, 19, 11, 3,
            60, 52, 44, 36, 63, 55, 47, 39, 31, 23, 15, 7,
            62, 54, 46, 38, 30, 22, 14, 6, 61, 53, 45, 37,
            29, 21, 13, 5, 28, 20, 12, 4 };
    key = permute(key, keyp, 56);
    int shift_table[16] = { 1, 1, 2, 2, 2, 2, 2, 2,
                            1, 2, 2, 2, 2, 2, 1 };
    int key_comp[48] = { 14, 17, 11, 24, 1, 5, 3, 28,
                         15, 6, 21, 10, 23, 19, 12, 4,
                         26, 8, 16, 7, 27, 20, 13, 2,
                         41, 52, 31, 37, 47, 55, 30, 40,
                         51, 45, 33, 48, 44, 49, 39, 56,
                         34, 53, 46, 42, 50, 36, 29, 32 };
    string left = key.substr(0, 28);
    string right = key.substr(28, 28);
   vector<string> rkb;
    vector<string> rk;
    for (int i = 0; i < 16; i++) {
        left = shift_left(left, shift_table[i]);
        right = shift_left(right, shift_table[i]);
        string combine = left + right;
        string RoundKey = permute(combine, key_comp, 48);
        rkb.push_back(RoundKey);
        rk.push_back(bin2hex(RoundKey));
    string cipher = encrypt(pt, rkb, rk);
```

```
cout << "\nCipher Text: " << cipher << endl;

reverse(rkb.begin(), rkb.end());
reverse(rk.begin(), rk.end());
string text = encrypt(cipher, rkb, rk);
cout << "\nPlain Text: " << text << endl;
}</pre>
```

Enter plain text(in hexadecimal)(123456ABCD132536): 123456ABCD132536

Enter key(in hexadecimal)(AABB09182736CCDD): AABB09182736CCDD

Cipher Text: E2789D9ADE6C1A3B

Plain Text: 123456ABCD132536

WEEK-4: RSA

```
#include<bits/stdc++.h>
using namespace std;
int GCD(int a,int b)
    if(a==0)
       return b;
    else if(b==0)
        return a;
    else
        return GCD(b,a%b);
int power(int m,int e,int n)
    int x=1;
    for(int i=1;i<=e;i++)</pre>
        x=x*m%n;
    return x;
int main()
    int p,q,m;
    cout<<"Enter P value:";</pre>
    cin>>p;
```

```
cout<<"Enter Q value:";</pre>
cin>>q;
cout<<"Enter M value:";</pre>
cin>>m;
int n=p*q;
int e=0;
int phi_n=(p-1)*(q-1);
for(int i=2;i<phi_n;i++)</pre>
    if(GCD(i,phi_n)==1)
        e=i;
        break;
    }
int d=1;
for(int i=2;(e*i)%phi_n!=1;i++)
    d=i;
d++;
int cipher_text=power(m,e,n)%n;
cout<<"Cipher text is:"<<cipher_text;</pre>
int decrypted_text=power(cipher_text,d,n)%n;
cout<<"\nDecrypted text is:"<<decrypted_text;</pre>
return 0;
```

Enter P value:3

Enter Q value:5

Enter M value:4

Cipher text is:4

Decrypted text is:4

WEEK-5: Deffie Helman

```
#include<bits/stdc++.h>
using namespace std;
int power(int m,int e,int n)
{
```

```
int x=1;
    for(int i=1;i<=e;i++)</pre>
        x=x*m%n;
    return x;
int main()
    int q,alpha;
    cout<<"Enter a prime number:";</pre>
    cin>>q;
    set<int> s;
    for(int i=2;i<q;i++)</pre>
        for(int j=1;j<q;j++)</pre>
             int x=power(i,j,q);
             x\%=q;
             s.insert(x);
         if(s.size()==q-1)
             alpha=i;
             break;
    int XA,XB;
    cout<<"Enter XA(Private key A):";</pre>
    cin>>XA;
    int YA=power(alpha,XA,q);
    YA%=q;
    cout<<"Enter XB(Private key B):";</pre>
    cin>>XB;
    int YB=power(alpha,XB,q);
    YB%=q;
    cout<<"Key of User A:";</pre>
    int KA=power(YB,XA,q);
    KA\%=q;
    cout<<KA<<endl;</pre>
    cout<<"Key of User B:";</pre>
    int KB=power(YA,XB,q);
    KB%=q;
    cout<<KB<<endl;</pre>
    return 0;
```

Enter a prime number:11

Enter XA(Private key A):8

Enter XB(Private key B):4

Key of User A:4

Key of User B:4