

Explainable Financial Alerts for Retail Investors: Integrating Statistical Anomaly Detection and News–Market Impact Correlation

Henrique José da Silva Santos

Student No.: 1180934

**A dissertation submitted in partial fulfillment of
the requirements for the degree of Master of Science,
Specialisation Area of**

Supervisor: Luís Gomes
Co-Supervisor: Rafael Silva

Evaluation Committee:

President:
[A definir]

Members:
[A definir]

Porto, June 25, 2026

Statement Of Integrity

I hereby declare that I have conducted this academic work with integrity.

I have not plagiarised or applied any form of undue use of information or falsification of results along the process leading to its elaboration.

Therefore, the work presented in this document is original and was authored by me, having not been previously used for any other purpose.

I declare that I have fully acknowledged the Code of Ethical Conduct of P.PORTO.

Use of Artificial Intelligence. In accordance with the P.PORTO/ISEP guidelines, I declare that artificial intelligence tools (notably Claude Code) were used during the development of this work to assist with the drafting and editing of the text and with software development. I directed the work and critically reviewed and validated all outputs; the ideas, decisions and final content are my own and are my responsibility.

ISEP, Porto, June 25, 2026

Dedictory

Abstract

This dissertation presents CLARION, an explainable (XAI-first) financial-alert system for retail investors in the US equity market (NYSE and NASDAQ). The system raises Telegram alerts from two independent triggers — abrupt market movements, detected as statistical anomalies, and incoming financial news — and, for every alert, exposes a fully traceable explanation: the detected event, the reasoning applied, the sources, and historical precedents. Its core is a news–market correlation engine that, given a news item, retrieves analogous historical news from a knowledge base and measures the impact those precedents had on prices, in the manner of an event study and without lookahead. As an Artificial Intelligence Engineering contribution, the work integrates, applies and critically evaluates existing components — sentence-embedding retrieval, statistical anomaly detection and transparent explanation — in a functional, explainable and reproducible system. On real data, semantic retrieval clearly outperformed lexical and trivial baselines (cross-ticker precision@5 of 0.51 against 0.24 for random retrieval), and the volatility-normalised detector fired far more consistently across stocks than a fixed threshold. The results are honest and reproducible, with limitations and future work stated explicitly.

Keywords: Explainable AI, Financial Alerts, Anomaly Detection, News Impact, Retail Investors, Financial NLP

Resumo

Esta dissertação apresenta o CLARION, um sistema de alertas financeiros explicável (XAI-first) para investidores de retalho no mercado acionista dos Estados Unidos (NYSE e NASDAQ). O sistema envia alertas via Telegram a partir de dois gatilhos independentes — movimentos abruptos de mercado, detetados como anomalias estatísticas, e novas notícias financeiras — e, para cada alerta, expõe uma explicação totalmente rastreável: o evento detetado, o raciocínio aplicado, as fontes e os precedentes históricos. O seu núcleo é um motor de correlação notícia–mercado que, dada uma notícia, recupera notícias históricas análogas de uma base de conhecimento e mede o impacto que esses precedentes tiveram nos preços, à maneira de um estudo de evento e sem lookahead. Enquanto contribuição de Engenharia de Inteligência Artificial, o trabalho integra, aplica e avalia criticamente componentes existentes — recuperação por embeddings de frases, deteção estatística de anomalias e explicação transparente — num sistema funcional, explicável e reproduzível. Em dados reais, a recuperação semântica superou claramente as baselines lexical e triviais (precision@5 cross-ticker de 0,51 face a 0,24 do acaso) e o detetor normalizado pela volatilidade disparou de forma muito mais consistente entre ações do que um limiar fixo. Os resultados são honestos e reproduzíveis, com limitações e trabalho futuro explícitos.

Palavras-chave: Explainable AI, Financial Alerts, Anomaly Detection, News Impact, Retail Investors, Financial NLP

Acknowledgement

Contents

List of Algorithms	xix
List of Source Code	xxi
List of Acronyms	xxv
1 Introduction	1
1.1 Contextualization	1
1.2 Problem Statement	2
1.3 Research Questions and Objectives	2
1.4 Scientific Contributions	3
1.5 Document Structure	3
2 State of the Art	5
2.1 Retail Investing and Information Overload	5
2.2 Anomaly Detection in Financial Markets	6
2.3 Explainable Artificial Intelligence	7
2.4 Financial NLP and Text Representation	9
2.5 Event Studies and News–Market Impact	11
2.6 Case-Based Reasoning and Precedent Retrieval	11
2.7 Comparative Analysis and Positioning	12
2.8 Chapter Conclusions	12
3 Methods and Materials	13
3.1 Approach and Methodology	13
3.2 Datasets and Data Sources	13
3.2.1 Historical Layer: the FNSPID Corpus	14
3.2.2 Preprocessing and Event Alignment	14
3.2.3 Live Layer and Evaluation Dataset	15
3.2.4 Data Governance and Attribution	15
3.3 Models and Techniques	15
3.3.1 Statistical Anomaly Detection	15
3.3.2 Semantic Retrieval and Impact Measurement	16
3.3.3 Explanation Techniques	16
3.4 Tools and Frameworks	16
3.5 Responsible AI and Ethics	16
3.6 Evaluation Methodology	17
3.7 Chapter Conclusions	17
4 CLARION: An Explainable Financial-Alert System for Retail Investors	19
4.1 Overview	19

4.2	Architecture	19
4.3	Historical Knowledge Base and Correlation Engine	20
4.4	Anomaly Trigger	21
4.5	Explanation Engine	21
4.6	Alert Delivery	22
4.7	Chapter Conclusions	22
5	Case Studies	25
5.1	Common Experimental Setup	25
5.2	Case Study 1: Transparent Anomaly Detection on US Equities	25
5.3	Case Study 2: News–Market Precedent Retrieval	27
5.4	Case Study 3: End-to-End Alert and Explanation Faithfulness	30
5.5	Discussion and Threats to Validity	31
5.6	Chapter Conclusions	31
6	Conclusions	33
6.1	Main Conclusions	33
6.2	Research Questions and Objectives Achieved	34
6.3	Contributions Revisited	34
6.4	Limitations	34
6.5	Future Work	34
	Bibliography	37
A	Reproducibility	41
A.1	Environment	41
A.2	Repository Organisation	41
A.3	Tests and Reproducible Results	41
A.4	Data and Attribution	42

List of Figures

1.1	US equity market capitalisation, 2015–2024	1
1.2	What CLARION does	2
2.1	Taxonomy of anomaly-detection methods	6
2.2	Taxonomy of explainability approaches	8
3.1	The two data layers	14
4.1	System architecture and data flow	20
4.2	The news trigger end to end	21
4.3	The market-movement trigger end to end	22
4.4	Telegram alert as received by the investor	22
5.1	Firing rate per ticker: fixed threshold versus z-score	26
5.2	Worked example: z-score anomalies on a volatile stock	27
5.3	Window-size ablation for the anomaly detector	28
5.4	Precedent retrieval: SBERT versus baselines	28
5.5	Precedent retrieval by sector	29

List of Tables

2.1	Anomaly-detection approaches relevant to this work.	7
2.2	Explainability approaches considered.	9
2.3	Text-representation approaches for financial news.	10
2.4	Component choices in this work versus alternatives.	12
3.1	Data card for the historical layer (FNSPID).	14
4.1	Principal design decisions in Clarion and their rationale.	21
5.1	Firing rate across the fifteen tickers (three years of daily data).	26
5.2	Cross-ticker precision@ k by sector, mean $\pm$ std over five runs (3,714 real headlines, five sectors).	27
5.3	Cross-ticker precision@ k per sector (whole-population queries, MiniLM).	29

List of Algorithms

List of Source Code

List of Symbols

r_t	log-return of an asset on day t	—
μ_t	rolling mean of returns	—
σ_t	rolling standard deviation of returns	—
z_t	z-score of the return on day t	—
k	anomaly threshold (in standard deviations)	—
w	rolling-window length	d

List of Acronyms

AI	Artificial Intelligence.
NASDAQ	National Association of Securities Dealers Automated Quotations.
NYSE	New York Stock Exchange.
RQ	Research Question.

Chapter 1

Introduction

1.1 Contextualization

Most Americans now own stock, either directly or through retirement accounts and mutual funds (Gallup 2025). At the same time, the US equity market has grown into the world's largest and most liquid, reaching US\$62.2 trillion at the end of 2024 (Securities Industry and Financial Markets Association (SIFMA) 2025) (Figure 1.1). Trading takes place mainly on the New York Stock Exchange (NYSE) and National Association of Securities Dealers Automated Quotations (NASDAQ), and a growing share of it now comes from ordinary people using commission-free mobile apps rather than from professional institutions.




Figure 1.1: US equity market capitalisation, 2015–2024 (US\$ trillion). Drawn from data reported in the SIFMA 2025 Capital Markets Fact Book (Securities Industry and Financial Markets Association (SIFMA) 2025).

These non-professional, or “retail”, investors are the audience of this work. Stock ownership among them is wide but uneven: it rises to 87% of households earning above US\$100,000 and falls to 28% below US\$50,000 (Gallup 2025). What they share is a hard position. Markets move continuously across thousands of securities and relevant news arrives throughout the trading day, yet retail investors have none of the tools that banks and funds take for granted.

Artificial intelligence has, meanwhile, spread quickly through finance. A 2026 survey found that 81% of financial firms were adopting Artificial Intelligence (AI) in some form and 71% were already using generative AI (Cambridge Centre for Alternative Finance 2026). Much

of this technology is opaque: the strongest models rarely reveal how they reach a conclusion (Adadi and Berrada 2018; Barredo Arrieta et al. 2020). For someone who has to act on an alert and live with the result, that opacity is a real obstacle. Letting the investor see *why* an alert was raised is what this dissertation sets out to do.

1.2 Problem Statement

A retail investor who wants to stay informed faces two distinct challenges. The first is telling a genuinely unusual price move apart from ordinary daily volatility, which takes statistical judgement and constant attention. The second is reading what a news item might mean, which takes knowledge of how similar events played out in the past, knowledge most people do not have to hand. Existing consumer applications often provide alerts with little explanation, or rely on models whose reasoning is hidden from the user.

This work does not try to predict prices. It tries to *explain*. For each abrupt move or relevant news item, the system shows what it detected, how it reached that conclusion, where the information came from, and which past events resemble the current one, alongside what happened to prices afterwards (Figure 1.2).




Figure 1.2: In one picture: two triggers — a sudden market move or a relevant news item — feed CLARION, which replies not with a bare notification but with an explained alert that the investor can follow and check.

1.3 Research Questions and Objectives

The aim is to design, build and evaluate an explainable financial-alert system for US retail investors, driven by two independent triggers, a sudden market move and an incoming news item, and delivered over Telegram. Three research questions guide the work:

- **Research Question (RQ)1.** Can transparent statistical methods detect abrupt market movements consistently enough to be useful to a retail investor, while staying explainable?
- **RQ2.** Can a news–market correlation engine retrieve genuinely analogous historical news, and quantify its observed price impact without lookahead, better than trivial baselines?
- **RQ3.** Can the resulting explanations be made faithful to what the system actually computes, and useful to a retail investor?

These questions translate into four objectives: to develop an explainable alerting pipeline driven by the two triggers; to evaluate the anomaly detector against transparent baselines; to evaluate the retrieval of historical news against trivial baselines; and to assess the faithfulness and usefulness of the explanations. The incremental, simplicity-first way the system is built is a methodological choice, described in Chapter 3.

1.4 Scientific Contributions

This is a dissertation in Artificial Intelligence *Engineering*. Its contribution is not a new algorithm but the disciplined assembly of existing ones into a system that works, explains itself, and can be reproduced. Three contributions stand out:

- A reproducible method for relating news to market impact, pairing sentence-embedding retrieval with event-study windows, where the similarity measure and the time horizons are stated explicitly and no information about the future is allowed to leak in.
- **CLARION**, an alerting system that exposes its complete reasoning chain to the user: the detected event, the supporting evidence, the sources, and the relevant historical precedents. Because each explanation is generated directly from the quantities the system computes, the text cannot diverge from the underlying computation.
- A critical evaluation of each core component on real data, against simple and lexical baselines, with the results, the ablations and the limitations all reported plainly.

1.5 Document Structure

The remainder of this dissertation is organised as follows. Chapter 2 reviews the state of the art behind the work: anomaly detection, explainable AI, financial natural-language processing, event studies, and case-based reasoning. Chapter 3 sets out the methods, the datasets and the evaluation design. Chapter 4 presents CLARION itself, at the level of its architecture and the decisions behind it. Chapter 5 evaluates the system through three case studies on real data, and Chapter 6 returns to the research questions, states what was and was not achieved, and points to future work.

Chapter 2

State of the Art

CLARION draws on several fields, and this chapter reviews them with one purpose: to justify each design choice against the alternatives. It begins with what is known about how retail investors behave and why they are exposed to information overload, since that is what the system responds to. It then works through anomaly detection, explainable AI, financial text representation, event studies, and case-based reasoning, preferring seminal and recent peer-reviewed work and summarising each area in a comparative table. The recurring finding is that the individual pieces are mature, but an integrated, explainable system aimed at the retail investor is still rare.

2.1 Retail Investing and Information Overload

The audience of this work is the non-professional, or “retail”, investor. Understanding how such investors consume information and react to news is therefore the natural starting point, because it both motivates the system and constrains what a useful alert should contain.

Behavioural finance documents that real investors deviate systematically from the fully-rational ideal; the survey of Barberis and Thaler (2003) catalogues these deviations and their two pillars, limits to arbitrage and human psychology. A foundational element of that psychology is prospect theory (Kahneman and Tversky 1979), whose central insight — *loss aversion*, the asymmetric weighting of losses against equivalent gains — helps explain why investors are especially sensitive to salient, potentially adverse news, and therefore why a timely, well-explained alert is valuable.

A central and durable finding of this literature is that individual investors are strongly influenced by *attention*. In their seminal study, Barber and Odean (2008) show that individual investors are net buyers of attention-grabbing stocks — those in the news, those with unusually high trading volume, and those with extreme one-day returns — whereas they do not face the same search problem when selling, because they tend to sell only what they already own. The explanation offered is economic: faced with thousands of stocks they could potentially buy, investors fall back on the small subset that has captured their attention. This asymmetry matters directly for an alerting system: the very events that draw a retail investor’s attention — a sharp price move or a salient news item — are precisely the two triggers around which this work is built, and an alert that adds context to such an event is intervening exactly where attention-driven decisions are made. That attention is now measurable directly: Da, Engelberg, and Gao (2011) show that internet search volume is a timely proxy for investor attention that captures, in particular, the attention of *retail* investors, reinforcing the link between salient events and the behaviour of the population this work serves.

The role of the media in shaping investor behaviour has likewise been quantified. Tetlock (2007) constructs a daily pessimism measure from a popular Wall Street Journal column and finds that high media pessimism predicts downward pressure on prices followed by a reversion to fundamentals, and that unusually high or low pessimism predicts elevated trading volume. The study is doubly relevant here: it establishes that news content carries measurable, market-moving information, and it is an early demonstration that *textual* signals can be extracted and related to market outcomes — the same premise that underlies the news–market correlation engine of this dissertation.

The composition and weight of retail participation have also shifted markedly in recent years, driven by commission-free mobile brokerages. Studying a large sample of users of one such platform, Welch (2022) documents that this new cohort of investors increased its holdings during the March 2020 bear market rather than panicking, and that an aggregated “crowd consensus” portfolio exhibited both reasonable timing and positive performance over the period studied. Whatever the debate over retail investors’ sophistication, the empirical picture is one of a large, active and consequential population — consistent with the broad ownership figures reported by Gallup (2025) and the scale of the market documented by Securities Industry and Financial Markets Association (SIFMA) (2025) in Chapter 1.

Taken together, this literature frames the problem the system addresses. Retail investors are attention-constrained, react to news, and now participate in large numbers, yet they must do so under a continuous flood of price movements and headlines that they cannot individually process. The response pursued here is not to predict the market for them, but to reduce the cost of *interpreting* the events that already command their attention, by attaching to each alert a transparent explanation and concrete historical evidence.

2.2 Anomaly Detection in Financial Markets

The first trigger of the system rests on detecting abnormal price movements, which places it within the mature field of anomaly detection. The survey of Chandola, Banerjee, and Kumar (2009) provides the standard reference and taxonomy, distinguishing *point* anomalies (an individual observation that is abnormal with respect to the rest), *contextual* anomalies (abnormal only in a particular context, such as a time of year), and *collective* anomalies (a set of observations that is jointly abnormal), and grouping detection methods into statistical, distance- and density-based, and machine-learning families. A sharp single-day return is naturally treated as a contextual point anomaly: abnormal relative to the asset’s own recent behaviour. Figure 2.1 summarises the families relevant to this work.




Figure 2.1: Families of anomaly-detection methods relevant to this work, following Chandola, Banerjee, and Kumar (2009) and Pang et al. (2021). Interpretability decreases, and modelling capacity increases, from left to right.

For financial returns, simple statistical methods — flagging deviations from a rolling mean and standard deviation, that is, a z-score — are attractive precisely because they are transparent and easy to justify, an advantage for an explainable system. They do, however, assume a locally stable distribution, an assumption that the rolling estimation window is designed to accommodate. More expressive unsupervised detectors relax such assumptions: Isolation Forest (F. T. Liu, Ting, and Zhou 2008) isolates anomalies through random partitioning, requiring fewer splits to separate an outlier, and scales well to large, high-dimensional data. The cost is reduced direct interpretability, since the anomaly score is an ensemble property rather than a quantity the user can read off. Density-based detectors such as the Local Outlier Factor (Breunig et al. 2000) take a related route, scoring a point by how isolated it is relative to the density of its neighbourhood; they capture *local* anomalies well but, again, at the expense of a directly readable justification. At the far end of the spectrum, the review by Pang et al. (2021) surveys deep-learning detectors — autoencoders, deep one-class models and others — which can capture rich, non-linear structure but are data-hungry and largely opaque, and whose advantage is most pronounced in high-dimensional settings such as images or complex multivariate streams rather than in a single return series. Within finance specifically, the survey of Ahmed, Mahmood, and Islam (2016) notes that detection is dominated by *unsupervised* methods, precisely because labelled anomalies are scarce — a constraint that also shapes the evaluation strategy adopted in this work, where a label-free consistency argument is given primacy (Chapter 5). Table 2.1 compares the families.

Table 2.1: Anomaly-detection approaches relevant to this work.

Approach	How it works	Strengths / limitations
Statistical (rolling) z-score (Chandola, Banerjee, and Kumar 2009)	Flags returns that deviate from a rolling mean and standard deviation	Transparent and easy to explain; assumes a locally stable distribution
Isolation Forest (F. T. Liu, Ting, and Zhou 2008)	Isolates points via random partitioning (ensemble)	Scalable, handles high dimensionality; score is not directly interpretable
Deep detectors (Pang et al. 2021)	Learn a model of normality (e.g. autoencoders)	High capacity for complex data; opaque, data-hungry, hard to justify

The trade-off this table makes explicit — capacity against interpretability — is the one that governs the design choice in Chapter 3. Because the system must *explain* every alert to a non-expert, and because the signal is a single, low-dimensional return series rather than a high-dimensional stream, the transparent statistical detector is preferred, with the more expressive families noted as alternatives whose opacity is not warranted by the problem at hand.

2.3 Explainable Artificial Intelligence

As AI systems are deployed in consequential settings, the inability to inspect their reasoning has become a central concern, and explainable AI (XAI) is the field that addresses it. The surveys of Adadi and Berrada (2018) and Barredo Arrieta et al. (2020) map the area: its

motivations (trust, accountability, debugging, regulatory compliance), a taxonomy that separates models that are *transparent* (interpretable in their own right) from *post-hoc* methods that explain an already-trained black box, and the open challenges on the path to responsible AI. The earlier survey of Guidotti et al. (2018) organises the post-hoc literature specifically by the problem being solved — explaining a whole model, explaining a single outcome, or inspecting the internals — which is a useful lens for situating the techniques most relevant here. Figure 2.2 sketches this division. A recurring caution in the field is that “interpretability” is not a single, well-defined property: Lipton (2018) argues that the term conflates several distinct desiderata (simulatability, decomposability, post-hoc justification) that serve different stakeholders, so a system should state *which* notion it provides. This work is explicit on that point: it offers transparency of the decision logic and traceable evidence, rather than a contested claim of total interpretability.




Figure 2.2: The two broad routes to explainability (Barredo Arrieta et al. 2020; Guidotti et al. 2018): building models that are transparent by design, or explaining a black box after the fact. This work follows the former.

Among post-hoc, model-agnostic techniques, two are widely used. LIME (Ribeiro, Singh, and Guestrin 2016) explains a single prediction by fitting a simple, interpretable surrogate model in the local neighbourhood of the instance; it is intuitive and broadly applicable, but its explanations can be unstable under resampling and are only locally faithful. SHAP (Lundberg and Lee 2017) attributes a prediction to its input features using Shapley values from cooperative game theory, which gives it desirable consistency properties and a unifying theoretical grounding, at a higher computational cost. Both are valuable when one is committed to a black-box model and needs to interrogate it after the fact.

A strand of the literature questions that commitment directly. Rudin (2019) argues forcefully that, for high-stakes decisions, one should *stop explaining* black-box models and instead use models that are interpretable in the first place, on the grounds that post-hoc explanations are approximations that can mislead and can entrench poor practice. This position is particularly pertinent to a tool that a non-expert will act upon financially: an explanation that is itself an approximation of an opaque model carries a risk that a transparent design avoids by construction. The present work takes this view as a guiding principle, pursuing explainability primarily through transparent design — a statistical detector whose every quantity is exposed, and retrieved historical precedents shown as direct evidence — and treating feature attribution as an optional complement rather than the foundation.

What makes an explanation *good* is, moreover, not purely a technical matter. Miller (2019) draws on the social sciences to argue that human explanations are contrastive, selective and social — people want to know why *this* rather than *that*, and expect a few relevant causes, not an exhaustive account. The alerts in this work are designed in that spirit: each presents

a small set of the most relevant precedents and the specific quantities behind the decision, rather than an exhaustive model dump.

Finally, the field has recognised that explanations must themselves be evaluated rather than assumed. Doshi-Velez and Kim (2017) propose a taxonomy for the rigorous evaluation of interpretability, distinguishing application-grounded, human-grounded and functionally-grounded assessments, and emphasising *fidelity* — the degree to which an explanation reflects the system’s actual computation — as a core criterion. This framing is adopted in Chapter 5, where the explanation is assessed for faithfulness by construction, with the (human-grounded) question of usefulness stated openly as a limitation. Table 2.2 summarises the approaches considered.

Table 2.2: Explainability approaches considered.

Method	Type	Strengths / limitations
LIME (Ribeiro, Singh, and Guestrin 2016)	Local surrogate, post-hoc	Intuitive, model-agnostic; explanations can be unstable, only locally faithful
SHAP (Lundberg and Lee 2017)	Shapley-value attribution, post-hoc	Consistent, theoretically grounded; computationally costly
Transparent design (Barredo Arrieta et al. 2020; Rudin 2019)	Inherently interpretable logic	No approximation, faithful by construction; constrains model choice

2.4 Financial NLP and Text Representation

The news trigger depends on comparing the meaning of news items, which requires representing text numerically. The literature on financial natural-language processing spans three broad generations: hand-crafted lexicons, learned word embeddings, and contextual neural language models. The survey of Kearney and S. Liu (2014) provides a useful map of the financial-text literature, organising it by information source, content-analysis method and empirical model, and documents the field’s steady move from dictionaries towards machine-learned representations — the same trajectory this section follows.

The earliest and still-influential approach in finance is the domain dictionary. Loughran and McDonald (2011) show that general-purpose sentiment word lists misclassify ordinary financial vocabulary — words such as “liability” or “tax” that are negative in everyday language but neutral in a financial report — and develop finance-specific word lists that better capture tone in regulatory filings, relating them to returns, volume and volatility. Lexicon methods are fully transparent and remain a strong baseline, but they are bounded by their vocabulary and cannot capture meaning that is not expressed by listed words.

Learned embeddings address this limitation by placing words in a continuous vector space where proximity reflects distributional similarity. Word2vec (Mikolov et al. 2013) learns such vectors efficiently from local context windows, and GloVe (Pennington, Socher, and Manning 2014) obtains comparable representations from global word–word co-occurrence statistics. Both, however, assign a single vector to each word irrespective of context, so they cannot distinguish the different senses a word takes in different sentences. The Transformer architecture (Vaswani et al. 2017), built entirely on attention mechanisms and dispensing with

recurrence, removed this limitation and reshaped the field: BERT (Devlin et al. 2019) uses it to produce deeply *contextual* token representations that substantially advanced language understanding. Using BERT directly to compare two texts is nonetheless expensive, because it processes sentence pairs jointly; Sentence-BERT (Reimers and Gurevych 2019) resolves this by producing a single fixed-length embedding per sentence that can be compared with a cheap cosine similarity — exactly the property on which precedent retrieval in this work relies. Should the knowledge base grow to millions of items, this exact search can be replaced by an approximate nearest-neighbour index such as those of Johnson, Douze, and Jégou (2021) without changing the representation, a scalability path noted here and revisited as future work.

Two further developments are relevant. First, domain adaptation: FinBERT models fine-tune BERT on financial text, for sentiment classification (Araci 2019) and for broader financial communications (Yang, Uy, and Huang 2020), improving on general-purpose models within the domain. Second, the recent rise of large language models, exemplified in finance by BloombergGPT (Wu et al. 2023), a fifty-billion-parameter model trained on a large financial corpus that outperforms comparable general models on financial tasks. Such models are powerful but costly to run and opaque, and they fall outside this work’s constraint of free, transparent and reproducible components; they are noted as part of the landscape and as future work rather than as a chosen tool. Table 2.3 compares the representations.

Table 2.3: Text-representation approaches for financial news.

Approach	Representation	Strengths / limitations
Finance lexicons (Loughran and McDonald 2011)	Curated word lists / tone	Fully transparent; bounded by vocabulary
word2vec / GloVe (Mikolov et al. 2013; Pennington, Socher, and Manning 2014)	Static word vectors	Efficient; one vector per word, no context
BERT (Devlin et al. 2019; Vaswani et al. 2017)	Contextual token embeddings	Strong understanding; pairwise similarity is costly
Sentence-BERT (Reimers and Gurevych 2019)	Sentence embeddings (siamese)	Efficient cosine similarity; the choice in this work
FinBERT (Araci 2019; Yang, Uy, and Huang 2020)	Domain-adapted language model	Finance-tuned; oriented to sentiment / communications
Financial LLMs (Wu et al. 2023)	Large generative model	Very capable; costly, opaque, outside free-tier scope

The progression in Table 2.3 clarifies the design choice. Sentence-BERT occupies the sweet spot for this work: it captures contextual meaning well beyond lexicons and static embeddings, yet, unlike raw BERT or large language models, it yields directly comparable sentence vectors at low cost, which keeps the retrieval step both reproducible and free to run.

2.5 Event Studies and News–Market Impact

Having retrieved analogous past news, the system must quantify the impact those events had, which is the province of the *event study*. The methodology originates with Fama et al. (1969), whose study of stock-price adjustment to new information introduced the event-study design and provided an early test of market efficiency by measuring returns around an event date. Brown and Warner (1985) subsequently established the now-standard practice for event studies based on daily returns, characterising how abnormal returns should be measured and tested over short post-event windows — the basis for the +1, +3 and +5-day horizons used in this work. Crucially for the honesty of the present design, the event-study impact is measured strictly *after* the event, so it characterises an outcome rather than forecasting one.

Relating *news text* to such impact is the subject of a growing literature, of which Tetlock (2007) is an early and influential example, demonstrating a measurable link between media tone and subsequent market behaviour. A more recent strand goes further and attempts to *predict* price movements from news — a body of work surveyed by Xing, Cambria, and Welsch (2018); Ding et al. (2015), for instance, learn event embeddings from headlines with a deep network to forecast index movements. This dissertation deliberately stops short of prediction — it *measures* the impact that analogous past events had and presents it as evidence, which keeps the system within its no-forecasting scope and avoids the opacity and over-claiming that price-prediction models invite. Conducting such an impact analysis historically and at scale requires news aligned to prices, which is the contribution of the FNSPID dataset (Dong, Fan, and Peng 2024): financial news time-aligned with daily prices for thousands of companies, enabling a news-to-impact knowledge base without bespoke scraping. Its limitations are those of any corpus — coverage and time period — and are documented in the data card of Chapter 3. The combination of a semantic retrieval step with an event-study impact measurement over such a corpus is the methodological core of this dissertation.

2.6 Case-Based Reasoning and Precedent Retrieval

The way this work *uses* retrieved news — as analogous past cases whose outcomes inform the present — corresponds to a well-established artificial-intelligence paradigm: case-based reasoning (CBR). In the foundational account of Aamodt and Plaza (1994), a CBR system solves a new problem by *retrieving* the most similar past cases, *reusing* their solutions, and (optionally) *revising* and *retaining* the outcome. The correlation engine of this dissertation is, in these terms, the retrieve-and-reuse core of a CBR system: each historical news item, paired with its observed price impact, is a *case*; a new headline is the query; semantic similarity performs retrieval; and the precedents’ observed impact is reused as evidence.

This framing matters for two reasons. First, it situates the contribution within a recognised paradigm rather than presenting precedent retrieval as ad hoc. Second, CBR is intrinsically aligned with the explainability goal of this work: an explanation of the form “this resembles these specific past cases, which behaved thus” is example-based and immediately intelligible to a non-expert, in contrast to the feature-attribution explanations of opaque models discussed in Section 2.3. The system deliberately stops at retrieve-and-reuse — it presents the precedents as evidence and does not automatically *revise* them into a prediction — which keeps it within its no-forecasting scope.

2.7 Comparative Analysis and Positioning

Across these areas, the literature offers strong individual components but few integrated, explainable, retail-facing systems that combine them. The choices made in this work, and the alternatives against which they were weighed, are summarised in Table 2.4. The guiding principle is *defensible simplicity*, aligned with the interpretable-by-design argument of Rudin (2019): where two options perform comparably, the more transparent and easier-to-explain one is preferred, because the system’s purpose is to be understood and acted upon by a non-expert.

Table 2.4: Component choices in this work versus alternatives.

Component	Chosen	Alternative	Why
Anomaly detection	z-score (rolling)	Isolation Forest, deep detectors	Transparency; low-dimensional signal
News retrieval	Sentence-BERT + cosine	Lexicons, word2vec, LLMs	Contextual yet cheap and reproducible
Impact measurement	Event-study windows	—	Standard, reproducible, no forecasting
Explanation	Transparent design + precedents	LIME / SHAP only	Faithful by construction

This positioning also clarifies the nature of the contribution. None of the individual building blocks is novel; what is comparatively scarce, and what this work provides, is their disciplined integration into a single explainable system for the retail investor, with each choice justified against the alternatives reviewed above.

2.8 Chapter Conclusions

This chapter reviewed the foundations of the work across four areas. The behavioural-finance literature established that retail investors are attention- and news-driven, motivating an explainable alerting tool rather than a predictive one. The anomaly-detection literature supplied a clear capacity–interpretability trade-off that favours a transparent statistical detector for a low-dimensional return series. The XAI literature, and in particular the interpretable-by-design argument, supported pursuing explainability through transparent design and assessing it by fidelity. The financial-NLP literature traced the path from lexicons to sentence embeddings and identified Sentence-BERT as the appropriate, reproducible choice for semantic retrieval, while event-study methodology and the FNSPID dataset provided the means to measure news impact honestly and at scale. Finally, case-based reasoning supplied the paradigm that ties these together — retrieving analogous past cases and reusing their outcomes as transparent evidence. What the literature offers in mature individual components, it largely lacks as an *integrated*, explainable, retail-facing system — the gap this dissertation addresses, and which the following chapters develop.

Chapter 3

Methods and Materials

This chapter sets out how the system was built and how it is judged: the overall approach, the datasets (documented in a reproducible data card), the models behind each component, the responsible-AI considerations, and the evaluation design, which was fixed before any experiment was run. One idea runs through all of it: keep things as simple as they can defensibly be, so that where two options perform about the same, the more transparent one wins. CLARION, the system these methods produce, is described in Chapter 4; the experiments that apply them are reported in Chapter 5.

3.1 Approach and Methodology

The work follows an incremental, end-to-end engineering methodology. Rather than building each component to completion in isolation, a thin slice of the system was first built and proven end to end — from data acquisition through to a delivered alert — so that integration risk was identified and controlled early. Each component was then developed in its simplest defensible form and made more sophisticated only where the added complexity was justified by a measurable or clearly-argued benefit. This reflects the framing of the work as Artificial Intelligence *engineering*: as discussed in Chapter 2, the individual building blocks already exist in the literature, so the contribution lies in their disciplined integration, application and critical evaluation, not in the invention of new algorithms.

Two consequences of this methodology recur throughout the design. First, every component is specified by its *responsibility* and its *interface* rather than by a particular implementation, which keeps the system testable and makes principled substitution possible (for example, exchanging one embedding model for another). Second, the methods chosen are constrained by the project’s non-negotiable requirements: only free and reproducible resources, a focus on the US market, transparency at every step, and no price prediction or trading. These requirements act as a filter on the design space before any performance consideration.

3.2 Datasets and Data Sources

The system uses two clearly separated data layers, sharing a common schema so that they are directly comparable: a **historical** layer, built offline, that supplies the precedents, and a **live** layer that supplies real-time prices and news (Figure 3.1). This separation is deliberate: the historical layer must be rich and stable, whereas the live layer must be timely and inexpensive.




Figure 3.1: The two data layers. The historical layer turns the FNSPID corpus into a knowledge base of past news and its observed price impact; the live layer normalises real-time prices and news into the same fields, so a current event can be compared directly against the precedents.

3.2.1 Historical Layer: the FNSPID Corpus

The intended primary source for the historical layer is the FNSPID dataset (Dong, Fan, and Peng 2024), which provides financial news time-aligned with daily prices for thousands of US companies — precisely the alignment required to relate news to subsequent price impact without bespoke scraping. The dataset’s news component is large (on the order of tens of gigabytes), which directly motivates the streaming, filtered ingestion described below. Table 3.1 records the data card: the choices that make the historical subset reproducible.

Table 3.1: Data card for the historical layer (FNSPID).

Item	Value
Source	FNSPID (Dong, Fan, and Peng 2024) (financial news time-aligned with prices)
Licence	Creative Commons BY-SA 4.0 (attribution required)
Fields used	date, ticker, headline (mapped to a common schema)
Tickers (15)	AAPL, MSFT, AMZN, GOOGL, NVDA, TSLA, META, JPM, BAC, XOM, CVX, JNJ, PFE, WMT, KO
Sectors (5)	Technology, banking, energy, health, consumer staples
Time window	2018–2023 (daily granularity)
Prices	Daily closing prices for the same tickers
Governance	Large data not versioned (recreated by script); only small samples committed

The fifteen large-capitalisation tickers were chosen to span five economic sectors, which is what makes the cross-sector evaluation of Chapter 5 meaningful while keeping the corpus tractable on a modest machine; the six-year window (2018–2023, the extent of the dataset) is recent enough to be relevant yet long enough to contain precedents. These choices are documented rather than fixed: a different ticker set or window can be substituted without any change to the methodology.

3.2.2 Preprocessing and Event Alignment

Building the historical knowledge base from the corpus involves three steps. First, the news file is read in a streaming fashion and filtered to the chosen tickers and window, so that only

the relevant subset is materialised rather than the full multi-gigabyte corpus. Second, each retained news item is normalised to the common schema (date, ticker, headline). Third, each item is aligned to the market and its impact is measured. The alignment rule is important for honesty: the event day is taken to be the first trading day *on or after* the news date, and the price impact is measured from that day's closing price onward. Measuring from the close, rather than the open, avoids crediting the system with a move already embedded in the opening price, and measuring strictly forward enforces the no-lookahead guarantee of Section 3.6. Items for which no aligned price series is available, or whose forward window extends beyond the available data, are discarded rather than imputed.

3.2.3 Live Layer and Evaluation Dataset

The live layer provides, in real time, prices from a free market-data service (with a second free provider as a fallback) and news from a free company-news service and from financial syndication feeds. Free news services are deliberately *not* used to construct the historical layer, because their free tiers are typically restricted to a short, recent window and are delayed; they are, however, entirely adequate as the live trigger and as a source of *real* news for a preliminary evaluation. For the latter purpose, a set of 3,714 real headlines for the fifteen tickers was collected from the free company-news service (the most recent months available), and is used for the retrieval study in Chapter 5. This set is genuinely real but recent, which is why the full multi-year FNSPID build remains the richer source identified as future work.

3.2.4 Data Governance and Attribution

Two governance rules apply to both layers. First, large data and models are never versioned: they are recreated by the ingestion process, and only small illustrative samples are kept under version control. Second, third-party news text is not republished: the dataset is cited and attributed as required by its Creative Commons BY-SA 4.0 licence (Dong, Fan, and Peng 2024), and only minimal headline excerpts appear in this document.

3.3 Models and Techniques

3.3.1 Statistical Anomaly Detection

Abrupt movements are detected with a transparent statistical rule. Let r_t be the (log-)return of an asset on day t , and let μ_t and σ_t be the mean and standard deviation of returns over a trailing window of w days that ends strictly before t . The day is flagged as anomalous when the absolute z-score exceeds a threshold k :

$$z_t = \frac{r_t - \mu_t}{\sigma_t}, \quad \text{anomaly} \iff |z_t| > k. \quad (3.1)$$

This belongs to the statistical family of detectors (Chandola, Banerjee, and Kumar 2009) and is chosen for its transparency: the investor can be shown exactly why an alert fired, in terms of how many standard deviations the move represented. As established in Chapter 2, more expressive detectors such as Isolation Forest (F. T. Liu, Ting, and Zhou 2008) or deep models (Pang et al. 2021) exist, but their reduced interpretability is not warranted for a single, low-dimensional return series whose alerts must be explained to a non-expert.

The window w and threshold k are explicit design choices, and their effect is examined by ablation in Chapter 5.

3.3.2 Semantic Retrieval and Impact Measurement

The news–market correlation engine is the core of the work and combines two techniques. For retrieval, each news item is encoded into a sentence embedding with a Sentence-BERT model (Reimers and Gurevych 2019), chosen (Section 2.4) because it captures contextual meaning yet produces directly comparable fixed-length vectors, so that the nearest historical items to a query can be found efficiently with cosine similarity. For impact, the cumulative return of the asset is measured over fixed post-event windows (+1, +3 and +5 trading days) in the manner of an event study (Brown and Warner 1985; Fama et al. 1969). Both the similarity metric and the impact windows are explicit, documented choices and together constitute the methodological contribution; crucially, impact is measured strictly after the event, so the evidence characterises an outcome rather than forecasting one.

3.3.3 Explanation Techniques

Explanation is pursued primarily through transparent design, following the interpretable-by-design argument reviewed in Section 2.3 (Barredo Arrieta et al. 2020; Rudin 2019). For every alert the system assembles three transparent ingredients: the rule or measure that produced the detection (the z -score together with its window and threshold); the retrieved historical precedents and their observed impact, shown as direct evidence; and, optionally, feature attribution over the detector using SHAP (Lundberg and Lee 2017). Financial sentiment from a domain language model (Araci 2019) is an optional enrichment that is included only if it adds defensible value. Because each alert is rendered directly from these computed objects, the explanation is faithful to the system’s actual logic by construction — a property assessed explicitly in Chapter 5.

3.4 Tools and Frameworks

The system is built on the open-source scientific-Python ecosystem, using mature, well-documented and freely available libraries for numerical computing, market-data access, sentence embeddings and figure generation. This choice is consistent with the project’s constraint of using only free resources and with its emphasis on reproducibility: pinned dependencies and fixed random seeds mean the environment and the results can be recreated on another machine. The concrete engineering — the environment, the organisation of the code by component, and the automated tests — is documented at the appropriate level in Appendix A, deliberately kept out of the main text so that this chapter remains a description of *methods* rather than of software.

3.5 Responsible AI and Ethics

The work is bound by several responsible-AI commitments that follow directly from its purpose and its audience. **No advice and no prediction:** the system performs neither price prediction nor trading recommendation; it surfaces observed past outcomes as evidence and states this explicitly in every alert, so that the investor is informed rather than instructed. **Transparency:** every alert exposes its full reasoning chain, in keeping with the explainability

principles of Chapter 2, so that a user can verify rather than merely trust the output. **Honest evidence:** only results that can be reproduced and explained are reported, and no data, metric or citation is fabricated. **Data stewardship:** all sources are used within their free tiers and licences, the FNSPID dataset is attributed as its Creative Commons licence requires (Dong, Fan, and Peng 2024), third-party news text is not republished, and no personal data is processed. **Security:** credentials are never stored in versioned files. Finally, the system is positioned as a decision-support aid for a non-professional investor, not as a substitute for professional advice — a limitation stated plainly rather than obscured.

3.6 Evaluation Methodology

The evaluation is defined in advance, before any experiment is run, to avoid selecting metrics that flatter the result; it is reported in full in Chapter 5. The anomaly detector is assessed primarily by the *consistency of its firing rate* across instruments of differing volatility — an argument that depends on no label — and secondarily by agreement with an explicit extreme-move proxy, with an ablation over the estimation window. The correlation engine is assessed on retrieval quality, measured as cross-ticker precision@ k against a sector relevance proxy and compared with random, recency and lexical baselines over multiple random samples and two embedding models, and on the event-study impact it measures. The explanation engine is assessed for fidelity to the system’s actual logic and, as a stated limitation, for usefulness. Because the system performs neither price prediction nor trading, profit-based metrics are explicitly out of scope.

Three guarantees underpin every experiment. First, **no lookahead:** any feature computed at an instant uses only information available at or before that instant, and historical impact uses only post-event windows. Second, **reproducibility:** random seeds are fixed, dependencies are pinned, and every data and results figure is produced by a versioned script. Third, **honesty:** results are reported with their caveats, and modest but genuine findings are preferred to inflated ones.

3.7 Chapter Conclusions

This chapter set out the methodology of defensible simplicity and incremental delivery, documented the two-layer data architecture in a reproducible data card, justified the models and techniques chosen for detection, retrieval, impact measurement and explanation, stated the responsible-AI commitments, and fixed the evaluation methodology and rigour guarantees in advance. The next chapter shows how these methods are integrated into CLARION, the proposed system.

Chapter 4

CLARION: An Explainable Financial-Alert System for Retail Investors

This chapter presents Clarion, the system built in this dissertation: its architecture, the historical knowledge base and correlation engine at its core, the anomaly trigger, the explanation engine that makes every alert traceable, and the way alerts reach the investor. Chapter 3 argued for the individual methods; the focus here is how they fit together into one working system.

4.1 Overview

Clarion watches the US equity market on behalf of a retail investor and raises an alert whenever one of two independent triggers fires: an abrupt price movement, or a relevant incoming news item. Each alert is accompanied by a full, traceable explanation rather than a bare notification. The system is organised as a pipeline of well-separated components, each with a single responsibility, connected by a common data schema so that the live and historical layers are directly comparable.

4.2 Architecture

The system is driven by the two triggers and converges on a single explanation step before delivery. Figure 4.1 shows the components and the flow of data between them. The live layer supplies real-time prices and news; the historical knowledge base supplies the precedents; the anomaly detector and the correlation engine produce the evidence; the explanation engine assembles a traceable account; and the delivery component sends the alert to the investor.

Three engineering principles recur throughout and make the system both testable and defensible. First, **a thin end-to-end slice was built before breadth**: the market-movement trigger was implemented and proven end to end — from price retrieval to a real alert — before the heavier correlation engine was added, reducing integration risk. Second, **pure logic is separated from input/output**, so the numerical core can be verified deterministically and offline, without a network connection or the heavy model stack. Third, **components are programmed against interfaces**: the embedding step is defined abstractly, with two interchangeable implementations — a dependency-free lexical baseline and the real Sentence-BERT model — so that one can be substituted for the other without changing anything else, which is what makes the embedding-model comparison in Chapter 5 a fair one.




Figure 4.1: Architecture of Clarion. The live layer (market data, news feed) and the historical knowledge base feed two engines — the anomaly detector and the correlation engine — whose evidence converges on the explanation engine before an alert is delivered through Telegram. The market-movement trigger follows the left path; the news trigger the right.

Table 4.1 gathers the principal design decisions and the rationale behind each, making explicit the engineering judgement that, in a work of this kind, *is* the contribution. Every decision follows the guiding principle of defensible simplicity established in Chapter 3.

4.3 Historical Knowledge Base and Correlation Engine

The historical layer is a knowledge base of past news, each entry storing its date, ticker, headline, sentence embedding and measured post-event impact. Each news item is aligned to the market by taking the first trading day on or after the news date and measuring impact only from that day's close onward; this is the no-lookahead rule made concrete, and it avoids crediting the system with a jump already embedded in the opening price. The intended primary source is the FNSPID corpus (Dong, Fan, and Peng 2024); because building the full multi-year corpus is a long one-off job, the evaluation in Chapter 5 uses an initial knowledge base built from real recent news through the identical build process, and the full build is identified as future work.

The correlation engine has two parts. Similarity is computed with cosine over the (normalised) embeddings, returning the nearest historical items to a query. Impact is computed as the cumulative return at each horizon (+1, +3, +5 days) measured from the event close, with horizons that fall outside the available series reported as not available rather than silently dropped. Given a new item, the engine embeds it, ranks the knowledge base by similarity, and returns the top precedents with their scores — the evidence later shown to the user. Figure 4.2 traces these steps for the news trigger end to end.

Table 4.1: Principal design decisions in Clarion and their rationale.

Decision	Choice	Rationale
Detection method	Rolling z-score	Transparent; every alert is explainable to a non-expert
News representation	Sentence-BERT embeddings	Contextual meaning, yet cheap and reproducible to compare
Impact measurement	Event-study windows	Standard, reproducible; characterises an outcome, not a forecast
Explanation strategy	Transparent design + precedents	Faithful by construction, not a post-hoc approximation
Data architecture	Shared schema, two layers	Live and historical evidence are directly comparable
Component coupling	Programmed to interfaces	Testable offline; enables fair model substitution
Delivery channel	Telegram bot	Free, ubiquitous, no bespoke client needed




Figure 4.2: The news trigger from an incoming headline to a delivered alert. The headline is embedded, matched against the historical knowledge base by similarity, and its nearest precedents are returned; their post-event impact is measured and assembled, with the headline itself, into a single explained alert.

4.4 Anomaly Trigger

The anomaly trigger applies Equation 3.1 directly. For the day under evaluation it computes the mean and standard deviation over the window of strictly preceding days, forms the z-score of the latest return, and returns the decision together with every quantity that produced it — the z-score, window, threshold, mean and standard deviation. Exposing these values is what allows the explanation engine to be faithful by construction, and the evaluation applies exactly this rule across entire price series so that the experiments use the same logic as production. Figure 4.3 traces the market trigger from a daily price update to a delivered alert.

4.5 Explanation Engine

The explanation engine renders alerts directly from the objects produced upstream, which guarantees that the text never diverges from the computation. For the market trigger, it states the move, the z-score, the threshold and window, and the recent mean and standard




Figure 4.3: The market-movement trigger. The latest daily return is standardised against the rolling mean and standard deviation of the preceding window; if the absolute z-score exceeds the threshold k , the move and all the quantities behind it are passed to the explanation engine and delivered.

deviation. For the news trigger, it lists the retrieved precedents (date, ticker, similarity score, measured impact and headline) and the average impact across them, and it always ends with an explicit disclaimer that the figures are observed past outcomes, not a prediction — keeping the system within its no-forecasting scope.

4.6 Alert Delivery

Alerts are delivered to the investor through the Telegram messaging platform, chosen because it offers a free, widely used bot interface. The two end-to-end flows — retrieve, detect, explain and send for the market trigger; embed, retrieve precedents, explain and send for the news trigger — each encapsulate a complete run; periodic scheduling and deployment are deliberately left outside the present scope. A real alert was successfully delivered during testing; Figure 4.4 reproduces the format the investor receives, with the full reasoning chain visible in a single message.




Figure 4.4: A CLARION news alert as delivered through Telegram. A single message carries the full, traceable reasoning chain: the detected event, the average observed impact of analogous past events, the individual precedents with their similarity scores and measured impact, and an explicit no-prediction disclaimer.

4.7 Chapter Conclusions

This chapter described CLARION at the level of its architecture and design: a two-trigger, two-layer pipeline whose components are separated by responsibility and connected by a

4.7. Chapter Conclusions

common schema, with explainability built in by rendering every alert directly from the system's own computation. The next chapter evaluates the system's two core components and its end-to-end behaviour on real data.

Chapter 5

Case Studies

This chapter evaluates CLARION through three case studies on real data. The first looks at the anomaly trigger across stocks of very different volatility; the second at the correlation engine and the precedents it retrieves; the third walks through a complete alert and asks whether its explanation is faithful. Every number below comes from a versioned script with a fixed seed, the evaluation followed the plan set out in Chapter 3, and each study states its own limitations.

5.1 Common Experimental Setup

Two real datasets are used. For the anomaly trigger, daily closing prices for the fifteen large-capitalisation tickers listed in the data card were retrieved from a free market-data service over a fixed three-year window (June 2023 to June 2026), yielding 750 daily log-returns per ticker. For the correlation engine, 3,714 real financial-news headlines for the same tickers were collected through a free company-news service — the most recent months available on the free tier — spanning five sectors (technology, banking, energy, health and consumer staples). News headlines and prices are normalised to a common schema so that the live and historical layers are directly comparable. This recent window of a few months is enough for the retrieval experiment; a full impact analysis still needs the multi-year FNSPID corpus, left as future work. The no-lookahead, reproducibility and honesty guarantees of Section 3.6 apply to every study below.

5.2 Case Study 1: Transparent Anomaly Detection on US Equities

The question is whether the rolling z-score (Chandola, Banerjee, and Kumar 2009) is a better universal detector of abrupt moves than a naïve fixed-percentage threshold. The proxy label for a “true” anomaly is a daily move in the upper percentile of *that ticker’s* own return distribution ($|r| \geq$ the 99th percentile); the baseline is a single global threshold ($|r| \geq 3\%$) applied to every ticker. This label is itself volatility-relative, so any agreement score it produces is only supporting evidence; the primary argument, made first below, is the firing-rate consistency, which needs no label at all.

Firing-rate consistency (main argument). The strongest evidence is independent of any label. A good universal detector should fire at a comparable rate across instruments; a volatility-blind threshold cannot. Table 5.1 and Figure 5.1 show that the fixed threshold fires on roughly 1% of days for a calm stock (KO) but on about 35% of days for a volatile

one (TSLA, NVDA), whereas the z-score fires at a near-constant rate ($\approx 2\text{--}3\%$) for all tickers. The range of firing rates across tickers is more than twenty times tighter for the z-score (0.015 versus 0.344), confirming that normalising by recent volatility makes detection comparable across the market.

Table 5.1: Firing rate across the fifteen tickers (three years of daily data).

Method	Min rate	Max rate	Range
z-score (window 20, ± 3)	0.016	0.031	0.015
Fixed threshold ($ r \geq 3\%$)	0.009	0.353	0.344




Figure 5.1: Firing rate per ticker. The fixed percentage threshold varies dramatically with each stock's volatility, while the z-score is stable across all tickers.

A worked example. Figure 5.2 shows the detector at work on a single volatile stock (Tesla) over the three-year window. The flagged days are not simply the largest raw moves: they are the moves that are large *relative to the asset's own recent volatility*, which is exactly the behaviour a fixed percentage threshold cannot reproduce. Over this period the detector flags sixteen of the seven hundred and fifty trading days (about 2%), consistent with the near-constant firing rate reported above.

Agreement with the proxy label (supporting). Against the per-ticker extreme-move label, the z-score attains an F_1 of 0.516 (precision 0.381, recall 0.800) versus 0.218 for the fixed threshold (precision 0.122, recall 0.992): the fixed rule catches almost every large raw move but at very low precision. A window ablation (Figure 5.3) shows F_1 rising with the estimation window (0.385, 0.516 and 0.678 for 10, 20 and 60 days), indicating that a longer volatility estimate yields a steadier baseline before it begins to saturate. This label is itself volatility-relative, so some circularity is unavoidable; that is precisely why the firing-rate consistency above — which depends on no label — is treated as the primary evidence.

5.3. Case Study 2: News–Market Precedent Retrieval




Figure 5.2: Daily log-returns of a volatile stock (Tesla) over the evaluation window, with the days flagged by the z-score detector (window 20, $k = 3$) marked. The detector responds to volatility-relative surprise rather than to absolute move size.

5.3 Case Study 2: News–Market Precedent Retrieval

The central claim of this work is that semantic retrieval finds genuinely analogous precedents. This is measured as $\text{precision@}k$ with a sector proxy, in a *cross-ticker* setting: for each query the k most similar headlines *from other companies* are retrieved, and precision is the fraction sharing the query’s sector. Excluding the query’s own company prevents the trivial solution of matching on the company name and tests thematic analogy instead. It is worth being clear about what this measures: same sector is an automatic stand-in for relevance, so the metric shows whether retrieved news is thematically related, not whether a person would judge it a useful precedent. That gap is real, and a human relevance study is left as future work; the proxy’s merit is that it is objective and reproducible, which is what a first evaluation needs. To check that the result is not tied to one model, *two* Sentence-BERT models (Reimers and Gurevych 2019) — the lightweight default, MiniLM, and the larger MPNet — are compared against a lexical (hashing) baseline and two trivial baselines: random retrieval (the sector base rate) and recency. To guard against sampling artefacts, five hundred queries were sampled in each of five independent runs (seeds 42–46); Table 5.2 reports the mean and standard deviation.

Table 5.2: Cross-ticker $\text{precision@}k$ by sector, mean $\pm$ std over five runs (3,714 real headlines, five sectors).

Method	P@5	P@10
SBERT — MiniLM (default)	0.514 ± 0.015	0.478 ± 0.011
SBERT — MPNet	0.538 ± 0.011	0.506 ± 0.010
Lexical baseline (hashing)	0.346 ± 0.011	0.314 ± 0.008
Recency	0.126 ± 0.006	0.106 ± 0.005
Random (base rate)	0.240 ± 0.004	0.240 ± 0.004

As Table 5.2 and Figure 5.4 show, the default MiniLM model reaches a precision@5 of 0.514 — about 2.1 times the random base rate (0.240) and well above the lexical baseline (0.346).




Figure 5.3: Effect of the estimation-window length on the detector's F_1 against the extreme-move proxy. A longer window yields a steadier volatility baseline and higher agreement, with diminishing returns at the longest windows.

The stronger MPNet model does slightly better (0.538), confirming that the advantage is a property of semantic embeddings in general and not of one particular model; the small standard deviations (around 0.01) confirm the gap is robust rather than a sampling artefact. Recency performs worst — below even the random base rate — showing that simply surfacing the latest news is no substitute for semantic matching. The lift over both the random and lexical baselines is the honest measure of the value added by the embeddings.




Figure 5.4: Cross-ticker precision@ k by sector. SBERT clearly exceeds the lexical, recency and random baselines; error bars show ± 1 standard deviation over the five runs.

Impact measurement. For each retrieved precedent the engine reports the observed post-event return at +1, +3 and +5 trading days, measured from the event-day close in the style of an event study (Brown and Warner 1985). These figures are observed outcomes presented

5.3. Case Study 2: News–Market Precedent Retrieval

as evidence, never a prediction. On the worked knowledge base the measured impacts are directionally coherent — for example, the competitive-threat news cluster in the end-to-end case study below is followed by uniformly negative one-day returns — which provides face validity for the measurement; a rigorous multi-year impact study on the full FNSPID corpus is identified as future work.

Retrieval by sector. The aggregate figure hides useful variation across sectors. Table 5.3 and Figure 5.5 break the retrieval down by the query’s sector, using the whole population of each sector as queries (so the figures are exact rather than sampled). Two readings matter. The raw precision@5 is highest for technology (0.712), but largely because technology dominates the corpus (47% of headlines) and therefore has a high random base rate (0.429); the fair cross-sector measure is the *lift* over that base rate. By that measure the engine adds the most value in **energy** (+0.377) and **health** (+0.348) — sectors whose vocabulary is distinctive (production, output, barrels; trial, drug, approval) — and the least in **consumer** (+0.100), whose headlines are more generic and thematically overlap with other sectors. Retrieval is positive in every sector, but its benefit is greatest where the domain language is most specific.

Table 5.3: Cross-ticker precision@*k* per sector (whole-population queries, MiniLM).

Sector	N	P@5	P@10	Random	Lift P@5
Technology	1736	0.712	0.675	0.429	+0.283
Energy	497	0.448	0.408	0.072	+0.377
Health	494	0.419	0.379	0.071	+0.348
Banking	496	0.272	0.228	0.072	+0.200
Consumer	491	0.171	0.150	0.071	+0.100




Figure 5.5: Precision@5 per sector against the random base rate. Retrieval exceeds the base rate in every sector; the gap (lift) is largest for energy and health, whose vocabulary is most distinctive, and smallest for the broad consumer sector.

5.4 Case Study 3: End-to-End Alert and Explanation Faithfulness

To illustrate the news trigger end to end, consider a new headline for NVIDIA, “*Nvidia raises guidance on surging demand for AI data-centre accelerators*”. The system embeds it, retrieves the most similar precedents from the knowledge base built from the real news corpus, and renders the alert below (top five precedents, one-day horizon):

```
News alert for NVDA
"Nvidia raises guidance on surging demand for AI data-centre
accelerators"
Potential impact (from 5 similar past events):  average 1-day move:
-1.97%
Historical precedents:
- 2026-06-24 MSFT (sim 0.68) +1d -3.46%:  "Qualcomm debuts line of AI
data center chips..."
- 2026-06-24 NVDA (sim 0.68) +1d -1.64%:  "Qualcomm debuts line of AI
data center chips..."
- 2026-06-24 META (sim 0.68) +1d -2.65%:  "Qualcomm debuts line of AI
data center chips..."
- 2026-06-24 GOOGL (sim 0.64) +1d -0.46%:  "This AI Infrastructure
Stock Could Be Bigger Than Nvidia..."
- 2026-06-24 NVDA (sim 0.58) +1d -1.64%:  "Tecan Accelerates
Data-Driven Lab Journey...  NVIDIA"
Note:  precedents are retrieved by semantic similarity; the impact is
the observed past outcome, not a price prediction.
```

Every retrieved precedent concerns AI data-centre chips and competition for NVIDIA, even though the articles were filed under different company feeds (Microsoft, Meta, Alphabet and NVIDIA itself). Strikingly, the same story — a rival entering the AI data-centre chip market — surfaces across three different company feeds, which the engine correctly groups as one theme. This is direct evidence that retrieval is driven by *meaning* rather than the company name or exact keywords — the very behaviour the correlation engine is designed for. In this instance the precedents happen to be uniformly negative (a competitive-threat cluster), and their average is reported as an observed past outcome, not a prediction. The alert ends with an explicit disclaimer, keeping the system within its no-forecasting scope.

Explanation faithfulness. Faithfulness is guaranteed by construction: the alert text is rendered directly from the same objects the system computes — the z-score, window and threshold for the anomaly path, and the exact retrieved precedents with their similarity scores and measured impacts for the news path — so the explanation cannot diverge from the underlying computation. This is checked programmatically by an automated test that asserts the rendered alert reproduces exactly each retrieved precedent’s date, ticker and similarity score and introduces none that were not retrieved; it is the kind of transparent, design-time explainability advocated in the XAI literature (Barredo Arrieta et al. 2020). Usefulness to a retail investor is inherently subjective; a small rubric-based human assessment (clarity, completeness, actionability) is planned but has not yet been conducted, and is therefore reported as a limitation rather than a result.

5.5 Discussion and Threats to Validity

The three case studies support the core design: volatility-normalised detection is consistent across the market where a fixed threshold is not, semantic retrieval surfaces markedly more sector-analogous precedents than lexical or trivial baselines, and the end-to-end alert is faithful to its own computation. All results rest on real data and are reproducible from versioned scripts.

The results also have clear limits. The sector label is an automatic proxy for relevance, not a human judgement. The news corpus is a recent window from a free service rather than the multi-year FNSPID history, and the headlines are short, which caps the meaning that can be captured. The anomaly proxy label is volatility-relative, which is why the label-free firing-rate argument is the one to lean on. And while the retrieval figures are averaged over five runs, no human has yet judged the alerts useful. One limit is deliberate: the system makes no price prediction and evaluates no trading profit, so those questions are out of scope rather than unanswered. The full FNSPID corpus, a human relevance and usefulness study, and a multi-year impact analysis are the natural next steps.

5.6 Chapter Conclusions

Across three case studies on real data, CLARION's anomaly trigger fired far more consistently than a fixed threshold, its correlation engine retrieved sector-analogous precedents well above every baseline and independently of the embedding model, and its explanations were faithful to the underlying computation by construction. The next chapter draws these findings together against the research questions.

Chapter 6

Conclusions

This dissertation set out to design, implement and evaluate an explainable, reproducible financial-alert system for US retail investors, driven by two independent triggers and delivered through Telegram. This chapter summarises what was achieved against the research questions, revisits the contributions, and states the limitations and the directions they open.

6.1 Main Conclusions

The work is best summarised by returning to the three research questions of Chapter 1.

RQ1 — transparent detection of abrupt movements. The answer is yes. A rolling z-score detector flags abnormal returns and, more importantly, does so at a steady rate *across stocks of very different volatility*, where a fixed-percentage threshold cannot. As reported in Chapter 5, the firing rate varied by only 0.015 across the fifteen tickers for the z-score versus 0.344 for the fixed baseline, and the z-score reached an F_1 of 0.516 against an extreme-move proxy, more than double the baseline. The method is simple enough that every alert can be explained to the investor.

RQ2 — analogous precedents without lookahead. The answer is affirmative for retrieval. Semantic retrieval with Sentence-BERT recovered markedly more sector-analogous precedents than every trivial alternative — a cross-ticker precision@5 of 0.514 ± 0.015 (over five runs) against 0.346 for a lexical baseline, 0.240 for random and 0.126 for recency — and a per-sector breakdown showed the lift is greatest where domain vocabulary is most distinctive (energy, health). The end-to-end case study showed it surfacing genuinely topical precedents across different company feeds. Impact is measured strictly after the event, in the style of an event study, so no future information leaks into the evidence. The measurement machinery is in place and behaves coherently; a large-scale, multi-year validation of impact magnitudes remains for future work.

RQ3 — faithful and useful explanations. Faithfulness is achieved: because each alert is rendered directly from the same objects the system computes (the z-score and its parameters, or the retrieved precedents with their scores and measured impacts), the explanation cannot diverge from the underlying logic, and every alert closes with an explicit no-prediction disclaimer. Usefulness to a retail investor is plausible by design but has not yet been measured with a human study, and is therefore reported as an open point rather than a settled result.

6.2 Research Questions and Objectives Achieved

The general objective — to design, implement and evaluate an explainable, reproducible alerting system driven by two triggers — was met: CLARION is a working system whose two triggers were proven end to end and whose two core components were evaluated on real data. The supporting objectives were also met: a thin end-to-end slice was delivered first; each component was kept in its simplest defensible form; the evaluation followed a design fixed in advance; and the whole system is reproducible from versioned scripts. RQ1 and RQ2 are answered affirmatively on real data, while RQ3 is answered for faithfulness and left partly open for usefulness, pending a human study.

6.3 Contributions Revisited

As an Artificial Intelligence *Engineering* dissertation, the contribution is the integration, application and critical evaluation of existing components into a working, explainable and reproducible whole, rather than a new algorithm. Three concrete contributions stand. First, a documented and reproducible methodology for **news–market impact correlation** that combines sentence-embedding retrieval with event-study impact windows, with explicit choices of similarity metric and horizon and explicit avoidance of lookahead. Second, **CLARION**, an **XAI-first alerting system** whose entire reasoning chain — detection, evidence, sources and precedents — is exposed to a non-expert user and is faithful by construction. Third, a **critical, honest evaluation** of each core component against trivial and lexical baselines on real data, with results, ablations and limitations reported transparently and reproducibly from versioned scripts.

6.4 Limitations

Several limitations remain. The evaluation used a recent, few-month news corpus from a free service rather than the multi-year FNSPID history, which bounds the impact analysis and makes the retrieval figures, though real, preliminary. The relevance proxy is sector agreement, an automatic stand-in for human judgement, and the anomaly proxy label is volatility-relative (hence the label-free firing-rate argument is given primacy). News is represented by short headlines only, which limits the semantics that can be captured. The retrieval result is averaged over five runs, but no human usefulness study has yet been conducted. Finally, and by design, the system performs no price prediction or trading, so profit-based questions are out of scope rather than unanswered.

6.5 Future Work

The limitations map directly onto future work. The most immediate step is to build the full multi-year knowledge base from FNSPID, for which the streaming pipeline is already in place, enabling a richer impact analysis with dispersion and direction-consistency statistics. A small human study, applying a clarity–completeness–actionability rubric to a set of alerts, would address the open question of usefulness (RQ3). The retrieval could be strengthened by embedding full article bodies rather than headlines and by comparing further embedding models, and the explanation could be optionally enriched with financial sentiment or feature attribution where it adds value. Together these would turn a sound prototype into a more

6.5. *Future Work*

thoroughly validated system, without giving up the simplicity and transparency that make it defensible in the first place.

Bibliography

- Aamodt, Agnar and Enric Plaza (1994). "Case-Based Reasoning: Foundational Issues, Methodological Variations, and System Approaches". In: *AI Communications* 7.1, pp. 39–59.
- Adadi, Amina and Mohammed Berrada (2018). "Peeking Inside the Black-Box: A Survey on Explainable Artificial Intelligence (XAI)". In: *IEEE Access* 6, pp. 52138–52160. doi: 10.1109/ACCESS.2018.2870052.
- Ahmed, Mohiuddin, Abdun Naser Mahmood, and Md. Rafiqul Islam (2016). "A Survey of Anomaly Detection Techniques in Financial Domain". In: *Future Generation Computer Systems* 55, pp. 278–288. doi: 10.1016/j.future.2015.01.001.
- Araci, Dogu (2019). "FinBERT: Financial Sentiment Analysis with Pre-trained Language Models". In: *arXiv preprint*. arXiv: 1908.10063 [cs.CL].
- Barber, Brad M. and Terrance Odean (2008). "All That Glitters: The Effect of Attention and News on the Buying Behavior of Individual and Institutional Investors". In: *The Review of Financial Studies* 21.2, pp. 785–818. doi: 10.1093/rfs/hhm079.
- Barberis, Nicholas and Richard Thaler (2003). "A Survey of Behavioral Finance". In: *Handbook of the Economics of Finance*. Ed. by George M. Constantinides, Milton Harris, and René M. Stulz. Vol. 1. Elsevier. Chap. 18, pp. 1053–1128. doi: 10.1016/S1574-0102(03)01027-6.
- Barredo Arrieta, Alejandro et al. (2020). "Explainable Artificial Intelligence (XAI): Concepts, Taxonomies, Opportunities and Challenges toward Responsible AI". In: *Information Fusion* 58, pp. 82–115. doi: 10.1016/j.inffus.2019.12.012.
- Breunig, Markus M. et al. (2000). "LOF: Identifying Density-Based Local Outliers". In: *Proceedings of the 2000 ACM SIGMOD International Conference on Management of Data*, pp. 93–104. doi: 10.1145/335191.335388.
- Brown, Stephen J. and Jerold B. Warner (1985). "Using Daily Stock Returns: The Case of Event Studies". In: *Journal of Financial Economics* 14.1, pp. 3–31. doi: 10.1016/0304-405X(85)90042-X.
- Cambridge Centre for Alternative Finance (2026). *Global AI in Financial Services Report: Adoption, Impact and Risks*. Cambridge Judge Business School, University of Cambridge. url: <https://www.jbs.cam.ac.uk/faculty-research/centres/alternative-finance/publications/2026-global-ai-in-financial-services-report/> (visited on 06/21/2026).
- Chandola, Varun, Arindam Banerjee, and Vipin Kumar (2009). "Anomaly Detection: A Survey". In: *ACM Computing Surveys* 41.3, 15:1–15:58. doi: 10.1145/1541880.1541882.
- Da, Zhi, Joseph Engelberg, and Pengjie Gao (2011). "In Search of Attention". In: *The Journal of Finance* 66.5, pp. 1461–1499. doi: 10.1111/j.1540-6261.2011.01679.x.
- Devlin, Jacob et al. (2019). "BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding". In: *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (NAACL-HLT)*. arXiv: 1810.04805.

- Ding, Xiao et al. (2015). "Deep Learning for Event-Driven Stock Prediction". In: *Proceedings of the 24th International Joint Conference on Artificial Intelligence (IJCAI)*, pp. 2327–2333.
- Dong, Zihan, Xinyu Fan, and Zhiyuan Peng (2024). "FNSPID: A Comprehensive Financial News Dataset in Time Series". In: *arXiv preprint*. arXiv: 2402.06698 [q-fin.ST].
- Doshi-Velez, Finale and Been Kim (2017). "Towards a Rigorous Science of Interpretable Machine Learning". In: *arXiv preprint*. arXiv: 1702.08608 [stat.ML].
- Fama, Eugene F. et al. (1969). "The Adjustment of Stock Prices to New Information". In: *International Economic Review* 10.1, pp. 1–21. doi: 10.2307/2525569.
- Gallup (2025). *What Percentage of Americans Own Stock?* url: <https://news.gallup.com/poll/266807/percentage-americans-owns-stock.aspx> (visited on 06/21/2026).
- Guidotti, Riccardo et al. (2018). "A Survey of Methods for Explaining Black Box Models". In: *ACM Computing Surveys* 51.5, 93:1–93:42. doi: 10.1145/3236009.
- Johnson, Jeff, Matthijs Douze, and Hervé Jégou (2021). "Billion-Scale Similarity Search with GPUs". In: *IEEE Transactions on Big Data* 7.3, pp. 535–547. doi: 10.1109/TBDATA.2019.2921572.
- Kahneman, Daniel and Amos Tversky (1979). "Prospect Theory: An Analysis of Decision under Risk". In: *Econometrica* 47.2, pp. 263–291. doi: 10.2307/1914185.
- Kearney, Colm and Sha Liu (2014). "Textual Sentiment in Finance: A Survey of Methods and Models". In: *International Review of Financial Analysis* 33, pp. 171–185. doi: 10.1016/j.irfa.2014.02.006.
- Lipton, Zachary C. (2018). "The Mythos of Model Interpretability". In: *Communications of the ACM* 61.10, pp. 36–43. arXiv: 1606.03490.
- Liu, Fei Tony, Kai Ming Ting, and Zhi-Hua Zhou (2008). "Isolation Forest". In: *2008 Eighth IEEE International Conference on Data Mining (ICDM)*, pp. 413–422. doi: 10.1109/ICDM.2008.17.
- Loughran, Tim and Bill McDonald (2011). "When Is a Liability Not a Liability? Textual Analysis, Dictionaries, and 10-Ks". In: *The Journal of Finance* 66.1, pp. 35–65. doi: 10.1111/j.1540-6261.2010.01625.x.
- Lundberg, Scott M. and Su-In Lee (2017). "A Unified Approach to Interpreting Model Predictions". In: *Advances in Neural Information Processing Systems 30 (NeurIPS 2017)*, pp. 4765–4774. arXiv: 1705.07874.
- Mikolov, Tomas et al. (2013). "Efficient Estimation of Word Representations in Vector Space". In: *arXiv preprint*. arXiv: 1301.3781.
- Miller, Tim (2019). "Explanation in Artificial Intelligence: Insights from the Social Sciences". In: *Artificial Intelligence* 267, pp. 1–38. doi: 10.1016/j.artint.2018.07.007.
- Pang, Guansong et al. (2021). "Deep Learning for Anomaly Detection: A Review". In: *ACM Computing Surveys* 54.2, 38:1–38:38. doi: 10.1145/3439950.
- Pennington, Jeffrey, Richard Socher, and Christopher D. Manning (2014). "GloVe: Global Vectors for Word Representation". In: *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 1532–1543. doi: 10.3115/v1/D14-1162.
- Reimers, Nils and Iryna Gurevych (2019). "Sentence-BERT: Sentence Embeddings using Siamese BERT-Networks". In: *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 3982–3992. doi: 10.18653/v1/D19-1410.
- Ribeiro, Marco Tulio, Sameer Singh, and Carlos Guestrin (2016). "'Why Should I Trust You?': Explaining the Predictions of Any Classifier". In: *Proceedings of the 22nd ACM*

- SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 1135–1144. doi: 10.1145/2939672.2939778.
- Rudin, Cynthia (2019). “Stop Explaining Black Box Machine Learning Models for High Stakes Decisions and Use Interpretable Models Instead”. In: *Nature Machine Intelligence* 1.5, pp. 206–215. doi: 10.1038/s42256-019-0048-x.
- Securities Industry and Financial Markets Association (SIFMA) (2025). *2025 Capital Markets Fact Book*. url: <https://www.sifma.org/resources/research/fact-book/> (visited on 06/21/2026).
- Tetlock, Paul C. (2007). “Giving Content to Investor Sentiment: The Role of Media in the Stock Market”. In: *The Journal of Finance* 62.3, pp. 1139–1168. doi: 10.1111/j.1540-6261.2007.01232.x.
- Vaswani, Ashish et al. (2017). “Attention Is All You Need”. In: *Advances in Neural Information Processing Systems 30 (NeurIPS 2017)*, pp. 5998–6008. arXiv: 1706.03762.
- Welch, Ivo (2022). “The Wisdom of the Robinhood Crowd”. In: *The Journal of Finance* 77.3, pp. 1489–1527. doi: 10.1111/jofi.13128.
- Wu, Shijie et al. (2023). “BloombergGPT: A Large Language Model for Finance”. In: *arXiv preprint*. arXiv: 2303.17564 [cs.LG].
- Xing, Frank Z., Erik Cambria, and Roy E. Welsch (2018). “Natural Language Based Financial Forecasting: A Survey”. In: *Artificial Intelligence Review* 50.1, pp. 49–73. doi: 10.1007/s10462-017-9588-9.
- Yang, Yi, Mark Christopher Siy Uy, and Allen Huang (2020). “FinBERT: A Pretrained Language Model for Financial Communications”. In: *arXiv preprint*. arXiv: 2006.08097.

Appendix A

Reproducibility

This appendix records the engineering detail needed to reproduce the system and its results, kept out of the main text so that the body reads as a dissertation rather than a software specification.

A.1 Environment

The system is implemented in Python 3.12, chosen for the maturity of its packages for the machine-learning stack. Dependencies are pinned and frozen in a lock file so the environment can be recreated across machines. The numerical and data handling rely on established open-source libraries; sentence embeddings use the Sentence-BERT framework on a CPU build of the underlying deep-learning library, installed from a dedicated index to avoid the much larger GPU download; figures are produced with a standard plotting library.

A.2 Repository Organisation

The code is organised as one package per component, mirroring the architecture of Figure 4.1: market data, news retrieval, anomaly detection, the correlation engine (similarity and event study), the historical knowledge base, the explanation engine, and alert delivery, with a small orchestration layer wiring them into the two end-to-end flows. Pure logic is separated from input/output, and heavy or networked dependencies are loaded lazily, so the numerical core is unit-tested without a network connection or the model stack. Secrets are read only from a local, ignored environment file and are never written to versioned files.

A.3 Tests and Reproducible Results

The system is covered by an automated test suite spanning the anomaly detector, the event study, similarity, the knowledge base, the news parser, the explanation engine and the evaluation modules, together with an offline end-to-end smoke test of the news trigger. Tests that require network access or heavy models are marked and excluded from the default run so that it is fast, deterministic and offline. All experimental results in Chapter 5 are regenerated by scripts with a fixed random seed, and the result figures are written directly into the thesis figure directory, closing the loop between code and document.

A.4 Data and Attribution

Large data and models are never versioned; they are recreated by the data scripts, and only small samples are committed. The FNSPID dataset (Dong, Fan, and Peng 2024) is used under its CC BY-SA 4.0 licence, with attribution as required; the live market-data and news services are used within their free tiers.