

YALOVA UNIVERSITY



Android Programming with Huawei Mobile Services


Berk Ozyurt Mehmet Yozgatli Cengiz Toru

W7: ANDROID

CONTENT

- Menus
- Fragments
- Navigation Component
- VCS

https://github.com/HSDTurkey/UserListMVVMRetrofit.git






Menus in Android

https://material.io/components/menus/android


https://developer.android.com/guide/topics/ui/menus

https://medium.com/@tomerpacific/an-introduction-to-android-menus-c9f382264b49

https://medium.com/@androidcookies1/menu-types-in-android-with-tutorial-4ebd402ebf83



Context Menu



Option 1
Option 2
Option 3

Popup Menu

Let's Create an Options Menu

STEPS

- Create a menu folder
- Create a menu file to hold menu items
- ✓ Inflate the menu
- ✓ Handle the menu items click action

× Menus

X Menus
Option 1
Option 2
Option 3



Fragments

https://developer.android.com/guide/fragments


https://www.geeksforgeeks.org/difference-between-a-fragment-and-an-activity-in-android/

https://oozou.com/blog/reasons-to-use-android-single-activity-architecture-with-navigation-component-36


Fragments



Has own layout and lifecycle




https://developer.android.com/reference/androidx/lifecycle/Lifecycle.State



https://developer.android.com/guide/fragments/lifecycle


Fragments

- Must be hosted by an activity or another fragment
- Change at runtime, store records into backstack
- Reusablity ex: Comment List
- Modularity




Fragments vs Activities


- ✓ Has lifecyle both
- Reusablity ex: Comment List
- Fragments must be hosted by an activity or another fragment
- ✓ Modularity, multi-pane UI
- More smooth transition animations with fragments
- Passing data between activities Singleton (accesible from everyone), Intent(object type-safety)



Activity	Fragment
Activity is an application component that gives a user interface where the user can interact.	The fragment is only part of an activity, it basically contributes its UI to that activity.
Activity is not dependent on fragment	Fragment is dependent on activity. It can't exist independently.
we need to mention all activity it in the manifest.xml file	Fragment is not required to mention in the manifest file
We can't create multi-screen UI without using fragment in an activity,	After using multiple fragments in a single activity, we can create a multi-screen UI.
Activity can exist without a Fragment	Fragment cannot be used without an Activity.
Creating a project using only Activity then it's difficult to manage	While Using fragments in the project, the project structure will be good and we can handle it easily.
Lifecycle methods are hosted by OS. The activity has its own life cycle.	Lifecycle methods in fragments are hosted by hosting the activity.
Activity is not lite weight.	The fragment is the lite weight.

Fragment Creating Example








Navigation Component

https://developer.android.com/guide/navigation

https://cengiztoru.medium.com/navigation-architecture-component-1-ekranlar-aras%C4%B1-ge%C3%A7i%C5%9F-i%CC%87%C5%9Flemleri-59937bdb7703

Navigation Component

- ✓ Navigation Graph
- ✓ NavHost
- Navigation Controller
- √ Safe Args




Navigation Component

The Navigation component provides a number of other benefits, including the following:


- Handling fragment transactions.
- Handling Up and Back actions correctly by default.
- Providing standardized resources for animations and transitions.
- Implementing and handling deep linking.
- Including Navigation UI patterns, such as navigation drawers and bottom navigation, with minimal additional work.
- Safe Args a Gradle plugin that provides type safety when navigating and passing data between destinations.
- ViewModel support you can scope a ViewModel to a navigation graph to share UI-related data between the graph's destinations.

In addition, you can use Android Studio's Navigation Editor to view and edit your navigation graphs.


Navigation Component Example







Navigation Component Example



```
<androidx.fragment.app.FragmentContainerView
    android:id="@+id/nav_host_fragment"
    android:name="androidx.navigation.fragment.NavHostFragment"
    android:layout_width="0dp"
    android:layout_height="0dp"
    app:defaultNavHost="true"
    app:layout_constraintBottom_toBottomOf="parent"
    app:layout_constraintLeft_toLeftOf="parent"
    app:layout_constraintRight_toRightOf="parent"
    app:layout_constraintTop_toTopOf="parent"
    app:navGraph="@navigation/nav_graph" />
```

```
mBinding.tvUserList.setOnClickListener {  it: View!
    findNavController().navigate(R.id.action_userListFragment_to_userDetailFragment)
}
```




Safe Arguments

https://cengiztoru.medium.com/navigation-architecture-component-2-veri-ta%C5%9F%C4%B1ma-i%CC%87%C5%9Flemleri-269775be977

Data Passing between Fragments

- ✓ newInstance, bundle, argument
- interface
- ✓ Shared ViewModel
- ✓ Objects
- Storing data into local

 Shared Preferences, Data Store, SQLite, Room
- ✓ Storing data into remote, backend
- √ Safe Arguments by Navigation Component (Type Safety)



https://cengiztoru.medium.com/type-safety-tip-t%C3%BCr-g%C3%BCvenli%C4%9Fi-12cbbb554dc4



LET'S TALK CONTACT INFORMATION

Berk Ozyurt

berk.ozyurt1@huawei.com

Mehmet Yozgatli mehmet.yozgatli1@huawei.com

Cengiz Toru cengiz.toru@huawei.com

Telegram Channel

will be created

Official Website

https://developer.huawei.com