

mne.convert_forward_solution

mne.convert_forward_solution(*fwd*, *surf_ori*=False, *force_fixed*=False, *copy*=True, *use_cps*=True, ***, *verbose*=None) [\[source\]](#)

Convert forward solution between different source orientations.

Parameters:

fwd : `Forward`

The forward solution to modify.

surf_ori : `bool`, optional (default `False`)

Use surface-based source coordinate system? Note that `force_fixed=True` implies `surf_ori=True`.

force_fixed : `bool`, optional (default `False`)

If True, force fixed source orientation mode.

copy : `bool`

Whether to return a new instance or modify in place.

use_cps : `bool`

Whether to use cortical patch statistics to define normal orientations for surfaces (default True).

verbose : `bool` | `str` | `int` | `None`

Control verbosity of the logging output. If `None`, use the default verbosity level. See the [logging documentation](#) and `mne.verbose()` for details. Should only be passed as a keyword argument.


Returns:

fwd : `Forward`

The modified forward solution.

Examples using

mne.convert_forward_solution



Optically pumped magnetometer (OPM) data

Display sensitivity maps for EEG and MEG sensors


Visualize source leakage among labels using a circular graph

Plot point-spread functions (PSFs) and cross-talk functions (CTFs)


Compute cross-talk functions for LCMV beamformers

Compute spatial resolution metrics in source space


Compute spatial resolution metrics to compare MEG with EEG+MEG




Cortical Signal Suppression (CSS) for removal of cortical signals



Head model and forward computation



The role of dipole orientations in distributed source localization



Corrupt known signal with point spread