

# HSR–Stud Document Classes

Naoki Pross <npross@hsr.ch>

June 1, 2020

## Contents

<b>1 Purpose of these document classes</b>	<b>1</b>
<b>2 Class Options</b>	<b>1</b>
<b>3 Extra Metadata</b>	<b>2</b>
<b>4 Zusammenfassung <code>hsrzf</code> class</b>	<b>2</b>
4.1 Class options . . . . .	2
4.2 Minimal working example . . . . .	2
<b>5 Bericht <code>hsrbericht</code> class</b>	<b>2</b>
5.1 Metadata . . . . .	2
5.2 Minimal working example . . . . .	3
<b>6 License</b>	<b>3</b>
<b>7 Implementation</b>	<b>3</b>

## 1 Purpose of these document classes

The following document classes were made by and for the HSR-Stud organization. These classes are intended to be used to create beautiful summaries and cheat sheets. Available classes are:

**`hsrzf`** For summaries (Zusammenfassung)

**`hsrbericht`** For reports (Bericht)

## 2 Class Options

**`sans`** Use Sans-Serif fonts (`cmbright` and `hfbright`).

**`slab`** Use Slab-Serif fonts (`bitter` and `eulervm`).

**`margin=<size>`** Sets up margins to reasonable size.

\* Any other given option is passed to the underlying class (article).

Size	H	V	Size	H	V
huge	45	40	small	20	20
large	35	35	tiny	10	20
big	30	30	minimal	5	20
normal	25	30			

Table 1: Sizes for the `margin` option. All sizes are in millimeters

### 3 Extra Metadata

Thanks to the `titling` package, normal metadata informations are available through the following commands: `\theauthor`, `\thedata`, `\thetitle`. Additionally, more metadata variables have been created for this class, to conserve informations related to the university course.

`\course` The degree programme of the discussed subject. Example: `Elektrotechnik`

`\module` Short name of the module according to the class schedule. Example: `ComEng1`

`\semester` Semester during which the summarized subject was taught. Example: `FS20`

`\institute` Internal institute in which the module was taught. This field is optional.

`\authoremail` Email of the author. This field is optional.

`\maintainer` Name of the person maintaining the work. This field is optional.

`\contributors` List of names of those who have contributed to the document. This field is optional.

Like `\date`, `\title`, etc. these fields have too an accessor macro `\the<metadata>`. For example: `\thecourse`, `\themodule`, and so on.

## 4 Zusammenfassung `hsrzf` class

This class is intended to be used to write short summaries.

### 4.1 Class options

`header` Use the HSR-Stud standard header. The option `noheader` disables the header.

### 4.2 Minimal working example

## 5 Bericht `hsrbericht` class

This class tries to conform to the indications given by the communication department of the HSR. The specifications are found in the “Werkzeugkastens Technische Berichte”.

### 5.1 Metadata

In addition to the metadata described in the previous section. This class requires:

`\subtitle` Pretty self explanatory.

`\category` Category assigned to the project. This field is optional.

`\project` Name or reference to your project.

`\topic` You chosen topic in the category.

`\instructor` Name of the instructor / academic that is following or has assigned your work.

`\startdate` Date when you started the project.

`\finishdate` Date when you finished the project (can be set to `\today` to keep automatically updated).

`\address` Address or place where your work is produced. This field is optional.

`\matriculationnr` Your matriculation number.


`\logo` Code to insert your logo.

`\clientlogo` Code to insert the logo of the client / research department / ...

## 5.2 Minimal working example

## 6 License

This work is licensed under a [Creative Commons](https://creativecommons.org/licenses/by-sa/4.0/) “[Attribution-ShareAlike 4.0 International](https://creativecommons.org/licenses/by-sa/4.0/)” license.



## 7 Implementation

```

1 %^^A%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
2 %^^A Class Headers
3
4 (*hsrzf)
5 \NeedsTeXFormat{LaTeX2e}
6 \ProvidesClass{hsrzf}[2020/04/05 v0.1 HSRStud Summary class]
7 \</hsrzf)
8
9 (*hsrbericht)
10 \NeedsTeXFormat{LaTeX2e}
11 \ProvidesClass{hsrbericht}[2020/05/05 v0.1 HSRStud Report class]
12 \</hsrbericht)
13
14 %^^A%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
15 %^^A Implementation
16 %
17 (*hsrzf | hsrbericht)
18
19 %% Coding Packages (Dependencies)
20 \RequirePackage{iftex}
21 \RequirePackage{kvoptions}
22 \RequirePackage{etoolbox}
23
24 %% Class options
25 \SetupKeyvalOptions{
26   family=hsr,
27   prefix=hsr@
28 }
29
30 %% Use header and footer
31 \DeclareBoolOption[false]{header}
32 \DeclareComplementaryOption{noheader}{header}
33

```

```

34 %% Use a sans-serif font
35 \DeclareBoolOption[false]{sans}
36 \DeclareBoolOption[false]{slab}
37
38 % secret option :)
39 \DeclareBoolOption[false]{concrete}
40
41 %% Configures the geometry package
42 %%
43 %% Possible values:
44 %% - huge      (45mm, 40mm)
45 %% - large     (35mm, 35mm)
46 %% - big       (30mm, 30mm)
47 %% - normal    (25mm, 30mm)
48 %% - small     (20mm, 20mm)
49 %% - tiny      (10mm, 20mm)
50 %% - minimal   ( 5mm, 20mm)
51 \DeclareStringOption{margin}[huge]
52
53 %% Configures the polyglossia package
54 % \DeclareStringOption[]{\lang}[german]
55
56
57 %% Pass other options to the class
58 \DeclareDefaultOption{%
59   \ifx\CurrentOptionValue\relax
60     \PackageWarningNoLine{\@currname}{%
61       Unknown option ``\CurrentOption'\MessageBreak
62       is passed to class ``article'%
63     }%
64     % Pass the option to package color.
65     % Again it is better to expand \CurrentOption.
66     \expandafter\PassOptionsToClass
67     \expandafter{\CurrentOption}{article}
68   \else
69     % Package color does not take options with values.
70     % We provide the standard LaTeX error.
71     \@unknownoptionerror
72   \fi
73 }
74
75 \ProcessKeyvalOptions{hsr}
76
77
78 %% Create new metadata fields
79
80 %% Required fields
81 \newcommand\course[1]{\gdef\hsr@course{#1}}
82 \newcommand\hsr@course{\ClassError{hsrzf}{no \noexpand\course given}{}}
83 \newcommand\thecourse{\hsr@course}
84
85 \newcommand\module[1]{\gdef\hsr@module{#1}}
86 \newcommand\hsr@module{\ClassError{hsrzf}{no \noexpand\module given}{}}
87 \newcommand\themodule{\hsr@module}
88
89 \newcommand\semester[1]{\gdef\hsr@semester{#1}}
90 \newcommand\hsr@semester{\ClassError{hsrzf}{no \noexpand\semester given}{}}
91 \newcommand\thesemester{\hsr@semester}

```

```

92
93 %% Optional fields
94 \newcommand\institute[1]{\gdef\hsr@institute{#1}}
95 \newcommand\hsr@institute{\ClassWarning{hsrzf}{no \noexpand\institute given}{}}
96 \newcommand\theinstitute{\hsr@institute}
97
98 \newcommand\authoremail[1]{\gdef\hsr@authoremail{#1}}
99 \newcommand\hsr@authoremail{\ClassWarning{hsrzf}{no \noexpand\authoremail given}{}}
100 \newcommand\theauthoremail{\hsr@authoremail}
101
102 \newcommand\maintainer[1]{\gdef\hsr@maintainer{#1}}
103 \newcommand\hsr@maintainer{\ClassWarning{hsrzf}{no \noexpand\maintainer given}{}}
104 \newcommand\themaintainer{\hsr@maintainer}
105
106 \newcommand\contributors[1]{\gdef\hsr@contributors{#1}}
107 \newcommand\hsr@contributors{\ClassWarning{hsrzf}{no \noexpand\contributors given}{}}
108 \newcommand\thecontributors{\hsr@contributors}
109 (/hsrzf | hsrbericht)
110 (*hsrbericht)
111 %% The report class has some extra metadata
112
113 %% Extra title informations
114 \newcommand\subtitle[1]{\gdef\hsr@subtitle{#1}}
115 \newcommand\hsr@subtitle{\ClassError{hsrbericht}{no \noexpand\subtitle given}{}}
116 \newcommand\thesubtitle{\hsr@subtitle}
117
118 %% Project informations
119 \newcommand\category[1]{\gdef\hsr@category{#1}}
120 \newcommand\hsr@category{\ClassWarning{hsrbericht}{no \noexpand\category given}{}}
121 \newcommand\thecategory{\hsr@category}
122
123 \newcommand\project[1]{\gdef\hsr@project{#1}}
124 \newcommand\hsr@project{\ClassError{hsrbericht}{no \noexpand\project given}{}}
125 \newcommand\theproject{\hsr@project}
126
127 \newcommand\topic[1]{\gdef\hsr@topic{#1}}
128 \newcommand\hsr@topic{\ClassError{hsrbericht}{no \noexpand\topic given}{}}
129 \newcommand\thetopic{\hsr@topic}
130
131 \newcommand\version[1]{\gdef\hsr@version{#1}}
132 \newcommand\hsr@version{\ClassError{hsrbericht}{no \noexpand\version given}{}}
133 \newcommand\theversion{\hsr@version}
134
135 \newcommand\instructor[1]{\gdef\hsr@instructor{#1}}
136 \newcommand\hsr@instructor{\ClassError{hsrbericht}{no \noexpand\instructor given}{}}
137 \newcommand\theinstructor{\hsr@instructor}
138
139 \newcommand\startdate[1]{\gdef\hsr@startdate{#1}}
140 \newcommand\hsr@startdate{\ClassError{hsrbericht}{no \noexpand\startdate given}{}}
141 \newcommand\thestartdate{\hsr@startdate}
142
143 \newcommand\finishdate[1]{\gdef\hsr@finishdate{#1}}
144 \newcommand\hsr@finishdate{\ClassError{hsrbericht}{no \noexpand\finishdate given}{}}
145 \newcommand\thefinishdate{\hsr@finishdate}
146
147 %% Author informations
148 \newcommand\address[1]{\gdef\hsr@address{#1}}
149 \newcommand\hsr@address{\ClassWarning{hsrbericht}{no \noexpand\address given}{}}

```

```

150 \newcommand\theaddress{\hsr@address}
151
152 \newcommand\matriculationnr[1]{\gdef\hsr@matriculationnr{#1}}
153 \newcommand\hsr@matriculationnr{\ClassError{hsrbericht}{no \noexpand\matriculationnr given}{}}
154 \newcommand\thematriculationnr{\hsr@matriculationnr}
155
156 %% Logos informations
157 \newcommand\logo[1]{\gdef\hsr@logo{#1}}
158 \newcommand\hsr@logo{\ClassWarning{hsrbericht}{no \noexpand\logo given}{}}
159 \newcommand\thelogo{\hsr@logo}
160
161 \newcommand\clientlogo[1]{\gdef\hsr@clientlogo{#1}}
162 \newcommand\hsr@clientlogo{\ClassWarning{hsrbericht}{no \noexpand\clientlogo given}{}}
163 \newcommand\theclientlogo{\hsr@clientlogo}
164 \hsrbericht
165 (*hsrzf | hsrbericht)
166
167 %^^A%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
168 %^^A Setup base class
169 \LoadClass[a4paper]{article}
170
171 %% Style deps
172 \RequirePackage{geometry}
173 \RequirePackage{fancyhdr}
174 \RequirePackage{titling}
175 \RequirePackage{lastpage}
176 \RequirePackage{array}
177
178 %% Insert metadata in the pdf
179 \PassOptionsToPackage{plainpages=false, pdfpagelabels, pdfusetitle}{hyperref}
180 \RequirePackage{hyperref}
181
182 %^^A%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
183 %^^A Setup Style
184 %
185
186
187 %% Configure Sans-Serif font
188 \ifhsr@sans
189   \ifhsr@slab
190     \PackageError{hsrzf}{%
191       sans ans slab options cannot be used at the same time
192     }
193   \fi
194   \ifhsr@concrete{hsrzf}{%
195     sans and concrete options cannot be used at the same time
196   }
197   \fi
198
199   \PassOptionsToPackage{T1}{fontenc}
200   \RequirePackage{fontenc}
201   \RequirePackage{cmbright}
202   \RequirePackage{sfbmath}
203 \fi
204
205 %% Configure Slab-Serif font
206 \ifhsr@slab
207   \ifhsr@sans

```

```

208 \PackageError{hsrzf}{%
209     slab and sans options cannot be used at the same time
210 }
211 \fi
212 \ifhsr@concrete{hsrzf}{%
213     slab and concrete options cannot be used at the same time
214 }
215 \fi
216
217 \PassOptionsToPackage{T1}{fontenc}
218 \RequirePackage{fontenc}
219 \PassOptionsToPackage{rm,light}{roboto}
220 \RequirePackage{roboto}
221 \fi
222
223 %% Configure (secret) concrete font
224 \ifhsr@concrete
225 \ifhsr@sans{hsrzf}{%
226     concrete and sans options cannot be used at the same time
227 }
228 \fi
229 \ifhsr@slab
230 \PackageError{hsrzf}{%
231     concrete and slab options cannot be used at the same time
232 }
233 \fi
234
235 \PassOptionsToPackage{boldsans,amssymb}{concmath}
236 \RequirePackage{concmath}
237 \PassOptionsToPackage{T1}{fontenc}
238 \RequirePackage{fontenc}
239 \fi
240
241 %% configure geometry
242 %% defaults to big
243 \newlength{\hsr@hmarginwidth}
244 \newlength{\hsr@vmarginheight}
245
246 \ifx\hsr@margin\@empty
247 \setlength{\hsr@hmarginwidth}{30mm}
248 \setlength{\hsr@vmarginheight}{30mm}
249 \else
250 \expandafter\ifstrequal\expandafter{\hsr@margin}{huge}{
251     \setlength{\hsr@hmarginwidth}{45mm}
252     \setlength{\hsr@vmarginheight}{40mm}}{
253 %%
254 \expandafter\ifstrequal\expandafter{\hsr@margin}{large}{
255     \setlength{\hsr@hmarginwidth}{35mm}
256     \setlength{\hsr@vmarginheight}{35mm}}{
257 %%
258 \expandafter\ifstrequal\expandafter{\hsr@margin}{big}{
259     \setlength{\hsr@hmarginwidth}{30mm}
260     \setlength{\hsr@vmarginheight}{30mm}}{
261 %%
262 \expandafter\ifstrequal\expandafter{\hsr@margin}{normal}{
263     \setlength{\hsr@hmarginwidth}{25mm}
264     \setlength{\hsr@vmarginheight}{30mm}}{
265 %%

```

```

266 \expandafter\ifstrequal\expandafter{\hsr@margin}{small}{
267 \setlength\hsr@hmarginwidth{20mm}
268 \setlength\hsr@vmarginheight{20mm}}{-}
269 %%
270 \expandafter\ifstrequal\expandafter{\hsr@margin}{tiny}{
271 \setlength\hsr@hmarginwidth{10mm}
272 \setlength\hsr@vmarginheight{20mm}}{-}
273 %%
274 \expandafter\ifstrequal\expandafter{\hsr@margin}{minimal}{
275 \setlength\hsr@hmarginwidth{ 5mm}
276 \setlength\hsr@vmarginheight{20mm}}{-}
277 %%
278 % TODO: fix this
279 % \ClassError{hsrzf}{Invalid margin size}
280 % \setlength\hsr@hmarginwidth{30mm}
281 % \setlength\hsr@vmarginheight{30mm}
282 \fi
283
284 </hsrzf | hsrbericht>
285
286 %^^A%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
287 %^^A HSR ZF specific
288 (*hsrzf)
289 %% TODO: change vmarginheight if header is on
290 \newgeometry{
291 hmargin=\hsr@hmarginwidth,
292 vmargin=\hsr@vmarginheight,
293 marginparsep=0pt,
294 marginpar=0pt,
295 }
296
297 \fancypagestyle{hsrzf}{%
298 \fancyhf{} % clear
299 \fancyhead[C]{\thetitle}
300 \fancyhead[R]{\rightmark}
301 \fancyhead[L]{\leftmark}
302 \fancyfoot[R]{\@date}
303 \fancyfoot[L]{\theauthor}
304 \renewcommand{\headrulewidth}{.5pt}
305 \renewcommand{\footrulewidth}{.5pt}
306 }
307
308 \fancypagestyle{hsrzf-norulers}{%
309 \fancyhf{} % clear
310 \fancyhead[C]{\thetitle}
311 \fancyhead[R]{\rightmark}
312 \fancyhead[L]{\leftmark}
313 \fancyfoot[R]{\@date}
314 \fancyfoot[L]{\theauthor}
315 \renewcommand{\headrulewidth}{0pt}
316 \renewcommand{\footrulewidth}{0pt}
317 }
318
319 \ifhsr@header
320 \pagestyle{hsrzf}
321 \fi
322 </hsrzf>
323

```



```

324 %^^A%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
325 %^^A HSR Bericht specific
326 (*hsrbericht)
327
328 %% Redefine title and abstract
329 \renewcommand\maketitle{%
330 \begin{titlepage}
331   \thispagestyle{hsrbericht}
332   \begin{center}
333     \vspace*{6cm}
334     \textbf{\fontsize{48}{60}\selectfont \@title}
335     \vspace{1.5cm} \\
336     \textbf{\fontsize{24}{48}\selectfont \hsr@subtitle}
337     \vspace{1cm} \\
338     \textbf{\fontsize{22}{48}\selectfont \hsr@category}
339     \vspace{0.5cm} \\
340     \begin{tabular}{rl}
341       \textbf{Version:} & \hsr@version \\
342     \end{tabular}
343     \vspace{4cm} \\
344     \begin{tabular}{rl p{1.5cm} rl}
345       \textbf{Autor:} & \textbf{\@author} & \hsr@dozent & \hsr@instructor \\
346       E-Mail: & \texttt{\hsr@authoremail} & \hsr@themengebiet & \hsr@topic \\
347       Matrikelnummer: & \hsr@matriculationnr & \hsr@studiengang & \hsr@course \\
348       Adresse: & \hsr@address & & \\
349     \end{tabular} \\
350     \vspace{2cm} \\
351     \begin{tabular}{rl}
352       \textbf{Erstellt am:} & \textbf{\hsr@startdate} \\
353       \textbf{Letzte Änderung am:} & \textbf{\hsr@finishdate} \\
354     \end{tabular}
355     \end{center}
356 \end{titlepage}}
357
358 \renewenvironment{abstract}{%
359   \section*{Abstract}%
360   \newcommand\problem{\paragraph{Problem}}
361   \newcommand\goal{\paragraph{Ziel}}
362   \newcommand\method{\paragraph{Method / Vorgehen}}
363   \newcommand\results{\paragraph{Wesentliche Ergebnisse}}
364   \newcommand\suggestions{\paragraph{Empfehlungen}}
365   \newcommand\keywords{\paragraph{Schlüsselwörter}}
366 }{}
367
368 %% TODO: twoside / book support
369 %% Debug:
370 %% \RequirePackage{showframe}
371
372 \newgeometry{
373   hmargin=\hsr@hmarginwidth,
374   vmargin=\hsr@vmarginheight,
375   marginparsep=0pt,
376   marginpar=0pt,
377 }
378
379 %% Configure headers
380 \fancypagestyle{hsrbericht}{%
381   \fancyhf{} % clear

```

```

382 \fancyhead[C]{\@title}
383 \fancyhead[R]{\hsr@clientlogo}
384 \fancyhead[L]{\hsr@logo}
385 \fancyfoot[R]{\thepage / \pageref{LastPage} }
386 \fancyfoot[L]{Dockument: \jobname \ \ Druck: \finishdate}
387 \renewcommand{\headrulewidth}{.5pt}
388 \renewcommand{\footrulewidth}{.5pt}
389 }
390
391 \fancypagestyle{plain}{%
392 \fancyhf{} % clear
393 \fancyhead[C]{\@title}
394 \fancyhead[R]{\hsr@clientlogo}
395 \fancyhead[L]{\hsr@logo}
396 \fancyfoot[R]{\thepage / \pageref{LastPage} }
397 \fancyfoot[L]{Dockument: \jobname \ \ Druck: \finishdate}
398 \renewcommand{\headrulewidth}{.5pt}
399 \renewcommand{\footrulewidth}{.5pt}
400 }
401
402 \pagestyle{hsrbericht}
403
404 </hsrbericht>

vim: set tw=80 sw=2 ts=2 et :

```