



THE UNIVERSITY OF TEXAS
AT AUSTIN

EE381V LARGE SCALE OPTIMIZATION

Problem Set 0

Edited by L^AT_EX

Department of Computer Science

STUDENT

Jimmy Lin

xl5224

COURSE COORDINATOR

Sujay Sanghavi

UNIQUE NUMBER

17350

RELEASE DATE

September 5, 2014

DUE DATE

September 11, 2014

TIME SPENT

10 hours

September 8, 2014

Table of Contents

1	Matlab and Computational Assignment	3
1.1	Algorithm 1: Least Square	3
1.1.1	Small-scale dataset: Succeed	3
1.1.2	Medium-scale dataset: Succeed	3
1.1.3	Large-scale dataset: Failed	3
1.2	Algorithm 2: optimization with LASSO	4
1.2.1	Small-scale dataset: Succeed	4
1.2.2	Medium-scale dataset: Succeed	4
1.2.3	Large-scale dataset: Failed	4
1.3	Orthogonal Matching Pursuit	5
1.3.1	Small-scale Dataset: Succeed	5
1.3.2	Medium-scale Dataset: Succeed	5
1.3.3	Large-scale Dataset: Succeed	5
2	Linear Algebra Review	6
2.1	More Range and Nullspace	6
2.1.1	Smallest and Largest rank of $C = AB$	6
2.1.2	Largest rank of $C = AB$	6
2.2	Riesz Representation Theorem	6
2.3	Polynomial Vector Spaces	7
2.3.1	$Tp = 2p(t) - tp'(t)$: True	7
2.3.2	$Tp = 2p(t) - 3tp'(t)$: True	7
2.3.3	Characterization of Surjectivity: $a_0 \neq 0$	7
2.4	Rank	7
2.4.1	Show that $\text{rank}(A) \leq \min\{m, n\}$	7
2.4.2	Sylvester's rank inequality	7
2.4.3	Subadditivity	7
2.4.4	Frobenius Rank Inequality	7
A	Codes Printout	8
A.1	Sparse Recovery	8
A.1.1	Algorithm 1: Least Square	8
A.1.2	Algorithm 2: Optimization with LASSO	9
A.2	Orthogonal Matching Pursuit	10
A.2.1	OMP Routine	10
A.2.2	Regression Scripts	11

Chapter 1

Matlab and Computational Assignment

1.1 Algorithm 1: Least Square

The command to invoke standard least-squared regression:

```
>> algo1()
```

Note that *algo1.m* includes scripts for all three datasets.

1.1.1 Small-scale dataset: Succeed

The brief summary of applying standard least-squared regression on small-scale dataset is as follows:

- Total CPU time (secs) = 0.18
- CPU time per iteration = 0.02
- Regression Error $\|X\beta - y\|$: 1.1698e-10
- Testing Error $\|X_{test}\beta - y_{test}\|$: 23.058394 (pretty large)

1.1.2 Medium-scale dataset: Succeed

The brief summary of applying standard least-squared regression on medium-scale dataset is as follows:

- Total CPU time (secs) = 43.95
- CPU time per iteration = 5.49
- Regression Error $\|X\beta - y\|$: 3.2594e-09
- Testing Error $\|X_{test}\beta - y_{test}\|$: 19.862394 (pretty large)

1.1.3 Large-scale dataset: Failed

This standard least-square regression task is too large-scaled to be computed.

1.2 Algorithm 2: optimization with LASSO

The command to invoke least-squared regression with LASSO:

```
>> algo2()
```

Note that *algo2.m* includes scripts for all three datasets.

1.2.1 Small-scale dataset: Succeed

The brief summary of applying least-squared regression with LASSO on small-scale dataset is as follows:

- Total CPU time (secs) = 0.38
- CPU time per iteration = 0.02
- Regression Error: 6.7886e-10
- Testing Error: 0.144338
- Supports (non-zeros entries of β): 43 (500 atoms in total)

1.2.2 Medium-scale dataset: Succeed

The brief summary of applying least-squared regression with LASSO on medium-scale dataset is as follows:

- Total CPU time (secs) = 126.66
- CPU time per iteration = 4.87
- Regression Error: 4.4292e-09
- Testing Error: 0.078289
- Supports (non-zeros entries of β): 342 (5000 atoms in total)

1.2.3 Large-scale dataset: Failed

This least-square regression with LASSO task is too large-scaled to be computed.

Remarks: Least-squared regression with LASSO does outperform standard least-squared regression in its prediction accuracy. Besides, it has higher computational complexity since it requires more iterations for convergence and each iteration cost more time to complete.

1.3 Orthogonal Matching Pursuit

The command to invoke regression with OMP preprocessing:

```
>> regress_omp()
```

1.3.1 Small-scale Dataset: Succeed

The brief summary of applying regression with OMP feature selection on small-scale dataset is as follows:

- Indices of Features selected by OMP (with order): 402, 235, 86, 11, 108.
- Elapsed time is 0.198106 seconds.
- Regression Error $\|X\beta - y\|$: 5.3785e-02
- Testing Error $\|X_{test}\beta - y_{test}\|$: 4.4208e-02

1.3.2 Medium-scale Dataset: Succeed

The brief summary of applying regression with OMP feature selection on medium-scale dataset is as follows:

- Indices of Features selected by OMP (with order): 577, 2760, 561, 3614, 3958.
- Elapsed time is 0.209093 seconds.
- Regression Error $\|X\beta - y\|$: 2.1955e-01
- Testing Error $\|X_{test}\beta - y_{test}\|$: 1.8219e-02

1.3.3 Large-scale Dataset: Succeed

The brief summary of applying regression with OMP feature selection on large-scale dataset is as follows:

- Indices of Features selected by OMP (with order): 17099, 29426, 35373, 22452, 43354.
- Elapsed time is 2.994790 seconds.
- Regression Error $\|X\beta - y\|$: 6.9964e-01
- Testing Error $\|X_{test}\beta - y_{test}\|$: 6.4437e-03

Note that Elapsed time is defined as OMP preprocessing and regression for selected atoms on that dataset, but not included computation for regression error and testing error.

Remarks: Least-squared regression on OMP feature selection performs much better than standard least-squared regression and least-squared regression with LASSO. Besides, it has lower computational complexity since it allows the large-scale dataset (third dataset) to be regressed.

Chapter 2

Linear Algebra Review

2.1 More Range and Nullspace

2.1.1 Smallest and Largest rank of $C = AB$

Conditions: $A \in \mathbb{R}^{10 \times 10}$ with $\text{rank}(A) = 5$ and $B \in \mathbb{R}^{10 \times 10}$ with $\text{rank}(B) = 5$.
 Sylvester's rank inequality: $\forall A \in \mathbb{R}^{m \times k}, B \in \mathbb{R}^{k \times n}$

$$\text{rank}(A) + \text{rank}(B) - k \leq \text{rank}(AB)$$

Smallest rank of $C = AB$ is $\text{rank}(A) + \text{rank}(B) - k = 5 + 5 - 10 = 0$.

Largest rank of $C = AB$ is $\min(\text{rank}(A), \text{rank}(B)) = \min(5, 5) = 5$.

2.1.2 Largest rank of $C = AB$

Conditions: $A \in \mathbb{R}^{10 \times 15}$ with $\text{rank}(A) = 7$ and $B \in \mathbb{R}^{15 \times 11}$ with $\text{rank}(B) = 8$.
 Largest rank of $C = AB$ is $\min(\text{rank}(A), \text{rank}(B)) = \min(7, 8) = 7$.

2.2 Riesz Representation Theorem

Linear map $f : \mathbb{R}^n \rightarrow \mathbb{R}$ has two critical properties due to its linearity:

$$\text{additivity: } f(x + y) = f(x) + f(y), \forall x, y \in \text{dom}(f) \quad (2.1)$$

$$\text{homogeneity: } f(\alpha x) = \alpha f(x), \forall \alpha \in \mathbb{R}, x \in \text{dom}(f) \quad (2.2)$$

Let arbitrary vector $\mathbf{w} = (\alpha_1, \alpha_2, \dots, \alpha_n) \in \mathbb{R}^n$. Then we can denote \mathbf{w} as linear combination of standard basis

$$\mathbf{w} = \alpha_1 \mathbf{e}_1 + \alpha_2 \mathbf{e}_2 + \dots + \alpha_n \mathbf{e}_n \quad (2.3)$$

Now we start to show that $f(\mathbf{w})$ can be represented as inner product of \mathbf{w} and another vector.

$$f(\mathbf{w}) = f(\alpha_1 \mathbf{e}_1 + \alpha_2 \mathbf{e}_2 + \dots + \alpha_n \mathbf{e}_n) \quad \text{standard basis representation(2.3)} \quad (2.4)$$

$$= f(\alpha_1 \mathbf{e}_1) + f(\alpha_2 \mathbf{e}_2) + \dots + f(\alpha_n \mathbf{e}_n) \quad \text{additivity of linear map(2.1)} \quad (2.5)$$

$$= \alpha_1 f(\mathbf{e}_1) + \alpha_2 f(\mathbf{e}_2) + \dots + \alpha_n f(\mathbf{e}_n) \quad \text{additivity of linear map(2.2)} \quad (2.6)$$

$$= \langle (f(\mathbf{e}_1), f(\mathbf{e}_2), \dots, f(\mathbf{e}_n)), (\alpha_1, \alpha_2, \dots, \alpha_n) \rangle \quad \text{definition of inner product} \quad (2.7)$$

$$= \langle \mathbf{x}, \mathbf{w} \rangle \quad \mathbf{x} = (f(\mathbf{e}_1), f(\mathbf{e}_2), \dots, f(\mathbf{e}_n)) \quad (2.8)$$

Hence, we have successfully proved that

$$\forall \text{ linear map } f : \mathbb{R}^n \rightarrow \mathbb{R}, \exists \mathbf{x} \in \mathbb{R}^n, f(\mathbf{w}) = \langle \mathbf{x}, \mathbf{w} \rangle \quad (2.9)$$

2.3 Polynomial Vector Spaces

2.3.1 $Tp = 2p(t) - tp'(t)$: True

T is represented by an upper bi-diagonal matrix with all diagonal entries being $a_0 = 2$ and sub-diagonal entries to be $a_1 = -1$. Obviously, the matrix is full-rank and hence the range is the entire $(d+1)$ -dimensional space.

2.3.2 $Tp = 2p(t) - 3tp'(t)$: True

T is represented by an upper bi-diagonal matrix with all diagonal entries being $a_0 = 2$ and sub-diagonal entries to be $a_1 = -3$. Obviously, the matrix is full-rank and hence the range is the entire $(d+1)$ -dimensional space.

2.3.3 Characterization of Surjectivity: $a_0 \neq 0$

If $a_0 = 0$, the matrix representing T is not full-rank anymore. The dimensionality of range is not $(d+1)$, which suggests that the vector q with highest degree d is not reachable by arbitrary pair of Tp . This also indicates that if $a_0 = 0$, the corresponding mapping T is not surjective anymore: for every polynomial(vector) $q \in V$, there does not exist a polynomial(vector) $p \in V$ such that $Tp = q$. In conclusion, we have

$$a_0 \neq 0 \implies \forall q \in V, \exists p \in V, s.t. Tp = q \quad (2.10)$$

2.4 Rank

2.4.1 Show that $\text{rank}(A) \leq \min\{m, n\}$

Proof. $\text{rank}(A)$ is defined as the number of columns that are linearly independent. Then, we have

$$\text{rank}(A) \leq \text{number of linearly independent columns} \leq n \quad (2.11)$$

Since the number of linearly independent columns equals to the number of linearly independent rows,

$$\text{rank}(A) \leq \text{number of linearly independent rows} \leq m \quad (2.12)$$

From (2.11) and (2.12), it is easy to derive the desired result:

$$\text{rank}(A) \leq \min\{m, n\} \quad (2.13)$$

□

2.4.2 Sylvester's rank inequality

Proof. adf

□

2.4.3 Subadditivity

2.4.4 Frobenius Rank Inequality

Appendix A

Codes Printout

A.1 Sparse Recovery

A.1.1 Algorithm 1: Least Square

```

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%% Scripts invoking cvx least-square routines to
%% solve problems using our three datasets.
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%% standard least-square for Small-scale dataset
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
cvx_begin
    variable b1(size(X1,2))
    minimize( norm( X1*b1-y1 ) )
cvx_end

RegressionError1 = norm( X1*b1-y1 )
TestingError1 = norm( X1test*b1 - y1test )

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%% standard least-square for Medium-scale dataset
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
cvx_begin
    variable b2(size(X2,2))
    minimize( norm( X2*b2 - y2 ) )
cvx_end

RegressError2 = norm( X2*b2 - y2 )
TestError2 = norm( X2test*b2 - y2test )

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%% standard least-square for Large-scale dataset
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
cvx_begin
    variable b3(size(X3,2))
    minimize( norm( X3*b3-y3 ) )
cvx_end

RegressionError3 = norm( X3*b3 - y3 )
TestingError3 = norm( X3test*b3 - y3test )

```

A.1.2 Algorithm 2: Optimization with LASSO

```

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%% Scripts invoking cvx least-square routines to
%% solve LASSO problems using our three datasets.
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

format short e
EPSILON = 10e-5;
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%% LASSO least-square for Small-scale dataset
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
cvx_begin
    variable b1(size(X1,2))
    minimize( norm( X1*b1-y1 ) + norm(b1,1) )
cvx_end

RegressionError1 = norm( X1*b1-y1 )
TestingError1 = norm( X1test * b1 - y1test )
Support1 = sum((b1 < EPSILON) + (b1 > -EPSILON)) < 2)

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%% LASSO least-square for Medium-scale dataset
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
cvx_begin
    variable b2(size(X2,2))
    minimize( norm( X2*b2-y2 ) + norm(b2, 1))
cvx_end

RegressionError2 = norm( X2*b2-y2 )
TestingError2 = norm( X2test * b2 - y2test )
Support2 = sum((b2 < EPSILON) + (b2 > -EPSILON)) < 2)

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%% LASSO least-square for Large-scale dataset
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
cvx_begin
    variable b3(size(X3,2))
    minimize( norm( X3*b3-y3 ) + norm(b3, 1) )
cvx_end

RegressionError3 = norm( X3*b3-y3 )
TestingError3 = norm( X3test * b3 - y3test )
Support3 = sum((b3 < EPSILON) + (b3 > -EPSILON)) < 2)

```

A.2 Orthogonal Matching Pursuit

A.2.1 OMP Routine

```

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%% Orthogonal matching Pursuit
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

function Iset = omp (X, y, SPARSITY)

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%% INITIALIZATION
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
[target_feat_dot_prod, target_feat_idx] = max(X' * y);
Iset = [target_feat_idx];

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%% AUGMENTATION
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
residual = y;
for iter = 1:(SPARSITY-1),
    % perpendicular complement of y to X.i
    phi = X(:, Iset);
    P = phi * inv(phi'*phi) * phi';
    I = eye(size(P));
    residual = (I - P) * residual;
    % elect new atom and add to selected atom set
    [target_feat_dot_prod, target_feat_idx] = max(X' * residual);
    % NOTE that new feature(atom) will not pre-exist in Iset
    % This is theoretically guaranteed by orthogonal projection
    Iset = [Iset, target_feat_idx];
end
end

```

A.2.2 Regression Scripts

```

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%% Invoke CVX least square regression after OMP
%% feature selection
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

SPARSITY = 5; % SPARSITY parameter for OMP

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%% Small-scale dataset
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
tic
Iset1 = omp(X1, y1, SPARSITY);
subX1 = X1(:, Iset1);
cvx_begin
    variable sub_b1(SPARSITY);
    minimize( norm(subX1 * sub_b1 - y1) )
cvx_end
toc

Iset1
RegressionError1 = norm(subX1*sub_b1 - y1)
TestingError1 = norm(X1test(:,Iset1)*sub_b1 - y1test)

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%% Medium-scale dataset
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
tic
Iset2 = omp(X2, y2, SPARSITY);
subX2 = X2(:, Iset2);
cvx_begin
    variable sub_b2(SPARSITY);
    minimize( norm(subX2 * sub_b2 - y2) )
cvx_end
toc

Iset2
RegressionError2 = norm(subX2*sub_b2 - y2)
TestingError2 = norm(X2test(:,Iset2)*sub_b2 - y2test)

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%% Large-scale dataset
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
tic
Iset3 = omp(X3, y3, SPARSITY);
subX3 = X3(:, Iset3);
cvx_begin
    variable sub_b3(SPARSITY);
    minimize( norm(subX3 * sub_b3 - y3) )
cvx_end
toc

Iset3
RegressionError3 = norm(subX3*sub_b3 - y3)
TestingError3 = norm(X3test(:,Iset3)*sub_b3 - y3test)

```