

Coding Agent Context Extension

Generated from `.specify/extensions/agent-context/README.md`

Artifact type: other

This bundled extension manages the **coding agent context/instruction file** (e.g. ``CLAUDE.md``, ``github/copilot-instructions.md``, ``AGENTS.md``, ``GEMINI.md``, ...) for the active integration.

Table of contents

Coding Agent Context Extension

Why an extension?

Commands

Configuration

Path to the coding agent context file managed by this extension

Optional list of coding agent context files to manage together.

When non-empty, this takes precedence over `context_file`.

Delimiters for the managed Spec Kit section

Requirements

or target the specific interpreter Spec Kit uses:

Disable

Body

Coding Agent Context Extension

This bundled extension manages the **coding agent context/instruction file** (e.g. ``CLAUDE.md``, ``github/copilot-instructions.md``, ``AGENTS.md``, ``GEMINI.md``, ...) for the active integration. It owns the lifecycle of the managed section delimited by the configurable start/end markers (defaults: `` ` / ` ``).

Why an extension?

Not every Spec Kit user wants Spec Kit to write into the coding agent's context file. Extracting this behavior into a dedicated extension lets users: - **Opt out** entirely with ``specify extension disable agent-context`` — Spec Kit will then never create or modify the agent context file. - **Customize the markers** by editing ``specify/extensions/agent-context/agent-context-config.yml`` — both the Python layer and the

bundled scripts honor the same ``context_markers`` value. - ****Synchronize multiple agent anchors**** by setting ``context_files`` when a project intentionally uses more than one coding agent context file, such as ``AGENTS.md`` and ``CLAUDE.md``. - ****Refresh on demand**** with ``/speckit.agent-context.update``, or automatically through the hooks declared in ``extension.yml`` (``after_specify``, ``after_plan``).

Commands

Command	Description
<code>`speckit.agent-context.update`</code>	Refresh the managed section in the agent context file with the current plan path.

Configuration

All configuration flows through the extension's own config file at ``.specify/extensions/agent-context/agent-context-config.yml``: ``yaml

Path to the coding agent context file managed by this extension

`context_file`: CLAUDE.md

Optional list of coding agent context files to manage together.

When non-empty, this takes precedence over context_file.

`context_files`: - AGENTS.md - CLAUDE.md

Delimiters for the managed Spec Kit section

`context_markers`: `start`: "" `end`: "" - ``context_file`` — the project-relative path to the coding agent context file, written by ``specify init`` and ``specify integration install``. - ``context_files`` — optional project-relative paths to multiple coding agent context files. When non-empty, the list takes precedence over ``context_file``. Absolute paths, backslash separators, and ``.`` path segments are rejected. - ``context_markers.start`` / ``context_markers.end`` — the delimiters around the managed section. Edit these to use custom markers.

Requirements

The bundled update scripts require ****Python 3**** with ****PyYAML**** for YAML/upsert processing (PowerShell can also use ``ConvertFrom-Yaml`` when available). PyYAML ships with the ``specify`` CLI and is normally available via the same ``python3`` interpreter. If a hook reports ****PyYAML is required ... not available in the current Python environment****, it means the system ``python3`` differs from the one used to install Spec Kit. To resolve, run: ```bash pip install pyyaml``

or target the specific interpreter Spec Kit uses:

/path/to/speckit-python -m pip install pyyaml ```

Disable

```bash specify extension disable agent-context ``` When disabled, Spec Kit skips context file creation, updates, and removal (the gates are inside `upsert\_context\_section()` and `remove\_context\_section()`). Disabled projects also ignore stale `context\_files` values during command rendering so disabling the extension remains a complete opt-out.

*source: .specify/extensions/agent-context/README.md | commit: n/a*