

Update Coding Agent Context

Generated from `.github/agents/speckit.agent-context.update.agent.md`

Artifact type: other

Table of contents

Update Coding Agent Context

Behavior

Execution

Body

Update Coding Agent Context

Refresh the managed Spec Kit section inside the active coding agent's context/instruction file (e.g. ``CLAUDE.md``, ``github/copilot-instructions.md``, ``AGENTS.md``).

Behavior

The script reads the agent-context extension config at ``.specify/extensions/agent-context/agent-context-config.yml`` to discover: - ``context_file`` — the path of the coding agent context file to manage. - ``context_files`` — optional project-relative paths for multiple coding agent context files. When non-empty, the script updates each listed file and the list takes precedence over ``context_file``. - ``context_markers.start`` / ``context_markers.end`` — the delimiters surrounding the managed section. Defaults to `` `` and `` `` when the field is missing. It then creates, replaces, or appends the managed block so that the section points at the most recent plan path when one can be discovered (``specs//plan.md``). If ``context_files`` and ``context_file`` are empty, the command reports nothing to do and exits successfully. Context file paths must stay project-relative; absolute paths, Windows drive paths, backslash separators, and ``..`` path segments are rejected.

Execution

- **Bash**: ``.specify/extensions/agent-context/scripts/bash/update-agent-context.sh [plan_path]`` - **PowerShell**: ``.specify/extensions/agent-context/scripts/powershell/update-agent-context.ps1 [plan_path]``
When ``plan_path`` is omitted, the script auto-detects the most recently modified ``specs/*/plan.md``.

source: [.github/agents/speckit.agent-context.update.agent.md](#) | commit: n/a