

# How is machine learning useful for macroeconomic forecasting?

**Philippe Goulet Coulombe | Maxime Leroux | Dalibor Stevanovic |  
Stéphane Surprenant**

Département des Sciences économiques,  
 Université du Québec à Montréal,  
 Montréal, Québec, Canada

## Correspondence

Philippe Goulet Coulombe and Dalibor Stevanovic, Département des Sciences économiques, Université du Québec à Montréal, Montréal, Québec, Canada.  
 Email: p.gouletcoulombe@gmail.com and dstevanovic.econ@gmail.com

## Summary

We move beyond *Is Machine Learning Useful for Macroeconomic Forecasting?* by adding the *how*. The current forecasting literature has focused on matching specific variables and horizons with a particularly successful algorithm. To the contrary, we study the usefulness of the underlying features driving ML gains over standard macroeconometric methods. We distinguish four so-called features (nonlinearities, regularization, cross-validation, and alternative loss function) and study their behavior in both the data-rich and data-poor environments. To do so, we design experiments that allow to identify the “treatment” effects of interest. We conclude that **(i)** nonlinearity is the true game changer for macroeconomic prediction, **(ii)** the standard factor model remains the best regularization, **(iii)** K-fold cross-validation is the best practice, and **(iv)** the  $L_2$  is preferred to the  $\bar{\epsilon}$ -insensitive in-sample loss. The forecasting gains of nonlinear techniques are associated with high macroeconomic uncertainty, financial stress and housing bubble bursts. Furthermore, ML nonlinearities are helpful when considering density forecasts.

## KEYWORDS

big data, forecasting, machine learning

## 1 | INTRODUCTION

The intersection of machine learning (ML) with econometrics has become an important research landscape in economics. ML has gained prominence due to the availability of large data sets, especially in microeconomic applications (Belloni et al., 2017; Athey, 2019). Despite the growing interest in ML, understanding *how* ML procedures can contribute when they are applied to predict macroeconomic outcomes remains challenging.<sup>1</sup> Yet that very understanding could prove very useful, probably more so than crowning a single algorithm. It is more appealing to applied econometricians to upgrade a standard framework with a subset of specific insights rather than to drop everything altogether for an off-the-shelf ML model.

Despite appearances, ML has a long history in macroeconomics (see Kuan and White (1994); Lee et al. (1993); Medeiros et al. (2006); Stock and Watson (1999); Swanson and White (1997); Trapletti et al. (2000)). However, only

<sup>1</sup>The linear techniques have been extensively examined since Stock and Watson (2002a, 2002b). Kotchoni et al. (2019) compare more than 30 forecasting models, including factor-augmented and regularized regressions. Giannone et al. (2018) study the relevance of sparse modeling in various economic prediction problems.

recently did macroeconomic forecasting experience a surge in the number of studies applying (successfully) ML methods.<sup>2</sup> The vast catalogue of tools creates a large conceptual space, much of which remains to be explored. To map that space without getting lost in it, we move beyond the coronation of a single winning model and its subsequent interpretation. Rather, we conduct a meta-analysis of many ML products by projecting them in their “characteristic” space. Then, we provide a direct assessment of which characteristics matter and which do not.

More precisely, we aim to answer the following question: what are the key ML features improving macroeconomic predictions? In particular, no clear attempt has been made at understanding why one algorithm might work while another does not. We address this question by designing an *experiment* to identify important characteristics of machine learning and big data techniques. The exercise consists of an extensive pseudo-out-of-sample forecasting horse race between many models that differ with respect to the four main features: nonlinearity, regularization, hyperparameter selection, and loss function. To control for the big data aspect, we consider data-poor and data-rich models, and administer those *patients* one particular ML *treatment* or combinations of them. Monthly forecast errors are constructed for five important macroeconomic variables, five forecasting horizons and for almost 40 years. Then, we provide a straightforward framework to identify which *features* are responsible for substantial forecasting accuracy improvements.

The main results can be summarized as follows. First, the ML nonparametric nonlinearity constitutes the most salient feature as they improve substantially the forecasting accuracy for all macroeconomic variables in our exercise, especially when predicting at long horizons.<sup>3</sup> Second, in the big data framework, alternative regularization methods (Lasso, Ridge, Elastic-net) do not improve over the workhorse factor model, which remains the preferred strategy for dimensionality reduction.

Third, the hyperparameter selection by K-fold cross-validation (CV) and the standard BIC (when possible) do better on average than any other criterion. This suggests that ignoring information criteria when opting for more complicated ML models is not harmful. This is also quite convenient: K-fold is the built-in CV option in most standard ML packages. Fourth, replacing the standard in-sample quadratic loss function by the  $\bar{\epsilon}$ -insensitive loss function in support vector regressions (SVRs) is not useful, except in very rare cases. The latter finding is a direct by-product of our strategy to disentangle treatment effects. In accordance with other empirical results (Colombo & Pelagatti, 2020; Sermpinis et al., 2014), in absolute terms, SVRs do perform well—even if they use a loss at odds with the one used for evaluation. However, that performance is a mixture of the attributes of both nonlinearities (via the kernel trick) *and* an alternative loss function. Our results reveal that this change in the loss function has detrimental effects on performance in terms of both mean squared errors and absolute errors. Fifth, the marginal effect of big data is positive and significant and improves as the forecast horizon grows. The robustness analysis shows that these results remain valid when (i) real-time data are used; (ii) the absolute loss is considered; (iii) quarterly targets are predicted; (iv) the exercise is reconducted with a large Canadian data set. Furthermore, our key results on the importance of nonlinearities hold when considering density forecasts.<sup>4</sup>

We find that the evolution of economic uncertainty and financial conditions are important drivers of the NL treatment effect. ML nonlinearities are particularly useful: (i) when the level of macroeconomic uncertainty is high; (ii) when financial conditions are tight; and (iii) during housing bubble bursts. The effects are bigger in the case of data-rich models, which suggests that combining nonlinearity with factors made of many predictors is an accurate way to capture complex macroeconomic relationships.

These results give a clear recommendation for practitioners. For most cases, one may first reduce dimensionality using principal components and then augment the standard diffusion indices model by a generic ML nonlinear function approx-

<sup>2</sup>Moshiri and Cameron (2000), Nakamura (2005), and Marcellino (2008) use neural networks to predict inflation and Cook and Smalter Hall (2017) explore deep learning. Sermpinis et al. (2014) apply support vector regressions, while Diebold and Shin (2019) propose a LASSO-based forecast combination technique. Ng (2014), Döpke et al. (2017), and Medeiros et al. (2019) improve forecast accuracy with random forests and boosting, while Yousuf and Ng (2019) use boosting for high-dimensional predictive regressions with time varying parameters. Others compare machine learning methods in horse races (Ahmed et al., 2010; Chen et al., 2019; Kim & Swanson, 2018; Li & Chen, 2014; Milunovich, 2020; Smeekes & Wijler, 2018; Stock & Watson, 2012b). Works such as Joseph (2019) and Zhao and Hastie (2019) contribute to the interpretability of a given model.

<sup>3</sup>These novel empirical results also complement a growing theoretical literature on nonlinear ML methods beyond the assumption of independent observations (Alquier et al., 2013). Mohri and Rostamizadeh (2010) provide generalization bounds for Support Vector Machines and Regressions, and Kernel Ridge Regression under the assumption of a stationary joint distribution of predictors and target variable. Kuznetsov and Mohri (2015) generalize some of those results to non-stationary distributions and non-mixing processes. Davis et al. (2020) provides consistency for Random Forest in a time series context.

<sup>4</sup>While they are relatively robust, these results rely on empirical data. More conclusive answers and some additional clarity may be obtained by exploring them in Monte Carlo simulations.

imator. That recommendation is conditional on being able to keep overfitting in check. To that end, if cross-validation must be applied to hyperparameter selection, the best practice is the standard K-fold.

In the remainder of this paper, we first present the general prediction problem with machine learning and big data. Section 3 describes the four features of machine learning methods. Section 4 presents the empirical setup, Section 5 discusses the main results, followed by Section 6 that aims to open the black box. Section 7 present results from density forecasting. Section 8 concludes. Appendices A–E contain, respectively, tables with overall performance, robustness of treatment analysis, additional results, robustness of nonlinearity analysis, and density forecasting details. The supporting information contains the results for absolute loss, for quarterly US data and for monthly Canadian data, the description of CV techniques, and technical details on forecasting models.

## 2 | MAKING PREDICTIONS WITH MACHINE LEARNING AND BIG DATA

Machine learning methods are meant to improve our predictive ability especially when the “true” model is unknown and complex. To illustrate this point, let  $y_{t+h}$  be the variable to be predicted  $h$  periods ahead (target) and  $Z_t$  the  $N_Z$ -dimensional vector of predictors made out of  $H_t$ , the set of all the inputs available at time  $t$ . Let  $g^*(Z_t)$  be the true model and  $g(Z_t)$  a functional (parametric or not) form selected by the practitioner. In addition, denote  $\hat{g}(Z_t)$  and  $\hat{y}_{t+h}$  the fitted model and its forecast. The forecast error can be decomposed as

$$y_{t+h} - \hat{y}_{t+h} = \underbrace{g^*(Z_t) - g(Z_t)}_{\text{approximation error}} + \underbrace{g(Z_t) - \hat{g}(Z_t)}_{\text{estimation error}} + e_{t+h}. \quad (1)$$

The intrinsic error  $e_{t+h}$  is not shrinkable, while the estimation error can be reduced by adding more data. The approximation error is controlled by the functional estimator choice. While it can be minimized by using flexible functions, it raises the risk of overfitting and a judicious regularization is needed. This can be embedded in the prediction setup (Hastie et al., 2009)

$$\min_{g \in \mathcal{G}} \{\hat{L}(y_{t+h}, g(Z_t)) + pen(g; \tau)\}, \quad t = 1, \dots, T. \quad (2)$$

This setup has four main features:

1.  $\mathcal{G}$  is the space of possible functions  $g$  that combine the data to form the prediction. In particular, the interest is how much nonlinearities can we allow for in order to reduce the approximation error in (1)?
2.  $pen()$  is the regularization penalty limiting the flexibility of the function  $g$  and hence controlling the overfitting risk. This is quite general and can accommodate Bridge-type penalties and dimension reduction techniques.
3.  $\tau$  is the set of hyperparameters including those in the penalty and the approximator  $g$ . The usual problem is to choose the best data-driven method to optimize  $\tau$ .
4.  $\hat{L}$  is the loss function that defines the optimal forecast. Some ML models feature an in-sample loss function different from the standard  $l_2$  norm.

Most of (supervised) machine learning consists of a combination of those ingredients and popular methods like linear (penalized) regressions can be obtained as special cases of (2).

### 2.1 | Predictive modeling

We consider the *direct* predictive modeling in which the target is projected on the information set, and the forecast is made directly using the most recent observables. This is opposed to *iterative* approach where the model recursion is used to simulate the future path of the variable.<sup>5</sup> Also, the direct approach is the standard practice for in ML applications.

We now define the forecast objective given the variable of interest  $Y_t$ . If  $Y_t$  is stationary, we forecast its level  $h$  periods ahead:

$$y_{t+h}^{(h)} = y_{t+h}, \quad (3)$$

<sup>5</sup>Marcellino et al. (2006) conclude that the direct approach provides slightly better results but does not dominate uniformly across time and series. See Chevillon (2007) for a survey on multi-step forecasting.

where  $y_t \equiv \ln Y_t$  if  $Y_t$  is strictly positive. If  $Y_t$  is I(1), then we forecast the average growth rate over the period  $[t+1, t+h]$  (Stock & Watson, 2002b). We shall therefore define  $y_{t+h}^{(h)}$  as follows:

$$y_{t+h}^{(h)} = (1/h) \ln(Y_{t+h}/Y_t). \quad (4)$$

In order to avoid a cumbersome notation, we use  $y_{t+h}$  instead of  $y_{t+h}^{(h)}$  in what follows. In addition, all the predictors in  $Z_t$  are assumed to be covariance stationary.

## 2.2 | Data-poor versus data-rich environments

Large time series panels are now widely constructed and used for macroeconomic analysis. The most popular is FRED-MD monthly panel of US variables constructed by McCracken and Ng (2016).<sup>6</sup> Unfortunately, the performance of standard econometric models tends to deteriorate as the dimensionality of data increases.

Stock and Watson (2002b) first proposed to solve the problem by replacing the high-dimensional predictor set by common factors.<sup>7</sup>

On other hand, even though the machine learning models do not require big data, they are useful to perform variable selection and digest large information sets to improve the prediction. Therefore, in addition to treatment effects in terms of characteristics of forecasting models, we will also interact those with the width of the sample. The data-poor, defined as  $H_t^-$ , will only contain a finite number of lagged values of the target, while the data-rich panel, defined as  $H_t^+$  will also include a large number of exogenous predictors. Formally,

$$H_t^- \equiv \{y_{t-j}\}_{j=0}^{p_y} \text{ and } H_t^+ \equiv \left[ \{y_{t-j}\}_{j=0}^{p_y}, \{X_{t-j}\}_{j=0}^{p_f} \right]. \quad (5)$$

The analysis we propose can thus be summarized in the following way. We will consider two standard models for forecasting.

1. The  $H_t^-$  model is the *autoregressive direct* (AR) model, which is specified as follows:

$$y_{t+h} = c + \rho(L)y_t + e_{t+h}, \quad t = 1, \dots, T, \quad (6)$$

where  $h \geq 1$  is the forecasting horizon. The only hyperparameter in this model is  $p_y$ , the order of the lag polynomial  $\rho(L)$ .

2. The  $H_t^+$  workhorse model is the autoregression augmented with diffusion indices (ARDI) from Stock and Watson (2012b):

$$y_{t+h} = c + \rho(L)y_t + \beta(L)F_t + e_{t+h}, \quad t = 1, \dots, T \quad (7)$$

$$X_t = \Lambda F_t + u_t \quad (8)$$

where  $F_t$  are  $K$  consecutive static factors, and  $\rho(L)$  and  $\beta(L)$  are lag polynomials of orders  $p_y$  and  $p_f$  respectively. The feasible procedure requires an estimate of  $F_t$  that is usually obtained by principal component analysis (PCA).

Then, we will take these models as two types of “patients” and will administer them one ML treatment or combinations of them. That is, we will upgrade them with one or many features of ML and evaluate the gains/losses in both environments. From the perspective of the ML literature, Equation (8) motivates the use of PCA as a form of feature engineering. Although more sophisticated methods have been used<sup>8</sup>, PCA remains popular (Uddin et al., 2018). As we insist on treating models as symmetrically as possible, we will use the same feature transformations throughout such that nonlinear

<sup>6</sup>Fortin-Gagnon et al. (2020) have recently proposed similar data for Canada.

<sup>7</sup>Another way to approach the dimensionality problem is to use Bayesian methods. Indeed, some of our Ridge regressions will look like a direct version of a Bayesian VAR with a Litterman (1979) prior. Giannone et al. (2015) have shown that an hierarchical prior can lead the BVAR to perform as well as a factor model.

<sup>8</sup>The autoencoder method of Gu et al. (2020a) can be seen as a form of feature engineering, just as the independent components used in conjunction with SVR in Lu et al. (2009).

models will introduce nonlinear transformations of lagged target values and of lagged values of the principal components. Hence, nonlinear models postulate that a sparse set of latent variables impact the target in a flexible way.<sup>9</sup>

## 2.3 | Evaluation

The objective of this paper is to disentangle important characteristics of the ML prediction algorithms when forecasting macroeconomic variables. To do so, we design an *experiment* that consists of a pseudo-out-of-sample (POOS) forecasting horse race between many models that differ with respect to the four main features above, that is, nonlinearity, regularization, hyperparameter selection, and loss function. To create variation around those *treatments*, we will generate forecast errors from different models associated to each feature.

To test this paper's hypothesis, suppose the following model for forecasting errors

$$e_{t,h,v,m}^2 = \alpha_m + \psi_{t,v,h} + \nu_{t,h,v,m} \quad (9a)$$

$$\alpha_m = \alpha'_F \mathbf{1} + \eta_m \quad (9b)$$

where  $e_{t,h,v,m}^2$  are squared prediction errors of model  $m$  for variable  $v$  and horizon  $h$  at time  $t$ .  $\psi_{t,v,h}$  is a fixed effect term that demeans the dependent variable by “forecasting target,” that is a combination of  $t$ ,  $v$  and  $h$ .  $\alpha_F$  is a vector of  $\alpha_G$ ,  $\alpha_{pen()}$ ,  $\alpha_\tau$  and  $\alpha_L$  terms associated to each feature. We re-arrange Equation (9) to obtain

$$e_{t,h,v,m}^2 = \alpha'_F \mathbf{1} + \psi_{t,v,h} + u_{t,h,v,m}. \quad (10)$$

$H_0$  is now  $\alpha_f = 0 \forall f \in F = [G, pen(), \tau, \hat{L}]$ . In other words, the null is that there is no predictive accuracy gain with respect to a base model that does not have this particular feature.<sup>10</sup> By interacting  $\alpha_F$  with other fixed effects or variables, we can test many hypotheses about the heterogeneity of the “ML treatment effect.” To get interpretable coefficients, we define  $R_{t,h,v,m}^2 \equiv 1 - \frac{e_{t,h,v,m}^2}{\sum_{t=1}^T (y_{v,t+h} - \bar{y}_{v,h})^2}$  and run

$$R_{t,h,v,m}^2 = \dot{\alpha}'_F \mathbf{1} + \dot{\psi}_{t,v,h} + \dot{u}_{t,h,v,m}. \quad (11)$$

While (10) has the benefit of connecting directly with the specification of a Diebold and Mariano (1995) test, the transformation of the regressand in (11) has two main advantages justifying its use. First and foremost, it provides standardized coefficients  $\dot{\alpha}_F$  interpretable as marginal improvements in OOS- $R^2$ 's. In contrast,  $\alpha_F$  are a unit- and series-dependant marginal increases in MSE. Second, the  $R^2$  approach has the advantage of standardizing *ex-ante* the regressand and removing an obvious source of  $(v, h)$ -driven heteroskedasticity.

While the generality of (10) and (11) is appealing, when investigating the heterogeneity of specific partial effects, it will be much more convenient to run specific regressions for the multiple hypothesis we wish to test. That is, to evaluate a feature  $f$ , we run

$$\forall m \in \mathcal{M}_f : R_{t,h,v,m}^2 = \dot{\alpha}_f + \dot{\phi}_{t,v,h} + \dot{u}_{t,h,v,m} \quad (12)$$

where  $\mathcal{M}_f$  is defined as the set of models that differs only by the feature under study  $f$ . An analogous evaluation setup has been considered in Carriero et al. (2019).

## 3 | FOUR FEATURES OF ML

In this section we detail the forecasting approaches that create variations for each characteristic of the machine learning prediction problem defined in (2).

<sup>9</sup>We omit considering a VAR as an additional option. VAR iterative approach to produce  $h$ -step-ahead predictions is not comparable with the direct forecasting used with ML models.

<sup>10</sup>If we consider two models that differ in one feature and run this regression for a specific  $(h, v)$  pair, the  $t$ -test on coefficients amounts to Diebold and Mariano (1995)—conditional on having the proper standard errors.

### 3.1 | Feature 1: Nonlinearity

Although linearity is popular in practice, if the data generating process (DGP) is complex, using linear  $g$  introduces approximation error as shown in (1). As a solution, ML proposes an apparatus of nonlinear functions able to estimate the true DGP and thus reduces the approximation error. We focus on applying the kernel trick and random forests to our two baseline models to see if the nonlinearities they generate will lead to significant improvements.<sup>11</sup>

#### 3.1.1 | Kernel ridge regression

A simple way to make predictive regressions (6) and (7) nonlinear is by considering a generalized linear model with many expansions based out of original regressors. However, creating all possible interactions and higher order terms quickly becomes unmanageable. The *kernel trick* allows to obtain such nonlinearities without the aforementioned burden. A *Kernel Ridge Regression* (KRR) has several implementation advantages. It has a closed-form solution ruling out convergence problems which are inevitably frequent with gradient descent. It is also fast to implement since it implies inverting a  $T \times T$  matrix. To show how KT is implemented in our benchmark models, suppose a Ridge regression direct forecast with generic regressors  $Z_t$

$$\min_{\beta} \sum_{t=1}^T (y_{t+h} - Z_t \beta)^2 + \lambda \sum_{k=1}^K \beta_k^2.$$

The solution to that problem is  $\hat{\beta} = (Z'Z + \lambda I_k)^{-1}Z'y$ . By the representer theorem of Smola and Schölkopf (2004),  $\beta$  can also be obtained by solving the dual of the convex optimization problem above. The dual solution for  $\beta$  is  $\hat{\beta} = Z'(ZZ' + \lambda I_T)^{-1}y$ . This equivalence allows to rewrite the conditional expectation in the following way:

$$\hat{E}(y_{t+h}|Z_t) = Z_t \hat{\beta} = \sum_{i=1}^t \hat{\alpha}_i \langle Z_i, Z_t \rangle$$

where  $\hat{\alpha} = (ZZ' + \lambda I_T)^{-1}y$  is the solution to the dual Ridge Regression problem.

Suppose now we approximate a general nonlinear model  $g(Z_t)$  with basis functions  $\phi()$

$$y_{t+h} = g(Z_t) + \varepsilon_{t+h} = \phi(Z_t)' \gamma + \varepsilon_{t+h}.$$

The so-called kernel trick is the fact that there exist a reproducing kernel  $K()$  such that

$$\hat{E}(y_{t+h}|Z_t) = \sum_{i=1}^t \hat{\alpha}_i \langle \phi(Z_i), \phi(Z_t) \rangle = \sum_{i=1}^t \hat{\alpha}_i K(Z_i, Z_t).$$

This means we do not need to specify the numerous basis functions, a well-chosen kernel implicitly replicates them. This paper will use the standard radial basis function (RBF) kernel

$$K_\sigma(\mathbf{x}, \mathbf{x}') = \exp\left(-\frac{\|\mathbf{x} - \mathbf{x}'\|^2}{2\sigma^2}\right)$$

<sup>11</sup> A popular approach to model nonlinearity is deep learning. However, since we re-optimize our models recursively in a POOS, selecting an accurate network architecture by cross-validation is practically infeasible. In addition to optimize numerous neural net hyperparameters (such as the number of hidden layers and neurons, and activation function), our forecasting models also require careful input selection (number of lags and number of factors in case of data-rich). An alternative is to fix ex ante a variety of networks as in Gu et al. (2020b), but this would potentially benefit other models that are optimized over time. Still, since few papers have found similar predictive ability of random forests and neural nets (Gu et al., 2020a; Joseph, 2019), we believe that considering random forests and the kernel trick is enough to properly identify the ML nonlinear treatment. Moreover, it is known that deep learning's edge (over tree-based methods) is usually observed in environments that have little to do with our own—that is, when considering datasets with a very large number of observations, or non-tabular data (like images or speech sequences). Nevertheless, we have conducted a robustness analysis with feed-forward neural networks and boosted trees. The results are presented in Appendix D.

where  $\sigma$  is a tuning parameter to be chosen by cross-validation. This choice of kernel is motivated by its good performance in macroeconomic forecasting as reported in Sermpinis et al. (2014) and Exterkate et al. (2016). The advantage of the kernel trick is that, by using the corresponding  $Z_t$ , we can easily make our data-rich or data-poor model nonlinear. For instance, in the case of the factor model, we can apply it to the regression equation to implicitly estimate

$$y_{t+h} = c + g(Z_t) + \varepsilon_{t+h}, \quad (13)$$

$$Z_t = \left[ \{y_{t-j}\}_{j=0}^{p_y}, \{F_{t-j}\}_{j=0}^{p_f} \right], \quad (14)$$

$$X_t = \Lambda F_t + u_t. \quad (15)$$

In terms of implementation, this means extracting factors via PCA and then getting

$$\hat{E}(y_{t+h}|Z_t) = K_\sigma(Z_t, Z)(K_\sigma(Z_t, Z) + \lambda I_T)^{-1}y_t. \quad (16)$$

The final set of tuning parameters for such a model is  $\tau = \{\lambda, \sigma, p_y, p_f, n_f\}$ .

### 3.1.2 | Random forests

Another way to introduce nonlinearity in the estimation of the predictive Equation (7) is to use regression trees instead of OLS. The idea is to split sequentially the space of  $Z_t$ , as defined in (14) into several regions and model the response by the mean of  $y_{t+h}$  in each region. The process continues according to some stopping rule. The details of the recursive algorithm can be found in Hastie et al. (2009). Then, the tree regression forecast has the following form:

$$\hat{f}(Z) = \sum_{m=1}^M c_m I_{(Z \in R_m)}, \quad (17)$$

where  $M$  is the number of terminal nodes,  $c_m$  are node means and  $R_1, \dots, R_M$  represents a partition of feature space. In the diffusion indices setup, the regression tree would estimate a nonlinear relationship linking factors and their lags to  $y_{t+h}$ . Once the tree structure is known, it can be related to a linear regression with dummy variables and their interactions.

While the idea of obtaining nonlinearities via decision trees is intuitive and appealing—especially for its interpretability potential, the resulting prediction is usually plagued by high variance. The recursive tree fitting process is (i) unstable and (ii) prone to overfitting. The latter can be partially addressed by the use of pruning and related methodologies (Hastie et al., 2009). Notwithstanding, a much more successful (and hence popular) fix was proposed in Breiman (2001): random forests. This consists in growing many trees on subsamples of observations. Further randomization of underlying trees is obtained by considering a random subset of regressors for each potential split.<sup>12</sup> The main hyperparameter to be selected is the number of variables to be considered at each split. The forecasts of the estimated regression trees are then averaged to make one single “ensemble” prediction of the targeted variable.

## 3.2 | Feature 2: Regularization

In this section we will only consider models where dimension reduction is needed, which are the models with  $H_t^+$ . The traditional shrinkage method used in macroeconomic forecasting is the ARDI model that consists of extracting principal components of  $X_t$  and to use them as data in an ARDL model. Obviously, this is only one out of many ways to compress the information contained in  $X_t$  to run a well-behaved regression of  $y_{t+h}$  on it.<sup>13</sup>

In order to create identifying variations for *pen()* treatment, we need to generate multiple different shrinkage schemes. Some will also blend in selection, some will not. The alternative shrinkage methods will all be special cases of the elastic

<sup>12</sup>Only using a bootstrap sample of observations would be a procedure called Bagging. Selecting randomly regressors has the effect of decorrelating the trees and hence improving variance reduction of averaging them.

<sup>13</sup>De Mol et al. (2008) compares Lasso, Ridge and ARDI and finds that forecasts are very much alike.

net (EN) problem:

$$\min_{\beta} \sum_{t=1}^T (y_{t+h} - Z_t \beta)^2 + \lambda \sum_{k=1}^K (\zeta |\beta_k| + (1 - \zeta) \beta_k^2) \quad (18)$$

where  $Z_t = B(H_t)$  is a transformation of the original predictive set  $X_t$ .  $\zeta \in [0, 1]$  and  $\lambda > 0$  can either be fixed or found via CV. By using different  $B$  operators, we get shrinkage schemes. Also, by setting  $\zeta$  to either 1 or 0 we generate LASSO and Ridge Regression respectively. These possibilities are alternatives to the factor hard-thresholding procedure that is ARDI.

Each type of shrinkage in this section will be defined by the tuple  $S = \{\zeta, B()\}$ . To begin with the most straightforward dimension, for a given  $B$ , we will evaluate the results for  $\zeta \in \{0, \hat{\zeta}_{CV}, 1\}$ . For instance, if  $B$  is the identity mapping, we get in turns the LASSO, EN and Ridge shrinkage. We now detail different  $pen()$  resulting when we vary  $B()$  for a fixed  $\zeta$ .

1. **(Fat Regression)**: First, we consider the case  $B_1() = I()$ . That is, we use the entirety of the untransformed high-dimensional data set. The results of Giannone et al. (2018) point in the direction that specifications with a higher  $\zeta$  should do better, that is, sparse models do worse than models where every regressor is kept but shrunk to zero.
2. **(Big ARDI)**: Second,  $B_2()$  corresponds to first rotating  $X_t \in \mathbb{R}^N$  so that we get  $N$ -dimensional uncorrelated  $F_t$ . Contrary to the ARDI approach, we do not select  $F_t$  recursively, we keep them all to preserve the same information span as  $X_t$ . Comparing LASSO and Ridge will allow to verify whether sparsity emerges in a rotated space.
3. **(Principal component regression)**: A third possibility is to rotate  $H_t^+$  rather than  $X_t$  and still keep all the factors.  $H_t^+$  includes all the relevant preselected lags. If we were to just drop the  $F_t$  using some hard-thresholding rule, this would correspond to principal component regression (PCR). Note that  $B_3() = B_2()$  only when no lags are included.

Hence, the tuple  $S$  has a total of 9 elements. Since we will be considering both POOS-CV and K-fold CV for each of these models, this leads to a total of 18 models.<sup>14</sup>

To see clearly through all of this, we describe where the benchmark ARDI model stands in this setup. Since it uses a hard thresholding rule that is based on the eigenvalues ordering, it cannot be a special case of the EN problem. While it uses  $B_2$ , we would need to set  $\lambda = 0$  and select  $F_t$  *a priori* with a hard-thresholding rule. The closest approximation in this EN setup would be to set  $\zeta = 1$  and fix the value of  $\lambda$  to match the number of consecutive factors selected by an information criterion directly in the predictive regression (7).

### 3.3 | Feature 3: Hyperparameter optimization

The conventional wisdom in macroeconomic forecasting is to use information criteria. The prime reason for the popularity of CV is that it can be applied to any model, including those for which the derivation of an information criterion is impossible.<sup>15</sup> It is not obvious that CV should work better only because it is “out of sample” while AIC and BIC are “in sample.” All model selection methods are approximations to the OOS prediction error relying on different assumptions/approximations.<sup>16</sup> Hence, it is nearly impossible *a priori* to think of one model selection technique being the most appropriate for macroeconomic forecasting.

For small samples encountered in macro, the question of which one is optimal in the forecasting sense is inevitably an empirical one. For instance, Granger and Jeon (2004) compared AIC and BIC in a generic forecasting exercise. In this paper, we will compare AIC, BIC and two types of CV for our two baseline models. The two types of CV are POOS CV and K-fold CV. The first one behaves correctly in the context of time series data, but may be inefficient by only using the end of the training set. The latter provides a valid estimation of the prediction MSE only if residual autocorrelation is absent (Bergmeir et al., 2018). If it were not to be the case, then we should expect K-fold to underperform at estimating the “true” MSE. However, how a *ranking* of cross-validation MSEs with respect to a given hyperparameter could be distorted by serial dependence remains unclear. The specific details of the implementation of both CVs is discussed in Appendix S5.

<sup>14</sup>Adaptive versions (in the sense of Zou (2006)) of the 9 models were also considered but gave either similar or deteriorated results with respect to their plain counterparts.

<sup>15</sup>Abadie and Kasy (2019) show that hyperparameter tuning by CV performs uniformly well in high-dimensional context.

<sup>16</sup>Asymptotically, these methods have similar behavior. Hansen and Timmermann (2015) show equivalence between test statistics for OOS forecasting performance and in-sample Wald statistics. For instance, one can show that Leave-one-out CV is asymptotically equivalent to the Takeuchi Information criterion (TIC, (Claeskens & Hjort, 2008)). AIC is a special case of TIC under assumption that all models being considered are at least correctly specified. Thus, under the latter assumption, Leave-one-out CV is asymptotically equivalent to AIC.

The contributions of this section are twofold. First, it will shed light on which model selection method is most appropriate for typical macroeconomic data and models. Second, we will explore how much of the gains/losses of using ML can be attributed to widespread use of CV. Since most nonlinear ML models cannot be easily tuned by anything other than CV, it is hard for the researcher to disentangle between gains coming from the ML method itself or just the way it is tuned. Hence, it is worth asking the question whether some gains from ML are simply coming from selecting hyperparameters differently. To investigate that, a natural first step is to look at our benchmark macro models, AR and ARDI, and see if using CV selects different models and how it affects forecasting performances.

### 3.4 | Feature 4: Loss function

All models presented thus far use a quadratic loss function which is natural since the quadratic loss is also used for out-of-sample evaluation. Thus, one may legitimately wonder if the fate of the SVR is not sealed in advance as it uses an in-sample loss function which is inconsistent with the out-of-sample performance metric. As we will discuss after the presentation of the SVR, there are reasons to believe the alternative (and mismatched) loss function can help. As a matter of fact, SVR has been successfully applied to forecasting financial and macroeconomic time series.<sup>17</sup> An important question remains unanswered: are the good results due to kernel-based nonlinearities or to the use of an alternative loss function?

We provide a strategy to isolate the marginal effect of the SVR's  $\bar{\epsilon}$ -insensitive loss function which consists in, perhaps unsurprisingly by now, estimating different variants of the same model. To isolate the “treatment effect” of a different in-sample loss function, we consider: (1) the linear SVR with  $H_t^-$ ; (2) the linear SVR with  $H_t^+$ ; (3) the RBF Kernel SVR with  $H_t^-$ ; and (4) the RBF Kernel SVR with  $H_t^+$ .

What follows is a bird's-eye overview of the underlying mechanics of the SVR. As it was the case for the Kernel Ridge regression, the SVR estimator approximates the function  $g \in G$  with basis functions, but it chooses a weight vector that will ignore the contribution of points that are “close” to its fitted values. The  $\epsilon$ -SVR is defined by

$$\begin{aligned} \min_{\gamma} \frac{1}{2} \gamma' \gamma + C \left[ \sum_{t=1}^T (\xi_t + \xi_t^*) \right] \\ \text{s.t. } \begin{cases} y_{t+h} - \gamma' \phi(Z_t) - c \leq \bar{\epsilon} + \xi_t \\ \gamma' \phi(Z_t) + c - y_{t+h} \leq \bar{\epsilon} + \xi_t^* \\ \xi_t, \xi_t^* \geq 0. \end{cases} \end{aligned}$$

where  $\xi_t, \xi_t^*$  are slack variables,  $\phi()$  is the basis function of the feature space implicitly defined by the kernel,  $\gamma$  are the related weights,  $c$  is a constant, and  $T$  is the size of the sample used for estimation.  $C$  and  $\bar{\epsilon}$  are hyperparameters, the latter defining an insensitivity tube twice its size around predicted values. In case of the RBF kernel, a scale parameter  $\sigma$  also has to be cross-validated. Associating Lagrange multipliers  $\lambda_j, \lambda_j^*$  to the first two types of constraints and moving to the dual problem, Smola and Schölkopf (2004) show that the optimal weights are  $\gamma = \sum_{j=1}^T (\lambda_j - \lambda_j^*) \phi(Z_j)$  and the forecasted values are

$$\hat{E}(y_{t+h}|Z_t) = \hat{c} + \sum_{j=1}^T (\lambda_j - \lambda_j^*) \phi(Z_j) \phi(Z_j) = \hat{c} + \sum_{j=1}^T (\lambda_j - \lambda_j^*) K(Z_j, Z_t). \quad (19)$$

By the Karush–Kuhn–Tucker conditions, only points outside the insensitivity tube have nonzero Lagrange multipliers making them the only points that contribute to the weight vector  $\gamma$ . It can be shown that the loss function associated with the  $\epsilon$ -SVR is

$$P_{\bar{\epsilon}}(e_{t+h|t}) := \begin{cases} 0 & \text{if } |e_{t+h}| \leq \bar{\epsilon} \\ |e_{t+h}| - \bar{\epsilon} & \text{otherwise} \end{cases}.$$

We can recover the absolute loss as the special case  $\bar{\epsilon} = 0$  whereas the previous case of quadratic loss would be  $P(e_{t+h}) := e_{t+h}^2$ . Note that for our other estimators, the rate of the penalty increases with the size of the forecasting error, but for  $\epsilon$ -SVR the penalty increases at a constant rate once errors are sufficiently large.

<sup>17</sup>See, for example, Lu et al. (2009), Choudhury et al. (2014), Patel et al. (2015a), Patel et al. (2015b), Yeh et al. (2011) and Qu and Zhang (2016) for financial forecasting. See Sermpinis et al. (2014) and Zhang et al. (2010) macroeconomic forecasting.

As discussed briefly earlier, given that SVR forecasts will eventually be evaluated according to a quadratic loss, it is reasonable to ask why this alternative loss function isn't trivially suboptimal. Smola et al. (1998) show that the optimal size of  $\bar{\epsilon}$  is a linear function of the underlying noise, with the exact relationship depending on the nature of the data generating

TABLE 1 List of all forecasting models

Models	Feature 1: selecting the function $g$	Feature 2: selecting the regularization	Feature 3: optimizing hyperparameters $\tau$	Feature 4: selecting the loss function
Data-poor models				
AR,BIC	Linear		BIC	Quadratic
AR,AIC	Linear		AIC	Quadratic
AR,POOS-CV	Linear		POOS CV	Quadratic
AR,K-fold	Linear		K-fold CV	Quadratic
RRAR,POOS-CV	Linear	Ridge	POOS CV	Quadratic
RRAR,K-fold	Lineal	Ridge	K-fold CV	Quadratic
RFAR,POOS-CV	Nonlinear		POOS CV	Quadratic
RFAR,K-fold	Nonlinear		K-fold CV	Quadratic
KRRAR,POOS-CV	Nonlinear	Ridge	POOS CV	Quadratic
KRRAR,K-fold	Nonlinear	Ridge	K-fold CV	Quadratic
SVR-AR,Lin,POOS-CV	Linear	Ridge	POOS CV	$\bar{\epsilon}$ -insensitive
SVR-AR,Lin,K-fold	Linear	Ridge	K-fold CV	$\bar{\epsilon}$ -insensitive
SVR-AR,RBF,POOS-CV	Nonlinear	Ridge	POOS CV	$\bar{\epsilon}$ -insensitive
SVR-AR,RBF,K-fold	Nonlinear	Ridge	K-fold CV	$\bar{\epsilon}$ -insensitive
Data-rich models				
ARDI,BIC	Linear	PCA	BIC	Quadratic
ARDI,AIC	Linear	PCA	AIC	Quadratic
ARDI,POOS-CV	Linear	PCA	POOS CV	Quadratic
ARDI,K-fold	Linear	PCA	K-fold CV	Quadratic
RRARDI,POOS-CV	Linear	Ridge-PCA	POOS CV	Quadratic
RRARDI,K-fold	Linear	Ridge-PCA	K-fold CV	Quadratic
RFARDI,POOS-CV	Nonlinear	PCA	POOS CV	Quadratic
RFARDI,K-fold	Nonlinear	PCA	K-fold CV	Quadratic
KRRARDI,POOS-CV	Nonlinear	Ridge-PCA	POOS CV	Quadratic
KRRARDI,K-fold	Nonlinear	Ridge-PCA	K-fold CV	Quadratic
( $B_1, \zeta = \hat{\zeta}$ ),POOS-CV	Linear	EN	POOS CV	Quadratic
( $B_1, \zeta = \hat{\zeta}$ ),K-fold	Linear	EN	K-fold CV	Quadratic
( $B_1, \zeta = 1$ ),POOS-CV	Linear	Lasso	POOS CV	Quadratic
( $B_1, \zeta = 1$ ),K-fold	Linear	Lasso	K-fold CV	Quadratic
( $B_1, \zeta = 0$ ),POOS-CV	Linear	Ridge	POOS CV	Quadratic
( $B_1, \zeta = 0$ ),K-fold	Linear	Ridge	K-fold CV	Quadratic
( $B_2, \zeta = \hat{\zeta}$ ),POOS-CV	Linear	EN-PCA	POOS CV	Quadratic
( $B_2, \zeta = \hat{\zeta}$ ),K-fold	Linear	EN-PCA	K-fold CV	Quadratic
( $B_2, \zeta = 1$ ),POOS-CV	Linear	Lasso-PCA	POOS CV	Quadratic
( $B_2, \zeta = 1$ ),K-fold	Linear	Lasso-PCA	K-fold CV	Quadratic
( $B_2, \zeta = 0$ ),POOS-CV	Linear	Ridge-PCA	POOS CV	Quadratic
( $B_2, \zeta = 0$ ),K-fold	Linear	Ridge-PCA	K-fold CV	Quadratic
( $B_3, \zeta = \hat{\zeta}$ ),POOS-CV	Linear	EN-PCR	POOS CV	Quadratic
( $B_3, \zeta = \hat{\zeta}$ ),K-fold	Linear	EN-PCR	K-fold CV	Quadratic
( $B_3, \zeta = 1$ ),POOS-CV	Linear	Lasso-PCR	POOS CV	Quadratic
( $B_3, \zeta = 1$ ),K-fold	Linear	Lasso-PCR	K-fold CV	Quadratic
( $B_3, \zeta = 0$ ),POOS-CV	Linear	Ridge-PCR	POOS CV	Quadratic
( $B_3, \zeta = 0$ ),K-fold	Linear	Ridge-PCR	K-fold CV	Quadratic
SVR-ARDI,Lin,POOS-CV	Linear	Ridge-PCA	POOS CV	$\bar{\epsilon}$ -insensitive
SVR-ARDI,Lin,K-fold	Linear	Ridge-PCA	K-fold CV	$\bar{\epsilon}$ -insensitive
SVR-ARDI,RBF,POOS-CV	Nonlinear	Ridge-PCA	POOS CV	$\bar{\epsilon}$ -insensitive
SVR-ARDI,RBF,K-fold	Nonlinear	Ridge-PCA	K-fold CV	$\bar{\epsilon}$ -insensitive

Note: PCA stands for principal component analysis, EN for elastic net regularizer, PCR for principal component regression, and RBF for radial basis function (the kernel being used). Finally,  $B_1$ ,  $B_2$ ,  $B_3$ , and  $\zeta$  are defined in Section 3.2.

process. This idea is similar to Gu et al. (2020a) using the Huber Loss for asset pricing with ML (where outliers seldom happen in-sample) or Colombo and Pelagatti (2020) successfully using SVR to forecast (notoriously noisy) exchange rates.

To sum up, the Table 1 shows a list of all forecasting models and highlights their relationship with each of four features discussed above. The computational details for every model in this list are available in Appendix S6.

## 4 | EMPIRICAL SETUP

This section presents the data and the design of the pseudo-of-sample experiment used to generate the treatment effects above.

### 4.1 | Data

We use historical data to evaluate and compare the performance of all the forecasting models described previously. The dataset is FRED-MD, available at the Federal Reserve of St-Louis's web site. It contains 134 monthly US macroeconomic and financial indicators observed from 1960M01 to 2017M12. Since many of them are usually very persistent or not stationary, we follow McCracken and Ng (2016) in the choice of transformations in order to achieve stationarity.<sup>18</sup> Even though the universe of time series available at FRED is huge, we stick to FRED-MD for several reasons. First, we want to have the test set as long as possible and most of the variables do not start early enough. Second, most of the timely available series are disaggregated components of the variables in FRED-MD. Hence, adding them alters the estimation of common factors (Boivin & Ng, 2006) and induces too much collinearity for Lasso performance (Fan & Lv, 2010). Third, it is the standard high-dimensional dataset that has been extensively used in the macroeconomic literature.

### 4.2 | Variables of interest

We focus on predicting five representative macroeconomic indicators of the US economy: Industrial Production (INDPRO), Unemployment rate (UNRATE), Consumer Price Index (INF), difference between 10-year Treasury Constant Maturity rate and Federal funds rate (SPREAD) and housing starts (HOUST). INDPRO, CPI, and HOUST are assumed  $I(1)$ , so we forecast the average growth rate as in Equation (4). UNRATE is considered  $I(1)$ , and we target the average change as in (4) but without logs. SPREAD is  $I(0)$  and the target is as in (3).<sup>19</sup>

### 4.3 | Pseudo-out-of-sample experiment design

The pseudo-out-of-sample period is 1980M01–2017M12. The forecasting horizons considered are 1, 3, 9, 12, and 24 months. Hence, there are 456 evaluation periods for each horizon. All models are estimated recursively with an expanding window as means of erring on the side of including more data so as to potentially reduce the variance of more flexible models.<sup>20</sup>


Hyperparameter optimization is done with in-sample criteria (AIC and BIC) and two types of CV (POOS and K-fold). The in-sample selection is standard, we fix the upper bounds for the set of HPs. For the POOS CV, the validation set consists of last 25% of the in-sample. In case of K-fold CV, we set  $k = 5$ . We re-optimize hyperparameters every two years. This isn't uncommon for computationally demanding studies.<sup>21</sup> It is also reasonable to assume that optimal hyperparameters would not be terribly affected by expanding the training set with observations that account for 2–3% of the new training set size. The selection of second order hyperparameters is detailed in Appendix S6.

<sup>18</sup> Alternative data transformations in the context of ML modeling are used in Goulet Coulombe et al. (2020).

<sup>19</sup> The US CPI is sometimes modeled as  $I(2)$  due to the possible stochastic trend in inflation rate in the 1970s and 1980s, see Stock and Watson (2002b). Since in our test set the inflation is mostly stationary, we treat the price index as  $I(1)$ , as in Medeiros et al. (2019). We have compared the mean squared predictive errors of best models under  $I(1)$  and  $I(2)$  alternatives and found that errors are minimized when predicting the inflation rate directly.

<sup>20</sup> The alternative is that of a rolling window, which could be more robust to issues of model instability. These are valid concerns and have motivated methods for taking them into account (Boot & Pick, 2020; Inoue et al., 2017; Pesaran et al., 2013; Pesaran & Timmermann, 2007). We compared both approaches in Section B.2.

<sup>21</sup> Sermpinis et al. (2014), for example, split their out-of-sample into four year periods and update both hyperparameters and model parameter estimates every 4 years. Likewise, Teräsvirta (2006) selected the number of lagged values to be included in nonlinear autoregressive models once and for all at the start of the POOS.



**FIGURE 1** This figure plots the distribution of  $\hat{\alpha}_F^{(h,v)}$  from Equation (11) done by  $(h, v)$  subsets. That is, we are looking at the average partial effect on the pseudo-OOS  $R^2$  from augmenting the model with ML features, keeping everything else fixed.  $X$  is making the switch from data-poor to data-rich. Finally, variables are INDPRO, UNRATE, SPREAD, INF, and HOUST. Within a specific color block, the horizon increases from  $h = 1$  to  $h = 24$  as we are going down. As an example, we clearly see that the partial effect of  $X$  on the  $R^2$  of INF increases drastically with the forecasted horizon  $h$ . SEs are HAC. Lines around the bullets are the 95% confidence bands

#### 4.4 | Forecast evaluation metrics

Following a standard practice in the forecasting literature, we evaluate the quality of our point forecasts using the root mean square prediction error (MSPE). Diebold and Mariano (1995) (DM) procedure is used to test the predictive accuracy of each model against the reference (ARDI,BIC). We also implement the Model Confidence Set (MCS), (Hansen et al., 2011), that selects the subset of best models at a given confidence level. These metrics measure the overall predictive performance and classify models according to DM and MCS tests. Regression analysis from Section 2.3 is used to estimate the treatment effect of each ML ingredient.

### 5 | RESULTS

For the sake of space, we only present the results regarding the marginal effect of important features of ML using regressions described in Section 2.3. Tables containing the relative root MSPEs (to AR,BIC model) with DM and MCS outputs, for the whole pseudo-out-of-sample and NBER recession periods are in the Appendix A. Overall, those results show that using data-rich models and nonlinear g functions improves macroeconomic prediction and their marginal contribution depends on the state of the economy.

#### 5.1 | Disentangling ML treatment effects

In order to disentangle the marginal effects of ML features we turn to the regression analysis described in Section 2.3. In what follows, [X, NL, SH, CV, and LF] stand for data-rich, nonlinearity, alternative shrinkage, cross-validation, and loss function features respectively.


Figure 1 shows the distribution of  $\hat{\alpha}_F^{(h,v)}$  from Equation (11) done by  $(h, v)$  subsets. Hence, here we allow for heterogeneous treatment effects according to 25 different targets. This figure highlights by itself the main findings of this paper. **First**, ML nonlinearities improve substantially the forecasting accuracy in almost all situations. The effects are positive and significant for all horizons in case of INDPRO and SPREAD, and for most of the cases when predicting UNRATE, INF and HOUST. The improvements of the nonlinearity treatment reach up to 23% in terms of pseudo- $R^2$ . This is in contrast with previous literature that did not find substantial forecasting power from nonlinear methods; see for example, Stock and Watson (1999). In fact, the ML nonlinearity is highly flexible and well disciplined by a careful regularization, and thus can solve the general overfitting problem of standard nonlinear models (Teräsvirta, 2006). This is also in line with the finding in Gu et al. (2020b) that nonlinearities (from ML models) can help predicting financial returns.

**Second**, alternative regularization means of dimensionality reduction do not improve on average over the standard factor model, except few cases. Choosing sparse modeling can decrease the forecast accuracy by up to 20% of the pseudo- $R^2$  which is not negligible. Interestingly, Gu et al. (2020b) also reach similar conclusions that dense outperforms sparse in the context of applying ML to returns.

**Third**, the average effect of CV appears not significant. However, as we will see in Section 5.1.3, the averaging in this case hides some interesting and relevant differences between K-fold and POOS CVs. **Fourth**, on average, dropping the

**FIGURE 2** This figure plots the distribution of  $\hat{\alpha}_F^{(v)}$  and  $\hat{\alpha}_F^{(h)}$  from Equation (11) averaged across horizons (left) and targets (right). That is, we are looking at the average partial effect on the pseudo-OOS  $R^2$  from augmenting the model with ML features, keeping everything else fixed.  $X$  is making the switch from data-poor to data-rich. However, in this graph,  $v$ -specific heterogeneity and  $h$ -specific heterogeneity have been integrated out in turns. SEs are HAC. Lines around the bullets are the 95% confidence bands

## Distribution of averaged ML Treatment Effects



standard in-sample squared-loss function for what the SVR proposes is not useful, except in very rare cases. **Fifth** and lastly, the marginal benefits of data-rich models ( $X$ ) seems roughly to increase with horizons for every variable-horizon pair, except for few cases with spread and housing. Note that this is almost exactly like the picture we described for NL. Indeed, visually, it seems like the results for  $X$  are a compressed-range version of NL that was translated to the right. Seeing NL models as data augmentation via basis expansions, we conclude that for predicting macroeconomic variables, we need to augment the AR( $p$ ) model with more regressors either created from the lags of the dependent variable itself or coming from additional data. The possibility of joining these two forces to create a “data-filthy-rich” model is studied in Section 5.1.1.


The robustness of these findings is studied in the Appendix B. ML treatment effects plots of very similar shapes are obtained for data-poor models only (Figure B1), data-rich models only (Figure B2), and recessions/expansions periods (Figures B3 and B4). Nonlinearity effect is not only present during recession periods, but it is even more important during expansions.<sup>22</sup> The only exception is the data-rich feature that has negative and significant effects for housing starts prediction when we condition on the last 20 years of the forecasting exercise (Figure B5). The main findings remain valid when the exercise is conducted on real-time data vintages as shown in Section B.1 and Figure B6. Lastly, our main results are intact when replacing expanding window estimation for a rolling window approach as discussed in Section B.2 and depicted in Figure B7.

Figure 2 aggregates by  $h$  and  $v$  in order to clarify whether variable or horizon heterogeneity matters most. Two facts detailed earlier are now quite easy to see. For both  $X$  and NL, the average marginal effects roughly increase in  $h$ . In addition, it is now clear that all the variables benefit from both additional information and nonlinearities. Alternative shrinkage is least harmful for inflation and housing, and at short horizons. Cross-validation has negative and sometimes significant impacts, while the SVR loss function is often damaging.

Supporting information contains additional results. Appendix S1 shows the results obtained using the absolute loss. The importance of each feature and the way it behaves according to the variable/horizon pair is the same. In section B we show predictive performance results based on sign forecast test of Pesaran and Timmermann (1992). The ML models are very resilient, especially during recession periods. Appendices S3 and S4 show results for two similar exercises. The first consider quarterly US data where we forecast the average growth rate of GDP, consumption, investment and disposable income, and the PCE inflation. The results are consistent with the findings obtained in the main body of this paper. In the second, we use a large Canadian monthly dataset and forecast the same target variables for Canada. Results are qualitatively in line with those on US data, except that NL effect is smaller in size.


<sup>22</sup>This suggests that our models behave relatively similarly over the business cycle and that our analysis does not suffer from undesirable forecast ranking due to extreme events as pointed out in Lerch et al. (2017).

### Contribution of Non-Linearity, by variables



**FIGURE 3** This figure compares the two NL models averaged over all horizons. The unit of the x axis are improvements in OOS  $R^2$  over the basis model. SEs are HAC. Lines around the bullets are the 95% confidence bands

### Contribution of Non-Linearity, by horizons



**FIGURE 4** This figure compares the two NL models averaged over all variables. The unit of the x axis are improvements in OOS  $R^2$  over the basis model. SEs are HAC. These are the 95% confidence bands

In what follows we break down averages and run specific regressions as in (12) to study how homogeneous are the marginal effects reported above.


#### 5.1.1 | Nonlinearities

Figure 3 suggests that nonlinearities can be very helpful at forecasting all the five variables in the data-rich environment. The marginal effects of random forests and KRR are almost never statistically different for data-rich models, except for inflation combined with data-rich, suggesting that the common NL feature is the driving force. However, this is not the case for data-poor models where the kernel-type nonlinearity shows significant improvements for all variables, while the random forests have positive impact on predicting INDPRO and inflation, but decrease forecasting accuracy for the rest of the variables.

Figure 4 suggests that nonlinearities are in general more useful for longer horizons in data-rich environment while the KRR can be harmful for a very short horizon. Note again that both nonlinear models follow the same pattern for

**FIGURE 5** This figure compares models of Section 3.2 averaged over all variables and horizons. The unit of the  $x$  axis are improvements in OOS  $R^2$  over the basis model. The base models are ARDIs specified with POOS-CV and KF-CV respectively. SEs are HAC. These are the 95% confidence bands

### Alternative shrinkage wrt ARDI



data-rich models with RF often being better (but never statistically different from KRR). For data-poor models, it is KRR that has a (statistically significant) growing advantage as  $h$  increases. Seeing NL models as data augmentation via some basis expansions, we can join the two facts together to conclude that the need for a complex and “data-filthy-rich” model arises for predicting macroeconomic variables at longer horizons. Similar conclusions are obtained with neural networks and boosted trees as shown in Figures D1 and D2.

Figure C3 plots the cumulative and 3-year rolling window root MSPE for linear and nonlinear data-poor and data-rich models, for  $h = 12$ , as well as Giacomini and Rossi (2010) fluctuation test for those alternatives. The cumulative root MSPE clearly shows the positive impact on forecast accuracy of both nonlinearities and data-rich environment for all series except INF. The rolling window depicts the changing level of forecast accuracy. For all series except the SPREAD, there is a common cyclical behavior with two relatively similar peaks (1981 and 2008 recessions), as well as a drop in MSPE during the Great Moderation period. Fluctuation tests confirm the important role of nonlinear and data-rich models.

For CPI inflation at horizons of 3, 9, and 12 months, random forests perform distinctively well. In both its data-poor and data-rich incarnations, the algorithm is included in the superior model set of Hansen et al. (2011) and significantly outperforms the AR-BIC benchmark according to the DM test. This result can help shed some light on long-standing issues in the inflation forecasting literature. A consensus emerged that nonlinear models in-sample good performance does not materialize out-of-sample (Marcellino, 2008; Stock & Watson, 2009).<sup>23</sup> In contrast, we found—as in Medeiros et al. (2019), that random forests are a particularly potent tool to forecast CPI inflation. One possible explanation is that previous studies suffer from overfitting (Marcellino, 2008) while RF are arguably completely immune from it (Goulet Coulombe, 2020), all this while retaining relevant nonlinearities. In that regard, it is noted that INF is the only target where KRR performance does not match that of RF in the data-rich environment. In the data-poor case, roles are reversed. Unlike most other targets, it seems the type of NL being used matters for inflation. Nonetheless, ML generally appears to be useful for inflation forecasting by providing better-behaved non-parametric nonlinearities than what was considered by the older literature.

#### 5.1.2 | Regularization

Figure 5 shows that the ARDI reduces dimensionality in a way that certainly works well with economic data: all competing schemes do at most as good on average. It is overall safe to say that on average, all shrinkage schemes give similar

<sup>23</sup>Concurrently, simple benchmarks such as a random walk or moving averages emerged as surprisingly hard to beat (Atkeson & Ohanian, 2001; Stock & Watson, 2009; Kotchoni et al., 2019).

	(1) All	(2) Data-rich	(3) Data-poor	(4) Data-rich	(5) Data-poor
CV-KF	-0.0380 (0.800)	-0.314 (0.711)	0.237 (0.411)	-0.494 (0.759)	-0.181 (0.438)
CV-POOS	-1.351 (0.800)	-1.440* (0.711)	-1.262** (0.411)	-1.069 (0.759)	-1.454*** (0.438)
AIC	-0.509 (0.800)	-0.648 (0.711)	-0.370 (0.411)	-0.580 (0.759)	-0.812 (0.438)
CV-KF * Recessions				1.473 (2.166)	3.405** (1.251)
CV-POOS * Recessions				-3.020 (2.166)	1.562 (1.251)
AIC * Recessions				-0.550 (2.166)	3.606** (1.251)
Observations	91200	45600	45600	45600	45600

TABLE 2 CV comparison

Note: Displayed are  $\hat{\alpha}_f$ 's of Equation (12). HAC standard errors in parentheses.

\* $p < 0.05$ .

\*\* $p < 0.01$ .

\*\*\* $p < 0.001$ .

or lower performance, which is in line with conclusions from Stock and Watson (2012b) and Kim and Swanson (2018), but contrary to Smeekes and Wijler (2018). No clear superiority for the Bayesian versions of some of these models was also documented in De Mol et al. (2008). This suggests that the factor model view of the macroeconomy is quite accurate in the sense that when we use it as a means of dimensionality reduction, it extracts the most relevant information to forecast the relevant time series. This is good news. The ARDI is the simplest model to run and results from the preceding section tells us that adding nonlinearities to an ARDI can be quite helpful.

Obviously, the deceiving behavior of alternative shrinkage methods does not mean there are no interesting  $(h, v)$  cases where using a different dimensionality reduction has significant benefits as discussed in Appendix A and Smeekes and Wijler (2018). Furthermore, LASSO and Ridge can still be useful to tackle specific time series problems (other than dimensionality reduction), as shown with time-varying parameters in Coulombe (2019).


### 5.1.3 | Hyperparameter optimization

Different model selection methods lead to quite different models. Figure C1 shows how many regressors are kept by different selection methods in the case of ARDI. BIC is in general the lower envelope of each of these graphs. Both cross-validations favor larger models, especially when combined with Ridge regression.<sup>24</sup> There is a common upward trend for all model selection methods in case of INDPRO and UNRATE. This is not the case for inflation where large models have been selected in the 80s and most recently since 2005. In case of HOUST, there is a downward trend since the 2000s which is consistent with the finding in Figure B5 that data-poor models do better in last 20 years.


We now turn to the impact on predictions. First, let us note that changes in OOS- $R^2$  are much smaller in magnitude for CV (as can be seen easily in Figures 1 and 2) than for other studied ML treatment effects. Nevertheless, Table 2 tells many interesting tales. The models included in the regressions are the standard linear ARs and ARDIs (i.e., excluding the Ridge versions) that have all been tuned using BIC, AIC, POOS CV, and CV-KF. First, we see that overall, only POOS CV is distinctively worse, especially in data-rich environment, and that AIC and CV-KF are not significantly different from BIC on average. For data-poor models and during recessions, AIC and CV-KF are being significantly better than BIC in downturns, while CV-KF seems harmless. The state-dependent effects are not significant in data-rich environment. Hence, for that class of models, we can safely opt for either BIC or CV-KF. Assuming some degree of external validity beyond that

<sup>24</sup>POOS CV selection is more volatile and selects bigger models for unemployment rate, spread and housing. While K-fold also selects models of considerable size, it does so in a more slowly growing fashion. This is not surprising because K-fold samples from all available data to build the CV criterion: adding new data points only gradually change the average. POOS CV is a shorter window approach that offers flexibility against structural hyperparameters change at the cost of greater variance and vulnerability of rapid regime changes in the data.

**FIGURE 6** This figure compares the two CV methods averaged over all the models using them. The unit of the  $x$  axis are improvements in OOS  $R^2$  over the basis model. SEs are HAC. These are the 95% confidence bands



**FIGURE 7** This figure compares the two cross-validation (CV) methods averaged over all the models using them. The unit of the  $x$  axis are improvements in OOS  $R^2$  over the basis model. SEs are HAC. These are the 95% confidence bands




model class, we can be reassured that the quasi-necessity of leaving ICs behind when opting for more complicated ML models is not harmful.

We now consider models that are usually tuned by CV and compare the performance of the two CVs by horizon and variables. Since we are now pooling multiple models, including all the alternative shrinkage models, if a clear pattern only attributable to a certain CV existed, it would most likely appear in Figure 6. What we see are two things. First, CV-KF is at least as good as POOS CV on average for almost all variables and horizons, irrespective of the informational content of the regression. The exceptions are HOUST in data-rich and INF in data-poor frameworks, and the two-year horizon with large data. Figure 7's message has the virtue of clarity. POOS CV's failure is mostly attributable to its poor record in recessions periods for the first three variables at any horizon. Note that this is the same subset of variables that benefits from adding in more data ( $X$ ) and nonlinearities as discussed in 5.1.1.

By using only recent data, POOS CV will be more robust to gradual structural change but will perhaps have an Achilles heel in regime switching behavior. If the optimal hyperparameters are state-dependent, then a switch from expansion to

## Linear SVR Relative Performance to ARDI



**FIGURE 8** This graph displays the marginal (un)improvements by variables and horizons to opt for the SVR in-sample loss function in both recession and expansion periods. The unit of the  $x$  axis are improvements in OOS  $R^2$  over the basis model. SEs are HAC. These are the 95% confidence bands

recession at time  $t$  can be quite harmful. K-fold, by taking the average over the whole sample, is less immune to such problems. Since results in the Appendix A point in the direction that smaller models are better in expansions and bigger models in recessions, the behavior of CV and how it picks the effective complexity of the model can have an effect on overall predictive ability. This is exactly what we see in Figure 7: POOS CV is having a hard time in recessions with respect to K-fold.

### 5.1.4 | Loss function


In this section, we investigate whether replacing the  $l_2$  norm as an in-sample loss function for the SVR machinery helps in forecasting. We again use as baseline models ARs and ARDIs trained by the same corresponding CVs. The very nature of this ML feature is that the model is less sensitive to extreme residuals, thanks to the  $l_1$  norm outside of the  $\bar{\epsilon}$ -insensitivity tube. We first compare linear models in Figure 8. Clearly, changing the loss function is generally harmful and that is mostly due to recessions period. However, in expansions, the linear SVR is better on average than a standard ARDI for UNRATE and SPREAD, but these small gains are clearly offset (on average) by the huge recession losses.

The SVR is usually used in its nonlinear form. We hereby compare KRR and SVR-NL to study whether the loss function effect could reverse when a nonlinear model is considered. Comparing these models makes sense since they both use the same kernel trick (with an RBF kernel). Hence, like linear models of Figure 8, models in Figure 9 only differ by the use of a different loss function  $\hat{L}$ . It turns out conclusions are exactly the same as for linear models with the negative effects being slightly smaller in nonlinear world. There are few exceptions: inflation rate and 1 month ahead horizon during recessions. Furthermore, Figures C4 and C5 in the Appendix C confirm that these findings are valid for both the data-rich and the data-poor environments.

By investigating these results more in depth using Tables A1–A5, we see an emerging pattern. First, SVR sometimes does very good (best model for UNRATE at horizon 3 months) but underperforms for many targets—in its AR or ARDI form. When it does perform well compared to the benchmark, it is more often than not outshined marginally by the KRR version. For instance, in Table A2, linear and nonlinear SVR-Kfold provide respectively reductions of 17% and 13% in RMSPE over the benchmark for UNRATE at horizon 9 months. However, analogous KRR and RF similarly do so. Moreover, for targets for which SVR fails, the two models it is compared to in order to extract  $\alpha_{\hat{L}}$ , KRR or the AR/ARDI, have a more stable (good) record. Hence, on average nonlinear SVR is much worse than KRR and the linear SVR is also inferior to the plain ARDI. This explains the clear-cut results reported in this section: if the SVR wins, it is rather for its use of the kernel trick (nonlinearities) than an alternative in-sample loss function.

These results point out that an alternative  $\hat{L}$  like the  $\bar{\epsilon}$ -insensitive loss function is not the most salient feature ML has to offer for macroeconomic forecasting. From a practical point of view, our results indicate that, on average, one can obtain

**FIGURE 9** This graph displays the marginal (un)improvements by variables and horizons to opt for the SVR in-sample loss function in both recession and expansion periods. The unit of the  $x$  axis are improvements in OOS  $R^2$  over the basis model. SEs are HAC. These are the 95% confidence bands



the benefits of SVR and more by considering the much simpler KRR. This is convenient since obtaining the KRR forecast is a matter of less than 10 lines of codes implying the most straightforward form of linear algebra. In contrast, obtaining the SVR solution can be a serious numerical enterprise.

## 6 | WHEN ARE THE ML NONLINEARITIES IMPORTANT?

In this section we aim to explain some of the heterogeneity of ML treatment effects by interacting them in Equation (12) with few macroeconomic variables  $\xi_t$  that have been used to explain main sources of observed nonlinear macroeconomic fluctuations. We focus on NL feature only given its importance for both macroeconomic prediction and modeling.

The first element in  $\xi_t$  is the Chicago Fed adjusted national financial conditions index (ANFCI). Adrian et al. (2019) find that lower quantiles of GDP growth are time varying and are predictable by tighter financial conditions, suggesting that higher order approximations are needed in general equilibrium models with financial frictions. In addition, Beaudry et al. (2018) build on the observation that recessions are preceded by accumulations of business, consumer and housing capital, while Beaudry et al. (2020) add nonlinearities in the estimation part of a model with financial frictions and household capital accumulation. Therefore, we add to the list the house price growth (HOUSPRICE), measured by the S&P/Case–Shiller US National Home Price Index. The goal is to test if financial conditions and capital buildups are associated with the nonlinear ML feature and its superior predictive performance.

Uncertainty is also related to nonlinearity in macroeconomic modeling (Bloom, 2009). Benigno et al. (2013) provide a second-order approximation solution for a model with time-varying risk that has its own effect on endogenous variables. Gorodnichenko and Ng (2017) find evidence on volatility factors that are persistent and load on the housing sector, while Carriero et al. (2018) estimate uncertainty and its effects in a large nonlinear VAR model. Hence, we include the Macro Uncertainty from Jurado et al. (2015) (MACROUNCERT).<sup>25</sup>

Then we add measures of sentiments: University of Michigan Consumer Expectations (UMCSENT) and Purchasing Managers Index (PMI). Angeletos and La'O (2013) and Benhabib et al. (2015) have suggested that waves of pessimism and optimism play an important role in generating (nonlinear) macroeconomic fluctuations. In the case of Benhabib et al. (2015), optimal decisions based on sentiments produce multiple self-fulfilling rational expectations equilibria. Consequently, including measures of sentiment in  $\xi_t$  aims to test if this channel plays a role for nonlinearities in macro forecasting. Standard monetary VAR series are used as controls: UNRATE, PCE inflation (PCEPI), and 1-year treasury rate (GS1).<sup>26</sup>

<sup>25</sup>We did not consider the Economic Policy Uncertainty from Baker et al. (2016) as it starts only from 1985.

<sup>26</sup>We consider GS1 instead of the federal funds rate because of the long zero lower bound period. Time series of elements in  $\xi_t$  are plotted in Figure C2.

	(1) Base	(2) All horizons	(3) Data-rich	(4) Last 20 years
NL	8.998*** (0.748)	5.808*** (0.528)	13.48*** (1.012)	19.87*** (1.565)
HOUSPRICE	-9.668*** (1.269)	-4.491*** (0.871)	-11.56*** (1.715)	-1.219 (1.596)
ANFCI	7.244*** (1.881)	2.625 (1.379)	6.803** (2.439)	20.29*** (4.891)
MACROUNCERT	17.98*** (1.875)	10.28*** (1.414)	34.87*** (2.745)	9.660*** (2.038)
UMCSENT	4.695** (1.768)	3.853** (1.315)	10.29*** (2.294)	-3.625 (1.922)
PMI	0.0787 (1.179)	-1.443 (0.879)	-2.048 (1.643)	-1.919 (1.288)
UNRATE	0.834 (1.353)	2.517** (0.938)	5.732*** (1.734)	8.526*** (2.199)
GS1	-14.24*** (2.288)	-9.500*** (1.682)	-17.30*** (3.208)	2.081 (3.390)
PCEPI	5.953* (2.828)	6.814** (2.180)	-1.142 (4.093)	-6.242 (3.888)
Observations	136,800	228,000	68,400	72,300

TABLE 3 Heterogeneity of NL treatment effect

Note: HAC standard errors in parentheses.

\* $p < 0.05$ .

\*\* $p < 0.01$ .

\*\*\* $p < 0.001$ .

Interactions are formed with  $\xi_{t-h}$  to measure its impact when the forecast is made. This is of interest for practitioners as it indicates which macroeconomic conditions favor nonlinear ML forecast modeling. Hence, this expands Equation (12) to

$$\forall m \in \mathcal{M}_{NL} : R_{t,h,v,m}^2 = \dot{\alpha}_{NL} + \dot{\gamma} I(m \in NL) \xi_{t-h} + \dot{\phi}_{t,v,h} + \dot{u}_{t,h,v,m}$$

where  $\mathcal{M}_{NL}$  is defined as the set of models that differs only by the use of NL.

The results are presented in Table 3. The first column shows regression coefficients for  $h = \{9, 12, 24\}$ , since nonlinearity has been found more important for longer horizons. The second column average across all horizons, while the third presents the results for data-rich models only. The last column shows the heterogeneity of NL treatments during last 20 years.

Results show that macroeconomic uncertainty is a true game changer for ML nonlinearity as it improves its forecast accuracy by 34% in the case of data-rich models. This means that if the macro uncertainty goes from -1 standard deviation to +1 standard deviation from its mean, the expected NL treatment effect (in terms OOS- $R^2$  difference) is  $2 * 34 = +68\%$ . Tighter financial conditions and a decrease in house prices are also positively correlated with a higher NL treatment, which supports the findings in Adrian et al. (2019) and Beaudry et al. (2020). It is particularly interesting that the effect of ANFCI reaches 20% during last 20 years, while the impact of uncertainty decreases to less than 10%, emphasizing that the determinant role of financial conditions in recent US macro history is also reflected in our results. Waves of consumer optimism positively affect nonlinearities, especially with data-rich models.

Among control variables, unemployment rate has a positive effect on nonlinearity. As expected, this suggests that the importance of nonlinearities is a cyclical feature. Lower interest rates also improve NL treatment by as much as 17% in the data-rich setup. Higher inflation also leads to stronger gains from ML nonlinearities, but mainly at shorter horizons and for data-poor models, as suggested by comparing specifications (2) and (3).

These results document clear historical situations where NL consistently helps: (i) when the level of macroeconomic uncertainty is high and (ii) during episodes of tighter financial conditions and housing bubble bursts.<sup>27</sup> Also, we note that

<sup>27</sup>Granziera and Sekhposyan (2019) have exploited similar regression setup for model selection and found that ‘economic’ forecasting models, AR augmented by few macroeconomic indicators, outperform the time series models during turbulent times (recessions, tight financial conditions and high uncertainty).

effects are often bigger in the case of data-rich models. Hence, allowing nonlinear relationship between factors made of many predictors can capture better the complex relationships that characterize the episodes above.

These findings suggest that ML captures important macroeconomic nonlinearities, especially in the context of financial frictions and high macroeconomic uncertainty. They can also serve as guidance for forecasters that use a portfolio of predictive models: one should put more weight on nonlinear specifications if economic conditions evolve as described above.

## 7 | IMPORTANCE OF ML NONLINEARITIES FOR DENSITY FORECASTING

We now assess the importance of the nonlinearity feature in terms of density forecasting. We opted to build the predictive density from quantile forecasts as proposed by Adrian et al. (2019). For a conditional quantile  $\tau$ , we produce quantile forecasts

$$\hat{Q}_{y_{t+h}}(\tau|X_t) = g(X_t, \hat{\theta}).$$

We then obtain the fitted predictive density,  $\hat{f}(y_{t+h}|X_t)$ , by minimizing the squared distance between the predicted quantiles and the quantiles implied by the skewed Student distribution. It is a parsimonious way to allow for both skewness and fatter tails than the normal law and it is the same choice made by Adrian et al. (2019).

In order to disentangle the impact of nonlinearity, two competing models are considered. We consider the Quantile Random Forests (QRF) and the Quantile ARDI (QARDI).<sup>28</sup> The technical implementation details are presented in Appendix E. Following Diebold et al. (2017), we consider interval and density evaluation metrics.

### 7.1 | Interval forecast evaluation

We consider relative standards such as coverage rate and interval length. The coverage rate is the frequency with which the forecasts of each variable fall inside the  $100(1 - \text{size})$  highest density interval. A realized frequency of more (less) than the nominal level means that the corresponding predictive density is too wide (narrow). The average prediction interval lengths are considered as well.

Each  $100(1 - \text{size})$  forecast interval may be constructed using either the quantile forecasts directly or the implied quantiles of the fitted distribution. Table 4 reports the frequency with which forecasts are inside the 90% intervals constructed from  $\hat{f}(y_{t+h}|X_t)$ .<sup>29</sup> These are presented in the first row of each cell. The  $p$ -values of the hypothesis of correct coverage (empirical = nominal coverage of 90%) are shown in parentheses. The second row of each cell reports average prediction interval lengths.

The results clearly recall our earlier findings about the gains of nonlinear methods. At horizons of 9, 12 and 24 months, the QRF estimated coverage is much closer to 90% than the linear ones, and only once it is significantly different from the nominal coverage. At shorter horizons the results are mixed, but the nonlinear model coverage is closer to the nominal rate in a majority of cases. Interval lengths suggest that the linear model tend to produce intervals that are too narrow and that the gain from using the fitted densities of nonlinear models comes in good part from widening them to achieve the correct level.

### 7.2 | Density forecast evaluation

We evaluate density forecasts on the basis of the log score and the probability integral transform (PIT). The former is defined as

$$LS_{t+h} = -\log(\hat{f}(y_{t+h}|X_t)).$$

<sup>28</sup>In both cases, we restricted our attention to ARDI given its good performances in point forecasting. We note that Duan et al. (2020) made a similar comparison for the Chinese economy. They applied the Meinshausen and Ridgeway (2006) QRF algorithm, as well as linear quantile regression using principal components as inputs to predict downside macroeconomic systemic risk.

<sup>29</sup>The equivalent tables for 70% intervals and for directly predicted quantiles are presented in Appendix E.

Methods	Variables	<b><i>h</i> = 1</b>	<b><i>h</i> = 3</b>	<b><i>h</i> = 9</b>	<b><i>h</i> = 12</b>	<b><i>h</i> = 24</b>
QRF	INDPRO	<b>95 (0)</b> 0.023	96 (0) 0.016	<b>92 (0.19)</b> 0.012	<b>93 (0.14)</b> 0.011	<b>91 (0.38)</b> 0.009
	UNRATE	<b>93 (0)</b> 0.568	<b>94 (0.01)</b> 0.327	<b>93 (0.17)</b> 0.251	<b>91 (0.4)</b> 0.232	<b>88 (0.27)</b> 0.173
	T10YFFM	98 (0) 3.349	97 (0) 3.877	<b>93 (0.11)</b> 4.635	<b>91 (0.37)</b> 4.715	<b>88 (0.26)</b> 5.29
	CPIAUCSL	<b>87 (0.02)</b> 0.008	<b>88 (0.16)</b> 0.007	<b>89 (0.32)</b> 0.006	<b>89 (0.39)</b> 0.006	<b>90 (0.48)</b> 0.007
	HOUST	98 (0) 0.511	<b>95 (0.01)</b> 0.566	<b>90 (0.49)</b> 0.716	<b>86 (0.18)</b> 0.756	<b>80 (0.01)</b> 0.788
QARDI	INDPRO	85 (0) 0.02	<b>85 (0.03)</b> 0.013	85 (0.04) 0.01	80 (0) 0.008	75 (0) 0.006
	UNRATE	75 (0) 0.441	79 (0) 0.264	79 (0) 0.193	80 (0) 0.188	70 (0) 0.143
	T10YFFM	<b>92 (0.05)</b> 2.794	<b>91 (0.27)</b> 3.487	86 (0.1) 3.933	86 (0.12) 4.182	79 (0) 4.562
	CPIAUCSL	78 (0) 0.007	80 (0) 0.006	79 (0) 0.005	78 (0) 0.005	80 (0) 0.005
	HOUST	<b>86 (0.01)</b> 0.406	85 (0.03) 0.422	74 (0) 0.485	66 (0) 0.464	58 (0) 0.517

Note: This table show case mean coverage rates and *p*-values in parentheses for a test of nominal correspondance, that is,  $\hat{\beta} = 1 - \text{size}$ . We use HAC standard errors. Models with coverage closest to  $1 - \text{size}$  are in bold. Mean intervals lengths are indicated below coverages rates.

Variables	<b><i>h</i> = 1</b>	<b><i>h</i> = 3</b>	<b><i>h</i> = 9</b>	<b><i>h</i> = 12</b>	<b><i>h</i> = 24</b>
INDPRO	<b>-1.21 (0)</b>	<b>-1.14 (0)</b>	<b>-0.61 (0.01)</b>	<b>-1.28 (0)</b>	<b>-1.7 (0.01)</b>
UNRATE	<b>-1.9 (0)</b>	<b>-1.63 (0)</b>	<b>-1.95 (0)</b>	<b>-1.4 (0.02)</b>	<b>-2.68 (0)</b>
T10YFFM	<b>-0.5 (0.01)</b>	<b>-0.6 (0.01)</b>	<b>-1.25 (0.02)</b>	<b>-1.54 (0.01)</b>	-1.44 (0.06)
CPIAUCSL	<b>-1.74 (0)</b>	<b>-1.12 (0)</b>	<b>-1.07 (0)</b>	<b>-1.57 (0)</b>	<b>-1.97 (0.01)</b>
HOUST	<b>-1.18 (0)</b>	<b>-0.91 (0)</b>	<b>-1.86 (0)</b>	<b>-3.35 (0)</b>	<b>-4.85 (0)</b>

Note: This table show case Diebold–Mariano statistics and *p*-values (in parentheses). We use HAC standard errors. Scores are negative oriented (i.e., smaller is better) and bold indicates a statistically significant edge in favor of QRF.

It conveys the intuition that better density forecasts place more mass close to the realized value. We can then construct a Diebold–Mariano test statistic by regressing

$$d_t = LS_{t,QRF} - LS_{t+h,Linear}$$

on a constant. The  $H_0$  of equal performance is then a zero constant, and negative values favor QRF. Table 5 reports those results with bold representing cases where QRF has a statistically significant edge. Everywhere except for the spread (T10YFFM) at 24 months, the density implied forecasts of the QRF performs significantly better to that of the linear QARDI alternative. This conforms to the previous findings regarding the density implied intervals.


Of course, one possibility is that the linear model happens to produce deeply misspecified densities. To rule this out, we consider a specification test based on the PIT introduced in Diebold et al. (1998). It is defined as the cumulative density of the random variable  $y_{t+h}$  evaluated at the true value of the outcome

$$z_{h,t} = \int_{-\infty}^{y_{t+h}} F(\tilde{y}_{t+h}|X_t) d\tilde{y}_{i,t+h}.$$

For  $h = 1$ , a correctly specified model would imply  $z_{v,h,t} \sim iid U[0, 1]$ . This test has a convenient visual representation as we are comparing the empirical CDF with the CDF of a uniform distribution which is to say, the 45° line. To handle the serial dependence introduced when  $h > 1$ , we follow Rossi and Sekhposyan (2019) who propose a bootstrap method to

TABLE 4 Smoothed interval forecasts (90%)

**FIGURE 10** Conditional predictive density tests



get the correct confidence intervals. The result of the tests are displayed in Figure 10 for the inflation rate and industrial production and in Figures E1–E3 for other variables.

The null of a correctly specified density is rejected for QRF for industrial production at 3 and 12 months, as it is for the QARDI for both variables at 12 months. We can see in other figures that, in general, both models lie within the confidence intervals, except for the spread where both models perform quite poorly. Those results suggest that the log score advantage lent to the QRF does not rest on the linear model being particularly poorly specified.

In summary, this section showed how nonlinear models can be helpful beyond the scope of point forecasts and may carry over to interval and density forecasts.

## 8 | CONCLUSION

In this paper we have studied important features driving the performance of machine learning techniques in the context of macroeconomic forecasting. We have considered many ML methods in a substantive POOS setup over 38 years for five key variables and five horizons. We have classified these models by “features” of machine learning: nonlinearities, regularization, cross-validation, and alternative loss function. The data-rich and data-poor environments were considered. In order to recover their marginal effects on forecasting performance, we designed a series of experiments that easily allow to identify the treatment effects of interest.

The first result indicates that nonlinearities are the true game changer for the data-rich environment, as they improve substantially the forecasting accuracy for all macroeconomic variables in our exercise and especially when predicting at long horizons. This gives a stark recommendation for practitioners. It recommends for most variables and horizons what is in the end a partially nonlinear factor model—that is, factors are still obtained by PCA. The best of ML (at least of what considered here) can be obtained by simply generating the data for a standard ARDI model and then feed it into a ML nonlinear function of choice. The performance of nonlinear models is magnified during periods of high macroeconomic uncertainty, financial stress, and housing bubble bursts. These findings suggest that Machine Learning is useful for macroeconomic forecasting by mostly capturing important nonlinearities that arise in the context of uncertainty and financial frictions. Beyond the statistical significance, this amelioration is particularly valuable for the conduct of economic policies that often require accurate forecasts of important macroeconomic variables.

The second result is that the standard factor model remains the best regularization. Alternative regularization schemes are most of the time harmful. Third, if cross-validation has to be applied to select models' features, the best practice is the standard K-fold. Finally, the standard  $L_2$  is preferred to the  $\bar{\epsilon}$ -insensitive loss function for macroeconomic predictions. We found that most (if not all) the benefits from the use of SVR in fact comes from the nonlinearities it creates via the kernel trick rather than its use of an alternative loss function.

## ACKNOWLEDGMENTS

We thank Barbara Rossi and referees for valuable comments. The third author acknowledges financial support from the Fonds de recherche sur la société et la culture (Québec) and the Social Sciences and Humanities Research Council.

## OPEN RESEARCH BADGES



This article has been awarded Open Data Badge for making publicly available the digitally-shareable data necessary to reproduce the reported results. Data is available at <http://qed.econ.queensu.ca/jae/datasets/goulet-coulombe001/>.

## DATA AVAILABILITY STATEMENT

All data used to generate the results in this paper are available on <http://qed.econ.queensu.ca/jae/datasets/goulet-coulombe001/>.

## REFERENCES

- Abadie, A., & Kasy, M. (2019). Choosing among regularized estimators in empirical economics: The risk of machine learning. *Review of Economics and Statistics*, 101(5), 743–762.
- Adrian, T., Boyarchenko, N., & Giannone, D. (2019). Vulnerable growth. *American Economic Review*, 109(4), 1263–1289.
- Ahmed, N. K., Atiya, A. F., El Gayar, N., & El-Shishiny, H. (2010). An empirical comparison of machine learning models for time series forecasting. *Econometric Reviews*, 29(5), 594–621.
- Alquier, P., Li, X., & Wintenberger, O. (2013). Prediction of time series by statistical learning: General losses and fast rates. *Dependence Modeling*, 1(1), 65–93.
- Angeletos, G.-M., & La'O, J. (2013). Sentiments. *Econometrica*, 81(2), 739–779.
- Athey, S. (2019). The impact of machine learning on economics. In Agrawal, A., Gans, J., & Goldfarb, A. (Eds.), *The economics of artificial intelligence: An agenda*: University of Chicago Press, pp. 507–552.
- Athey, S., Tibshirani, J., & Wager, S. (2019). Generalized random forests. *Annals of Statistics*, 47(2), 1148–1178.
- Atkeson, A., & Ohanian, L. E. (2001). Are Phillips curves useful for forecasting inflation? *Quarterly Review*, 25(1), 2–11.
- Baker, S. R., Bloom, N., & Davis, S. J. (2016). Measuring economic policy uncertainty. *The Quarterly Journal of Economics*, 131(4), 1593–1636.
- Beaudry, P., Galizia, D., & Portier, F. (2018). Reconciling Hayek's and Keynes' views of recessions. *Review of Economic Studies*, 85(1), 119–156.
- Beaudry, P., Galizia, D., & Portier, F. (2020). Putting the cycle back into business cycle analysis. *American Economic Review*, 110(1), 1–47.
- Belloni, A., Chernozhukov, V., Fernandes-Val, I., & Hansen, C. B. (2017). Program evaluation and causal inference with high-dimensional data. *Econometrica*, 85(1), 233–298.
- Benhabib, J., Wang, P., & Wen, Y. (2015). Sentiments and aggregate demand fluctuations. *Econometrica*, 83(2), 549–585.
- Benigno, G., Benigno, P., & Nisticò, S. (2013). Second-order approximation of dynamic models with time-varying risk. *Journal of Economic Dynamics and Control*, 37(7), 1231–1247.
- Bergmeir, C., & Benítez, J. M. (2012). On the use of cross-validation for time series predictor evaluation. *Information Sciences*, 191, 192–213.
- Bergmeir, C., Hyndman, R. J., & Koo, B. (2018). A note on the validity of cross-validation for evaluating autoregressive time series prediction. *Computational Statistics and Data Analysis*, 120, 70–83.
- Bloom, N. (2009). The impact of uncertainty shocks. *Econometrica*, 77(3), 623–685.
- Boivin, J., & Ng, S. (2006). Are more data always better for factor analysis? *Journal of Econometrics*, 132(1), 169–194.
- Boot, T., & Pick, A. (2020). Does modeling a structural break improve forecast accuracy? *Journal of Econometrics*, 215(1), 35–59.
- Bordo, M. D., Redish, A., & Rockoff, H. (2015). Why didn't Canada have a banking crisis in 2008 (or in 1930, or 1907, or...)? *Economic History Review*, 68(1), 218–243.
- Breiman, L. (2001). Random forests. *Machine Learning*, 45, 5–32.
- Carriero, A., Galvão, A. B., & Kapetanios, G. (2019). A comprehensive evaluation of macroeconomic forecasting methods. *International Journal of Forecasting*, 35(4), 1226–1239.
- Carriero, A., Clark, T. E., & Marcellino, M. (2018). Measuring uncertainty and its impact on the economy. *Review of Economics and Statistics*, 100(5), 799–815.
- Chen, J., Dunn, A., Hood, K., & Batch, A. (2019). Off to the races: A comparison of machine learning and alternative data for Nowcasting of economic indicators. In Abraham, K., Jarmin, R. S., Moyer, B., & Shapiro, M. D. (Eds.), *Big data for 21st century economic statistics*. University of Chicago Press.
- Chevillon, G. (2007). Direct multi-step estimation and forecasting. *Journal of Economic Surveys*, 21(4), 746–785.
- Choudhury, S., Ghosh, S., Bhattacharya, A., Fernandes, K. J., & Tiwari, M. K. (2014). A real time clustering and SVM based price-volatility prediction for optimal trading strategy. *Neurocomputing*, 131, 419–426.
- Claeskens, G., & Hjort, N. L. (2008). Akaike's information criterion. In Claeskens, G., & Hjort, N. L. (Eds.), *Model averaging and model selection* (pp. 22–69).
- Colombo, E., & Pelagatti, M. (2020). Statistical learning and exchange rate forecasting. *International Journal of Forecasting*, 36(4), 1260–1289.

- Cook, T., & Smalter Hall, A. (2017). Macroeconomic indicator forecasting with deep neural networks.
- Coulombe, P. G. (2019). Time-varying parameters: A machine learning approach.
- Davis, R. A., Nielsen, M. S., et al. (2020). Modeling of time series using random forests: Theoretical developments. *Electronic Journal of Statistics*, 14(2), 3644–3671.
- De Mol, C., Giannone, D., & Reichlin, L. (2008). Forecasting using a large number of predictors: Is Bayesian shrinkage a valid alternative to principal components? *Journal of Econometrics*, 146(2), 318–328.
- Diebold, F. X., Gunther, T. A., & Tay, A. S. (1998). Evaluating density forecasts with applications to financial risk management. *International Economic Review*, 39, 863–883.
- Diebold, F. X., & Mariano, R. S. (1995). Comparing predictive accuracy. *Journal of Business and Economic Statistics*, 13(3), 253–263.
- Diebold, F. X., Schorfheide, F., & Minchul, S. (2017). Real-time forecast evaluation of DSGE models with stochastic volatility. *Journal of Econometrics*, 201(2), 322–332.
- Diebold, F. X., & Shin, M. (2019). Machine learning for regularized survey forecast combination: Partially-egalitarian LASSO and its derivatives. *International Journal of Forecasting*, 35(4), 1679–1691.
- Döpke, J., Fritzsche, U., & Pierdzioch, C. (2017). Predicting recessions with boosted regression trees. *International Journal of Forecasting*, 33(4), 745–759.
- Duan, Y., Fan, X., & Li, H. (2020). Does the quantile regression forest learn more information on chinese systemic risk? Available at SSRN 3556400.
- Exterkate, P., Groenen, P. J. F., Heij, C., & van Dijk, D. (2016). Nonlinear forecasting with many predictors using kernel ridge regression. *International Journal of Forecasting*, 32(3), 736–753.
- Fan, J., & Lv, J. (2010). A selective overview of variable selection in high dimensional feature space. *Statistica Sinica*, 20(1), 101–148.
- Fortin-Gagnon, O., Leroux, M., Stevanovic, D., & Surprenant, S. (2020). A large Canadian database for macroeconomic analysis.
- Giacomini, R., & Rossi, B. (2010). Forecast comparisons in unstable environments. *Journal of Applied Econometrics*, 25(4), 595–620.
- Giannone, D., Lenza, M., & Primiceri, G. E. (2015). Prior selection for vector autoregressions. *Review of Economics and Statistics*, 97(2), 436–451.
- Giannone, D., Lenza, M., & Primiceri, G. E. (2018). Economic predictions with big data: The illusion of sparsity.
- Gorodnichenko, Y., & Ng, S. (2017). Level and volatility factors in macroeconomic data. *Journal of Monetary Economics*, 91, 52–68.
- Goulet Coulombe, P. (2020). To bag is to prune. *arXiv preprint arXiv:2008.07063*.
- Goulet Coulombe, P., Leroux, M., Stevanovic, D., & Surprenant, S. (2020). Macroeconomic data transformations matter. *arXiv preprint arXiv:2008.01714*.
- Granger, C. W. J., & Jeon, Y. (2004). Thick modeling. *Economic Modelling*, 21(2), 323–343.
- Granziera, E., & Sekhposyan, T. (2019). Predicting relative forecasting performance: An empirical investigation. *International Journal of Forecasting*, 35(4), 1636–1657.
- Gu, S., Kelly, B., & Xiu, D. (2020a). Autoencoder asset pricing models. *Journal of Econometrics*, 0(0).
- Gu, S., Kelly, B., & Xiu, D. (2020b). Empirical asset pricing via machine learning. *Review of Financial Studies*, 33(5), 2223–2273.
- Hansen, P. R., Lunde, A., & Nason, J. M. (2011). The model confidence set. *Econometrica*, 79(2), 453–497.
- Hansen, P. R., & Timmermann, A. (2015). Equivalence between out-of-sample forecast comparisons and wald statistics. *Econometrica*, 83(6), 2485–2505.
- Hastie, T., Tibshirani, R., & Friedman, J. (2009). *The elements of statistical learning: Data mining, inference, and prediction* (2nd edition). Springer Science & Business Media.
- Inoue, A., Jin, L., & Rossi, B. (2017). Rolling window selection for out-of-sample forecasting with time-varying parameters. *Journal of Econometrics*, 196(1), 55–67.
- Joseph, A. (2019). Parametric inference with universal function approximators.
- Jurado, K., Ludvigson, S. C., & Ng, S. (2015). Measuring uncertainty. *American Economic Review*, 105(3), 1177–1216.
- Kim, H. H., & Swanson, N. R. (2018). Mining big data using parsimonious factor, machine learning, variable selection and shrinkage methods. *International Journal of Forecasting*, 34(2), 339–354.
- Koenker, R., & Machado, J. A. F. (1999). Goodness of fit and related inference processes for quantile regression. *Journal of the American Statistical Association*, 94(448), 1296–1310.
- Kotchoni, R., Leroux, M., & Stevanovic, D. (2019). Macroeconomic forecast accuracy in a data-rich environment. *Journal of Applied Econometrics*, 34(7), 1050–1072.
- Kuan, C. M., & White, H. (1994). Artificial neural networks: An econometric perspective. *Econometric Reviews*, 13(1).
- Kuznetsov, V., & Mohri, M. (2015). Learning theory and algorithms for forecasting non-stationary time series. In *Advances in neural information processing systems*, pp. 541–549.
- Lee, T. H., White, H., & Granger, C. W. J. (1993). Testing for neglected nonlinearity in time series models. A comparison of neural network methods and alternative tests. *Journal of Econometrics*, 56(3), 269–290.
- Lechner, S., Thorarinsdottir, T. L., Ravazzolo, F., & Gneiting, T. (2017). Forecaster's dilemma: Extreme events and forecast evaluation. *Statistical Science*, 32(1), 106–127.

- Li, J., & Chen, W. (2014). Forecasting macroeconomic time series: LASSO-based approaches and their forecast combinations with dynamic factor models. *International Journal of Forecasting*, 30(4), 996–1015.
- Litterman, R. B. (1979). Techniques of forecasting using vector autoregressions.
- Lu, C. J., Lee, T. S., & Chiu, C. C. (2009). Financial time series forecasting using independent component analysis and support vector regression. *Decision Support Systems*, 47(2), 115–125.
- Marcellino, M. (2008). A linear benchmark for forecasting GDP growth and inflation? *Journal of Forecasting*, 27(4), 305–340.
- Marcellino, M., Stock, J. H., & Watson, M. W. (2006). A comparison of direct and iterated multistep AR methods for forecasting macroeconomic time series. *Journal of Econometrics*, 135(1–2), 499–526.
- McCracken, M. W., & Ng, S. (2016). FRED-MD: A monthly database for macroeconomic research. *Journal of Business and Economic Statistics*, 34(4), 574–589.
- Medeiros, M. C., Teräsvirta, T., & Rech, G. (2006). Building neural network models for time series: A statistical approach. *Journal of Forecasting*.
- Medeiros, M. C., Vasconcelos, G. F. R., Veiga, A., & Zilberman, E. (2019). Forecasting inflation in a data-rich environment: The benefits of machine learning methods. *Journal of Business and Economic Statistics*, 0(0), 1–45.
- Meinshausen, N., & Ridgeway, G. (2006). Quantile regression forests. *Journal of Machine Learning Research*, 7(6).
- Milunovich, G. (2020). Forecasting Australia's real house price index: A comparison of time series and machine learning methods. *Journal of Forecasting*, 1–21.
- Mohri, M., & Rostamizadeh, A. (2010). Stability bounds for stationary  $\phi$ -mixing and  $\beta$ -mixing processes. *Journal of Machine Learning Research*, 11, 789–814.
- Moshiri, S., & Cameron, N. (2000). Neural network versus econometric models in forecasting inflation. *Journal of Forecasting*, 19(3), 201–217.
- Nakamura, E. (2005). Inflation forecasting using a neural network. *Economics Letters*, 86(3), 373–378.
- Ng, S. (2014). Viewpoint: Boosting recessions. *Canadian Journal of Economics*, 47(1), 1–34.
- Patel, J., Shah, S., Thakkar, P., & Kotecha, K. (2015a). Predicting stock and stock price index movement using Trend Deterministic Data Preparation and machine learning techniques. *Expert Systems with Applications*, 42(1), 259–268.
- Patel, J., Shah, S., Thakkar, P., & Kotecha, K. (2015b). Predicting stock market index using fusion of machine learning techniques. *Expert Systems with Applications*, 42(4), 2162–2172.
- Pesaran, M. H., Pick, A., & Pranovich, M. (2013). Optimal forecasts in the presence of structural breaks. *Journal of Econometrics*, 177(2), 134–152.
- Pesaran, M. H., & Timmermann, A. (1992). A simple nonparametric test of predictive performance. *Journal of Business and Economic Statistics*, 10(4), 461–465.
- Pesaran, M. H., & Timmermann, A. (2007). Selection of estimation window in the presence of breaks. *Journal of Econometrics*, 137(1), 134–161.
- Qu, H., & Zhang, Y. (2016). A new kernel of support vector regression for forecasting high-frequency stock returns. *Mathematical Problems in Engineering*, 1–9.
- Rossi, B., & Sekhonposyan, T. (2019). Alternative tests for correct specification of conditional predictive densities. *Journal of Econometrics*, 208(2), 638–657.
- Sermpinis, G., Stasinakis, C., Theofilatos, K., & Karathanasopoulos, A. (2014). Inflation and unemployment forecasting with genetic support vector regression. *Journal of Forecasting*, 33(6), 471–487.
- Smeekes, S., & Wijler, E. (2018). Macroeconomic forecasting using penalized regression methods. *International Journal of Forecasting*, 34(3), 408–430.
- Smola, A. J., Murata, N., Schölkopf, B., & Müller, K.-R. (1998). Asymptotically optimal choice of  $\epsilon$ -loss for support vector machines. In *International conference on artificial neural networks*, Springer, London, pp. 105–110.
- Smola, A. J., & Schölkopf, B. (2004). A tutorial on support vector regression. *Statistics and Computing*, 14, 199–222.
- Stock, J. H., & Watson, M. W. (1999). A comparison of linear and nonlinear univariate models for forecasting macroeconomic time series. In Engle, R. F., & White, H. (Eds.), *Cointegration, causality and forecasting: A festschrift for Clive W.J. Granger* (pp. 1–44). Oxford: Oxford University Press.
- Stock, J. H., & Watson, M. W. (2002a). Forecasting using principal components from a large number of predictors. *Journal of the American Statistical Association*, 97(460), 1167–1179.
- Stock, J. H., & Watson, M. W. (2002b). Macroeconomic forecasting using diffusion indexes. *Journal of Business and Economic Statistics*, 20(2), 147–162.
- Stock, J. H., & Watson, M. W. (2009). Phillips curve inflation forecasts. In Fuhrer, J., Kodrzycki, Y. K., Sneddon Little, J., & Olivei, G. P. (Eds.), *Understanding inflation and the implication for monetary policy* (pp. 99–202). Cambridge, Massachusetts: MIT Press.
- Stock, J. H., & Watson, M. W. (2012a). Disentangling the channels of the 2007–09 recession. *Brookings Papers on Economic Activity*, 1, 81–156.
- Stock, J. H., & Watson, M. W. (2012b). Generalized shrinkage methods for forecasting using many predictors. *Journal of Business and Economic Statistics*, 30(4), 481–493.
- Swanson, N. R., & White, H. (1997). A model selection approach to real-time macroeconomic forecasting using linear models and artificial neural networks. *The Review of Economics and Statistics*, 79(4), 540–550.
- Tashman, L. J. (2000). Out-of-sample tests of forecasting accuracy: An analysis and review. *International Journal of Forecasting*, 16(4), 437–450.

- Teräsvirta, T. (2006). Forecasting economic variables with nonlinear models. In Granger, C. W. J., & Elliott, G. (Eds.), *Handbook of economic forecasting*: Elsevier, pp. 413–457.
- Trapletti, A., Leisch, F., & Hornik, K. (2000). Stationary and integrated autoregressive neural network processes. *Neural Computation*, 12(10), 2427–2450.
- Uddin, M. F., Lee, J., Rizvi, S., & Hamada, S. (2018). Proposing enhanced feature engineering and a selection model for machine learning processes. *Applied Sciences (Switzerland)*, 8(4), 1–32.
- Yeh, C. Y., Huang, C. W., & Lee, S. J. (2011). A multiple-kernel support vector regression approach for stock market price forecasting. *Expert Systems with Applications*, 38(3), 2177–2186.
- Yousuf, K., & Ng, S. (2019). Boosting high dimensional predictive regressions with time varying parameters.
- Zhang, X. R., Hu, L. Y., & Wang, Z. S. (2010). Multiple kernel support vector regression for economic forecasting. *2010 International Conference on Management Science and Engineering, ICMSE 2010*, 70872025, 129–134.
- Zhao, Q., & Hastie, T. (2019). Causal interpretations of Black-Box models. *Journal of Business and Economic Statistics*, 0(0), 1–19.
- Zou, H. (2006). The adaptive lasso and its oracle properties. *Journal of the American Statistical Association*, 101(476), 1418–1429.

## SUPPORTING INFORMATION

Additional supporting information can be found online in the Supporting Information section at the end of the article.

**How to cite this article:** Coulombe P. G., Leroux, M., Stevanovic, D., & Surprenant, S. (2022). How is machine learning useful for macroeconomic forecasting? *Journal of Applied Econometrics*, 37(5), 920–964. <https://doi.org/10.1002/jae.2910>

## APPENDIX A: DETAILED OVERALL PREDICTIVE PERFORMANCE

Tables A1–A5 summarize the overall predictive performance in terms of root MSPE relative to the reference model AR,BIC. The analysis is done for the full out-of-sample as well as for NBER recessions (i.e., when the target belongs to a recession episode). This address two questions: is ML already useful for macroeconomic forecasting and when?<sup>30</sup>

In case of industrial production, Table A1 shows that principal component regressions  $B_2$  and  $B_3$  with Ridge and Lasso penalty respectively are the best at short-run horizons of 1 and 3 months. The kernel ridge ARDI with POOS CV is best for  $h = 9$ , while its autoregressive counterpart with K-fold minimizes the MSPE at the 1-year horizon. Random forest ARDI, the alternative nonlinear approximator, outperforms the reference model by 11% for  $h = 24$ . During recessions, the ARDI with CV is the best for 1, 3, and 9 months ahead, while the nonlinear SVR-ARDI minimizes the MSPE at the 1-year horizon. The ridge regression ARDI is the best for  $h = 24$ . Ameliorations with respect to AR,BIC are much larger during economic downturns, and the MCS selects fewer models.

Results for the unemployment rate, Table A2, highlight the performance of nonlinear models especially for longer horizons. Improvements with respect to the AR,BIC model are bigger for both full OOS and recessions. MCSs are narrower than in case of INDPRO. A similar pattern is observed during NBER recessions. Table A3 summarizes results for the Spread. Nonlinear models are generally the best, combined with data-rich predictors' set.

For inflation, Table A4 shows that the kernel ridge autoregressive model with K-fold CV is the best for 3, 9, and 12 months ahead, while the nonlinear SVR-ARDI optimized with K-fold CV reduces the MSPE by more than 20% at 2-year horizon. Random forest models are very resilient, as in Medeiros et al. (2019), but generally outperformed by KRR form of nonlinearity. During recessions, the fat regression models ( $B_1$ ) are the best at short horizons, while the ridge regression ARDI with K-fold dominates for  $h = 9, 12, 24$ . Housing starts, in Table A5, are best predicted with nonlinear data-rich models for almost all horizons.

The importance of ML modeling goes beyond the statistical significance. Having reliable predictions is also important for the conduct of economic policies. For instance, standard monetary policy needs accurate forecasts of inflation rates at longer horizons. Table A4 shows that in terms of standard deviation, when forecasting inflation one year ahead, the best nonlinear model improves the forecast precision by 32 basis points over the benchmark.

<sup>30</sup>The knowledge of the models that have performed best historically during recessions is of interest for practitioners. If the probability of recession is high enough at a given period, our results can provide an ex ante guidance on which model is likely to perform best in such circumstances.

TABLE A1 Industrial production: Relative root MSPE

Models	Full out-of-sample					NBER recessions periods				
	<i>h</i> = 1	<i>h</i> = 3	<i>h</i> = 9	<i>h</i> = 12	<i>h</i> = 24	<i>h</i> = 1	<i>h</i> = 3	<i>h</i> = 9	<i>h</i> = 12	<i>h</i> = 24
Data-poor ( $H_t^-$ ) models										
AR,BIC (RMSPE)	0.0765	<b>0.0515</b>	<b>0.0451</b>	<b>0.0428</b>	<b>0.0344</b>	0.127	0.1014	0.0973	0.0898	0.0571
AR,AIC	0.991*	<b>1.000</b>	<b>0.999</b>	<b>1.000</b>	<b>1.000</b>	0.987*	1.000	1.000	1.000	1.000
AR,POOS-CV	0.999	1.021***	<b>0.985*</b>	<b>1.001</b>	1.032*	1.01	1.023***	0.988*	1.000	1.076**
AR,K-fold	0.991*	<b>1.000</b>	<b>0.987*</b>	<b>1.000</b>	1.033*	0.987*	1.000	0.992*	1.000	1.078**
RRAR,POOS-CV	1.003	1.041**	<b>0.989</b>	<b>0.993*</b>	<b>1.002</b>	1.039**	1.083**	0.991	0.993	1.016**
RRAR,K-fold	0.988**	<b>1.000</b>	<b>0.991</b>	<b>1.001</b>	<b>1.027</b>	0.992	1.007**	0.995	1.001**	1.074**
RFAR,POOS-CV	0.995	1.045	<b>0.985</b>	<b>0.955</b>	<b>0.991</b>	1.009	1.073	0.902***	0.890**	0.983
RFAR,K-fold	0.995	<b>1.020</b>	<b>0.960</b>	<b>0.930**</b>	<b>0.983</b>	0.999	1.013	0.894***	0.887***	0.970*
KRR-AR,POOS-CV	1.023	1.09	<b>0.980</b>	<b>0.944</b>	<b>0.982</b>	1.117	1.166*	0.896**	0.853***	0.903***
KRR,AR,K-fold	<b>0.947***</b>	<b>0.937**</b>	<b>0.936</b>	<b>0.910*</b>	<b>0.959</b>	0.922**	0.902**	0.835***	<b>0.799***</b>	0.864***
SVR-AR,Lin,POOS-CV	1.134***	1.226***	1.114***	1.132***	<b>0.952*</b>	1.186**	1.285***	1.079**	1.034***	0.893***
SVR-AR,Lin,K-fold	1.069*	1.159**	1.055**	1.042***	1.016***	1.268***	1.319***	1.067***	1.035***	1.013***
SVR-AR,RBF,POOS-CV	0.999	1.061***	<b>1.020</b>	<b>1.048</b>	<b>0.980</b>	1.062*	1.082***	0.876***	0.941***	0.930***
SVR-AR,RBF,K-fold	<b>0.978*</b>	<b>1.004</b>	1.080*	1.193**	1.017***	0.992	1.009	0.989	1.016***	1.012***
Data-rich ( $H_t^+$ ) models										
ARDI,BIC	<b>0.946*</b>	<b>0.991</b>	1.037	<b>1.004</b>	<b>0.968</b>	<b>0.801***</b>	<b>0.807***</b>	0.887**	0.833***	0.784***
ARDI,AIC	<b>0.959*</b>	<b>0.968</b>	<b>1.017</b>	<b>0.998</b>	<b>0.943</b>	0.840***	<b>0.803***</b>	0.844**	<b>0.798**</b>	<b>0.768***</b>
ARDI,POOS-CV	0.994	<b>1.015</b>	<b>0.984</b>	<b>0.968</b>	<b>0.966</b>	0.896***	<b>0.698***</b>	<b>0.773***</b>	<b>0.777***</b>	0.812***
ARDI,K-fold	<b>0.940*</b>	<b>0.977</b>	<b>1.013</b>	<b>0.982</b>	<b>0.912*</b>	<b>0.787***</b>	<b>0.812***</b>	0.841**	<b>0.808**</b>	<b>0.762***</b>
RRARDI,POOS-CV	<b>0.994</b>	<b>1.032</b>	<b>0.987</b>	<b>0.973</b>	<b>0.948</b>	0.908**	<b>0.725***</b>	0.793***	<b>0.778***</b>	0.861**
RRARDI,K-fold	<b>0.943**</b>	<b>0.977</b>	<b>0.986</b>	<b>0.990</b>	<b>0.921</b>	0.847**	<b>0.718***</b>	<b>0.794***</b>	<b>0.796***</b>	<b>0.702***</b>
RFARDI,POOS-CV	<b>0.948**</b>	<b>0.991</b>	<b>0.951</b>	<b>0.919*</b>	<b>0.899**</b>	0.865**	<b>0.802***</b>	0.837***	<b>0.782***</b>	0.819***
RFARDI,K-fold	<b>0.953**</b>	<b>1.016</b>	<b>0.957</b>	<b>0.924*</b>	<b>0.890**</b>	0.889***	<b>0.864*</b>	0.846***	<b>0.803***</b>	<b>0.767***</b>
KRR-ARDI,POOS-CV	1.038	<b>1.016</b>	<b>0.921*</b>	<b>0.934</b>	<b>0.959</b>	1.152*	1.021	0.847***	0.814***	0.886**
KRR,ARDI,K-fold	<b>0.971</b>	<b>0.983</b>	<b>0.923*</b>	<b>0.914*</b>	<b>0.959</b>	1.006	0.983	0.827***	<b>0.793***</b>	0.848***
( $B_1$ , $\alpha = \hat{\alpha}$ ),POOS-CV	1.014	<b>1.001</b>	<b>1.023</b>	<b>0.996</b>	<b>0.946</b>	1.067	0.956	0.979	0.916**	0.855***
( $B_1$ , $\alpha = \hat{\alpha}$ ),K-fold	<b>0.957**</b>	<b>0.952</b>	<b>1.029</b>	1.046	1.051	0.908**	0.856***	0.874**	<b>0.816***</b>	0.890*
( $B_1$ , $\alpha = 1$ ),POOS-CV	<b>0.971*</b>	<b>1.013</b>	1.067*	<b>1.020</b>	<b>0.955</b>	0.991	0.889	1.01	0.935*	0.880**
( $B_1$ , $\alpha = 1$ ),K-fold	<b>0.957**</b>	<b>0.952</b>	<b>1.029</b>	<b>1.046</b>	1.051	0.908**	0.856***	0.874**	<b>0.816***</b>	0.890*
( $B_1$ , $\alpha = 0$ ),POOS-CV	1.047	1.112**	<b>1.021</b>	1.051	<b>0.969</b>	1.134*	1.182**	0.997	1.005	0.821***
( $B_1$ , $\alpha = 0$ ),K-fold	1.025	1.056*	1.065	1.082	1.052	1.032	0.974	0.923	0.929	0.847***
( $B_2$ , $\alpha = \hat{\alpha}$ ),POOS-CV	1.061	<b>0.968</b>	<b>0.975</b>	<b>0.999</b>	<b>0.923**</b>	1.237	0.810***	0.889***	0.904**	0.869**
( $B_2$ , $\alpha = \hat{\alpha}$ ),K-fold	1.098	<b>0.949</b>	<b>0.993</b>	<b>0.974</b>	<b>0.970</b>	1.332	<b>0.801***</b>	0.896**	0.851***	<b>0.756***</b>
( $B_2$ , $\alpha = 1$ ),POOS-CV	<b>0.973</b>	1.045	<b>1.012</b>	<b>1.023</b>	<b>0.920**</b>	1.034	1.033	0.997	0.957	0.839***
( $B_2$ , $\alpha = 1$ ),K-fold	<b>0.956**</b>	1.022	1.032	<b>1.025</b>	<b>0.990</b>	0.961	0.935	0.959	0.913**	0.809***
( $B_2$ , $\alpha = 0$ ),POOS-CV	<b>0.933***</b>	<b>0.955</b>	<b>0.972</b>	<b>0.937</b>	<b>0.913**</b>	0.902**	<b>0.781***</b>	0.904**	0.840***	0.807***
( $B_2$ , $\alpha = 0$ ),K-fold	<b>0.937**</b>	<b>0.927**</b>	<b>0.961</b>	<b>0.927</b>	<b>0.959</b>	0.871***	<b>0.787***</b>	0.858***	<b>0.775***</b>	0.776***
( $B_3$ , $\alpha = \hat{\alpha}$ ),POOS-CV	<b>0.980</b>	<b>0.994</b>	<b>1.016</b>	1.05	<b>0.952</b>	1.032	0.95	0.957	0.97	0.861***
( $B_3$ , $\alpha = \hat{\alpha}$ ),K-fold	<b>0.973**</b>	<b>0.946**</b>	1.042	<b>0.948</b>	<b>0.997</b>	1.016	0.916**	0.938	0.825***	0.827***
( $B_3$ , $\alpha = 1$ ),POOS-CV	<b>0.969**</b>	1.053	1.053	1.080*	<b>0.956</b>	0.972	0.946	1.002	1.014	0.906**
( $B_3$ , $\alpha = 1$ ),K-fold	<b>0.946***</b>	<b>0.913**</b>	<b>0.994</b>	<b>0.976</b>	1.01	0.924**	0.829***	0.888*	<b>0.803***</b>	0.822***
( $B_3$ , $\alpha = 0$ ),POOS-CV	<b>0.976</b>	1.049	1.04	1.063	<b>0.973</b>	1.034	1.061	0.997	0.932*	0.846***
( $B_3$ , $\alpha = 0$ ),K-fold	0.981	1.01	1.03	<b>1.011</b>	<b>0.985</b>	1.002	0.997	0.95	<b>0.826***</b>	0.787***
SVR-ARDI,Lin,POOS-CV	<b>0.989</b>	1.165**	1.216**	1.193**	<b>1.034</b>	0.915*	0.900**	1.006	0.862**	<b>0.778***</b>
SVR-ARDI,Lin,K-fold	1.109**	1.367***	<b>1.024</b>	<b>1.038</b>	<b>1.028</b>	1.129	1.133	<b>0.776***</b>	<b>0.808***</b>	<b>0.726***</b>
SVR-ARDI,RBF,POOS-CV	<b>0.968*</b>	<b>0.986</b>	1.100*	<b>0.960</b>	<b>0.936*</b>	0.958	0.900*	0.873**	<b>0.760***</b>	0.820***
SVR-ARDI,RBF,K-fold	<b>0.951*</b>	<b>0.946</b>	<b>0.993</b>	<b>0.952</b>	<b>1.001</b>	0.860**	<b>0.793***</b>	<b>0.806***</b>	<b>0.777***</b>	0.791***

Note: The numbers represent the relative, with respect to AR,BIC model, root MSPE. Values below 1 imply improvement over the benchmark. Models retained in model confidence set are in bold; the minimum values are underlined.

\*\*\*1% significance of Diebold–Mariano test.

\*\*5% significance of Diebold–Mariano test.

\*10% significance of Diebold–Mariano test.

TABLE A2 Unemployment rate: Relative root MSPE

Models	Full out-of-sample					NBER recessions periods				
	<i>h</i> = 1	<i>h</i> = 3	<i>h</i> = 9	<i>h</i> = 12	<i>h</i> = 24	<i>h</i> = 1	<i>h</i> = 3	<i>h</i> = 9	<i>h</i> = 12	<i>h</i> = 24
<b>Data-poor (<math>H_t^-</math>) models</b>										
AR,BIC (RMSPE)	1.9578	1.1905	1.0169	1.0058	0.869	2.5318	2.0826	1.8823	1.7276	1.0562
AR,AIC	0.991	0.984	0.988	0.993***	1.000	0.958	0.960**	0.984*	1.000	1.000
AR,POOS-CV	0.988	0.999	1.002	0.995	0.987	0.978	0.980**	0.996	0.998	1.04
AR,K-fold	0.994	0.984	0.989	0.986***	0.991	0.956*	0.960**	0.998	1.000	1.038
RRAR,POOS-CV	0.989	1.000	1.002	0.990*	0.972**	0.984	0.988*	0.997	0.991*	1.001
RRAR,K-fold	0.988	0.982*	0.983*	0.989**	0.999	0.963	0.971*	0.992	0.995	1.033
RFAR,POOS-CV	0.983	0.995	0.968	1.000	1.002	0.989	1.003	0.929**	0.951**	0.994
RFAR,K-fold	0.98	0.985	0.979	1.006	0.99	0.985	0.972	0.896***	0.943*	0.983
KRR-AR,POOS-CV	0.99	1.04	<b>0.882***</b>	<b>0.889***</b>	0.876***	1.04	1.116	0.843***	0.883***	0.904**
KRR,AR,K-fold	<b>0.940***</b>	<b>0.910***</b>	<b>0.878***</b>	<b>0.869***</b>	0.852***	0.847***	0.838***	<b>0.788***</b>	<b>0.798***</b>	0.908**
SVR-AR,Lin,POOS-CV	1.028	1.133**	1.130***	1.108***	1.174***	1.065*	1.274***	1.137***	1.094***	1.185***
SVR-AR,Lin,K-fold	0.993	1.061**	1.068***	1.045***	1.013***	1.062**	1.108***	1.032**	1.011	1.018***
SVR-AR,RBF,POOS-CV	1.019	1.094*	1.029	1.076**	1.01	1.097**	1.247**	1.047*	1.034***	1.112*
SVR-AR,RBF,K-fold	0.997	1.011	1.078**	1.053*	0.993	1.026	1.009	1.058	1.023	0.985
<b>Data-rich (<math>H_t^+</math>) models</b>										
ARDI,BIC	<b>0.937**</b>	<b>0.893**</b>	0.938	0.939	0.875***	<b>0.690***</b>	0.715***	<b>0.798***</b>	0.782***	<b>0.783***</b>
ARDI,AIC	<b>0.933**</b>	<b>0.878***</b>	0.928	0.953	0.893**	<b>0.720***</b>	0.719***	<b>0.798***</b>	0.799***	<b>0.787***</b>
ARDI,POOS-CV	<b>0.924***</b>	<b>0.913*</b>	0.957	0.925*	<b>0.856***</b>	<b>0.686***</b>	<b>0.676***</b>	0.840**	<b>0.737***</b>	<b>0.777***</b>
ARDI,K-fold	<b>0.935**</b>	<b>0.895**</b>	0.929	0.93	0.915**	<b>0.696***</b>	0.697***	<b>0.801***</b>	0.807***	<b>0.787***</b>
RRARDI,POOS-CV	<b>0.924***</b>	<b>0.896*</b>	0.968	0.946	0.870***	<b>0.711***</b>	<b>0.635***</b>	0.849**	<b>0.768***</b>	<b>0.767***</b>
RRARDI,K-fold	<b>0.940**</b>	<b>0.899**</b>	0.946	0.931*	0.908**	<b>0.755**</b>	<b>0.681***</b>	<b>0.803***</b>	0.790***	<b>0.753***</b>
RFARDI,POOS-CV	<b>0.934***</b>	0.945	<b>0.857***</b>	<b>0.842***</b>	<b>0.763***</b>	<b>0.724***</b>	0.769***	<b>0.718***</b>	<b>0.734***</b>	<b>0.722***</b>
RFARDI,K-fold	<b>0.932***</b>	<b>0.897***</b>	<b>0.873**</b>	<b>0.854***</b>	<b>0.785***</b>	<b>0.749***</b>	0.742***	<b>0.731***</b>	<b>0.720***</b>	<b>0.710***</b>
KRR-ARDI,POOS-CV	<b>0.959*</b>	<b>0.961</b>	<b>0.839***</b>	<b>0.813***</b>	<b>0.804***</b>	1.01	1.017	<b>0.748***</b>	<b>0.732***</b>	0.828***
KRR,ARDI,K-fold	<b>0.938***</b>	<b>0.907**</b>	<b>0.827***</b>	<b>0.817***</b>	<b>0.795***</b>	0.925	0.933	<b>0.785***</b>	<b>0.729***</b>	<b>0.814***</b>
( $B_1$ . $\alpha$ = $\hat{\alpha}$ ),POOS-CV	0.979	<b>0.945</b>	0.976	0.953	0.913***	1.049	0.899*	0.933	0.910*	0.871***
( $B_1$ . $\alpha$ = $\hat{\alpha}$ ),K-fold	0.971	<b>0.925**</b>	<b>0.867***</b>	0.919*	0.925*	0.787***	0.848***	0.840***	0.839***	0.829**
( $B_1$ . $\alpha$ = 1),POOS-CV	0.947***	<b>0.937*</b>	0.962	0.922**	0.889***	0.857**	0.789***	0.888**	0.860***	0.915*
( $B_1$ . $\alpha$ = 1),K-fold	0.971	<b>0.925**</b>	<b>0.867***</b>	0.919*	0.925*	0.787***	0.848***	0.840***	0.839***	0.829**
( $B_1$ . $\alpha$ = 0),POOS-CV	1.238**	1.319**	1.021	1.07	1.01	1.393*	1.476*	0.979	0.972	<b>0.764***</b>
( $B_1$ . $\alpha$ = 0),K-fold	1.246**	0.994	1.062*	1.077*	1.018	1.322	0.963	0.991	0.933	0.802***
( $B_2$ , $\alpha$ = $\hat{\alpha}$ ),POOS-CV	<b>0.907***</b>	<b>0.918**</b>	0.926*	0.936*	0.911**	<b>0.756***</b>	0.767***	0.869**	0.832***	0.808***
( $B_2$ , $\alpha$ = $\hat{\alpha}$ ),K-fold	<b>0.917***</b>	<b>0.900***</b>	0.915*	0.931	0.974	<b>0.728***</b>	0.777***	0.829***	<b>0.738***</b>	<b>0.713***</b>
( $B_2$ , $\alpha$ = 1),POOS-CV	<b>0.914***</b>	0.955	1.057	1.011	0.883***	0.810***	0.830***	1.029	0.952	0.795***
( $B_2$ , $\alpha$ = 1),K-fold	0.97	<b>0.901**</b>	0.991	0.983	0.918**	0.837**	0.754***	0.903	0.833***	<b>0.753***</b>
( $B_2$ , $\alpha$ = 0),POOS-CV	<b>0.908***</b>	<b>0.893***</b>	0.991	0.922*	0.889***	0.781**	0.769***	0.915	0.786***	<b>0.788***</b>
( $B_2$ , $\alpha$ = 0),K-fold	<b>0.949**</b>	<b>0.898***</b>	0.908**	0.906**	0.967	0.875	0.777***	0.817***	<b>0.756***</b>	<b>0.741***</b>
( $B_3$ , $\alpha$ = $\hat{\alpha}$ ),POOS-CV	<b>0.949**</b>	<b>0.888***</b>	0.952	0.943	0.874***	0.933	0.843***	0.886**	0.829***	0.827***
( $B_3$ , $\alpha$ = $\hat{\alpha}$ ),K-fold	<b>0.937**</b>	<b>0.910***</b>	<b>0.882**</b>	0.923*	0.921**	0.836*	0.831***	0.868***	0.839***	<b>0.795***</b>
( $B_3$ , $\alpha$ = 1),POOS-CV	<b>0.929***</b>	<b>0.921**</b>	0.958	0.983	0.884***	0.812**	0.771***	0.864**	0.851**	0.845***
( $B_3$ , $\alpha$ = 1),K-fold	0.968	0.941*	<b>0.861***</b>	0.907*	0.943	0.808**	0.806***	0.832***	0.873**	<b>0.736***</b>
( $B_3$ , $\alpha$ = 0),POOS-CV	<b>0.948**</b>	0.974	0.994	1.066	0.946*	0.979	1.03	0.956	0.877**	<b>0.799***</b>
( $B_3$ , $\alpha$ = 0),K-fold	0.969	<b>0.918***</b>	0.983	0.998	0.945*	0.963	0.901*	0.957	0.912*	<b>0.730***</b>
SVR-ARDI,Lin,POOS-CV	<b>0.960*</b>	1.041	1.072	0.929	1.028	0.872	0.858*	0.941	0.809***	<b>0.779***</b>
SVR-ARDI,Lin,K-fold	0.959*	<b>0.873***</b>	<b>0.838***</b>	0.926	0.946	0.801**	0.791***	<b>0.756***</b>	<b>0.800**</b>	0.872*
SVR-ARDI,RBF,POOS-CV	<b>0.966</b>	<b>0.995</b>	1.016	0.957	0.872***	0.938	0.859*	0.937	0.786***	<b>0.777**</b>
SVR-ARDI,RBF,K-fold	<b>0.943**</b>	0.958	<b>0.871***</b>	0.911*	0.930*	<b>0.769***</b>	0.796***	<b>0.770***</b>	<b>0.763***</b>	<b>0.787***</b>

Note: The numbers represent the relative, with respect to AR,BIC model, root MSPE. Values below 1 implies improvement over the benchmark. Models retained in model confidence set are in bold; the minimum values are underlined.

\*\*\*1% significance of Diebold–Mariano test.

\*\*5% significance of Diebold–Mariano test.

\*10% significance of Diebold–Mariano test.

TABLE A3 Term spread: Relative root MSPE

Models	Full out-of-sample					NBER recessions periods				
	<i>h</i> = 1	<i>h</i> = 3	<i>h</i> = 9	<i>h</i> = 12	<i>h</i> = 24	<i>h</i> = 1	<i>h</i> = 3	<i>h</i> = 9	<i>h</i> = 12	<i>h</i> = 24
<b>Data-poor (<math>H_t^-</math>) models</b>										
AR,BIC (RMSPE)	<b>6.4792</b>	12.8246	<b>16.3575</b>	20.0828	22.2091	<b>13.3702</b>	23.16	23.5697	31.597	23.0842
AR,AIC	<b>1.002*</b>	0.998	<b>1.053*</b>	1.034**	1.041**	<b>1.002</b>	1.001	1.034	0.993	0.972
AR,POOS-CV	<b>1.055*</b>	1.139*	<b>1.000</b>	0.969	1.040**	<b>1.041</b>	1.017	0.895*	0.857*	0.972
AR,K-fold	<b>1.001</b>	1.000	<b>1.003</b>	0.979	1.038*	<b>1.002</b>	0.998	0.911	0.890*	0.983
RRAR,POOS-CV	<b>1.055**</b>	1.142*	<b>1.004</b>	0.998	1.016	<b>1.036</b>	1.014	0.899	0.966	0.945**
RRAR,K-fold	<b>1.044*</b>	0.992	<b>1.027</b>	0.96	1.015	<b>1.024</b>	0.982	0.959	0.795**	0.957*
RFAR,POOS-CV	<b>0.997</b>	0.886	1.125***	1.019	1.107**	<b>0.906</b>	<b>0.816</b>	1.039	0.747**	1.077**
RFAR,K-fold	<b>0.991</b>	0.941	1.136***	1.011	1.084**	<b>0.909</b>	0.823	1.023	0.764*	1.038
KRR-AR,POOS-CV	1.223**	0.881	<b>0.949</b>	<b>0.888**</b>	0.945*	<b>1.083</b>	<b>0.702</b>	<b>0.788***</b>	0.758***	0.948
KRR,AR,K-fold	<b>1.141</b>	0.983	<b>1.098**</b>	0.999	1.048	<b>0.999</b>	<b>0.737</b>	0.833*	<b>0.663**</b>	<b>0.924</b>
SVR-AR,Lin,POOS-CV	1.158**	1.326***	<b>1.071*</b>	1.045	1.045	1.111*	1.072	0.894*	0.828*	0.967
SVR-AR,Lin,K-fold	1.191**	1.056	<b>1.018</b>	0.963	0.993	1.061	1.009	0.886**	0.845**	0.916***
SVR-AR,RBF,POOS-CV	<b>1.006</b>	1.039	<b>1.050*</b>	0.951	0.969	<b>0.964</b>	0.902	0.876*	0.761**	<b>0.864***</b>
SVR-AR,RBF,K-fold	<b>0.985</b>	0.911	<b>1.038</b>	0.946	0.933**	<b>0.990</b>	<b>0.737</b>	0.851**	0.747*	0.968
<b>Data-rich (<math>H_t^+</math>) models</b>										
ARDI,BIC	<b>0.953</b>	0.971	<b>0.979</b>	0.93	<b>0.892***</b>	<b>0.921</b>	0.9	<b>0.790***</b>	<b>0.633***</b>	1.049
ARDI,AIC	<b>0.970</b>	0.956	<b>1.019</b>	0.944	0.917**	<b>0.929</b>	0.867	<b>0.814***</b>	<b>0.647***</b>	1.076
ARDI,POOS-CV	<b>0.954</b>	1.015	<b>1.067</b>	0.991	<b>0.915**</b>	<b>0.912</b>	0.92	0.958	0.769**	1.087
ARDI,K-fold	<b>0.991</b>	1.026	<b>1.001</b>	0.928	0.939	<b>0.958</b>	0.967	0.812***	<b>0.662***</b>	1.041
RRARDI,POOS-CV	<b>0.936</b>	0.994	<b>1.078</b>	0.991	0.964	<b>0.896</b>	<b>0.850</b>	0.952	0.784**	1.092
RRARDI,K-fold	<b>1.015</b>	0.992	<b>1.018</b>	0.934	0.981	<b>0.978</b>	0.899	0.881*	<b>0.635***</b>	1.163*
RFARDI,POOS-CV	<b>0.988</b>	<b>0.830*</b>	<b>0.957</b>	<b>0.873**</b>	<b>0.921**</b>	<b>0.804</b>	<b>0.691</b>	<b>0.785***</b>	<b>0.606***</b>	0.985
RFARDI,K-fold	<b>1.010</b>	0.883	<b>0.997</b>	0.909	0.935**	<b>0.808</b>	<b>0.778</b>	0.827**	<b>0.626***</b>	0.97
KRR-ARDI,POOS-CV	1.355**	0.898	<b>0.993</b>	<b>0.856**</b>	<b>0.884***</b>	<b>0.861</b>	<b>0.682*</b>	<b>0.772***</b>	<b>0.621**</b>	<b>0.905*</b>
KRR,ARDI,K-fold	1.382***	0.96	<b>0.974</b>	<b>0.827**</b>	<b>0.862***</b>	<b>0.858</b>	<b>0.684*</b>	<b>0.754***</b>	<b>0.569***</b>	0.912*
( $B_1$ , $\alpha = \hat{\alpha}$ ),POOS-CV	1.114	1.06	1.126***	1.021	<b>0.866***</b>	<b>1.009</b>	0.981	1.02	<b>0.701**</b>	1.012
( $B_1$ , $\alpha = \hat{\alpha}$ ),K-fold	<b>1.089</b>	1.149**	1.199**	1.106*	0.969	<b>1.001</b>	1.041	0.885	0.767**	0.941
( $B_1$ , $\alpha = 1$ ),POOS-CV	1.125*	1.115	1.172***	1.072	<b>0.844***</b>	1.071	1.006	1.033	0.833	0.96
( $B_1$ , $\alpha = 1$ ),K-fold	<b>1.089</b>	1.149**	1.199**	1.106*	0.969	<b>1.001</b>	1.041	0.885	0.767**	0.941
( $B_1$ , $\alpha = 0$ ),POOS-CV	1.173**	1.312**	1.176***	1.088	0.978	1.089	1.065	0.981	0.799	0.966
( $B_1$ , $\alpha = 0$ ),K-fold	1.163*	1.059	<b>1.069</b>	0.929	<b>0.921**</b>	<b>1.041</b>	0.869	<b>0.810**</b>	0.729**	<b>0.880*</b>
( $B_2$ , $\alpha = \hat{\alpha}$ ),POOS-CV	<b>1.025</b>	0.993	<b>1.101**</b>	1.028	<b>0.897***</b>	<b>0.918</b>	0.908	1.02	<b>0.651***</b>	0.989
( $B_2$ , $\alpha = \hat{\alpha}$ ),K-fold	<b>0.976</b>	0.954	<b>1.098*</b>	1.059	0.935*	<b>0.931</b>	0.875	0.938	0.779*	0.952
( $B_2$ , $\alpha = 1$ ),POOS-CV	1.062	0.968	<b>1.125**</b>	1.049	0.926***	<b>0.897</b>	0.855	1.058	0.79	1.001
( $B_2$ , $\alpha = 1$ ),K-fold	<b>0.980</b>	0.938	<b>1.130**</b>	1.01	0.950*	<b>0.948</b>	0.858	0.976	0.679**	1.001
( $B_2$ , $\alpha = 0$ ),POOS-CV	1.118*	1.082	<b>1.097**</b>	1.008	<b>0.901***</b>	<b>1.004</b>	0.919	1.008	<b>0.669***</b>	1.016
( $B_2$ , $\alpha = 0$ ),K-fold	1.102	0.988	<b>1.047</b>	1.041	<b>0.919**</b>	<b>0.985</b>	0.909	0.870*	0.757*	0.986
( $B_3$ , $\alpha = \hat{\alpha}$ ),POOS-CV	<b>0.971</b>	0.964	<b>1.089**</b>	1.076	0.933*	<b>0.887</b>	<b>0.837</b>	0.908	0.783*	0.904**
( $B_3$ , $\alpha = \hat{\alpha}$ ),K-fold	<b>0.968</b>	0.944	<b>1.009</b>	0.999	<b>0.898***</b>	<b>0.895</b>	0.872	0.883**	0.744**	<b>0.907***</b>
( $B_3$ , $\alpha = 1$ ),POOS-CV	<b>1.006</b>	1.066	<b>1.059*</b>	1.039	<b>0.896***</b>	<b>0.894</b>	1.131	0.974	0.764*	0.987
( $B_3$ , $\alpha = 1$ ),K-fold	<b>0.994</b>	0.924	<b>1.037</b>	0.96	0.975	<b>0.934</b>	0.852	0.834**	0.712**	1.01
( $B_3$ , $\alpha = 0$ ),POOS-CV	1.181*	0.961	<b>1.104**</b>	1.056	0.937**	1.215	0.901	1.013	0.825	0.919*
( $B_3$ , $\alpha = 0$ ),K-fold	<b>0.999</b>	0.953	<b>1.036</b>	0.94	0.97	<b>0.897</b>	0.845	0.923	0.735**	0.925**
SVR-ARDI,Lin,POOS-CV	<b>1.062</b>	0.967	<b>1.164**</b>	1.113*	1.065	1.016	<b>0.762*</b>	1.117	0.714**	1.097
SVR-ARDI,Lin,K-fold	<b>0.990</b>	0.98	<b>1.011</b>	<b>0.922</b>	<b>0.909**</b>	<b>0.935</b>	0.885	0.825**	<b>0.667**</b>	0.994
SVR-ARDI,RBF,POOS-CV	<b>0.972</b>	0.937	<b>1.069</b>	1.039	1.068	<b>0.875</b>	<b>0.741</b>	<b>0.796***</b>	0.707***	1.204*
SVR-ARDI,RBF,K-fold	<b>1.018</b>	0.938	<b>1.123</b>	<b>0.914*</b>	<b>0.882***</b>	<b>0.931</b>	<b>0.781</b>	0.858**	0.778**	<b>0.858**</b>

Note: The numbers represent the relative, with respect to AR,BIC model, root MSPE. Values below 1 implies improvement over the benchmark. Models retained in model confidence set are in bold; the minimum values are underlined.

\*\*\*1% significance of Diebold–Mariano test.

\*\*5% significance of Diebold–Mariano test.

\*10% significance of Diebold–Mariano test.

TABLE A4 CPI inflation: Relative root MSPE

Models	Full out-of-sample					NBER recessions periods				
	<i>h</i> = 1	<i>h</i> = 3	<i>h</i> = 9	<i>h</i> = 12	<i>h</i> = 24	<i>h</i> = 1	<i>h</i> = 3	<i>h</i> = 9	<i>h</i> = 12	<i>h</i> = 24
<b>Data-poor (<math>H_t^-</math>) models</b>										
AR,BIC (RMSPE)	0.0312	0.0257	0.0194	0.0187	0.0188	0.0556	0.0484	0.032	0.0277	0.0221
AR,AIC	0.969***	0.984	0.976*	0.988	0.995	1.000	0.970**	0.999	0.992	1.005
AR,POOS-CV	0.966**	0.988	0.997	0.992	1.009	0.961**	0.981	0.995	0.978	1.003
AR,K-fold	0.972**	0.976**	0.975*	0.988	0.987	1.002	0.965***	0.998	0.992	1.005
RRAR,POOS-CV	0.969**	0.984	0.99	0.993	1.006	0.961**	0.982	0.995	0.963*	0.998
RRAR,K-fold	0.964***	0.979**	0.970*	0.980*	0.989	0.989	0.973**	0.996	0.992	0.997
RFAR,POOS-CV	0.983	<b>0.944*</b>	<b>0.909*</b>	<b>0.930</b>	1.022	1.018	0.998	1.063	1.047	0.998
RFAR,K-fold	<b>0.975</b>	<b>0.927**</b>	<b>0.909*</b>	<b>0.956</b>	0.998	1.032	0.972	1.065	1.103	1.019
KRR-AR,POOS-CV	<b>0.972</b>	<b>0.905**</b>	<b>0.872**</b>	<b>0.872**</b>	0.907**	1.023	<b>0.930**</b>	0.927	0.91	0.852*
KRR,AR,K-fold	<b>0.931***</b>	<b>0.888***</b>	<b>0.836**</b>	<b>0.827***</b>	0.942	0.965	<b>0.920**</b>	0.92	0.915	0.975
SVR-AR,Lin,POOS-CV	1.119**	1.291**	1.210***	1.438***	1.417***	1.116	1.196**	1.204**	1.055	1.613***
SVR-AR,Lin,K-fold	1.239***	1.369**	1.518***	1.606***	1.411***	1.159*	1.326*	1.459**	1.501*	1.016
SVR-AR,RBF,POOS-CV	0.988	1.004	1.086*	1.068**	1.127**	0.999	1.004	0.969	1.091**	1.501***
SVR-AR,RBF,K-fold	0.99	1.025	1.025	1.003	1.370***	0.965	0.979	0.996	0.896**	1.553**
<b>Data-rich (<math>H_t^+</math>) models</b>										
ARDI,BIC	0.96	<b>0.973</b>	1.024	<b>0.895*</b>	0.880*	0.919*	<b>0.906*</b>	0.779*	0.755**	0.713**
ARDI,AIC	<b>0.954</b>	<b>0.990</b>	1.034	<b>0.895</b>	0.884	0.925	<b>0.898</b>	0.778*	<b>0.736**</b>	0.676**
ARDI,POOS-CV	<b>0.950</b>	<b>0.984</b>	1.017	<b>0.910</b>	0.916	0.916*	<b>0.913*</b>	0.832**	0.781***	<b>0.669**</b>
ARDI,K-fold	<b>0.941*</b>	<b>0.990</b>	1.028	<b>0.873*</b>	<b>0.858*</b>	0.891**	<b>0.900</b>	0.784*	<b>0.709***</b>	<b>0.635**</b>
RRARDI,POOS-CV	<b>0.943*</b>	<b>0.975</b>	1.001	<b>0.917</b>	0.914	0.905*	<b>0.912*</b>	0.828**	<b>0.780***</b>	<b>0.666**</b>
RRARDI,K-fold	<b>0.943**</b>	<b>0.983</b>	1.022	<b>0.875*</b>	<b>0.882</b>	0.927*	<b>0.901</b>	<b>0.744**</b>	<b>0.664***</b>	<b>0.613**</b>
RFARDI,POOS-CV	<b>0.947**</b>	<b>0.908***</b>	<b>0.853**</b>	<b>0.914*</b>	0.979	0.976	<b>0.939**</b>	0.988	1.051	0.964
RFARDI,K-fold	<b>0.936***</b>	<b>0.907***</b>	<b>0.854**</b>	<b>0.868**</b>	0.909*	0.962	<b>0.933**</b>	0.979	0.93	1.003
KRR-ARDI,POOS-CV	1.006	1.043	0.959	0.972	1.067	1.046	1.093	0.952	0.948	0.946
KRR,ARDI,K-fold	<b>0.985</b>	0.999	0.983	0.977	0.938	0.998	0.99	1.023	1.022	0.986
( $B_1$ , $\alpha = \hat{\alpha}$ ),POOS-CV	<b>0.918**</b>	<b>0.916*</b>	0.976	0.96	1.026	<b>0.803***</b>	<b>0.900*</b>	0.8	0.848	0.974
( $B_1$ , $\alpha = \hat{\alpha}$ ),K-fold	<b>0.908**</b>	<b>0.921*</b>	1.012	1.056	1.092*	<b>0.823**</b>	<b>0.873*</b>	<b>0.774</b>	0.836	1.069
( $B_1$ , $\alpha = 1$ ),POOS-CV	<b>0.960</b>	<b>0.908**</b>	1.11	1.03	1.076	<b>0.813**</b>	<b>0.889*</b>	0.794	0.825	0.989
( $B_1$ , $\alpha = 1$ ),K-fold	<b>0.908**</b>	<b>0.921*</b>	1.012	1.056	1.092*	<b>0.823**</b>	<b>0.873*</b>	<b>0.774</b>	0.836	1.069
( $B_1$ , $\alpha = 0$ ),POOS-CV	0.971	1.035	1.114*	1.048	1.263**	0.848**	<b>0.906</b>	0.935	0.881	0.99
( $B_1$ , $\alpha = 0$ ),K-fold	<b>0.945*</b>	1.057	1.246**	1.289**	1.260***	<b>0.850***</b>	<b>0.939</b>	0.954	0.944	1.095
( $B_2$ , $\alpha = \hat{\alpha}$ ),POOS-CV	<b>0.923**</b>	<b>0.956**</b>	<b>0.940</b>	0.934	0.945	0.871*	0.959	0.803*	0.802*	0.822*
( $B_2$ , $\alpha = \hat{\alpha}$ ),K-fold	<b>0.921**</b>	<b>0.963*</b>	0.995	0.956	1.037	0.868*	0.957*	0.817*	0.778**	0.861
( $B_2$ , $\alpha = 1$ ),POOS-CV	<b>0.942</b>	<b>0.959</b>	1.158*	1.174**	1.151**	0.877	0.927	0.799	0.907	1.087
( $B_2$ , $\alpha = 1$ ),K-fold	<b>0.922**</b>	<b>0.970</b>	1.066	0.995	1.168*	0.879	0.929	0.853	0.816*	1.009
( $B_2$ , $\alpha = 0$ ),POOS-CV	<b>0.921**</b>	<b>0.940</b>	1.079	0.959	1.071	0.857*	<b>0.881</b>	1.129	0.883	0.851
( $B_2$ , $\alpha = 0$ ),K-fold	<b>0.919**</b>	<b>0.929*</b>	0.997	1.011	1.212**	0.865*	<b>0.883</b>	0.825	0.961	0.853
( $B_3$ , $\alpha = \hat{\alpha}$ ),POOS-CV	<b>0.935*</b>	<b>0.941***</b>	<b>0.961</b>	<b>0.849**</b>	0.901*	0.889*	<b>0.947**</b>	0.791**	0.785**	0.808**
( $B_3$ , $\alpha = \hat{\alpha}$ ),K-fold	<b>0.938*</b>	<b>0.952**</b>	<b>0.937</b>	<b>0.915</b>	0.952	0.891*	0.958*	0.801*	0.784**	0.91
( $B_3$ , $\alpha = 1$ ),POOS-CV	<b>0.933*</b>	<b>0.960</b>	1.076	1.000	1.017	<b>0.856*</b>	<b>0.917*</b>	<b>0.755*</b>	<b>0.769**</b>	0.86
( $B_3$ , $\alpha = 1$ ),K-fold	<b>0.943</b>	0.978	1.006	<b>0.894</b>	1.002	0.889	0.946	0.805	0.806*	0.879
( $B_3$ , $\alpha = 0$ ),POOS-CV	<b>0.946*</b>	<b>0.939**</b>	<b>0.896*</b>	<b>0.871**</b>	1.022	0.894*	<b>0.931**</b>	0.865	0.875	0.896
( $B_3$ , $\alpha = 0$ ),K-fold	<b>0.921***</b>	<b>0.975</b>	<b>0.926</b>	<b>0.920</b>	1.106	0.877***	<b>0.936</b>	0.839	0.892	1.147
SVR-ARDI,Lin,POOS-CV	1.148***	1.202*	1.251***	1.209***	1.219**	1.068	1.053	0.969	0.969	0.943
SVR-ARDI,Lin,K-fold	1.115***	1.390**	1.197**	1.114	1.177*	1.058	1.295*	0.944	0.954	1.036
SVR-ARDI,RBF,POOS-CV	0.963	1.031	1.002	0.962	0.951	0.922	<b>0.915</b>	0.848	0.861	0.996
SVR-ARDI,RBF,K-fold	<b>0.951**</b>	1.002	0.997	0.945	<b>0.797***</b>	0.927*	0.964	0.816**	0.826**	<b>0.659**</b>

Note: The numbers represent the relative, with respect to AR,BIC model, root MSPE. Values below 1 implies improvement over the benchmark. Models retained in model confidence set are in bold; the minimum values are underlined. \*\*\*, \*\*, \* stand for 1%, 5% and 10% significance of -Mariano test.

TABLE A5 Housing starts: Relative Root MSPE

Models	Full Out-of-Sample					NBER Recessions Periods				
	<i>h</i> = 1	<i>h</i> = 3	<i>h</i> = 9	<i>h</i> = 12	<i>h</i> = 24	<i>h</i> = 1	<i>h</i> = 3	<i>h</i> = 9	<i>h</i> = 12	<i>h</i> = 24
<i>Data-poor (<math>H_t^-</math>) models</i>										
AR,BIC (RMSPE)	<b>0.9040</b>	<b>0.4142</b>	<b>0.2499</b>	0.2198	0.1671	<b>1.2526</b>	0.6658	0.4897	0.4158	0.2954
AR,AIC	<b>0.998</b>	<b>1.019</b>	<b>1.000</b>	<b>1.000</b>	1.000	1.01	0.965*	1.000	1.000	1.000
AR,POOS-CV	<b>1.001</b>	<b>1.012</b>	<b>1.019*</b>	1.01	1.036**	1.015	<b>0.936**</b>	1.011*	1.013	1.057**
AR,K-fold	<b>0.993</b>	<b>1.017</b>	<b>1.001</b>	1.000	1.02	1.01	<b>0.951**</b>	1.000	1.000	1.036
RRAR,POOS-CV	<b>1.007</b>	<b>1.007</b>	<b>1.008</b>	1.009	1.031**	1.027*	<b>0.939**</b>	1.001	1.013	1.050**
RRAR,K-fold	<b>0.999</b>	<b>1.014</b>	<b>0.998</b>	<b>0.998</b>	1.024*	1.013	<b>0.941**</b>	1.000**	0.999	1.042**
RFAR,POOS-CV	1.030***	<b>1.026*</b>	<b>1.028*</b>	1.045**	1.018	1.023	<b>0.941*</b>	<b>0.992</b>	1.048*	1.013
RFAR,K-fold	1.017*	<b>1.022</b>	<b>1.007</b>	1.031**	1.008	1.02	<b>0.942*</b>	<b>0.990</b>	1.026	1.01
KRR-AR,POOS-CV	<b>0.995</b>	<b>0.999</b>	<b>0.969*</b>	1.044*	1.037*	<b>0.990</b>	<b>0.972</b>	<b>0.971</b>	1.050**	0.993
KRR,AR,K-fold	<b>0.977*</b>	<b>0.975</b>	<b>0.957**</b>	<b>0.989</b>	1.001	<b>0.985</b>	<b>0.976</b>	1.01	1.006	1.004
SVR-AR,Lin,POOS-CV	1.032***	<b>0.997</b>	<b>1.044***</b>	1.064***	1.223**	1.024*	<b>0.962*</b>	<b>0.986*</b>	0.984	<b>0.957***</b>
SVR-AR,Lin,K-fold	1.036***	1.031	<b>1.002</b>	1.006	1.002	1.013	0.976	1.002	1.009	1.004
SVR-AR,RBF,POOS-CV	<b>1.008</b>	1.047**	<b>1.023</b>	1.035***	1.060***	<b>1.014</b>	0.981	<b>0.947***</b>	1.015	1.017
SVR-AR,RBF,K-fold	1.009	<b>1.011</b>	<b>1.012**</b>	1.020***	1.034**	1.021*	0.969*	1.010***	1.017**	1.001
<i>Data-rich (<math>H_t^+</math>) models</i>										
ARDI,BIC	<b>0.973*</b>	<b>0.989</b>	<b>1.031</b>	1.051	1.05	<b>0.946</b>	1.139	1.048	0.988	0.944
ARDI,AIC	<b>0.992</b>	<b>0.995</b>	<b>1.018</b>	1.06	1.078	<b>1.000</b>	1.113	1.025	1.025	0.96
ARDI,POOS-CV	1.01	<b>1.007</b>	<b>1.080</b>	1.027	0.998	1.023	1.128	1.054	1.015	1.021
ARDI,K-fold	<b>0.992</b>	<b>0.984</b>	<b>1.026</b>	1.061	1.094	<b>1.011</b>	1.093	1.027	1.027	0.958
RRARDI,POOS-CV	<b>0.998</b>	<b>1.007</b>	<b>1.043</b>	<b>0.996</b>	1.082	1.008	1.119	1.041	0.991	1.022
RRARDI,K-fold	<b>0.998</b>	<b>0.988</b>	<b>1.051</b>	1.064	1.089	1.017	1.118	1.033	0.998	0.941
RFARDI,POOS-CV	<b>0.997</b>	<b>0.944**</b>	<b>0.930**</b>	<b>0.920*</b>	0.899**	<b>0.982</b>	<b>0.971</b>	<b>0.965</b>	0.957	0.972
RFARDI,K-fold	<b>0.994</b>	<b>0.962</b>	<b>0.939*</b>	<b>0.914*</b>	<b>0.838***</b>	<b>0.993</b>	0.985	<b>0.986</b>	<b>0.943</b>	0.902*
KRR-ARDI,POOS-CV	<b>0.980</b>	<b>0.943***</b>	<b>0.915**</b>	<b>0.942**</b>	<b>0.884***</b>	<b>0.941*</b>	<b>0.952*</b>	<b>0.949</b>	0.964**	0.986
KRR,ARDI,K-fold	<b>0.982**</b>	<b>0.949**</b>	<b>0.928</b>	<b>0.933</b>	<b>0.889**</b>	<b>0.973</b>	<b>0.973</b>	<b>1.003</b>	1.022	0.994
( $B_1$ , $\alpha = \hat{\alpha}$ ),POOS-CV	<b>1.006</b>	<b>1.000</b>	<b>1.063</b>	1.016	<b>0.895**</b>	1.023	1.099	<b>0.985</b>	1.026	1.022
( $B_1$ , $\alpha = \hat{\alpha}$ ),K-fold	1.040*	1.095**	1.250**	1.335**	1.151*	1.096*	1.152**	1.021	1.127	<b>0.890</b>
( $B_1$ , $\alpha = 1$ ),POOS-CV	1.032**	1.039	1.155	1.045	0.949	1.013	1.063	<b>0.961</b>	1.025	1.062
( $B_1$ , $\alpha = 1$ ),K-fold	1.040*	1.095**	1.250**	1.335**	1.151*	1.096*	1.152**	1.021	1.127	<b>0.890</b>
( $B_1$ , $\alpha = 0$ ),POOS-CV	<b>0.982</b>	<b>0.977</b>	1.084	1.337**	0.959	<b>0.999</b>	1.017	1.014	1.152**	0.964
( $B_1$ , $\alpha = 0$ ),K-fold	<b>0.982</b>	<b>1.006</b>	1.137*	1.158**	1.007	<b>0.994</b>	1.03	<b>1.017</b>	1.067	<b>0.809**</b>
( $B_2$ , $\alpha = \hat{\alpha}$ ),POOS-CV	1.044	<b>0.992</b>	<b>0.975</b>	0.988	0.969	1.177	1.126*	1.034	0.989	0.972
( $B_2$ , $\alpha = \hat{\alpha}$ ),K-fold	<b>0.988</b>	<b>1.003</b>	<b>1.069</b>	1.193**	1.069	1.11	1.188*	1.085	1.133*	0.917
( $B_2$ , $\alpha = 1$ ),POOS-CV	<b>1.001</b>	<b>1.000</b>	<b>0.967</b>	1.02	0.940*	<b>0.961</b>	1.047	<b>0.943</b>	0.985	1.006
( $B_2$ , $\alpha = 1$ ),K-fold	<b>0.989</b>	1.095	1.245**	1.203*	1.093	1.007	1.322***	1.1	<b>0.919</b>	<b>0.848**</b>
( $B_2$ , $\alpha = 0$ ),POOS-CV	1.091*	<b>0.949</b>	<b>0.987</b>	<b>0.971</b>	0.939	1.255	1.027	<b>0.992</b>	<b>0.956</b>	0.994
( $B_2$ , $\alpha = 0$ ),K-fold	1.066	<b>1.068</b>	1.19	1.044	1.064	1.248	1.332**	1.057	<b>0.896***</b>	0.917
( $B_3$ , $\alpha = \hat{\alpha}$ ),POOS-CV	1.009	<b>0.951*</b>	<b>0.935</b>	0.99	<b>0.891**</b>	1.028	1.019	<b>0.958</b>	<b>0.963</b>	0.987
( $B_3$ , $\alpha = \hat{\alpha}$ ),K-fold	<b>0.998</b>	<b>0.977</b>	<b>1.007</b>	1.055	1.044	1.019	1.115	1.017	<b>0.979</b>	<b>0.882*</b>
( $B_3$ , $\alpha = 1$ ),POOS-CV	<b>0.997</b>	<b>0.975</b>	<b>1.024</b>	0.996	0.928*	<b>0.976</b>	1.001	1.021	<b>0.940</b>	1.001
( $B_3$ , $\alpha = 1$ ),K-fold	1.013	<b>1.040</b>	1.071	1.106	1.145	1.042	1.219*	1.036	0.992	1.009
( $B_3$ , $\alpha = 0$ ),POOS-CV	1.022*	<b>0.951*</b>	<b>0.962</b>	<b>0.944</b>	0.932*	1.022	0.981	<b>0.930</b>	<b>0.915**</b>	1.001
( $B_3$ , $\alpha = 0$ ),K-fold	1.030**	<b>1.003</b>	<b>1.005</b>	1.011	1.029	<b>0.986</b>	1.114	<b>0.998</b>	<b>0.955</b>	0.934
SVR-ARDI,Lin,POOS-CV	<b>0.998</b>	1.078*	1.154*	1.137*	1.142	1.047	1.111	<b>0.989</b>	1.009	1.111
SVR-ARDI,Lin,K-fold	<b>0.992</b>	<b>0.971</b>	<b>1.017</b>	1.038	1.11	1.007	1.021	<b>0.988</b>	<b>0.937</b>	0.959
SVR-ARDI,RBF,POOS-CV	<b>0.991</b>	<b>1.004</b>	<b>1.010</b>	1.044	1.034	<b>0.987</b>	1.095	<b>0.981</b>	0.969	1.096
SVR-ARDI,RBF,K-fold	<b>1.003</b>	<b>0.998</b>	<b>1.045</b>	1.078	1.162*	1.022	1.081	1.03	0.984	1.026

Note: The numbers represent the relative, with respect to AR,BIC model, root MSPE. Values below 1 implies improvement over the benchmark. Models retained in model confidence set are in bold; the minimum values are underlined.

\*\*\*1% significance of Diebold–Mariano test.

\*\*5% significance of Diebold–Mariano test.


\*10% significance of Diebold–Mariano test.

## APPENDIX B: ROBUSTNESS OF TREATMENT EFFECTS GRAPHS


### B.1 | Real-time data analysis

We now turn to a real-time forecasting exercise using the vintages of FRED-MD available from 1998M08 to 2017M12 as an additional robustness check. For some series the publication lag can be larger than 1 month, and for those cases we replace missing observations at the forecasting origin date using the factor structure of all the series available in each vintage (EM algorithm as in Stock and Watson (2002b)).


**FIGURE B1** This figure plots the distribution of  $\hat{\alpha}_F^{(h,v)}$  from Equation (11) done by  $(h, v)$  subsets. The subsample under consideration here is **data-poor models**. The unit of the x axis are improvements in OOS  $R^2$  over the basis model. Variables are INDPRO, UNRATE, SPREAD, INF, and HOUST. Within a specific color block, the horizon increases from  $h = 1$  to  $h = 24$  as we are going down. SEs are HAC. These are the 95% confidence bands




**FIGURE B2** This figure plots the distribution of  $\hat{\alpha}_F^{(h,v)}$  from Equation (11) done by  $(h, v)$  subsets. The subsample under consideration here is **data-rich models**. The unit of the x axis are improvements in OOS  $R^2$  over the basis model. Variables are INDPRO, UNRATE, SPREAD, INF, and HOUST. Within a specific color block, the horizon increases from  $h = 1$  to  $h = 24$  as we are going down. SEs are HAC. These are the 95% confidence bands




**FIGURE B3** This figure plots the distribution of  $\hat{\alpha}_F^{(h,v)}$  from Equation (11) done by  $(h, v)$  subsets. The subsample under consideration here are **recessions**. The unit of the x axis are improvements in OOS  $R^2$  over the basis model. Variables are INDPRO, UNRATE, SPREAD, INF, and HOUST. Within a specific color block, the horizon increases from  $h = 1$  to  $h = 24$  as we are going down. SEs are HAC. These are the 95% confidence bands






**FIGURE B4** This figure plots the distribution of  $\hat{\alpha}_F^{(h,v)}$  from Equation (11) done by  $(h, v)$  subsets. The subsample under consideration here are **expansions**. The unit of the  $x$  axis are improvements in OOS  $R^2$  over the basis model. Variables are INDPRO, UNRATE, SPREAD, INF, and HOUST. Within a specific color block, the horizon increases from  $h = 1$  to  $h = 24$  as we are going down. SEs are HAC. These are the 95% confidence bands



**FIGURE B5** This figure plots the distribution of  $\hat{\alpha}_F^{(h,v)}$  from Equation (11) done by  $(h, v)$  subsets. The subsample under consideration here are **the last 20 years**. The unit of the  $x$  axis are improvements in OOS  $R^2$  over the basis model. Variables are INDPRO, UNRATE, SPREAD, INF, and HOUST. Within a specific color block, the horizon increases from  $h = 1$  to  $h = 24$  as we are going down. SEs are HAC. These are the 95% confidence bands




**FIGURE B6** This figure plots the distribution of  $\hat{\alpha}_F^{(h,v)}$  from Equation (11) done by  $(h, v)$  subsets using real-time data vintages. The subsample under consideration here is 2001M09–2017M12. The unit of the  $x$  axis are improvements in OOS  $R^2$  over the basis model. Variables are INDPRO, UNRATE, SPREAD, INF, and HOUST. Within a specific color block, the horizon increases from  $h = 1$  to  $h = 24$  as we are going down. SEs are HAC. These are the 95% confidence bands

Due to our longest forecasting horizon ( $h = 24$ ) we end up forecasting observations from 2001M9 to 2017M12. The results presented here should thus be compared to those for the last 20 years as depicted in Figure B5 above. We compute the forecasting errors using the first release of the data but the results are robust to using the final release. The results are presented in Figure B6. By comparing with results in Figure B5 we can see that all treatment effects are comparable. For instance, the effect of nonlinearity is similar for INDPRO, UNRATE, and INF but weaker for HOUST.


## B.2 | Rolling window analysis

We have performed the same analysis as described in Section 4 but this time with the rolling window approach. The size of the window is 240 and pseudo-out-of-sample period is the same as before. Figure B7 resumes the main results. The pseudo- $R^2$ 's from both expanding and rolling window specifications are pooled when estimating Equation (11). An additional dummy variable is added for the type of the window (the bottom line labeled  $W$ ). Treatment effects are similar to those depicted in Figure 2 except for the hyperparameter tuning feature. Indeed, using cross validation techniques positively impact the predictive performance when rolling window is used. Interestingly, the expanding window approach seems more appropriate for real activity targets, but not for inflation forecasting. This is reasonable given large swings in inflation before it stabilizes since the 90s.


**FIGURE B7** This figure plots the distribution of  $\hat{\alpha}_F^{(h,v)}$  from Equation (11) done by  $(h, v)$  subsets using pooled forecast errors from both expanding and rolling window approaches. The unit of the  $x$  axis are improvements in OOS  $R^2$  over the basis model. Variables are INDPRO, UNRATE, SPREAD, INF, and HOUST. Within a specific color block, the horizon increases from  $h = 1$  to  $h = 24$  as we are going down. SEs are HAC. These are the 95% confidence bands




## APPENDIX C: ADDITIONAL RESULTS



**FIGURE C1** This figure shows the number of regressors in linear ARDI models. Results averaged across horizons




**FIGURE C2** This figure plots time series of variables explaining the heterogeneity of NL treatment effects in Section 6



**FIGURE C3** This figure shows the 3-year rolling window root mean square prediction error (MSPE), the cumulative root MSPE, and Giacomini and Rossi (2010) fluctuation tests for linear and nonlinear data-poor and data-rich models, at 12-month horizon


### Linear SVR Relative Performance to ARDI



**FIGURE C4** This graph display the marginal (un)improvements by variables and horizons to opt for the support vector regression (SVR) in-sample loss function in comparing the data-poor and data-rich environments for linear models. The unit of the x axis are improvements in OOS  $R^2$  over the basis model. SEs are HAC. These are the 95% confidence bands

**FIGURE C5** This graph display the marginal (un)improvements by variables and horizons to opt for the support vector regression (SVR) in-sample loss function in comparing the data-poor and data-rich environments for nonlinear models. The unit of the x axis are improvements in OOS  $R^2$  over the basis model. SEs are HAC. These are the 95% confidence bands

### Non-Linear SVR Relative Performance to KRR



## APPENDIX D: NONLINEARITIES MATTER—A ROBUSTNESS CHECK

In this appendix, we trade random forests for Boosted Trees and KRR for Neural Networks. First, we briefly introduce the newest addition to our nonlinear arsenal. Second, we demonstrate that very similar conclusions to that of Section 5.1.1 are reached using those. This further backs our claim that nonlinearities matter, whichever way they were obtained.

## D.1 | Data-poor

**Boosted Trees AR (BTAR).** This algorithm provides an alternative means of approximating nonlinear functions by additively combining regression trees in a sequential fashion. Let  $\eta \in [0, 1]$  be the learning rate and  $\hat{y}_{t+h}^{(n)}$  and  $e_{t+h}^{(n)} := y_{t+h} - \eta \hat{y}_{t+h}^{(n)}$  be the step  $n$  predicted value and pseudo-residuals, respectively. Then, the step  $n+1$  prediction is obtained as

Contribution of Non-Linearities, by variables




FIGURE D1 This figure compares the two alternative NL models averaged over all horizons. The unit of the  $x$  axis are improvements in OOS  $R^2$  over the basis model. SEs are HAC. These are the 95% confidence bands

Contribution of Non-Linearities, by horizons




FIGURE D2 This figure compares the two alternative NL models averaged over all variables. The unit of the  $x$  axis are improvements in OOS  $R^2$  over the basis model. SEs are HAC. These are the 95% confidence bands

$$\hat{y}_{t+h}^{(n+1)} = y_{t+h}^{(n)} + \rho_{n+1} f(Z_t, c_{n+1})$$

where  $(c_{n+1}, \rho_{n+1}) := \arg \min_{\rho, c} \sum_{t=1}^T (e_{t+h}^{(n)} - \rho_{n+1} f(Z_t, c_{n+1}))^2$  and  $c_{n+1} := (c_{n+1,m})_{m=1}^M$  are the parameters of a regression tree.

In other words, it recursively fits trees on pseudo-residuals. The maximum depth of each tree is set to 10 and all features are considered at each split. We select the number of steps and  $\eta \in [0, 1]$  with Bayesian optimization. We impose  $p_y = 12$ .

**Neural Network AR (NNAR).** We opted for fully connected feed-forward neural networks. The value of the input vector  $[Z_{it}]_{i=1}^{N_0}$  is represented by a layer of input neurons, each taking on the value of a different element in the vector. Each neuron  $j$  of the first hidden layer takes on a value  $h_{jt}^{(n)}$  which is determined by applying a potentially nonlinear transformation to a weighted sum of the input value. The same is true of each subsequent hidden layer until we have reached the output layer which contains a single neuron whose value is the  $h$  period ahead forecast of the model. Formally, our neural network models have the following form:

$$h_{jt}^{(n)} = \begin{cases} f^{(1)} \left( \sum_{i=1}^{N_0} w_{ji}^{(1)} Z_{it} + w_{j0}^{(1)} \right) & n = 1 \\ f^{(n)} \left( \sum_{i=1}^{N_k} w_{ji}^{(n)} h_{it}^{(n-1)} + w_{j0}^{(n)} \right) & n > 1 \end{cases}$$

$$\hat{y}_{t+h} = \sum_{i=1}^{N_h} w_i^{(y)} h_{jt}^{(N_h)} + w_0^{(y)}.$$

We restrict our attention to two fixed architectures: the first one uses a single hidden layer of 32 neurons ( $(N_h, N_1) = (1, 32)$ ) and the second one uses two hidden layers of 32 and 16 neurons, respectively ( $(N_h, N_1, N_2) = (2, 32, 16)$ ). In all cases, we use rectified linear units (ReLU) as the activation functions, that is,

$$f^{(n)}(z) = \max\{0, z\}, \forall n = 1, \dots, N_h.$$

The training is carried out by batch gradient descent using the Adam algorithm. This algorithm is initialized with a learning rate of 0.01 and we use an early stopping rule<sup>31</sup>. And, in an effort to mitigate the effects of overfitting and the impact of random initialization of weights, we train five neural networks with the same architecture and use their average output as our prediction value. In essence, those neural networks are simplified versions of the neural networks used in Gu et al. (2020b) where we got rid of the hyperparameter optimization and use 5 base learners instead of 10. For this algorithm, the input is a set of  $p_y = 12$  lagged values of the target variable. We do not make use of cross-validation, but we do estimate model weights recursively.

## D.2 | Data-rich

**Boosted Trees ARDI (BTARDI).** We consider a vanilla Boosted Trees where the maximum depth of each tree is set to 10 and all features are considered at each split. We select the number of steps and  $\eta \in [0, 1]$  with Bayesian optimization. We impose  $p_y = 12$ ,  $p_f = 12$  and  $K = 8$ .

**Neural Network ARDI (NNARDI).** We opted for fully connected feed-forward neural network with the same architecture as the data-poor version, but we now use  $(p_y, p_f, K) = (12, 10, 12)$  for the inputs.

## D.3 | Results

In line with what reported in Section 5.1.1, we find that NL's treatment effect is magnified for horizons 9, 12, and 24. Additionally, it is found that both algorithms give very homogeneous improvements in the data-rich environment, another finding detailed in the main text. Results for the data-poor environment are more scattered, as they were before. Targets benefiting most from NL in the data-rich environment are INF and HOUST, which is analogous to earlier findings. How-

<sup>31</sup>If improvements in the performance metric doesn't exceed a tolerance threshold for five consecutive epochs, we stop the training.

ever, it was found that the real activity targets benefited more from NL in our main text configuration, which is the sole noticeable difference with results reported here.

## APPENDIX E: DENSITY FORECASTING—TECHNICAL DETAILS

### E.1 | Constructing predictive densities

We opted to build density forecasts from quantile forecasts as proposed by Adrian et al. (2019). For a conditional quantile  $\tau$ , we produce quantile forecasts

$$\hat{Q}_{y_{t+h}|X_t}(\tau|X_t) = g(X_t, \hat{\theta}).$$

We consider the forecasts of quantile random forests<sup>32</sup> and of a quantile regression. We then fit the skewed Student distribution with density

$$f(y; \mu, \sigma, \alpha, \nu) = \frac{2}{\sigma} t\left(\frac{y - \mu}{\sigma}; \nu\right) T\left(\alpha \frac{y - \mu}{\sigma} \sqrt{\frac{\nu + 1}{\nu + \left(\frac{y - \mu}{\sigma}\right)^2}}; \nu + 1\right)$$

where  $t(\cdot)$  and  $T(\cdot)$  are the density and cumulative distribution functions for the Student distribution, respectively, by minimizing the squared distance between the predicted quantiles and the quantiles implied by the selected vector of parameter values<sup>33</sup>. Note that  $\mu$  is the expectation,  $\sigma$  is the variance,  $\alpha$  controls skewness, and  $\nu$ , the degrees of freedom, control kurtosis. Note this estimated counterpart of this density  $\hat{f}(y_{t+h}|X_t)$ .

Methods	Variables	<b><math>h = 1</math></b>	<b><math>h = 3</math></b>	<b><math>h = 9</math></b>	<b><math>h = 12</math></b>	<b><math>h = 24</math></b>
QRF	INDPRO	80 (0) 0.014	83 (0) 0.01	82 (0) 0.008	81 (0) 0.007	83 (0) 0.005
	UNRATE	<b>72 (0.13)</b> 0.347	78 (0) 0.2	78 (0.02) 0.154	<b>76 (0.1)</b> 0.142	<b>67 (0.29)</b> 0.106
	T10YFFM	80 (0) 2.129	75 (0.11) 2.438	<b>70 (0.5)</b> 2.892	66 (0.21) 2.93	<b>64 (0.11)</b> 3.266
	CPIAUCSL	<b>71 (0.35)</b> 0.005	<b>69 (0.41)</b> 0.004	<b>70 (0.47)</b> 0.004	<b>73 (0.17)</b> 0.004	<b>75 (0.03)</b> 0.004
	HOUST	83 (0) 0.324	82 (0) 0.355	<b>76 (0.11)</b> 0.441	<b>74 (0.21)</b> 0.465	<b>63 (0.09)</b> 0.483
QARDI	INDPRO	<b>69 (0.27)</b> 0.012	<b>68 (0.27)</b> 0.008	<b>70 (0.46)</b> 0.006	<b>62 (0.03)</b> 0.005	<b>58 (0)</b> 0.004
	UNRATE	56 (0) 0.274	<b>65 (0.05)</b> 0.164	<b>65 (0.13)</b> 0.12	61 (0.02) 0.117	55 (0) 0.089
	T10YFFM	<b>67 (0.11)</b> 1.795	<b>66 (0.13)</b> 2.214	66 (0.18) 2.491	<b>66 (0.2)</b> 2.63	55 (0) 2.851
	CPIAUCSL	64 (0.01) 0.004	63 (0.01) 0.004	64 (0.05) 0.003	61 (0) 0.003	64 (0.02) 0.003
	HOUST	<b>61 (0)</b> 0.261	<b>61 (0.01)</b> 0.27	58 (0.01) 0.307	50 (0) 0.294	42 (0) 0.322


TABLE E1 Smoothed interval forecasts (70%)

Note: This table shows case mean coverage rates and  $p$ -values in parentheses for a test of nominal correspondance, that is,  $\beta = 1 - \text{size}$ . We use HAC standard errors. Models with coverage closest to  $1 - \text{size}$  are in bold. Mean intervals lengths are indicated below coverages rates.

<sup>32</sup>We use the method proposed in Athey et al. (2019) and implemented in the R package grf.

<sup>33</sup>Note that we minimize over the same grid as Adrian et al. (2019), that is,  $\tau \in \{0.1, 0.25, 0.5, 0.75, 0.9\}$ , but that we produced quantile forecasts for  $\tau \in \{0.05, 0.1, \dots, 0.9, 0.95\}$

**FIGURE E1** Unemployment rate



We produce quantile forecasts from the Quantile Random Forests ARDI and from the Quantile ARDI. The quantile forest was given the largest possible grid of inputs that we used in the rest of the paper  $p_y = 12$  autoregressive lags and  $p_f = 12$  lags of each of the  $n_f = 10$  factors recursively estimated as in the rest of the paper. The input selection for the linear model is complicated by the fact that each quantile requires its own regression. We opted to impose a common set of inputs across all quantiles, but allowed this set to change over time. Specifically, we created a grid of  $p_y, p_f \in \{1, 3, 6, 12\}$  and  $n_f \in \{3, 6, 10\}$  and updated our selection every 24 months as in the rest of the paper using  $K = 5$  fold cross-validation. Since the primary object of interest are the densities, we minimized the average of quantile losses across the quantile grid we use for fitting those densities.


## E.2 | Additional results

**TABLE E2** Interval forecasts (90%)

Methods	Variables	$h = 1$	$h = 3$	$h = 9$	$h = 12$	$h = 24$
QRF	INDPRO	<b>95 (0)</b> 0.023	<b>95 (0)</b> 0.016	<b>93 (0.16)</b> 0.012	<b>92 (0.26)</b> 0.011	<b>91 (0.38)</b> 0.008
	UNRATE	<b>97 (0)</b> 0.573	<b>96 (0)</b> 0.331	<b>92 (0.23)</b> 0.255	<b>91 (0.4)</b> 0.236	<b>86 (0.17)</b> 0.169
	T10YFFM	<b>95 (0)</b> 2.302	<b>91 (0.3)</b> 3.151	<b>89 (0.35)</b> 4.299	<b>87 (0.21)</b> 4.524	<b>84 (0.05)</b> 5.192
	CPIAUCSL	<b>87 (0.04)</b> 0.008	<b>88 (0.16)</b> 0.007	<b>89 (0.4)</b> 0.006	<b>90 (0.43)</b> 0.007	<b>91 (0.32)</b> 0.007
	HOUST	<b>96 (0)</b> 0.422	<b>95 (0.01)</b> 0.503	<b>91 (0.37)</b> 0.7	<b>88 (0.27)</b> 0.75	<b>81 (0.02)</b> 0.786
QARDI	INDPRO	76 (0) 0.019	70 (0) 0.011	78 (0) 0.009	61 (0) 0.007	55 (0) 0.005
	UNRATE	69 (0) 0.396	73 (0) 0.241	71 (0) 0.173	73 (0) 0.174	62 (0) 0.129
	T10YFFM	70 (0) 1.198	70 (0) 2.122	65 (0) 2.747	65 (0) 3.163	58 (0) 3.744
	CPIAUCSL	69 (0) 0.006	73 (0) 0.005	73 (0) 0.004	66 (0) 0.004	68 (0) 0.004
	HOUST	63 (0) 0.187	66 (0) 0.231	55 (0) 0.361	47 (0) 0.357	46 (0) 0.48

Note: This table shows mean coverage rates and  $p$ -values in parentheses for a test of nominal correspondance, that is,  $\hat{\beta} = 1 - \text{size}$ . We use HAC standard errors. Models with coverage closest to  $1 - \text{size}$  are in bold. Mean intervals lengths are indicated below coverages rates.

**FIGURE E2** Spread



### E.3 | Exploring potential sources of the density forecasting performance

We briefly investigate the sources of those gains by performing the regressions featured in Table 3 using log score differences<sup>34</sup> and present results in Tables E4 and E5. The results suggest that the QRF is advantaged during periods of high macroeconomic uncertainty and high pessimism, but also during periods of economic expansion and falling unemployment rate. One possible explanation is that the QRF model got most of its edge from economic recoveries, while another is that the QRF model got most of it during the 1980s when macroeconomic aggregates were more volatile.

Methods	Variables	<b><i>h = 1</i></b>	<b><i>h = 3</i></b>	<b><i>h = 9</i></b>	<b><i>h = 12</i></b>	<b><i>h = 24</i></b>
QRF	INDPRO	79 (0)	<b>80 (0)</b>	77 (0.04)	<b>76 (0.09)</b>	<b>74 (0.19)</b>
		0.013	0.01	0.007	0.007	0.005
	UNRATE	85 (0)	82 (0)	80 (0)	79 (0.01)	<b>73 (0.24)</b>
		0.335	0.191	0.145	0.135	0.109
	T10YFFM	82 (0)	<b>76 (0.04)</b>	<b>70 (0.48)</b>	<b>72 (0.33)</b>	<b>67 (0.27)</b>
		1.295	1.835	2.631	2.795	3.237
QARDI	CPIAUCSL	<b>69 (0.3)</b>	<b>70 (0.48)</b>	<b>69 (0.37)</b>	<b>70 (0.48)</b>	<b>72 (0.21)</b>
		0.004	0.004	0.004	0.004	0.004
	HOUST	<b>85 (0)</b>	<b>81 (0)</b>	<b>73 (0.25)</b>	<b>70 (0.47)</b>	<b>61 (0.05)</b>
		0.26	0.303	0.415	0.452	0.486
	INDPRO	<b>61 (0)</b>	58 (0)	<b>64 (0.05)</b>	52 (0)	47 (0)
		0.012	0.008	0.006	0.005	0.004
QARDI	UNRATE	<b>57 (0)</b>	<b>64 (0.01)</b>	<b>65 (0.12)</b>	<b>61 (0.02)</b>	52 (0)
		0.298	0.172	0.118	0.113	0.089
	T10YFFM	<b>60 (0)</b>	56 (0)	54 (0)	58 (0)	49 (0)
		0.714	1.419	1.984	2.292	2.806
	CPIAUCSL	58 (0)	59 (0)	62 (0.02)	55 (0)	54 (0)
		0.004	0.003	0.003	0.003	0.003
QARDI	HOUST	54 (0)	54 (0)	45 (0)	42 (0)	34 (0)
		0.137	0.174	0.253	0.283	0.345

TABLE E3 Interval forecasts (70%)

Note: This table shows case mean coverage rates and *p*-values in parentheses for a test of nominal correspondance, that is,  $\hat{\beta} = 1 - \text{size}$ . We use HAC standard errors. Models with coverage closest to  $1 - \text{size}$  are in bold. Mean intervals lengths are indicated below coverages rates.




FIGURE E3 Housing starts

<sup>34</sup>They are arranged so that a positive difference maps into an advantage for the QRF model.

TABLE E4 Heterogeneity of NL treatment effect on log scores

	(1) Base	(2) All horizons	(3) Last 20 years	(4) Last 20 years—all horizons
itr_CHSPI	0.266 (0.184)	0.357* (0.139)	-0.0401 (0.213)	0.0592 (0.157)
itr_ANFCI	-0.260 (0.274)	-0.426* (0.210)	0.0201 (0.481)	-0.257 (0.338)
itr_MacroU_h1	0.784** (0.259)	0.600** (0.191)	0.492 (0.330)	0.350 (0.248)
itr_UMCSENT	-0.643* (0.324)	-0.599* (0.250)	-0.265 (0.300)	-0.227 (0.237)
itr_PMI	0.222 (0.172)	0.148 (0.130)	-0.285 (0.241)	-0.293 (0.177)
itr_UNRATE_exante	-0.497** (0.180)	-0.00502 (0.143)	0.00794 (0.253)	0.239 (0.189)
itr_GS1	-0.175 (0.329)	0.271 (0.256)	0.153 (0.434)	0.210 (0.330)
itr_PCEPI	1.414*** (0.419)	0.827** (0.302)	0.593 (0.514)	0.257 (0.376)
Observations	6840	11400	3615	6025

Note: Standard errors in parentheses.

\* $p < 0.05$ .

\*\* $p < 0.01$ .

\*\*\* $p < 0.001$ .

TABLE E5 Heterogeneity of NL treatment effect on log scores

	(1) Base	(2) All horizons	(3) Last 20 years	(4) Last 20 years—all horizons
rec	-1.075* (0.540)	-0.375 (0.408)	-0.998* (0.502)	-0.857 (0.447)
itr_CHSPI	0.188 (0.194)	0.337* (0.146)	-0.136 (0.228)	-0.0112 (0.165)
itr_ANFCI	-0.279 (0.273)	-0.418* (0.210)	-0.00820 (0.481)	-0.234 (0.339)
itr_MacroU_h1	0.860** (0.271)	0.623** (0.199)	0.491 (0.329)	0.354 (0.249)
itr_UMCSENT	-0.640* (0.322)	-0.622* (0.248)	-0.345 (0.302)	-0.274 (0.237)
itr_PMI	0.266 (0.172)	0.151 (0.130)	-0.241 (0.243)	-0.315 (0.177)
itr_UNRATE_exante	-0.638** (0.199)	-0.0532 (0.155)	-0.142 (0.281)	0.136 (0.206)
itr_GS1	-0.187 (0.328)	0.281 (0.255)	0.274 (0.429)	0.239 (0.325)
itr_PCEPI	1.588*** (0.433)	0.856** (0.307)	0.687 (0.529)	0.385 (0.396)
Observations	6840	11400	3615	6025

Note: Standard errors in parentheses.

\* $p < 0.05$ .

\*\* $p < 0.01$ .

\*\*\* $p < 0.001$ .