

*Test condition: • STANDA controllers; • Power supply – 36V.

Specifications Ordering Information 0.5 mm Lead screw pitch Travel Weight, Qty. Model range, Resolution in full step* $2.5 \, \mu m$ kg mm Resolution in 1/8 step 0.31 µm 8MT175-100 100 1.5 Max. speed* 10 mm/s 8MT175-100-MEn1 1.5 100 Load capacity 8MT175-150 150 1.5 Horizontal 8 kg Vertical 3 kg 8MT175-150-MEn1 150 1.5 Motor connector DB9(M) 8MT175-200 200 1.6 (wiring 8MT175-200-MEn1 200 1.6 diagram) 8MT175-50 50 Stepper motor 4247 **Assemblies** 8MT175-50-MEn1 50 1 X-Y directly 8MT175V-100-VSS42 100 1.5 Ζ 2AB175 8MT175V-150-VSS42 150 1.5 Recommended 8SMC5-USB 8MT175V-200-VSS42 200 1.6 controllers 8MT175V-50-VSS42 50 1 1 Mechanical end limit 2 switches - ...-MEn1 models have motor with integrated rotary ecoder Switch polarity pushed is - ...-VSS42 are vacuum compatible models (up to 10⁻⁶ closed

Related products







Similar products












7T175-150



8MT175-50 Motorized Linear Stage is integrated as a Z-axis in 6-axis motorized system.




8MT175 Motorized Linear Stages are incorporated in multi-axis automated system.

→ **STANDA** in Lithuania STANDA P.BOX 2684 , 03001 Vilnius 9 P.O., Lithuania Phone +370 5 2651474, Fax +370 5 2651483 E-mail: sales@standa.LT







Vacuum compatible (10 $^{\rm -6}$ Torr) encoder equipped 8MT175 $\!\pmb{V}\!\!\!V$ motorized linear stages demonstration.



Vacuum compatible (10⁻⁶ Torr) motorized linear stages in XYZ assembly.



8MT175-100 Motorized Linear Stage is utilized as a Z-axis in multi-axis motorized system.



Products | Support | Company | Contacts | Trade Shows | You Tube

Motorized Linear Stages © 2000 - 2023 STANDA LTD. All rights reserved.