

# TROTTER CIRCUIT OPTIMIZATION THROUGH ADIABATIC COMPUTATION

**Kim, Hyunseong**

Quantum Field and Gravity Theory Group,  
GIST, Department of Physics and Photonics

August 31, 2023

- 1 Lie-Trotter Formula and Circuit . . . . . 3**
  - 1.1 Trotterization . . . . . 3
- 2 Optimization of Hamiltonian . . . . . 5**
  - 2.1 Mutually Commuting Partition . . . . . 6
  - 2.2 Pauli Frame . . . . . 13
- 3 Degenerate Reducing of Mutually Hamiltonian . . . . . 16**
- 4 Optimization Example . . . . . 20**
  - 4.1 HeH+ molcular hamiltonian . . . . . 20

## Part I

### QUBO PROBLEMS IN CIRCUIT OPTIMIZATION

# LIE-TROTTER FORMULA AND CIRCUIT

## TROTTERIZATION

To simulate time-evolving process such as adiabatic quantum process, we approximate continuous process with discrete steps.

We call the discretized approximation as **Trotter** formula.

$$\exp(-i\mathcal{H}t) \approx \prod_i^n \exp\left(-i\mathcal{H}_i \frac{t}{n}\right) \quad (1)$$

where,  $n$  is a trotter steps.


As we increase the step number  $n$ , we get more precise unitary transformation.

# LIE-TROTTER FORMULA AND CIRCUIT

## TROTTERIZATION

Practically, each terms of Hamiltonian are described with **Pauli string**. A single Pauli string, for example  $XZ/Y$ , Hamiltonian has a well known corresponding circuit.

$$\exp(-i\Delta t(X \otimes Z \otimes I \otimes Y)) \quad (2)$$



## OPTIMIZATION OF HAMILTONIAN

Optimization of evolution circuit is a combination of two parts.

- ▶ Mutually Commuting Partition
- ▶ Pauli-Frame

# OPTIMIZATION OF HAMILTONIAN

## MUTUALLY COMMUTING PARTITION

Pauli strings are always anti-commute or commute each other.

For given two Pauli strings,  $P_i, P_j$ ,

$$\text{either } [P_i, P_j] = 0 \text{ or } \{P_i, P_j\} = 0 \quad (3)$$

where,  $[\ ]$  is a commutator, and  $\{ \}$  is an anti-commutator.

If all Pauli-terms of Hamiltonian are mutually commute each other, Eq(1) becomes an unitary operator of total Hamiltonian evolution of time  $t$ .

$$\exp(-i\mathcal{H}t) = \prod_i^n \exp(-i\mathcal{H}_i t) \quad (4)$$

# OPTIMIZATION OF HAMILTONIAN

## MUTUALLY COMMUTING PARTITION

1. We must know all commuting relation of the given Pauli-string set.
2. How to make a mutually partitions of the given set?



# OPTIMIZATION OF HAMILTONIAN

## MUTUALLY COMMUTING PARTITION

To make a mutually commuting partition, we have to know all commuting relationships of the given Pauli-terms of Hamiltonian. We can check the commutation with General commutativity(GC), see Gokhale et al., 2020.

If a system is  $n$  qubits system and there are  $m$  number of Pauli-terms, total operation would be, roughly,

$$\binom{m}{2} * n = O(m^2 n) \quad (5)$$

Unfortunately,  $\max(m) = 2^n$  for  $n$ -qubit system Hamiltonian, it could be exponentially growth.

# OPTIMIZATION OF HAMILTONIAN

## MUTUALLY COMMUTING PARTITION

Chapuis et al., 2018 suggested acceleration of commuting term determination.  
They decompose single Pauli-string into  $X$  and  $Z$  families.

- ▶  $X$ -family:  $III X, X I X I, I I X I, X X I I, I X X X, \dots$
- ▶  $Z$ -family:  $III Z, Z I Z I, I I Z I, Z Z I I, I Z Z Z, \dots$

$$YZIX = XIIX \cdot ZZII = x_i \cdot z_j \quad (6)$$

$$[P_i, P_j] = [x_k z_l, x_m, z_n] = \begin{cases} 0 & \text{if } [z_l, x_m] = [x_k, z_n] \\ -2P_i P_j & \text{otherwise} \end{cases} \quad (7)$$

# OPTIMIZATION OF HAMILTONIAN

## MUTUALLY COMMUTING PARTITION

Now, if we have compatible graph of Pauli-set, we can extract mutually commuting partition by solving a sequential Max-Clique problem of the commute graph.

It is well known NP-complete problem, from 21-complete problems. See Karp, 1972.


Kurita et al., 2023 suggested Ising formulation for finding Max-clique finding problem of compatible graph.

$$\mathcal{H} = -\mu_0 \sum Z_i + \mu_1 \sum h_{ij} Z_i Z_j \quad (8)$$

where,  $h_{ij} = 0$  if  $Z_i - Z_j$  edge weight is 0 otherwise 1,  $\mu_0 = 1, \mu_1 = 2$  in Kurita et al..


# OPTIMIZATION OF HAMILTONIAN

## MUTUALLY COMMUTING PARTITION




# OPTIMIZATION OF HAMILTONIAN

## MUTUALLY COMMUTING PARTITION



# OPTIMIZATION OF HAMILTONIAN


## PAULI FRAME



$$\mathcal{H} = tXZIY + \theta_1 XIII + \theta_2 IZII + \theta_3 IIII$$

# OPTIMIZATION OF HAMILTONIAN

## PAULI FRAME




$$\mathcal{H} = tXZIY + \theta_1XIII + \theta_2XZII + \theta_3IIII$$

# OPTIMIZATION OF HAMILTONIAN

## PAULI FRAME

Schmitz et al., 2023 analyzed and Pauli-Frame method and optimized circuit with minimum cost of  $CNOT$ ,  $H$ ,  $S$  operations to

$$\begin{array}{ccccccc}
 Z_1 & X_1 & & X_1 & Z_1 & & X_1 & Z_1 & & X_1 & Z_1 \\
 Z_2 & X_2 & & Z_2 & Z_2 & & X_1 Z_2 & Z_1 X_2 & & X_1 Z_2 & Z_1 X_2 \\
 Z_3 & X_3 & \rightarrow_{H_2, H_4 - S_4} & Z_3 & X_3 & \rightarrow_{CNOT^{1,2}} & Z_3 & X_3 & \rightarrow_{CNOT^{2,4}} & Z_3 & X_3 \\
 Z_4 & X_4 & & Y_4 & Z_4 & & Y_4 & X_4 & & X_1 Z_2 Y_4 & Z_1 X_2 Z_4
 \end{array} \quad (9)$$



$$\mathcal{H} = tXZIY + \theta_1 XIII + \theta_2 XZII + \theta_3 IIII$$



## DEGENERATE REDUCING OF MUTUALLY HAMILTONIAN

If there are two max clique on graph, sharing same number of nodes, the next Hamiltonian pick one of them randomly.

$$\mathcal{H} = -\mu_0 \sum Z_i + \mu_1 \sum h_{ij} Z_i Z_j \quad (10)$$

Eventhough, they are same in commutation graph, frame change cost can be different.


In this project, we only consider  $H$ ,  $S$  costs. The weight of each Pauli-terms would be calculated with function  $w(, )$ , such that

- ▶  $w(, ) = 0$ :  $(X, X), (Y, Y), (Z, Z), (Z, I)$
- ▶  $w(, ) = 1$ :  $(X, Z), (X, Y), (X, I)$
- ▶  $w(, ) = 2$ :  $(Y, I), (Y, Z)$

For  $N$ -qubit system, extended weight function  $W(, )$  is defined as,

$$W(S_i, S_j) := \frac{1}{N} \sum_{k=1}^N w((S_i)_k, (S_j)_k) \quad (11)$$

## DEGENERATE REDUCING OF MUTUALLY HAMILTONIAN



**Figure.** Compatible and basis transform weight graph example. Left graph is a compatible graph of 5 Pauli basis of 2 qubits system and edges are indicating commutation relationship. Right graph is a basis transform weight graph of the same Pauli-basis set of the left.

## DEGENERATE REDUCING OF MUTUALLY HAMILTONIAN

We can redefine a Hamiltonian for optimization,

$$\mathcal{H} = -\mu_0 \sum Z_i + \mu_1 \sum_{i < j} h_{ij} Z_i Z_j + \mu_2 \sum_{i < j} w_{ij} Z_i Z_j \quad (12)$$

To avoid the degeneration of energy and to conserve max and commuting condition, the coefficients,  $\mu_0, \mu_1, \mu_2$  have next relationship.

For  $N$  qubits system,

$$\|\mu_1\| > N \|\mu_0\| \quad \|\mu_0\| > \frac{1}{2} N(N-1) \|\mu_2\| \quad (13)$$

## DEGENERATE REDUCING OF MUTUALLY HAMILTONIAN

Full procedure of algorithm.

1. Find a compatible graph of the given Hamiltonian
2. Calculate weight between Pauli-strings with Eq(11)
3. Find a min-number of mutually commuting partition,  $p_1, p_2, \dots$ , using **adiabatic computer**.
4. Find a shortest hamilton path of each local partition  $p_i$ , <- reduced problem, you can use classic algorithm.
5. Connecting  $p_i$  in order to following 4 step result.

## OPTIMIZATION EXAMPLE

### HEH+ MOLECULAR HAMILTONIAN


Pennylane HeH+ molecule Hamiltonian:

4 qubits are required and consist of 25 Pauli-terms.

'ZXZX','IYIY','ZYZY','IZIZ','XZXZ','XIXI','YZYZ','YIYI','ZIZI', 'IIIZ', 'ZZII', 'IZZI', 'ZIIZ', 'IIZI', 'IIZI', 'IIZI', 'IIZI',  
'XZXI', 'YZYI', 'XXYY', 'YXXY', 'YYXX', 'XYYX', 'IYZY', 'IXZX'

# OPTIMIZATION EXAMPLE

## HEH+ MOLECULAR HAMILTONIAN



**Figure.** Commuting Partition HeH+ Hamiltonian Pauli-terms. Left: Ising formula solution of D-Wave. Right: Basis cost term weight added optimization.

## OPTIMIZATION EXAMPLE

### HEH+ MOLECULAR HAMILTONIAN

The optimization result is 3 number of partition.


$p_0$  ['ZXZX', 'IYIY', 'ZYZY', 'IZIZ', 'XZXZ', 'XIXI', 'YZYZ', 'YIYI', 'ZIZI']

$p_1$  ['IIIZ', 'ZZII', 'IZZI', 'ZIIZ', 'IZII', 'IIZI', 'ZIII', 'IIZZ']

$p_2$  ['XZXI', 'YZYI', 'XXYY', 'YXXY', 'YYXX', 'XYYX', 'IYZY', 'IXZX']

# OPTIMIZATION EXAMPLE

HEH+ MOLECULAR HAMILTONIAN





# OPTIMIZATION EXAMPLE

## HEH+ MOLECULAR HAMILTONIAN






Compare to PennyLane ApproxTimeEvolve() circuit

```
gates: 270
depth: 169
shots: Shots(total=None)
gate_types:
{'RZ': 106, 'CNOT': 84, 'RX': 80}
gate_sizes:
{1: 186, 2: 84}
```

```
gates: 137
depth: 107
shots: Shots(total=None)
gate_types:
{'Hadamard': 16, 'CNOT': 74, 'RZ': 25, 'S': 11, 'Adjoint(S)': 11}
gate_sizes:
{1: 63, 2: 74}
```

**Figure.** Left: PennyLane ApproxTimeEvolve() trotter number =1 circuit. Right: Optimized evolve circuit.

## REFERENCES I

-  Chapuis, G., Djidjev, H. N., Hahn, G., & Rizk, G. (2018, April). **Finding Maximum Cliques on the D-Wave Quantum Annealer [arXiv:1801.08649 [quant-ph]]**.
-  Gokhale, P., Angiuli, O., Ding, Y., Gui, K., Tomesh, T., Suchara, M., Martonosi, M., & Chong, F. T. (2020).  $O(N^3)$  **Measurement cost for variational quantum eigensolver on molecular hamiltonians**. *IEEE Transactions on Quantum Engineering*, 1, 1–24.  
<https://doi.org/10.1109/TQE.2020.3035814>
-  Karp, R. M. (1972). **Reducibility among combinatorial problems**. In R. E. Miller, J. W. Thatcher, & J. D. Bohlinger (Eds.), *Complexity of computer computations: Proceedings of a symposium on the complexity of computer computations, held march 20–22, 1972, at the ibm thomas j. watson research center, yorktown heights, new york, and sponsored by the office of naval research, mathematics program, ibm world trade corporation, and the ibm research mathematical sciences department* (pp. 85–103). Springer US. [https://doi.org/10.1007/978-1-4684-2001-2\\_9](https://doi.org/10.1007/978-1-4684-2001-2_9)
-  Kurita, T., Morita, M., Oshima, H., & Sato, S. (2023). **Pauli string partitioning algorithm with the ising model for simultaneous measurements [PMID: 36653017]**. *The Journal of Physical Chemistry A*, 127(4), 1068–1080. <https://doi.org/10.1021/acs.jpca.2c06453>
-  Schmitz, A. T., Sawaya, N. P. D., Johri, S., & Matsuura, A. Y. (2023, May). **Graph Optimization Perspective for Low-Depth Trotter-Suzuki Decomposition [arXiv:2103.08602 [cond-mat, physics:math-ph, physics:physics, physics:quant-ph]]**.