

Example data :

If you want to start the program without any measured data and preexisting model, Do the following:

Rename picks.sgt to any other name (e.g. pick1.sgt), start reframodel. When asked whether you want to open another pick file, say no and when asked to choose a model, click on abandon (or whatever it is on English systems, so don't choose an existing model). Then you will be asked for the geometry of the synthetic model you want to create as described in the manual. The resulting figures are shown in folder "Figures/No_starting-model", after having reduced the data as shown in Figure "Dialog_select_picks.png". Then run "Tools/Run Forward Model" to get the figure with calculated arrival times.

If you want to reconstruct the outputs shown in folder "Figures/Using-existing-model", let file picks.sgt untouched and start the program choosing file "model.txt" as existing model and reducing the number of picks as shown in Figure "Dialog_select_picks.png". Run "Tools/Run Forward Model" to get the figure with calculated arrival times.

To get the two inversion results, run the inversion ("Tools/Inversion Parameters...") once with a simple gradient starting model (folder "Figures/Inversion_gradient") using the parameters shown in figure "Dialog_inversion_gradient.png" (the outputs from reframodel are stored in "Example/inversion_gradient_model", and then starting with the interactive model, using the parameters shown in file "Dialog_inversion_interactive_model.png" in that folder. The program outputs for the two inversions are in folders "inversion_gradient_model" and "inversion_interactive_model" respectively.