

NETWORK SERVICES

QUẢN TRỊ MẠNG VÀ HỆ THỐNG Networks and Systems Administration

MSc. Trần Thị Dung



Content

- O DHCP
- O NAT
- O ACL

Content

- O DHCP
- O NAT
- O ACL


DHCP

- ODHCP Overview
- DHCP Operation
- DHCP Implementation

DHCP overview

 DHCP assigns IP addresses and other network configuration information dynamically


- DHCP server provides
 - IP address
 - Subnet mask
 - Default gateway
 - DNS server




DHCP

- ODHCP Overview
- DHCP Operation
- DHCP Implementation


DHCP overview




DHCP Server on modem/AP



450M Wireless N Router Model No. TL-WR940N



DHCP Server on modem/AP




DHCP

- ODHCP Overview
- DHCP Operation
- DHCP Implementation


DHCP Operation

- Router as a DHCP server
- Router as a DHCP Relay agent


Router as a DHCP Server



Router as a DHCP Relay agent



Router as a DHCP Relay agent



Content


- O DHCP
- \circ NAT
- O ACL

NAT


- ONAT Overview
- NAT Operation

NAT overview

 Private IP addresses are used within an organization and home networks.




 Public IP address can be routed over the Internet



NAT overview (Cont.)

- Private IP addresses cannot be routed over the Internet.
- NAT is used to translate private IP addresses to public addresses that can be routed over the Internet.
- One public IPv4 address can be used for thousands of devices that have private IP addresses.



NAT overview (Cont.)

- Network Address Translation NAT
- Case 1: All devices in local network share one or many public IPv4 addresses to access Internet
- Case 2: The Internet client wants to connect to server behind NAT with public IP address



Content

- ONAT Overview
- NAT Operation




NAT operation

 Case 1: All devices in local network share one or many public IPv4 addresses to access Internet



NAT Operation






NAT Operation

 Case 2: The Internet client wants to connect to server behind NAT with public IP address




NAT Operation

2: NAT router changes datagram destination address from 118.69.123.142, 80 to 10.0.0.10, 80, that is pre-defined in the table




3: server replies, source address: 10.0.0.10, 80



1: Client 138.76.29.7 sends / datagram to 118.69.123.142, 80




NAT Forwarding – Port Forwarding





NAT Forwarding – Port Forwarding





Content

- O DHCP
- O NAT
- OACL

ACL overview

O An ACL is a sequential list of permit or deny statements that control whether a router forwards or drops packets based on information found in the packet header.

