


1 Create a new project in MyCSC portal

1. Log in to the CSC environment, <https://my.csc.fi/>.
2. Navigate to the **Projects** tab in MyCSC portal management view and click **+ New Project**.




3. Enter the required project details:
 - **Project name and description**
 - **Course end date:** can be at most six months from the creation date.
 - **Project resources:**
 - o Primary science area: **Engineering and technology**
 - o Secondary science area: **Other engineering and technologies**
 - Review the Terms of Use and READ CAREFULLY [documentation about CSC services for students](#)

Click the **Create Project** button.


* A course project is single-use. It cannot be extended, copied, or allocated additional resources. The default resource allocation for the project is 100 000 BU (billing units).

* The project and all its resources will be automatically deleted after the end date.


Note: Personal data must not be stored in course project services.




4. Add services to your project. In this course, you will need the Rahti service from CSC's offerings. You will also need the **project number** later for the actual application deployment.




5. Click on the **+ Add services** button. A new view with services listed will appear. Select **Rahti**, accept the terms of use for the Rahti and click **Add selected services** button.




6. In the **Services** card, you will now see **Rahti Container Cloud** service. Log in to the Rahti service by clicking the **Login** button.




A new tab <https://rahti.csc.fi/> will open in your browser. Click the **Login** button.



Click **Login** and sign in using your **CSC** or **Haka** credentials.



Note: if you have registered to my.csc.fi just before following these instructions, it may take some time for your account to activate, so you might see an error message: “Could not find user”. Try going back to the Rahti service login step after a while.




Once your login is successful, you can get started with a tour to improve your workflow or skip it.

2 Deploy a Spring Boot Application with an H2 database on Rahti

2.1 Prepare your Spring Boot Application

1. Create a new file in the **root** directory of your Spring Boot application and name it **Dockerfile** (without a file extension).




2. Copy the following content into the **Dockerfile** (this can also be found in the course's Moodle page):

```
FROM eclipse-temurin:17-jdk-focal as builder
WORKDIR /opt/app
COPY .mvn/ .mvn
COPY mvnw pom.xml ./
RUN chmod +x ./mvnw
RUN ./mvnw dependency:go-offline
COPY ./src ./src
RUN ./mvnw clean install -DskipTests
RUN find ./target -type f -name '*.jar' -exec cp {} /opt/app/app.jar \; -
quit
FROM eclipse-temurin:17-jre-alpine
COPY --from=builder /opt/app/*.jar /opt/app/
EXPOSE 8080
ENTRYPOINT ["java", "-jar", "/opt/app/app.jar"]
```
3. Push your updated application to GitHub.
Note: These instructions assume your GitHub repository is **public**. (If needed, you can make it public temporarily during deployment and switch it back to private later.) Private repositories can also be used, but this document does not cover that method.

2.2. Spring Boot application deployment

1. Navigate to the top left menu. Choose your role **Administrator** → **Home** → **Projects**. The deployment is done by creating a new project in the Rahti service, click the **Create Project** button.



2. Enter the required details. **Name** must be **unique** and it is **case sensitive**. Click **Create** button.
Note: To successfully create the project, you must enter the **CSC project number** (e.g. **csc_project:<project number>**) in the **Description** field.
If you don't know project number, see **step 1.4**.

Create Project

An OpenShift project is an alternative representation of a Kubernetes namespace.
[Learn more about working with projects](#)

Name * ?

studentlist-project

Display name

Student list deployment with H2 database

Description

csc_project2013444

Cancel Create



HAAGA-HELIA
ammattikorkeakoulu


Software Development

Dovile Martinonyte
Renne Jämsén


2025-05-14

6 (12)


- Now you can deploy your Spring Boot application inside the newly created project in the Rahti service. Navigate to **Developer** mode. If your project name is not visible, select it from the **Project** drop-down menu.



- Click **+Add** and from the available resources select **Git Repository** → **Import from Git**.



5. Fill in the **Import from Git** form by entering the **Git Repo URL**.



Project: studentlist-project Application: All applications

Import from Git

Git

Git Repo URL *

https://github.com/dovile-mart/studentlistH2


Validated

> Show advanced Git options

Multiple import strategies detected
The Dockerfile at Dockerfile is recommended.

Dockerfile Edit Import Strategy

If your repository contains multiple projects, open **Advanced Git options** and specify the path to the root folder in the **Content dir** field:



Project: studentlist-project-2 Application: All applications

Import from Git

Git

Git Repo URL *

https://github.com/dovile-mart/repository-student-app.git

Validated

Hide advanced Git options

Git reference

Optional branch, tag, or commit.

Context dir

/StudentListCrud

Optional subdirectory for the source code, used as a context directory for build.

A name for your application component in **Name** field is be generated automatically but you can also create your own **unique name**. This component will be used to name associated resources. Then click the **Create** button.



General

Application

studentlist-h-2-app

Select an Application to group this component.

Name *

studentlist-h-2

A unique name given to the component that will be used to name associated resources.

Build

Build Option

Buids

Build Option to use for building the application.

[Show advanced Build option](#)

Deploy

Resource type

Deployment

Resource type to generate. The default can be set in [User Preferences](#).

[Show advanced Deployment option](#)

Advanced options

Target port

8080

Target port for traffic.

☒ Create a route
Exposes your component at a public URL.


[Show advanced Routing options](#)

Click on the names to access advanced options for [Health checks](#), [Scaling](#), [Resource limits](#), and [Labels](#).


Create

Cancel


6. The build process will start and may take a few minutes. You can find application component under **Developer** mode → **Topology** view:




7. Follow the build progress in the **Developer** mode → **Builds** view. While application is being built, its status will be **Running**.



8. Once the build is complete, the status will change to **complete**.



9. You can find your application's URL, by navigating to the **Topology** view → selecting the component → when the sidebar on the right opens, navigate to the **Resources** tab → the application's URL will be under **Routes**. Click the link, and the application will open in your web browser.



10. Congratulations, your application is deployed!

