Uplink: How It Works

One photo of leftover food becomes a safe, completed donation, decided by three AI agents with competing goals and no boss.

A complete guide to the project: what it does, how the agents work together, the architecture, and how to explain it to others.

UCSC AI Hackathon · Cisco Cloud AI track, "When AI Agents Disagree" · October 10, 2026

1. Uplink in one minute
2. The problem and who uses it
3. A donation's journey
4. System architecture
5. The agentic workflow
6. Safety rules and red lines
7. When the agents should not agree
8. The wider agent network
9. Reading the photo
10. Voices
11. The two websites
12. Evidence: does the team do better?
13. What's real and what's simulated
14. Code map
15. How to run it
16. Explaining Uplink to others
17. Glossary

1 Uplink in one minute

Uplink turns one photo of leftover food into a safe, completed donation. A business photographs its surplus food, AI identifies it, and three AI agents with competing goals work out where it should go and who should drive it.

AGENT	WHAT IT WANTS	A TYPICAL ARGUMENT
Speed	Food delivered fast and reliably, long before it spoils	"Hot food can't wait. The paid courier is 8 minutes away."
Cost	Spend as little as possible on drivers	"Use the volunteer. She's free."
Need	Food goes to whoever has waited longest	"Grace Kitchen hasn't had a donation in 4 days."

No agent is the boss. They propose plans, vote, and give ground until they agree. **Safety rules written in plain code** remove every unsafe option before the debate starts, so the agents can never argue their way into an unsafe delivery. When they truly can't agree, or agreeing would cross a line one of them refuses to cross, they **stop and ask a person** instead of forcing a bad decision.

Every agent runs as **its own service**: shelters, drivers and the three negotiators find each other through an agent directory and talk over the network, like a small marketplace. When the food arrives, Uplink writes the donation record that California's SB 1383 law requires.

> **THE ONE-SENTENCE PITCH**
> Food rescue is full of real tradeoffs. Our agents negotiate them with no boss, safety is never up for debate, and when they truly can't agree, they ask a human.

---

2 The problem and who uses it

California's SB 1383 requires many food businesses (grocery stores, large restaurants, hotels, caterers, schools) to donate edible surplus food and keep records of it. Much of it is still thrown away, because donating is a hassle: someone has to find a shelter that can take *this* food *tonight*, check it has a fridge, find a driver, and do the paperwork.

Every one of those choices is a tradeoff. The fastest driver costs money. The free volunteer may not show up. The nearest shelter may already have been fed today, while another has waited four days. Uplink cuts the business's part down to one photo and lets agents handle the tradeoffs.

WHO	WHAT THEY WANT	WHAT THEY USE IN UPLINK
Business café, bakery, hotel kitchen	Get leftover food picked up now, with proof for compliance	The customer site at `/`: schedule a pickup, track it, download the receipt
Shelter or pantry	Food it can actually use, with no surprises	The shelter phone page at `/shelter`: accept, take part, or decline each request, by tap or by voice
Driver volunteer, paid courier, a nonprofit's own van	Trips that fit their range and schedule	Simulated in this demo; each driver has its own agent that bids on trips
Coordinator the human in the loop	Step in only when the agents shouldn't decide alone	The Decisions inbox on the ops dashboard
Judges, presenters	See how the agents think, and proof it works	The ops dashboard at `/ops`: live negotiation, map, logs, evidence, how it works

WHY IT'S DIFFERENT FROM EXISTING APPS

Services like Copia already match donations to nonprofits, but businesses still have to enter details and coordinate. Uplink cuts it to one photo, and the agents handle matching, failures and paperwork, including the hard tradeoffs a fixed rule gets wrong.

3 A donation's journey, step by step


At 2:00 PM a hotel kitchen has 30 servings of chicken curry left over. Here is everything that happens next, in plain words, with the technical name of each step and the file that does it.

1. **The manager takes a photo** on the customer site. (vision · `vision.py`)
   The photo goes to an AI vision model, which names the food, counts it, and says how sure it is. Uplink's own code, not the AI, turns the count into servings, weight and how long the food stays safe.
2. **The manager checks and confirms.** If the AI got something wrong, they fix it. If they aren't sure about allergens, they tick "Not sure".
3. **The food is announced to the network.** (agent network · `network.py`)
   Every shelter's agent answers from its own point of view: "Yes, we can take all 30", "We can take 12 of the 30", or "Sorry, we're full". Every driver's agent bids on each trip with an arrival time and a price, or says no if it's too far.
4. **Safety rules remove anything unsafe.** (safety rules · `world.py`)
   No fridge for cold food, an allergen the shelter must avoid, closed by arrival time, no room, or arriving too close to when the food spoils. Those options disappear before any agent sees them.

5. **Speed, Cost and Need negotiate.** (negotiation · `agents.py`)
   Each proposes a plan, votes on every plan on the table, and gives ground over up to three rounds. Here they agree: Riverside Family Center, via a paid courier arriving in about 10 minutes.
6. **If they can't or shouldn't agree, a person decides.** (escalation)
   The question lands in the coordinator's Decisions inbox with the reason, the agents' top two options, and a "decide by" time.
7. **The shelter confirms.** (shelter phone)
   If someone is answering the shelter's phone page, they accept, take part, or decline. Otherwise the plan goes ahead.
8. **The driver picks up and delivers.** (simulated world)
   The manager watches on the tracking page: "Driver on the way, arrives 2:19 PM." (times here are an example)
9. **Something may change mid-route.** (adaptation)
   A shelter fills up, or a volunteer cancels. The agents re-plan from wherever the food is now.
10. **Delivered, and the record is written.** (SB 1383 record)
    Donor, recipient, items, weight, pickup and delivery times and transport type are logged automatically, ready to print or download.

4 System architecture

Uplink is a Python web server (Flask) that simulates the city, plus **one separate process per agent**. Each agent is also an **AGNTCY A2A agent over NATS** (Cisco's open agent stack): the agents find each other through an agent directory and exchange A2A messages, one broadcast per step. The agents' decisions are real; the city around them (shelters' locations, drivers moving, the clock) is simulated.



Each agent is a separate process that registers in the directory and answers messages. Dashed boxes are optional; without any keys everything still runs.

IN PLAIN WORDS


Each shelter, driver and negotiator is its own little program, like separate people with their own phones. A directory works like a phone book: agents list themselves there, and anyone can look up who can take food or drive a trip. If one agent goes offline, it drops out of the phone book and the others carry on.

TECHNICAL DETAIL

The **clock thread** advances simulated time (1 simulated minute per real second at 1×). The **planner thread** runs each negotiation outside the shared lock, so a slow agent never freezes the dashboard. Each agent process serves an A2A AgentCard over NATS with the AGNTCY app-sdk (and an HTTP fallback); the launcher starts about 16 of them, plus the NATS server if needed, and they all exit when the app exits.

5 The agentic workflow: negotiation with no boss

Three agents with competing goals decide every plan together. Shared code only counts the votes; no supervisor picks the winner.



One donation's decision. Every step between agents is a real message: offers, bids, and each negotiator's evaluation, proposal and votes. The agents never see an unsafe plan, and a human is asked only when agreeing would be wrong.

IN PLAIN WORDS

Think of three coworkers with different priorities picking a delivery plan. Each suggests their favourite, everyone gives a thumbs up or down with a reason, and if nobody budges, each is willing to accept a slightly worse option for their goal. Each also has one line they will never cross.

TECHNICAL DETAIL

Each agent scores every safe plan from 0 to 1 against its own goal. It accepts a plan scoring at least 90%, 78% then 65% of its best option in rounds 1, 2 and 3. When proposing in later rounds it blends its own score with the least-happy other agent's (weight 0, 0.45, 0.75). Vote weights start at 1.0; a majority needs 2.0. Before round 1, each negotiator sends the others its scores and vetoes for every plan (`plan.evaluate`), so every agent argues from shared evidence.

How each agent scores a plan

AGENT	SCORE (0 TO 1)	RED LINE: ALWAYS VETOES
Speed	Minutes to spare ÷ minutes left, weighted by driver reliability	Under 10 minutes to spare, or a driver under 50% reliable
Cost	Cheaper is better, weighted by reliability (a no-show means paying a courier to rescue the food)	Over $20 for one donation
Need	Days since the shelter's last donation (70%) and room left (30%)	Feeding a shelter that got food today while another has waited 4+ days

RULES OR AI REASONING

By default the agents reason with these scoring rules, which are fast and repeatable for demos and tests. With `LLM_AGENTS=1` and a Claude key, each agent's proposals, votes and reasons come from Claude, told its goal and red line. Red lines are still enforced in code, and any failed AI call falls back to the rules for that agent. In testing, Claude-driven agents agreed more readily, so the rules show disagreement more clearly.

6 Safety rules and red lines

There are two kinds of limits. Safety rules protect people and are never up for debate. Red

lines protect each agent's goal and act as vetoes inside the debate.

Safety rules: plain code, applied before any agent sees a plan

RULE	A PLAN IS REMOVED WHEN…
Food type	The shelter doesn't accept that category (hot prepared, cold prepared, packaged, produce)
Cold chain	The food must stay cold and the shelter has no fridge
Allergens	The food contains an allergen the shelter must avoid, or allergens are unconfirmed and the shelter avoids any (unconfirmed counts as present)
Capacity	The shelter has no room, counting food already on its way
Opening hours	The shelter would be closed when the driver arrives
Safe time	The food would arrive less than 5 minutes before it becomes unsafe
Full	The shelter has said it's full

> **WHY THIS MATTERS**
>
> "Is the AI deciding if food is safe?" No. Safety is fixed rules in code. The agents only choose among options that already passed them, so they can never pick an unsafe one, however persuasive an argument is.

Red lines: each agent's veto

A veto holds in every round, and a majority cannot override it. If the only plan two agents like is vetoed by the third, the agents don't force it through: they hand the choice to a person and explain why. That is how Uplink shows **"consensus is not always the right outcome"**, which the Cisco challenge asks for. The red lines are in the scoring table in section 5.

---

7 When the agents should not agree

A negotiation can end six ways. Three act on a plan, and three stop and ask a person,

because agreeing would be wrong.

OUTCOME	WHEN IT HAPPENS	WHAT HAPPENS NEXT
Consensus	All three agents accept a plan	It goes ahead
Majority with dissent	After 3 rounds, 2 of 3 (by vote weight) accept a plan nobody vetoed	It goes ahead; the losing agent's objection is kept on record
Time is short	Under 30 minutes until the food is unsafe	Stop debating; act on the best-supported plan nobody vetoed
Unacceptable compromise	The majority's plan crosses the third agent's red line	Ask a human, with the reason and the top two options
Irreconcilable goals	After 3 rounds, no plan has majority support	Ask a human
Insufficient evidence	An agent's best plan is blocked only by an unconfirmed fact (allergens), with 45+ minutes left	Ask the business; wait up to 15 minutes, then act on what is known

A plan that costs more than $25 also goes to a human.

Fallback rules (disclosed, not decision-makers)

- **Nobody answers the coordinator.** The agents act at the last moment an option can still arrive safely, using their best-ranked option that still makes it. The Decisions card shows this "decide by" time.
- **Any approval is re-checked.** If time has passed and an option would now arrive too late, it isn't dispatched; the agents find one that still works.
- **Scripted test runs** have no human at the keyboard, so a simulated coordinator picks the agents' top-ranked option. The activity feed labels all of these.

> **WHY THE FALLBACKS WERE REDESIGNED**
>
> The first version waited until 15 minutes before the food spoiled. In testing, every option by then took 25 minutes, so food arrived spoiled. Now the deadline is computed from the options themselves (the latest safe departure, minus 2 minutes), so the fallback always leaves a plan that still works.

8 The wider agent network

Beyond the three negotiators, every shelter and every driver has its own agent. Together

they behave like a small marketplace with no central dispatcher.

Business agent

Announces the surplus to the network: what it is, how much, and how long it's safe.

Shelter agents

Each answers from its own situation: accept all, counter-offer to take only part (for example "12 of 30, we're low on room"), or decline with a reason.

Driver agents

Each bids on each trip with an arrival time, a price and its reliability, or refuses a trip beyond its range (volunteers drive 12 km at most by default).

Speed, Cost, Need

Negotiate over every (shelter offer × driver bid) combination that passed the safety rules.

What makes the network adaptive

BEHAVIOUR	HOW IT WORKS
Discovery	Agents search a directory of shelters by capability (food types, fridge, hours, room). A new pantry can join mid-run, and waiting donations are reconsidered.
Re-planning	A shelter saying "full" or a driver cancelling sends the donation back to the agents. If the driver already has the food, they re-plan from the driver's position.
Learning who was right	A driver who cancels loses 30 points of reliability, and every agent sees it. An agent that warned about that driver gains +0.25 vote weight for the rest of the run.
Split donations	If the winning plan is a counter-offer, the rest of the food is split off and announced again, so nothing is left behind.
Combined trips	Two donations from the same pickup can ride in one vehicle (up to 150 servings), keeping another driver free. Cost values this.
Shelter phones	When a person is answering a shelter's phone page, the agents ask first and hold the driver for up to 8 simulated minutes, then try elsewhere.

Every agent is its own service

PIECE	HOW IT WORKS
Agent directory	Each agent publishes a record: its id, name, skills (for example `food.receive`, `trip.bid`, `plan.vote`), what it can do (food types, fridge, range) and its address. Modeled on AGNTCY's Agent Directory and OASF agent records.
Heartbeats	Every agent checks in every 2 seconds. One that goes silent for 6 seconds, or shuts down, drops out and is no longer discovered.
Messages	**AGNTCY A2A over NATS**, one broadcast per step: `offer.request` to every shelter, `bid.batch` to every driver, `plan.evaluate`, `plan.propose` and `plan.vote` to the three negotiators. HTTP is the automatic fallback. Every message is traced with sender, receiver, type and reply time (a few ms locally).
Resilience	Stop a shelter's agent and it isn't consulted; the food goes elsewhere. A pantry or driver that joins mid-run gets its own agent, which registers itself. If a negotiator is down, the same logic stands in for it and that is logged.
Proof it's the same	`tests/test_mesh.py` replays all 9 scenarios through the real processes twice, over AGNTCY A2A/NATS (about 1,100 messages, all over A2A) and over HTTP (about 1,700), with 0 failures, and checks every number and every negotiation matches the in-process version exactly.

> **WHAT'S AGNTCY AND WHAT'S OURS**
>
> From AGNTCY: the A2A protocol, the AgentCards, the NATS transport and the broadcast pattern (via the AGNTCY app-sdk, as in Cisco's coffeeAGNTCY demo), and OASF records. Ours: the agents and their decisions, the safety rules, the negotiation, and the agent directory with heartbeats (modeled on AGNTCY's Agent Directory).

---

9 Reading the photo

The AI model only does what it's good at: naming the food and counting what it can see. Uplink's code does the math, so the same count always gives the same numbers.

1. **Prepare the photo.** Fix its rotation, shrink it to 1568 pixels on the long side, and convert iPhone HEIC photos to JPEG. This happens in the browser and again on the server.
2. **The model identifies and counts.** For each kind of food it gives a count range (a range when some is hidden), says how it counted ("3 rows of 4"), lists likely allergens, and states its confidence: high, medium or low.
3. **Code computes the rest** from a unit table: 1 bagel ≈ 1 serving and 0.25 lb, 1 pizza slice ≈ 1 serving, 1 catering tray ≈ 10 servings. Safe time comes from the category (hot prepared about 2 hours, cold about

90 minutes, packaged 24 hours).

4. **The business checks.** Low-confidence counts are highlighted, and every field can be edited before confirming.
5. **Never a fake answer.** If the call fails or the photo isn't food, the form comes back empty with the reason. With no model connected, a clearly labeled demo result appears instead.

Or pick from your menu. Each business has its own menu. Instead of a photo or typing, staff can pick leftovers straight from it, and after a photo the items are matched to the menu so allergens and category come from the business's own data.

Two ways to run the model

OPTION	HOW	TRADEOFFS
Claude (current)	Anthropic's API, through the official Python SDK. Key in `.env`.	Most accurate; about 2 to 4 cents per photo; needs internet
Qwen2.5-VL on an NVIDIA Brev GPU (backup)	An open model served by vLLM on a rented L4 GPU, reached through a private tunnel. `scripts/start_vision.sh`	No API key needed; less accurate; about $0.90 per hour while running

> TESTED RESULT
> A photo of a cut vegetable pizza came back as "vegetable pizza, 8 slices, high confidence", noting one slice had a bite taken out. A busy bagel display came back as 23 labelled kinds, 240 to 367 bagels, low confidence, which is honest because many were stacked out of sight.

The camera at the business

`camera.py` watches the counter with a fast on-device detector (YOLO-World) that counts food live. At closing time it sends one snapshot to the vision model, which splits the leftovers into one donation per food category, since safety rules differ by category. Video never leaves the laptop.

---

10 Voices

With an ElevenLabs key, the debate can be heard, and shelters can answer by speaking.

- **The agents speak.** Turn on Demo controls → Sound and look → Voices on the ops dashboard. Speed, Cost and Need each read their lines in a different voice, and a dispatcher voice announces the outcome. Each line waits for the previous one to finish.
- **The shelter hears requests.** On the shelter phone page, turn Voice on, and each new request is read aloud.

- **The shelter answers out loud.** Tap "Answer by voice" and say "yes", "no", or a number like "just 20". ElevenLabs turns speech into text, and Uplink's code turns that into accept, decline or take part.
- **The Phone line.** On the ops dashboard, after the agents choose a shelter, a dispatcher voice "calls" it: it reads out the food, driver and arrival time, and the shelter answers with its agent's actual reply ("We'll take 20 of the 30"). Voices use ElevenLabs Flash; spoken answers are transcribed with ElevenLabs Scribe. It's a voiced replay in the browser, not a call over the phone network; a staff member's real spoken answer from the shelter phone page appears in it too.
- **No key?** It falls back to the browser's built-in voice and speech recognition.

---

11 The two websites

Two audiences, two sites. The customer site shows what a real business would use. The ops dashboard shows judges what happens behind the scenes.

Customer site · `/`

Built for a busy café manager who isn't technical. No agent jargon anywhere, only outcomes.

PAGE	WHAT IT SHOWS
Home	"Leftover food? We'll get it picked up." One button: Schedule a pickup.
Schedule	3 steps: photo, pick from your menu, or type it in → "Does this look right?" summary → scheduled
Track	A status timeline (Received → Finding a place → Driver assigned → Picked up → Delivered), the shelter and arrival time in big text, and a map of only this pickup. If Uplink needs an answer, a simple yes/no question appears here.
My donations	Past donations and printable SB 1383 receipts, with CSV download
Help	Short answers: what food is accepted, is it safe, what it costs (free), what record you get

Ops dashboard · `/ops`

PAGE	WHAT IT SHOWS
Live	A dark judges' view: headline numbers; a live **agent network diagram** (business → shelter agents → driver agents → the three negotiators, with every message in a log beside it); the **Phone line**; the current donation; the three agents' positions and the outcome; and the city map. "See the debate" opens the full transcript and vote matrix.
Decisions	The coordinator's inbox: escalations with options and a "decide by" time. A red badge in the nav shows the count.
Activity	Agent network messages, agent feed, safety decision log, donations list, and **Agent services**: every agent's process, port, skills, message count and reply time, with Stop and Restart buttons and a live message trace
Evidence	Team versus baselines across scripted and randomized scenarios
Records · How it works	Printable SB 1383 records; a short visual explanation for judges
Demo controls	Scenario picker, speed, pause, voices, and "inject a problem" buttons: shelter full, driver cancels, new pantry joins, camera closing time


The shelter phone page (`/shelter`) is a third, phone-sized page a teammate can hold on stage to play a shelter.

12 Evidence: does the team do better?

The Cisco challenge asks: "Can independent AI agents make better decisions together than they can individually?" Uplink answers with numbers from repeatable scenarios.

The same 9 scripted scenarios run under five decision policies. **Nearest shelter** uses no agents and no safety checks. **Speed, Cost or Need alone** use the same safety rules as the team, but one agent decides by itself.

Servings lost (lower is better)




Shelters fed (higher is better)



Money spent on drivers (lower is better)



Times a human was asked



All 9 scripted scenarios combined, rules mode, from `python scenarios.py` on October 10, 2026. Meals delivered safely: 763 for nearest shelter, 934 for every other policy.

What the numbers say (honestly)

1. **The safety rules matter most.** Nearest shelter lost 171 servings; every policy with the safety rules lost none, including one agent deciding alone.
2. **The team spreads food most fairly.** It fed 23 shelters, more than any single agent.
3. **The team is not the cheapest.** It spent $229, more than Cost alone ($84), because it pays for reliable couriers and fairness. That is the tradeoff, and we say so.
4. **Refusing bad compromises involves people.** The team asked a human 6 times, where single agents just acted. That is by design: those are the cases where agreeing would have been wrong.
5. **Real disagreement needs red lines.** Before red lines were added, every negotiation in the original scenarios ended in full agreement. Now the team's 48 decisions ended: consensus 39, unacceptable compromise 4, majority 2, insufficient evidence 2, irreconcilable 1.

The strongest evidence: random scenarios the system had never seen

100 random scenarios (3 to 6 donations each, driver no-shows, full shelters, new pantries), not used while building:

POLICY	SERVINGS LOST	MEALS DELIVERED	SHELTERS FED	DRIVER COST
Nearest shelter	3,834	13,620	254	$2,927
Speed alone	1,336	16,118	309	$3,228
Cost alone	1,726	15,728	292	**$1,305**
Need alone	1,459	15,995	386	$2,581
Team	**676**	**16,778**	**440**	$2,115

IN PLAIN WORDS

Working together, the agents lost **half as much food as the best agent working alone** (49% less) and 82% less than the simple approach, delivered the most meals and reached the most shelters. They were never worse than the simple approach in any run. The trade-off: the cost-minimizing agent alone is cheaper.

---

13 What's real and what's simulated

The agents and their decisions are real. The world around them is simulated, which judges expect at a hackathon.

Real

- Photo reading by a vision model (Claude, or Qwen on a GPU)
- The agent loop: offers, bids, proposals, votes, red lines, outcomes
- Re-planning when a shelter declines or a driver cancels
- Safety rules and fallback rules
- Human approvals, business answers, shelter replies (tap or voice)
- Generated donation records
- Voices and speech recognition (with keys)
- Each agent as its own process, the agent directory, and the messages between them

Simulated

- Shelters, drivers and businesses: fictional, placed near Santa Clara
- The clock: 1 simulated minute = 1 real second at 1× speed
- Driver movement along straight lines
- Events like a full shelter, a no-show or a new pantry, triggered from Demo controls or scripted scenarios
- The Phone line is voiced in the browser, not a real phone call (the shelter's words are its agent's real reply)

Skipped on purpose: logins and accounts, payments, real traffic routing, and training our own model.

---

14 Code map

FILE	WHAT IT DOES
`app.py`	Flask server: page routes, the JSON API, the clock thread and the planner thread
`world.py`	The simulated city: directory, safety rules, drivers, clock, events, routes, records, fallback rules, the baseline and single-agent policies
`network.py`	Shelter agents (accept, counter, decline) and driver agents (bid or refuse)
`agents.py`	Speed, Cost and Need: scoring, red lines, the negotiation protocol, the evidence check, optional Claude reasoning
`mesh/`	The agent mesh: directory, one service per agent, the client that discovers and messages them (with a trace), and the launcher
`config.py`	Every tuning knob in one place: thresholds, timeouts, limits, speeds
`vision.py`	Photo → food details: preparation, the counting prompt, the unit table, failure handling
`llm.py`, `env.py`	Model wrapper (Claude SDK or an OpenAI-style server) and loading keys from `.env`
`menu.py`	Each business's menu: pick leftovers from it, and match photo results to it
`voice.py`	ElevenLabs text-to-speech and speech-to-text; understanding "yes", "no" and numbers
`camera.py`	The business camera: live food counting, closing-time snapshot
`scenarios.py`	9 scripted scenarios and the five-policy comparison
`static/`	Web pages: customer site (`app.*`), ops dashboard (`dashboard.*`), shelter phone, records, shared styles
`data/`	Fictional shelters, drivers and businesses
`tests/`	`test_core.py`: 34 automated checks, such as cold food never going without a fridge. `test_mesh.py`: the agent processes decide identically and survive a stopped agent
`scripts/`	Brev GPU setup, start and stop scripts; the photo accuracy test
`docs/`	Architecture, results, Brev setup guide, and this document

15 How to run it

> START THE APP
>
> `cd ~/uplink`
> `source .venv/bin/activate`
> `pip install -r requirements.txt` (first time only)
> `python app.py` (port 5050 by default; it also starts the agent processes)

PAGE	ADDRESS
Customer site	`http://localhost:5050`
Ops dashboard	`http://localhost:5050/ops`
Shelter phone	`http://localhost:5050/shelter?id=northside-youth`
Records	`http://localhost:5050/records`

On a phone on the same Wi-Fi, replace `localhost` with the laptop's IP address. Campus Wi-Fi sometimes blocks this; a phone hotspot works.

Keys and settings (in `.env`, never committed)

SETTING	EFFECT
`ANTHROPIC_API_KEY`	Claude reads photos (and, with `LLM_AGENTS=1`, writes the agents' arguments)
`ELEVENLABS_API_KEY`	Real voices for the debate and shelter phone
`LLM_AGENTS=1`	Agents reason with Claude instead of rules
`MESH=0`	Run every agent in-process instead of as separate services
none	Everything runs: a labeled demo photo result, rules-based agents, the browser's voice

Run the checks with `python tests/test_core.py` and `python tests/test_mesh.py`, and the evidence with `python scenarios.py`.

16 Explaining Uplink to others

The 3-minute demo

1. **Problem (30 s).** Businesses throw away edible food, and California now requires many to donate it. But donating is a hassle full of tradeoffs.
2. **Photo (20 s).** Photograph real leftover food on the customer site. The details fill in.
3. **Agents negotiate (40 s).** On `/ops`, Speed, Cost and Need argue, the safety rules remove an unsafe shelter, and a truck starts moving.
4. **Things change (45 s).** Click "Shelter says full": they reroute. Click "Driver cancels": reliability drops and the agent that warned gains weight. Run a deadlock scenario: they ask a human. Then open Activity → Agent services and stop a shelter's agent: it drops out of the directory and the next donation goes elsewhere.
5. **Evidence (25 s).** The Evidence page: team versus single agents and the simple baseline.
6. **Close (20 s).** "Our agents negotiate real tradeoffs with no boss, safety is never up for debate, and they ask a human when they truly can't agree."

Answers to likely questions

Who makes the final decision?
No single agent. A plan wins by agreement, or by majority after up to 3 rounds without a veto; otherwise a person decides.

What if the agents never agree?
After 3 rounds, or if the best plan crosses a red line or costs over $25, a coordinator gets the question with both sides' reasons and a deadline.

Is the AI deciding whether food is safe?
No. Safety is fixed rules in code (time, refrigeration, allergens, capacity, hours) that remove unsafe plans before any agent sees them.

How do you know this beats a simple approach?
We ran the same scenarios against a nearest-shelter baseline and against each agent alone. See section 12, including where the team costs more.

How do you know the amount from a photo?
The model counts what it can see and gives a range and a confidence level. Code computes servings and weight, and the business confirms or corrects every number.

Are these really separate agents?
Yes. Each shelter, driver and negotiator runs as its own process and is an AGNTCY A2A agent over NATS, registered in an agent directory. You can stop one live and watch the others carry on. A test proves the distributed agents decide exactly as the in-process ones.

Is this real?
The agents, photo reading, safety rules and records are real. The city, drivers and clock are simulated for the demo.

How is this different from Copia?
Copia makes businesses enter details and coordinate. Uplink cuts it to one photo, and the agents handle matching, failures, tradeoffs and paperwork.

17 Glossary

TERM	MEANING
Agent	A piece of software with its own goal that makes decisions on its own
Agentic workflow	A process where agents act, react to events and re-plan, instead of following fixed steps once
Consensus	All three agents accept the same plan
Majority with dissent	Two of three accept; the third's objection is kept on record
Red line / veto	A limit one agent never accepts crossing; a majority can't override it
Unacceptable compromise	The majority's plan crosses the third agent's red line, so a person decides
Irreconcilable	After 3 rounds no plan has majority support, so a person decides
Insufficient evidence	The decision depends on a fact nobody has confirmed, so the agents ask before guessing
Safety rules	Fixed code that removes unsafe plans before negotiation
Fallback rule	A disclosed automatic action when nobody answers in time, so food doesn't spoil
Baseline	A simple comparison policy (nearest shelter, or one agent alone) used to measure the team
Counter-offer	A shelter offering to take only part of a donation; the rest is re-announced
Agent directory	A registry where agents list who they are, what they can do and where to reach them, so others can find them
Heartbeat	A regular "still here" signal; an agent that stops sending it drops out of the directory
A2A message	Agent-to-agent protocol message (used by AGNTCY); here sent over NATS, a fast message server
NATS	A lightweight message server; the agents' A2A messages travel through it
OASF record	AGNTCY's standard format for describing an agent; our directory records are modeled on it
Vision model	AI that understands images; here, it identifies and counts food
vLLM / Brev	Software that serves an open AI model; Brev rents the NVIDIA GPU it runs on

SB 1383	California law requiring many food businesses to donate edible surplus food and keep records
AGNTCY	Cisco's open-source infrastructure for agent discovery and messaging (optional for this track)