

Programming Challenge: M&C Interactive Problem Solver

Abstract:

This program emulates the classic Missionaries and Cannibals logic puzzle. It is a nice way to work through possible solutions and will reveal an inapplicable or fatal move. It even has an option to reveal the move list used to achieve a viable solution (or not viable if you want to review where a mistake was made).

MC Code

```
( defun establish-world ()
  ( setf *left-bank* '(M M M C C C B) )
  ( setf *right-bank* '() )
)

( defun init-move-list ()
  ( setf *move-list* '() )
)

( defun mc ()
  ( establish-world )
  ( init-move-list )
  ( make-moves )
)

( defun display-world ()
  ( format t "~a~%" *left-bank* )
  ( format t "~a~%" *right-bank* )
)

( defun display-solution ()
  *move-list*
)
```

```

( defun goalp ()
  ( cond
    ( ( and
      ( = ( count 'M *right-bank* ) 3)
      ( = ( count 'C *right-bank* ) 3)
    ) t
    )
    (t
      nil
    )
  )
)

( defun feast-state-p ()
  (cond
    ( ( and ( > ( count 'C *left-bank* ) ( count 'M *left-bank* ) )
      ( > ( count 'M *left-bank* ) 0 ) )
      t
    )
    ( ( and ( > ( count 'C *right-bank* ) ( count 'M *right-bank* ) )
      ( > ( count 'M *right-bank* ) 0 ) )
      t
    )
    (t
      nil
    )
  )
)

```

```

( defun current-bank ()
  ( cond
    ( ( = ( count 'B *left-bank* ) 1 )
      *left-bank* )
    ( t
      *right-bank* )
  )
)

( defun applicable-p ( move )
  ( cond
    ( ( and ( <= ( count 'M move ) ( count 'M ( current-bank ) ) )
              ( <= ( count 'C move ) ( count 'C ( current-bank ) ) )
              ( <= ( count 'B move ) ( count 'B ( current-bank ) ) )
              ( = ( count 'B move ) 1 )
              ( < ( length move ) 4 )
              ( or ( > ( count 'M move ) 0 ) ( > ( count 'C move ) 0 ) ) )
      T
    )
    ( t
      nil
    )
  )
)

```

```

( defun make-moves ()
  ( display-world )
  ( cond
    ( ( goalp )
      ( write-line "Good work!" )
      nil
    )
    ( ( feast-state-p )
      ( write-line "Yummy yummy yummy, I got Good in my tummy!!" )
      nil
    )
    ( t
      ( let ( m )
        ( format t ">>> " ) ( setf m ( read ) )
        ( if ( applicable-p m )
          ( let () ( perform-move m ) ( make-moves ) )
          ( let () ( write-line "Move inapplicable" ) nil )
        )
      )
    )
  )
)

( defun snoc ( o l )
  ( append l ( list o ) )
)

```

```

( defun perform-move ( move )
  ( setf *move-list* ( snoc move *move-list* ) )
  ( if ( equal ( current-bank ) *left-bank* )
    ( move-lr move )
    ( move-rl move )
  )
)

( defun move-lr-1 (ml)
  ( setf *left-bank* ( remove ml *left-bank* :count 1 ) )
  ( setf *right-bank* ( append ( list ml ) *right-bank* ) )
)

( defun move-lr ( ml )
  ( if ( null ml ) ( return-from move-lr ) )
  ( move-lr-1 ( first ml ) )
  ( move-lr ( rest ml ) )
)

( defun move-rl-1 (ml)
  ( setf *right-bank* ( remove ml *right-bank* :count 1 ) )
  ( setf *left-bank* ( append ( list ml ) *left-bank* ) )
)

```

```

( defun move-rl ( ml )
  ( if ( null ml ) ( return-from move-rl ) )
  ( move-rl-1 ( first ml ) )
  ( move-rl ( rest ml ) )
)

```

MC Demo

```
[2]> ( mc )
*left-bank* (M M M C C C B)
*right-bank* NIL
>>> ( m b )
*left-bank* (M M C C C)
*right-bank* (B M)
Yummy yummy yummy, I got Good in my tummy!!
NIL
[3]> ( mc )
*left-bank* (M M M C C C B)
*right-bank* NIL
>>> ( m c b )
*left-bank* (M M C C)
*right-bank* (B C M)
>>> ( c c b )
Move inapplicable
NIL
[4]> ( mc )
*left-bank* (M M M C C C B)
*right-bank* NIL
>>> ( b m c )
*left-bank* (M M C C)
*right-bank* (C M B)
>>> ( b m )
*left-bank* (M B M M C C)
*right-bank* (C)
>>> ( b c c )
*left-bank* (M M M)
*right-bank* (C C B C)
>>> ( b c )
*left-bank* (C B M M M)
*right-bank* (C C)
```

```
>>> ( b m m )
*left-bank* (C M)
*right-bank* (M M B C C)
>>> ( b m c )
*left-bank* (C M B C M)
*right-bank* (M C)
>>> ( b m m )
*left-bank* (C C)
*right-bank* (M M B M C)
>>> ( b c )
*left-bank* (C B C C)
*right-bank* (M M M)
>>> ( b c c )
*left-bank* (C)
*right-bank* (C C B M M M)
>>> ( b c )
*left-bank* (C B C)
*right-bank* (C M M M)
>>> ( b c c )
*left-bank* NIL
*right-bank* (C C B C M M M)
Good work!
NIL
[5]> ( display-solution )
((B M C) (B M) (B C C) (B C) (B M M) (B M C) (B M M) (B C) (B C C) (B C)
 (B C C))
```