

CHECKSUM

Checksum = check + sum

sender side \Rightarrow checksum creation.

Receiver side \Rightarrow checksum validation.

Sender side

- ① Break the original message into k (~~4, 8, 16, 32, ...~~) number of blocks ^{sections} with n bits in each block.
[i.e. \rightarrow 20 bits in 4 blocks = 5 bit each blocks] \rightarrow 4, 8, 16, 32, ...
- ② sum all the 'k' data blocks.
- ③ Add the carry to the sum, if any. (one's complement arithmetic)
- ④ Do 1's complement to the sum = checksum
(checksum also be n bits).

Example: 10011001.11100010.00100100.10000100 (data word)

1	0	0	1	1	0	0	1
1	1	1	0	0	0	1	0
0	0	1	0	0	1	0	0
1	0	0	0	0	0	0	0
<hr/>							
10	0	0	1	0	0	0	1
<hr/>							
0	0	1	0	0	1	0	1

1's complement : 1 1 0 1 1 0 1 0

∴ checksum : 1 1 0 1 1 0 1 0

Codeword : 10011001.11100010.00100100.10000100.11011010

Receiver side :

- ① collect all the data blocks including the checksum
- ② Sum all the data blocks and checksum
- ③ Add the carry to the sum, if any. (one's complement addition)
- ④ Do ~~1st~~ complement to the sum = checksum

If the checksum is 0, this means that the data is not corrupted. (Accepted)

$$\begin{array}{r} \cancel{10011001.11100010.00100100.10000100.11011010} \\ 10011001 \\ 11100010 \\ 00100100 \\ 10000100 \\ 11011010 \\ \hline 10 \quad 111111001 \\ \hline \quad \quad \quad 100 \\ \hline 11111111 \end{array}$$

∴ 1's complement \Rightarrow 00000000 (checksum)

(Accepted)

(sending 16 bit Use MD5) Intersect checksum + Book-300 page (3)

* A sender needs to send the four data items 3456, ABCE, 02BC, and EEEE

Sender site

1	2	2	2
3	4	5	6

A B C E

0 2 B C

E E E E

D 1 C C

1

D 1 C D \Rightarrow sum

1101

0001

1100

1101

1st complement \Rightarrow 0010 1110 0011 0010

\downarrow

\downarrow

\downarrow

\downarrow

2

E

3

2

checksum \Rightarrow 2E32 (subtracting Each Value by 15)

Data word: 3456, ABCE, 02BC, EEEE, 2E32

Hexadecimal:

0-9, A, B, C, D, E, F

0-9, 10, 11, 12, 13, 14, 15

6

12

12

14

16) 44 (2 \Rightarrow carry)

32

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

At the Receiver site

~~D1CD~~
~~2E32~~

3456

ABCC

02BC

EEEE

2E32

D1CD

2E32

FFFF

FFFF

1st complement: $\begin{matrix} \text{||||} \\ 0000 \end{matrix}$ $\begin{matrix} \text{||||} \\ 0000 \end{matrix}$ $\begin{matrix} \text{||||} \\ 0000 \end{matrix}$ $\begin{matrix} \text{||||} \\ 0000 \end{matrix}$
[Subtracting Each value by 15]
Receiver checksum: 0000

Q-1: Find the checksum at the sender site.

Q-2: Find the checksum at the receiver site.

Q-3: send Mr. X send Message - - - - .
In the receiver site ^{Message is} ~~rejected~~ Accepted/
Rejected.