

Industrial Steam Cooker

Specification

- Source: Steam Operated
- Automation Grade: Automatic
- Voltage Supply: 440v
- Capacity: 250kg to 2000kg/hr
- Material: Stainless Steel
- Frequency: 50-60Hz

Key Features

- Excellent product texture and appearance
- Up to 8% higher yield
- Decrease energy costs by 25% to 85%
- Automatic hood lifting mechanism for easy clean
- Meets rigorous food safety and sanitary design standards
- Uniform, Consistent and predictable product temperature
- Cookers are easily configurable to meet specific customer needs

The cooker uses a forced convection method and the process consist of a low temperature mixture of air steam and condensate water which is constantly circulated inside the chamber and distributes heat uniformly and efficiently. The products are cooked, blanched or pasteurized consistently using less steam than traditional methods, and helps in maintaining the high quality of the products.

The unique design as well as the PID controlled motorized steam valves and VFD controlled blowers ensures that the cooking yield is always kept at a maximum and gives an energy savings better than any other cooking method in the market. The Steam Cooker is manufactured entirely in stainless steel and non- corrosive materials for providing the best possible conditions for quality processing. The twin layer insulated outer body gives very little heat loss to the surroundings.

Counter Flow Cooler

Specification

- Type: Vertical
- Frequency: 50-60Hz
- Warranty: 1 Year
- Automation Grade: Automatic
- Voltage: 440V
- Body Material: Stainless Steel
- Capacity: Upto 500kg/hour
- Motor Power: 5 HP

Key Features

- Improves yield.
- Energy savings of 25% to 75%.
- Compared to ice methods or traditional water chilling.
- Improves product quality and consistency.
- Integrated controls.

The counter flow cooler and the conveyor are manufactured entirely in stainless steel and non-corrosive material. The unit comes with easy clean features making it possible to meet even the strictest cleaning demand. It is equipped with a centrifugal pump to ensure rapid chilling of the cooked products by maintaining the water flow in the tank.

The belt speed and flow rate are easily adjustable. The product is exposed to a final spray wash at the outlet of the tank.

Rain Water Shower Cooler

Specification

- Body Material: Stainless Steel
- Capacity: Upto 2000kg/hour
- Usage/Application: Food Industry (For Fish)
- Voltage: 440V
- Features: Improves Yield, Energy savings of 25% to 75%, Compared to ice methods or traditional water chilling
- Frequency: 50-60Hz

Key Features

- Improves yield.
- Energy savings of 25% to 75%. Compared to ice methods or traditional water chilling.
- Improves product quality and consistency.
- Integrated controls.

Designed for use with the KILIYARA INDUSTRIAL SYSTEMS series of Cookers and Blanchers. After cooking or steaming, the product is immediately fed into the KILIYARA INDUSTRIAL SYSTEMS's Rain shower cooler where chilled-water gently falls evenly over the product through the rain shower system. The system is designed for the product to achieve core temperature of 5°C or less.

The modular design of KILIYARA INDUSTRIAL SYSTEMS Rain water shower makes it customizable to customers specific needs. Machine operation is based on thermodynamic principles. The upper-level sensor is placed to control the solenoid valve which provides the water into the tanks thus avoiding overflow and the lower-level sensor provided for the safety of the pumps placed to avoid dry run if water inside is insufficient.

Iqf Freezer

Specification

- Brand Name: MULTIJET NXT
- Driven Type: Mechanical, Electric
- Automatic Grade: Fully Automatic
- Power: 35kW
- Door Type: Folding Door
- Style: Air Cooled
- Certification: ISO 9001:2008 Certified
- Capacity: As Per Requirement
- Weight: 2000-3000kg
- Warranty: 2years
- Castors: Yes
- Body Material: Stainless Steel 304
- Usage/Application: Food Industry Fish, Shrimps, Cuttle Fish, Squid, Octopus, Vegetables, Meat poultry, Ready To eat
- Delivery Time: 16 weeks

Key Features

- Energy-efficient blower modules and Effective Air flow management can give you upto 40% energy saving.
- Long running hours without stopping for defrosting (continuous running for 36+ hrs depending on the product moisture content)
- Flexibility to process different products in the same line. you can automatically adjust the air duct height based on the product selected
- (2Kg Trays / different shrimp grades/fish/ Cuttle fish /Squid etc. all in the same line without stopping or making any manual adjustments)
- Long infeed section for product setting and placement
- Flexible layout configuration based on customer plant layout
- Online belt cleaning system

IQF Freezer HARDENER

Specification

- Automatic Grade: Fully Automatic, Automatic
- Door Type: Folding Door
- Certification: ISO 9001:2008 Certified
- Capacity: 500Litre
- Weight: 1000-2000kg
- Warranty: 2years
- Castors: No
- Usage/application: Food Industries to Freeze the Ready to Eat Products Cooled Better Storage
- Payment Terms: L/C, D/A, D/P, T/T
- Power: 9-12kw
- Style: Air Cooled
- Voltage: 440V, 380V
- Type: Iqf Freezer
- Defrost Type: Auto-Defrost
- Temperature Range: -40 Degree Celsius
- Frequency: 50-60Hz

Key Features

- Worlds only machine with a fully automated lifting mechanism.
- Best product appearance.
- Live conveyor washing system.
- Less freezing time.
- Improve yield.
- Eliminate downtime.
- Less power consumption.
- Suitable for all types of products.

Spiral IQF Freezer

Specification

- Automatic Grade: Fully Automatic, PLC Controlled, Automatic
- Style: Air Cooled
- Voltage: 440V, 380V
- Type: Iqf Freezer
- Warranty: 5years
- Temperature Range: -40 Degree Celsius
- Refrigerant: Ammonia
- Payment Terms: L/C
- Power: 9-12kw
- Certification: ISO 9001:2008 Certified
- Capacity: as per requirement
- Defrost Type: Auto-Defrost
- Power Source: Electric
- Storage Capacity: Upto 2000 Kg/Hour

Key Features

- Compact size.
- Less Space is required for installation.
- Uses double impingement technology.
- Fast freezing in minimal time.
- Less power consumption.

Edge Drive Spiral Conveyor

Specification

- Usage/application: Food Industries to Process Vegetables, Shrimps, Seafoods, Fish
- Material: Stainless Steel
- Capacity: 100kg to 2000kg/hr and Above
- Material Grade: SS304
- Voltage: 440V
- Frequency: 50-60Hz

Key Features

- Low power consumption.
- Economical.
- Highly efficient.
- Less Space.

The spiral conveyor transports the products vertically to bridge a difference of height or to function as a buffer zone. The key to its unique compact construction which saves valuable floor space is the spiral shaped conveyor track.

Dip Glazer

Specification

- Usage/Application: Food Industry
- Voltage: 440V
- Dimensions: 3400x1250x1500mm
- Type: Dip Glazer for Seafoods
- Power: 2.49kW

Key Features

- New design allows glazing on both sides of the products.
- Controllable speed depending on the product and glazing proportion.
- High glazing proportion meeting the customers requirement.
- New belt design ensures smooth product transfer.

The unit is designed to form part of an automated processing line, where a precise, high capacity and quality glaze is paramount. The frozen products via the in-feed chute distributed onto the conveyor belt and led straight into the dip section of the belt. The products being fully submerged and surrounded by water, an even and very uniform glaze is then formed on the products.

