

# C | SecureAES

## - High-Performance AES Encryption in C -

Ji Yong-Hyeon



**Department of Information Security, Cryptology, and Mathematics**  
College of Science and Technology  
Kookmin University

December 19, 2023



## Acknowledgements

**Note (XOR Operation and Modular Reduction in  $GF(2^n)$ ).** In the context of Galois Field  $GF(2^n)$ , particularly in binary polynomial arithmetic, the XOR operation is equivalent to addition and also plays a crucial role in modular reduction. We explore this equivalence through the principles of field theory and polynomial arithmetic.

- **Field Properties:**

A Galois Field,  $GF(p^n)$ , is a finite field that contains a finite number of elements, where

- $p$  is a prime number (base of the field) and
- $n$  is a positive integer (degree of the field).

For the binary field  $GF(2^n)$ ,  $p = 2$ , which implies that every element in this field is either 0 or 1.

- **Addition in  $GF(2^n)$ :**

In  $GF(2^n)$ , the addition of two elements is performed modulo 2. For any two elements  $a, b \in GF(2^n)$ , the addition is defined as:

$$a + b = a \oplus b$$

Since 2 is the base of the field, the addition wraps around upon reaching 2, which is effectively what the XOR operation does.

- **Polynomial Representation:**

Elements in  $GF(2^n)$  can be represented as polynomials where each coefficient is in  $GF(2) = \{0, 1\}$ . A general element can be written as:

$$a(x) = a_{n-1}x^{n-1} + a_{n-2}x^{n-2} + \cdots + a_1x + a_0$$

where  $a_i \in \{0, 1\}$  for all  $i$ .

- **Modular Reduction:**

Modular reduction in  $GF(2^n)$  involves reducing a polynomial by a fixed irreducible polynomial of degree  $n$ , ensuring that the result remains within the field. Let  $m(x)$  be the irreducible polynomial. The reduction of a polynomial  $f(x)$  is given by:  $f(x) \bmod m(x)$

- **XOR as Modular Reduction:**

During modular reduction, the subtraction used in polynomial division becomes XOR, because subtraction and addition are the same in  $GF(2)$ . Therefore, reducing a polynomial  $f(x)$  by  $m(x)$  is effectively performed using XOR on the coefficients of corresponding terms.

For example, if  $f(x)$  has a term  $x^k$  where  $k \geq n$ , and  $m(x)$  has a term  $x^k$ , then reducing  $f(x)$  by  $m(x)$  involves XORing the coefficients of  $x^k$  in  $f(x)$  and  $m(x)$ , effectively eliminating the  $x^k$  term in  $f(x)$ .

In summary, the XOR operation becomes equivalent to both addition and modular reduction in  $GF(2^n)$  due to the binary nature of the field. This equivalence simplifies polynomial arithmetic in binary fields, making it a cornerstone of operations in cryptographic algorithms.

# Contents

- 1 Block Cipher AES-128 . . . . . 1**
  - 1.1 Overview of AES-128 . . . . . 1
  - 1.2 Functions and Constants used in AES . . . . . 2
    - 1.2.1 Key Expansion . . . . . 2
    - 1.2.2 AddRoundKey . . . . . 4
    - 1.2.3 SubBytes / InvSubBytes . . . . . 5
    - 1.2.4 ShiftRows / InvShiftRows . . . . . 6
    - 1.2.5 MixColumns / InvMixColumns . . . . . 8
- 2 AES - 128 / 192 / 256 (Byte Version) . . . . . 13**
  - 2.1 Specification . . . . . 13
  - 2.2 Key Expansion (General Version) . . . . . 14
  - 2.3 Advanced Encryption Standard - 128 / 192 / 256 . . . . . 15
- 3 AES - 128 / 192 / 256 (32-bit Version) . . . . . 16**
  - 3.1  $8 \times 32$  Table Look Up . . . . . 16
  - 3.2 SubMix and InvSubInvMix . . . . . 16
  - 3.3 Generation of  $8 \times 32$  Tables . . . . . 18
- A Additional Data A . . . . . 20**
  - A.1 Substitution-BOX . . . . . 20

# Chapter 1

## Block Cipher AES-128

### 1.1 Overview of AES-128

- KeyExpansion :  $\{0, 1\}^{128} \rightarrow \{0, 1\}^{1408=4 \cdot (10+1) \cdot 32}$ .
- AddRoundKey :  $\{0, 1\}^{128} \times \{0, 1\}^{128} \rightarrow \{0, 1\}^{128}$ .
- SubBytes/ShiftRows/MixColumns :  $\{0, 1\}^{128} \rightarrow \{0, 1\}^{128}$ .

---

**Algorithm 1:** Encryption of AES-128

---

**Input:** block  $\text{src} \in \{0, 1\}^{128}$ , round-keys  $\{rk_i\}_{i=0}^{11}$  ( $rk_i \in \{0, 1\}^{128}$ )

**Output:** block  $\text{dst} \in \{0, 1\}^{128}$

```
1  $t \leftarrow \text{AddRoundKey}(\text{src}, rk_0);$ 
2 for  $i \leftarrow 1$  to 9 do
3    $t \leftarrow (\text{MixColumns} \circ \text{ShiftRows} \circ \text{SubBytes})(t);$ 
4    $t \leftarrow \text{AddRoundKey}(t, rk_i);$ 
5 end
6  $t \leftarrow (\text{ShiftRows} \circ \text{SubBytes})(t);$ 
7  $t \leftarrow \text{AddRoundKey}(t, rk_{10});$ 
8  $\text{dst} \leftarrow t;$ 
9 return  $\text{dst};$ 
```

---

---

**Algorithm 2:** Decryption of AES-128

---

**Input:** block  $\text{src} \in \{0, 1\}^{128}$ , round-keys  $\{rk_i\}_{i=0}^{11}$  ( $rk_i \in \{0, 1\}^{128}$ )

**Output:** block  $\text{dst} \in \{0, 1\}^{128}$

```
1  $t \leftarrow \text{AddRoundKey}(\text{src}, rk_{10});$ 
2 for  $i \leftarrow 9$  to 1 do
3    $t \leftarrow (\text{InvSubBytes} \circ \text{InvShiftRows})(t);$ 
4    $t \leftarrow \text{AddRoundKey}(t, rk_i);$ 
5    $t \leftarrow \text{InvMixColumns}(t);$ 
6 end
7  $t \leftarrow (\text{InvShiftRows} \circ \text{InvSubBytes})(t);$ 
8  $t \leftarrow \text{AddRoundKey}(t, rk_0);$ 
9  $\text{dst} \leftarrow t;$ 
10 return  $\text{dst};$ 
```

---

## 1.2 Functions and Constants used in AES

### 1.2.1 Key Expansion

- **RotWord** :  $\{0, 1\}^{32} \rightarrow \{0, 1\}^{32}$  is defined by

$$\text{RotWord}(X_0 \parallel X_1 \parallel X_2 \parallel X_3) := X_1 \parallel X_2 \parallel X_3 \parallel X_0 \quad \text{for } X_i \in \{0, 1\}^8.$$

Code 1.1: RotWord rotates the input word left by one byte

```
1 u32 RotWord(u32 word) {
2     return (word << 0x08) | (word >> 0x18);
3 }
```

- **SubWord** :  $\{0, 1\}^{32} \rightarrow \{0, 1\}^{32}$  is defined by

$$\text{SubWord}(X_0 \parallel X_1 \parallel X_2 \parallel X_3) := s(X_0) \parallel s(X_1) \parallel s(X_2) \parallel s(X_3) \quad \text{for } X_i \in \{0, 1\}^8.$$

Here,  $s : \{0, 1\}^8 \rightarrow \{0, 1\}^8$  is the **S-box**.

Code 1.2: SubWord applies the S-box to each byte of the input word

```
1 u32 SubWord(u32 word) {
2     return (u32)s_box[word >> 0x18] << 0x18 |
3         (u32)s_box[(word >> 0x10) & 0xFF] << 0x10 |
4         (u32)s_box[(word >> 0x08) & 0xFF] << 0x08 |
5         (u32)s_box[word & 0xFF];
6 }
```

- **Round Constant rCon**:

The constant  $\text{rCon}_i \in \mathbb{F}_{2^8}$  used in generating the  $i$ -th round key corresponds to the value of  $x^{i-1}$  in the binary finite field  $\mathbb{F}_{2^8}$  and is as follows:

$i$	1	2	3	4	5	6	7	8	9	10
$\text{Rcon}_i$	0x01	0x02	0x04	0x08	0x10	0x20	0x40	0x80	0x1b	0x36

Code 1.3: rCon Array Declaration

```
1 static const u32 rCon[10] = {
2     0x01000000, 0x02000000, 0x04000000, 0x08000000,
3     0x10000000, 0x20000000, 0x40000000, 0x80000000,
4     0x1b000000, 0x36000000
5 };
```

**Algorithm 3:** Key Schedule (AES-128)

---

**Input:** User key  $uk = (uk_0, \dots, uk_{15})$  ( $uk_i \in \{0, 1\}^8$ ); //  $uk \in \{0, 1\}^{128}$  is 16-byte

**Output:** round-keys  $\{rk_i\}_{i=0}^{43}$  ( $rk_i \in \{0, 1\}^{32}$ ); //  $\{rk_i\}_{i=0}^{43} \in \{0, 1\}^{1408}$  is 176-byte

---

```

1  $rk_0 \leftarrow uk_0 \parallel uk_1 \parallel uk_2 \parallel uk_3$ ;
2  $rk_1 \leftarrow uk_4 \parallel uk_5 \parallel uk_6 \parallel uk_7$ ;
3  $rk_2 \leftarrow uk_8 \parallel uk_9 \parallel uk_{10} \parallel uk_{11}$ ;
4  $rk_3 \leftarrow uk_{12} \parallel uk_{13} \parallel uk_{14} \parallel uk_{15}$ ;
5 for  $i = 4$  to 43 do
6    $t \leftarrow rk_{i-1}$ ;
7   if  $i \bmod 4 = 0$  then
8     /* SubWord  $\circ$  RotWord :  $\{0, 1\}^{32} \rightarrow \{0, 1\}^{32}$  */
9      $t \leftarrow \text{RotWord}(t)$ ;
10     $t \leftarrow \text{SubWord}(t)$ ;
11     $t \leftarrow t \oplus (\text{rCon}_{i/4} \parallel 0x00 \parallel 0x00 \parallel 0x00)$ ;
12  end
13  $rk_i \leftarrow rk_{i-4} \oplus_{32} t$ ;
14 end

```

---

## Code 1.4: AES Key Expansion

```

1 void KeyExpansion(const u8* uKey, u32* rKey) {
2   u32 temp;
3   int i = 0;
4
5   // Copy the input key to the first round key
6   while (i < 4) {
7     rKey[i] = (u32)uKey[4*i] << 0x18 |
8     (u32)uKey[4*i+1] << 0x10 |
9     (u32)uKey[4*i+2] << 0x08 |
10    (u32)uKey[4*i+3];
11    i++;
12  }
13
14  i = 4;
15
16  // Generate the remaining round keys
17  while (i < 44) {
18    temp = rKey[i-1];
19    if (i % 4 == 0) {
20      temp = SubWord(RotWord(temp)) ^ rCon[i/4-1];
21    }
22    rKey[i] = rKey[i-4] ^ temp;
23    i++;
24  }
25 }

```

## 1.2.2 AddRoundKey

- $\text{AddRoundKey} : \{0, 1\}^{128} \times \{0, 1\}^{128} \rightarrow \{0, 1\}^{128}$  is defined by

$$\text{AddRoundKey}(\{X_i\}_{i=0}^{15}, \{rk_i\}_{i=0}^3) := \{X_i \oplus_8 uk_i\}_{i=0}^{15}.$$

Code 1.5: AES AddRoundKey

```

1 void AddRoundKey(u8* state, const u32* rKey) {
2     for (int i = 0; i < AES_KEY_SIZE; i++) {
3         // i = 0, 1, 2, 3 => wordIndex = 0
4         // i = 4, 5, 6, 7 => wordIndex = 1
5         // i = 8, 9, 10, 11 => wordIndex = 2
6         // i = 12, 13, 14, 15 => wordIndex = 3
7         int wordIndex = i / 4;
8
9         // i = 0, 1, 2, 3 => bytePosition = 0, 1, 2, 3
10        // i = 4, 5, 6, 7 => bytePosition = 0, 1, 2, 3
11        // i = 8, 9, 10, 11 => bytePosition = 0, 1, 2, 3
12        // i = 12, 13, 14, 15 => bytePosition = 0, 1, 2, 3
13        int bytePosition = i % 4;
14        /*
15         * +-----+-----+-----+-----+
16         * | i      | wordIndex | bytePosition | shiftedWord |
17         * +-----+-----+-----+-----+
18         * | 0-3    | 0        | 0          | rKey[0] >> 0x18 |
19         * |        |        | 1          | rKey[0] >> 0x10 |
20         * |        |        | 2          | rKey[0] >> 0x08 |
21         * |        |        | 3          | rKey[0]         |
22         * +-----+-----+-----+-----+
23         * | 4-7    | 1        | 0          | rKey[1] >> 24   |
24         * |        |        | 1          | rKey[1] >> 16   |
25         * |        |        | 2          | rKey[1] >> 8    |
26         * |        |        | 3          | rKey[1]         |
27         * +-----+-----+-----+-----+
28         * | ...    | ...      | ...        | ...            |
29         * +-----+-----+-----+-----+
30         * | 15     | 3        | 3          | rKey[3]         |
31         * +-----+-----+-----+-----+
32        */
33        u32 shiftedWord =
34            rKey[wordIndex] >> (8 * (3 - bytePosition));
35
36        u8 keyByte = shiftedWord & 0xFF;
37        state[i] ^= keyByte;
38
39        /* Extract the corresponding byte from the round key word */
40        // state[i] ^= (rKey[i / 4] >> (8 * (3 - (i % 4)))) & 0xFF;
41    }
42 }

```



### 1.2.3 SubBytes / InvSubBytes

- SubBytes :  $\{0, 1\}^{128} \rightarrow \{0, 1\}^{128}$  is defined by

$$\text{SubBytes}(\{X_i\}_{i=0}^{15}) = \{s(X_i)\}_{i=0}^{15}.$$

- InvSubBytes :  $\{0, 1\}^{128} \rightarrow \{0, 1\}^{128}$  is defined by

$$\text{SubBytes}(\{X_i\}_{i=0}^{15}) = \{s^{-1}(X_i)\}_{i=0}^{15}.$$

Table 1.1: Substitution Box

	00	01	02	03	04	05	06	07	08	09	0a	0b	0c	0d	0e	0f
00	63	7c	77	7b	f2	6b	6f	c5	30	01	67	2b	fe	d7	ab	76
10	ca	82	...	...	...	...	...	...	...	...	...	...	...	...	...	...
30	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
40	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
50	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
60	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
70	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
80	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
90	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
a0	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
b0	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
c0	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
d0	...	...	...	...	...	...	...	...	...	...	...	...	...	c1	...	...
e0	...	...	...	...	...	...	...	...	...	...	...	...	...	...	28	...
f0	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...	16

Code 1.6: Byte Substitution

```

1 void SubBytes(u8* state) {
2     for (int i = 0; i < AES_KEY_SIZE; i++) {
3         state[i] = s_box[state[i]];
4     }
5 }

```

Code 1.7: Inverse Byte Substitution

```

1 void SubBytes(u8* state) {
2     for (int i = 0; i < AES_KEY_SIZE; i++) {
3         state[i] = inv_s_box[state[i]];
4     }
5 }

```

## 1.2.4 ShiftRows / InvShiftRows

- ShiftRows :  $\{0, 1\}^{128} \rightarrow \{0, 1\}^{128}$  is defined by

$X_0$	$X_4$	$X_8$	$X_{12}$
$X_1$	$X_5$	$X_9$	$X_{13}$
$X_2$	$X_6$	$X_{10}$	$X_{14}$
$X_3$	$X_7$	$X_{11}$	$X_{15}$

 $\Rightarrow$ 

$X_0$	$X_4$	$X_8$	$X_{12}$
$X_5$	$X_9$	$X_{13}$	$X_1$
$X_{10}$	$X_{14}$	$X_2$	$X_6$
$X_{15}$	$X_3$	$X_7$	$X_{11}$

- InvShiftRows :  $\{0, 1\}^{128} \rightarrow \{0, 1\}^{128}$  is defined by

$X_0$	$X_4$	$X_8$	$X_{12}$
$X_1$	$X_5$	$X_9$	$X_{13}$
$X_2$	$X_6$	$X_{10}$	$X_{14}$
$X_3$	$X_7$	$X_{11}$	$X_{15}$

 $\Rightarrow$ 

$X_0$	$X_4$	$X_8$	$X_{12}$
$X_{13}$	$X_1$	$X_5$	$X_9$
$X_{10}$	$X_{14}$	$X_2$	$X_6$
$X_7$	$X_{11}$	$X_{15}$	$X_3$

Code 1.8: ShiftRows

```

1 void ShiftRows(u8* state) {
2     u8 temp;
3
4     // Row 1: shift left by 1
5     temp = state[1];
6     state[1] = state[5];
7     state[5] = state[9];
8     state[9] = state[13];
9     state[13] = temp;
10
11    // Row 2: shift left by 2
12    temp = state[2];
13    state[2] = state[10];
14    state[10] = temp;
15    temp = state[6];
16    state[6] = state[14];
17    state[14] = temp;
18
19    // Row 3: shift left by 3 (or right by 1)
20    temp = state[15];
21    state[15] = state[11];
22    state[11] = state[7];
23    state[7] = state[3];
24    state[3] = temp;
25 }

```

Code 1.9: Inverse ShiftRows

```
1 void InvShiftRows(u8* state) {  
2     u8 temp;  
3  
4     // Row 1: shift left by 3 (or right by 1)  
5     temp = state[13];  
6     state[13] = state[9];  
7     state[9] = state[5];  
8     state[5] = state[1];  
9     state[1] = temp;  
10  
11    // Row 2: shift left by 2  
12    temp = state[2];  
13    state[2] = state[10];  
14    state[10] = temp;  
15    temp = state[6];  
16    state[6] = state[14];  
17    state[14] = temp;  
18  
19    // Row 3: shift left by 1  
20    temp = state[3];  
21    state[3] = state[7];  
22    state[7] = state[11];  
23    state[11] = state[15];  
24    state[15] = temp;  
25 }
```

### 1.2.5 MixColumns / InvMixColumns

- Multiplication in the finite field  $GF(2^8)$ .

$$\text{MUL}_{GF(2^8)} : \{0, 1\}^8 \times \{0, 1\}^8 \rightarrow \{0, 1\}^8.$$

Here,

$$\{0, 1\}^8 \simeq GF(2^8) = \mathbb{F}_{2^8} := \mathbb{F}_2[z]/(z^8 + z^4 + z^3 + z + 1) = \left\{ a_7z^7 + \dots + a_1z + a_0 : a_i \in \mathbb{F}_2 \right\}.$$

Note that

$$a(z) \times b(z) := a(z) \times b(z) \bmod (z^8 + z^4 + z^3 + z + 1)$$

**Note.** Given two polynomials  $a(x)$  and  $b(x)$  in  $GF(2^8)$ :

$$a(x) = a_7x^7 + a_6x^6 + a_5x^5 + a_4x^4 + a_3x^3 + a_2x^2 + a_1x + a_0,$$

$$b(x) = b_7x^7 + b_6x^6 + b_5x^5 + b_4x^4 + b_3x^3 + b_2x^2 + b_1x + b_0.$$

The algorithm performs polynomial multiplication in the finite field  $GF(2^8)$ . It uses a shift-and-add method, with an additional reduction step modulo an irreducible polynomial  $m(x) = x^8 + x^4 + x^3 + x + 1$ .

1. Initialization: Set  $p(x) = 0$  to initialize the product polynomial.
2. Iterate over each bit of  $b(x)$ , from LSB to MSB.
  - (i) If the current bit  $b_i$  of  $b(x)$  is 1, update  $p(x)$  as  $p(x) \oplus a(x)$ . In  $GF(2^8)$ , addition is equivalent to the XOR operation:

$$p(x) = p(x) \oplus a(x).$$

- (ii) Shift  $a(x)$  left by 1 (multiply by  $x$ ), increasing its degree by 1:

$$a(x) = a(x) \cdot x.$$

- (iii) If the coefficient of  $x^8$  in  $a(x)$  is 1, reduce  $a(x)$  by  $m(x)$  to keep the degree under 8:

$$a(x) = a(x) \oplus m(x).$$

- (iv) Shift  $b(x)$  right by 1 (divide by  $x$ ) for the next iteration:

$$b(x) = b(x) / x.$$

3. After all bits of  $b(x)$  are processed,  $p(x)$  be the product of  $a(x)$  and  $b(x)$  modulo  $m(x)$ .

**Note (Modular Reduction in  $GF(2^8)$  using XOR).** In the context of multiplication in the binary finite field  $GF(2^8)$ , modular reduction ensures that results of operations remain within the field. The use of XOR for modular reduction is due to the properties of polynomial arithmetic over  $GF(2)$  and the representation of elements in  $GF(2^8)$ .

– **Polynomial Representation in  $GF(2^8)$ :**

1. **Elements as Polynomials:** Each element in  $GF(2^8)$  can be represented as a polynomial of degree less than 8, where each coefficient is either 0 or 1, i.e.,

$$GF(2^8) = \mathbb{F}_2[x]/(x^8 + x^4 + x^3 + x + 1) = \{a_7x^7 + \dots + a_1x + a_0 : a_i \in \mathbb{F}_2\}.$$

This corresponds to an 8-bit binary number, with each bit representing a coefficient of the polynomial, i.e.,

$$a_7x^7 + \dots + a_1x + a_0 \iff (a_7 \dots a_1a_0)_2.$$

2. **Binary Operations:** In  $GF(2)$ , addition and subtraction are equivalent to the XOR operation, since  $1 + 1 = 0$  in this field, the same as  $1 \oplus 1$ .

– **Modular Reduction with an Irreducible Polynomial**

1. **Irreducible Polynomial:** In  $GF(2^8)$ , an irreducible polynomial of degree 8, typically  $p(x) = x^8 + x^4 + x^3 + x + 1$  (represented as `0x11b` in binary), is used for modular reduction.
  2. **Modular Reduction Process:** After multiplying two polynomials, if the resulting polynomial's degree is 8 or higher, it must be reduced modulo the irreducible polynomial to ensure the result remains a polynomial of degree less than 8, thus staying within  $GF(2^8)$ .
  3. **XOR for Reduction:** XOR is used for modular reduction in  $GF(2^8)$  because polynomial subtraction in  $GF(2)$  is performed by XORing coefficients.
- Given two elements in  $GF(2^8)$ ,  $a(x)$  and  $b(x)$ , their product is  $c(x) = a(x) \cdot b(x)$ . If  $\deg(c(x)) \geq 8$ , then  $c(x)$  must be reduced modulo the irreducible polynomial  $p(x)$ . This is achieved by XORing the coefficients of  $c(x)$  and  $p(x)$ :

$$c(x) = a(x) \cdot b(x) \mod p(x)$$

If  $c(x)$  has a term  $x^8$  or higher, we subtract  $p(x)$  from  $c(x)$  to reduce its degree. In  $GF(2)$ , subtraction is equivalent to addition, performed by XORing coefficients:

$$c'(x) = c(x) \oplus p(x)$$

This operation effectively eliminates the term  $x^8$  (or higher) in  $c(x)$ , ensuring that the result remains within  $GF(2^8)$ . Consider the product of two polynomials  $a(x)$  and  $b(x)$  in  $GF(2^8)$ :

$$a(x) = x^6 + x^4 + x^2 + x + 1 \quad \text{and} \quad b(x) = x^7 + x + 1$$

The product  $c(x) = a(x) \cdot b(x)$  might yield a polynomial of degree 8 or higher. To reduce  $c(x)$  modulo  $p(x) = x^8 + x^4 + x^3 + x + 1$ , we perform XOR between the coefficients of  $c(x)$  and  $p(x)$ , ensuring the result stays within  $GF(2^8)$ .

Code 1.10: Multiplication in  $GF(2^8)$ 

```

1  u8 MUL_GF256(u8 a, u8 b) {
2      u8 res = 0;
3      // Mask for detecting the MSB (0x80 = 0b10000000)
4      u8 MSB_mask = 0x80;
5      u8 MSB;
6      /*
7       * The reduction polynomial
8       * (x^8 + x^4 + x^3 + x + 1) = 0b100011011
9       * for AES, represented in hexadecimal
10     */
11     u8 modulo = 0x1B;
12
13     for (int i = 0; i < 8; i++) {
14         // Add a to result if LSB(b)=1
15         if (b & 1)
16             res ^= a;
17
18         MSB = a & MSB_mask; // Store the MSB of a
19         a <<= 1; // Multiplying it by x effectively
20
21         // Reduce the result modulo the reduction polynomial
22         if (MSB)
23             a ^= modulo;
24
25         b >>= 1; // Moving to the next bit
26     }
27
28     return res;
29 }
30
31 #define MUL_GF256(a, b) ({ \
32     u8 res = 0; \
33     u8 MSB_mask = 0x80; \
34     u8 MSB; \
35     u8 modulo = 0x1B; \
36     u8 temp_a = (a); \
37     u8 temp_b = (b); \
38     for (int i = 0; i < 8; i++) { \
39         if (temp_b & 1) \
40             res ^= temp_a; \
41         MSB = temp_a & MSB_mask; \
42         temp_a <<= 1; \
43         if (MSB) \
44             temp_a ^= modulo; \
45         temp_b >>= 1; \
46     } \
47     res; \
48 })

```

- MixColumns :  $\{0, 1\}^{128} \rightarrow \{0, 1\}^{128}$  is defined by

$$\text{MixColumns} \begin{pmatrix} X_0 & X_4 & X_8 & X_{12} \\ X_1 & X_5 & X_9 & X_{13} \\ X_2 & X_6 & X_{10} & X_{14} \\ X_3 & X_7 & X_{11} & X_{15} \end{pmatrix} := \begin{pmatrix} 0x02 & 0x03 & 0x01 & 0x01 \\ 0x01 & 0x02 & 0x03 & 0x01 \\ 0x01 & 0x01 & 0x02 & 0x03 \\ 0x03 & 0x01 & 0x01 & 0x02 \end{pmatrix} \begin{pmatrix} X_0 & X_4 & X_8 & X_{12} \\ X_1 & X_5 & X_9 & X_{13} \\ X_2 & X_6 & X_{10} & X_{14} \\ X_3 & X_7 & X_{11} & X_{15} \end{pmatrix}.$$

- InvMixColumns :  $\{0, 1\}^{128} \rightarrow \{0, 1\}^{128}$  is defined by

$$\text{MixColumns} \begin{pmatrix} X_0 & X_4 & X_8 & X_{12} \\ X_1 & X_5 & X_9 & X_{13} \\ X_2 & X_6 & X_{10} & X_{14} \\ X_3 & X_7 & X_{11} & X_{15} \end{pmatrix} := \begin{pmatrix} 0x0e & 0x0b & 0x0d & 0x09 \\ 0x09 & 0x0e & 0x0b & 0x0d \\ 0x0d & 0x09 & 0x0e & 0x0b \\ 0x0b & 0x0d & 0x09 & 0x0e \end{pmatrix} \begin{pmatrix} X_0 & X_4 & X_8 & X_{12} \\ X_1 & X_5 & X_9 & X_{13} \\ X_2 & X_6 & X_{10} & X_{14} \\ X_3 & X_7 & X_{11} & X_{15} \end{pmatrix}.$$

Code 1.11: MixColumns

```

1 void MixColumns(u8* state) {
2     u8 temp[4];
3     // Multiply and add the elements in the column
4     // by the fixed polynomial
5     for (int i = 0; i < 4; i++) {
6         temp[0] =
7             MUL_GF256(0x02, state[i * 4]) ^
8             MUL_GF256(0x03, state[i * 4 + 1]) ^
9             state[i * 4 + 2] ^
10            state[i * 4 + 3];
11
12        temp[1] =
13            state[i * 4] ^
14            MUL_GF256(0x02, state[i * 4 + 1]) ^
15            MUL_GF256(0x03, state[i * 4 + 2]) ^
16            state[i * 4 + 3];
17
18        temp[2] =
19            state[i * 4] ^
20            state[i * 4 + 1] ^
21            MUL_GF256(0x02, state[i * 4 + 2]) ^
22            MUL_GF256(0x03, state[i * 4 + 3]);
23
24        temp[3] =
25            MUL_GF256(0x03, state[i * 4]) ^
26            state[i * 4 + 1] ^
27            state[i * 4 + 2] ^
28            MUL_GF256(0x02, state[i * 4 + 3]);
29
30        // Copy the mixed column back to the state
31        for (int j = 0; j < 4; j++)
32            state[i * 4 + j] = temp[j];
33    }
34 }

```

Code 1.12: Inverse MixColumns

```

1  void InvMixColumns(u8* state) {
2      u8 temp[4];
3
4      for (int i = 0; i < 4; i++) {
5          temp[0] =
6              MUL_GF256(0x0e, state[i * 4]) ^
7              MUL_GF256(0x0b, state[i * 4 + 1]) ^
8              MUL_GF256(0x0d, state[i * 4 + 2]) ^
9              MUL_GF256(0x09, state[i * 4 + 3]);
10
11         temp[1] =
12             MUL_GF256(0x09, state[i * 4]) ^
13             MUL_GF256(0x0e, state[i * 4 + 1]) ^
14             MUL_GF256(0x0b, state[i * 4 + 2]) ^
15             MUL_GF256(0x0d, state[i * 4 + 3]);
16
17         temp[2] =
18             MUL_GF256(0x0d, state[i * 4]) ^
19             MUL_GF256(0x09, state[i * 4 + 1]) ^
20             MUL_GF256(0x0e, state[i * 4 + 2]) ^
21             MUL_GF256(0x0b, state[i * 4 + 3]);
22
23         temp[3] =
24             MUL_GF256(0x0b, state[i * 4]) ^
25             MUL_GF256(0x0d, state[i * 4 + 1]) ^
26             MUL_GF256(0x09, state[i * 4 + 2]) ^
27             MUL_GF256(0x0e, state[i * 4 + 3]);
28
29         for (int j = 0; j < 4; j++)
30             state[i * 4 + j] = temp[j];
31     }
32 }

```



# Chapter 2

## AES - 128 / 192 / 256 (Byte Version)

### 2.1 Specification

Table 2.1: Parameters of the Block Cipher AES

Algorithms	Block Size ( $N_b$ -byte)	Key Length ( $N_k$ -byte)	Number of Rounds ( $N_r$ )	Round-Key Length (byte)	Number of Round-Keys ( $N_r + 1$ )	Total Size of Round-Keys ( $N_b(N_r + 1)$ )
AES-128	16	16 (128-bit)	10	16	11	176
AES-192	16	24 (192-bit)	12	16	13	208
AES-256	16	32 (256-bit)	14	16	15	240

Code 2.1: Configuration

```
1 // Define macros for AES key length
2 #define AES_VERSION 128 // Can be 128, 192, or 256
3 // Define macro for AES block size
4 #define AES_BLOCK_SIZE 16
5
6 // Define Nk and Nr based on AES key length
7 #if AES_VERSION == 128
8     #define Nk 4
9     #define Nr (Nk + 6) // 10
10    #define ROUND_KEYS_SIZE (16 * (Nr + 1)) // 176
11 #elif AES_VERSION == 192
12     #define Nk 6
13     #define Nr (Nk + 6) // 12
14     #define ROUND_KEYS_SIZE (16 * (Nr + 1)) // 208
15 #elif AES_VERSION == 256
16     #define Nk 8
17     #define Nr (Nk + 6) // 14
18     #define ROUND_KEYS_SIZE (16 * (Nr + 1)) // 240
19 #else
20     #error "Invalid AES ky length"
21 #endif
```

## 2.2 Key Expansion (General Version)

---

### Algorithm 4: Key Schedule (General Version)

---

**Input:** User-key  $uk = (uk_0, \dots, uk_{N_k-1})$  ( $uk_i \in \{0, 1\}^8$ ); //  $uk$  is 16/24/32-byte

**Output:** Round-key  $\{rk_i\}_{i=0}^{4(N_r+1)-1}$  ( $rk_i \in \{0, 1\}^{32}$ )

/\*  $\{rk_i\}_{i=0}^{4(N_r+1)-1}$  is 176/208/240-byte \*/

```

1  $l \leftarrow N_k/4;$  //  $l = 4, 6, 8$ 
2 for  $i = 0$  to  $l - 1$  do
3    $rk_i \leftarrow uk_{4i} \parallel uk_{4i+1} \parallel uk_{4i+2} \parallel uk_{4i+3};$ 
4 end
5 for  $i = l$  to  $4(N_r + 1) - 1$  do
6    $t \leftarrow rk_{i-1};$ 
7   if  $i \bmod l = 0$  then
8      $t \leftarrow \text{SubWord} \circ \text{RotWord}(t);$ 
9      $t \leftarrow t \oplus (\text{rCon}_{i/l} \parallel 0x00 \parallel 0x00 \parallel 0x00);$ 
10  else if  $l > 6 \ \&\& \ i \bmod l = 4$  then
11     $t \leftarrow \text{SubWord}(t);$ 
12  end
13   $rk_i \leftarrow rk_{i-l} \oplus_{32} t;$ 
14 end

```

---

Code 2.2: Key Expansion (General ver.)

```

1 void KeyExpansion(const u8* uKey, u32* rKey) {
2   u32 temp;
3
4   for (int i = 0; i < Nk; i++) {
5     rKey[i] = (u32)uKey[4*i] << 0x18 |
6              (u32)uKey[4*i+1] << 0x10 |
7              (u32)uKey[4*i+2] << 0x08 |
8              (u32)uKey[4*i+3];
9   }
10
11  for (int i = Nk; i < (Nr + 1) * 4; i++) {
12    temp = rKey[i - 1];
13    if (i % Nk == 0) {
14      temp = SubWord(RotWord(temp)) ^ rCon[i / Nk - 1];
15    } else if (Nk > 6 && i % Nk == 4) {
16      // Additional S-box transformation for AES-256
17      temp = SubWord(temp);
18    }
19    rKey[i] = rKey[i - Nk] ^ temp;
20  }
21 }

```

## 2.3 Advanced Encryption Standard - 128 / 192 / 256

---

### Algorithm 5: Encryption of AES

---

**Input:** block  $\text{src} \in \{0, 1\}^{128}$ , round-keys  $\{rk_i\}_{i=0}^{N_r+1}$  ( $rk_i \in \{0, 1\}^{128}$ )

**Output:** block  $\text{dst} \in \{0, 1\}^{128}$

```

1  $t \leftarrow \text{src};$ 
2  $t \leftarrow \text{AddRoundKey}(t, rk_0);$ 
3 for  $i \leftarrow 1$  to  $N_r - 1$  do
4    $t \leftarrow \text{SubBytes}(t);$ 
5    $t \leftarrow \text{ShiftRows}(t);$ 
6    $t \leftarrow \text{MixColumns}(t);$ 
7    $t \leftarrow \text{AddRoundKey}(t, rk_i);$ 
8 end
9  $t \leftarrow \text{SubBytes}(t);$ 
10  $t \leftarrow \text{ShiftRows}(t);$ 
11  $t \leftarrow \text{AddRoundKey}(t, rk_{N_r});$ 
12  $\text{dst} \leftarrow t;$ 
13 return  $\text{dst};$ 

```

---



---

### Algorithm 6: Decryption of AES

---

**Input:** block  $\text{src} \in \{0, 1\}^{128}$ , round-keys  $\{rk_i\}_{i=0}^{N_r+1}$  ( $rk_i \in \{0, 1\}^{128}$ )

**Output:** block  $\text{dst} \in \{0, 1\}^{128}$

```

1  $t \leftarrow \text{src};$ 
2  $t \leftarrow \text{AddRoundKey}(t, rk_{N_r});$ 
3 for  $i \leftarrow N_r - 1$  to 1 do
4    $t \leftarrow \text{InvShiftRows}(t);$ 
5    $t \leftarrow \text{InvSubBytes}(t);$ 
6    $t \leftarrow \text{AddRoundKey}(t, rk_i);$ 
7    $t \leftarrow \text{InvMixColumns}(t);$ 
8 end
9  $t \leftarrow \text{InvSubBytes}(t);$ 
10  $t \leftarrow \text{InvShiftRows}(t);$ 
11  $t \leftarrow \text{AddRoundKey}(t, rk_0);$ 
12  $\text{dst} \leftarrow t;$ 
13 return  $\text{dst};$ 

```

---

## Chapter 3

# AES - 128 / 192 / 256 (32-bit Version)

### 3.1 $8 \times 32$ Table Look Up

Convert the 8-bit string  $\{X_i\}_{i=0}^{15}$  ( $X_i \in \{0, 1\}^8$ ) into a 32-bit string  $\{Y_i\}_{i=0}^3$  ( $Y_i \in \{0, 1\}^{32}$ ) as follows:

$$Y_i := (X_{4i} \ll 24) \parallel (X_{4i+1} \ll 16) \parallel (X_{4i+2} \ll 8) \parallel (X_{4i+3}) \in \{0, 1\}^{32}$$

for  $i = 0, 1, 2, 3$ . In other words,

$X_0$	$(Y_0 \gg 0x18) \& 0xff$	$X_4$	$(Y_1 \gg 0x18) \& 0xff$
$X_1$	$(Y_0 \gg 0x10) \& 0xff$	$X_5$	$(Y_1 \gg 0x10) \& 0xff$
$X_2$	$(Y_0 \gg 0x08) \& 0xff$	$X_6$	$(Y_1 \gg 0x08) \& 0xff$
$X_3$	$(Y_0) \& 0xff$	$X_7$	$(Y_1) \& 0xff$
$X_8$	$(Y_2 \gg 0x18) \& 0xff$	$X_{12}$	$(Y_3 \gg 0x18) \& 0xff$
$X_9$	$(Y_2 \gg 0x10) \& 0xff$	$X_{13}$	$(Y_3 \gg 0x10) \& 0xff$
$X_{10}$	$(Y_2 \gg 0x08) \& 0xff$	$X_{14}$	$(Y_3 \gg 0x08) \& 0xff$
$X_{11}$	$(Y_2) \& 0xff$	$X_{15}$	$(Y_3) \& 0xff$

Note that

$X_0$	$X_1$	$X_2$	$X_3$	$X_4$	$X_5$	$X_6$	$X_7$	$X_8$	$X_9$	$X_{10}$	$X_{11}$	$X_{12}$	$X_{13}$	$X_{14}$	$X_{15}$
$Y_0$				$Y_1$				$Y_2$				$Y_3$			

### 3.2 SubMix and InvSubInvMix

- $\text{SubMix} : \{0, 1\}^{128} \rightarrow \{0, 1\}^{128}$  and  $\text{InvSubInvMix} : \{0, 1\}^{128} \rightarrow \{0, 1\}^{128}$  are defined by

$$\text{SubMix} := \text{MixColumns} \circ \text{SubBytes}$$

$$\text{InvSubInvMix} := \text{InvMixColumns} \circ \text{InvSubBytes}.$$

---

**Algorithm 7:** Encryption of AES

---

**Input:** block  $\text{src} \in \{0, 1\}^{128}$ , round-keys  $\{rk_i\}_{i=0}^{N_r+1}$  ( $rk_i \in \{0, 1\}^{128}$ )**Output:** block  $\text{dst} \in \{0, 1\}^{128}$ 

```

1  $t \leftarrow \text{src};$ 
2  $t \leftarrow \text{AddRoundKey}(t, rk_0);$ 
3 for  $i \leftarrow 1$  to  $N_r - 1$  do
4    $t \leftarrow \text{SubBytes}(t);$ 
5    $t \leftarrow \text{ShiftRows}(t);$ 
6    $t \leftarrow \text{MixColumns}(t);$ 
7    $t \leftarrow \text{AddRoundKey}(t, rk_i);$ 
8 end
9  $t \leftarrow \text{SubBytes}(t);$ 
10  $t \leftarrow \text{ShiftRows}(t);$ 
11  $t \leftarrow \text{AddRoundKey}(t, rk_{N_r});$ 
12  $\text{dst} \leftarrow t;$ 
13 return  $\text{dst};$ 

```

---



---

**Algorithm 8:** Decryption of AES

---

**Input:** block  $\text{src} \in \{0, 1\}^{128}$ , round-keys  $\{rk_i\}_{i=0}^{N_r+1}$  ( $rk_i \in \{0, 1\}^{128}$ )**Output:** block  $\text{dst} \in \{0, 1\}^{128}$ 

```

1  $t \leftarrow \text{src};$ 
2  $t \leftarrow \text{AddRoundKey}(t, rk_{N_r});$ 
3 for  $i \leftarrow N_r - 1$  to  $1$  do
4    $t \leftarrow \text{InvShiftRows}(t);$ 
5    $t \leftarrow \text{InvSubBytes}(t);$ 
6    $t \leftarrow \text{AddRoundKey}(t, rk_i);$ 
7    $t \leftarrow \text{InvMixColumns}(t);$ 
8 end
9  $t \leftarrow \text{InvSubBytes}(t);$ 
10  $t \leftarrow \text{InvShiftRows}(t);$ 
11  $t \leftarrow \text{AddRoundKey}(t, rk_0);$ 
12  $\text{dst} \leftarrow t;$ 
13 return  $\text{dst};$ 

```

---

### 3.3 Generation of $8 \times 32$ Tables

Note that

$$\begin{aligned}
 \begin{pmatrix} X'_0 & X'_4 & X'_8 & X'_{12} \\ X'_1 & X'_5 & X'_9 & X'_{13} \\ X'_2 & X'_6 & X'_{10} & X'_{14} \\ X'_3 & X'_7 & X'_{11} & X'_{15} \end{pmatrix} &= \text{SubMix} \left( \begin{pmatrix} X_0 & X_4 & X_8 & X_{12} \\ X_1 & X_5 & X_9 & X_{13} \\ X_2 & X_6 & X_{10} & X_{14} \\ X_3 & X_7 & X_{11} & X_{15} \end{pmatrix} \right) := \\
 &\begin{pmatrix} 0x02 & 0x03 & 0x01 & 0x01 \\ 0x01 & 0x02 & 0x03 & 0x01 \\ 0x01 & 0x01 & 0x02 & 0x03 \\ 0x03 & 0x01 & 0x01 & 0x02 \end{pmatrix} \begin{pmatrix} s(X_0) & s(X_4) & s(X_8) & s(X_{12}) \\ s(X_1) & s(X_5) & s(X_9) & s(X_{13}) \\ s(X_2) & s(X_6) & s(X_{10}) & s(X_{14}) \\ s(X_3) & s(X_7) & s(X_{11}) & s(X_{15}) \end{pmatrix}, \\
 \begin{pmatrix} X'_0 & X'_4 & X'_8 & X'_{12} \\ X'_1 & X'_5 & X'_9 & X'_{13} \\ X'_2 & X'_6 & X'_{10} & X'_{14} \\ X'_3 & X'_7 & X'_{11} & X'_{15} \end{pmatrix} &= \text{InvSubInvMix} \left( \begin{pmatrix} X_0 & X_4 & X_8 & X_{12} \\ X_1 & X_5 & X_9 & X_{13} \\ X_2 & X_6 & X_{10} & X_{14} \\ X_3 & X_7 & X_{11} & X_{15} \end{pmatrix} \right) := \\
 &\begin{pmatrix} 0x0e & 0x0b & 0x0d & 0x09 \\ 0x09 & 0x0e & 0x0b & 0x0d \\ 0x0d & 0x09 & 0x0e & 0x0b \\ 0x0b & 0x0d & 0x09 & 0x0e \end{pmatrix} \begin{pmatrix} s^{-1}(X_0) & s^{-1}(X_4) & s^{-1}(X_8) & s^{-1}(X_{12}) \\ s^{-1}(X_1) & s^{-1}(X_5) & s^{-1}(X_9) & s^{-1}(X_{13}) \\ s^{-1}(X_2) & s^{-1}(X_6) & s^{-1}(X_{10}) & s^{-1}(X_{14}) \\ s^{-1}(X_3) & s^{-1}(X_7) & s^{-1}(X_{11}) & s^{-1}(X_{15}) \end{pmatrix}.
 \end{aligned}$$

Then

$$\begin{aligned}
 \begin{pmatrix} X'_{4i} \\ X'_{4i+1} \\ X'_{4i+2} \\ X'_{4i+3} \end{pmatrix} &= \begin{pmatrix} 0x02 & 0x03 & 0x01 & 0x01 \\ 0x01 & 0x02 & 0x03 & 0x01 \\ 0x01 & 0x01 & 0x02 & 0x03 \\ 0x03 & 0x01 & 0x01 & 0x02 \end{pmatrix} \begin{pmatrix} s(X_{4i}) \\ s(X_{4i+1}) \\ s(X_{4i+2}) \\ s(X_{4i+3}) \end{pmatrix} \\
 &= s(X_{4i}) \begin{pmatrix} 0x02 \\ 0x01 \\ 0x01 \\ 0x03 \end{pmatrix} \oplus s(X_{4i+1}) \begin{pmatrix} 0x03 \\ 0x02 \\ 0x01 \\ 0x01 \end{pmatrix} \oplus s(X_{4i+2}) \begin{pmatrix} 0x01 \\ 0x03 \\ 0x02 \\ 0x01 \end{pmatrix} \oplus s(X_{4i+3}) \begin{pmatrix} 0x01 \\ 0x01 \\ 0x03 \\ 0x02 \end{pmatrix}, \\
 \begin{pmatrix} X'_{4i} \\ X'_{4i+1} \\ X'_{4i+2} \\ X'_{4i+3} \end{pmatrix} &= \begin{pmatrix} 0x0e & 0x0b & 0x0d & 0x09 \\ 0x09 & 0x0e & 0x0b & 0x0d \\ 0x0d & 0x09 & 0x0e & 0x0b \\ 0x0b & 0x0d & 0x09 & 0x0e \end{pmatrix} \begin{pmatrix} s^{-1}(X_{4i}) \\ s^{-1}(X_{4i+1}) \\ s^{-1}(X_{4i+2}) \\ s^{-1}(X_{4i+3}) \end{pmatrix} \\
 &= s^{-1}(X_{4i}) \begin{pmatrix} 0x0e \\ 0x09 \\ 0x0d \\ 0x0b \end{pmatrix} \oplus s^{-1}(X_{4i+1}) \begin{pmatrix} 0x0b \\ 0x0e \\ 0x09 \\ 0x0d \end{pmatrix} \oplus s^{-1}(X_{4i+2}) \begin{pmatrix} 0x0d \\ 0x0b \\ 0x0e \\ 0x09 \end{pmatrix} \oplus s^{-1}(X_{4i+3}) \begin{pmatrix} 0x09 \\ 0x0d \\ 0x0b \\ 0x0e \end{pmatrix}.
 \end{aligned}$$

We define  $Te_i/Td_i : \{\mathbf{0}, \mathbf{1}\}^8 \rightarrow \{\mathbf{0}, \mathbf{1}\}^{32}$  ( $i \in \{0, 1, 2, 3\}$ ) as follows:

$$\begin{aligned} Te_0(X) &:= (\mathbf{0x02} \otimes s(X), s(X), s(X), \mathbf{0x03} \otimes s(X)) , \\ Te_1(X) &:= (\mathbf{0x03} \otimes s(X), \mathbf{0x02} \otimes s(X), s(X), \mathbf{0x03} \otimes s(X)) , \\ Te_2(X) &:= (s(X), \mathbf{0x03} \otimes s(X), s(X), \mathbf{0x03} \otimes s(X)) , \\ Te_3(X) &:= (s(X), s(X), s(X), \mathbf{0x03} \otimes s(X)) , \end{aligned}$$

SubMix and InvSubInvMix are computed as follows:

SubMix :

$$\text{where } \begin{cases} Y_0 := X_0 \parallel X_1 \parallel X_2 \parallel X_3 \\ Y_1 := X_4 \parallel X_5 \parallel X_6 \parallel X_7 \\ Y_2 := X_8 \parallel X_9 \parallel X_{10} \parallel X_{11} \\ Y_3 := X_{12} \parallel X_{13} \parallel X_{14} \parallel X_{15} \end{cases} \quad \text{and}$$

---

**Algorithm 9:** SubMix and InvSubInvMix

---

**Input:**  $X_0 \parallel X_1 \parallel X_2 \parallel X_3$

**Output:**  $Y_0 \parallel Y_1 \parallel Y_2 \parallel Y_3$

1 **Function** SubMix:

2   **for**  $i \leftarrow 0$  **to** 3 **do**

3      $Y_i \leftarrow Te_0((X_i \gg \mathbf{0x18}) \& \mathbf{0xff});$

4      $Y_i \leftarrow Y_i \oplus Te_1((X_i \gg \mathbf{0x10}) \& \mathbf{0xff});$

5      $Y_i \leftarrow Y_i \oplus Te_2((X_i \gg \mathbf{0x08}) \& \mathbf{0xff});$

6      $Y_i \leftarrow Y_i \oplus Te_3(X_i \& \mathbf{0xff});$

7   **end**

8 **end**

9 **return**  $Y_0 \parallel Y_1 \parallel Y_2 \parallel Y_3$

---

**Input:**  $X_0 \parallel X_1 \parallel X_2 \parallel X_3$

**Output:**  $Y_0 \parallel Y_1 \parallel Y_2 \parallel Y_3$

1 **Function** InvSubInvMix:

2   **for**  $i \leftarrow 0$  **to** 3 **do**

3      $Y_i \leftarrow Td_0((X_i \gg \mathbf{0x18}) \& \mathbf{0xff});$

4      $Y_i \leftarrow Y_i \oplus Td_1((X_i \gg \mathbf{0x10}) \& \mathbf{0xff});$

5      $Y_i \leftarrow Y_i \oplus Td_2((X_i \gg \mathbf{0x08}) \& \mathbf{0xff});$

6      $Y_i \leftarrow Y_i \oplus Td_3(X_i \& \mathbf{0xff});$

7   **end**

8 **end**

9 **return**  $Y_0 \parallel Y_1 \parallel Y_2 \parallel Y_3$

---

# Appendix A

## Additional Data A

### A.1 Substitution-BOX

```
1 static const u8 s_box[256] = {
2     0x63, 0x7c, 0x77, 0x7b, 0xf2, 0x6b, 0x6f, 0xc5,
3     0x30, 0x01, 0x67, 0x2b, 0xfe, 0xd7, 0xab, 0x76,
4     0xca, 0x82, 0xc9, 0x7d, 0xfa, 0x59, 0x47, 0xf0,
5     0xad, 0xd4, 0xa2, 0xaf, 0x9c, 0xa4, 0x72, 0xc0,
6     0xb7, 0xfd, 0x93, 0x26, 0x36, 0x3f, 0xf7, 0xcc,
7     0x34, 0xa5, 0xe5, 0xf1, 0x71, 0xd8, 0x31, 0x15,
8     0x04, 0xc7, 0x23, 0xc3, 0x18, 0x96, 0x05, 0x9a,
9     0x07, 0x12, 0x80, 0xe2, 0xeb, 0x27, 0xb2, 0x75,
10    0x09, 0x83, 0x2c, 0x1a, 0x1b, 0x6e, 0x5a, 0xa0,
11    0x52, 0x3b, 0xd6, 0xb3, 0x29, 0xe3, 0x2f, 0x84,
12    0x53, 0xd1, 0x00, 0xed, 0x20, 0xfc, 0xb1, 0x5b,
13    0x6a, 0xcb, 0xbe, 0x39, 0x4a, 0x4c, 0x58, 0xcf,
14    0xd0, 0xef, 0xaa, 0xfb, 0x43, 0x4d, 0x33, 0x85,
15    0x45, 0xf9, 0x02, 0x7f, 0x50, 0x3c, 0x9f, 0xa8,
16    0x51, 0xa3, 0x40, 0x8f, 0x92, 0x9d, 0x38, 0xf5,
17    0xbc, 0xb6, 0xda, 0x21, 0x10, 0xff, 0xf3, 0xd2,
18    0xcd, 0x0c, 0x13, 0xec, 0x5f, 0x97, 0x44, 0x17,
19    0xc4, 0xa7, 0x7e, 0x3d, 0x64, 0x5d, 0x19, 0x73,
20    0x60, 0x81, 0x4f, 0xdc, 0x22, 0x2a, 0x90, 0x88,
21    0x46, 0xee, 0xb8, 0x14, 0xde, 0x5e, 0x0b, 0xdb,
22    0xe0, 0x32, 0x3a, 0x0a, 0x49, 0x06, 0x24, 0x5c,
23    0xc2, 0xd3, 0xac, 0x62, 0x91, 0x95, 0xe4, 0x79,
24    0xe7, 0xc8, 0x37, 0x6d, 0x8d, 0xd5, 0x4e, 0xa9,
25    0x6c, 0x56, 0xf4, 0xea, 0x65, 0x7a, 0xae, 0x08,
26    0xba, 0x78, 0x25, 0x2e, 0x1c, 0xa6, 0xb4, 0xc6,
27    0xe8, 0xdd, 0x74, 0x1f, 0x4b, 0xbd, 0x8b, 0x8a,
28    0x70, 0x3e, 0xb5, 0x66, 0x48, 0x03, 0xf6, 0x0e,
29    0x61, 0x35, 0x57, 0xb9, 0x86, 0xc1, 0x1d, 0x9e,
30    0xe1, 0xf8, 0x98, 0x11, 0x69, 0xd9, 0x8e, 0x94,
31    0x9b, 0x1e, 0x87, 0xe9, 0xce, 0x55, 0x28, 0xdf,
32    0x8c, 0xa1, 0x89, 0x0d, 0xbf, 0xe6, 0x42, 0x68,
33    0x41, 0x99, 0x2d, 0x0f, 0xb0, 0x54, 0xbb, 0x16
34 };
```



```

1  static const u8 inv_s_box[256] = {
2      0x52, 0x09, 0x6a, 0xd5, 0x30, 0x36, 0xa5, 0x38,
3      0xbf, 0x40, 0xa3, 0x9e, 0x81, 0xf3, 0xd7, 0xfb,
4      0x7c, 0xe3, 0x39, 0x82, 0x9b, 0x2f, 0xff, 0x87,
5      0x34, 0x8e, 0x43, 0x44, 0xc4, 0xde, 0xe9, 0xcb,
6      0x54, 0x7b, 0x94, 0x32, 0xa6, 0xc2, 0x23, 0x3d,
7      0xee, 0x4c, 0x95, 0x0b, 0x42, 0xfa, 0xc3, 0x4e,
8      0x08, 0x2e, 0xa1, 0x66, 0x28, 0xd9, 0x24, 0xb2,
9      0x76, 0x5b, 0xa2, 0x49, 0x6d, 0x8b, 0xd1, 0x25,
10     0x72, 0xf8, 0xf6, 0x64, 0x86, 0x68, 0x98, 0x16,
11     0xd4, 0xa4, 0x5c, 0xcc, 0x5d, 0x65, 0xb6, 0x92,
12     0x6c, 0x70, 0x48, 0x50, 0xfd, 0xed, 0xb9, 0xda,
13     0x5e, 0x15, 0x46, 0x57, 0xa7, 0x8d, 0x9d, 0x84,
14     0x90, 0xd8, 0xab, 0x00, 0x8c, 0xbc, 0xd3, 0x0a,
15     0xf7, 0xe4, 0x58, 0x05, 0xb8, 0xb3, 0x45, 0x06,
16     0xd0, 0x2c, 0x1e, 0x8f, 0xca, 0x3f, 0x0f, 0x02,
17     0xc1, 0xaf, 0xbd, 0x03, 0x01, 0x13, 0x8a, 0x6b,
18     0x3a, 0x91, 0x11, 0x41, 0x4f, 0x67, 0xdc, 0xea,
19     0x97, 0xf2, 0xcf, 0xce, 0xf0, 0xb4, 0xe6, 0x73,
20     0x96, 0xac, 0x74, 0x22, 0xe7, 0xad, 0x35, 0x85,
21     0xe2, 0xf9, 0x37, 0xe8, 0x1c, 0x75, 0xdf, 0x6e,
22     0x47, 0xf1, 0x1a, 0x71, 0x1d, 0x29, 0xc5, 0x89,
23     0x6f, 0xb7, 0x62, 0x0e, 0xaa, 0x18, 0xbe, 0x1b,
24     0xfc, 0x56, 0x3e, 0x4b, 0xc6, 0xd2, 0x79, 0x20,
25     0x9a, 0xdb, 0xc0, 0xfe, 0x78, 0xcd, 0x5a, 0xf4,
26     0x1f, 0xdd, 0xa8, 0x33, 0x88, 0x07, 0xc7, 0x31,
27     0xb1, 0x12, 0x10, 0x59, 0x27, 0x80, 0xec, 0x5f,
28     0x60, 0x51, 0x7f, 0xa9, 0x19, 0xb5, 0x4a, 0x0d,
29     0x2d, 0xe5, 0x7a, 0x9f, 0x93, 0xc9, 0x9c, 0xef,
30     0xa0, 0xe0, 0x3b, 0x4d, 0xae, 0x2a, 0xf5, 0xb0,
31     0xc8, 0xeb, 0xbb, 0x3c, 0x83, 0x53, 0x99, 0x61,
32     0x17, 0x2b, 0x04, 0x7e, 0xba, 0x77, 0xd6, 0x26,
33     0xe1, 0x69, 0x14, 0x63, 0x55, 0x21, 0x0c, 0x7d
34 };

```