

Analysis and Implementation of ECDSA over secp256r1 in libecc

Your Name
Cryptography Lab, XYZ University

June 8, 2025

Abstract

In this report, we analyze the ECDSA (Elliptic Curve Digital Signature Algorithm) implementation in the libecc library, focusing on the secp256r1 (P-256) curve. We cross-reference the FIPS 186-5 specification with the source code, detailing how domain parameters are loaded, how big-integer arithmetic is realized, how point-operations are implemented, and how the `ecdsa_sign()` and `ecdsa_verify()` functions faithfully follow the standard. Security considerations and testing results are also discussed.

Contents

1	Introduction	3
1.1	Background	3
1.2	Purpose and Scope	3
2	ECDSA Specification Overview	3
2.1	Domain Parameters for secp256r1	3
2.2	Key-Pair Generation	3
2.3	Signature Generation	3
2.4	Signature Verification	4
3	Code Repository Layout	4
4	Mapping Specification to Code	4
4.1	Domain Parameters	4
4.1.1	Code: <code>ec_params_secp256r1.h</code>	4
4.1.2	Code: <code>ec_params_load_shortw</code>	5
4.2	Big-Integer (NN) Arithmetic	5
4.3	Elliptic-Curve Arithmetic	5
4.4	ECDSA Key Generation	6
4.5	ECDSA Signature Generation	6
4.6	ECDSA Signature Verification	7

5	Testing and Validation	7
5.1	Self-Test Vectors	7
5.2	Randomized and Interoperability Tests	7
6	Security Considerations	7
7	Conclusion	7

1 Introduction

1.1 Background

ECDSA is an elliptic-curve variant of the Digital Signature Algorithm, widely used for secure digital signatures. secp256r1 (P-256) is a NIST-recommended curve with 256-bit security.

1.2 Purpose and Scope

This report details the mapping between the ECDSA specification (FIPS 186-5) and the libecc C implementation, limited to secp256r1. We assume familiarity with basic modular arithmetic and elliptic-curve fundamentals.

2 ECDSA Specification Overview

2.1 Domain Parameters for secp256r1

The secp256r1 curve is defined by:

$$\begin{aligned} p &= \text{0xFFFFFFFF0000000100000000000000000000FFFFFFFFFFFFFFFFFFFFFFF}, \\ a &= p - 3, \\ b &= \text{0x5AC635D8AA3A93E7B3EBBD55769886BC651D06B0CC53B0F63BCE3C3E27D2604B}, \\ G_x &= \text{0x6B17D1F2E12C4247F8BCE6E563A440F277037D812DEB33A0F4A13945D898C296}, \\ G_y &= \text{0x4FE342E2FE1A7F9B8EE7EB4A7C0F9E162BCE33576B315ECECB B6406837BF51F5}, \\ n &= \text{0xFFFFFFFF00000000FFFFFFFFFFFFFFFFFBCE6FAADA7179E84F3B9CAC2FC632551}, \\ h &= 1. \end{aligned}$$

2.2 Key-Pair Generation

1. Select private key $d \in [1, n - 1]$ uniformly at random.
2. Compute public key $Q = d \cdot G$ on the curve.

2.3 Signature Generation

Steps per FIPS 186-5:

1. Compute $e = \text{Hash}(m) \bmod n$.
2. Select random nonce $k \in [1, n - 1]$.
3. Compute $(x_1, y_1) = k \cdot G$, set $r = x_1 \bmod n$; if $r = 0$, go back to 2.
4. Compute $s = k^{-1}(e + d r) \bmod n$; if $s = 0$, go back to 2.
5. Output signature (r, s) .

2.4 Signature Verification

1. Verify $1 \leq r, s \leq n - 1$. If not, reject.
2. Compute $e = \text{Hash}(m) \bmod n$.
3. Compute $w = s^{-1} \bmod n$.
4. Compute $u_1 = e w \bmod n, u_2 = r w \bmod n$.
5. Compute $P = u_1 \cdot G + u_2 \cdot Q$. If P is at infinity, reject.
6. Let $v = P_x \bmod n$. Accept if $v = r$.

3 Code Repository Layout

```

1 libecc/
2 |—— include/libecc
3 |   |—— curves/known/ec_params_secp256r1.h
4 |   |—— curves/ec_params.h
5 |   |—— curves/aff_pt.h
6 |   |—— curves/ec_shortw.h
7 |   |—— nn/nn.h
8 |   |—— nn/nn_rand.h
9 |   |—— sig/ecdsa_common.h
10 |  |—— sig/ecdsa.h
11 |  |—— hash/sha256.h
12 |  |—— utils/utils_rand.h
13 |—— src
14 |—— curves/ec_params.c
15 |—— curves/aff_pt.c
16 |—— curves/ec_shortw.c
17 |—— nn/nn.c, nn_add.c, nn_mul.c, nn_modinv.c, nn_rand.c
18 |—— sig/ecdsa_common.c, ecdsa.c
19 |—— hash/sha256.c
20 |—— utils/utils_rand.c

```

4 Mapping Specification to Code

4.1 Domain Parameters

4.1.1 Code: ec_params_secp256r1.h

```
1 #define SECP256R1_P_HEX "
    FFFFFFFF00000000100000000000000000000000FFFFFFFFFFFFFFFFFFFFFFFFFFFF"
2 #define SECP256R1_A_HEX "
    FFFFFFFF00000000100000000000000000000000FFFFFFFFFFFFFFFFFFFFFFFFFC"
3 #define SECP256R1_B_HEX "5
    AC635D8AA3A93E7B3EBBD55769886BC651D06B0CC53B0F63BCE3C3E27D2604B"
```

```

4 #define SECP256R1_GX_HEX "6
    B17D1F2E12C4247F8BCE6E563A440F277037D812DEB33A0F4A13945D898C296"
5 #define SECP256R1_GY_HEX "4
    FE342E2FE1A7F9B8EE7EB4A7C0F9E162BCE33576B315ECECBB6406837BF51F5"
6 #define SECP256R1_N_HEX "
    FFFFFFFF00000000FFFFFFFFFFFFFFFFBCE6FAADA7179E84F3B9CAC2FC632551"
7 #define SECP256R1_H 1

```

4.1.2 Code: ec_params_load_shortw

```

1 int ec_params_load_shortw(ec_curve_shortw_t *C, const char *name) {
2     if (strcmp(name, "SECP256R1") == 0) {
3         nn_set_hex(&C->p, SECP256R1_P_HEX);
4         nn_set_hex(&C->a, SECP256R1_A_HEX);
5         nn_set_hex(&C->b, SECP256R1_B_HEX);
6         nn_set_hex(&C->Gx, SECP256R1_GX_HEX);
7         nn_set_hex(&C->Gy, SECP256R1_GY_HEX);
8         nn_set_hex(&C->n, SECP256R1_N_HEX);
9         C->h = SECP256R1_H;
10        return 0;
11    }
12    return -1;
13 }

```

4.2 Big-Integer (NN) Arithmetic

```

1 // nn_t definition in nn.h
2 typedef struct {
3     uint32_t words[NN_MAX_WORDS];
4     int used;
5     int sign;
6 } nn_t;
7
8 // Core operations:
9 void nn_set_hex(nn_t *r, const char *hexstr);
10 void nn_mod_mul(nn_t *r, const nn_t *a, const nn_t *b, const nn_t *m);
11 void nn_mod_inv(nn_t *r, const nn_t *a, const nn_t *m);

```

4.3 Elliptic-Curve Arithmetic

```

1 // ec_shortw_add in ec_shortw.c
2 void ec_shortw_add(affine_point_t *R,
3 const affine_point_t *P,
4 const affine_point_t *Q,
5 const ec_curve_shortw_t *C) {
6     // handle infinity cases...
7     nn_sub(&num, &Q->y, &P->y);

```

```

8     nn_sub(&den, &Q->x, &P->x);
9     nn_mod_inv(&den_inv, &den, &C->p);
10    nn_mod_mul(&lambda, &num, &den_inv, &C->p);
11    // compute x3, y3...
12    R->x = x3; R->y = y3; R->is_inf = 0;
13 }

```

4.4 ECDSA Key Generation

```

1 int ecdsa_keygen(ssize_t curve_id, nn_t *priv, affine_point_t *pub) {
2     ec_curve_shortw_t C;
3     get_curve_shortw(&C, (int)curve_id);
4     do { nn_rand(priv, &C.n); }
5     while (nn_is_zero(priv) || nn_cmp(priv, &C.n) >= 0);
6     affine_point_t G = { C.Gx, C.Gy, 0 };
7     ec_shortw_mul(pub, &G, priv, &C);
8     return 0;
9 }

```

4.5 ECDSA Signature Generation

```

1 int ecdsa_sign(ssize_t curve_id, const nn_t *priv,
2 const uint8_t *msg, size_t msglen,
3 ecdsa_sig_t *sig) {
4     ec_curve_shortw_t C;
5     get_curve_shortw(&C, (int)curve_id);
6     uint8_t hash[32]; sha256(msg, msglen, hash);
7     nn_t e; ecdsa_hash_to_int(&e, hash, &C.n);
8     nn_t k, k_inv, tmp; affine_point_t Rpt, G = {C.Gx, C.Gy, 0};
9     do {
10         do { nn_rand(&k, &C.n); } while (...);
11         ec_shortw_mul(&Rpt, &G, &k, &C);
12         nn_mod(&sig->r, &Rpt.x, &C.n);
13         if (nn_is_zero(&sig->r)) continue;
14         nn_mul(&tmp, priv, &sig->r);
15         nn_add(&tmp, &tmp, &e);
16         nn_mod(&tmp, &tmp, &C.n);
17         nn_mod_inv(&k_inv, &k, &C.n);
18         nn_mod_mul(&sig->s, &k_inv, &tmp, &C.n);
19     } while (nn_is_zero(&sig->s));
20     return 0;
21 }

```

4.6 ECDSA Signature Verification

```

1 int ecdsa_verify(ssize_t curve_id,
2 const affine_point_t *pub,

```

```

3  const uint8_t *msg, size_t msglen,
4  const ecdsa_sig_t *sig) {
5      ec_curve_shortw_t C; get_curve_shortw(&C, (int)curve_id);
6      if (invalid_range(sig->r, sig->s, &C.n)) return 0;
7      uint8_t hash[32]; sha256(msg, msglen, hash);
8      nn_t e; ecdsa_hash_to_int(&e, hash, &C.n);
9      nn_t w; nn_mod_inv(&w, &sig->s, &C.n);
10     nn_t u1, u2; nn_mod_mul(&u1, &e, &w, &C.n); nn_mod_mul(&u2, &sig->r, &w, &C.n)
11         ;
12     affine_point_t G={C.Gx, C.Gy, 0}, u1G, u2Q, Rpt;
13     ec_shortw_mul(&u1G, &G, &u1, &C);
14     ec_shortw_mul(&u2Q, pub, &u2, &C);
15     ec_shortw_add(&Rpt, &u1G, &u2Q, &C);
16     if (Rpt.is_inf) return 0;
17     nn_t v; nn_mod(&v, &Rpt.x, &C.n);
18     return (nn_cmp(&v, &sig->r)==0);
19 }

```

5 Testing and Validation

5.1 Self-Test Vectors

Discuss test harness in `src/tests/ec_self_tests.c` using known signatures.

5.2 Randomized and Interoperability Tests

Describe cross-verification with OpenSSL, random message tests, etc.

6 Security Considerations

Discuss constant-time, public-key validation, deterministic k (RFC 6979), side-channels.

7 Conclusion

Summarize mapping fidelity, correctness, compliance, and recommended improvements.

References

- FIPS 186-5: Digital Signature Standard (DSS).
- SEC 2: Recommended Elliptic Curve Domain Parameters.
- NIST P-256 specification.
- libecc source repository (commit XYZ).