

EasyCrypt Library in Jasmin

v 1.0

Ji, Yong-hyeon

(`hacker3740@kookmin.ac.kr`)

KMU

Department of Information Security, Cryptology, and Mathematics

College of Science and Technology


Kookmin University



CSE CRYPTO & SECURITY
ENGINEERING Lab
암호 및 보안 공학 연구실

January 3, 2025

File Structure



Copyright

© 2024 Crypto and Security Engineering Lab All rights reserved.

This document and its content are the intellectual property of “Ji, Yong-hyeon”. No part of this document may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of the author, except in the case of brief quotations embodied in critical reviews and certain other noncommercial uses permitted by copyright law. For permission requests, write to the author at the e-mail.

Changelog

| | | |
|------|------------|------------------|
| v1.0 | 2025-01-03 | Initial release: |
|------|------------|------------------|

Contents

| | | |
|----------|------------------|----------|
| 1 | JUtils | 2 |
| 2 | JArray | 5 |
| A | Algebra | 6 |
| A.1 | IntDiv | 6 |

1 JUtils

```
require import AllCore IntDiv List Bool StdOrder.
import IntOrder.
```

```
https://github.com/EasyCrypt/easycrypt
easycrypt/theories/core/AllCore.ec
easycrypt/theories/core/Bool.ec
easycrypt/theories/algebra/IntDiv.ec
easycrypt/theories/algebra/StdOrder.ec
easycrypt/theories/datatypes/List.ec
```

LEMMA: modz_comp

```
lemma modz_cmp m d : 0 < d => 0 <= m %% d < d.
proof. smt (edivzP). qed.
```

Statement. For two integers m and $d > 0$, the remainder of m divided by d satisfies:

$$0 \leq m \bmod d < d.$$

Analysis. This property follows directly from the division algorithm:

$$m = q \cdot d + r, \quad 0 \leq r < d$$

where $q = \lfloor m/d \rfloor$ and $r = m \bmod d$.

Proof Tactics. SMT solver with the pre-proved property edivzP (in IntDiv).

LEMMA: `divz_cmp`

```
lemma divz_cmp d i n : 0 < d => 0 <= i < n * d => 0 <= i % d < n.
```

```
proof.
```

```
  by move=> hd [hi1 hi2]; rewrite divz_ge0 // hi1 /= ltz_divLR.
```

```
qed.
```

Statement. For integers d, i, n where $d > 0$ and $0 \leq i < n \cdot d$, the integer division satisfies

$$0 \leq \frac{i}{d} < n.$$

Analysis. TBA

Proof Tactics. TBA

LEMMA: `mulz_cmp_r`

```
lemma mulz_cmp_r i m r : 0 < m => 0 <= i < r => 0 <= i * m < r * m.
```

```
proof.
```

```
  move=> h0m [h0i hir]; rewrite IntOrder.divr_ge0 //:=; 1: by apply ltzW.
```

```
  by rewrite IntOrder.ltr_pmul2r.
```

```
qed.
```

Statement. TBA

Analysis. TBA

Proof Tactics. TBA

LEMMA: `cmpW`

```
lemma cmpW i d : 0 <= i < d => 0 <= i <= d.
```

```
proof. by move=> [h1 h2]; split => // ?; apply ltzW. qed.
```

Statement. TBA

Analysis. TBA

Proof Tactics. TBA

LEMMA: `le_modz`

```

lemma le_modz m d : 0 <= m => m %% d <= m.
proof.
  move=> hm.
  have [ ->| [] hd]: d = 0  $\vee$  d < 0  $\vee$  0 < d by smt().
  + by rewrite modz0.
  + by rewrite -modzN {2}(divz_eq m (-d)); smt (divz_ge0).
  by rewrite {2}(divz_eq m d); smt (divz_ge0).
qed.

```

Statement. TBA

Analysis. TBA

Proof Tactics. TBA

2 JArray

References

A Algebra

A.1 IntDiv

```

op euclidef (m d : int) (qr : int * int) =
  m = qr.`1 * d + qr.`2
  /\ (d <> 0 => 0 <= qr.`2 < `|d|).

op edivn (m d : int) =
  if (d < 0 /\ m < 0) then (0, 0) else
    if d = 0 then (0, m) else choiceb (euclidef m d) (0, 0)
axiomatized by edivn_def.

op edivz (m d : int) =
  let (q, r) =
    if 0 <= m then edivn m `|d| else
      let (q, r) = edivn (-(m+1)) `|d| in
        (- (q + 1), `|d| - 1 - r)
    in (signz d * q, r)
axiomatized by edivz_def.

abbrev (%) (m d : int) = (edivz m d).`1.
abbrev (%) (m d : int) = (edivz m d).`2.

```

```

lemma edivzP (m d : int) :
  m = (m %/ d) * d + (m %% d) /\ (d <> 0 => 0 <= m %% d < `|d|).
proof. by case: (edivzP_r m d). qed.

```
