Orientation to Post-Quantum Cryptographic Hard Problems

Your Name

Your Institution / Research Group

March 9, 2026

Outline

1. Motivation
2. What Is a Hard Problem?
3. Main Families of PQC Hard Problems
4. Lattice-Based Hard Problems
5. Code-Based Hard Problems
6. Multivariate and Hash-Based Problems
7. Security Perspective
8. From Hard Problems to Schemes
9. Research Orientation
10. Conclusion

Why Post-Quantum Cryptography?

- Classical public-key cryptography relies heavily on problems such as integer factorization and discrete logarithms.
- Large-scale quantum computers would threaten these assumptions through algorithms such as Shor's algorithm.
- Post-quantum cryptography (PQC) seeks cryptographic constructions secure against both classical and quantum adversaries.
- The central question is therefore:

Core Question

Which mathematical problems remain computationally intractable even in the presence of quantum computation?

Role of Hard Problems in Cryptography

A cryptosystem is only as strong as the computational assumption on which it is built.

In the post-quantum setting, hard problems serve as:

- the **foundation of security proofs**,
- the **source of asymptotic and concrete hardness**,
- the **bridge** between abstract mathematics and practical protocol design.

Thus, understanding PQC requires understanding its underlying hard problems.

Definition of a Hard Problem

Informally, a computational problem is considered *hard* if no efficient algorithm is known for solving it on average or in the worst case under relevant parameter choices.

In cryptography, one typically asks:

- Is the problem difficult for **classical** algorithms?
- Is the problem difficult for **quantum** algorithms?
- Is the hardness supported by **reductions**, **evidence**, or **long-standing study**?
- Does the problem admit **efficient implementation** in real systems?

Desirable Features of a Cryptographic Assumption

A useful cryptographic hardness assumption should ideally have:

1. **Strong evidence of intractability**,
2. **Resistance to known classical and quantum attacks**,
3. **Efficient parameterization**,
4. **Reduction-based security arguments**,
5. **Robustness under implementation constraints**.

In practice, there is often a trade-off between theoretical elegance and implementation efficiency.

Major Families of Post-Quantum Hard Problems

The principal mathematical families include:

- **Lattice-based problems**
  - Shortest Vector Problem (SVP)
  - Closest Vector Problem (CVP)
  - Learning With Errors (LWE)
  - Module-LWE / Ring-LWE
- **Code-based problems**
  - Syndrome Decoding
  - General decoding problems for linear codes
- **Multivariate problems**
  - Solving systems of multivariate polynomial equations over finite fields
- **Hash-based assumptions**
  - Preimage resistance, second-preimage resistance, collision resistance
- **Isogeny-based problems** (historically important, though currently more fragile in practice)

Lattices: Geometric Background

A lattice $\Lambda \subset \mathbb{R}^n$ is the set of all integer linear combinations of basis vectors:

$$\Lambda = \left\{ \sum_{i=1}^{m} z_i \boldsymbol{b}_i : z_i \in \mathbb{Z} \right\}.$$

Fundamental computational questions include:

- finding a short nonzero vector,
- finding a lattice vector close to a target point,
- solving noisy linear relations derived from lattice structure.

Shortest Vector Problem (SVP)

SVP

Given a lattice basis for Λ, find a nonzero vector $\boldsymbol{v} \in \Lambda$ minimizing $\|\boldsymbol{v}\|$.

Why it matters:

- It is a canonical worst-case lattice problem.
- Approximate variants of SVP are central in complexity theory and cryptography.
- Many security reductions relate average-case cryptographic assumptions to worst-case lattice problems.

Learning With Errors (LWE)

LWE Problem

Given samples of the form

$$(\boldsymbol{a}_i, b_i = \langle \boldsymbol{a}_i, \boldsymbol{s} \rangle + e_i \bmod q),$$

recover the secret $\boldsymbol{s}$ or distinguish such samples from uniform.

Here:

- $\boldsymbol{a}_i \in \mathbb{Z}_q^n$ is public,
- $\boldsymbol{s} \in \mathbb{Z}_q^n$ is secret,
- e_i is a small error term.

LWE is one of the most important assumptions in modern post-quantum cryptography.

Why LWE Is Foundational

LWE is especially attractive because:

- it admits strong reduction-based evidence from worst-case lattice problems,
- it supports encryption, signatures, key exchange, FHE, IBE, and more,
- it has natural structured variants such as Ring-LWE and Module-LWE.

Many standardized PQC schemes are based on this family of assumptions.

Code-Based Assumptions

Code-based cryptography is built on the difficulty of decoding a random linear code.

Syndrome Decoding Problem

Given a parity-check matrix H, a syndrome $\boldsymbol{s}$, and a weight bound w, find an error vector $\boldsymbol{e}$ such that

$$H\boldsymbol{e}^T = \boldsymbol{s}^T$$

and $\mathrm{wt}(\boldsymbol{e}) \leq w$.

This problem is believed to be hard even for quantum adversaries, though parameters must be chosen carefully.

Strengths and Limitations of Code-Based Cryptography

Strengths

- Long history of cryptanalytic study,
- Conservative security posture,
- Fast low-level operations in some settings.

Limitations

- Large public keys in many constructions,
- More limited flexibility compared with lattice-based designs for advanced primitives.

Multivariate Polynomial Problems

Multivariate cryptography relies on the difficulty of solving systems of nonlinear polynomial equations over finite fields.

General form:

$$f_1(x_1, \ldots, x_n) = \cdots = f_m(x_1, \ldots, x_n) = 0.$$

These problems are attractive because:

- evaluation can be very efficient,
- signing can be fast in carefully designed systems.

However, the design space is delicate and vulnerable to algebraic attacks if structure is not controlled.

Hash-Based Assumptions

Hash-based cryptography relies on standard assumptions such as:

- preimage resistance,
- second-preimage resistance,
- collision resistance.

Hash-based signatures are among the most conservative post-quantum constructions because their security reduces to the security of the underlying hash function.

Their main trade-offs often concern:

- signature size,
- state management (for stateful variants),
- performance in constrained environments.

What Makes a PQC Problem Credible?

The credibility of a post-quantum hardness assumption depends on:

- **Cryptanalytic maturity**: how long and how deeply the problem has been studied;
- **Reduction theory**: whether security can be related to better-understood problems;
- **Quantum attack landscape**: whether known quantum algorithms provide substantial speedups;
- **Parameter discipline**: whether implementations preserve the intended hardness level.

Classical vs. Quantum Attack Models

In practice, one evaluates hard problems under both:

1. **Classical attacks**
   - combinatorial methods,
   - algebraic attacks,
   - lattice reduction,
   - information-set decoding,
   - Gröbner-basis techniques.
2. **Quantum attacks**
   - Shor-type exponential attacks where applicable,
   - Grover-type quadratic speedups,
   - quantum adaptations of classical search or algebraic methods.

From Assumptions to Cryptographic Constructions

A hard problem becomes practically relevant only when it supports efficient schemes:

$$\textbf{Hard Problem} \longrightarrow \textbf{Assumption} \longrightarrow \textbf{Construction} \longrightarrow \textbf{Implementation}$$

Examples:

- LWE / Module-LWE $\rightarrow$ key encapsulation mechanisms,
- lattice trapdoors $\rightarrow$ digital signatures,
- hash assumptions $\rightarrow$ stateless and stateful signatures,
- decoding problems $\rightarrow$ code-based encryption/KEMs.

Practical Evaluation Criteria

In real deployments, we compare candidate assumptions and schemes by:

- claimed security level,
- public key and ciphertext/signature size,
- runtime and memory cost,
- implementation simplicity,
- side-channel resilience,
- confidence in long-term hardness.

How to Study PQC Hard Problems

A productive orientation path includes:

1. Learn the precise mathematical formulation of each problem.
2. Understand known classical and quantum algorithms against it.
3. Study reduction results and hardness evidence.
4. Examine how the assumption is instantiated in concrete schemes.
5. Track implementation and parameter-selection issues.

Suggested Research Questions

Possible guiding questions for a new student or researcher:

- What type of hardness evidence is available: worst-case, average-case, heuristic, or empirical?
- How does algebraic structure improve efficiency, and what security risk does it introduce?
- Which attacks dominate the concrete security estimates?
- How should one compare assumptions across different PQC families?
- What are the open problems in reduction theory, parameter setting, and implementation security?

Conclusion

- Post-quantum cryptography is fundamentally an exercise in identifying and exploiting robust hard problems.
- Lattice, code-based, multivariate, and hash-based assumptions provide distinct trade-offs.
- The study of PQC hard problems requires both mathematical rigor and cryptographic realism.
- A clear understanding of these assumptions is essential for evaluating present and future post-quantum schemes.

Thank You

Thank you for your attention.

Questions and discussion are welcome.