

# Free Software and Version Control 101

A introductory course on FOSS, git, curl and web integrations

J. Rodrigues   F. Carvalho

HackerSchool

## Section 1

### Version control?

# What is version control?

Version control is the practice of managing and documenting *data* (code, schematics, etc.) iterations.

It is particularly important in our context of Free and Open Source software, as a careful documentation of alterations between versions and the ability to inspect older or deprecated sources can make issue resolution and feature integration much more agile.

git?

Git is a version control software created by Linus Torvalds (which also created the Linux Kernel). Its free software under the GPL v2.0.

Git allows cloning, pulling, pushing, etc. of data stored in git instances.

It has happened to all of us!



proj.py  
20.4 kB



proj2.py  
20.4 kB



proj3.py  
20.4 kB



projectFI  
NAL.py  
20.4 kB



projectFI  
NAL\_  
ULTIMO.  
py  
20.4 kB

Time to ditch this...

# For something waaaay better

\* `commit eebc2e011fa88bfae93e8105e665fa5873499569` (`HEAD -> master`, `origin/master`)

Author: Francisco Carvalho <franciscojcarvalho@tecnico.ulisboa.pt>

Date: Thu Oct 13 16:42:39 2022 +0100

Database changes (to be implemented in backend)

\* `commit bf2162b4080243bb4458f916319a53ebfa3d9253`

Author: Francisco Carvalho <franciscojcarvalho@tecnico.ulisboa.pt>

Date: Sat Oct 8 19:36:46 2022 +0100

Login system bypass as it's not needed. LF endings

\* `commit bf5c4c51b9fba1ffdc18b44abf24491d7a1bf6c4`

Author: Francisco Carvalho <franciscojcarvalho@tecnico.ulisboa.pt>

Date: Fri Oct 7 14:32:27 2022 +0100

.desktop file and autorun script

\* `commit 0b9bfc255efc9fc897189b46885acc7d51251e2c`

Author: Francisco Carvalho <franciscojcarvalho@tecnico.ulisboa.pt>

Date: Fri Sep 30 21:01:59 2022 +0100

Code cleanup

\* `commit 764c31a6c26b3ef19e8921895cbeb50cc271920f`

Author: Francisco Carvalho <franciscojcarvalho@tecnico.ulisboa.pt>

Date: Fri Sep 30 20:51:04 2022 +0100

Bug: week number stuck at 1

• **schema.sql:9:** CREATE TABLE IF NOT EXISTS etcs\_users(

```

9      course varchar,
10     primary key (ist_id)
11 );

```

```

12 CREATE TABLE IF NOT EXISTS etcs_subjects(
13     subject_id numeric,
14     term varchar,

```

• **schema.sql:37:** CREATE TABLE IF NOT EXISTS etcs\_subjects(

```

21     subject_ta numeric,
22     subject_t numeric,
23     subject_period numeric,

```

```

24     primary key (subject_id)
25 );
26 CREATE TABLE IF NOT EXISTS etcs_enrolled_in(

```

• **schema.sql:71:** CREATE TABLE IF NOT EXISTS etcs\_academic\_terms(

```

-

```

```

9      course varchar,
10     primary key (ist_id)
11 );
12
13 CREATE TABLE IF NOT EXISTS etcs_work(
14     identifier numeric,
15     name varchar,
16     primary key (identifier)
17 );
18
19 CREATE TABLE IF NOT EXISTS etcs_extra_activity(
20     identifier numeric,
21     description varchar,
22     type numeric,
23     foreign key (identifier)
24         REFERENCES etcs_work(identifier),
25     primary key (identifier)
26 );
27
28 CREATE TABLE IF NOT EXISTS etcs_subjects(
29     subject_id numeric,
30     term varchar,

```

```

37     subject_ta numeric,
38     subject_t numeric,
39     subject_period numeric,
40     foreign key (subject_id)
41         REFERENCES etcs_work(identifier),
42     primary key (subject_id)
43 );
44 CREATE TABLE IF NOT EXISTS etcs_enrolled_in(

```

# curl?

Curl (short for client-url), is the command line tool that makes use of libcurl, a data transfer library that supports a array of network protocols such as FTP, HTTP, etc.

We will use curl to communicate with the GitHub API in the next sections.

Curl and libcurl are FOSS licensed under the curl license, based on the MIT License, and compatible with the GPL v3.0

## Section 2

Let's Start!



# Setting up your git/GitHub environment

- Create a GitHub account (using your institutional e-mail is often valuable).
- Get the git and curl packages.
- Generate a OAuth key, ssh key, or any mean of remote authentication.
- Save it somewhere safe (encrypt it with gpg, or use a password manager (for example: keepass)).

Let's waddle back to the terminal

```
git config --global user.name "@user.name"
```

```
git config --global user.email @user.email
```

# Setting up a GitHub repository with curl and git

Let's start with creating a remote and local repository (note: this can also be done in github's website)

```
curl -u @user https://api.github.com/user/repos -d \
'{"name":"@string","private":false}'
```

```
mkdir @string && cd @string
```

Now we can initialize our local repo and link it to the remote one

```
git init
```

```
git remote add origin https://github.com/@name/@string.git
```

## Section 3

### Your first commit!

# Git Status

This command allows you to view the state of your project (repo)

```
francisco@archboxSigma:~/repos/studyTracker$ git status
On branch master
Your branch is up to date with 'origin/master'.

Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   main.py
        modified:   templates/dash.html

Untracked files:
  (use "git add <file>..." to include in what will be committed)
        README.md
        __pycache__/
        app/
        config.ini.old
        diagramaEA.png
        etcs_weeks.py
        etcs.db
        populate.sql
        static/favicon.svg
        templates/timer.html
        test.sql

no changes added to commit (use "git add" and/or "git commit -a")
```

# Add

- When we want the git log changes made to a file `git add <file_path>`
- When the file hasn't ever been tracked `add` tells git to start to
- This command only selects the files/modifications, it **does not** commit

```
francisco@archboxSigma:~/repos/studyTracker$ git add main.py README.md
francisco@archboxSigma:~/repos/studyTracker$ git status
On branch master
Your branch is up to date with 'origin/master'.

Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
    new file:   README.md
    modified:   main.py

Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
    modified:   templates/dash.html
```

Figure 2: Git Add

# Commit

- To commit (record the selected changes to the history) we use the command `git commit -m "commit message"`

```
francisco@archboxSigma:~/repos/studyTracker$ git add main.py
francisco@archboxSigma:~/repos/studyTracker$ git commit -m "minor comment"
[master a6b509e] minor comment
 1 file changed, 2 insertions(+)
francisco@archboxSigma:~/repos/studyTracker$ █
```

Figure 3: git commit

# Push

- You can push your history to a remote repo using the command `git push <name_of_remote_repo>`
  - Usually when using Github this remote is called **origin**
- You can even have multiple remotes!
  - to add one use `git remote add <name> <url>`, as seen in the curl part of this presentation

```
francisco@archboxSigma:~/repos/studyTracker$ git push origin
Enumerating objects: 5, done.
Counting objects: 100% (5/5), done.
Delta compression using up to 8 threads
Compressing objects: 100% (3/3), done.
Writing objects: 100% (3/3), 367 bytes | 367.00 KiB/s, done.
Total 3 (delta 2), reused 0 (delta 0), pack-reused 0
remote: Resolving deltas: 100% (2/2), completed with 2 local objects.
remote: This repository moved. Please use the new location:
remote:   https://github.com/SrFrancisco/tracker.git
To https://github.com/SrFrancisco/etcs.git
eebc2e0..a6b509e  master -> master
```

Figure 4: git push

# Frontends (Vscode)



## Section 4

Working together!

# Working together!

## Cloning

Cloning allows you to download a git remote repository

```
git clone https://github.com/HackerSchool/inar.git
```

## Pulling

Oposite of push, allows you to download remote changes to your existing local repo

```
git pull origin
```

# Repositories and actions




Figure 5: Actions and interactions between repositories

# A practical example: hackerschool.io





Figure 6: Git/GitHub flow of the hackerschool.io repository

# Forking

Note: This is a feature of Github and not git itself

- Forking is an important collaboration tool as it allows you to make your own private copy of an exciting repository
- This means you can work freely, without pushing “trash” to the main repo
  - You can even start your own version of the project!
- Once you're ready to merge your changes into the main repo you can open a **pull request**
  - This is one way of contributing code to a public repo if you aren't a contributor (=have write access)
- In medium-small projects, branching may be enough



# Pull Requests

SrFrancisco / **recrutamento-22-23-s1** Public  
forked from HackerSchool/recrutamento-22-23-s1

< Code Pull requests Actions Projects Wiki Security Insights Settings

main 1 branch 0 tags

This branch is up to date with HackerSchool/recrutamento-22-23-s1:main.

Contribute Sync fork

**NuclearMonk** Added python project c92085 1 hour ago 2 commits

File	Commit Message	Time Ago
Projeto_Python.md	Added python project	1 hour ago
README.md	Started directories	4 days ago

README.md

**Desktop Programming (OOP)**

About  
1st 22/23 call recruitment repository  
Readme  
0 stars  
0 watching  
1 fork

Releases  
No releases published  
[Create a new release](#)

When we want to merge with the original repo we open a pull request

This branch is 1 commit ahead of HackerSchool:main.

Contribute Sync fork

**SrFrancisco** Update README.md 3 commits

File	Commit Message	Time Ago
Projeto_Python.md	Added python project	1 hour ago
README.md	Update README	20 seconds ago

README.md

**This branch is 1 commit ahead of HackerSchool:main.**  
Open a pull request to contribute your changes upstream.

[Open pull request](#)

## Section 5

### Tying our work with freedom

# On FOSS and CC

The first written document that described FOSS as a trend among hackers, programmers, engineers, etc. was the GNU Manifesto. This file also gave the philosophical foundations for the Free Software Foundation Network, and FOSS worldwide.

In the context of HackerSchool FOSS is a core principle. Initiated in the administration of 22-23, HackerSchool has embraced free alternatives such as *GNU/Linux distros*, *FreeCAD*, *Jitsi*, *Signal*, allowing hackers to walk a path that is flexible, secure, and overall hacker-y.

Since we benefit from this communal effort it is only fair that we also contribute to the greater good, therefore all HackerSchool code and documents are non-proprietary.



# The two software architectures

- **The Cathedral**

We can apply this architectural decision to both:

- **Free Software**

The source code is centralized in an organizational environment, however it is released with any main binary. You will rarely look to the code in development.

- **Proprietary Software**

The source code is never released, it is kept confined within the Corporations walls. The binary is spewed out of it, but you will have to reverse it to understand what it does!

# The two software architectures

- **The Bazaar**

The Bazaar is characteristic of free software.

In a Bazaar architecture the source code is visible at all times, being normally communal projects, made of differently written modules. Its all nodes that compose a de-centralized tree!

This architecture as the advantage of going according to Linus's Law:

*“given enough eyeballs, all bugs are shallow”*

# Licenses

A	B	C	D	E	F
	Public Domain	Permissive	Copyleft	Non-Commercial	Proprietary
Is the source code available?	Yes	Yes	Yes	Yes	No
Copyright and authorship claim	No	Yes	Yes	Yes	Yes
Can I copy it	Yes	Yes	Yes	Yes	Yes
Can I distribute it?	Yes	Yes (under the same license)	Yes (under the same license)	Yes (under the same license)	Yes
Can I modify it?	Yes	Yes	Yes	Yes	Yes
Can I sell it? (modified or unmodified)	Yes	Yes	Yes	No	Yes
Can I sublicense the modified code?	Yes	Yes	No	Yes	Yes
Software License Example(s)	The Unlicense CC0	Apache License BSD License MIT License	GNU Public License (GPL) Affero GPL	Aladdin Free Public License	Proprietary License
Other Documents License Example(s)	CC0	CC-BY	CC-BY-SA	CC-BY-NC	Proprietary License
Software/media/file example	"Equilíbrios líquido-vapor de componentes da aguarrás para destilação multicomponente"	"Big Buck Bunny"	Linux Kernel GNU utils 99.9% of the code I make	GhostScript	Microsoft Bimbows

Figure 7: Licenses and properties