



Vikings

Mon, 17 Nov 2025 05:53:58 UTC

TABLE OF CONTENTS

- Vulnerabilities by Host
 - 192.168.1.8
- Compliance 'FAILED'
- Compliance 'SKIPPED'
- Compliance 'PASSED'
- Compliance 'INFO', 'WARNING', 'ERROR'
- Remediations
 - Suggested Remediations

Vulnerabilities by Host

Collapse All | Expand All

192.168.1.8



Scan Information

Start time: Mon Nov 17 05:23:36 2025
End time: Mon Nov 17 05:53:58 2025

Host Information

IP: 192.168.1.8
MAC Address: 08:00:27:39:05:83
OS: Linux Kernel 4.15 on Ubuntu 18.04 (bionic)

Vulnerabilities

201456 - Canonical Ubuntu Linux SEoL (18.04.x) -

Synopsis

An unsupported version of Canonical Ubuntu Linux is installed on the remote host.

Description

According to its version, Canonical Ubuntu Linux is 18.04.x. It is, therefore, no longer maintained by its vendor or provider.

Lack of support implies that no new security patches for the product will be released by the vendor. As a result, it may contain security vulnerabilities.

See Also

<https://ubuntu.com/blog/18-04-end-of-standard-support>

Solution

Upgrade to a version of Canonical Ubuntu Linux that is currently supported.

Risk Factor

Critical

CVSS v3.0 Base Score

10.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

Plugin Information

Published: 2024/07/03, Modified: 2025/03/26

Plugin Output

tcp/22/ssh

OS : Ubuntu Linux 18.04
Security End of Life : May 31, 2023
Time since Security End of Life (Est.) : >= 2 years

10704 - Apache Multiviews Arbitrary Directory Listing

Synopsis

The remote web server is affected by an information disclosure vulnerability.

Description

The Apache web server running on the remote host is affected by an information disclosure vulnerability. An unauthenticated, remote attacker can exploit this, by sending a crafted request, to display a listing of a remote directory, even if a valid index file exists in the directory.

For Apache web server later than 1.3.22, review listing directory configuration to avoid disclosing sensitive information

See Also

<http://www.nessus.org/u?f39e976b>
<http://www.nessus.org/u?a96611bc>
<http://www.nessus.org/u?c1c382bc>

Solution

Upgrade to Apache version 1.3.22 or later. Alternatively, as a workaround, disable Multiviews.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v3.0 Temporal Score

4.8 (CVSS:3.0/E:P/RL:O/RC:C)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.9 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	3009
CVE	CVE-2001-0731
XREF	OWASP:OWASP-CM-004
XREF	EDB-ID:21002

Plugin Information

Published: 2016/02/16, Modified: 2020/10/21

Plugin Output

tcp/80/www

```
Nessus was able to exploit the issue using the following request :

http://192.168.1.8/?M=A

This produced the following truncated output (limited to 10 lines) :
----- snip -----
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 3.2 Final//EN">
<html>
<head>
<title>Index of /</title>
</head>
<body>
<h1>Index of /</h1>
<table>
<tr><th valign="top"></th><th><a href="?C=N;O=D">Name</a></th><th><a href="?C=M;O=A">Last
modified</a></th><th><a href="?C=S;O=A">Size</a></th><th><a href="?C=D;O=A">Description</a></th></tr>
<tr><th colspan="5"><hr></th></tr>
[...]
```

187315 - SSH Terrapin Prefix Truncation Weakness (CVE-2023-48795) -

Synopsis

The remote SSH server is vulnerable to a mitm prefix truncation attack.

Description

The remote SSH server is vulnerable to a man-in-the-middle prefix truncation weakness known as Terrapin. This can allow a remote, man-in-the-middle attacker to bypass integrity checks and downgrade the connection's security.

Note that this plugin only checks for remote SSH servers that support either ChaCha20-Poly1305 or CBC with Encrypt-then-MAC and do not support the strict key exchange countermeasures. It does not check for vulnerable software versions.

See Also

<https://terrapin-attack.com/>

Solution

Contact the vendor for an update with the strict key exchange countermeasures or disable the affected algorithms.

Risk Factor

Medium

CVSS v3.0 Base Score

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:N/I:H/A:N)

CVSS v3.0 Temporal Score

5.3 (CVSS:3.0/E:P/RL:O/RC:C)

CVSS v2.0 Base Score

5.4 (CVSS2#AV:N/AC:H/Au:N/C:N/I:C/A:N)

CVSS v2.0 Temporal Score

4.2 (CVSS2#E:POC/RL:OF/RC:C)

References

CVE [CVE-2023-48795](#)

Plugin Information

Published: 2023/12/27, Modified: 2024/01/29

Plugin Output

tcp/22/ssh

Supports following ChaCha20-Poly1305 Client to Server algorithm : chacha20-poly1305@openssh.com
Supports following Encrypt-then-MAC Client to Server algorithm : umac-64-etm@openssh.com
Supports following Encrypt-then-MAC Client to Server algorithm : umac-128-etm@openssh.com
Supports following Encrypt-then-MAC Client to Server algorithm : hmac-sha2-256-etm@openssh.com
Supports following Encrypt-then-MAC Client to Server algorithm : hmac-sha2-512-etm@openssh.com
Supports following Encrypt-then-MAC Client to Server algorithm : hmac-sha1-etm@openssh.com
Supports following ChaCha20-Poly1305 Server to Client algorithm : chacha20-poly1305@openssh.com
Supports following Encrypt-then-MAC Server to Client algorithm : umac-64-etm@openssh.com
Supports following Encrypt-then-MAC Server to Client algorithm : umac-128-etm@openssh.com
Supports following Encrypt-then-MAC Server to Client algorithm : hmac-sha2-256-etm@openssh.com
Supports following Encrypt-then-MAC Server to Client algorithm : hmac-sha2-512-etm@openssh.com
Supports following Encrypt-then-MAC Server to Client algorithm : hmac-sha1-etm@openssh.com

48204 - Apache HTTP Server Version

Synopsis

It is possible to obtain the version number of the remote Apache HTTP server.

Description

The remote host is running the Apache HTTP Server, an open source web server. It was possible to read the version number from the banner.

See Also

<https://httpd.apache.org/>

Solution

n/a

Risk Factor

None

References

XREF	IAVT:0001-T-0030
XREF	IAVT:0001-T-0530

Plugin Information

Published: 2010/07/30, Modified: 2023/08/17

Plugin Output

tcp/80/www

URL : http://192.168.1.8/
Version : 2.4.99
Source : Server: Apache/2.4.29 (Ubuntu)
backported : 1
os : ConvertedUbuntu

39520 - Backported Security Patch Detection (SSH)

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote SSH server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2015/07/07

Plugin Output

tcp/22/ssh

Give Nessus credentials to perform local checks.

39521 - Backported Security Patch Detection (WWW)**Synopsis**

Security patches are backported.

Description

Security patches may have been 'backported' to the remote HTTP server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2015/07/07

Plugin Output

tcp/80/www

Give Nessus credentials to perform local checks.

45590 - Common Platform Enumeration (CPE)**Synopsis**

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>
<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2025/07/14

Plugin Output

tcp/0

Following application CPE's matched on the remote system :

cpe:/a:apache:http_server:2.4.29 -> Apache Software Foundation Apache HTTP Server
cpe:/a:apache:http_server:2.4.99 -> Apache Software Foundation Apache HTTP Server
cpe:/a:openbsd:openssh:7.6 -> OpenBSD OpenSSH
cpe:/a:openbsd:openssh:7.6p1 -> OpenBSD OpenSSH

54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

Remote device type : general-purpose
Confidence level : 95

35716 - Ethernet Card Manufacturer Detection

Synopsis

The manufacturer can be identified from the Ethernet OUI.

Description

Each ethernet MAC address starts with a 24-bit Organizationally Unique Identifier (OUI). These OUIs are registered by IEEE.

See Also

<https://standards.ieee.org/faqs/regauth.html>
<http://www.nessus.org/u?794673b4>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/02/19, Modified: 2020/05/13

Plugin Output

tcp/0

The following card manufacturers were identified :

08:00:27:39:05:83 : PCS Systemtechnik GmbH

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

The following is a consolidated list of detected MAC addresses:
- 08:00:27:39:05:83

43111 - HTTP Methods Allowed (per directory)

Synopsis

This plugin determines which HTTP methods are allowed on various CGI directories.

Description

By calling the OPTIONS method, it is possible to determine which HTTP methods are allowed on each directory.

The following HTTP methods are considered insecure:
PUT, DELETE, CONNECT, TRACE, HEAD

Many frameworks and languages treat 'HEAD' as a 'GET' request, albeit one without any body in the response. If a security constraint was set on 'GET' requests such that only 'authenticatedUsers' could access GET requests for a particular servlet or resource, it would be bypassed for the 'HEAD' version. This allowed unauthorized blind submission of any privileged GET request.

As this list may be incomplete, the plugin also tests - if 'Thorough tests' are enabled or 'Enable web applications tests' is set to 'yes' in the scan policy - various known HTTP methods on each directory and considers them as unsupported if it receives a response code of 400, 403, 405, or 501.

Note that the plugin output is only informational and does not necessarily indicate the presence of any security vulnerabilities.

See Also

<http://www.nessus.org/u?d9c03a9a>
<http://www.nessus.org/u?b019cbdb>
[https://www.owasp.org/index.php/Test_HTTP_Methods_\(OTG-CONFIG-006\)](https://www.owasp.org/index.php/Test_HTTP_Methods_(OTG-CONFIG-006))

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/12/10, Modified: 2022/04/11

Plugin Output

tcp/80/www

Based on the response to an OPTIONS request :

- HTTP methods GET HEAD OPTIONS POST are allowed on :
/

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/80/www

The remote web server type is :
Apache/2.4.29 (Ubuntu)

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/80/www

Response Code : HTTP/1.1 200 OK

Protocol version : HTTP/1.1
HTTP/2 TLS Support: No
HTTP/2 Cleartext Support: No
SSL : no
Keep-Alive : yes
Options allowed : (Not implemented)
Headers :

Date: Mon, 17 Nov 2025 05:28:43 GMT
Server: Apache/2.4.29 (Ubuntu)
Vary: Accept-Encoding
Content-Length: 743
Keep-Alive: timeout=5, max=100
Connection: Keep-Alive
Content-Type: text/html; charset=UTF-8

Response Body :

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 3.2 Final//EN">
<html>
<head>
<title>Index of /</title>
</head>
<body>
<h1>Index of /</h1>
<table>
<tr><th valign="top"></th><th><a href="?C=N;O=D">Name</a></th><th><a href="?C=M;O=A">Last
modified</a></th><th><a href="?C=S;O=A">Size</a></th><th><a href="?C=D;O=A">Description</a></th></tr>
<tr><th colspan="5"><hr></th></tr>
<tr><td valign="top"></td><td><a href="site/">site/</a></td><td align="right">2020-10-29
21:07 </td><td align="right"> - </td><td>&nbsp;</td></tr>
<tr><th colspan="5"><hr></th></tr>
</table>
<address>Apache/2.4.29 (Ubuntu) Server at 192.168.1.8 Port 80</address>
</body></html>
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2025/06/25

Plugin Output

tcp/0

```
Information about this scan :

Nessus version : 10.9.3
Nessus build : 20023
Plugin feed version : 202508200628
Scanner edition used : Nessus

ERROR: Your plugins have not been updated since 2025/8/20
Performing a scan with an older plugin set will yield out-of-date results and
produce an incomplete audit. Please run nessus-update-plugins to get the
newest vulnerability checks from Nessus.org.

Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : Vikings
Scan policy used : Advanced Scan
Scanner IP : 192.168.1.15
Port scanner(s) : netstat
```

```
Port range : 65535
Ping RTT : 107.652 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialled checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 100
Max checks : 5
Recv timeout : 5
Backports : Detected
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2025/11/17 5:24 UTC
Scan duration : 1753 sec
Scan for malware : no
```

64582 - Netstat Connection Information

Synopsis

Nessus was able to parse the results of the 'netstat' command on the remote host.

Description

The remote host has listening ports or established connections that Nessus was able to extract from the results of the 'netstat' command.

Note: The output for this plugin can be very long, and is not shown by default. To display it, enable verbose reporting in scan settings.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/02/13, Modified: 2023/05/23

Plugin Output

tcp/0

14272 - Netstat Portscanner (SSH)

Synopsis

Remote open ports can be enumerated via SSH.

Description

Nessus was able to run 'netstat' on the remote host to enumerate the open ports. If 'netstat' is not available, the plugin will attempt to use 'ss'.

See the section 'plugins options' about configuring this plugin.

Note: This plugin will run on Windows (using netstat.exe) in the event that the target being scanned is localhost.

See Also

<https://en.wikipedia.org/wiki/Netstat>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2025/05/27

Plugin Output

tcp/22/ssh

Port 22/tcp was found to be open

14272 - Netstat Portscanner (SSH)

Synopsis

Remote open ports can be enumerated via SSH.

Description

Nessus was able to run 'netstat' on the remote host to enumerate the open ports. If 'netstat' is not available, the plugin will attempt to use 'ss'.

See the section 'plugins options' about configuring this plugin.

Note: This plugin will run on Windows (using netstat.exe) in the event that the target being scanned is localhost.

See Also

<https://en.wikipedia.org/wiki/Netstat>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2025/05/27

Plugin Output

udp/68

Port 68/udp was found to be open

14272 - Netstat Portscanner (SSH)

Synopsis

Remote open ports can be enumerated via SSH.

Description

Nessus was able to run 'netstat' on the remote host to enumerate the open ports. If 'netstat' is not available, the plugin will attempt to use 'ss'.

See the section 'plugins options' about configuring this plugin.

Note: This plugin will run on Windows (using netstat.exe) in the event that the target being scanned is localhost.

See Also

<https://en.wikipedia.org/wiki/Netstat>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2025/05/27

Plugin Output

tcp/80/www

Port 80/tcp was found to be open

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, “OS Identification”, the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

Following OS Fingerprints were found

Remote operating system : Ubuntu 18.04 Linux Kernel 4.15
Confidence level : 56
Method : MLSinFP
Type : unknown
Fingerprint : unknown

Remote operating system : Linux Kernel 4.15 on Ubuntu 18.04 (bionic)
Confidence level : 95
Method : SSH
Type : general-purpose
Fingerprint : SSH:SSH-2.0-OpenSSH_7.6p1 Ubuntu-4ubuntu0.5

Remote operating system : Cisco Catalyst 9200 Series Switches
Cisco Catalyst 9300 Series Switches
Cisco Catalyst IE9300 Rugged Series
Nutanix
Confidence level : 59
Method : SinFP
Type :
Fingerprint : SinFP:
P1:B10113:F0x12:W64240:00204ffff:M1460:
P2:B10113:F0x12:W65160:00204ffff0402080affffff4445414401030307:M1460:
P3:B00000:F0x00:W0:00:M0
P4:191303_7_p=22

Following fingerprints could not be used to determine OS :
HTTP:!:Server: Apache/2.4.29 (Ubuntu)

11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

tcp/0

Remote operating system : Linux Kernel 4.15 on Ubuntu 18.04 (bionic)
Confidence level : 95
Method : SSH

The remote host is running Linux Kernel 4.15 on Ubuntu 18.04 (bionic)

181418 - OpenSSH Detection

Synopsis

An OpenSSH-based SSH server was detected on the remote host.

Description

An OpenSSH-based SSH server was detected on the remote host.

See Also

<https://www.openssh.com/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/09/14, Modified: 2025/08/19

Plugin Output

tcp/22/ssh

Service : ssh
Version : 7.6p1
Banner : SSH-2.0-OpenSSH_7.6p1 Ubuntu-4ubuntu0.5

66334 - Patch Report

Synopsis

The remote host is missing several patches.

Description

The remote host is missing one or more security patches. This plugin lists the newest version of each patch to install to make sure the remote host is up-to-date.

Note: Because the 'Show missing patches that have been superseded' setting in your scan policy depends on this plugin, it will always run and cannot be disabled.

Solution

Install the patches listed below.

Risk Factor

None

Plugin Information

Published: 2013/07/08, Modified: 2025/08/12

Plugin Output

tcp/0

- . You need to take the following action :
- [SSH Terrapin Prefix Truncation Weakness (CVE-2023-48795) (187315)]
- + Action to take : Contact the vendor for an update with the strict key exchange countermeasures or disable the affected algorithms.

70657 - SSH Algorithms and Languages Supported

Synopsis

An SSH server is listening on this port.

Description

This script detects which algorithms and languages are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/10/28, Modified: 2025/01/20

Plugin Output

tcp/22/ssh

Nessus negotiated the following encryption algorithm(s) with the server :

Client to Server: aes256-ctr
Server to Client: aes256-ctr

The server supports the following options for compression_algorithms_server_to_client :

none
zlib@openssh.com

The server supports the following options for mac_algorithms_client_to_server :

hmac-sha1
hmac-sha1-etm@openssh.com
hmac-sha2-256
hmac-sha2-256-etm@openssh.com
hmac-sha2-512
hmac-sha2-512-etm@openssh.com
umac-128-etm@openssh.com
umac-128@openssh.com
umac-64-etm@openssh.com
umac-64@openssh.com

The server supports the following options for server_host_key_algorithms :

ecdsa-sha2-nistp256
rsa-sha2-256
rsa-sha2-512
ssh-ed25519
ssh-rsa

The server supports the following options for encryption_algorithms_client_to_server :

aes128-ctr
aes128-gcm@openssh.com
aes192-ctr
aes256-ctr
aes256-gcm@openssh.com
chacha20-poly1305@openssh.com

The server supports the following options for mac_algorithms_server_to_client :

hmac-sha1
hmac-sha1-etm@openssh.com
hmac-sha2-256
hmac-sha2-256-etm@openssh.com
hmac-sha2-512
hmac-sha2-512-etm@openssh.com
umac-128-etm@openssh.com
umac-128@openssh.com
umac-64-etm@openssh.com
umac-64@openssh.com

The server supports the following options for kex_algorithms :

curve25519-sha256
curve25519-sha256@libssh.org

```
diffie-hellman-group-exchange-sha256
diffie-hellman-group14-sha1
diffie-hellman-group14-sha256
diffie-hellman-group16-sha512
diffie-hellman-group18-sha512
ecdh-sha2-nistp256
ecdh-sha2-nistp384
ecdh-sha2-nistp521
```

The server supports the following options for `compression_algorithms_client_to_server` :

```
none
zlib@openssh.com
```

The server supports the following options for `encryption_algorithms_server_to_client` :

```
aes128-ctr
aes128-gcm@openssh.com
aes192-ctr
aes256-ctr
aes256-gcm@openssh.com
chacha20-poly1305@openssh.com
```

102094 - SSH Commands Require Privilege Escalation

-

Synopsis

This plugin reports the SSH commands that failed with a response indicating that privilege escalation is required to run them.

Description

This plugin reports the SSH commands that failed with a response indicating that privilege escalation is required to run them. Either privilege escalation credentials were not provided, or the command failed to run with the provided privilege escalation credentials.

NOTE: Due to limitations inherent to the majority of SSH servers, this plugin may falsely report failures for commands containing error output expected by `sudo`, such as 'incorrect password', 'not in the sudoers file', or 'not allowed to execute'.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0507

Plugin Information

Published: 2017/08/01, Modified: 2020/09/22

Plugin Output

tcp/0

```
Login account : ragnar
Commands failed due to privilege escalation failure:
- Escalation account : ragnar + root
Escalation method : su + sudo
Plugins :
- Plugin Filename : netstat_portscan.nasl
Plugin ID : 14272
Plugin Name : Netstat Portscanner (SSH)
- Command : "netstat -a -n"
Response : null
Error : "\nsh_shell_handler [channel 0]: ERROR - Bad privilege escalation password. Sending CTRL+C and removing privilege escalation
from credential set.\nsh_shell_handler [channel 0]: ERROR - unable to get back to command prompt."
```

149334 - SSH Password Authentication Accepted

-

Synopsis

The SSH server on the remote host accepts password authentication.

Description

The SSH server on the remote host accepts password authentication.

See Also

<https://tools.ietf.org/html/rfc4252#section-8>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/05/07, Modified: 2021/05/07

Plugin Output

tcp/22/ssh

10881 - SSH Protocol Versions Supported

Synopsis

A SSH server is running on the remote host.

Description

This plugin determines the versions of the SSH protocol supported by the remote SSH daemon.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/03/06, Modified: 2024/07/24

Plugin Output

tcp/22/ssh

```
The remote SSH daemon supports the following versions of the
SSH protocol :

- 2.0
```

153588 - SSH SHA-1 HMAC Algorithms Enabled

Synopsis

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Description

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Although NIST has formally deprecated use of SHA-1 for digital signatures, SHA-1 is still considered secure for HMAC as the security of HMAC does not rely on the underlying hash function being resistant to collisions.

Note that this plugin only checks for the options of the remote SSH server.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/09/23, Modified: 2022/04/05

Plugin Output

tcp/22/ssh

The following client-to-server SHA-1 Hash-based Message Authentication Code (HMAC) algorithms are supported :

hmac-sha1
hmac-sha1-etm@openssh.com

The following server-to-client SHA-1 Hash-based Message Authentication Code (HMAC) algorithms are supported :

hmac-sha1
hmac-sha1-etm@openssh.com

10267 - SSH Server Type and Version Information

-

Synopsis

An SSH server is listening on this port.

Description

It is possible to obtain information about the remote SSH server by sending an empty authentication request.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0933

Plugin Information

Published: 1999/10/12, Modified: 2024/07/24

Plugin Output

tcp/22/ssh

SSH version : SSH-2.0-OpenSSH_7.6p1 Ubuntu-4ubuntu0.5
SSH supported authentication : publickey,password

22964 - Service Detection

-

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2024/03/26

Plugin Output

tcp/22/ssh

An SSH server is running on this port.

22964 - Service Detection

-

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2024/03/26

Plugin Output

tcp/80/www

A web server is running on this port.

25220 - TCP/IP Timestamps Supported

-

Synopsis

The remote service implements TCP timestamps.

Description

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

See Also

<http://www.ietf.org/rfc/rfc1323.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2023/10/17

Plugin Output

tcp/0

150799 - Target Access Problems by Authentication Protocol - Maximum Privilege Account Used in Scan

-

Synopsis

Nessus scanned the target host with the highest available privilege level. Yet Nessus encountered permissions issues while accessing one or more items during the scan.

Description

Nessus was able to log in to the remote host using the provided credentials. The provided credentials have the highest privilege possible on the remote host. Yet Nessus encountered permissions issues while accessing items during the scan.

It is likely that this condition is caused by one or more of the following:

- 1) A plugin tried to access a resource that requires a special privilege level such as NT_AUTHORITY on Windows. The resource may have had its permissions altered since the plugin was written.
 - 2) Environmental issues may have caused an intermittent failure in authentication that caused Nessus to stop attempting privilege escalation.
 - 3) A resource on the host that Nessus attempts to access multiple times may be configured with access limits. Related lockouts may look like permissions failures.
 - 4) Nessus may have tried to access a resource that does not exist on a target that fails to properly report permissions issues.
- For instance, on some legacy unix systems such as AIX or HP-UX there is no way to distinguish a missing resource from a permissions error.

If you believe that the plugin indicated attempted to access the wrong resource or a resource that has recently received special OS protection, please contact Tenable Support.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/07/06, Modified: 2021/07/06

Plugin Output

tcp/22/ssh

Nessus was able to log in to the remote host via the following protocol as ragnar. During the scan Nessus encountered the following permissions issues while performing the planned checks:

Protocol : SSH
Port : 22

See the output of the following plugin for details :

Plugin ID : 102094
Plugin Name : SSH Commands Require Privilege Escalation

Note: Nessus was unable to determine the privilege of the logged in user and therefore is reporting permissions problems here. Please check to see whether privilege escalation failed or whether the scan can be configured to supply more access.

141118 - Target Credential Status by Authentication Protocol - Valid Credentials Provided -

Synopsis

Valid credentials were provided for an available authentication protocol.

Description

Nessus was able to determine that valid credentials were provided for an authentication protocol available on the remote target because it was able to successfully authenticate directly to the remote target using that authentication protocol at least once. Authentication was successful because the authentication protocol service was available remotely, the service was able to be identified, the authentication protocol was able to be negotiated successfully, and a set of credentials provided in the scan policy for that authentication protocol was accepted by the remote service. See plugin output for details, including protocol, port, and account.

Please note the following :

- This plugin reports per protocol, so it is possible for valid credentials to be provided for one protocol and not another. For example, authentication may succeed via SSH but fail via SMB, while no credentials were provided for an available SNMP service.

- Providing valid credentials for all available authentication protocols may improve scan coverage, but the value of successful authentication for a given protocol may vary from target to target depending upon what data (if any) is gathered from the target via that protocol. For example, successful authentication via SSH is more valuable for Linux targets than for Windows targets, and likewise successful authentication via SMB is more valuable for Windows targets than for Linux targets.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2020/10/15, Modified: 2024/03/25

Plugin Output

tcp/22/ssh

Nessus was able to log in to the remote host via the following :

User: 'ragnar'

Port: 22
Proto: SSH
Method: password

10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2023/12/04

Plugin Output

udp/0

For your information, here is the traceroute from 192.168.1.15 to 192.168.1.8 :
192.168.1.15
192.168.1.8

Hop Count: 1

Compliance 'FAILED'

Compliance 'SKIPPED'

Compliance 'PASSED'

Compliance 'INFO', 'WARNING', 'ERROR'

Remediations

Suggested Remediations