02 : 17 : 38
HRS   MIN   SEC

Shopee Code League 2022 - Qualification Round

LIVE   INVITE ONLY ACCESS

Mar 19, 2022, 03:00 PM SGT - Mar 19, 2022, 06:00 PM SGT

INSTRUCTIONS   PROBLEMS   SUBMISSIONS   LEADERBOARD   ANALYTICS   JUDGE

← Problems / Shopee Xpress Delivery

Shopee Xpress Delivery

Max. score: 100

00	0	1	2	3	4	5	6	7
0	go					1		
1		1					2	
2								
3			1					
4						2		2
5								
6			3					3
7				2				end

Description

Bob is a Shopee Xpress deliveryman and is delivering a package to his destination. He started his journey from one of our Shopee warehouses at position *(0, 0)*, and his destination is at the bottom-right corner of the map. For example, if the map is an 8x8 grid, the destination is *(7, 7)*.

Each step, his car can move 1 square up, down, left, or right. If his car reaches a black hole, it can teleport to any other location connected to the black hole at no cost, he also can skip the teleport feature. For example, if the car reaches black hole A at position (1, 1), Bob can teleport to position (0, 5) without costing an additional step.

Find the least number of steps (shortest path) that Bob can take to move from *(0, 0)* to the destination.

So, one path of least steps for example map is:

0,0 -> 0,1 -> 1,1/0,5 -> 1,5-> 1,6/7,3 -> 7,2 -> 6,2/6,7-> 7.7 , the answer is *7*.

Input:

The first line contains two numbers M, N ($1 \leq M, N \leq 1000$). M refers to the number of rows in the map, N refers to the number of columns in the map.

The next M rows contain N values x_{ij} ($0 \leq x[i][j] \leq 255$), where 0 means that position (i, j) is an empty square, and non-zero values mean that a black hole is present in the square. Non-zero values are guaranteed to have at least 2 or more instances on the map.

Output:

To print the integer of the least number of steps needed.

SAMPLE INPUT

```
8 8
0 0 1 0 0 0 0 0
0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0
0 0 0 0 0 0 1 0
0 0 0 0 0 0 0 0
```

SAMPLE OUTPUT

```
4
```

Explanation

NA

|	
Time Limit:	1.0 sec(s) for each input file.
Memory Limit:	256 MB
Source Limit:	1024 KB
Marking Scheme:	Score is assigned when all the testcases pass.
Allowed Languages:	Bash, C, C++, C++14, C++17, Clojure, C#, D, Erlang, F#, Go, Groovy, Haskell, Java, Java 8, Java 14, JavaScript(Rhino), JavaScript(Node.js), Julia, Kotlin, Lisp, Lisp (SBCL), Lua, Objective-C, OCaml, Octave, Pascal, Perl, PHP, Python, Python 3, Python 3.8, Racket, Ruby, Rust, Scala, Swift-4.1, Swift, TypeScript, Visual Basic

CODE EDITOR

Save   C++14 (g++ 10.3.0)

```
1    /*
2    // Sample code to perform I/O:
3
4    cin >> name;                              // Reading input from STDIN
5    cout << "Hi, " << name << ".\n";         // Writing output to STDOUT
6
7    // Warning: Printing unwanted or ill-formatted data to output will cause
     the test cases to fail
8    */
9
10   // Write your code here
11
```

1:1 vscode

Test against custom input ▼

Compile & Test code   Submit code

🖋 **Tip:** You can submit any number of times you want. Your best submission is considered for computing total score.

Your Rating: Like 0   Share

💬 View all comments

Resources

Tech Recruitment Blog

Product Guides

Developer hiring guide

Engineering Blog

Developers Blog

Developers Wiki

Competitive Programming

Start a Programming Club

Practice Machine Learning

Solutions

Assess Developers

Conduct Remote Interviews

Assess University Talent

Organize Hackathons

Company

About Us

Press

Careers

Service & Support

Technical Support

Contact Us

+1-650-461-4192

contact@hackerearth.com