Congestion Pipe Attack

HTTP Pipelining

Alexis Savard



What is HTTP Pipelining

- HTTP pipelining is a feature of HTTP/1.1 that allows a client to send multiple HTTP requests over a single TCP connection without waiting for the corresponding responses.
- Pipelining relies on either the Transfer-Encoding or Content-Length header to be able to tell when one of the pipelined requests stops and the next one begins.
- This technique aims to reduce the latency caused by waiting for each response before sending the next request, which is particularly beneficial in high-latency network conditions.
- Normally used by front-end and back-end communication



How to exploit HTTP Pipelining

When using HTTP pipelining, responses must be returned in the same order as the requests, requiring the server to process them sequentially. If an attacker sends a request requiring lengthy processing, such as a complex database query, all subsequent requests must wait until it's finished, causing delays.



HTTP pipelining can be exploited for Denial of Service (DoS):

- Attackers can send requests requiring lengthy processing, such as complex database queries or resource-intensive computations.
- Subsequent requests in the pipeline are delayed until the server completes the time-consuming task, leading to degraded performance or service unavailability.

A safe way to test the potential of HTTP pipelining without causing service exhaustion is by gradually adding requests to the main request while monitoring the response times (or alternatively increasing the number of database elements, if applicable). This method helps assess the performance impact of pipelining, showcasing its strain on the server without risking system instability.

Enhancing Request Potential (TIPS)

There are several ways to further exploit this vulnerability. For example, if the system is fetching data from a database, you could exp
processing l
techniques c

- **Inclu** nse and proce
- **Inflat** d during data
- **Utiliz** band signif
- **Requ** by a comp
- **Explore** ch as manipulating nested queries or requesting complex operations.



Articles

- https://blog.apnic.net/2022/11/18/service-exhaustion-floods-http-https-flood-http-pipelining-and-ssl-renegotiation-ddos-attack/
  - “Google’s researchers said that the attack on the Google Cloud Armor customer was the equivalent of getting all the daily requests to Wikipedia in just 10 seconds and the attack continued for 69 minutes.”

- https://www.infoworld.com/article/2294811/researcher-devises-hard-to-detect-dos-attack-against-http-servers.html