



Open Banking API

Technical Reference

Endpoints, parameters, request and response schemas, and error codes for engineering teams

Scope of this document

This is the technical companion to the neotek Open Banking master guide. It is written for engineers integrating against the APIs directly: every endpoint, its parameters, request and response fields, sample calls, and the error codes it can return. Business context and product rationale are covered in the master guide; this document assumes that context and focuses on the wire-level detail.

Authentication

Every API uses OAuth2 Client Credentials. A bearer token is obtained from the token endpoint using a client id, client secret, and the scope that matches the API being called. Request a separate token per scope; do not mix scopes in one token request.

Token request

```
POST {baseUrl}/oauth2security/oauth2/token
Content-Type: application/x-www-form-urlencoded

grant_type=client_credentials
&client_id=<client_id>
&client_secret=<client_secret>
&scope=<scope>
```

Using the token

```
authorization: Bearer <access_token>
x-request-id: <RFC4122-UUID> // optional, recommended for tracing
```

Scopes

single_api	Accounts Links API (consent management) and Single API Aggregator
e_statements	E-Statements
average_balance	Average Balance
account_insights	Account Insights
income_verification	Income Verification Plus
cashflow	Cashflow Report
credit_profile_assessment	Enhanced Credit Profile Assessment

Cache the token for the duration of its validity. Do not request a new token on every call.

Common headers

Parameter	In	Required	Description
authorization	header	Yes	Bearer token from the OAuth2 token endpoint.
x-request-id	header	No	RFC4122 UUID for end-to-end correlation. Always returned in the response even when omitted on the request.
Content-Type	header	No	application/json for all POST requests with a body.

Consent and connection APIs

These endpoints establish the customer's consent and are called before any product API below. They are shared infrastructure, not billable products in themselves.

Endpoint index

Endpoint	Purpose
POST /oauth2security/oauth2/token	Obtain an OAuth2 bearer token via Client Credentials
GET /financial-institutions-information/v1/financial-institutions	List participating banks available for account linking
POST /accounts-information/v1/accounts-links	Create a consent link for a customer
GET /accounts-information/v1/accounts-links	List and check the status of a customer's consent links

List Financial Institutions

Returns every participating bank so the customer can choose which one to connect.

GET /financial-institutions-information/v1/financial-institutions?IsActive=true authorization: Bearer <token>		
Field	Type	Description
FinancialInstitutionId	string	8-character SWIFT BIC identifying the institution, used in Create Account Link.
NameEn / NameAr	string	English and Arabic display name.
Logo	string	URL of the institution logo.
SecurityProfiles	array	Supported consent authorization flows for this institution.
IsActive	boolean	Whether the institution is currently available for linking.

Create Account Link

Registers the customer's consent for a selected institution and returns a redirection URL to complete authorization at the bank.

POST /accounts-information/v1/accounts-links authorization: Bearer <token> Content-Type: application/json		
<pre>{ "Data": { "PSUID": "<customer_id>", "FinancialInstitutionId": "RJHISARI", "SecurityProfile": "Redirection", "DataGroups": [{ "DataGroupId": "AccountDetails", "Permissions": ["ReadAccountsBasic","ReadAccountsDetail","ReadBalances"] }, { "DataGroupId": "AccountTransactions", "Permissions": ["ReadTransactionsBasic","ReadTransactionsDetail","ReadTransactionsCredits","ReadTransactionsDebits"] }], "AccountTypesList": ["KSAOB.Retail"], "PurposeList": ["Account Aggregation"] } }</pre>		
Field	Type	Description

Data.PSUID	string	Stable internal customer identifier, consistent across all calls for this customer.
Data.FinancialInstitutionId	string	SWIFT BIC of the institution the customer selected.
Data.SecurityProfile	string (enum)	Consent authorization flow. Redirection is the standard supported value.
Data.DataGroups	array	Data categories and permissions being requested. See DataGroup reference below.
Data.AccountTypesList	array (enum)	KSAOB.Retail and/or KSAOB.Corporate. Defaults to Retail if omitted.
Data.PurposeList	array (enum)	Business purpose for the consent, matching the product being integrated.
Data.ExpirationDateTime	date-time	Optional consent expiry. Omit for long-lived consent.

DataGroup reference

Field	Type	Description
AccountDetails	-	ReadAccountsBasic, ReadAccountsDetail, ReadBalances
AccountTransactions	-	ReadTransactionsBasic, ReadTransactionsDetail, ReadTransactionsCredits, ReadTransactionsDebits
RegularPayments	-	ReadBeneficiariesBasic, ReadBeneficiariesDetail, ReadStandingOrdersBasic, ReadStandingOrdersDetail, ReadDirectDebits, ReadScheduledPaymentsBasic, ReadScheduledPaymentsDetail
PartyDetails	-	ReadParty, ReadPartyPSUIdentity, ReadPartyPSU

Response: 201 Created

```
{
  "Data": {
    "AccountsLinkId": "226928827241365060738212769455",
    "RedirectionURL": "https://auth1.lab.openbanking.sa/auth?request_uri=..."
  }
}
```

Redirect the customer to RedirectionURL immediately; it is time-limited.

List Account Links

Retrieves the current state of a customer's consent links, including status and the AccountsLinkId needed for any product call.

```
GET /accounts-information/v1/accounts-links?PSUID=<id>&Status=Active
authorization: Bearer <token>
```

Parameter	In	Required	Description
PSUID	query	Yes	Customer identifier. Returns only links belonging to this PSU.
Status	query	No	Filter by status, comma-separated: Active, Pending, Rejected, Revoked, Expired.
AccountsLinkId	query	No	Filter to a specific link.
Page	query	No	Page number for paginated results.

Status values

Field	Type	Description
Pending	-	Consent created, customer has not yet completed authorization at their bank.
Active	-	Customer has authorized. Data retrieval begins; product APIs become usable once data is ready.
Rejected	-	Customer declined consent at the bank.

Field	Type	Description
Revoked	-	Consent was revoked by the customer, the bank, or the integrator. Re-consent required.
Expired	-	Consent passed its ExpirationDateTime. A new Account Link is required.

Errors

Code	Status	Typical cause
400	Bad Request	A required field is missing or a value fails validation. Check the error Code and Path in the response body.
401	Unauthorized	The bearer token is missing, expired, or invalid. Request a new token and retry.
403	Forbidden	The token does not carry the scope or permissions required for this endpoint. Verify the consent DataGroups and the requested scope.
404	Not Found	No resource matches the provided identifier (for example an unknown StatementId or AccountId).
405	Method Not Allowed	The HTTP verb used is not supported on this path.
406	Not Acceptable	The Accept header does not match a supported representation. Use application/json.
415	Unsupported Media Type	The Content-Type header is missing or incorrect. Use application/json.
429	Too Many Requests	The rate limit has been exceeded. Wait for the duration in the Retry-After header before retrying.
500	Internal Server Error	An unexpected server error occurred. Retry with backoff and include x-request-id when contacting support.

Single API Aggregator

Base path	/single-api-aggregator/v1
Scope	single_api

Exposes a customer's connected account data as a set of resource-oriented endpoints: accounts, balances, transactions, beneficiaries, parties, direct debits, standing orders, and scheduled payments.

Endpoints

Endpoint	Purpose
GET /profiles/accounts	List Profiles Accounts.
GET /profiles/balances	List Profiles Balances.
GET /profiles/beneficiaries	List Profiles Beneficiaries.
GET /profiles/transactions	List Profile Transactions.
GET /profile/direct-debits/{account_id}	Get Account Direct Debits
GET /profile/parties/{account_id}	Get Account Parties
GET /profile/scheduled-payments/{account_id}	Get Account Scheduled Payments
GET /profile/standing-orders/{account_id}	Get Account Standing Orders

GET /profiles/accounts

List profiles' accounts linked to a PSU. You can filter listed accounts by profile, financial institution, accounts link, account, ...etc.

Parameter	In	Required	Description
x-request-id	header	No	An RFC4122 UID used as a correlation id.
PSUId	query	Yes	The ID of the Payment Services User (PSU).
ProfileId	query	No	The ID of the profile that contains the Accounts Link(s) added by the PSU to the current profile.
FinancialInstitutionId	query	No	The ID of the financial institution with which the PSU may have established Accounts Link(s).
FinancialInstitutionName	query	No	The name of the financial institution with which the PSU may have established Accounts Link(s).
AccountsLinkId	query	No	The ID associated with the Accounts Link, an abstraction layer over OB consent. This ID is used in the Authorization Gateway, a Neotek product that simplifies Open Banking by abstracting its specifications and FAPI regulations.
AccountId	query	No	The unique ID for a specific account held by a PSU in a financial institution. This ID is used to manage and retrieve information related to the specific account through OB APIs.
Status	query	No	Filter by the status of accounts in code form. - Active: It means that the account is active and exists. - NotActive: It means that the account has been not active for 6 to 12 months. - Dormant: It means that the accounts has been Inactive for 1 to 5 years. -...
Currency	query	No	Identification of the currency in which the account is held. A code allocated to a currency under an international currency identification scheme, as described in the latest edition of the international standard ISO 4217 'Codes for the representation of curre...
AccountType	query	No	Filter by the type of accounts.
AccountSubType	query	No	Filter by the sub type of accounts (product family group).
FromOpeningDate	query	No	It sets a lower date-time limit for filtering accounts by opening date.

Parameter	In	Required	Description
ToOpeningDate	query	No	It sets an upper date-time limit for filtering accounts by opening date.
IncludeBalancesFlag	query	No	IncludeBalancesFlag is a boolean flag used to specify whether to include balance information for each account.
BalanceType	query	No	Filter by the type of balance for the account. Encoded with allowable values of: * 'ClosingAvailable' - end of day balance specifying the amount available to PSU 1 to withdraw or use. * 'ClosingBooked' - end of day balance including value of payments for cheq...
Page	query	No	The current page number of the paginated resources.
Order	query	No	Sort/Order accounts by opening date

GET /profiles/balances

List profiles' balances linked to a PSU. You can filter listed balances by profile, financial institution, accounts link, account, ...etc.

Parameter	In	Required	Description
x-request-id	header	No	An RFC4122 UID used as a correlation id.
PSUId	query	Yes	The ID of the Payment Services User (PSU).
ProfileId	query	No	The ID of the profile that contains the Accounts Link(s) added by the PSU to the current profile.
FinancialInstitutionId	query	No	The ID of the financial institution with which the PSU may have established Accounts Link(s).
FinancialInstitutionName	query	No	The name of the financial institution with which the PSU may have established Accounts Link(s).
AccountsLinkId	query	No	The ID associated with the Accounts Link, an abstraction layer over OB consent. This ID is used in the Authorization Gateway, a Neotek product that simplifies Open Banking by abstracting its specifications and FAPI regulations.
AccountId	query	No	The unique ID for a specific account held by a PSU in a financial institution. This ID is used to manage and retrieve information related to the specific account through OB APIs.
BalanceType	query	No	Filter by the type of balance for the account. Encoded with allowable values of: * 'ClosingAvailable' - end of day balance specifying the amount available to PSU 1 to withdraw or use. * 'ClosingBooked' - end of day balance including value of payments for cheq...
Currency	query	No	Identification of the currency in which the account is held. A code allocated to a currency under an international currency identification scheme, as described in the latest edition of the international standard ISO 4217 'Codes for the representation of curre...
BalanceAmountType	query	No	A number of monetary units specified in an active currency where the unit of currency is explicit and compliant with ISO 4217.
FromAmount	query	No	Starting range for amount JSON path: Data.Balances.*.Amount.Amount
ToAmount	query	No	Ending range for amount. JSON path: Data.Balances.*.Amount.Amount
Page	query	No	The current page number of the paginated resources.

Sample

```
GET /single-api-aggregator/v1/profiles/balances?PSUId=<id>&AccountsLinkId=<id>
authorization: Bearer <token>
```

GET /profiles/beneficiaries

List profiles' beneficiaries linked to a PSU. You can filter listed beneficiaries by profile, financial institution, accounts link, account, ...etc.

Parameter	In	Required	Description
x-request-id	header	No	An RFC4122 UID used as a correlation id.
PSUId	query	Yes	The ID of the Payment Services User (PSU).
ProfileId	query	No	The ID of the profile that contains the Accounts Link(s) added by the PSU to the current profile.
FinancialInstitutionId	query	No	The ID of the financial institution with which the PSU may have established Accounts Link(s).
FinancialInstitutionName	query	No	The name of the financial institution with which the PSU may have established Accounts Link(s).
AccountsLinkId	query	No	The ID associated with the Accounts Link, an abstraction layer over OB consent. This ID is used in the Authorization Gateway, a Neotek product that simplifies Open Banking by abstracting its specifications and FAPI regulations.
AccountId	query	No	The unique ID for a specific account held by a PSU in a financial institution. This ID is used to manage and retrieve information related to the specific account through OB APIs.
BeneficiaryType	query	No	Filter by the Beneficiary Type.
BeneficiaryName	query	No	The Beneficiary Name is the name or names of the Beneficiary account owner(s) represented at the account level, as displayed by the Creditor Agent's online channels and as provided by the Beneficiary to the PSU 1 when adding the Beneficiary in the Beneficiary...
BeneficiaryShortName	query	No	Filter by the Beneficiary account holder nick name. JSON Path: Data.Beneficiaries.*.AccountHolderShortName
BeneficiaryBankName	query	No	Name by which an agent is known and which is usually used to identify that agent. JSON Path: Data.Beneficiaries.*.CreditorAgent.Name
Page	query	No	The current page number of the paginated resources.

GET /profiles/transactions

List profiles' transactions linked to a PSU. You can filter listed transactions by profile, financial institution, accounts link, account, ...etc.

Parameter	In	Required	Description
x-request-id	header	No	An RFC4122 UID used as a correlation id.
PSUId	query	Yes	The ID of the Payment Services User (PSU).
ProfileId	query	No	The ID of the profile that contains the Accounts Link(s) added by the PSU to the current profile.
FinancialInstitutionId	query	No	The ID of the financial institution with which the PSU may have established Accounts Link(s).
FinancialInstitutionName	query	No	The name of the financial institution with which the PSU may have established Accounts Link(s).
AccountsLinkId	query	No	The ID associated with the Accounts Link, an abstraction layer over OB consent. This ID is used in the Authorization Gateway, a Neotek product that simplifies Open Banking by abstracting its specifications and FAPI regulations.
AccountId	query	No	The unique ID for a specific account held by a PSU in a financial institution. This ID is used to manage and retrieve information related to the specific account through OB APIs.

Parameter	In	Required	Description
TransactionType	query	No	TransactionType
TransactionSubType	query	No	TransactionSubType
TransactionFlags	query	No	TransactionFlags
PaymentMode	query	No	PaymentMode
TransactionAmountType	query	No	TransactionAmountType
TransactionStatus	query	No	TransactionStatus
TransactionMutability	query	No	TransactionMutability
FromBookingDate	query	No	FromBookingDate
ToBookingDate	query	No	ToBookingDate
FromAmount	query	No	Starting range for amount JSON path: Data.Balances.*.Amount.Amount
ToAmount	query	No	Ending range for amount. JSON path: Data.Balances.*.Amount.Amount
Currency	query	No	Identification of the currency in which the account is held. A code allocated to a currency under an international currency identification scheme, as described in the latest edition of the international standard ISO 4217 'Codes for the representation of curre...
MerchantName	query	No	MerchantName
CardSchemeName	query	No	CardSchemeName
Page	query	No	The current page number of the paginated resources.
Order	query	No	Order by TransactionDateTime

GET /profile/direct-debits/{account_id}

Parameter	In	Required	Description
x-request-id	header	No	An RFC4122 UID used as a correlation id.
account_id	path	Yes	
psu_id	query	No	

GET /profile/parties/{account_id}

Parameter	In	Required	Description
x-request-id	header	No	An RFC4122 UID used as a correlation id.
account_id	path	Yes	
psu_id	query	No	

Response body (key fields)

Field	Type	Description
Data.Party[].PartyId	string	Unique identifier for the party.
Data.Party[].PartyType	string	Type of party, e.g. Sole, Joint.
Data.Party[].VerifiedClaims[].Claims.Name	string	Full verified name.
Data.Party[].VerifiedClaims[].Claims.PhoneNumber	string	Verified phone number.
Data.Party[].VerifiedClaims[].Verification.AssuranceLevel	string	Assurance level of the identity verification.

Sample

```
GET /single-api-aggregator/v1/profile/parties/{account_id}?psu_id=<id>
authorization: Bearer <token>
```

GET /profile/scheduled-payments/{account_id}

Parameter	In	Required	Description
x-request-id	header	No	An RFC4122 UID used as a correlation id.
account_id	path	Yes	
psu_id	query	No	

GET /profile/standing-orders/{account_id}

Parameter	In	Required	Description
x-request-id	header	No	An RFC4122 UID used as a correlation id.
account_id	path	Yes	
psu_id	query	No	

Errors

This API returns the standard neotek error structure and status codes.

Code	Status	Typical cause
400	Bad Request	A required field is missing or a value fails validation. Check the error Code and Path in the response body.
401	Unauthorized	The bearer token is missing, expired, or invalid. Request a new token and retry.
403	Forbidden	The token does not carry the scope or permissions required for this endpoint. Verify the consent DataGroups and the requested scope.
404	Not Found	No resource matches the provided identifier (for example an unknown StatementId or AccountId).
405	Method Not Allowed	The HTTP verb used is not supported on this path.
406	Not Acceptable	The Accept header does not match a supported representation. Use application/json.
415	Unsupported Media Type	The Content-Type header is missing or incorrect. Use application/json.
429	Too Many Requests	The rate limit has been exceeded. Wait for the duration in the Retry-After header before retrying.
500	Internal Server Error	An unexpected server error occurred. Retry with backoff and include x-request-id when contacting support.

Average Balances

Base path	/balances/v1
Scope	average_balance

Returns 3, 6 and 12 month average balance and transaction count, aggregated across a PSU's linked accounts.

Endpoints

Endpoint	Purpose
GET /average-balances	

GET /average-balances

Parameter	In	Required	Description
authorization	header	Yes	An authorisation Token as per https://tools.ietf.org/html/rfc6750
x-request-id	header	No	An RFC4122 UID used as a correlation id.
AccountsLinkId	query	Yes	Accounts Link Identifier
PSUIId	query	Yes	PSU Identifier
CustomerType	query	No	CustomerType (SME / Retail)
Duration	query	Yes	Date Range

Response body (key fields)

Field	Type	Description
AccountId	string	The account this result relates to.
3_months	string	Average balance over the trailing 3 months.
6_months	string	Average balance over the trailing 6 months.
12_months	string	Average balance over the trailing 12 months.
TransactionCount	string	Number of transactions in the period.

Sample

```
GET /balances/v1/average-balances?AccountsLinkId=<id>&PSUIId=<id>&Duration=6
authorization: Bearer <token>
```

Errors

This API returns the standard neotek error structure and status codes.

Code	Status	Typical cause
400	Bad Request	A required field is missing or a value fails validation. Check the error Code and Path in the response body.
401	Unauthorized	The bearer token is missing, expired, or invalid. Request a new token and retry.
403	Forbidden	The token does not carry the scope or permissions required for this endpoint. Verify the consent DataGroups and the requested scope.
404	Not Found	No resource matches the provided identifier (for example an unknown StatementId or AccountId).
405	Method Not Allowed	The HTTP verb used is not supported on this path.
406	Not Acceptable	The Accept header does not match a supported representation. Use application/json.
415	Unsupported Media Type	The Content-Type header is missing or incorrect. Use application/json.

Code	Status	Typical cause
429	Too Many Requests	The rate limit has been exceeded. Wait for the duration in the Retry-After header before retrying.
500	Internal Server Error	An unexpected server error occurred. Retry with backoff and include x-request-id when contacting support.

Account Insights

Base path	/open-banking/v1
Scope	account_insights

Returns categorized spend and income insight for a business (corporate) account over a requested period.

Endpoints

Endpoint	Purpose
POST /account-insights	Account Insights

POST /account-insights

Parameter	In	Required	Description
authorization	header	Yes	An authorization Token as per https://tools.ietf.org/html/rfc6750
x-request-id	header	No	An RFC4122 UID used as a correlation id.

Request body

Field	Type	Description
psu_id	string	PSU identifier.
account_link_id	string	Accounts Link identifier for the consented account.
from_date / to_date	string	Period to analyze.
account_ids	array	Specific accounts to include, if not the full linked set.
transaction_amount_threshold_in_sar	number	Minimum transaction size to include in the analysis.
filters	array	Additional category or type filters.

Response body (key fields)

Field	Type	Description
accounts_insights	object	Overall account-level insight summary.
pos_transactions_insights	object	Point-of-sale spend breakdown.
e_commerce_transactions_insights	object	E-commerce spend breakdown.

Sample

```
POST /open-banking/v1/account-insights
authorization: Bearer <token>

{ "psu_id": "<id>", "account_link_id": "<id>", "from_date": "2026-01-01", "to_date": "2026-06-30" }
```

Errors

This API returns the standard neotek error structure and status codes.

Code	Status	Typical cause
400	Bad Request	A required field is missing or a value fails validation. Check the error Code and Path in the response body.
401	Unauthorized	The bearer token is missing, expired, or invalid. Request a new token and retry.
403	Forbidden	The token does not carry the scope or permissions required for this endpoint. Verify the consent DataGroups and the requested scope.
404	Not Found	No resource matches the provided identifier (for example an unknown StatementId or AccountId).

Code	Status	Typical cause
405	Method Not Allowed	The HTTP verb used is not supported on this path.
406	Not Acceptable	The Accept header does not match a supported representation. Use application/json.
415	Unsupported Media Type	The Content-Type header is missing or incorrect. Use application/json.
429	Too Many Requests	The rate limit has been exceeded. Wait for the duration in the Retry-After header before retrying.
500	Internal Server Error	An unexpected server error occurred. Retry with backoff and include x-request-id when contacting support.

Income Verification Plus

Base path	/income-verification/v1
Scope	income_verification

Asynchronous income verification for personal accounts. The first call starts processing and returns 400; poll the same request until it returns 200 with the final result.

Endpoints

Endpoint	Purpose
POST /income-verification-plus	List Accounts Income Verification

POST /income-verification-plus

Parameter	In	Required	Description
authorization	header	Yes	An authorization Token as per https://tools.ietf.org/html/rfc6750
x-request-id	header	No	An RFC4122 UID used as a correlation id.

Request body

Field	Type	Description
psu_id	string	PSU identifier.
account_link_id	string	Accounts Link identifier.
from_date / to_date	string	Period to analyze for income patterns.
account_ids	array	Specific accounts to include.

Sample

```
POST /income-verification/v1/income-verification-plus
authorization: Bearer <token>

{ "psu_id": "<id>", "account_link_id": "<id>" }
-- returns 400 while processing, poll until 200 OK --
```

Errors

This API returns the standard neotek error structure and status codes.

Code	Status	Typical cause
400	Bad Request	A required field is missing or a value fails validation. Check the error Code and Path in the response body.
401	Unauthorized	The bearer token is missing, expired, or invalid. Request a new token and retry.
403	Forbidden	The token does not carry the scope or permissions required for this endpoint. Verify the consent DataGroups and the requested scope.
404	Not Found	No resource matches the provided identifier (for example an unknown StatementId or AccountId).
405	Method Not Allowed	The HTTP verb used is not supported on this path.
406	Not Acceptable	The Accept header does not match a supported representation. Use application/json.
415	Unsupported Media Type	The Content-Type header is missing or incorrect. Use application/json.
429	Too Many Requests	The rate limit has been exceeded. Wait for the duration in the Retry-After header before retrying.
500	Internal Server Error	An unexpected server error occurred. Retry with backoff and include x-request-id when contacting support.

E-Statements

Base path	/financial-statements/v1
Scope	e_statements

Event-driven: statement data is generated after account consent completes and a webhook confirms data is ready. Do not call any endpoint, including Create E-Statement, before that callback.

Endpoints

Endpoint	Purpose
POST /estatemements-request	Create E-Statements
GET /e-statements/{StatementId}	Get E-Statement by E-Statement Id
GET /e-statements/{StatementId}/pdf	Get E-Statement PDF by E-Statement Id
GET /e-statements/{StatementId}/csv	Get E-Statement CSV by E-Statement Id

POST /estatemements-request

This path is used to create E-Statements.

Parameter	In	Required	Description
authorization	header	Yes	An authorisation Token as per https://tools.ietf.org/html/rfc6750
x-request-id	header	No	An RFC4122 UID used as a correlation id.

Request body

Field	Type	Description
AccountsLinkIds	array	List of account link IDs to include in the statement request.
PSUID	string	PSU identifier (1-35 characters).
TransactionType	string (enum)	Optional filter by transaction type.
TransactionFromTimestamp / TransactionToTimestamp	date-time	ISO 8601 filter range. Defaults to the last 6 months.
TransactionFromAmount / TransactionToAmount	number	Optional amount range filter.
IsCategorized	boolean	Includes AI-categorized transaction data. Requires a separate subscription.

Response body (key fields)

Field	Type	Description
Data.RequestId	string	Identifier for the overall statement request.
Data.EStatements[].StatementId	string	Per-account statement identifier used on the retrieval endpoints.
Data.EStatements[].FinancialInstitutionId	string	8-character SWIFT BIC of the account's institution.

Sample

```
POST /financial-statements/v1/estatemements-request
authorization: Bearer <token>

{ "PSUID": "<id>", "AccountsLinkIds": ["LINK-001"], "IsCategorized": false }
```

GET /e-statements/{StatementId}

This path is used to get E-Statement by E-Statement Id.

Parameter	In	Required	Description
StatementId	path	Yes	
authorization	header	Yes	An authorisation Token as per https://tools.ietf.org/html/rfc6750
x-request-id	header	No	An RFC4122 UID used as a correlation id.

Response body (key fields)

Field	Type	Description
CustomerName	string	Full name of the account holder.
OpeningBalance / ClosingBalance	number	Balance at the start and end of the period.
TotalOfDeposit / TotalOfWithdraw	number	Aggregate totals for the period.
Transactions[]	array	Full transaction list for the statement.

GET /e-statements/{StatementId}/pdf

This path is used to get E-Statement PDF by E-Statement Id.

Parameter	In	Required	Description
StatementId	path	Yes	
authorization	header	Yes	An authorisation Token as per https://tools.ietf.org/html/rfc6750
x-request-id	header	No	An RFC4122 UID used as a correlation id.

Response body (key fields)

Field	Type	Description
Data.PDF	string	Base64-encoded PDF document.

GET /e-statements/{StatementId}/csv

This path is used to get E-Statement CSV by E-Statement Id.

Parameter	In	Required	Description
StatementId	path	Yes	
authorization	header	Yes	An authorisation Token as per https://tools.ietf.org/html/rfc6750
x-request-id	header	No	An RFC4122 UID used as a correlation id.

Response body (key fields)

Field	Type	Description
(raw body)	text/csv	Plain CSV response, no JSON envelope.

Errors

This API returns the standard neotek error structure and status codes.

Code	Status	Typical cause
400	Bad Request	A required field is missing or a value fails validation. Check the error Code and Path in the response body.
401	Unauthorized	The bearer token is missing, expired, or invalid. Request a new token and retry.
403	Forbidden	The token does not carry the scope or permissions required for this endpoint. Verify the consent DataGroups and the requested scope.

Code	Status	Typical cause
404	Not Found	No resource matches the provided identifier (for example an unknown StatementId or AccountId).
405	Method Not Allowed	The HTTP verb used is not supported on this path.
406	Not Acceptable	The Accept header does not match a supported representation. Use application/json.
415	Unsupported Media Type	The Content-Type header is missing or incorrect. Use application/json.
429	Too Many Requests	The rate limit has been exceeded. Wait for the duration in the Retry-After header before retrying.
500	Internal Server Error	An unexpected server error occurred. Retry with backoff and include x-request-id when contacting support.

Cashflow Report

Base path	/open-banking/v1
Scope	cashflow

Returns a structured summary of inflow and outflow movements for an account over a requested period.

Endpoints

Endpoint	Purpose
GET /reports/cashflow	Cashflow Report

GET /reports/cashflow

This path is used to retrieve the cashflow report for an account.

Parameter	In	Required	Description
authorization	header	Yes	An authorisation Token as per https://tools.ietf.org/html/rfc6750
x-request-id	header	No	An RFC4122 UID used as a correlation id.
psu_id	query	Yes	
from_date	query	Yes	
to_date	query	Yes	
account_id	query	No	
financial_institution_id	query	No	

Sample

```
GET /open-banking/v1/reports/cashflow?psu_id=<id>&from_date=2026-01-01&to_date=2026-06-30
authorization: Bearer <token>
```

Errors

This API returns the standard neotek error structure and status codes.

Code	Status	Typical cause
400	Bad Request	A required field is missing or a value fails validation. Check the error Code and Path in the response body.
401	Unauthorized	The bearer token is missing, expired, or invalid. Request a new token and retry.
403	Forbidden	The token does not carry the scope or permissions required for this endpoint. Verify the consent DataGroups and the requested scope.
404	Not Found	No resource matches the provided identifier (for example an unknown StatementId or AccountId).
405	Method Not Allowed	The HTTP verb used is not supported on this path.
406	Not Acceptable	The Accept header does not match a supported representation. Use application/json.
415	Unsupported Media Type	The Content-Type header is missing or incorrect. Use application/json.
429	Too Many Requests	The rate limit has been exceeded. Wait for the duration in the Retry-After header before retrying.
500	Internal Server Error	An unexpected server error occurred. Retry with backoff and include x-request-id when contacting support.

Enhanced Credit Profile Assessment

Base path	/credit-profile-assessment/v1
Scope	credit_profile_assessment

Generates a credit score (0-1000) and rating (AAA to D) from Open Banking transaction data, with optional PDF report output. Currency defaults to SAR.

Endpoints

Endpoint	Purpose
POST /credit-profile/getCreditProfileReport	Generate Credit Profile Report (JSON)
POST /credit-profile/getCreditProfileReport/v2/pdf	Generate Credit Profile Report (PDF V2 - 8 pages)

POST /credit-profile/getCreditProfileReport

Generates a comprehensive credit profile assessment report based on the customer's Open Banking transaction data. Returns detailed JSON response with score breakdown, financial metrics, and recommendations.

Request body

Field	Type	Description
psuId	string	PSU identifier.
accountLinkId	string	Account Link ID (consent identifier).
accountId	string	IBAN or account identifier.
customerType	string	Customer type for the assessment.
purpose	string	Purpose of the loan request.
requestedAmount	number	Requested loan amount in SAR.
loanTermMonths	integer	Loan term in months (default 60, or 240 for HOME_MORTGAGE).
annualInterestRate	number	Annual interest rate as a percentage (default 3.0).
age	integer	Customer age, enables AGE factor scoring.

Response body (key fields)

Field	Type	Description
totalScore	integer	Total credit score, 0-1000.
ratingClass	string	Rating classification from AAA (900-1000) to D (0-99).
ratingDescription	string	Description of the rating tier.
approvalRecommendation	string	Recommended approval outcome.
factorScores	array	Breakdown of the score by contributing factor.
financialMetrics	object	Underlying financial metrics used in scoring.

Sample

```
POST /credit-profile-assessment/v1/credit-profile/getCreditProfileReport
authorization: Bearer <token>

{ "psuId": "<id>", "accountLinkId": "<id>", "accountId": "<iban>", "requestedAmount":
50000, "loanTermMonths": 60 }
```

POST /credit-profile/getCreditProfileReport/v2/pdf

Generates an enhanced 8-page PDF credit profile report with: - Page 1: Executive Summary - Page 2: Credit Score Component Breakdown - Page 3: Financial Health Indicators - Page 4: Transaction Analysis - Page 5: Loan Exposure & Debt Profile - Page 6: Behavior Analysis - Page 7: Monthly Breakdown - Page 8: Final Recommendation (with Purpose Assessment)

Response body (key fields)

Field	Type	Description
(binary)	application/pdf	8-page PDF credit report: executive summary, score breakdown, financial health, transaction analysis, loan exposure, behavior analysis, monthly breakdown, and final recommendation.

Errors

This API returns the standard neotek error structure and status codes.

Code	Status	Typical cause
400	Bad Request	A required field is missing or a value fails validation. Check the error Code and Path in the response body.
401	Unauthorized	The bearer token is missing, expired, or invalid. Request a new token and retry.
403	Forbidden	The token does not carry the scope or permissions required for this endpoint. Verify the consent DataGroups and the requested scope.
404	Not Found	No resource matches the provided identifier (for example an unknown StatementId or AccountId).
405	Method Not Allowed	The HTTP verb used is not supported on this path.
406	Not Acceptable	The Accept header does not match a supported representation. Use application/json.
415	Unsupported Media Type	The Content-Type header is missing or incorrect. Use application/json.
429	Too Many Requests	The rate limit has been exceeded. Wait for the duration in the Retry-After header before retrying.
500	Internal Server Error	An unexpected server error occurred. Retry with backoff and include x-request-id when contacting support.