
# Implementation Guide for CDA Release 2 Tularemia PHCR CDA R2 Optional Subtitle



PROTOTYPE: FOR DISCUSSION
AND DEMONSTRATION USE ONLY
(Consolidated Developer Documentation)



# **Contents**

Acknowledgments	5
Revision History	7
·	
Chapter 1: INTRODUCTION	Q
Overview	
Approach	
Scope	
Audience	
Organization of This Guide	
Templates	
Vocabulary and Value Sets	
Use of Templates	
Originator Responsibilities	
Recipient Responsibilities	11
Conventions Used in This Guide	11
Conformance Requirements	
Keywords	
XML Examples	12
Chapter 2. DOCUMENT TEMPI ATES	12
Chapter 2: DOCUMENT TEMPLATES	
Tularemia Case Report	14
Chapter 3: SECTION TEMPLATES	17
Tularemia PHCR Clinical Information Section	
Tularemia PHCR Relevant Dx Tests Section	
Tularemia PHCR Social History Section	
Tularemia PHCR Treatment Information Section	
Tutatellia Frick Treatment information Section	20
Chapter 4: CLINICAL STATEMENT TEMPLATES	23
Location Of Lesion Observation	24
Tularemia Case Observation	24
Tularemia Possible Exposure Location And Type Act	25
Tularemia Result Observation.	
Tularemia Result Organizer	
Tularemia Signs And Symptoms Observation	
Tularemia Therapeutic Regimen Act	
Tularemia Treatment Given Substance Administration	
Tularemia Treatment Not Given Substance Administration	30
Chapter 5: OTHER CLASSES	31
Chapter 6: VALUE SETS	
Animal	
Disease Type (Tularemia)	34

Lab Test Result Name (Tularemia)	
Material Exposure Type	35
Medication Treatment (Tularemia)	35
Signs and Symptoms (Tularemia)	35
REFERENCES	37

### **Acknowledgments**

This document contains an example of healthcare standards and specifications publication generated from UML models, using the OHT Model Driven Health Tools (MDHT). Some portions of this document may not be publicly available but are included for demonstration purposes only, therefore this version of the document is to be treated as CONFIDENTIAL by the project participants.

This demonstration document contains informtion from the following sources:

©2010 ANSI. This material may be copied without permission from ANSI only if and to the extent that the text is not altered in any fashion and ANSI's copyright is clearly noted.

SNOMED CT® is the registered trademark of the International Health Terminology Standard Development Organization (IHTSDO).

This material contains content from LOINC® (http://loinc.org). The LOINC table, LOINC codes, and LOINC panels and forms file are copyright © 1995-2010, Regenstrief Institute, Inc. and the Logical Observation Identifiers Names and Codes (LOINC) Committee and available at no cost under the license at http://loinc.org/terms-of-use.

Certain materials contained in this Interoperability Specification are reproduced from Health Level Seven (HL7) HL7 Implementation Guide: CDA Release 2 – Continuity of Care Document (CCD), HL7 Implementation Guide for CDA Release 2: History and Physical (H&P) Notes, HL7 Implementation Guide for CDA Release 2: Consult Notes, or HL7 Implementation Guide for CDA Release 2: Operative Notes with permission of Health Level Seven, Inc. No part of the material may be copied or reproduced in any form outside of the Interoperability Specification documents, including an electronic retrieval system, or made available on the Internet without the prior written permission of Health Level Seven, Inc. Copies of standards included in this Interoperability Specification may be purchased from the Health Level Seven, Inc. Material drawn from these standards is credited where used.



# **Revision History**

Rev	Date	By Whom	Changes
New	July 2010	Dave Carlson	
First draft for posting	December 2010	Dave Carlson	Updated model content and publication format



# 1

# INTRODUCTION

#### Topics:

- Overview
- Approach
- Scope
- Audience
- Organization of This Guide
- Use of Templates
- Conventions Used in This Guide

#### **Overview**

This implementation guide is generated from UML models developed in the Open Health Tools (OHT) Model-Driven Health Tools (MDHT) project. The data specifications have been formalized into computational models expressed in UML. These models are used by automated tooling to generate this publication, plus validation tools and Java libraries for implementers.

#### **Approach**

Working with specifications generated from formal UML models provides the opportunity to work with the data from the perspective of the underlying model and electronic format and to explore many design issues thoroughly. Taking this as an initial step ensures that the data set developers and standards community can reach consensus prior to the larger commitment of time that would be required to bring the full data set into standard format.

This project supports reusability and ease of data collection through a standard data representation harmonized with work developed through Health Information Technology Expert Panel (HITEP), balloted through Health Level Seven (HL7) and/or recognized by the Health Information Technology Standards Panel (HITSP).

This implementation guide (IG) specifies a standard for electronic submission of NCRs in a Clinical Document Architecture (CDA), Release 2 format.

#### Scope

TODO: scope of this implementation guide.

#### **Audience**

The audience for this document includes software developers and implementers who wish to develop...

#### **Organization of This Guide**

The requirements as laid out in the body of this document are subject to change per the policy on implementation guides (see section 13.02" Draft Standard for Trial Use Documents" within the HL7 Governance and Operations Manual, <a href="http://www.hl7.org/documentcenter/public/membership/HL7\_Governance\_and\_Operations\_Manual.pdf">http://www.hl7.org/documentcenter/public/membership/HL7\_Governance\_and\_Operations\_Manual.pdf</a>).

#### **Templates**

Templates are organized by document (see Document Templates), by section (see Section Templates), and by clinical statements (see Clinical Statement Templates). Within a section, templates are arranged hierarchically, where a more specific template is nested under the more generic template that it conforms to. See Templates by Containment for a listing of the higher level templates by containment; the appendix Templates Used in This Guide includes a table of all of the templates Organized Hierarchically.

#### **Vocabulary and Value Sets**

Vocabularies recommended in this guide are from standard vocabularies. When SNOMED codes are used, rules defined in Using SNOMED CT in HL7 Version 3 are adhered to. In many cases, these vocabularies are further constrained into value sets for use within this guide. Value set names and OIDs are summarized in the table Summary of Value Sets. Each named value set in this summary table is stored in a template database that will be maintained by CHCA.

#### **Use of Templates**

When valued in an instance, the template identifier (templateId) signals the imposition of a set of template-defined constraints. The value of this attribute provides a unique identifier for the templates in question.

#### **Originator Responsibilities**

An originator can apply a templateId to assert conformance with a particular template.

In the most general forms of CDA exchange, an originator need not apply a templateId for every template that an object in an instance document conforms to. This implementation guide asserts when templateIds are required for conformance.

#### **Recipient Responsibilities**

A recipient may reject an instance that does not contain a particular templateId (e.g., a recipient looking to receive only CCD documents can reject an instance without the appropriate templateId).

A recipient may process objects in an instance document that do not contain a templateId (e.g., a recipient can process entries that contain Observation acts within a Problems section, even if the entries do not have templateIds).

#### **Conventions Used in This Guide**

#### **Conformance Requirements**

Conformance statements are grouped and identified by the name of the template, along with the templateId and the context of the template (e.g., ClinicalDocument, section, observation), which specifies the element under constraint. If a template is a specialization of another template, its first constraint indicates the more general template. In all cases where a more specific template conforms to a more general template, asserting the more specific template also implies conformance to the more general template. An example is shown below.

#### Template name

```
[<type of template>: templateId <XXXX.XX.XXX.XXX>]
```

Description of the template will be here .....

- 1. Conforms to <The template name> Template (templateId: XXXX<XX>XXX>YYY).
- **2. SHALL** contain [1..1] @classCode = <AAA> <code display name> (CodeSystem: 123.456.789 <XXX> Class) **STATIC** (CONF:<number>).
- **3.** ......

#### Figure 1: Template name and "conforms to" appearance

The conformance verb keyword at the start of a constraint (SHALL, SHOULD, MAY, etc.) indicates business conformance, whereas the cardinality indicator (0..1, 1..1, 1..\*, etc.) specifies the allowable occurrences within an instance. Thus, "MAY contain 0..1" and "SHOULD contain 0..1" both allow for a document to omit the particular component, but the latter is a stronger recommendation that the component be included if it is known.

The following cardinality indicators may be interpreted as follows:

- 0...1 as zero to one present
- 1..1 as one and only one present
- 2..2 as two must be present
- 1..\* as one or more present
- 0..\* as zero to many present

Value set bindings adhere to HL7 Vocabulary Working Group best practices, and include both a conformance verb (SHALL, SHOULD, MAY, etc.) and an indication of DYNAMIC vs. STATIC binding. The use of SHALL requires that the component be valued with a member from the cited value set; however, in every case any HL7 "null" value such as other (OTH) or unknown (UNK) may be used.

Each constraint is uniquely identified (e.g., "CONF:605") by an identifier placed at or near the end of the constraint. These identifiers are not sequential as they are based on the order of creation of the constraint.

- 1. SHALL contain [1..1] component/structuredBody (CONF:4082).
  - a. This component/structuredBody SHOULD contain [0..1] component (CONF:4130) such that it
    - **a. SHALL** contain [1..1] Reporting Parameters section (templateId:2.16.840.1.113883.10.20.17.2.1) (CONF:4131).
  - b. This component/structuredBody SHALL contain [1..1] component (CONF:4132) such that it
    - **a. SHALL** contain [1..1] Patient data section NCR (templateId:2.16.840.1.113883.10.20.17.2.5) (CONF:4133).

#### Figure 2: Template-based conformance statements example

CCD templates are included within this implementation guide for ease of reference. CCD templates contained within this implementation guide are formatted WITHOUT typical **KEYWORD** and **XML** element styles. A WIKI site is available if you would like to make a comment to be considered for the next release of CCD: <a href="http://wiki.hl7.org/index.php?title=CCD\_Suggested\_Enhancements">http://wiki.hl7.org/index.php?title=CCD\_Suggested\_Enhancements</a> The user name and password are: wiki/wikiwiki. You will need to create an account to edit the page and add your suggestion.

- 1. The value for "Observation / @moodCode" in a problem observation SHALL be "EVN" 2.16.840.1.113883.5.1001 ActMood STATIC. (CONF: 814).
- 2. A problem observation SHALL include exactly one Observation / statusCode. (CONF: 815).
- **3.** The value for "Observation / statusCode" in a problem observation SHALL be "completed" 2.16.840.1.113883.5.14 ActStatus STATIC. (CONF: 816).
- **4.** A problem observation SHOULD contain exactly one Observation / effectiveTime, to indicate the biological timing of condition (e.g. the time the condition started, the onset of the illness or symptom, the duration of a condition). (CONF: 817).

Figure 3: CCD conformance statements example

#### Keywords

The keywords SHALL, SHALL NOT, SHOULD, SHOULD NOT, MAY, and NEED NOT in this document are to be interpreted as described in the *HL7 Version 3 Publishing Facilitator's Guide*:

- SHALL: an absolute requirement
- SHALL NOT: an absolute prohibition against inclusion
- SHOULD/SHOULD NOT: valid reasons to include or ignore a particular item, but must be understood and carefully weighed
- MAY/NEED NOT: truly optional; can be included or omitted as the author decides with no implications

#### **XML Examples**

XML samples appear in various figures in this document in a fixed-width font. Portions of the XML content may be omitted from the content for brevity, marked by an ellipsis (...) as shown in the example below.

```
<ClinicalDocument xmlns='urn:h17-org:v3'>
...
</ClinicalDocument>
```

#### Figure 4: ClinicalDocument example

XPath expressions are used in the narrative and conformance requirements to identify elements because they are familiar to many XML implementers.

2

## **DOCUMENT TEMPLATES**

#### Topics:

• Tularemia Case Report

This section contains the document level constraints for CDA documents that are compliant with this implementation guide.

#### **Tularemia Case Report**

```
[ClinicalDocument: templateId 2.16.840.1.113883.10.20.15.1.4]
```

- 1. SHALL conform to PHCR Public Health Case Report templateId:
- 2.16.840.1.113883.10.20.15)
- 2. Contains exactly one [1..1] typeId, where its data type is InfrastructureRootTypeId
- **3.** Contains exactly one [1..1] **id**, where its data type is II
- **4. SHALL** contain exactly one [1..1] **code/@code=** "55751-2" *Public Health Case Report* (CodeSystem: 2.16.840.1.113883.6.1 LOINC)
- 5. SHALL contain exactly one [1..1] title = "Public Health Case Report Tularemia" (CONF:1840)
- **6.** Contains exactly one [1..1] **effectiveTime**, where its data type is TS
- 7. Contains exactly one [1..1] confidentialityCode, where its data type is CE
- 8. Contains at least one [1..\*] recordTarget, where its type is *Record Target*
- **9.** Contains at least one [1..\*] **author**, where its type is *Author*
- **10.** Contains exactly one [1..1] **custodian**, where its type is *Custodian*
- 11. Contains exactly one [1..1] component, where its type is *Component2*
- 12. SHOULD contain zero or one [0..1] component (CONF:643, CONF:609), such that
  - **a.** Contains exactly one [1..1] *Pher Encounters Section* (templateId: 2.16.840.1.113883.10.20.15.2.2)
- 13. MAY contain zero or one [0..1] component, such that
  - a. Contains exactly one [1..1] CCD Immunizations Section (templateId: 2.16.840.1.113883.10.20.1.6)
- 14. SHOULD contain zero or one [0..1] component (CONF:1842, CONF:1843), such that
  - **a.** Contains exactly one [1..1] *Tularemia PHCR Social History Section* (templateId: 2.16.840.1.113883.10.20.15.2.18)
- 15. SHALL contain exactly one [1..1] component (CONF:1844, CONF:1845), such that
  - **a.** Contains exactly one [1..1] *Tularemia PHCR Clinical Information Section* (templateId: 2.16.840.1.113883.10.20.15.2.19)
- 16. SHOULD contain zero or one [0..1] component (CONF:1846, CONF:1847), such that
  - **a.** Contains exactly one [1..1] *Tularemia PHCR Treatment Information Section* (templateId: 2.16.840.1.113883.10.20.15.2.20)
- 17. SHOULD contain zero or one [0..1] component (CONF:1848, CONF:1849), such that
  - **a.** Contains exactly one [1..1] *PHCR Phcr Encounters Section* (templateId: 2.16.840.1.113883.10.20.15.2.2)
- 18. SHOULD contain zero or one [0..1] component (CONF:1850, CONF:1851), such that
  - **a.** Contains exactly one [1..1] *Tularemia PHCR Relevant Dx Tests Section* (templateId: 2.16.840.1.113883.10.20.15.2.21)
- **19. SHALL** contain [1..1] recordTarget (CONF:547)
  - [OCL]: self.recordTarget->one(recordTarget : cda::RecordTarget | not recordTarget.oclIsUndefined())
- **20.** RecordTarget **SHALL** contain [1..1] patientRole (CONF:548)
  - [OCL]: self.recordTarget.patientRole->one(patientRole : cda::PatientRole not patientRole.oclIsUndefined())
- 21. RecordTarget / PatientRole SHALL contain [1..\*] id (CONF:549)
  - [OCL]: self.recordTarget.patientRole.id->exists(id : datatypes::II | not id.root.oclIsUndefined() or not id.extension.oclIsUndefined() or not id.nullFlavor.oclIsUndefined())
- **22.** RecordTarget / PatientRole **SHOULD** contain [0..\*] addr (CONF:550)

- **23.** RecordTarget / PatientRole **SHOULD** contain [0..\*] telecom (CONF:551)
- **24.** RecordTarget / PatientRole **SHOULD** contain [0..1] patient (CONF:552)
- **25.** RecordTarget / PatientRole / Patient **SHOULD** contain [0..\*] name (CONF:553)
- **26.** RecordTarget / PatientRole / Patient **SHOULD** contain [0..1] administrativeGenderCode/@code, which **SHALL** be selected from ValueSet 2.16.840.1.113883.1.11.1 Administrative Gender (HL7 V3) DYNAMIC (CONF:554)
- 27. RecordTarget / PatientRole / Patient SHOULD contain [0..1] birthTime (CONF:555)
- **28.** RecordTarget / PatientRole / Patient **SHOULD** contain [0..1] ethnicGroupCode, which **SHALL** be selected from ValueSet 2.16.840.1.114222.4.11.837 Ethnicity group DYNAMIC (CONF:556)
- **29.** RecordTarget / PatientRole / Patient **SHOULD** contain [0..1] birthplace/place, which **SHALL** be selected from ValueSet 2.16.840.1.114222.4.11.3200 Birth Country DYNAMIC (CONF:557)
- **30. SHALL** contain [1..\*] author (CONF:1853)
  - [OCL]: self.author->exists(author : cda::Author | not author.oclIsUndefined())
- **31.** Author **SHALL** contain [1..1] time (CONF:560)
  - [OCL]: self.author.time->one(time : datatypes::TS | not time.value.oclIsUndefined())
- **32.** Author **SHALL** contain [1..1] assigned Author (CONF:561)
  - [OCL]: self.author.assignedAuthor->one(assignedAuthor: cda::AssignedAuthor | not assignedAuthor.oclIsUndefined())
- **33.** Author / AssignedAuthor **SHALL** contain [1..\*] id (CONF:562)
  - [OCL]: self.author.assignedAuthor.id->exists(id : datatypes::II | not id.root.oclIsUndefined() or not id.extension.oclIsUndefined() or not id.nullFlavor.oclIsUndefined())
- **34.** Author / Assigned Author **SHALL** contain [1..1] addr (CONF:562)
  - [OCL]: self.author.assignedAuthor.addr->one(addr : datatypes::AD | not addr.oclIsUndefined())
- **35.** Author / AssignedAuthor **SHALL** contain [1..1] telecom (CONF:564)
  - [OCL]: self.author.assignedAuthor.telecom->one(tel: datatypes::TEL | not tel.oclIsUndefined())
- **36.** Author / AssignedAuthor **SHALL** contain [1..1] assignedPerson/name (CONF:565)
  - [OCL]: self.author.assignedAuthor.assignedPerson->one(assignedPerson: cda::Person | not assignedPerson.oclIsUndefined()) and self.author.assignedAuthor.assignedPerson.name->one(name: datatypes::PN | not name.oclIsUndefined())
- **37.** The custodian of a public health case report **SHALL** be the reporting organization. (CONF:1616)
- **38. SHALL** contain [1..1] legalAuthenticator (CONF:1854)
  - [OCL]: self.legalAuthenticator->one(legalAuthenticator: cda::LegalAuthenticator | not legalAuthenticator.oclIsUndefined())
- **39.** LegalAuthenticator **SHALL** contain [1..1] time (CONF:1855)
  - [OCL]: self.legalAuthenticator.time->one(time : datatypes::TS | not time.value.oclIsUndefined())
- **40.** Legal Authenticator **SHALL** contain [1..1] assigned Entity (CONF:1856)
  - [OCL]: self.legalAuthenticator.assignedEntity->one(assignedEntity: cda::AssignedEntity | not assignedEntity.oclIsUndefined())
- **41.** LegalAuthenticator / AssignedEntity **SHALL** contain [1..\*] id (CONF:1857)
  - [OCL]: self.legalAuthenticator.assignedEntity.id->exists(id: datatypes::II | not id.root.oclIsUndefined() or not id.extension.oclIsUndefined())
- **42.** LegalAuthenticator / AssignedEntity **SHALL** contain [1..1] addr (CONF:1857)
  - [OCL]: self.legalAuthenticator.assignedEntity.addr->one(addr: datatypes::AD | not addr.oclIsUndefined())

- **43.** LegalAuthenticator / AssignedEntity **SHALL** contain [1..1] telecom (CONF:1859)
- 44. Legal Authenticator / Assigned Entity SHALL contain [1..1] assigned Person/name (CONF:1860)
  - [OCL]: self.legalAuthenticator.assignedEntity.assignedPerson>one(assignedPerson : cda::Person | not assignedPerson.oclIsUndefined())
    and self.legalAuthenticator.assignedEntity.assignedPerson.name>one(name : datatypes::PN | not name.oclIsUndefined())
- **45.** Where a Public Health Case Report CDA R2 document contains any of the section or clinical statement templates defined in this implementation guide, such section or clinical statement **SHALL** include a templateId/@root valued with the corresponding template's identifier. (CONF:2017)

**Tularemia Case Report example** 

3

## **SECTION TEMPLATES**

#### Topics:

- Tularemia PHCR Clinical Information Section
- Tularemia PHCR Relevant Dx Tests Section
- Tularemia PHCR Social History Section
- Tularemia PHCR Treatment Information Section

#### **Tularemia PHCR Clinical Information Section**

[Section: templateId 2.16.840.1.113883.10.20.15.2.19]

- **1. SHALL** conform to *PHCR Phcr Clinical Information Section* template (templateId: 2.16.840.1.113883.10.20.15.2.1)
- 2. SHALL contain exactly one [1..1] code/@code="55752-0" Clinical Information (CodeSystem: 2.16.840.1.113883.6.1 LOINC) (CONF:540)
- **3. SHALL** contain exactly one [1..1] **title** = "Clinical Information" (CONF:541)
- **4. SHALL** contain exactly one [1..1] **text** (CONF:542)
- 5. MAY contain zero or one [0..1] entry (CONF:1912, CONF:1913, CONF:1914), such that
  - a. Contains @typeCode="DRIV" DRIV (is derived from)
  - **b.** Contains exactly one [1..1] *Patient Condition Alive Observation* (templateId: 2.16.840.1.113883.10.20.15.3.42)
- 6. MAY contain zero or one [0..1] entry (CONF:1915, CONF:1916, CONF:1917), such that
  - a. Contains @typeCode="DRIV" DRIV (is derived from)
  - **b.** Contains exactly one [1..1] *Patient Condition Deceased Observation* (templateId: 2.16.840.1.113883.10.20.15.3.17)
- 7. SHALL contain exactly one [1..1] entry (CONF:1718, CONF:1719), such that
  - a. Contains @typeCode="DRIV" DRIV (is derived from)
  - **b.** Contains exactly one [1..1] *Tularemia Case Observation* (templateId: 2.16.840.1.113883.10.20.15.3.46)
- 8. TemplateId 2.16.840.1.113883.10.20.15.3.42 (Patient condition alive) and templateId 2.16.840.1.113883.10.20.15.3.17 (Patient condition deceased) SHALL NOT be present together in a CDA PHCR instance. (CONF:1918)

```
• [OCL]: self.getObservations()->exists(obs3 : cda::Observation | obs3.oclIsKindOf(phcr::PatientConditionAliveObservation) and not self.getObservations()->exists(obs4 : cda::Observation | obs4.oclIsKindOf(phcr::PatientConditionDeceasedObservation))) or self.getObservations()->exists(obs1 : cda::Observation | obs1.oclIsKindOf(phcr::PatientConditionDeceasedObservation) and not self.getObservations()->exists(obs2 : cda::Observation | obs2.oclIsKindOf(phcr::PatientConditionAliveObservation))) or self.getObservations()->forAll(obs : cda::Observation | not obs.oclIsKindOf(phcr::PatientConditionAliveObservation)) and not obs.oclIsKindOf(phcr::PatientConditionDeceasedObservation))
```

**Tularemia PHCR Clinical Information Section example** 

#### Tularemia PHCR Relevant Dx Tests Section

[Section: templateId 2.16.840.1.113883.10.20.15.2.21]

- 1. SHALL conform to CCD Results Section template (templateId: 2.16.840.1.113883.10.20.1.14)
- **2. SHALL** conform to *PHCR Phcr Relevant Dx Tests Section* template (templateId: 2.16.840.1.113883.10.20.15.2.3)
- 3. SHALL contain exactly one [1..1] code/@code="30954-2" Relevant diagnostic tests and/or laboratory data (CodeSystem: 2.16.840.1.113883.6.1 LOINC) (CONF-389, CONF:735)
- **4. SHALL** contain exactly one [1..1] **title** = "Relevant diagnostic tests and/or laboratory data" (CONF-391, CONF:736)
- **5. SHALL** contain exactly one [1..1] **text** (CONF-388, CONF:737)

- 6. MAY contain zero or more [0..\*] entry (CONF:2014, CONF:2015, CONF:2016), such that
  - a. Contains @typeCode="DRIV" DRIV (is derived from)
  - **b.** Contains exactly one [1..1] *Imaging Observation* (templateId: 2.16.840.1.113883.10.20.15.3.5)
- 7. MAY contain zero or more [0..\*] entry (CONF:1830), such that
  - a. Contains @typeCode="DRIV" DRIV (is derived from)
  - **b.** Contains exactly one [1..1] *Tularemia Result Organizer* (templateId: 2.16.840.1.113883.10.20.15.3.52)
- **8. SHOULD** contain zero or more [0..\*] **entry** (CONF:1833), such that
  - a. Contains @typeCode="DRIV" DRIV (is derived from)
  - **b.** Contains exactly one [1..1] *Tularemia Result Observation* (templateId: 2.16.840.1.113883.10.20.15.3.51)
- 9. MAY contain zero or more [0..\*] entry (CONF:1836), such that
  - **a.** Contains @typeCode="DRIV" DRIV (is derived from)
  - **b.** Contains exactly one [1..1] *PHCR Imaging Observation* (templateId: 2.16.840.1.113883.10.20.15.3.5)
- 10. SHOULD satisfy: Contains a case-insensitive language-insensitive string containing 'results'. (CONF-392)
  - UNIMPLEMENTABLE

Tularemia PHCR Relevant Dx Tests Section example

#### **Tularemia PHCR Social History Section**

[Section: templateId 2.16.840.1.113883.10.20.15.2.18]

- 1. SHALL conform to CCD Social History Section template (templateId: 2.16.840.1.113883.10.20.1.15)
- **2. SHALL** conform to *PHCR Phcr Social History Section* template (templateId: 2.16.840.1.113883.10.20.15.2.22)
- **3. SHALL** contain exactly one [1..1] **code/@code**="29762-2" *Social History* (CodeSystem: 2.16.840.1.113883.6.1 LOINC) (CONF:1894)
- **4. SHALL** contain exactly one [1..1] **title** = "Social History" (CONF:1895)
- **5. SHALL** contain exactly one [1..1] text (CONF:1896)
- **6. SHOULD** contain zero or more [0..\*] **entry**, such that
  - a. Contains exactly one [1..1] Social History Observation (templateId: 2.16.840.1.113883.10.20.1.33)
- 7. SHOULD contain zero or more [0..\*] entry (CONF:1897, CONF:1898, CONF:1899), such that
  - a. Contains @typeCode="DRIV" DRIV (is derived from)
  - **b.** Contains exactly one [1..1] *Geotemporal History Observation* (templateId: 2.16.840.1.113883.10.20.15.3.3)
- 8. SHOULD contain zero or one [0..1] entry (CONF:1900, CONF:1901, CONF:1902), such that
  - a. Contains @typeCode="DRIV" DRIV (is derived from)
  - **b.** Contains exactly one [1..1] *Most Recent Time Arrived In USA Observation* (templateId: 2.16.840.1.113883.10.20.15.3.6)
- 9. SHOULD contain zero or more [0..\*] entry (CONF:1903, CONF:1904, CONF:1905), such that
  - a. Contains @typeCode="DRIV" DRIV (is derived from)
  - **b.** Contains exactly one [1..1] *Race Observation* (templateId: 2.16.840.1.113883.10.20.15.3.9)
- 10. SHOULD contain zero or more [0..\*] entry (CONF:1906, CONF:1907, CONF:1908), such that
  - a. Contains @typeCode="DRIV" DRIV (is derived from)
  - **b.** Contains exactly one [1..1] *Occupation Observation* (templateId: 2.16.840.1.113883.10.20.15.3.7)

- 11. MAY contain zero or more [0..\*] entry (CONF:1909, CONF:1910, CONF:1911), such that
  - a. Contains @typeCode="DRIV" DRIV (is derived from)
  - **b.** Contains exactly one [1..1] *Pregnancy Observation* (templateId: 2.16.840.1.113883.10.20.15.3.8)
- 12. MAY contain zero or more [0..\*] entry (CONF:1669, CONF:1670), such that
  - a. Contains @typeCode="DRIV" DRIV (is derived from)
  - **b.** Contains exactly one [1..1] *Tularemia Possible Exposure Location And Type Act* (templateId: 2.16.840.1.113883.10.20.15.3.43)
- 13. SHOULD satisfy: Contains a case-insensitive language-insensitive string containing 'social history'. (CONF-236)
  - UNIMPLEMENTABLE
- **14.** Marital status **SHOULD** be represented as ClinicalDocument / recordTarget / patientRole / patient / maritalStatusCode. Additional information **MAY** be represented as social history observations (CONF-250)
  - [OCL]: self.getClinicalDocument().recordTarget->select(r | not r.patientRole.patient.maritalStatusCode.hasContent() )->isEmpty()
- **15.** Religious affiliation **SHOULD** be represented as ClinicalDocument / recordTarget / patientRole / patient / religiousAffiliationCode. Additional information **MAY** be represented as social history observations (CONF-251)
  - [OCL]: self.getClinicalDocument().recordTarget->select(r | not r.patientRole.patient.religiousAffiliationCode.hasContent() )->isEmpty()
- **16.** A patients race **SHOULD** be represented as ClinicalDocument / recordTarget / patientRole / patient / raceCode. Additional information **MAY** be represented as social history observations (CONF-252)
  - [OCL]: self.getClinicalDocument().recordTarget->select(r | not r.patientRole.patient.raceCode.hasContent())->isEmpty()
- 17. The value for ClinicalDocument / recordTarget / patientRole / patient / raceCode MAY be selected from codeSystem 2.16.840.1.113883.5.104 (Race) (CONF-253)
  - [OCL]: self.getClinicalDocument().recordTarget->forAll(r | r.patientRole.patient.raceCode.codeSystem = '2.16.840.1.113883.5.104')
- **18.** A patients ethnicity **SHOULD** be represented as ClinicalDocument / recordTarget / patientRole / patient / ethnicGroupCode. Additional information **MAY** be represented as social history observations. (CONF-254)
  - [OCL]: self.getClinicalDocument().recordTarget->select(r | not r.patientRole.patient.ethnicGroupCode.hasContent())->isEmpty()
- **19.** The value for ClinicalDocument / recordTarget / patientRole / patient / ethnicGroupCode **MAY** be selected from codeSystem 2.16.840.1.113883.5.50 (Ethnicity). (CONF-255)
  - [OCL]: self.getClinicalDocument().recordTarget->forAll(r | r.patientRole.patient.ethnicGroupCode.codeSystem = '2.16.840.1.113883.5.50')

Tularemia PHCR Social History Section example

#### Tularemia PHCR Treatment Information Section

[Section: templateId 2.16.840.1.113883.10.20.15.2.20]

- **1. SHALL** conform to *PHCR Phcr Treatment Information Section* template (templateId: 2.16.840.1.113883.10.20.15.2.4)
- **2. SHALL** contain exactly one [1..1] **code/@code**="55753-8" *Treatment Information* (CodeSystem: 2.16.840.1.113883.6.1 LOINC) (CONF:663)
- **3. SHALL** contain exactly one [1..1] **title** = "Treatment Information" (CONF:664)
- **4. SHALL** contain exactly one [1..1] text (CONF:665)
- 5. SHALL contain exactly one [1..1] entry (CONF:1782, CONF:1783, CONF:1784), such that
  - a. Contains @typeCode="DRIV" DRIV (is derived from)

**b.** Contains exactly one [1..1] *Tularemia Therapeutic Regimen Act* (templateId: 2.16.840.1.113883.10.20.15.3.48)

**Tularemia PHCR Treatment Information Section example** 

4

## **CLINICAL STATEMENT TEMPLATES**

#### **Topics:**

- Location Of Lesion Observation
- Tularemia Case Observation
- Tularemia Possible Exposure Location And Type Act
- Tularemia Result Observation
- Tularemia Result Organizer
- Tularemia Signs And Symptoms Observation
- Tularemia Therapeutic Regimen Act
- Tularemia Treatment Given Substance Administration
- Tularemia Treatment Not Given Substance Administration

This section of the Implementation Guide details the clinical statement entries referenced in the document section templates. The clinical statement entry templates are arranged alphabetically.

#### **Location Of Lesion Observation**

[Observation: templateId 2.16.840.1.113883.10.20.15.3.44]

- 1. SHALL contain exactly one [1..1] @classCode="OBS" Observation (CodeSystem: 2.16.840.1.113883.5.6 HL7ActClass) (CONF:1672)
- **2. SHALL** contain exactly one [1..1] **@moodCode**="EVN" *Event* (CodeSystem: 2.16.840.1.113883.5.1001 HL7ActMood) (CONF:1673)
- 3. SHALL contain exactly one [1..1] code/@code="ASSERTION" (CodeSystem: 2.16.840.1.113883.5.4 HL7ActCode) (CONF:1675)
- **4. SHALL** contain exactly one [1..1] **statusCode/@code**="completed" (CodeSystem: 2.16.840.1.113883.5.14 ActStatus) (CONF:1676)
- **5. SHOULD** contain zero or one [0..1] **effectiveTime** (CONF:1677)
- 6. SHALL contain exactly one [1..1] value, which SHALL be selected from ValueSet 2.16.840.1.114222.4.11.3215 Signs and Symptoms (Tularemia) DYNAMIC, where its data type is CD (CONF:1678)
- 7. SHALL contain at least one [1..\*] targetSiteCode, which SHALL be selected from ValueSet 2.16.840.1.113883.3.88.12.3221.8.9 Body Site DYNAMIC (CONF:1679)

**Location Of Lesion Observation example** 

#### **Tularemia Case Observation**

[Observation: templateId 2.16.840.1.113883.10.20.15.3.46]

- 1. SHALL conform to CCD Problem Observation template (templateId: 2.16.840.1.113883.10.20.1.28)
- **2. SHALL** conform to *PHCR Case Observation* template (templateId: 2.16.840.1.113883.10.20.15.3.54)
- **3. SHALL** contain exactly one [1..1] **@classCode**="OBS" *Observation* (CodeSystem: 2.16.840.1.113883.5.6 HL7ActClass) (CONF:1868)
- **4. SHALL** contain exactly one [1..1] **@moodCode**="EVN" *Event* (CodeSystem: 2.16.840.1.113883.5.1001 HL7ActMood) (CONF:1869)
- **5.** MAY contain zero or more [0..\*] id (CONF:1870)
- 6. SHALL contain exactly one [1..1] code/@code="ASSERTION" (CodeSystem: 2.16.840.1.113883.5.4 HL7ActCode) (CONF:1871)
- 7. SHALL contain exactly one [1..1] statusCode/@code="completed" (CodeSystem: 2.16.840.1.113883.5.14 ActStatus) (CONF:1872)
- **8. SHOULD** contain zero or one [0..1] **effectiveTime** (CONF:1873)
- SHALL contain exactly one [1..1] value, which SHALL be selected from ValueSet
   2.16.840.1.114222.4.11.3223 Disease Type (Tularemia) DYNAMIC, where its data type is CD (CONF:1693)
- 10.MAY contain zero or one [0..1] entryRelationship (CONF-162), such that
  - a. Contains @typeCode="REFR" REFR (refers to)
  - **b.** Contains exactly one [1..1] *Problem Status Observation* (templateId: 2.16.840.1.113883.10.20.1.50)
- 11. MAY contain zero or one [0..1] entryRelationship (CONF-165), such that
  - **a.** Contains @typeCode="REFR" REFR (refers to)
  - **b.** Contains exactly one [1..1] *Problem Health Status Observation* (templateId: 2.16.840.1.113883.10.20.1.51)
- 12. MAY contain zero or one [0..1] entryRelationship (CONF-160), such that
  - a. Contains @typeCode="SUBJ" SUBJ (has subject)

```
b. Contains exactly one [1..1] Age Observation (templateId: 2.16.840.1.113883.10.20.1.38)
13. SHOULD contain zero or one [0..1] entryRelationship (CONF:1884, CONF:1885, CONF:1886), such that
  a. Contains @typeCode="REFR" REFR (refers to)
  b. Contains exactly one [1..1] CCD Problem Status Observation (templateId:
     2.16.840.1.113883.10.20.1.50)
14. SHALL contain zero or more [0..*] entryRelationship (CONF:1706, CONF:1708, CONF:1709), such that
  a. Contains @typeCode="MFST" MFST (is manifestation of)
  b. Contains exactly one [1..1] Tularemia Signs And Symptoms Observation (templateId:
     2.16.840.1.113883.10.20.15.3.45)
15. MAY contain zero or more [0..*] entryRelationship (CONF:1710), such that
  a. Contains @typeCode="MFST" MFST (is manifestation of)
  b. Contains exactly one [1..1] Location Of Lesion Observation (templateId:
     2.16.840.1.113883.10.20.15.3.44)
16. SHALL contain one or more sources of information. (CONF-161)
  • [OCL]: not self.informant->isEmpty()
     or not self.getSection().informant->isEmpty()
     or not self.getClinicalDocument().informant->isEmpty()
     or self.reference->exists(ref : cda::Reference | ref.typeCode =
      vocab::x ActRelationshipExternalReference::XCRPT)
     or (self.entryRelationship->exists(rel : cda::EntryRelationship
         rel.typeCode = vocab::x_ActRelationshipEntryRelationship::REFR
         and rel.observation.code.code = '48766-0'))
17. MAY contain exactly one Patient Awareness (CONF-180)
     [OCL]: self.participant->one(partic : cda::Participant2 |
      partic.oclIsKindOf(ccd::PatientAwareness))
18. SHOULD contain [0..1] effective Time/low (CONF:1873)
  • [OCL]: self.effectiveTime->exists(time : datatypes::IVL_TS | not
      time.low.oclIsUndefined())
19. SHOULD contain [0..1] author (CONF:1875)
     [OCL]: self.author->exists(author : cda::Author | not
      author.oclIsUndefined())
20. Author SHALL contain [1..1] time (CONF:1876)
21. Author SHALL contain [1..1] assignedAuthor (CONF:1877)
     [OCL]: self.author.assignedAuthor->exists(assignedAuthor:
      cda::AssignedAuthor | not assignedAuthor.oclIsUndefined())
22. Author / AssignedAuthor SHALL contain [1..*] id (CONF:1878)
23. Author / Assigned Author MAY contain [0..*] addr (CONF:1879)
24. Author / AssignedAuthor MAY contain [0..*] telecom (CONF:1880)
25. Author / AssignedAuthor MAY contain [0..1] assignedPerson (CONF:1881)
```

**26.** Author / AssignedAuthor / Person **MAY** contain [0..1] name (CONF:1882)

27. Author / AssignedAuthor MAY contain [0..1] representedOrganization (CONF:1883)

**Tularemia Case Observation example** 

#### **Tularemia Possible Exposure Location And Type Act**

```
[Act: templateId 2.16.840.1.113883.10.20.15.3.43]
```

- 1. SHALL contain exactly one [1..1] @classCode="ACT" Act (CodeSystem: 2.16.840.1.113883.5.6 HL7ActClass) (CONF:1617)
- 2. SHALL contain exactly one [1..1] @moodCode="EVN" Event (CodeSystem: 2.16.840.1.113883.5.1001 HL7ActMood) (CONF:1618)

- **3. SHALL** contain exactly one [1..1] **code/@code**="413350009" *Finding with explicit context* (CodeSystem: 2.16.840.1.113883.6.96 SNOMEDCT) (CONF:1619)
- **4. SHALL** contain exactly one [1..1] **statusCode/@code**="completed" (CodeSystem: 2.16.840.1.113883.5.14 ActStatus) (CONF:1626)
- 5. SHALL contain [1..1] qualifier, SHALL contain [1..1] name/@code="246090004" Associated finding (CodeSystem: 2.16.840.1.113883.6.96 SNOMEDCT) STATIC, SHALL contain [1..1] value/@code="PHC818" Tularemia exposure (CodeSystem: 2.16.840.1.114222.4.5.274 PHIN VADS code system) STATIC (CONF:1620)
- 6. SHALL contain [1..1] qualifier, which SHALL contain [1..1] name/@code="408729009" Finding context (CodeSystem: 2.16.840.1.113883.6.96 SNOMEDCT) STATIC, SHALL contain [1..1] value/ @code="410590009" Known possible (CodeSystem: 2.16.840.1.113883.6.96 SNOMEDCT) STATIC (CONF:1623)
- **7. SHALL** contain [1..\*] participant, which **SHALL** contain [1..1] @typeCode="LOC" Location (CodeSystem: 2.16.840.1.113883.5.90 HL7ParticipationType) STATIC (CONF:1627)
- **8.** MAY contain [0..\*] participant, which if present SHALL contain [1..1] @typeCode="DIR" Direct target (CodeSystem: 2.16.840.1.113883.5.90 HL7ParticipationType) STATIC (CONF:1637)
- **9. MAY** contain [0..\*] participant, which if present **SHALL** contain [1..1] @typeCode="DIR" Direct target (CodeSystem: 2.16.840.1.113883.5.90 HL7ParticipationType) STATIC (CONF:1645)

Tularemia Possible Exposure Location And Type Act example

#### **Tularemia Result Observation**

[Observation: templateId 2.16.840.1.113883.10.20.15.3.51]

- 1. SHALL conform to CCD Result Observation template (templateId: 2.16.840.1.113883.10.20.1.31)
- **2. SHALL** conform to *PHCR Result Observation* template (templateId: 2.16.840.1.113883.10.20.15.3.58)
- 3. SHALL contain exactly one [1..1] @classCode="OBS" Observation (CodeSystem: 2.16.840.1.113883.5.6 HL7ActClass)
- **4. SHALL** contain exactly one [1..1] **@moodCode**="EVN" *Event* (CodeSystem: 2.16.840.1.113883.5.1001 HL7ActMood) (CONF-408)
- **5. SHALL** contain at least one [1..\*] **id** (CONF-409)
- SHALL contain exactly one [1..1] code, which SHALL be selected from ValueSet
   2.16.840.1.114222.4.11.3208 Lab Test Result Name (Tularemia) DYNAMIC (CONF:1788)
- 7. SHALL contain exactly one [1..1] statusCode/@code="completed" (CodeSystem: 2.16.840.1.113883.5.14 ActStatus) (CONF-410)
- 8. SHOULD contain exactly one [1..1] effectiveTime (CONF-411)
  - Represents the biologically relevant time (e.g. time the specimen was obtained from the patient).
- **9. SHALL** contain exactly one [1..1] **value** (CONF-416)
- 10. SHOULD contain zero or more [0..\*] interpretationCode (CONF-418)
  - Can be used to provide a rough qualitative interpretation of the observation, such as 'N' (normal), 'L' (low), 'S' (susceptible), etc. Interpretation is generally provided for numeric results where an interpretation range has been defined, or for antimicrobial susceptibility test interpretation.
- 11. MAY contain zero or one [0..1] methodCode (CONF-414)
  - Included if the method isn't inherent in code or if there is a need to further specialize the method in code.
- **12.** The value for 'code' **SHOULD** be selected from LOINC (codeSystem 2.16.840.1.113883.6.1) or SNOMED CT (codeSystem 2.16.840.1.113883.6.96), and **MAY** be selected from CPT-4 (codeSystem 2.16.840.1.113883.6.12). (CONF-413)
  - [OCL]: self.code.codeSystem = '2.16.840.1.113883.6.1' xor self.code.codeSystem = '2.16.840.1.113883.6.96' xor self.code.codeSystem = '2.16.840.1.113883.6.12'

- 13. The methodCode SHALL NOT conflict with the method inherent in code (CONF-415)
  - UNIMPLEMENTABLE
- **14.** Where value is a physical quantity, the unit of measure **SHALL** be expressed using a valid Unified Code for Units of Measure (UCUM) expression. (CONF-417)
  - UNIMPLEMENTABLE
- **15. SHOULD** satisfy: Contain one or more referenceRange to show the normal range of values for the observation result (CONF-419)
  - [OCL]: not self.referenceRange->isEmpty()
- **16. SHALL NOT** contain referenceRange / observationRange / code, as this attribute is not used by the HL7 Clinical Statement or Lab Committee models. (CONF-420)
  - [OCL]: self.referenceRange->forAll(range : cda::ReferenceRange | range.observationRange.code.code.oclIsUndefined())
- **17. SHALL** satisfy: Contains one or more sources of information. (CONF-421)

```
• [OCL]: not self.informant->isEmpty()
or not self.getSection().informant->isEmpty()
or not self.getClinicalDocument().informant->isEmpty()
or self.reference->exists(ref : cda::Reference | ref.typeCode =
    vocab::x_ActRelationshipExternalReference::XCRPT)
or (self.entryRelationship->exists(rel : cda::EntryRelationship |
    rel.typeCode = vocab::x_ActRelationshipEntryRelationship::REFR
    and rel.observation.code.code = '48766-0'))
```

**Tularemia Result Observation example** 

#### Tularemia Result Organizer

[Organizer: templateId 2.16.840.1.113883.10.20.15.3.52]

- 1. SHALL conform to CCD Result Organizer template (templateId: 2.16.840.1.113883.10.20.1.32)
- **2. SHALL** conform to *PHCR Result Organizer* template (templateId: 2.16.840.1.113883.10.20.15.3.59)
- 3. SHALL contain exactly one [1..1] @classCode="BATTERY" (CodeSystem: 2.16.840.1.113883.5.6 HL7ActClass) (CONF:1996)
- **4. SHALL** contain exactly one [1..1] **@moodCode**="EVN" *Event* (CodeSystem: 2.16.840.1.113883.5.1001 HL7ActMood) (CONF-394, CONF:1997)
- 5. SHALL contain at least one [1..\*] id (CONF-395, CONF:1998)
- 6. SHALL contain exactly one [1..1] code, which SHALL be selected from ValueSet 2.16.840.1.114222.4.11.3208 Lab Test Result Name (Tularemia) DYNAMIC (CONF:1877)
- 7. SHALL contain exactly one [1..1] statusCode/@code="completed" (CodeSystem: 2.16.840.1.113883.5.14 ActStatus) (CONF-396, CONF:2000)
- 8. SHALL contain exactly one [1..1] effectiveTime (CONF:2001)
- 9. SHOULD contain at least one [1..\*] specimen (CONF-399), such that
  - Should be included if the specimen isn't inherent in code value.
- 10. MAY contain zero or one [0..1] component (CONF:2009, CONF:2010), such that
  - **a.** Contains exactly one [1..1] *Specimen Collection Procedure* (templateId: 2.16.840.1.113883.10.20.15.3.2)
- 11. SHALL contain at least one [1..\*] component (CONF:1825, CONF:1826), such that
  - **a.** Contains exactly one [1..1] *Tularemia Result Observation* (templateId: 2.16.840.1.113883.10.20.15.3.51)

- **12.** The value for 'code' in a result organizer **SHOULD** be selected from LOINC (codeSystem 2.16.840.1.113883.6.1) or SNOMED CT (codeSystem 2.16.840.1.113883.6.96), and **MAY** be selected from CPT-4 (codeSystem 2.16.840.1.113883.6.12) or ValueSet 2.16.840.1.113883.1.11.20.16 ResultTypeCode STATIC. (CONF-398)
  - [OCL]: self.code.codeSystem = '2.16.840.1.113883.6.1' xor self.code.codeSystem = '2.16.840.1.113883.6.96' xor self.code.codeSystem = '2.16.840.1.113883.6.12' xor self.code.codeSystem = '2.16.840.1.113883.1.11.20.16'
- 13. The specimen element SHALL NOT conflict with the specimen inherent in code (CONF-400)
  - UNIMPLEMENTABLE
- **14.** specimen / specimenRole / id **SHOULD** be set to equal a Procedure / specimen / specimenRole / id to indicate that the Results and the Procedure are referring to the same specimen. (CONF-401)
  - UNIMPLEMENTABLE
- **15. SHALL** satisfy: Contains one or more component (CONF-402)
  - [OCL]: not self.component->isEmpty()
- **16.** The target of one or more result organizer component relationships **MAY** be a procedure, to indicate the means or technique by which a result is obtained, particularly if the means or technique isn't inherent in code or if there is a need to further specialize the code value. (CONF-403)
  - UNIMPLEMENTABLE
- **17.** A result organizer component / procedure **MAY** be a reference to a procedure described in the Procedure section. (CONF-404)
  - UNIMPLEMENTABLE
- 18. SHALL satisfy: Contains one or more sources of information. (CONF-406)

```
• [OCL]: not self.informant->isEmpty()
or not self.getSection().informant->isEmpty()
or not self.getClinicalDocument().informant->isEmpty()
or self.reference->exists(ref : cda::Reference | ref.typeCode =
   vocab::x_ActRelationshipExternalReference::XCRPT)
```

Tularemia Result Organizer example

#### **Tularemia Signs And Symptoms Observation**

[Observation: templateId 2.16.840.1.113883.10.20.15.3.45]

- **1. SHALL** conform to *PHCR Signs And Symptoms Observation* template (templateId: 2.16.840.1.113883.10.20.15.3.53)
- **2. SHALL** contain exactly one [1..1] **@classCode**="OBS" *Observation* (CodeSystem: 2.16.840.1.113883.5.6 HL7ActClass) (CONF:1861)
- **3. SHALL** contain exactly one [1..1] **@moodCode**="EVN" *Event* (CodeSystem: 2.16.840.1.113883.5.1001 HL7ActMood) (CONF:1862)
- **4. SHALL** contain exactly one [1..1] @negationInd (CONF:1863)
- 5. SHALL contain exactly one [1..1] code/@code="ASSERTION" (CodeSystem: 2.16.840.1.113883.5.4 HL7ActCode) (CONF:1864)
- 6. SHALL contain exactly one [1..1] statusCode/@code="completed" (CodeSystem: 2.16.840.1.113883.5.14 ActStatus) (CONF:1865)
- 7. **SHOULD** contain zero or one [0..1] **effectiveTime** (CONF:1866)
- 8. SHALL contain exactly one [1..1] value, which SHALL be selected from ValueSet 2.16.840.1.114222.4.11.3215 Signs and Symptoms (Tularemia) DYNAMIC, where its data type is CD (CONF:1686)
- **9.** PHCR Case Observation **SHOULD** contain zero or more [0..\*] entryRelationship (CONF:1887, CONF:1888, CONF:1890), such that Contains @typeCode="MFST" MFST (is manifestation of), such that Contains

@inversionInd="true", and Contains exactly one [1..1] Signs And Symptoms Observation (templateId: 2.16.840.1.113883.10.20.15.3.53) (CONF:1889)

**Tularemia Signs And Symptoms Observation example** 

#### Tularemia Therapeutic Regimen Act

[Act: templateId 2.16.840.1.113883.10.20.15.3.48]

- **1. SHALL** conform to *PHCR Therapeutic Regimen Act* template (templateId: 2.16.840.1.113883.10.20.15.3.57)
- 2. SHALL contain exactly one [1..1] @classCode="ACT" Act (CodeSystem: 2.16.840.1.113883.5.6 HL7ActClass) (CONF:1940)
- **3. SHALL** contain exactly one [1..1] **@moodCode**="EVN" *Event* (CodeSystem: 2.16.840.1.113883.5.1001 HL7ActMood) (CONF:1941)
- **4. SHALL** contain exactly one [1..1] **@negationInd** (CONF:1942)
- **5. SHALL** contain exactly one [1..1] **code/@code**="133877004" *Therapeutic regimen* (CodeSystem: 2.16.840.1.113883.6.96 SNOMEDCT) (CONF:1943)
- **6. SHALL** contain exactly one [1..1] **statusCode/@code**="completed" (CodeSystem: 2.16.840.1.113883.5.14 ActStatus) (CONF:1944)
- SHOULD contain zero or more [0..\*] entryRelationship (CONF:1753, CONF:1754, CONF:1755), such that
  - **a.** Contains @typeCode="COMP" COMP (has component)
  - **b.** Contains exactly one [1..1] *Tularemia Treatment Given Substance Administration* (templateId: 2.16.840.1.113883.10.20.15.3.47)
- 8. MAY contain zero or more [0..\*] entryRelationship (CONF:1778, CONF:1779, CONF:1790), such that
  - a. Contains @typeCode="COMP" COMP (has component)
  - **b.** Contains exactly one [1..1] *Tularemia Treatment Not Given Substance Administration* (templateId: 2.16.840.1.113883.10.20.15.3.50)
- 9. SHALL
- 10. SHALL contain [1..1] entryRelationship, which SHALL contain [1..1] @typeCode="REFR" Refers to (CodeSystem: 2.16.840.1.113883.5.1002 HL7ActRelationshipType) STATIC, SHALL contain [1..1] observation (CONF:1745)

Tularemia Therapeutic Regimen Act example

#### **Tularemia Treatment Given Substance Administration**

[SubstanceAdministration: templateId 2.16.840.1.113883.10.20.15.3.47]

- **1. SHALL** conform to *PHCR Treatment Given Substance Administration* template (templateId: 2.16.840.1.113883.10.20.15.3.55)
- 2. SHALL contain exactly one [1..1] @classCode="SBADM" (CodeSystem: 2.16.840.1.113883.5.6 HL7ActClass) (CONF:1919)
- **3. SHALL** contain exactly one [1..1] **@moodCode**="EVN" *Event* (CodeSystem: 2.16.840.1.113883.5.1001 HL7ActMood) (CONF:1920)
- **4. SHALL** contain exactly one [1..1] @negationInd (CONF:1921)
- **5. SHALL** contain exactly one [1..1] **statusCode** (CodeSystem: 2.16.840.1.113883.5.14 ActStatus) (CONF:1922)
- **6. SHOULD** contain zero or one [0..1] **effectiveTime** (CONF:1923)
- 7. SHOULD contain zero or one [0..1] routeCode (CodeSystem: 2.16.840.1.113883.3.88.12.3221.8.7 Medication Route FDA) (CONF:1925)

- **8.** Contains exactly one [1..1] **consumable**, where its type is *Consumable*
- **9. SHOULD** satisfy: Should contain [0..1] low (CONF:1924)
- **10. SHALL** satisfy: Shall contain consumable (CONF:1926)
- 11. SHALL contain exactly one [1..1] @negationInd="false" (CONF:1921)
  - [OCL]: self.negationInd=false
- **12. SHALL** contain [1..1] consumable, **SHALL** contain [1..1] manufacturedProduct, **SHALL** contain [1..1] manufacturedMaterial, which **SHALL** contain [1..1] code/@code, which **SHALL** be selected from ValueSet 2.16.840.1.114222.4.11.3217 Medication Treatment (Tularemia) (CONF:1736)

Tularemia Treatment Given Substance Administration example

#### Tularemia Treatment Not Given Substance Administration

[SubstanceAdministration: templateId 2.16.840.1.113883.10.20.15.3.50]

- **1. SHALL** conform to *PHCR Treatment Not Given Substance Administration* template (templateId: 2.16.840.1.113883.10.20.15.3.56)
- 2. SHALL contain exactly one [1..1] @classCode="SBADM" (CodeSystem: 2.16.840.1.113883.5.6 HL7ActClass) (CONF:1931)
- **3. SHALL** contain exactly one [1..1] **@moodCode**="EVN" *Event* (CodeSystem: 2.16.840.1.113883.5.1001 HL7ActMood) (CONF:1932)
- **4. SHALL** contain exactly one [1..1] **@negationInd** (CONF:1933)
- 5. SHALL contain exactly one [1..1] statusCode/@code="completed" (CodeSystem: 2.16.840.1.113883.5.14 ActStatus) (CONF:1934)
- **6.** Contains exactly one [1..1] **consumable**, where its type is *Consumable*
- 7. SHALL satisfy: Shall contain consumable (CONF:1935)
- **8. SHALL** contain exactly one [1..1] @negationInd="true" (CONF:1933)
  - [OCL]: self.negationInd=true
- 9. SHALL contain [1..1] consumable, SHALL contain [1..1] manufacturedProduct, SHALL contain [1..1] manufacturedMaterial, which SHALL contain [1..1] code/@code, which SHALL be selected from ValueSet 2.16.840.1.114222.4.11.3217 Medication Treatment (Tularemia) (CONF:1770)

Tularemia Treatment Not Given Substance Administration example

5

# **OTHER CLASSES**

This section of the Implementation Guide describes other classes that are not CDA Clinical Documents, Sections, or Clinical Statements.



## **VALUE SETS**

#### Topics:

- Animal
- Disease Type (Tularemia)
- Lab Test Result Name (Tularemia)
- Material Exposure Type
- Medication Treatment (Tularemia)
- Signs and Symptoms (Tularemia)

The following tables summarize the value sets used in this Implementation Guide.

#### **Animal**

Value Set	Animal - 2.16.840.1.114222.4.11.1074
Source	PHIN VADS
Source URL	https://phinvads.cdc.gov/vads/ViewValueSet.action?oid=2.16.840.1.114222.4.11.1074
Definition	Animal Keyword: Animal Type based on SNOMED domain (387961004)

## **Disease Type (Tularemia)**

Value Set	Disease Type (Tularemia) - 2.16.840.1.114222.4.11.3223
Source	PHIN VADS
Source URI	https://phinvads.cdc.gov/vads/ViewValueSet.action?oid=2.16.840.1.114222.4.11.3223
Definition	Tularemia disease type value set has problems or disease related to Tularemia. This value set is based upon SNOMED CT.

Concept Code	Concept Name	Code System	Description
186293006	Cryptogenic tularemia	SNOMEDCT	
398599000	Enteric tularemia	SNOMEDCT	
34023009	Generalized tularemia	SNOMEDCT	
21857006	Glandular tularemia	SNOMEDCT	
73363000	Oculoglandular tularemia	SNOMEDCT	
398575000	Oropharyngeal tularemia	SNOMEDCT	
45556008	Pulmonary tularemia	SNOMEDCT	
19265001	Tularemia	SNOMEDCT	
398554008	Typhoidal tularemia	SNOMEDCT	
37722001	Ulceroglandular tularemia	SNOMEDCT	

## **Lab Test Result Name (Tularemia)**

Value Set	Lab Test Result Name (Tularemia) - 2.16.840.1.114222.4.11.3208
Code System	LOINC - 2.16.840.1.113883.6.1
Source	PHIN VADS
Source URL	https://phinvads.cdc.gov/vads/ViewValueSet.action?oid=2.16.840.1.114222.4.11.3208
Definition	Tularemia lab test result name value set is based upon the Lab LOINC concepts that are defined in the CSTE standardized reporting definition for Tularemia.

## **Material Exposure Type**

Value Set	Material Exposure Type - 2.16.840.1.114222.4.11.3211
Source	PHIN VADS
Source URL	https://phinvads.cdc.gov/vads/ViewValueSet.action?oid=2.16.840.1.114222.4.11.3211
Definition	Types of exposure related to material such as suspicious mail and powder including animal material. This value set is primarily based upon SNOMED CT Material (260769002) hierarchy.

## **Medication Treatment (Tularemia)**

Value Set	Medication Treatment (Tularemia) - 2.16.840.1.114222.4.11.3217
Source	PHIN VADS
Source URL	https://phinvads.cdc.gov/vads/ViewValueSet.action?oid=2.16.840.1.114222.4.11.3217
Definition	Tularemia treatment value set has medication concepts used to treat tularemia.

# Signs and Symptoms (Tularemia)

Value Set	Signs and Symptoms (Tularemia) - 2.16.840.1.114222.4.11.3215
Source	PHIN VADS
Source URL	https://phinvads.cdc.gov/vads/ViewValueSet.action?oid=2.16.840.1.114222.4.11.3215
Definition	Tularemia Signs and Symptoms value set is primarily based upon the SNOMED concepts that are defined in the CSTE standardized reporting definition for Anthrax

Concept Code	Concept Name	Code System	Description
21522001	Abdominal pain	SNOMEDCT	
84387000	Asymptomatic	SNOMEDCT	
29857009	Chest pain	SNOMEDCT	
43724002	Chill	SNOMEDCT	
9826008	Conjunctivitis	SNOMEDCT	
49727002	Cough	SNOMEDCT	
62315008	Diarrhea	SNOMEDCT	
267036007	Dyspnea	SNOMEDCT	
386661006	Fever		
25064002	Headache	SNOMEDCT	
57676002	Joint pain	SNOMEDCT	
30746006	Lymphadenopathy	SNOMEDCT	
367391008	Malaise	SNOMEDCT	

Concept Code	Concept Name	Code System	Description
7180009	Meningitis	SNOMEDCT	
68962001	Muscle pain	SNOMEDCT	
422587007	Nausea	SNOMEDCT	
162397003	Pain in throat	SNOMEDCT	
405737000	Pharyngitis	SNOMEDCT	
233604007	Pneumonia	SNOMEDCT	
46742003	Skin ulcer	SNOMEDCT	
270031000	Sputum: contains blood	SNOMEDCT	
91302008	Systemic infection	SNOMEDCT	
422400008	Vomiting	SNOMEDCT	
89362005	Weight loss finding	SNOMEDCT	

#### REFERENCES

- HL7 Implementation Guide: CDA Release 2 Continuity of Care Document (CCD) A CDA implementation of ASTM E2369-05 Standard Specification for Continuity of Care Record<sup>©</sup> (CCR) April 01, 2007 available through HL7.
- HL7 Implementation Guide for CDA Release 2 Quality Reporting Document Architecture (QRDA) Draft Standard for Trial Use March 2009. Available at: *Quality Reporting Document Architecture (QRDA)*
- HL7 Implementation Guide for CDA Release 2 CDA for Public Health Case Reports (PHCR) Informative Standard October 2009. Available through *HL7*.
- HL7 Implementation Guide for CDA Release 2: NHSN Healthcare Associated Infection (HAI) Reports, Release 2 Draft Standard for Trial Use January 2009 Available at: NHSN Healthcare Associated Infection (HAI) Reports
- Dolin RH, Alschuler L, Boyer S, Beebe C, Behlen FM, Biron PV, Shabo A, (Editors). HL7 Clinical Document Architecture, Release 2.0. ANSI-approved HL7 Standard; May 2005. Ann Arbor, Mich.: Health Level Seven, Inc. Available through *HL7* or if an HL7 member with the following link: *CDA Release 2 Normative Web Edition*.
- LOINC®: Logical Observation Identifiers Names and Codes, Regenstrief Institute.
- SNOMED CT®: SNOMED Clinical Terms SNOMED International Organization.
- Extensible Markup Language, www.w3.org/XML.
- Dolin RH, Alschuler L, Boyer S, Beebe C, Behlen FM, Biron PV, Shabo A., HL7 Clinical Document Architecture, Release 2. J Am Med Inform Assoc. 2006;13:30-39. Available at: <a href="http://www.jamia.org/cgi/reprint/13/1/30">http://www.jamia.org/cgi/reprint/13/1/30</a>.
- Using SNOMED CT in HL7 Version 3; Implementation Guide, Release 1.5. Available through *HL7* or if an HL7 member with the following link: *Using SNOMED CT in HL7 Version 3*