# Design Assignment 2B

Student Name: Itzel Becerril
Student #:2000478001
Student Email: becerri2@unlv.nevada.edu
Primary Github address: hadidbuilds
Directory: DA2B

1.   COMPONENTS LIST AND CONNECTION BLOCK DIAGRAM w/ PINS

List of Components used:
- Atmel Studio 7
- Atmega328P
- Xplained mini
- microUsb Cord
- Multifunctional shield
- Switch and LED on board

Block diagram with pins used in the Atmega328P

2.CODE IN ASSEMBLY

```
.ORG 0  ;location for reset
JMP MAIN

.ORG 0x02 ;location for external interrupt 0
JMP EX0_ISR

MAIN:
;initialize stack
LDI R20,HIGH(RAMEND)
OUT SPH,R20
LDI R20,LOW(RAMEND)
OUT SPL,R20
;initialize stack

LDI R16, 0xFF  ;load register to set all leds
OUT DDRB, R16  ;enable output
```

```asm
OUT PORTB, R16 ;set low
LDI R16, 0x04  ;load in register and will be used later for xor
LDI R21, 56    ;used for xor later
LDI R19, 0xFF  ;used later to set pins to low

LDI R20, 0X2   ;make INT0 falling edge triggered
STS EICRA, R20 ;pull-up activated
SBI DDRB, 2 ;port.2 = output
SBI PORTD, 2 ; pull-up activated
LDI R20, (1<<INT0) ;enable INT0
OUT EIMSK, R20
SEI ;enable interrupts

HERE:
OUT PORTB, R19 ;setting to low
JMP HERE

EX0_ISR:
        EOR R21, R16     ;toggling LEDs
        OUT PORTB, R21        ;ouputs LED

;;;;;Delay subroutine;;;;;;;;;;;;;;;
        LDI R23, 70
D3:
        LDI R24, 229
D4:
        LDI R22, 249
D5:
        NOP
        NOP
        DEC R22
        BRNE D5
        DEC R24
        BRNE D4
        DEC R23
        BRNE D3
        RETI
;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;
```

3.CODE IN C

```c
#define F_CPU 16000000UL
#include <avr/io.h>
#include <avr/interrupt.h>
#include <util/delay.h>

int main()
{
        DDRB |= (1<<5);        //PB5 as an output
        PORTB |= (1<<5);  //turn off LED5
        DDRB |= (1<<2);   //PB2 as an output
        PORTB |= (1<<2);  //turn off LED2

        PORTD |= (1<<2);  //pull-up activated

        EIMSK = (1<<INT0); //enable external interrupt 0
        sei(); //enable interrupt
```

```
        while(1); //wait here
}
//ISR for external interrupt 0
ISR(INT0_vect)
{
        PORTB ^= (1<<2); //toggle PORT.2
        _delay_ms(1250); //delay of 1.25 seconds
        PORTB ^= (1<<2); //toggle PORT.2
}
```

4.SCHEMATIC

5.SCREENSHOTS OF EACH TASK OUTPUT (ATMEL STUDIO OUTPUT)

Delay recording for Assembly: Delay recordings for C:

6.SCREENSHOT OF EACH DEMO (BOARD SETUP)
Both will be setup as below:
Before   **After**

4.   VIDEO LINKS OF EACH DEMO
C code
https://www.youtube.com/watch?v=46IXtT1coqI

Assembly Code
https://www.youtube.com/watch?v=KAQsZGh4fos

5.   GITHUB LINK OF THIS DA

https://github.com/HadidBuilds/hw_sub_da1

Student Academic Misconduct Policy
http://studentconduct.unlv.edu/misconduct/policy.html

"*This assignment submission is my own, original work*".
Itzel Becerril