

Comprehension Check due May 18, 2021 14:59 +03

Use the following libraries for these questions:

```
library(tidyverse)
library(dslabs)
```

Question 9

1/1 point (graded)

Examine the built-in dataset `co2`. This dataset comes with base R, not **dslabs** - just type `co2` to access the dataset.

Is `co2` tidy? Why or why not?

☐ `co2` is tidy data: it has one year for each row.

☐ `co2` is tidy data: each column is a different month.

☐ `co2` is not tidy: there are multiple observations per column.

☒ `co2` is not tidy: to be tidy we would have to wrangle it to have three columns (year, month and value), and then each `co2` observation would have a row.



Explanation

These data are not tidy because month is a variable and should be stored as a column instead of across multiple columns in the header. There are also multiple observations per row, and each observation should be a different row.

Submit

You have used 1 of 2 attempts

i Answers are displayed within the problem

Question 10

1/1 point (graded)

Run the following command to define the `co2_wide` object:

```
co2_wide <- data.frame(matrix(co2, ncol = 12, byrow = TRUE)) %>%  
  setNames(1:12) %>%  
  mutate(year = as.character(1959:1997))
```

Use the `gather()` function to make this dataset tidy. Call the column with the CO2 measurements `co2` and call the month column `month`. Name the resulting object `co2_tidy`.

Which code would return the correct tidy format?

☐ `co2_tidy <- gather(co2_wide, month, co2, year)`

☐ `co2_tidy <- gather(co2_wide, co2, month, -year)`

☐ `co2_tidy <- gather(co2_wide, co2, month, year)`

☒ `co2_tidy <- gather(co2_wide, month, co2, -year)`



Explanation

`gather` takes 4 arguments: (1) the data, (2) the name of the key column, (3) the name of the value column, and optionally (4) the names of any columns not to gather. We want to collect the months as the key and CO2 as the value while keeping the year column as-is.

Submit

You have used 1 of 2
attempts

i Answers are displayed within the problem

Question 11

1/1 point (graded)

Use `co2_tidy` to plot CO2 versus month with a different curve for each year:

```
co2_tidy %>% ggplot(aes(as.numeric(month), co2, color = year)) + geom_line
```

What can be concluded from this plot?

- ☐ CO2 concentrations increased monotonically (never decreased) from 1959 to 1997.
- ☒ CO2 concentrations are highest around May and the yearly average increased from 1959 to 1997.
- ☐ CO2 concentrations are highest around October and the yearly average increased from 1959 to 1997.
- ☐ Yearly average CO2 concentrations have remained constant over time.
- ☐ CO2 concentrations do not have a seasonal trend.



Explanation

In every year, the highest CO2 level is around May. The line legend shows that earlier years had lower CO2 levels and that CO2 levels generally increase relative to the previous year. The most recent years have the highest CO2.

Submit

You have used 1 of 2 attempts

i Answers are displayed within the problem

Question 12

1/1 point (graded)

Load the `admissions` dataset from **dslabs**, which contains college admission information for men and women across six majors, and remove the `applicants` percentage column:

```
library(dslabs)
data(admissions)
dat <- admissions %>% select(-applicants)
```

Your goal is to get the data in the shape that has one row for each major, like this:

major	men	women
A	62	82
B	63	68
C	37	34
D	33	35
E	28	24
F	6	7

Which command could help you to wrangle the data into the desired format?

☐ `dat_tidy <- spread(dat, major, admitted)`

☐ `dat_tidy <- spread(dat, gender, major)`

☒ `dat_tidy <- spread(dat, gender, admitted)`

☐ `dat_tidy <- spread(dat, admitted, gender)`



Explanation

`spread` takes 3 arguments: (1) the data frame, (2) the key to spread across columns, and (3) the value to put in individual cells of the table.

Submit

You have used 1 of 2 attempts

i Answers are displayed within the problem

Question 13

1/1 point (graded)

Now use the `admissions` dataset to create the object `tmp`, which has columns `major`, `gender`, `key` and `value`:

```
tmp <- gather(admissions, key, value, admitted:applicants)
tmp
```

Combine the key and gender and create a new column called `column_name` to get a variable with the following values: `admitted_men`, `admitted_women`, `applicants_men` and `applicants_women`. Save the new data as `tmp2`.

Which command could help you to wrangle the data into the desired format?

☐

```
tmp2 <- spread(tmp, column_name, key, gender)
```

☐

```
tmp2 <- gather(tmp, column_name, c(gender, key))
```

☐

```
tmp2 <- unite(tmp, column_name, c(gender, key))
```

☐

```
tmp2 <- spread(tmp, column_name, c(key, gender))
```



```
tmp2 <- unite(tmp, column_name, c(key, gender))
```



Explanation

`unite` takes 3 arguments: (1) the data frame, (2) the name of the new column to create, and (3) a vector of the columns to unite with an underscore, in order.

Submit

You have used 1 of 2 attempts

i Answers are displayed within the problem

Question 14

1/1 point (graded)

Which function can reshape `tmp2` to a table with six rows and five columns named `major`, `admitted_men`, `admitted_women`, `applicants_men` and `applicants_women`?



`gather()`



`spread()`



`separate()`



`unite()`



Explanation

```
spread(tmp2, column_name, value)
```

Submit

You have used 1 of 2
attempts

i Answers are displayed within the problem